

Pos. Tag - ID	Description	Quantity	Unit	Price (EUR)
				Total
10	<p>7ML5883-0AE01-0AB0-Z A00+B00+C01+E01+L05+M03</p> <p>SITRANS LG270 Guided radar level transmitter: continuous, contact, 60 m (197 ft) range. Monitors level and interface in liquids in extreme environments.</p> <p>0A Approval: General Purpose (CSA, FM, CE)</p> <p>E Version / Material: Exchangeable rod diameter 16 mm (0.63 inch)/ 316L</p> <p>01 Process fitting/Material: Thread 1 1/2" NPT (ASME B1.20.1) PN400/316L</p> <p>0 Electronics: Two-wire 4...20mA/HART</p> <p>A Seal/Process temperature: Ceramic-graphite/ with / -196 ... +280 °C</p> <p>B Housing/Protection/Cable: Plastic IP66/IP67 1/2" NPT/blind stopper</p> <p>0 Lengths: Rod diameter 16 mm/316L: 300 mm (11.81 inch)</p> <p>A00 Supplementary electronics: without</p> <p>B00 Dimensions centering weight (diameter/height): without</p> <p>C01 Rod mounted: mounted</p> <p>E01 Indicating/adjustment module: mounted</p> <p>L05 Language of Display: Spanish</p> <p>M03 Operating instructions: Spanish</p> <p>Netweight: 6.000 KG Delivery time (working days): 20 plus transportation time Price group: 8L4 LKZ: DE AL: N ECCN: EAR99I Commodity code: 90261029</p>	1 PC		on demand
Total Price				on demand