

NUTANIX X-RAY

Table of Contents

1. About X-Ray
2. Target Overview
3. Scenario Overview
4. Extended Node Failure (25 VDI VMs)

Report Information

Generated On	Wednesday, April 11, 2018 at 9:28 PM UTC
Report Version	Version 2.3.0 (89b0897b)

About X-Ray

X-Ray is an automated testing application for virtualized infrastructure solutions. It is capable of running test scenarios end-to-end to evaluate system attributes in real-world use cases. The test scenarios in X-Ray provide information about the following system attributes:

Data Availability and Performance During Failure or Maintenance

X-Ray performs modeled failure scenarios to test data availability during a failure. Systems should be able to handle failures without losing data and with minimal impact to performance.

Performance Consistency with Mixed Workloads

X-Ray tests the system's ability to handle mixed workloads, demonstrating the degree to which workloads may interfere with one another. Systems should be able to perform well with mixed workloads.

Feature Set Implications

X-Ray tests use standard APIs throughout tests to clone and manage VMs, take snapshots, and perform other system manipulations. Systems should perform efficiently while using features intended for virtualized infrastructure.

This report includes the results of completed test scenarios that demonstrate the system's capabilities and responses to scenario events. Consider the following when reviewing the results:

- In scenarios that present *IOPS*, consider the variability over the test. Also consider how scenario events may affect the system's ability to perform the requested workload.
- In scenarios that present *errors* and *VM availability*, consider the impact that any observed errors or loss of availability may have on an application.

Target Overview

TARGET NAME	CLUSTER TYPE		HYPERVISOR		MANAGER		NODE COUNT
POC14	Nutanix	5.5.0.6	AHV	20170830.58	Prism	5.5.0.6	4

Scenario Overview

FINISH DATE	TIME	DURATION	NAME	TARGET NAME	RESULT
2018-04-11	04:39:38 AM UTC	5h 37m 1s	Extended Node Failure (25 VDI VMs)	POC14	Passed

Extended Node Failure (25 VDI VMs)

TARGET NAME	RESULT
POC14	Passed

Scenario Description

Test Objectives

NOTE: THIS TEST HAS BEEN MODIFIED TO REDUCE THE TOTAL NUMBER OF VDI VMs WHILE WRITING A COMPARABLE AMOUNT OF DATA TO THE CLUSTER.

This test is designed to demonstrate what happens to the performance of VMs in the cluster when a node is failed without warning, similar to a single-node power failure.

Setup

1. Deploy the OLTP DB and VDI VM templates.
2. Clone 25 VDI VMs per host in cluster.
3. Clone one OLTP DB VM per host in the cluster.
4. Power on the VMs.
5. Pre-fill the OLTP DB and every VDI VM.
6. Warm up the OLTP DB VMs.

Measurement

1. Start the OLTP workload on every OLTP DB VM.
2. Wait for 20 minutes.
3. Fail the first node in the cluster by powering off through the out-of-band management.
4. Wait for 2.5 hours in the failed state for observation.

Test Requirements

- vCPUs: 54 vCPUs on every node
- RAM: 29 GB on every node
- Cluster Storage: 366GB per node
- IP Addresses: 26 per node

Note: This test scales with the number of nodes.

This test performs hardware power operations on the target's nodes, which may result in unavailability or permanent damage to non-Nutanix targets.

