



# **Advanced deployment**

## **Set up and administration**

NetApp

November 10, 2022

This PDF was generated from <https://docs.netapp.com/us-en/cloud-manager-setup-admin/task-launching-aws-mktp.html> on November 10, 2022. Always check docs.netapp.com for the latest.

# Table of Contents

- Advanced deployment ..... 1
  - Create a Connector from the AWS Marketplace ..... 1
  - Create a Connector from the Azure Marketplace ..... 8
  - Install the Connector on an existing Linux host that has internet access ..... 11
  - Install the Connector on-prem without internet access ..... 15

# Advanced deployment

## Create a Connector from the AWS Marketplace

For an AWS commercial region, it's best to create a Connector directly from BlueXP, but you can launch a Connector from the AWS Marketplace, if you prefer. For AWS Government regions, you can't deploy the Connector in a Government region from the BlueXP SaaS website, so the next best option is to do so from the AWS Marketplace.



You can also download and install the Connector software on an existing Linux host in your network or in the cloud. [Learn how to install the Connector on an existing Linux host.](#)

### Create the Connector in an AWS commercial region

You can launch the Connector instance in an AWS commercial region directly from the AWS Marketplace offering for BlueXP.

#### Before you get started

The IAM user who creates the Connector must have AWS Marketplace permissions to subscribe and unsubscribe.

#### Steps

1. Set up permissions in AWS:
  - a. From the IAM console, create your own policy by copying and pasting the contents of [the IAM policy for the Connector](#).
  - b. Create an IAM role with the role type Amazon EC2 and attach the policy that you created in the previous step to the role.
2. Go to the [BlueXP page on the AWS Marketplace](#) to deploy the Connector from an AMI:
3. On the Marketplace page, click **Continue to Subscribe** and then click **Continue to Configuration**.

**a**

Cloud Manager - Manual Installation without access keys

By: [NetApp, Inc.](#) Latest Version: 3.8.4

Read below for instructions on how to deploy Cloud Volumes ONTAP.

Linux/Unix ★★★★★ 6 AWS reviews

Typical Total Price  
**\$0.226/hr**  
Total pricing per instance for services hosted on t3.xlarge in US East (N. Virginia). [View Details](#)

Continue to Subscribe

Save to List

Overview Pricing Usage Support Reviews

### Product Overview

Do NOT subscribe on this page unless instructed by NetApp or redirected here from the NetApp website.

This listing lets you manually launch a Cloud Manager instance without providing your AWS credentials. After launching the Cloud Manager software in AWS, you can access it by entering the instance's IP address in a web browser. If you subscribe here, you still need to subscribe on the listing below for PAYGO charges.

### Highlights

- See Product Overview for instructions on how to deploy NetApp Cloud Manager.

**b**

Cloud Manager - Manual Installation without access keys

Continue to Configuration

< Product Detail [Subscribe](#)

## Subscribe to this software

You're subscribed to this software. Please see the terms and pricing details below or click the button above to configure your software.

### Terms and Conditions

#### NetApp, Inc. Offer

You have subscribed to this software and agreed that your use of this software is subject to the pricing terms and the seller's [End User License Agreement \(EULA\)](#). You agreed that AWS may share information about this transaction (including your payment terms) with the respective seller, reseller or underlying provider, as applicable, in accordance with the [AWS Privacy Notice](#). Your use of AWS services remains subject to the [AWS Customer Agreement](#) or other agreement with AWS governing your use of such services.

4. Change any of the default options and click **Continue to Launch**.
5. Under **Choose Action**, select **Launch through EC2** and then click **Launch**.

These steps describe how to launch the instance from the EC2 Console because the console enables you to attach an IAM role to the Connector instance. This isn't possible using the **Launch from Website** action.

6. Follow the prompts to configure and deploy the instance:
  - **Name and tags**: Enter a name and tags for the instance.
  - **Application and OS Image**: Skip this section. The Connector AMI is already selected.
  - **Instance type**: Depending on region availability, choose one of the supported instance types (t3.xlarge is recommended).

[Review the instance requirements.](#)

- **Key pair (login):** Select the key pair that you want to use to securely connect to the instance.
- **Network settings:** Edit the network settings as needed:
  - Choose the desired VPC and subnet.
  - Specify whether the instance should have a public IP address.
  - Specify firewall settings that enable the required connection methods for the Connector instance: SSH, HTTP, and HTTPS.
- **Configure storage:** Keep the default storage options.
- **Advanced details:** Under **IAM instance profile**, choose the IAM role that you created in step 1.
- **Summary:** Review the summary and click **Launch instance**.

AWS launches the software with the specified settings. The Connector instance and software should be running in approximately five minutes.

7. Open a web browser from a host that has a connection to the Connector instance and enter the following URL:

`https://ipaddress`

8. After you log in, set up the Connector:
  - a. Specify the NetApp account to associate with the Connector.

[Learn about NetApp accounts.](#)

- b. Enter a name for the system.



9. Open a web browser and go to <https://cloudmanager.netapp.com> to start using the Connector with BlueXP.

### Result

The Connector is now installed and set up with your NetApp account. BlueXP will automatically use this Connector when you create new working environments. But if you have more than one Connector, you'll need to [switch between them](#).

If you have Amazon S3 buckets in the same AWS account where you created the Connector, you'll see an Amazon S3 working environment appear on the Canvas automatically. [Learn more about what you can do with this working environment](#).

## Create the Connector in an AWS Government region

To deploy the Connector in an AWS Government region, you need to go to the EC2 service and select the BlueXP offering from the AWS Marketplace.

### Steps

1. Set up permissions in AWS:
  - a. From the IAM console, create your own policy by copying and pasting the contents of [the IAM policy for the Connector](#).
  - b. Create an IAM role with the role type Amazon EC2 and attach the policy that you created in the previous step to the role.
2. Go to the BlueXP offering in the AWS Marketplace.

The IAM user must have AWS Marketplace permissions to subscribe and unsubscribe.

- a. Open the EC2 service and select **Launch instance**.
- b. Select **AWS Marketplace**.
- c. Search for BlueXP and select the offering.



- d. Click **Continue**.
3. Follow the prompts to configure and deploy the instance:
- **Choose an Instance Type:** Depending on region availability, choose one of the supported instance types (t3.xlarge is recommended).
- [Review the instance requirements.](#)
- **Configure Instance Details:** Select a VPC and subnet, choose the IAM role that you created in step 1, enable termination protection (recommended), and choose any other configuration options that meet your requirements.

Number of instances	<input type="text" value="1"/>	<a href="#">Launch into Auto Scaling Group</a>
Purchasing option	<input type="checkbox"/> Request Spot instances	
Network	vpc-a76d91c2   VPC4QA (default)	<a href="#">Create new VPC</a>
Subnet	subnet-39536c13   QASubnet1   us-east-1b 155 IP Addresses available	<a href="#">Create new subnet</a>
Auto-assign Public IP	Enable	
Placement group	<input type="checkbox"/> Add instance to placement group	
Capacity Reservation	Open	<a href="#">Create new Capacity Reservation</a>
IAM role	Cloud_Manager	<a href="#">Create new IAM role</a>
CPU options	<input type="checkbox"/> Specify CPU options	
Shutdown behavior	Stop	
Enable termination protection	<input checked="" type="checkbox"/> Protect against accidental termination	
Monitoring	<input type="checkbox"/> Enable CloudWatch detailed monitoring <a href="#">Additional charges apply.</a>	

- **Add Storage:** Keep the default storage options.
- **Add Tags:** Enter tags for the instance, if desired.
- **Configure Security Group:** Specify the required connection methods for the Connector instance: SSH, HTTP, and HTTPS.
- **Review:** Review your selections and click **Launch**.

AWS launches the software with the specified settings. The Connector instance and software should be running in approximately five minutes.

4. Open a web browser from a host that has a connection to the Connector instance and enter the following URL:

`https://ipaddress`

5. After you log in, set up the Connector:
  - a. Specify the NetApp account to associate with the Connector.  
[Learn about NetApp accounts.](#)
  - b. Enter a name for the system.





## Result

The Connector is now installed and set up with your NetApp account.

Any time that you want to use BlueXP, open your web browser and connect to the IP address of the Connector instance: <https://ipaddress>

Since the Connector was deployed in a Government region, it's not accessible from <https://cloudmanager.netapp.com>.

## Open port 3128 for AutoSupport messages

If you plan to deploy Cloud Volumes ONTAP systems in a subnet where an outbound internet connection won't be available, then BlueXP automatically configures Cloud Volumes ONTAP to use the Connector as a proxy server.

The only requirement is to ensure that the Connector's security group allows *inbound* connections over port 3128. You'll need to open this port after you deploy the Connector.

If you use the default security group for Cloud Volumes ONTAP, then no changes are needed to its security group. But if you plan to define strict outbound rules for Cloud Volumes ONTAP, then you'll also need to ensure that the Cloud Volumes ONTAP security group allows *outbound* connections over port 3128.

# Create a Connector from the Azure Marketplace

For an Azure commercial region, it's best to create a Connector directly from BlueXP, but you can launch a Connector from the Azure Marketplace, if you prefer. For Azure Government regions, you can't deploy the Connector in a Government region from the BlueXP SaaS website, so the next best option is to do so from the Azure Marketplace.



You can also download and install the Connector software on an existing Linux host in your network or in the cloud. [Learn how to install the Connector on an existing Linux host.](#)

## Creating a Connector in Azure

Deploy the Connector in Azure using the image in the Azure Marketplace and then log in to the Connector to specify your NetApp account.

### Steps

1. Go to the NetApp Connector VM page in the Azure Marketplace.
  - [Azure Marketplace page for commercial regions](#)
  - [Azure Marketplace page for Azure Government regions](#)
2. Click **Get it now** and then click **Continue**.
3. From the Azure portal, click **Create** and follow the steps to configure the virtual machine.

Note the following as you configure the VM:

- The Connector can perform optimally with either HDD or SSD disks.
- Choose a VM size that meets CPU and RAM requirements. We recommend DS3 v2.

[Review the VM requirements.](#)

- For the network security group, the Connector requires inbound connections using SSH, HTTP, and HTTPS.

[Learn more about security group rules for the Connector.](#)

- Under **Management**, enable **System assigned managed identity** for the Connector by selecting **On**.

This setting is important because a managed identity allows the Connector virtual machine to identify itself to Azure Active Directory without providing any credentials. [Learn more about managed identities for Azure resources.](#)

4. On the **Review + create** page, review your selections and click **Create** to start the deployment.

Azure deploys the virtual machine with the specified settings. The virtual machine and Connector software should be running in approximately five minutes.

5. Open a web browser from a host that has a connection to the Connector virtual machine and enter the following URL:

`https://ipaddress`

6. After you log in, set up the Connector:
  - a. Specify the NetApp account to associate with the Connector.  
[Learn about NetApp accounts.](#)
  - b. Enter a name for the system.



## Result

The Connector is now installed and set up with your NetApp account.

If the Connector is in an Azure commercial region, open a web browser and go to <https://cloudmanager.netapp.com> to start using the Connector with BlueXP.

If the Connector is in an Azure Government region, you can use BlueXP by opening your web browser and connecting to the IP address of the Connector instance: `https://ipaddress`

Since the Connector was deployed in a Government region, it's not accessible from <https://cloudmanager.netapp.com>.

## Granting Azure permissions

When you deployed the Connector in Azure, you should have enabled a [system-assigned managed identity](#). You must now grant the required Azure permissions by creating a custom role and then by assigning the role to the Connector virtual machine for one or more subscriptions.

## Steps

1. Create a custom role:
  - a. Copy the contents of the [custom role permissions for the Connector](#) and save them in a JSON file.
  - b. Modify the JSON file by adding Azure subscription IDs to the assignable scope.

You should add the ID for each Azure subscription from which users will create Cloud Volumes ONTAP systems.

## Example

```
"AssignableScopes": [  
  "/subscriptions/d333af45-0d07-4154-943d-c25fbzzzzzzz",  
  "/subscriptions/54b91999-b3e6-4599-908e-416e0zzzzzzz",  
  "/subscriptions/398e471c-3b42-4ae7-9b59-ce5bbzzzzzzz"
```

- c. Use the JSON file to create a custom role in Azure.

The following steps describe how to create the role by using Bash in Azure Cloud Shell.

- Start [Azure Cloud Shell](#) and choose the Bash environment.
- Upload the JSON file.



- Enter the following Azure CLI command:

```
az role definition create --role-definition  
Policy_for_Setup_As_Service_Azure.json
```

You should now have a custom role called BlueXP Operator that you can assign to the Connector virtual machine.

2. Assign the role to the Connector virtual machine for one or more subscriptions:

- a. Open the **Subscriptions** service and then select the subscription in which you want to deploy Cloud Volumes ONTAP systems.
- b. Click **Access control (IAM) > Add > Add role assignment**.
- c. In the **Role** tab, select the **BlueXP Operator** role and click **Next**.



BlueXP Operator is the default name provided in the BlueXP policy. If you chose a different name for the role, then select that name instead.

d. In the **Members** tab, complete the following steps:

- Assign access to a **Managed identity**.
- Click **Select members**, select the subscription in which the Connector virtual machine was created, choose **Virtual machine**, and then select the Connector virtual machine.
- Click **Select**.
- Click **Next**.

e. Click **Review + assign**.

- f. If you want to deploy Cloud Volumes ONTAP from additional subscriptions, switch to that subscription and then repeat these steps.

## Result

The Connector now has the permissions that it needs to manage resources and processes within your public cloud environment. BlueXP will automatically use this Connector when you create new working environments. But if you have more than one Connector, you'll need to [switch between them](#).

If you have Azure Blob storage in the same Azure account where you created the Connector, you'll see an Azure Blob working environment appear on the Canvas automatically. [Learn more about what you can do with this working environment](#).

## Open port 3128 for AutoSupport messages

If you plan to deploy Cloud Volumes ONTAP systems in a subnet where an outbound internet connection won't be available, then BlueXP automatically configures Cloud Volumes ONTAP to use the Connector as a proxy server.

The only requirement is to ensure that the Connector's security group allows *inbound* connections over port 3128. You'll need to open this port after you deploy the Connector.

If you use the default security group for Cloud Volumes ONTAP, then no changes are needed to its security group. But if you plan to define strict outbound rules for Cloud Volumes ONTAP, then you'll also need to ensure that the Cloud Volumes ONTAP security group allows *outbound* connections over port 3128.

## Install the Connector on an existing Linux host that has internet access

The most common way to create a Connector is directly from BlueXP or from a cloud provider's marketplace. But you have the option to download and install the Connector software on an existing Linux host in your network or in the cloud. These steps are

specific to hosts that have internet access.

[Learn about other ways to deploy a Connector.](#)



If you want to create a Cloud Volumes ONTAP system in Google Cloud, then you must have a Connector that's running in Google Cloud as well. You can't use a Connector that's running in AWS, Azure, or on-prem.

## Verify host requirements

The Connector software must run on a host that meets specific operating system requirements, RAM requirements, port requirements, and so on.

### A dedicated host is required

The Connector is not supported on a host that is shared with other applications. The host must be a dedicated host.

### CPU

4 cores or 4 vCPUs

### RAM

14 GB

### AWS EC2 instance type

An instance type that meets the CPU and RAM requirements above. We recommend t3.xlarge.

### Azure VM size

An instance type that meets the CPU and RAM requirements above. We recommend DS3 v2.

### GCP machine type

An instance type that meets the CPU and RAM requirements above. We recommend n2-standard-4.

The Connector is supported in Google Cloud on a VM instance with an OS that supports [Shielded VM features](#)

## Supported operating systems

- CentOS 7.6
- CentOS 7.7
- CentOS 7.8
- CentOS 7.9
- Red Hat Enterprise Linux 7.6
- Red Hat Enterprise Linux 7.7
- Red Hat Enterprise Linux 7.8
- Red Hat Enterprise Linux 7.9

The Red Hat Enterprise Linux system must be registered with Red Hat Subscription Management. If it is not registered, the system cannot access repositories to update required 3rd party software during Connector installation.

The Connector is supported on English-language versions of these operating systems.

## Hypervisor

A bare metal or hosted hypervisor that is certified to run CentOS or Red Hat Enterprise Linux  
[Red Hat Solution: Which hypervisors are certified to run Red Hat Enterprise Linux?](#)

## Disk space in /opt

100 GiB of space must be available

## Disk space in /var

20 GiB of space must be available

## Outbound internet access

The installer for the Connector must access the following URLs during the installation process:

- <https://dl.fedoraproject.org/pub/epel/epel-release-latest-7.noarch.rpm>
- <https://s3.amazonaws.com/aws-cli/awscli-bundle.zip>
- [https://\\*.blob.core.windows.net](https://*.blob.core.windows.net) or <https://hub.docker.com>

The host might try to update operating system packages during installation. The host can contact different mirroring sites for these OS packages.

## Install the Connector

After you verify that you have a supported Linux host, you can obtain the Connector software and then install it.

## Required privileges

Root privileges are required to install the Connector.

## About this task

- The installation installs the AWS command line tools (awscli) to enable recovery procedures from NetApp support.

If you receive a message that installing the awscli failed, you can safely ignore the message. The Connector can operate successfully without the tools.

- The installer that is available on the NetApp Support Site might be an earlier version. After installation, the Connector automatically updates itself if a new version is available.

## Steps

1. Download the Connector software from the [NetApp Support Site](#), and then copy it to the Linux host.

For help with connecting and copying the file to an EC2 instance in AWS, see [AWS Documentation: Connecting to Your Linux Instance Using SSH](#).

2. Assign permissions to run the script.

```
chmod +x OnCommandCloudManager-V3.9.19.sh
```

3. Run the installation script.

If you have a proxy server, you will need to enter the command parameters as shown below. The installer doesn't prompt you to provide information about a proxy.

```
./OnCommandCloudManager-V3.9.19.sh [silent] [proxy=ipaddress]  
[proxyport=port] [proxyuser=user_name] [proxypwd=password]
```

*silent* runs the installation without prompting you for information.

*proxy* is required if the host is behind a proxy server.

*proxyport* is the port for the proxy server.

*proxyuser* is the user name for the proxy server, if basic authentication is required.

*proxypwd* is the password for the user name that you specified.

4. Unless you specified the silent parameter, enter **Y** to continue with the installation.

The Connector is now installed. At the end of the installation, the Connector service (occm) restarts twice if you specified a proxy server.

5. Open a web browser and enter the following URL:

`https://ipaddress`

*ipaddress* can be localhost, a private IP address, or a public IP address, depending on the configuration of the host. For example, if the Connector is in the public cloud without a public IP address, you must enter a private IP address from a host that has a connection to the Connector host.

6. Sign up or log in.
7. If you installed the Connector in Google Cloud, set up a service account that has the permissions that BlueXP needs to create and manage Cloud Volumes ONTAP systems in projects.
  - a. [Create a role in GCP](#) that includes the permissions defined in the [Connector policy for GCP](#).
  - b. [Create a GCP service account and apply the custom role that you just created](#).
  - c. [Associate this service account with the Connector VM](#).
  - d. If you want to deploy Cloud Volumes ONTAP in other projects, [grant access by adding the service account with the BlueXP role to that project](#). You'll need to repeat this step for each project.
8. After you log in, set up BlueXP:
  - a. Specify the NetApp account to associate with the Connector.  
  
[Learn about NetApp accounts](#).
  - b. Enter a name for the system.





## Result

The Connector is now installed and set up with your NetApp account. BlueXP will automatically use this Connector when you create new working environments.

## After you finish

Set up permissions so BlueXP can manage resources and processes within your public cloud environment:

- AWS: [Set up an AWS account and then add it to BlueXP](#)
- Azure: [Set up an Azure account and then add it to BlueXP](#)
- Google Cloud: See step 7 above

## Install the Connector on-prem without internet access

You can install the Connector on an on-premises Linux host that doesn't have internet access. You can then discover on-prem ONTAP clusters, replicate data between them, back up volumes using Cloud Backup, and scan them with Cloud Data Sense.

These installation instructions are specifically for the use case described above. [Learn about other ways to deploy a Connector.](#)

## Verify host requirements

The Connector software must run on a host that meets specific operating system requirements, RAM requirements, port requirements, and so on.

### A dedicated host is required

The Connector is not supported on a host that is shared with other applications. The host must be a dedicated host.

### CPU

4 cores or 4 vCPUs

### RAM

14 GB

### Supported operating systems

- CentOS 7.6
- CentOS 7.7
- CentOS 7.8
- CentOS 7.9
- Red Hat Enterprise Linux 7.6
- Red Hat Enterprise Linux 7.7
- Red Hat Enterprise Linux 7.8
- Red Hat Enterprise Linux 7.9

The Red Hat Enterprise Linux system must be registered with Red Hat Subscription Management. If it is not registered, the system cannot access repositories to update required 3rd party software during Connector installation.

The Connector is supported on English-language versions of these operating systems.

### Hypervisor

A bare metal or hosted hypervisor that is certified to run CentOS or Red Hat Enterprise Linux  
[Red Hat Solution: Which hypervisors are certified to run Red Hat Enterprise Linux?](#)

### Disk type

An SSD is required

### Disk space in /opt

100 GiB of space must be available

### Disk space in /var

20 GiB of space must be available

### Docker Engine

Docker Engine version 19 or later is required on the host before you install the Connector. [View installation instructions.](#)

## Install the Connector

After you verify that you have a supported Linux host, you can obtain the Connector software and then install it.

### Required privileges

Root privileges are required to install the Connector.

### Steps

1. Verify that docker is enabled and running.

```
sudo systemctl enable docker && sudo systemctl start docker
```

2. Download the BlueXP software from the [NetApp Support Site](#).
3. Copy the installer to the Linux host.
4. Assign permissions to run the script.

```
chmod +x /path/cloud-manager-connector-offline-v3.9.19
```

5. Run the installation script:

```
sudo /path/cloud-manager-connector-offline-v3.9.19
```


6. Open a web browser and enter `https://ipaddress` where *ipaddress* is the IP address of the Linux host.

You should see the following screen.



7. Click **Set Up New BlueXP** and follow the prompts to set up the system.

- **System Details:** Enter a name for the Connector and your company name.



The screenshot shows a web interface for the 'System Details' step of a setup wizard. At the top, there are three tabs: '1 System Details' (active), '2 Create Admin User', and '3 Review'. The main heading is 'System Details'. Below it, a message reads: 'To help us provide better support, enter a name for Cloud Manager and your company name.' There are two input fields: 'Cloud Manager Name' and 'Company Name', both with empty text boxes.

- **Create Admin User:** Create the admin user for the system.

This user account runs locally on the system. There's no connection to the auth0 service available through BlueXP.

- **Review:** Review the details, accept the license agreement, and then click **Set Up**.

8. Log in to BlueXP using the admin user that you just created.

## Result

The Connector is now installed and you can start using the BlueXP features that are available in a dark site deployment.

## What's next?

- [Discover on-prem ONTAP clusters](#)
- [Replicate data between on-prem ONTAP clusters](#)
- [Back up on-prem ONTAP volume data to StorageGRID using Cloud Backup](#)
- [Scan on-prem ONTAP volume data using Cloud Data Sense](#)

When new versions of the Connector software are available, they'll be posted to the NetApp Support Site. [Learn how to upgrade the Connector.](#)

## Copyright information

Copyright © 2022 NetApp, Inc. All Rights Reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means—graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system—without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP “AS IS” AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

LIMITED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (b)(3) of the Rights in Technical Data -Noncommercial Items at DFARS 252.227-7013 (FEB 2014) and FAR 52.227-19 (DEC 2007).

Data contained herein pertains to a commercial product and/or commercial service (as defined in FAR 2.101) and is proprietary to NetApp, Inc. All NetApp technical data and computer software provided under this Agreement is commercial in nature and developed solely at private expense. The U.S. Government has a non-exclusive, non-transferrable, nonsublicensable, worldwide, limited irrevocable license to use the Data only in connection with and in support of the U.S. Government contract under which the Data was delivered. Except as provided herein, the Data may not be used, disclosed, reproduced, modified, performed, or displayed without the prior written approval of NetApp, Inc. United States Government license rights for the Department of Defense are limited to those rights identified in DFARS clause 252.227-7015(b) (FEB 2014).

## Trademark information

NETAPP, the NETAPP logo, and the marks listed at <http://www.netapp.com/TM> are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.