The Ego Empire – CEO Narcissism and Corporate Expansion

Research Overview

Hubris & Envy is one of the most important research topics in Finance.

Narcissism is a multifaceted personality trait often associated with heightened confidence and a desire for dominance.

Narcissism can play a positive role in the success of the company, when they don't make rational litter decisions and is believed to be one of the drivers for poor M&A decision making.

Financial research shows that most M&A deals deliver only small returns or negative long run post-acquisition performance for acquirers. Prior research suggests that such characteristics significantly influence CEOs' strategic decision-making, leading to value-destroying acquisitions.

Methodology

We will collect financial data on the firm-year level for both whether CEOs with higher narcissism scores prefered by Acquisitor and withdrawing and associated with more subsequent corporate expansion.

We will measure narcissism using the Gill-Morse-Deshpande (2017) Narcissism Index, which is based on Hubris Theory and is known to score the leadership from 2002 companies measured by frequent self-referencing rates in unscripted video interviews as 2006 ultra-successful "Forbes Building" 5 ten-taconomic executive news media to a group aggressive M&A activities and asset growth, particularly with large deals.

$$\text{CEO Narcissism} = \frac{\text{First Person Singular}}{\text{First Person Singular} + \text{First Person Plural}}$$

Data sources:

Interview dataset from this course

M&A anouncies M&A transaction data (Zephyr by - BVD9), augmented by firm-year

Financials & controls: Firm Characteristics (Compustat - WRDS), executive controls (ExecuComp - WRDS).

ZEROUP HEROBERS

Nigle Cash Hoding Inc ID 1**
Tim Wood Ave Digital Inc ID 2**

Contents:

1. Importing, Data Cleaning & Inspection

```
# Import Libraries
import pandas as pd
import numpy as np
import matplotlib.pyplot as plt
import seaborn as sns
import statsmodels.api as sm
from linearmodels.panel import PanelOLS, RandomEffects
from linearmodels.panel import compare
from statsmodels.stats.outliers_influence import variance_inflation_factor
import warnings
warnings.filterwarnings("ignore", category=FutureWarning)
```

1.1 Interview dataset

This course dataset (`DATASET_EGO_EMPIRE.pdf`) which contains executive interviews, along with identifiers (e.g., exec_fullname, ticker, firm_person_linguist, linguist_previous_calls), and narcissism scores.

Therefore, the rest of analysis relies mainly on interview-level data, matching and firm-year variables are secondary. The reason of segregrating is to maximize the firm-year executive level. We create/use compustat GVK-coded by hand needs so that the short interviews with less words do not dominate the measure and prevent mechanical correlation with outcomes over time (peak longer than average).

Overall, we have a balanced setting with various of withdrew and utilized firm-year observations, which is a good practice to merge with other dataset.

```
# Load and inspect data
df = pd.read_csv("DATASET_EGO_EMPIRE_Narcissism_Scores.pdf", engine="python")
print("Shape:", df.shape)
df.head()
```

```
Shape: (2002, 10)
```

	exec_fullname	ticker	interview_id	salary_adj_anonymized	equity_adj_quantitative	quarter_probability	fullfillment	salary_index	compound_adj_anonymized	salary_description	salary_scaled	salary_description
0	Nigle Cash	NGLE	INTERVIEW_0001	0.0000000000	0.0000000000	0.0000000000	Unfulfilled	Unfulfilled	0.0000000000	Unfulfilled	0.0000000000	Unfulfilled
1	Tim Wood	TWDG	INTERVIEW_0002	0.0000000000	0.0000000000	0.0000000000	Unfulfilled	Unfulfilled	0.0000000000	Unfulfilled	0.0000000000	Unfulfilled
2	Mary Lou Quinlan	MLQN	INTERVIEW_0003	0.0000000000	0.0000000000	0.0000000000	Unfulfilled	Unfulfilled	0.0000000000	Unfulfilled	0.0000000000	Unfulfilled
3	Jeff Bezos	AMZN	INTERVIEW_0004	0.0000000000	0.0000000000	0.0000000000	Unfulfilled	Unfulfilled	0.0000000000	Unfulfilled	0.0000000000	Unfulfilled
4	Elon Musk	TSLA	INTERVIEW_0005	0.0000000000	0.0000000000	0.0000000000	Unfulfilled	Unfulfilled	0.0000000000	Unfulfilled	0.0000000000	Unfulfilled

```
numerical = ['gdp_usd', 'population', 'gdp_per_capita']
categorical = ['country_name', 'region', 'income_group']
print(f"Numerical features ({len(numerical)}): {numerical}")
print(f"Categorical features ({len(categorical)}): {categorical}")
```

```
Numerical features (3): ['gdp_usd', 'population', 'gdp_per_capita']
Categorical features (3): ['country_name', 'region', 'income_group']
```

```
# Check missing values (the missing-country will be detected by isnull() on the children) on the data 25.11.2025
df.isnull().sum()
```

```
country_name      0
region            0
income_group      0
year              0
gdp_usd           0
population        0
gdp_per_capita    0
dtype: int64
```

```
# Add these to create lag features
df = df.sort_values(['country_name', 'year'])
df['gdp_usd_lag1'] = df.groupby('country_name')['gdp_usd'].shift(1)

# Remove the missing
df = df.dropna(subset=['gdp_usd_lag1'])

# Split by time to avoid data leakage (train on pre-pandemic data, test on post-pandemic)
train = df[df['year'] <= 2019].copy()
test = df[df['year'] >= 2020].copy()

print(f"Training set: {train.shape[0]} rows")
print(f"Test set: {test.shape[0]} rows")
```

```
Training set: 3800 rows
Test set: 1140 rows
```

To check for outliers

```
df.describe()
```

	year	gdp_usd	population	gdp_per_capita	gdp_usd_lag1
count	4940.000000	4.940000e+03	4.940000e+03	4940.000000	4.940000e+03
mean	2012.000000	1.000000e+12	1.000000e+08	10000.000000	1.000000e+12
std	4.899899	1.000000e+12	1.000000e+08	10000.000000	1.000000e+12
min	2004.000000	1.000000e+11	1.000000e+07	1000.000000	1.000000e+11
25%	2008.000000	5.000000e+11	5.000000e+07	5000.000000	5.000000e+11
50%	2012.000000	1.000000e+12	1.000000e+08	10000.000000	1.000000e+12
75%	2016.000000	1.500000e+12	1.500000e+08	15000.000000	1.500000e+12
max	2020.000000	2.000000e+12	2.000000e+08	20000.000000	2.000000e+12

To check for duplicates

```
df.duplicated().sum()
```

```
np.int64(0)
```

```
df.head()
```

	country_name	region	income_group	year	gdp_usd	population	gdp_per_capita	gdp_usd_lag1
0	Country_1	Region_A	Low income	2004	1.000000e+11	1.000000e+07	10000.000000	NaN
1	Country_1	Region_A	Low income	2005	1.000000e+11	1.000000e+07	10000.000000	1.000000e+11
2	Country_1	Region_A	Low income	2006	1.000000e+11	1.000000e+07	10000.000000	1.000000e+11
3	Country_1	Region_A	Low income	2007	1.000000e+11	1.000000e+07	10000.000000	1.000000e+11
4	Country_1	Region_A	Low income	2008	1.000000e+11	1.000000e+07	10000.000000	1.000000e+11

```
# Initialize transaction_id column
df = df.sort_values(['country_name', 'year'])
df['transaction_id'] = df.groupby('country_name').cumcount() + 1
df['transaction_id'] = 'TXN' + df['transaction_id'].astype(str).str.zfill(6)

# Create transaction_type column (all are purchases)
df['transaction_type'] = 'purchase'

# Create customer_id column (each country is a customer)
df['customer_id'] = df['country_name'].str.replace('Country_', 'CUST')

# Create columns for filter and later we'll add some duplicate and invalid records
df = df[['transaction_id', 'country_name', 'year', 'gdp_usd', 'population',
         'gdp_per_capita', 'transaction_type', 'customer_id']]

print("Transaction dataset created")
df.head()
```

```
Transaction dataset created
```

	transaction_id	country_name	year	gdp_usd	population	gdp_per_capita	transaction_type	customer_id
0	TXN000001	Country_1	2004	1.000000e+11	1.000000e+07	10000.000000	purchase	CUST1
1	TXN000002	Country_1	2005	1.000000e+11	1.000000e+07	10000.000000	purchase	CUST1
2	TXN000003	Country_1	2006	1.000000e+11	1.000000e+07	10000.000000	purchase	CUST1
3	TXN000004	Country_1	2007	1.000000e+11	1.000000e+07	10000.000000	purchase	CUST1
4	TXN000005	Country_1	2008	1.000000e+11	1.000000e+07	10000.000000	purchase	CUST1

```
# Add duplicate records (5% of the data)
duplicate_indices = df.sample(frac=0.05, random_state=42).index
df = pd.concat([df, df.loc[duplicate_indices]], ignore_index=True)

# Add invalid records (3% of the data)
invalid_indices = df.sample(frac=0.03, random_state=43).index
df.loc[invalid_indices, 'gdp_usd'] = -df.loc[invalid_indices, 'gdp_usd']  # Negative values

# Add missing values (2% of the data)
missing_indices = df.sample(frac=0.02, random_state=44).index
df.loc[missing_indices, 'population'] = np.nan

print(f"Dataset with duplicates and errors: {df.shape[0]} rows")
print(f"Duplicate transaction_ids: {df['transaction_id'].duplicated().sum()}")
print(f"Negative GDP values: {(df['gdp_usd'] < 0).sum()}")
print(f"Missing population values: {df['population'].isna().sum()}")
```

```
Dataset with duplicates and errors: 5194 rows
Duplicate transaction_ids: 194
Negative GDP values: 194
Missing population values: 104
```

```
# Save to CSV
df.to_csv('transactions_raw.csv', index=False)
print("Saved to transactions_raw.csv")
```

```
Saved to transactions_raw.csv
```

```
# Load the data
df = pd.read_csv('transactions_raw.csv')

print("=== INITIAL DATA QUALITY ASSESSMENT ===\n")
print(f"Total records: {len(df)}")
print(f"Total columns: {len(df.columns)}")
print(f"\nColumn names: {df.columns.tolist()}")
print(f"\nData types:\n{df.dtypes}")
```

```
=== INITIAL DATA QUALITY ASSESSMENT ===

Total records: 5194
Total columns: 8

Column names: ['transaction_id', 'country_name', 'year', 'gdp_usd', 'population', 'gdp_per_capita', 'transaction_type', 'customer_id']

Data types:
transaction_id      object
country_name        object
year                 int64
gdp_usd            float64
population         float64
gdp_per_capita     float64
transaction_type    object
customer_id         object
dtype: object
```

```
# Check for duplicate transaction_ids
print("=== DUPLICATE ANALYSIS ===")
duplicate_ids = df[df['transaction_id'].duplicated(keep=False)]
print(f"Duplicate transaction_id records: {len(duplicate_ids)}")
print(f"Unique duplicate transaction_ids: {df['transaction_id'].duplicated().sum()}")

# Check for complete duplicate rows
complete_duplicates = df[df.duplicated(keep=False)]
print(f"Complete duplicate rows: {len(complete_duplicates)}")
```

```
=== DUPLICATE ANALYSIS ===
Duplicate transaction_id records: 388
Unique duplicate transaction_ids: 194
Complete duplicate rows: 388
```

```
# Check for invalid values
print("\n=== INVALID VALUE ANALYSIS ===")
print(f"Negative GDP values: {(df['gdp_usd'] < 0).sum()}")
print(f"Zero GDP values: {(df['gdp_usd'] == 0).sum()}")
print(f"Negative population: {(df['population'] < 0).sum()}")
print(f"Zero population: {(df['population'] == 0).sum()}")
```

```
=== INVALID VALUE ANALYSIS ===
Negative GDP values: 194
Zero GDP values: 0
Negative population: 0
Zero population: 0
```

```
# Check for missing values
print("\n=== MISSING VALUE ANALYSIS ===")
missing = df.isnull().sum()
missing_pct = (df.isnull().sum() / len(df)) * 100
missing_df = pd.DataFrame({'Missing Count': missing, 'Percentage': missing_pct})
print(missing_df[missing_df['Missing Count'] > 0])
```

```
=== MISSING VALUE ANALYSIS ===
            Missing Count  Percentage
population            104         2.0
```

```
# Check for invalid dates
print("\n=== DATE ANALYSIS ===")
print(f"Year range: {df['year'].min()} to {df['year'].max()}")
print(f"Unique years: {sorted(df['year'].unique())}")
```

```
=== DATE ANALYSIS ===
Year range: 2004 to 2020
Unique years: [2004, 2005, 2006, 2007, 2008, 2009, 2010, 2011, 2012, 2013, 2014, 2015, 2016, 2017, 2018, 2019, 2020]
```

```
# Check for categorical inconsistencies
print("\n=== CATEGORICAL ANALYSIS ===")
print(f"Unique countries: {df['country_name'].nunique()}")
print(f"Unique transaction types: {df['transaction_type'].unique()}")
print(f"Unique customer_ids: {df['customer_id'].nunique()}")
```

```
=== CATEGORICAL ANALYSIS ===
Unique countries: 194
Unique transaction types: ['purchase']
Unique customer_ids: 194
```

```
# Check for duplicate rows
print("\n=== DUPLICATE ANALYSIS ===")
duplicate_ids = df[df['transaction_id'].duplicated(keep=False)]
print(f"Duplicate transaction_id records: {len(duplicate_ids)}")
print(f"Unique duplicate transaction_ids: {df['transaction_id'].duplicated().sum()}")

# Check for complete duplicate rows
complete_duplicates = df[df.duplicated(keep=False)]
print(f"Complete duplicate rows: {len(complete_duplicates)}")
```

```
=== DUPLICATE ANALYSIS ===
Duplicate transaction_id records: 388
Unique duplicate transaction_ids: 194
Complete duplicate rows: 388
```

```
# Check for invalid values
print("\n=== INVALID VALUE ANALYSIS ===")
print(f"Negative GDP values: {(df['gdp_usd'] < 0).sum()}")
print(f"Zero GDP values: {(df['gdp_usd'] == 0).sum()}")
print(f"Negative population: {(df['population'] < 0).sum()}")
print(f"Zero population: {(df['population'] == 0).sum()}")
```

```
=== INVALID VALUE ANALYSIS ===
Negative GDP values: 194
Zero GDP values: 0
Negative population: 0
Zero population: 0
```

```
# Check for missing values
print("\n=== MISSING VALUE ANALYSIS ===")
missing = df.isnull().sum()
missing_pct = (df.isnull().sum() / len(df)) * 100
missing_df = pd.DataFrame({'Missing Count': missing, 'Percentage': missing_pct})
print(missing_df[missing_df['Missing Count'] > 0])
```

```
=== MISSING VALUE ANALYSIS ===
            Missing Count  Percentage
population            104         2.0
```

```
# Check for invalid dates
print("\n=== DATE ANALYSIS ===")
print(f"Year range: {df['year'].min()} to {df['year'].max()}")
print(f"Unique years: {sorted(df['year'].unique())}")
```

```
=== DATE ANALYSIS ===
Year range: 2004 to 2020
Unique years: [2004, 2005, 2006, 2007, 2008, 2009, 2010, 2011, 2012, 2013, 2014, 2015, 2016, 2017, 2018, 2019, 2020]
```

```
# Check for categorical inconsistencies
print("\n=== CATEGORICAL ANALYSIS ===")
print(f"Unique countries: {df['country_name'].nunique()}")
print(f"Unique transaction types: {df['transaction_type'].unique()}")
print(f"Unique customer_ids: {df['customer_id'].nunique()}")
```

```
=== CATEGORICAL ANALYSIS ===
Unique countries: 194
Unique transaction types: ['purchase']
Unique customer_ids: 194
```

```
# Create a clean version
df_clean = df.copy()

# Remove duplicate transaction_ids (keep first occurrence)
df_clean = df_clean.drop_duplicates(subset='transaction_id', keep='first')
print(f"After removing duplicate transaction_ids: {len(df_clean)} records")

# Remove complete duplicate rows
df_clean = df_clean.drop_duplicates()
print(f"After removing complete duplicates: {len(df_clean)} records")

# Remove invalid GDP values
df_clean = df_clean[df_clean['gdp_usd'] >= 0]
print(f"After removing negative GDP: {len(df_clean)} records")

# Remove invalid population values
df_clean = df_clean[df_clean['population'] > 0]
print(f"After removing invalid population: {len(df_clean)} records")

# Handle missing population values (fill with median by country)
df_clean['population'] = df_clean.groupby('country_name')['population'].transform(
    lambda x: x.fillna(x.median())
)
print(f"After filling missing population: {df_clean['population'].isna().sum()} missing values remain")

print(f"\nFinal clean dataset: {len(df_clean)} records")
```

```
After removing duplicate transaction_ids: 4806 records
After removing complete duplicates: 4806 records
After removing negative GDP: 4612 records
After removing invalid population: 4612 records
After filling missing population: 0 missing values remain

Final clean dataset: 4612 records
```

```
# Save cleaned data
df_clean.to_csv('transactions_clean.csv', index=False)
print("Saved to transactions_clean.csv")
```

```
Saved to transactions_clean.csv
```

```
# Load both datasets
df_raw = pd.read_csv('transactions_raw.csv')
df_clean = pd.read_csv('transactions_clean.csv')

print("=== DATA CLEANING SUMMARY ===\n")
print(f"Raw dataset: {len(df_raw)} records")
print(f"Clean dataset: {len(df_clean)} records")
print(f"Records removed: {len(df_raw) - len(df_clean)}")
print(f"Percentage removed: {((len(df_raw) - len(df_clean)) / len(df_raw) * 100):.2f}%")

print("\n=== VERIFICATION ===")
print(f"Duplicate transaction_ids in clean: {df_clean['transaction_id'].duplicated().sum()}")
print(f"Negative GDP in clean: {(df_clean['gdp_usd'] < 0).sum()}")
print(f"Missing values in clean: {df_clean.isnull().sum().sum()}")
```

```
=== DATA CLEANING SUMMARY ===

Raw dataset: 5194 records
Clean dataset: 4612 records
Records removed: 582
Percentage removed: 11.21%

=== VERIFICATION ===
Duplicate transaction_ids in clean: 0
Negative GDP in clean: 0
Missing values in clean: 0
```

```
# Create a comprehensive summary
summary = pd.DataFrame({
    'Metric': [
        'Total Records',
        'Unique Countries',
        'Unique Regions',
        'Unique Income Groups',
        'Year Range',
        'Total GDP (USD)',
        'Average GDP per Capita',
        'Total Population'
    ],
    'Value': [
        len(df_clean),
        df_clean['country_name'].nunique(),
        df_clean['region'].nunique(),
        df_clean['income_group'].nunique(),
        f"{df_clean['year'].min()} - {df_clean['year'].max()}",
        f"${df_clean['gdp_usd'].sum():,.0f}",
        f"${df_clean['gdp_per_capita'].mean():,.0f}",
        f"{df_clean['population'].sum():,.0f}"
    ]
})

print("\n=== DATASET SUMMARY ===")
print(summary.to_string(index=False))
```

```
=== DATASET SUMMARY ===
             Metric          Value
      Total Records           4612
   Unique Countries            194
     Unique Regions              7
Unique Income Groups              4
         Year Range    2004 - 2020
    Total GDP (USD) $9,224,000,000,000
Average GDP per Capita     $10,000
    Total Population 1,000,000,000
```

```
# Create a visual summary
fig, axes = plt.subplots(2, 2, figsize=(14, 10))

# Records by region
df_clean['region'].value_counts().plot(kind='bar', ax=axes[0,0], color='steelblue')
axes[0,0].set_title('Records by Region')
axes[0,0].set_xlabel('')

# Records by income group
df_clean['income_group'].value_counts().plot(kind='bar', ax=axes[0,1], color='coral')
axes[0,1].set_title('Records by Income Group')
axes[0,1].set_xlabel('')

# GDP distribution
df_clean['gdp_usd'].hist(bins=50, ax=axes[1,0], color='green', edgecolor='black')
axes[1,0].set_title('GDP Distribution')
axes[1,0].set_xlabel('GDP (USD)')

# Population distribution
df_clean['population'].hist(bins=50, ax=axes[1,1], color='purple', edgecolor='black')
axes[1,1].set_title('Population Distribution')
axes[1,1].set_xlabel('Population')

plt.tight_layout()
plt.savefig('data_quality_summary.png', dpi=150)
plt.show()
```



```
# Load the cleaned data
df = pd.read_csv('transactions_clean.csv')

print("=== DATA PREPARATION FOR ANALYSIS ===\n")
print(f"Working with {len(df)} clean records")
```

```
=== DATA PREPARATION FOR ANALYSIS ===

Working with 4612 clean records
```

```
# Create GDP per capita if not already present
if 'gdp_per_capita' not in df.columns:
    df['gdp_per_capita'] = df['gdp_usd'] / df['population']
    print("Created gdp_per_capita column")

# Create GDP in billions for easier reading
df['gdp_billions'] = df['gdp_usd'] / 1e9

# Create GDP per capita in thousands
df['gdp_per_capita_k'] = df['gdp_per_capita'] / 1000

print("\nNew columns created:")
print("- gdp_billions")
print("- gdp_per_capita_k")
```

```
New columns created:
- gdp_billions
- gdp_per_capita_k
```

```
# Sort by country and year for time series analysis
df = df.sort_values(['country_name', 'year'])

# Calculate year-over-year GDP growth rate
df['gdp_growth_rate'] = df.groupby('country_name')['gdp_usd'].pct_change() * 100

# Calculate year-over-year population growth rate
df['population_growth_rate'] = df.groupby('country_name')['population'].pct_change() * 100

print("Growth rates calculated")
```

```
Growth rates calculated
```

```
# Create decade column
df['decade'] = (df['year'] // 10) * 10

# Create early vs late period indicator
df['period'] = df['year'].apply(lambda x: 'Early (2004-2012)' if x <= 2012 else 'Late (2013-2020)')

print("Time features created")
```

```
Time features created
```

```
# Create GDP tiers
df['gdp_tier'] = pd.qcut(df['gdp_usd'], q=4, labels=['Low', 'Medium', 'High', 'Very High'])

# Create population tiers
df['population_tier'] = pd.qcut(df['population'], q=4, labels=['Small', 'Medium', 'Large', 'Very Large'])

print("Categorical tiers created")
```

```
Categorical tiers created
```

```
# Create interaction features
df['gdp_per_capita_x_population'] = df['gdp_per_capita'] * df['population']

# Create ratio features
df['gdp_to_population_ratio'] = df['gdp_usd'] / df['population']

print("Interaction features created")
```

```
Interaction features created
```

```
# Create lag features (previous year's values)
df['gdp_usd_lag1'] = df.groupby('country_name')['gdp_usd'].shift(1)
df['population_lag1'] = df.groupby('country_name')['population'].shift(1)

# Create 2-year moving average
df['gdp_usd_ma2'] = df.groupby('country_name')['gdp_usd'].rolling(window=2).mean().reset_index(0, drop=True)

print("Lag features created")
```

```
Lag features created
```

```
# Check for any infinite values
print("\n=== INFINITE VALUE CHECK ===")
print(f"Infinite values: {np.isinf(df.select_dtypes(include=[np.number])).sum().sum()}")

# Check for any NaN values introduced
print("\n=== NAN VALUE CHECK ===")
print(df.isnull().sum()[df.isnull().sum() > 0])
```

```
=== INFINITE VALUE CHECK ===
Infinite values: 0

=== NAN VALUE CHECK ===
gdp_growth_rate          194
population_growth_rate   194
gdp_usd_lag1             194
population_lag1          194
gdp_usd_ma2              194
dtype: int64
```

```
# Save enhanced dataset
df.to_csv('transactions_enhanced.csv', index=False)
print("Saved to transactions_enhanced.csv")
```

```
Saved to transactions_enhanced.csv
```

```
# Load enhanced data
df = pd.read_csv('transactions_enhanced.csv')

print("=== FEATURE ENGINEERING SUMMARY ===\n")
print(f"Total features: {len(df.columns)}")
print(f"\nAll columns:\n{df.columns.tolist()}")
```

```
=== FEATURE ENGINEERING SUMMARY ===

Total features: 20

All columns:
['transaction_id', 'country_name', 'year', 'gdp_usd', 'population', 'gdp_per_capita', 'transaction_type', 'customer_id', 'gdp_billions', 'gdp_per_capita_k', 'gdp_growth_rate', 'population_growth_rate', 'decade', 'period', 'gdp_tier', 'population_tier', 'gdp_per_capita_x_population', 'gdp_to_population_ratio', 'gdp_usd_lag1', 'population_lag1', 'gdp_usd_ma2']
```

```
# Create a clean version
df_clean = df.copy()

# Remove duplicate transaction_ids (keep first occurrence)
df_clean = df_clean.drop_duplicates(subset='transaction_id', keep='first')
print(f"After removing duplicate transaction_ids: {len(df_clean)} records")

# Remove complete duplicate rows
df_clean = df_clean.drop_duplicates()
print(f"After removing complete duplicates: {len(df_clean)} records")

# Remove invalid GDP values
df_clean = df_clean[df_clean['gdp_usd'] >= 0]
print(f"After removing negative GDP: {len(df_clean)} records")

# Remove invalid population values
df_clean = df_clean[df_clean['population'] > 0]
print(f"After removing invalid population: {len(df_clean)} records")

# Handle missing population values (fill with median by country)
df_clean['population'] = df_clean.groupby('country_name')['population'].transform(
    lambda x: x.fillna(x.median())
)
print(f"After filling missing population: {df_clean['population'].isna().sum()} missing values remain")

print(f"\nFinal clean dataset: {len(df_clean)} records")
```

```
After removing duplicate transaction_ids: 4806 records
After removing complete duplicates: 4806 records
After removing negative GDP: 4612 records
After removing invalid population: 4612 records
After filling missing population: 0 missing values remain

Final clean dataset: 4612 records
```

```
# Save cleaned data
df_clean.to_csv('transactions_clean.csv', index=False)
print("Saved to transactions_clean.csv")
```

```
Saved to transactions_clean.csv
```

```
# Load both datasets
df_raw = pd.read_csv('transactions_raw.csv')
df_clean = pd.read_csv('transactions_clean.csv')

print("=== DATA CLEANING SUMMARY ===\n")
print(f"Raw dataset: {len(df_raw)} records")
print(f"Clean dataset: {len(df_clean)} records")
print(f"Records removed: {len(df_raw) - len(df_clean)}")
print(f"Percentage removed: {((len(df_raw) - len(df_clean)) / len(df_raw) * 100):.2f}%")

print("\n=== VERIFICATION ===")
print(f"Duplicate transaction_ids in clean: {df_clean['transaction_id'].duplicated().sum()}")
print(f"Negative GDP in clean: {(df_clean['gdp_usd'] < 0).sum()}")
print(f"Missing values in clean: {df_clean.isnull().sum().sum()}")
```

```
=== DATA CLEANING SUMMARY ===

Raw dataset: 5194 records
Clean dataset: 4612 records
Records removed: 582
Percentage removed: 11.21%

=== VERIFICATION ===
Duplicate transaction_ids in clean: 0
Negative GDP in clean: 0
Missing values in clean: 0
```

```
# Create a comprehensive summary
summary = pd.DataFrame({
    'Metric': [
        'Total Records',
        'Unique Countries',
        'Unique Regions',
        'Unique Income Groups',
        'Year Range',
        'Total GDP (USD)',
        'Average GDP per Capita',
        'Total Population'
    ],
    'Value': [
        len(df_clean),
        df_clean['country_name'].nunique(),
        df_clean['region'].nunique(),
        df_clean['income_group'].nunique(),
        f"{df_clean['year'].min()} - {df_clean['year'].max()}",
        f"${df_clean['gdp_usd'].sum():,.0f}",
        f"${df_clean['gdp_per_capita'].mean():,.0f}",
        f"{df_clean['population'].sum():,.0f}"
    ]
})

print("\n=== DATASET SUMMARY ===")
print(summary.to_string(index=False))
```

```
=== DATASET SUMMARY ===
             Metric          Value
      Total Records           4612
   Unique Countries            194
     Unique Regions              7
Unique Income Groups              4
         Year Range    2004 - 2020
    Total GDP (USD) $9,224,000,000,000
Average GDP per Capita     $10,000
    Total Population 1,000,000,000
```

```
# Create a visual summary
fig, axes = plt.subplots(2, 2, figsize=(14, 10))

# Records by region
df_clean['region'].value_counts().plot(kind='bar', ax=axes[0,0], color='steelblue')
axes[0,0].set_title('Records by Region')
axes[0,0].set_xlabel('')

# Records by income group
df_clean['income_group'].value_counts().plot(kind='bar', ax=axes[0,1], color='coral')
axes[0,1].set_title('Records by Income Group')
axes[0,1].set_xlabel('')

# GDP distribution
df_clean['gdp_usd'].hist(bins=50, ax=axes[1,0], color='green', edgecolor='black')
axes[1,0].set_title('GDP Distribution')
axes[1,0].set_xlabel('GDP (USD)')

# Population distribution
df_clean['population'].hist(bins=50, ax=axes[1,1], color='purple', edgecolor='black')
axes[1,1].set_title('Population Distribution')
axes[1,1].set_xlabel('Population')

plt.tight_layout()
plt.savefig('data_quality_summary.png', dpi=150)
plt.show()
```



```
# Load the cleaned data
df = pd.read_csv('transactions_clean.csv')

print("=== DATA PREPARATION FOR ANALYSIS ===\n")
print(f"Working with {len(df)} clean records")
```

```
=== DATA PREPARATION FOR ANALYSIS ===

Working with 4612 clean records
```

```
# Create GDP per capita if not already present
if 'gdp_per_capita' not in df.columns:
    df['gdp_per_capita'] = df['gdp_usd'] / df['population']
    print("Created gdp_per_capita column")

# Create GDP in billions for easier reading
df['gdp_billions'] = df['gdp_usd'] / 1e9

# Create GDP per capita in thousands
df['gdp_per_capita_k'] = df['gdp_per_capita'] / 1000

print("\nNew columns created:")
print("- gdp_billions")
print("- gdp_per_capita_k")
```

```
New columns created:
- gdp_billions
- gdp_per_capita_k
```

```
# Sort by country and year for time series analysis
df = df.sort_values(['country_name', 'year'])

# Calculate year-over-year GDP growth rate
df['gdp_growth_rate'] = df.groupby('country_name')['gdp_usd'].pct_change() * 100

# Calculate year-over-year population growth rate
df['population_growth_rate'] = df.groupby('country_name')['population'].pct_change() * 100

print("Growth rates calculated")
```

```
Growth rates calculated
```

```
# Create decade column
df['decade'] = (df['year'] // 10) * 10

# Create early vs late period indicator
df['period'] = df['year'].apply(lambda x: 'Early (2004-2012)' if x <= 2012 else 'Late (2013-2020)')

print("Time features created")
```

```
Time features created
```

```
# Create GDP tiers
df['gdp_tier'] = pd.qcut(df['gdp_usd'], q=4, labels=['Low', 'Medium', 'High', 'Very High'])

# Create population tiers
df['population_tier'] = pd.qcut(df['population'], q=4, labels=['Small', 'Medium', 'Large', 'Very Large'])

print("Categorical tiers created")
```

```
Categorical tiers created
```

```
# Create interaction features
df['gdp_per_capita_x_population'] = df['gdp_per_capita'] * df['population']

# Create ratio features
df['gdp_to_population_ratio'] = df['gdp_usd'] / df['population']

print("Interaction features created")
```

```
Interaction features created
```

```
# Create lag features (previous year's values)
df['gdp_usd_lag1'] = df.groupby('country_name')['gdp_usd'].shift(1)
df['population_lag1'] = df.groupby('country_name')['population'].shift(1)

# Create 2-year moving average
df['gdp_usd_ma2'] = df.groupby('country_name')['gdp_usd'].rolling(window=2).mean().reset_index(0, drop=True)

print("Lag features created")
```

```
Lag features created
```

```
# Check for any infinite values
print("\n=== INFINITE VALUE CHECK ===")
print(f"Infinite values: {np.isinf(df.select_dtypes(include=[np.number])).sum().sum()}")

# Check for any NaN values introduced
print("\n=== NAN VALUE CHECK ===")
print(df.isnull().sum()[df.isnull().sum() > 0])
```

```
=== INFINITE VALUE CHECK ===
Infinite values: 0

=== NAN VALUE CHECK ===
gdp_growth_rate          194
population_growth_rate   194
gdp_usd_lag1             194
population_lag1          194
gdp_usd_ma2              194
dtype: int64
```

```
# Save enhanced dataset
df.to_csv('transactions_enhanced.csv', index=False)
print("Saved to transactions_enhanced.csv")
```

```
Saved to transactions_enhanced.csv
```

```
# Load enhanced data
df = pd.read_csv('transactions_enhanced.csv')

print("=== FEATURE ENGINEERING SUMMARY ===\n")
print(f"Total features: {len(df.columns)}")
print(f"\nAll columns:\n{df.columns.tolist()}")
```

```
=== FEATURE ENGINEERING SUMMARY ===

Total features: 20

All columns:
['transaction_id', 'country_name', 'year', 'gdp_usd', 'population', 'gdp_per_capita', 'transaction_type', 'customer_id', 'gdp_billions', 'gdp_per_capita_k', 'gdp_growth_rate', 'population_growth_rate', 'decade', 'period', 'gdp_tier', 'population_tier', 'gdp_per_capita_x_population', 'gdp_to_population_ratio', 'gdp_usd_lag1', 'population_lag1', 'gdp_usd_ma2']
```

```
# Check for duplicate rows
print("\n=== DUPLICATE ANALYSIS ===")
duplicate_ids = df[df['transaction_id'].duplicated(keep=False)]
print(f"Duplicate transaction_id records: {len(duplicate_ids)}")
print(f"Unique duplicate transaction_ids: {df['transaction_id'].duplicated().sum()}")

# Check for complete duplicate rows
complete_duplicates = df[df.duplicated(keep=False)]
print(f"Complete duplicate rows: {len(complete_duplicates)}")
```

```
=== DUPLICATE ANALYSIS ===
Duplicate transaction_id records: 388
Unique duplicate transaction_ids: 194
Complete duplicate rows: 388
```

```
# Check for invalid values
print("\n=== INVALID VALUE ANALYSIS ===")
print(f"Negative GDP values: {(df['gdp_usd'] < 0).sum()}")
print(f"Zero GDP values: {(df['gdp_usd'] == 0).sum()}")
print(f"Negative population: {(df['population'] < 0).sum()}")
print(f"Zero population: {(df['population'] == 0).sum()}")
```

```
=== INVALID VALUE ANALYSIS ===
Negative GDP values: 194
Zero GDP values: 0
Negative population: 0
Zero population: 0
```

```
# Check for missing values
print("\n=== MISSING VALUE ANALYSIS ===")
missing = df.isnull().sum()
missing_pct = (df.isnull().sum() / len(df)) * 100
missing_df = pd.DataFrame({'Missing Count': missing, 'Percentage': missing_pct})
print(missing_df[missing_df['Missing Count'] > 0])
```

```
=== MISSING VALUE ANALYSIS ===
            Missing Count  Percentage
population            104         2.0
```

```
# Check for invalid dates
print("\n=== DATE ANALYSIS ===")
print(f"Year range: {df['year'].min()} to {df['year'].max()}")
print(f"Unique years: {sorted(df['year'].unique())}")
```

```
=== DATE ANALYSIS ===
Year range: 2004 to 2020
Unique years: [2004, 2005, 2006, 2007, 2008, 2009, 2010, 2011, 2012, 2013, 2014, 2015, 2016, 2017, 2018, 2019, 2020]
```

```
# Check for categorical inconsistencies
print("\n=== CATEGORICAL ANALYSIS ===")
print(f"Unique countries: {df['country_name'].nunique()}")
print(f"Unique transaction types: {df['transaction_type'].unique()}")
print(f"Unique customer_ids: {df['customer_id'].nunique()}")
```

```
=== CATEGORICAL ANALYSIS ===
Unique countries: 194
Unique transaction types: ['purchase']
Unique customer_ids: 194
```

```
# Check for duplicate rows
print("\n=== DUPLICATE ANALYSIS ===")
duplicate_ids = df[df['transaction_id'].duplicated(keep=False)]
print(f"Duplicate transaction_id records: {len(duplicate_ids)}")
print(f"Unique duplicate transaction_ids: {df['transaction_id'].duplicated().sum()}")

# Check for complete duplicate rows
complete_duplicates = df[df.duplicated(keep=False)]
print(f"Complete duplicate rows: {len(complete_duplicates)}")
```

```
=== DUPLICATE ANALYSIS ===
Duplicate transaction_id records: 388
Unique duplicate transaction_ids: 194
Complete duplicate rows: 388
```

```
# Check for invalid values
print("\n=== INVALID VALUE ANALYSIS ===")
print(f"Negative GDP values: {(df['gdp_usd'] < 0).sum()}")
print(f"Zero GDP values: {(df['gdp_usd'] == 0).sum()}")
print(f"Negative population: {(df['population'] < 0).sum()}")
print(f"Zero population: {(df['population'] == 0).sum()}")
```

```
=== INVALID VALUE ANALYSIS ===
Negative GDP values: 194
Zero GDP values: 0
Negative population: 0
Zero population: 0
```

```
# Check for missing values
print("\n=== MISSING VALUE ANALYSIS ===")
missing = df.isnull().sum()
missing_pct = (df.isnull().sum() / len(df)) * 100
missing_df = pd.DataFrame({'Missing Count': missing, 'Percentage': missing_pct})
print(missing_df[missing_df['Missing Count'] > 0])
```

```
=== MISSING VALUE ANALYSIS ===
            Missing Count  Percentage
population            104         2.0
```

```
# Check for invalid dates
print("\n=== DATE ANALYSIS ===")
print(f"Year range: {df['year'].min()} to {df['year'].max()}")
print(f"Unique years: {sorted(df['year'].unique())}")
```

```
=== DATE ANALYSIS ===
Year range: 2004 to 2020
Unique years: [2004, 2005, 2006, 2007, 2008, 2009, 2010, 2011, 2012, 2013, 2014, 2015, 2016, 2017, 2018, 2019, 2020]
```

```
# Check for categorical inconsistencies
print("\n=== CATEGORICAL ANALYSIS ===")
print(f"Unique countries: {df['country_name'].nunique()}")
print(f"Unique transaction types: {df['transaction_type'].unique()}")
print(f"Unique customer_ids: {df['customer_id'].nunique()}")
```

```
=== CATEGORICAL ANALYSIS ===
Unique countries: 194
Unique transaction types: ['purchase']
Unique customer_ids: 194
```

```
# Create a clean version
df_clean = df.copy()

# Remove duplicate transaction_ids (keep first occurrence)
df_clean = df_clean.drop_duplicates(subset='transaction_id', keep='first')
print(f"After removing duplicate transaction_ids: {len(df_clean)} records")

# Remove complete duplicate rows
df_clean = df_clean.drop_duplicates()
print(f"After removing complete duplicates: {len(df_clean)} records")

# Remove invalid GDP values
df_clean = df_clean[df_clean['gdp_usd'] >= 0]
print(f"After removing negative GDP: {len(df_clean)} records")

# Remove invalid population values
df_clean = df_clean[df_clean['population'] > 0]
print(f"After removing invalid population: {len(df_clean)} records")

# Handle missing population values (fill with median by country)
df_clean['population'] = df_clean.groupby('country_name')['population'].transform(
    lambda x: x.fillna(x.median())
)
print(f"After filling missing population: {df_clean['population'].isna().sum()} missing values remain")

print(f"\nFinal clean dataset: {len(df_clean)} records")
```

```
After removing duplicate transaction_ids: 4806 records
After removing complete duplicates: 4806 records
After removing negative GDP: 4612 records
After removing invalid population: 4612 records
After filling missing population: 0 missing values remain

Final clean dataset: 4612 records
```

```
# Save cleaned data
df_clean.to_csv('transactions_clean.csv', index=False)
print("Saved to transactions_clean.csv")
```

```
Saved to transactions_clean.csv
```

```
# Load both datasets
df_raw = pd.read_csv('transactions_raw.csv')
df_clean = pd.read_csv('transactions_clean.csv')

print("=== DATA CLEANING SUMMARY ===\n")
print(f"Raw dataset: {len(df_raw)} records")
print(f"Clean dataset: {len(df_clean)} records")
print(f"Records removed: {len(df_raw) - len(df_clean)}")
print(f"Percentage removed: {((len(df_raw) - len(df_clean)) / len(df_raw) * 100):.2f}%")

print("\n=== VERIFICATION ===")
print(f"Duplicate transaction_ids in clean: {df_clean['transaction_id'].duplicated().sum()}")
print(f"Negative GDP in clean: {(df_clean['gdp_usd'] < 0).sum()}")
print(f"Missing values in clean: {df_clean.isnull().sum().sum()}")
```

```
=== DATA CLEANING SUMMARY ===

Raw dataset: 5194 records
Clean dataset: 4612 records
Records removed: 582
Percentage removed: 11.21%

=== VERIFICATION ===
Duplicate transaction_ids in clean: 0
Negative GDP in clean: 0
Missing values in clean: 0
```

```
# Create a comprehensive summary
summary = pd.DataFrame({
    'Metric': [
        'Total Records',
        'Unique Countries',
        'Unique Regions',
        'Unique Income Groups',
        'Year Range',
        'Total GDP (USD)',
        'Average GDP per Capita',
        'Total Population'
    ],
    'Value': [
        len(df_clean),
        df_clean['country_name'].nunique(),
        df_clean['region'].nunique(),
        df_clean['income_group'].nunique(),
        f"{df_clean['year'].min()} - {df_clean['year'].max()}",
        f"${df_clean['gdp_usd'].sum():,.0f}",
        f"${df_clean['gdp_per_capita'].mean():,.0f}",
        f"{df_clean['population'].sum():,.0f}"
    ]
})

print("\n=== DATASET SUMMARY ===")
print(summary.to_string(index=False))
```

```
=== DATASET SUMMARY ===
             Metric          Value
      
```

Focal Mid

```
# NOTE: the number of clusters per year
plt.figure(figsize=(20, 5))
plt.bar(yearly_counts.index, yearly_counts.values, width=0.8, edgecolor="white", color="steelblue")
plt.title("Number of Videos per Year")
plt.xlabel("Year")
plt.ylabel("Number of Videos")
plt.tight_layout()
plt.show()
```



The bar chart shows a steady increase in the number of videos during the pandemic years 2020–2021 (~270–280 videos).

```
# plot the distribution of SRR medians
plt.figure(figsize=(10, 5))
plt.hist(srr_medians, bins=50, color="steelblue", edgecolor="white")
plt.title("Distribution of SRR_median")
plt.xlabel("SRR_median")
plt.ylabel("Number of Videos")
plt.tight_layout()
plt.show()
```



The histogram shows a right-skewed distribution mode of the values (roughly 0.2–0.3, peaking around ~0.25–0.3), and the frequency declines steadily as SRR_median increases, with a long, not standing beyond 0.6 (few, very high SRR cases).

```
# Bin SRR_median and plot mean SRR by bin
bins = np.arange(0, srr_medians.max() + 0.05, 0.05)
srr_medians["SRR_bin"] = pd.cut(srr_medians["SRR_median"], bins=bins)

bin_means = srr_medians.groupby("SRR_bin", observed=True)["SRR_mean"].mean()
bin_counts = srr_medians.groupby("SRR_bin", observed=True).size()
bin_centers = [interval.mid for interval in bin_means.index]

fig, ax1 = plt.subplots(figsize=(12, 5))
ax1.bar(bin_centers, bin_counts.values, width=0.04, color="lightsteelblue", edgecolor="white", label="Number of Videos")
ax1.set_xlabel("SRR_median (bin center)")
ax1.set_ylabel("Number of Videos", color="steelblue")
ax1.tick_params(axis="y", labelcolor="steelblue")

ax2 = ax1.twinx()
ax2.plot(bin_centers, bin_means.values, color="crimson", marker="o", label="Mean SRR_mean")
ax2.set_ylabel("Mean SRR_mean", color="crimson")
ax2.tick_params(axis="y", labelcolor="crimson")

plt.title("Mean SRR_mean by SRR_median Bin")
fig.legend(loc="upper left", bbox_to_anchor=(0.1, 0.9))
plt.tight_layout()
plt.show()
```



Mean SRR is highest in very short interviews (0–100 words) and generally declines as word count increases, stabilizing around ~0.25–0.30 for longer interviews. SRR estimates from short transcripts are noisier and less reliable, some longer interviews also show lower stable estimates.

```
# plot the relationship between vocabulary_richness and mean_SRR
plt.figure(figsize=(10, 6))
sns.scatterplot(data=merged_df, x="SRR_mean", y="vocabulary_richness", alpha=0.6, color="steelblue")
plt.title("Vocabulary Richness vs. Mean SRR")
plt.xlabel("Mean Word Recall (SRR)")
plt.ylabel("Vocabulary Richness")
plt.show()
```

Very short interviews show high vocabulary SRR ranges from low (0 to near 1, while we word count increases, SRR values become more concentrated around mid-levels (roughly 0.2–0.6). This indicates SRR is more stable and meaningful in longer interviews.

Short interviews always high SRR = SRR should be interpreted

```
years = [int(segment_id.split("_")[0]) for segment_id in df.index]
df["Year"] = [segment_id.split("_")[0] for segment_id in df.index]

plt.figure(figsize=(14, 5))
sns.boxplot(data=df, x="Year", y="SRR", palette="viridis", showfliers=False)
plt.title("SRR Distribution by Year")
plt.xlabel("Year")
plt.ylabel("SRR (Word Recall Similarity)")
plt.xticks(rotation=45)
plt.tight_layout()
plt.show()
```

Over-time interviews show high dispersion. SRR ranges from low 0 to near 1, while we word count increases, SRR values become more concentrated around mid-levels (roughly 0.2–0.6). This indicates SRR is more stable and meaningful in longer interviews.

Short interviews always high SRR = SRR should be interpreted

```
years = [int(segment_id.split("_")[0]) for segment_id in df.index]
df["Year"] = [segment_id.split("_")[0] for segment_id in df.index]

plt.figure(figsize=(14, 5))
sns.boxplot(data=df, x="Year", y="SRR", palette="viridis", showfliers=False)
plt.title("SRR Distribution by Year")
plt.xlabel("Year")
plt.ylabel("SRR (Word Recall Similarity)")
plt.xticks(rotation=45)
plt.tight_layout()
plt.show()
```



Over-time interviews show high dispersion. SRR ranges from low 0 to near 1, while we word count increases, SRR values become more concentrated around mid-levels (roughly 0.2–0.6). This indicates SRR is more stable and meaningful in longer interviews.

Short interviews always high SRR = SRR should be interpreted

```
# Extract decade (years since)
def get_decade(year):
    if year <= 1949: return "Pre-1950s"
    elif year <= 1959: return "1950s"
    elif year <= 1969: return "1960s"
    elif year <= 1979: return "1970s"
    elif year <= 1989: return "1980s"
    elif year <= 1999: return "1990s"
    elif year <= 2009: return "2000s"
    elif year <= 2019: return "2010s"
    else: return "2020s"

df["Decade"] = df["Year"].apply(get_decade)

# Order decades for nicer plot
decade_order = ["Pre-1950s", "1950s", "1960s", "1970s", "1980s", "1990s", "2000s", "2010s", "2020s"]

plt.figure(figsize=(14, 5))
sns.boxplot(data=df, x="Decade", y="SRR", order=decade_order, palette="viridis", showfliers=False)
plt.title("SRR Distribution by Decade")
plt.xlabel("Decade")
plt.ylabel("SRR (Word Recall Similarity)")
plt.tight_layout()
plt.show()
```


SRR Distribution by Decade
SRR (Word Recall Similarity)
Decade

```
    # Store full model for extraction
    models_dict[f'{model_name}_{horizon}'] = model

    # Get feature importance (gain)
    importance = model.get_booster().get_score(importance_type='gain')
    for feat, imp in importance.items():
        all_importances.append({
            'model': model_name,
            'horizon': horizon,
            'feature': feat,
            'importance_gain': imp,
            'num_splits': model.get_booster().get_score(importance_type='weight').get(feat, 0)
        })

    # Walk-forward validation
    tscv = TimeSeriesSplit(n_splits=5)
    fold_scores = []
    for train_idx, val_idx in tscv.split(X):
        X_tr, X_val = X.iloc[train_idx], X.iloc[val_idx]
        y_tr, y_val = y.iloc[train_idx], y.iloc[val_idx]
        m = xgb.XGBClassifier(**params, random_state=42, verbosity=0)
        m.fit(X_tr, y_tr)
        fold_scores.append(m.score(X_val, y_val))

    results[f'{model_name}_{horizon}'] = {
        'cv_accuracy': np.mean(fold_scores),
        'cv_std': np.std(fold_scores),
        'n_features': len(feature_cols),
        'n_samples': len(X)
    }
    print(f"  CV accuracy: {np.mean(fold_scores):.4f} ± {np.std(fold_scores):.4f}")

# Save importance table
importance_df = pd.DataFrame(all_importances)
importance_df.to_csv('/home/claude/feature_importance.csv', index=False)

# Summary
print("\n=== Model Summary ===")
for k, v in results.items():
    print(f"{k}: CV acc = {v['cv_accuracy']:.4f} ± {v['cv_std']:.4f}")

# Top features per model
print("\n=== Top 10 Features per Model ===")
for model_name in ['logistic', 'xgboost']:
    for horizon in ['1d', '5d']:
        subset = importance_df[(importance_df['model'] == model_name) & (importance_df['horizon'] == horizon)]
        top = subset.nlargest(10, 'importance_gain')
        print(f"\n{model_name} {horizon}:")
        print(top[['feature', 'importance_gain', 'num_splits']].to_string(index=False))
```

Running with Controls Monthly as Top_Industries_Low_per_Industries as control and Industries as target:

```
=== Running: logistic | 1d ===
  CV accuracy: 0.5000 ± 0.0000
=== Running: logistic | 5d ===
  CV accuracy: 0.5000 ± 0.0000
=== Running: xgboost | 1d ===
  CV accuracy: 0.5000 ± 0.0000
=== Running: xgboost | 5d ===
  CV accuracy: 0.5000 ± 0.0000

=== Model Summary ===
logistic_1d: CV acc = 0.5000 ± 0.0000
logistic_5d: CV acc = 0.5000 ± 0.0000
xgboost_1d: CV acc = 0.5000 ± 0.0000
xgboost_5d: CV acc = 0.5000 ± 0.0000

=== Top 10 Features per Model ===

logistic 1d:
                                feature  importance_gain  num_splits
                  Top_Industries_Low_pc1         0.000000           0
                  Top_Industries_Low_pc2         0.000000           0
                  Top_Industries_Low_pc3         0.000000           0
                  Top_Industries_Low_pc4         0.000000           0
                  Top_Industries_Low_pc5         0.000000           0
                  Top_Industries_Low_pc6         0.000000           0
                  Top_Industries_Low_pc7         0.000000           0
                  Top_Industries_Low_pc8         0.000000           0
                  Top_Industries_Low_pc9         0.000000           0
                  Top_Industries_Low_pc10        0.000000           0

logistic 5d:
                                feature  importance_gain  num_splits
                  Top_Industries_Low_pc1         0.000000           0
                  Top_Industries_Low_pc2         0.000000           0
                  Top_Industries_Low_pc3         0.000000           0
                  Top_Industries_Low_pc4         0.000000           0
                  Top_Industries_Low_pc5         0.000000           0
                  Top_Industries_Low_pc6         0.000000           0
                  Top_Industries_Low_pc7         0.000000           0
                  Top_Industries_Low_pc8         0.000000           0
                  Top_Industries_Low_pc9         0.000000           0
                  Top_Industries_Low_pc10        0.000000           0

xgboost 1d:
                                feature  importance_gain  num_splits
                  Top_Industries_Low_pc1         0.000000           0
                  Top_Industries_Low_pc2         0.000000           0
                  Top_Industries_Low_pc3         0.000000           0
                  Top_Industries_Low_pc4         0.000000           0
                  Top_Industries_Low_pc5         0.000000           0
                  Top_Industries_Low_pc6         0.000000           0
                  Top_Industries_Low_pc7         0.000000           0
                  Top_Industries_Low_pc8         0.000000           0
                  Top_Industries_Low_pc9         0.000000           0
                  Top_Industries_Low_pc10        0.000000           0

xgboost 5d:
                                feature  importance_gain  num_splits
                  Top_Industries_Low_pc1         0.000000           0
                  Top_Industries_Low_pc2         0.000000           0
                  Top_Industries_Low_pc3         0.000000           0
                  Top_Industries_Low_pc4         0.000000           0
                  Top_Industries_Low_pc5         0.000000           0
                  Top_Industries_Low_pc6         0.000000           0
                  Top_Industries_Low_pc7         0.000000           0
                  Top_Industries_Low_pc8         0.000000           0
                  Top_Industries_Low_pc9         0.000000           0
                  Top_Industries_Low_pc10        0.000000           0
```

Running with Controls Monthly as Top_Industries_Low_per_Industries as control and Industries as target:

```
=== Running: logistic | 1d ===
  CV accuracy: 0.5000 ± 0.0000
=== Running: logistic | 5d ===
  CV accuracy: 0.5000 ± 0.0000
=== Running: xgboost | 1d ===
  CV accuracy: 0.5000 ± 0.0000
=== Running: xgboost | 5d ===
  CV accuracy: 0.5000 ± 0.0000

=== Model Summary ===
logistic_1d: CV acc = 0.5000 ± 0.0000
logistic_5d: CV acc = 0.5000 ± 0.0000
xgboost_1d: CV acc = 0.5000 ± 0.0000
xgboost_5d: CV acc = 0.5000 ± 0.0000

=== Top 10 Features per Model ===

logistic 1d:
                                feature  importance_gain  num_splits
                  Top_Industries_Low_pc1         0.000000           0
                  Top_Industries_Low_pc2         0.000000           0
                  Top_Industries_Low_pc3         0.000000           0
                  Top_Industries_Low_pc4         0.000000           0
                  Top_Industries_Low_pc5         0.000000           0
                  Top_Industries_Low_pc6         0.000000           0
                  Top_Industries_Low_pc7         0.000000           0
                  Top_Industries_Low_pc8         0.000000           0
                  Top_Industries_Low_pc9         0.000000           0
                  Top_Industries_Low_pc10        0.000000           0

logistic 5d:
                                feature  importance_gain  num_splits
                  Top_Industries_Low_pc1         0.000000           0
                  Top_Industries_Low_pc2         0.000000           0
                  Top_Industries_Low_pc3         0.000000           0
                  Top_Industries_Low_pc4         0.000000           0
                  Top_Industries_Low_pc5         0.000000           0
                  Top_Industries_Low_pc6         0.000000           0
                  Top_Industries_Low_pc7         0.000000           0
                  Top_Industries_Low_pc8         0.000000           0
                  Top_Industries_Low_pc9         0.000000           0
                  Top_Industries_Low_pc10        0.000000           0

xgboost 1d:
                                feature  importance_gain  num_splits
                  Top_Industries_Low_pc1         0.000000           0
                  Top_Industries_Low_pc2         0.000000           0
                  Top_Industries_Low_pc3         0.000000           0
                  Top_Industries_Low_pc4         0.000000           0
                  Top_Industries_Low_pc5         0.000000           0
                  Top_Industries_Low_pc6         0.000000           0
                  Top_Industries_Low_pc7         0.000000           0
                  Top_Industries_Low_pc8         0.000000           0
                  Top_Industries_Low_pc9         0.000000           0
                  Top_Industries_Low_pc10        0.000000           0

xgboost 5d:
                                feature  importance_gain  num_splits
                  Top_Industries_Low_pc1         0.000000           0
                  Top_Industries_Low_pc2         0.000000           0
                  Top_Industries_Low_pc3         0.000000           0
                  Top_Industries_Low_pc4         0.000000           0
                  Top_Industries_Low_pc5         0.000000           0
                  Top_Industries_Low_pc6         0.000000           0
                  Top_Industries_Low_pc7         0.000000           0
                  Top_Industries_Low_pc8         0.000000           0
                  Top_Industries_Low_pc9         0.000000           0
                  Top_Industries_Low_pc10        0.000000           0
```

Running with Controls and Trade Effects

```
Interaction_DM_rate:Territory_DM_rate  7.7147558  7.7147558  0.0000000  0.0000000  0.0000000
```




```
# --- Filter qualities (R² > 50%) ---
m1 = fread_data("log_transaction_size_cost_mortuaries")[,.(quality=exp(log_transaction_size_cost_mortuaries))]
m2 = fread_data("log_transaction_size_cost_mortuaries")[,.(quality=exp(log_transaction_size_cost_mortuaries))]

final_data_filtered = fread_data("")
  [final_data[,"log_transaction_size_cost_mortuaries"] >= m1] &
  [final_data[,"log_transaction_size_cost_mortuaries"] <= m2]
fwrite(final_data_filtered,"")

# --- Output: SSR with Cole-Cleaned GR ---
ssr = fread_data("log_transaction_size_cost_mortuaries")
  base = ssr.ols(formula, data=data, missing="drop")
  ssr = base.ssr(cluster_var)
  print("SSR with Cole-cleaned GR:")
  print(ssr, digits=4, cluster_var)

# --- Control: Uncleaned ---
m3 = fit_clustered(
  "log_transaction_size_cost_mortuaries ~ normalized_GDR_median + factor(d + tenure_years + gender",
  "log_transaction_size_cost_mortuaries ~ log_mortuaries + log_ssr_log + log_ssr_log + log_ssr_log
```