

Model 1 Factorial

"In mathematics, the *factorial* of a non-negative integer n , denoted by $n!$, is the product of all positive integers less than or equal to n . For example, $5! = 5 \times 4 \times 3 \times 2 \times 1 = 120$."

Source: <https://en.wikipedia.org/wiki/Factorial>

n	$n!$
0	1
1	1
2	2
3	6
4	24
5	120

Questions (25 min)

Start time:

1. Consider how to calculate $4! = 24$.

a) Write out all the numbers that need to be multiplied:

$$4! =$$

b) Rewrite the expression using $3!$ instead of $3 \times 2 \times 1$:

$$4! =$$

2. Write an expression similar to #1b showing how each factorial can be calculated in terms of a simpler factorial.

a) $3! =$

b) $2! =$

c) $100! =$

d) $n! =$

3. What is the value of $0!$ based on Model 1? Does it make sense to define $0!$ in terms of a simpler factorial? Why or why not?

*If we repeatedly break down a problem into smaller versions of itself, we eventually reach a basic problem that can't be broken down any further. Such a problem, like 0!, is referred to as the **base case**.*

4. Assume you already have a working method named `factorial(int n)` that returns $n!$ for any positive integer.

a) Review your answer to #2c that shows how to compute 100! using a simpler factorial. Convert this expression to Java by using the `factorial` method instead of the `!` operator.

b) Now rewrite your answer to #2d in Java using the variable `n`.

5. Here is a factorial method that includes output for debugging:

```
1 public static int factorial(int n) {
2     System.out.println("n is " + n);
3     if (n == 0) {
4         return 1; // base case
5     } else {
6         System.out.printf("need factorial of %d\n", n - 1);
7         int answer = factorial(n - 1);
8         System.out.printf("factorial of %d is %d\n", n - 1, answer);
9         return n * answer;
10    }
11 }
12
13 public static void main(String[] args) {
14     System.out.println(factorial(3));
15 }
```

a) What specific method is invoked on line 7?

b) Why is the `if` statement required on line 3?

6. A method that invokes itself is called **recursive**. What two steps were necessary to define the factorial method? How were these steps implemented in Java?

7. How many distinct method calls would be made to `factorial` to compute the factorial of 3? Identify the value of the parameter n for each of these separate calls.

8. Here is the complete output from the program in #5. Identify which distinct method call printed each line. In other words, which lines were printed by `factorial(3)`, which lines were printed by `factorial(2)`, and so on.

```
n is 3
need factorial of 2
n is 2
need factorial of 1
n is 1
need factorial of 0
n is 0
factorial of 0 is 1
factorial of 1 is 1
factorial of 2 is 2
6
```

9. What happens if you try to calculate the factorial of a negative number? How could you prevent this behavior in the `factorial` method?

10. Trivia question: What is the largest factorial you can compute in Java when using `int` as the data type? If you don't know, how could you find out?