

Introduction to Python

Scripting in Python

25th November 2016

Opening Files

```
f = open('foo.txt', 'r') # read  
f.close()
```

Opening Files

```
f = open( 'foo.txt' , 'r' ) # read  
f.close()
```

```
f = open( 'foo.txt' , 'w' ) # write  
f.close()
```

Opening Files

```
f = open( 'foo.txt' , 'r' ) # read  
f.close()
```

```
f = open( 'foo.txt' , 'w' ) # write  
f.close()
```

```
f = open( 'foo.txt' , 'a' ) # append  
f.close()
```

Opening Byte Files

If your file is not a simple text file you might have to treat it as a byte file. e.g. PDF, pickle files etc

```
f = open( 'foo.txt' , 'rb' ) # read  
f.close()
```

```
f = open( 'foo.txt' , 'wb' ) # write  
f.close()
```

```
f = open( 'foo.txt' , 'ab' ) # append  
f.close()
```

Better Opening Files

- You should always close a file that you open.
- The OS *should* take care of it if your program closes.

Better Opening Files

- You should always close a file that you open.
- The OS *should* take care of it if your program closes.
- The best way to handle this is with *context handlers*:

```
with open('foo.txt', 'r') as f:  
    # code
```

Reading Files

- The file handle has an internal state - position in the file.

Reading Files

- The file handle has an internal state - position in the file.
- Several of the "read" functions move that state forwards

Reading Files

- The file handle has an internal state - position in the file.
- Several of the "read" functions move that state forwards
- Use `seek()` to move around this state

Reading Files

- The file handle has an internal state - position in the file.
- Several of the "read" functions move that state forwards
- Use seek() to move around this state
- tell() returns the current line number

```
with open('foo.txt', 'r') as f:  
    lines = f.readlines() # list of lines  
    print f.readlines() # prints []  
    f.seek(0)  
    f.readlines() == lines # True
```

Reading Files

- `readlines()` returns an array of the lines
- `read()` returns a string of the whole file

Reading Files

- `readlines()` returns an array of the lines
- `read()` returns a string of the whole file
- Both of these require you to store whole file in memory, bad for big files

Reading Files

- `readlines()` returns an array of the lines
- `read()` returns a string of the whole file
- Both of these require you to store whole file in memory, bad for big files
- Iteration to the rescue!

```
with open('foo.txt', 'r') as f:  
    for line in f:  
        #analyse line  
        # f is now at end of file , seek to restart
```

Writing Files

```
with open('foo.txt', 'w') as f:  
    f.write("Hello _there\n") # note the \n
```

Writing Files

```
with open('foo.txt', 'w') as f:  
    f.write("Hello_there\n") # note the \n
```

```
x = "foo" + str(100) + "bar_\n"  
f.write(x)
```


Demo

Demo Time!

Serialisation

- Sometimes you need to save your data (or send it).

Serialisation

- Sometimes you need to save your data (or send it).
- We have seen how to write to a file - great for numbers, text etc.
- What about more complicated objects?

Serialisation

- Sometimes you need to save your data (or send it).
- We have seen how to write to a file - great for numbers, text etc.
- What about more complicated objects?
- Python's pickle library lets you store your objects to disk

Pickle example

```
x = some_huge_data_structure()  
# Lets store it on disk  
pickle.dump(x, open('mySaveFile.pb', 'wb'))  
# ... some other script  
y = pickle.load(open('mySaveFile.pb', 'rb'))
```

Not enough time

- PyPDF2 is a comprehensive PDF python library
- Concatenate PDF files, create new ones etc.

Not enough time

- PyPDF2 is a comprehensive PDF python library
- Concatenate PDF files, create new ones etc.
- Demo time - splitter.py

OS

- The os library lets you interact with the file system.
- e.g. view the files in the current directory, sort by last time modified

OS

- The os library lets you interact with the file system.
- e.g. view the files in the current directory, sort by last time modified
- As always, the docs are the place to go - good detailed info on all the useful functions.

os - important methods

```
os.chdir(path) #change current directory  
os.listdir(path) # list files in path  
os.rename(src, dest) # rename file  
os.execv(path, args) # execute program at path  
os.tmpfile() # a temporary file
```

re

- Regular expressions (Regex) are one of the most powerful single tools in programming.

re

- Regular expressions (Regex) are one of the most powerful single tools in programming.
- Spend a few hours learning it, its worth it!
- Plenty of resources online, especially <http://www.regular-expressions.info/tutorial.html>
- Python library is called re

Command Line Arguments

- When you launch a program the OS hands it the arguments it was launched with.

Command Line Arguments

- When you launch a program the OS hands it the arguments it was launched with.
- e.g.

```
python test.py
```

Command Line Arguments

- When you launch a program the OS hands it the arguments it was launched with.
- e.g.

```
python test.py
```

- Access these using the sys module in Python

```
import sys  
sys.argv # list of arguments  
sys.argv[0] # name of current program
```

The argparse Library

- For robust argument handling use the argparse library.

The argparse Library

- For robust argument handling use the argparse library.
- e.g.

```
python test.py -f 20 --input-file demoFile.dat
```

The argparse Library

- For robust argument handling use the argparse library.
- e.g.

```
python test.py -f 20 --input-file demoFile.dat
```

- Arguments have long and short versions, can be optional, be entered with different orders etc.

Demo

Demo Time - todo generator