

Introduction to Python

Iterables, Iterators and Generators

13 November 2015

Examples 1

- We have already seen that loops in Python are pretty flexible:

Examples 1

- We have already seen that loops in Python are pretty flexible:

```
for i in [1,2,3]:  
    print i # prints elements  
for i in "123":  
    print i # prints characterwise
```

Examples 2

- We have already seen that loops in Python are pretty flexible (excuse lack of indentation):

```
for i in xrange(4):  
    print i #prints the range without storing  
for i in enumerate([1,2,3]):  
    print i # gives me indices as well as elements
```

Examples 2

- We have already seen that loops in Python are pretty flexible (excuse lack of indentation):

```
for i in xrange(4):  
    print i #prints the range without storing  
for i in enumerate([1,2,3]):  
    print i # gives me indices as well as elements
```

- Hopefully you see this and think how do I do that in my code!

Definition

- An **iterable** is any object that responds to the function `iter(obj)`

Definition

- An **iterable** is any object that responds to the function `iter(obj)`
- Python likes to hide this!

```
for i in x:  
    # Do loop stuff
```

- Call `iter(x)` and assign to some name that is never used in the code.

Definition

- An **iterable** is any object that responds to the function `iter(obj)`
- Python likes to hide this!

```
for i in x:  
    # Do loop stuff
```

- Call `iter(x)` and assign to some name that is never used in the code.
- `iter(x)` returns an object that can do one thing and one thing alone - respond to `__next__()`

Definition

- An **iterable** is any object that responds to the function `iter(obj)`
- Python likes to hide this!

```
for i in x:  
    # Do loop stuff
```

- Call `iter(x)` and assign to some name that is never used in the code.
- `iter(x)` returns an object that can do one thing and one thing alone - respond to `__next__()`
- Assign `i` to the response to `__next__()` each time round until it throws `StopIteration` exception (sort of an error) and then move on.

Definition

```
for i in x:  
    # Do loop stuff
```

- This is equivalent to:

```
randomName = iter(x)  
while(True):  
    try:  
        i = randomName.__next__()  
        # Do loop stuff  
    except StopIteration:  
        break
```

Uses for Iterables

- Iterables can be used all over the place!

```
new_list = list(iterable)
total = sum(iterable)
smallest = min(iterable)
largest = max(iterable)
combined = ''.join(iterable)
result = [f(x) for x in iterable]
```

Make your own iterables

- To make an object and iterable you only need to define the `__iter__()` hook.
- **Generators** are a great way to create your own iterables that are extremely flexible

Make your own iterables

- To make an object and iterable you only need to define the `__iter__()` hook.
- **Generators** are a great way to create your own iterables that are extremely flexible
- You define generators in a similar way to function but using the keyword **yield**

```
def myXRange(n):  
    i = 0  
    while( i < n):  
        yield i  
        i += 1
```

Make your own iterables

- To make an object and iterable you only need to define the `__iter__()` hook.
- **Generators** are a great way to create your own iterables that are extremely flexible
- You define generators in a similar way to function but using the keyword **yield**

```
def myXRange(n):  
    i = 0  
    while( i < n):  
        yield i  
        i += 1
```

- This responds to the *next* call by running until it hits `yield` and then stopping and waiting.

Make your own iterables

- To make an object and iterable you only need to define the `__iter__()` hook.
- **Generators** are a great way to create your own iterables that are extremely flexible
- You define generators in a similar way to function but using the keyword **yield**

```
def myXRange(n):  
    i = 0  
    while( i < n):  
        yield i  
        i += 1
```

- This responds to the *next* call by running until it hits `yield` and then stopping and waiting.
- Demo Time!

Make your own iterables 2

- No reason to make our iterable only finite!
- Lets have all of the positive even numbers

```
def evens():  
    i = 2  
    while True:  
        yield i  
        i += 2
```


Make your own iterables 2

- No reason to make our iterable only finite!
- Lets have all of the positive even numbers

```
def evens():  
    i = 2  
    while True:  
        yield i  
        i += 2
```

- Be careful when using these! Don't try to make a list out of this one...

Make your own iterables 3

- Perhaps most importantly, we can make iterables that depend on other iterables.

Make your own iterables 3

- Perhaps most importantly, we can make iterables that depend on other iterables.

```
def myEnumerate(iterable):  
    index = 0  
    for i in iterable:  
        yield (index,i)  
        index += 1
```

- Demo Time!

Fin

- Suggested watching: Loop Like A Native, Ned Batchelder
- Suggested Library: itertools (This probably has what you need!)