

# Docker & DevOps Basics

Containerizzazione e Deployment Moderno

15 novembre 2025



# Indice

<b>Prefazione</b>	<b>1</b>
<b>1 Introduzione ai Container</b>	<b>9</b>
1.1 Cos'è un Container?	9
1.1.1 Definizione	9
1.1.2 Caratteristiche principali	10
1.2 Container vs Macchine Virtuali	10
1.2.1 Architettura a confronto	10
1.2.2 Differenze chiave	10
1.2.3 Virtual Machines	10
1.2.4 Containers	11
1.3 Vantaggi della Containerizzazione	11
1.3.1 1. Portabilità e Consistenza	11
1.3.2 2. Microservizi e Scalabilità	12
1.3.3 3. DevOps e CI/CD	12
1.3.4 4. Efficienza delle Risorse	13
1.4 Architettura Docker	13
1.4.1 Componenti principali	13
1.4.2 Oggetti Docker	14
1.5 Tecnologie Sottostanti	15
1.5.1 Namespace Linux	15
1.5.2 Control Groups (cgroups)	15
1.5.3 Union File System	15
1.6 Storia ed Evoluzione	16
1.6.1 Timeline	16
1.6.2 Open Container Initiative (OCI)	16
1.7 Casi d'Uso	16
1.7.1 Quando usare i container	16
1.7.2 Esempi reali	17
<b>2 Docker Basics: Comandi Fondamentali</b>	<b>21</b>
2.1 Installazione Docker	21
2.1.1 Linux (Ubuntu/Debian)	21
2.1.2 macOS	22
2.1.3 Windows	22
2.2 Docker Run: Eseguire Container	23
2.2.1 Sintassi base	23
2.2.2 Primo container	23
2.2.3 Container interattivo	23
2.2.4 Container in background (detached)	24
2.2.5 Opzioni comuni di docker run	24

2.2.6	Esempi pratici	25
2.3	Docker PS: Ispezionare Container	25
2.3.1	Listare container in esecuzione	25
2.3.2	Listare tutti i container (anche fermati)	25
2.3.3	Formattazione output	26
2.3.4	Filtri	26
2.4	Docker Images: Gestire Immagini	26
2.4.1	Listare immagini locali	26
2.4.2	Cercare immagini su Docker Hub	26
2.4.3	Scaricare immagini (pull)	27
2.4.4	Rimuovere immagini	27
2.4.5	Ispezionare immagini	27
2.5	Gestione Ciclo di Vita Container	28
2.5.1	Stati del container	28
2.5.2	Stop e Start	28
2.5.3	Pause e Unpause	29
2.5.4	Rimuovere container	29
2.6	Logs e Debugging	29
2.6.1	Visualizzare log	29
2.6.2	Eseguire comandi in container running	29
2.6.3	Inspect: Informazioni dettagliate	30
2.6.4	Stats: Monitoraggio risorse	30
2.6.5	Events: Monitorare eventi Docker	31
2.7	Pulizia Risorse	31
2.7.1	Disk usage	31
2.7.2	Prune: Pulizia automatica	31
<b>3</b>	<b>Dockerfile: Creare Immagini Custom</b>	<b>35</b>
3.1	Cos'è un Dockerfile	35
3.1.1	Definizione	35
3.1.2	Struttura base	35
3.1.3	Build dell'immagine	36
3.2	Istruzioni Fondamentali	36
3.2.1	FROM: Immagine Base	36
3.2.2	RUN: Eseguire Comandi	36
3.2.3	COPY e ADD: Copiare File	37
3.2.4	CMD: Comando Predefinito	38
3.2.5	ENTRYPOINT: Punto di Ingresso	38
3.2.6	ENV: Variabili d'Ambiente	39
3.2.7	ARG: Argomenti di Build	39
3.2.8	WORKDIR: Directory di Lavoro	40
3.2.9	EXPOSE: Documentare Porte	40
3.2.10	VOLUME: Punti di Montaggio	40
3.2.11	USER: Cambiare Utente	40
3.2.12	LABEL: Metadati	41
3.3	Esempi Completi di Dockerfile	41
3.3.1	Applicazione Python Flask	41
3.3.2	Applicazione Node.js	42
3.3.3	Applicazione Go (Static Binary)	42
3.4	Multi-Stage Builds	43
3.4.1	Concetto	43
3.4.2	Esempio: Java Application	43

3.4.3	Esempio: React Frontend	44
3.4.4	Esempio: Python con compilazione C	45
3.5	Ottimizzazione e Best Practices	45
3.5.1	Layer Caching	45
3.5.2	Minimizzare Dimensioni Immagine	46
3.5.3	Sicurezza	46
3.5.4	File .dockerignore	47
<b>4</b>	<b>Docker Compose: Orchestrazione Multi-Container</b>	<b>51</b>
4.1	Cos'è Docker Compose	51
4.1.1	Definizione	51
4.1.2	Installazione	52
4.2	File docker-compose.yml	52
4.2.1	Struttura Base	52
4.2.2	Comandi Base	52
4.3	Definire Services	53
4.3.1	Build da Dockerfile	53
4.3.2	Usare Immagini Esistenti	53
4.3.3	Opzioni Comuni dei Services	54
4.4	Dipendenze tra Servizi	54
4.4.1	depends_on	54
4.4.2	Health Checks e Readiness	55
4.5	Networks	55
4.5.1	Network di Default	55
4.5.2	Networks Custom	55
4.5.3	Network Esistente	56
4.6	Volumes	56
4.6.1	Named Volumes	56
4.6.2	Bind Mounts	57
4.6.3	Opzioni Volumi Avanzate	57
4.7	Variabili d'Ambiente	57
4.7.1	File .env	57
4.7.2	env_file per Container	58
4.8	Esempi Completi	58
4.8.1	Stack LAMP (Linux, Apache, MySQL, PHP)	58
4.8.2	Stack MERN (MongoDB, Express, React, Node)	59
4.8.3	Stack Microservizi con Nginx Reverse Proxy	61
4.8.4	Monitoring Stack (Prometheus + Grafana)	63
4.9	Comandi Avanzati	64
4.9.1	Override Files	64
4.9.2	Scale Services	64
4.9.3	Logs e Monitoring	65
<b>5</b>	<b>Networking e Volumes</b>	<b>69</b>
5.1	Docker Networking	69
5.1.1	Concetti Fondamentali	69
5.1.2	Comandi Base	69
5.2	Bridge Network	70
5.2.1	Default Bridge	70
5.2.2	User-Defined Bridge	71
5.2.3	Configurazione Bridge Avanzata	71
5.3	Host Network	72

5.4	Overlay Network	72
5.5	None Network	73
5.6	Port Mapping	73
5.6.1	Pubblicare Porte	73
5.6.2	Port Binding vs Expose	74
5.7	Service Discovery	74
5.7.1	DNS Automatico	74
5.7.2	Network Aliases	74
5.8	Isolamento e Sicurezza	75
5.8.1	Reti Multiple	75
5.8.2	Firewall e IPTables	75
5.9	Docker Volumes	76
5.9.1	Tipi di Persistenza	76
5.9.2	Named Volumes	76
5.9.3	Bind Mounts	77
5.9.4	tmpfs Mounts	77
5.10	Gestione Avanzata Volumi	78
5.10.1	Volume Drivers	78
5.10.2	Backup e Restore	78
5.10.3	Condivisione Volumi tra Container	79
5.10.4	Volumes from Container	79
5.11	Esempi Pratici	79
5.11.1	Database con Persistenza	79
5.11.2	Sviluppo con Hot Reload	80
5.11.3	Multi-Tier App Networking	80
<b>6</b>	<b>Docker Registry e Hub</b>	<b>85</b>
6.1	Docker Hub	85
6.1.1	Cos'è Docker Hub	85
6.1.2	Account e Login	86
6.1.3	Pull Immagini	86
6.1.4	Push Immagini	86
6.1.5	Repository Pubblici vs Privati	86
6.2	Tagging e Versioning	87
6.2.1	Strategie di Tag	87
6.2.2	Esempio Completo Tagging	87
6.2.3	Tag Immutabili	88
6.3	Registry Privati	88
6.3.1	Docker Registry (Open Source)	88
6.3.2	Registry con HTTPS e Autenticazione	88
6.3.3	Docker Compose per Registry	89
6.4	Harbor: Enterprise Registry	90
6.4.1	Cos'è Harbor	90
6.4.2	Installazione Harbor	90
6.4.3	Usare Harbor	91
6.5	Cloud Registry	91
6.5.1	AWS Elastic Container Registry (ECR)	91
6.5.2	Google Container Registry (GCR)	91
6.5.3	Azure Container Registry (ACR)	92
6.5.4	Confronto Cloud Registry	92
6.6	CI/CD Integration	92
6.6.1	GitHub Actions	92

6.6.2	GitLab CI/CD	93
6.6.3	Jenkins Pipeline	94
6.7	Security e Best Practices	95
6.7.1	Image Scanning	95
6.7.2	Content Trust	95
6.7.3	Image Signing con Cosign	95
6.7.4	Best Practices	96
6.8	Gestione Registry Avanzata	96
6.8.1	Garbage Collection	96
6.8.2	Replication	96
6.8.3	Webhook Notifications	97
6.9	Caso di Studio: Production Registry	97
<b>7</b>	<b>Deployment e Orchestrazione</b>	<b>101</b>
7.1	Introduzione	101
7.2	Obiettivi di Apprendimento	101
7.3	Strategie di Deployment	101
7.3.1	Deployment Patterns	101
7.3.2	Blue-Green Deployment	102
7.3.3	Canary Deployment	103
7.4	Docker Swarm	105
7.4.1	Inizializzazione Cluster	105
7.4.2	Deploy Stack con Docker Swarm	105
7.5	Kubernetes Fundamentals	108
7.5.1	Architettura Kubernetes	108
7.5.2	Deployment Completo Kubernetes	108
7.5.3	Gestione Secrets Kubernetes	112
7.6	Load Balancing e Service Discovery	112
7.6.1	Kubernetes Services	112
7.7	Advanced Health Checks	114
7.7.1	Multi-Level Health Checks	114
7.8	Deployment Automation	115
7.8.1	GitOps con ArgoCD	115
7.9	Best Practice Deployment	116
7.10	Errori Comuni	116
7.11	Riepilogo	116
7.12	Riferimenti	116
<b>8</b>	<b>CI/CD con Docker</b>	<b>119</b>
8.1	Introduzione	119
8.2	Obiettivi di Apprendimento	119
8.3	CI/CD Pipeline Architecture	119
8.4	GitHub Actions Complete Workflow	120
8.4.1	Multi-Stage CI/CD Pipeline	120
8.5	GitLab CI Complete Pipeline	126
8.5.1	GitLab CI/CD Configuration	126
8.6	Docker Build Optimization	131
8.6.1	Multi-Stage Dockerfile Optimized	131
8.7	Test Automation	133
8.7.1	Docker Compose for Testing	133
8.8	Container Registry Management	133
8.8.1	Multi-Registry Push	133

8.9	Advanced CI/CD Patterns . . . . .	134
8.9.1	Matrix Testing Strategy . . . . .	134
8.10	Secrets Management in CI/CD . . . . .	135
8.10.1	Vault Integration . . . . .	135
8.11	Best Practices CI/CD . . . . .	136
8.12	Errori Comuni . . . . .	136
8.13	Riepilogo . . . . .	136
8.14	Riferimenti . . . . .	136
<b>9</b>	<b>Monitoring e Logging</b>	<b>139</b>
9.1	Introduzione . . . . .	139
9.2	Obiettivi di Apprendimento . . . . .	139
9.3	Docker Logs Fundamentals . . . . .	139
9.3.1	Docker Logging Drivers . . . . .	139
9.4	Centralized Logging con ELK Stack . . . . .	140
9.4.1	ELK Stack Setup Completo . . . . .	140
9.4.2	Logstash Pipeline Configuration . . . . .	142
9.4.3	Filebeat Configuration . . . . .	144
9.5	Grafana Loki - Lightweight Logging . . . . .	144
9.5.1	Loki Stack Setup . . . . .	144
9.5.2	Promtail Configuration . . . . .	145
9.6	Prometheus Metrics Collection . . . . .	146
9.6.1	Prometheus Stack . . . . .	146
9.6.2	Prometheus Configuration . . . . .	148
9.6.3	Application Metrics in Go . . . . .	149
9.7	Alert Rules . . . . .	151
9.7.1	Prometheus Alert Rules . . . . .	151
9.7.2	Alertmanager Configuration . . . . .	153
9.8	Distributed Tracing . . . . .	155
9.8.1	Jaeger Tracing Setup . . . . .	155
9.9	Structured Logging Best Practices . . . . .	155
9.9.1	Structured Logging Example . . . . .	155
9.10	Best Practices . . . . .	156
9.11	Riepilogo . . . . .	157
9.12	Riferimenti . . . . .	157
<b>10</b>	<b>Best Practices e Security</b>	<b>159</b>
10.1	Introduzione . . . . .	159
10.2	Obiettivi di Apprendimento . . . . .	159
10.3	Dockerfile Optimization . . . . .	159
10.3.1	Esempio: Before vs After Optimization . . . . .	159
10.3.2	Layer Caching Optimization . . . . .	161
10.3.3	BuildKit Advanced Features . . . . .	161
10.4	.dockerignore Best Practices . . . . .	162
10.4.1	Comprehensive .dockerignore . . . . .	162
10.5	Security Hardening . . . . .	164
10.5.1	Non-Root User . . . . .	164
10.5.2	Read-Only Root Filesystem . . . . .	165
10.5.3	Security Scanning . . . . .	166
10.6	Network Security . . . . .	167
10.6.1	Network Isolation . . . . .	167
10.6.2	Kubernetes Network Policies . . . . .	168



10.7	Resource Limits	169
10.7.1	Docker Resource Constraints	169
10.8	Secrets Management	170
10.8.1	Docker Secrets (Swarm)	170
10.8.2	Kubernetes Secrets	171
10.8.3	External Secrets Operator	171
10.9	Image Signing and Verification	172
10.9.1	Cosign - Image Signing	172
10.10	Production Deployment Checklist	173
10.11	Common Security Anti-Patterns	174
10.12	Performance Optimization	175
10.12.1	Image Size Reduction	175
10.13	Errori Comuni	175
10.14	Riepilogo	175
10.15	Riferimenti	175
<b>A</b>	<b>Appendice: Cheat Sheet Comandi Docker</b>	<b>177</b>
A.1	Container Management	177
A.1.1	Lifecycle Commands	177
A.1.2	Inspection & Monitoring	177
A.1.3	Advanced Container Operations	178
A.2	Image Management	178
A.2.1	Image Operations	178
A.2.2	Build Commands	179
A.3	Volume Management	180
A.3.1	Volume Commands	180
A.4	Network Management	180
A.4.1	Network Commands	180
A.5	Docker Compose	181
A.5.1	Compose Commands	181
A.6	Docker Swarm	182
A.6.1	Swarm Management	182
A.7	Registry & Authentication	183
A.7.1	Registry Commands	183
A.8	System Management	183
A.8.1	System Commands	183
A.9	Security & Scanning	184
A.9.1	Security Commands	184
A.10	Advanced Debugging	184
A.10.1	Debugging Commands	184
A.11	Context & Remote Docker	185
A.11.1	Context Management	185
A.12	BuildKit Advanced	186
A.12.1	BuildKit Commands	186
A.13	Performance & Optimization	186
A.13.1	Performance Commands	186
A.14	Useful One-Liners	187
A.14.1	Cheat Sheet One-Liners	187
A.15	Environment Variables	188
A.15.1	Useful Docker Environment Variables	188
A.16	Quick Reference Tables	189
A.16.1	Common Flags	189

A.16.2 Restart Policies . . . . .	189
A.16.3 Network Drivers . . . . .	189
A.17 Riferimenti Rapidi . . . . .	189
<b>B Appendice: Progetti Completi</b>	<b>191</b>
B.1 Introduzione . . . . .	191
B.2 Progetto 1: Full-Stack MERN Application . . . . .	191
B.2.1 Architettura . . . . .	191
B.2.2 Directory Structure . . . . .	192
B.2.3 Frontend Dockerfile . . . . .	192
B.2.4 Backend Dockerfile . . . . .	193
B.2.5 Docker Compose - Development . . . . .	194
B.2.6 Docker Compose - Production . . . . .	196
B.2.7 Nginx Configuration . . . . .	198
B.2.8 GitHub Actions CI/CD . . . . .	199
B.3 Progetto 2: Microservices Architecture . . . . .	202
B.3.1 Architettura Microservices . . . . .	202
B.3.2 Microservices Docker Compose . . . . .	202
B.4 Progetto 3: WordPress Production . . . . .	205
B.4.1 WordPress Stack . . . . .	205
B.5 Progetto 4: Data Pipeline con Airflow . . . . .	207
B.5.1 Apache Airflow Stack . . . . .	207
B.6 Esercizi Pratici . . . . .	209
B.6.1 Esercizio 1: Multi-Stage Build Optimization . . . . .	209
B.6.2 Esercizio 2: Zero-Downtime Deployment . . . . .	210
B.6.3 Esercizio 3: Complete Observability . . . . .	210
B.6.4 Esercizio 4: Security Hardening . . . . .	210
B.7 Progetti Challenge . . . . .	211
B.7.1 Challenge 1: Production-Ready E-Commerce . . . . .	211
B.7.2 Challenge 2: Scalable Chat Application . . . . .	211
B.8 Soluzioni e Best Practices . . . . .	211
B.8.1 Deployment Strategy Decision Matrix . . . . .	211
B.8.2 Resource Sizing Guide . . . . .	212
B.9 Riferimenti . . . . .	212

# Prefazione

## A chi si rivolge questo manuale

Questi appunti sono stati pensati per studenti di istituti tecnici e professionali, sviluppatori e sistemisti che vogliono apprendere le tecnologie di containerizzazione e DevOps moderne. Il percorso è strutturato per accompagnare progressivamente dalla teoria ai container fino alla gestione di infrastrutture complesse con Docker e strumenti DevOps.

## Struttura del corso

Il corso è organizzato in 7 capitoli che coprono l'intero ecosistema Docker e le pratiche DevOps:

### **Parte I - Fondamenti Container** (Capitoli 1-2)

- Introduzione ai container e differenze con le macchine virtuali
- Architettura Docker e componenti fondamentali
- Comandi base per gestire container e immagini
- Ciclo di vita di un container

### **Parte II - Creazione Immagini** (Capitolo 3)

- Dockerfile: sintassi e istruzioni principali
- Best practices per immagini efficienti
- Multi-stage builds per ottimizzazione
- Layer caching e strategie di build

### **Parte III - Orchestrazione e Networking** (Capitoli 4-5)

- Docker Compose per applicazioni multi-container
- Networking: bridge, host, overlay
- Gestione volumi e persistenza dati
- Service discovery e load balancing

### **Parte IV - Distribuzione** (Capitolo 6)

- Docker Hub e registry pubblici
- Registry privati e sicurezza
- CI/CD con Docker
- Strategie di deployment

## Prerequisiti

Per affrontare questo corso è consigliabile avere:

- Conoscenze base di Linux e comandi shell
- Familiarità con networking (IP, porte, protocolli)
- Conoscenza di almeno un linguaggio di programmazione
- Comprensione dei concetti di client-server
- (Opzionale) Esperienza con macchine virtuali

## Strumenti necessari

**Software consigliato:**

- **Docker Engine:** Runtime per container Linux/Windows
- **Docker Desktop:** Applicazione GUI per macOS/Windows
- **Docker Compose:** Orchestrazione multi-container
- **Visual Studio Code:** Editor con estensioni Docker
- **Portainer:** Interfaccia web per gestione Docker

**Ambienti di sviluppo:**

- **Linux:** Ubuntu 20.04+, Debian, CentOS, Fedora
- **Windows:** Windows 10/11 Pro con WSL2
- **macOS:** macOS 10.15+ con Docker Desktop
- **Cloud:** AWS, Azure, Google Cloud (livello free tier)

**Tool aggiuntivi:**

- **Git:** Versioning del codice e Dockerfile
- **curl/wget:** Testing API e download
- **jq:** Parsing JSON per inspect e API
- **dive:** Analisi layer immagini Docker

## Come studiare

Per ottenere il massimo da questi appunti:

1. **Installa Docker:** Configura l'ambiente sul tuo sistema
2. **Digita i comandi:** Non copiare/incollare, scrivi manualmente
3. **Sperimenta:** Modifica i Dockerfile e osserva i risultati
4. **Leggi i log:** Impara a debuggare container in errore

5. **Costruisci progetti:** Containerizza applicazioni reali
6. **Studia i layer:** Usa `docker history` e `docker inspect`
7. **Pratica networking:** Testa comunicazione tra container
8. **Ottimizza:** Riduci dimensioni immagini e tempi di build

#### Nota

Questo manuale usa **Docker Engine 20.10+** e **Docker Compose V2**. La maggior parte dei comandi funziona anche su versioni precedenti, ma alcune funzionalità avanzate richiedono versioni recenti.

## Convenzioni tipografiche

Nel testo vengono utilizzate le seguenti convenzioni:

- **Comandi shell:** Comando da eseguire in terminale
- **Parole chiave:** Concetti importanti (container, image, volume)
- *Nomi di file/path:* Riferimenti a file (Dockerfile, `/var/lib/docker`)
- **Box colorati:** Note, Attenzioni, Best Practices, Errori Comuni
- **Diagrammi:** Architetture e flussi con TikZ

#### Formato comandi:

```
1 # Commento esplicativo
2 $ docker comando [OPZIONI] ARGOMENTO
```

#### Output esempio:

CONTAINER ID	IMAGE	COMMAND	STATUS
a1b2c3d4e5f6	nginx	...	Up 2 hours

## Architettura del manuale

#### Struttura di ogni capitolo:

1. **Obiettivi:** Cosa imparerai
2. **Teoria:** Concetti fondamentali
3. **Pratica:** Esempi completi commentati
4. **Diagrammi:** Visualizzazione architetture
5. **Best Practices:** Consigli professionali
6. **Errori Comuni:** Problemi da evitare
7. **Debugging:** Troubleshooting e log analysis
8. **Esercizi:** Sfide pratiche graduate
9. **Caso di Studio:** Progetto completo
10. **Riepilogo:** Riassunto concetti chiave
11. **Riferimenti:** Documentazione ufficiale

## Laboratorio pratico

Durante il corso costruirai:

- **Web app multi-tier:** Frontend + Backend + Database
- **Microservizi:** Architettura distribuita con API
- **CI/CD Pipeline:** Build automatizzata e deployment
- **Monitoring stack:** Prometheus + Grafana
- **Reverse proxy:** Nginx per load balancing

## Certificazioni

Questo corso prepara per:

- **Docker Certified Associate (DCA)**
- **Kubernetes fundamentals** (passo successivo naturale)
- **Linux Foundation certifications** (DevOps track)

## Sito web e risorse

Materiale aggiuntivo disponibile su:

- Repository GitHub: <https://github.com/campionluca/Appunti>
- Dockerfile di esempio scaricabili
- Docker Compose templates per progetti comuni
- Script di automazione e best practices
- Video tutorial e screencast
- Community Discord per supporto

## Filosofia DevOps

Docker è uno strumento fondamentale nella cultura DevOps:

### Principi DevOps

- **Automation:** Automatizza build, test, deployment
- **CI/CD:** Integrazione e consegna continue
- **Infrastructure as Code:** Infrastruttura versionata
- **Monitoring:** Osservabilità e metriche
- **Collaboration:** Dev e Ops lavorano insieme
- **Feedback rapido:** Cicli brevi di sviluppo

## Container nel mondo reale

Docker è utilizzato da:

- **Startup:** Deployment rapido e scalabile
- **Enterprise:** Modernizzazione applicazioni legacy
- **Cloud providers:** AWS ECS/Fargate, Azure ACI, GCP Cloud Run
- **Kubernetes:** Orchestrazione container in produzione
- **Sviluppatori:** Ambienti consistenti dev/staging/prod

## Roadmap di apprendimento

Percorso consigliato:

1. **Settimana 1-2:** Capitoli 1-2 (fondamenti e comandi base)
2. **Settimana 3-4:** Capitolo 3 (Dockerfile e build)
3. **Settimana 5-6:** Capitolo 4 (Docker Compose)
4. **Settimana 7-8:** Capitolo 5 (networking e volumes)
5. **Settimana 9-10:** Capitolo 6 (registry e deployment)
6. **Settimana 11-12:** Progetto finale completo

## Progetto finale

Al termine del corso sarai in grado di:

- Containerizzare qualsiasi applicazione
- Creare Dockerfile ottimizzati e sicuri
- Orchestrare stack multi-container con Compose
- Configurare reti e volumi persistenti
- Distribuire su registry pubblici e privati
- Implementare CI/CD con GitHub Actions + Docker
- Debuggare problemi di container in produzione

## Community e supporto

Dove trovare aiuto:

- **Docker Forums:** <https://forums.docker.com>
- **Stack Overflow:** Tag [docker] e [dockerfile]
- **Docker Community Slack:** Chat in tempo reale
- **Reddit:** r/docker per discussioni e best practices
- **GitHub Issues:** Report bug e feature requests

## Sicurezza

### Attenzione

La sicurezza dei container è fondamentale:

- Non eseguire container come root se evitabile
- Scansiona immagini per vulnerabilità (Trivy, Snyk)
- Usa immagini ufficiali da registry fidati
- Aggiorna regolarmente base images
- Limita risorse CPU/RAM per prevenire DoS
- Usa secrets manager per credenziali sensibili

## Ringraziamenti

Si ringrazia:

- Docker Inc. per l'eccellente documentazione ufficiale
- La community open source per contributi e feedback
- L'Istituto Tecnico Antonio Scarpa per il supporto
- Gli studenti che hanno testato e migliorato questi materiali

*Prof. Luca Campion*  
Novembre 2025

## Note sulla versione

**Versione 1.0** - Novembre 2025

- Prima release completa
- 7 capitoli + esempi pratici
- Coverage Docker: Engine, Compose, Networking, Registry
- Esempi testati su Docker 20.10+
- Diagrammi architettura con TikZ
- 100+ esempi di codice funzionanti
- Casi di studio reali da produzione

**Prossimi aggiornamenti:**

- Kubernetes fundamentals (orchestrazione avanzata)
- Docker Swarm per clustering



- Security scanning e hardening
- Monitoring con Prometheus/Grafana
- Service mesh con Istio

## Feedback

Questo manuale è in continua evoluzione. Invia suggerimenti, correzioni o richieste a:

- Email: `luca.campion@example.com`
- GitHub Issues: <https://github.com/campionluca/Appunti/issues>
- Pull Requests benvenute!

## Licenza

Questo materiale è distribuito con licenza Creative Commons BY-NC-SA 4.0:

- **BY**: Attribuzione obbligatoria
- **NC**: Uso non commerciale
- **SA**: Condivisione con stessa licenza

*"Containers are the future of software deployment"*  
– **Solomon Hykes, Docker Founder**



# Capitolo 1

## Introduzione ai Container

### Introduzione

I container rappresentano una rivoluzione nel modo in cui sviluppiamo, distribuiamo ed eseguiamo applicazioni. Questo capitolo introduce i concetti fondamentali della containerizzazione, le differenze con le macchine virtuali tradizionali e l'architettura di Docker.

### Obiettivi di apprendimento

- Comprendere cosa sono i container e come funzionano
- Confrontare container e macchine virtuali
- Conoscere i vantaggi della containerizzazione
- Capire l'architettura di Docker e i suoi componenti
- Identificare i casi d'uso appropriati per i container

### 1.1 Cos'è un Container?

#### 1.1.1 Definizione

Un **container** è un'unità software standardizzata che impacchetta il codice e tutte le sue dipendenze in modo che l'applicazione possa essere eseguita in modo rapido e affidabile da un ambiente di computing a un altro.

#### Analogia: Container di Spedizione

Come i container di spedizione standardizzano il trasporto merci, i container software standardizzano il deployment di applicazioni:

- **Dimensioni standard:** Formato uniforme e prevedibile
- **Portabilità:** Si spostano facilmente tra navi, treni, camion
- **Isolamento:** Il contenuto è separato dall'esterno
- **Efficienza:** Caricamento/scaricamento ottimizzato

### 1.1.2 Caratteristiche principali

1. **Isolamento:** Ogni container ha il proprio filesystem, processi, networking
2. **Portabilità:** "Build once, run anywhere" - funziona su qualsiasi sistema
3. **Leggerezza:** Condivide il kernel dell'host, avvio in secondi
4. **Immutabilità:** L'immagine non cambia, deployment consistenti
5. **Scalabilità:** Facilmente replicabile per gestire carico

## 1.2 Container vs Machine Virtuali

### 1.2.1 Architettura a confronto




Figura 1.1: Architettura: Virtual Machines vs Containers

### 1.2.2 Differenze chiave

Caratteristica	Virtual Machine	Container
Dimensione	GB (include intero OS)	MB (solo app + dipendenze)
Avvio	Minuti	Secondi
Performance	Overhead hypervisor	Quasi native
Isolamento	Completo (hardware)	A livello processo
Portabilità	Limitata (formato VM)	Eccellente (standard OCI)
Densità	Decine per host	Centinaia per host

Tabella 1.1: Confronto VM vs Container

### 1.2.3 Virtual Machines

**Vantaggi:**

- Isolamento completo a livello hardware
- Esecuzione di OS diversi sullo stesso host
- Sicurezza superiore (separazione hypervisor)

- Supporto per applicazioni legacy

**Svantaggi:**

- Overhead significativo (ogni VM ha un OS completo)
- Avvio lento (boot del sistema operativo)
- Consumo elevato di risorse (RAM, CPU, disco)
- Portabilità limitata tra hypervisor diversi

### 1.2.4 Containers

**Vantaggi:**

- Leggerezza: condividono il kernel dell'host
- Avvio istantaneo (secondi)
- Alta densità: centinaia di container per server
- Portabilità: funzionano ovunque ci sia Docker
- Efficienza: minor spreco di risorse
- CI/CD: integrazione perfetta in pipeline DevOps

**Svantaggi:**

- Isolamento meno robusto delle VM
- Stesso kernel dell'host (no OS diversi)
- Sicurezza: vulnerabilità kernel colpisce tutti i container
- Non adatti per applicazioni che richiedono kernel diverso

**Nota**

Container e VM non sono mutualmente esclusivi. Molte architetture moderne usano **container dentro VM**: le VM forniscono isolamento hardware, i container portano portabilità e densità.

## 1.3 Vantaggi della Containerizzazione

### 1.3.1 1. Portabilità e Consistenza

**Problema: "Works on my machine"****Scenario tradizionale:**

- Sviluppo su macOS
- Staging su Ubuntu 20.04
- Produzione su CentOS 8
- Risultato: bug dipendenti dall'ambiente

**Soluzione con container:**

- Immagine Docker identica ovunque
- Stesso runtime, librerie, dipendenze
- Risultato: comportamento prevedibile

### 1.3.2 2. Microservizi e Scalabilità

I container sono ideali per architetture a microservizi:

- **Isolamento:** Ogni servizio in un container separato
- **Scalabilità indipendente:** Scala solo i servizi sotto carico
- **Deployment incrementale:** Aggiorna un servizio alla volta
- **Resilienza:** Fallimento di un container non compromette il sistema

Listing 1.1: Esempio: Stack microservizi

```
1 # Frontend
2 Container 1: React app (3 repliche)
3
4 # Backend API
5 Container 2: Node.js API (5 repliche)
6 Container 3: Python ML service (2 repliche)
7
8 # Database
9 Container 4: PostgreSQL (1 replica master)
10 Container 5: Redis cache (2 repliche)
```

### 1.3.3 3. DevOps e CI/CD

I container accelerano il ciclo di sviluppo:

1. **Sviluppo:** Ambiente identico per tutti i developer
2. **Testing:** Test automatici in container isolati
3. **Build:** Immagine Docker come artifact immutabile
4. **Deployment:** Push immagine su registry, pull in produzione
5. **Rollback:** Ritorna alla versione precedente in secondi




Figura 1.2: Pipeline CI/CD con Docker

Metrica	VM	Container	Risparmio
Memoria per istanza	2 GB	100 MB	95%
Tempo avvio	60 sec	2 sec	97%
Istanze per server	10	100	10x
Costo cloud mensile	\$500	\$50	90%

Tabella 1.2: Confronto efficienza risorse (valori medi)




Figura 1.3: Architettura Docker

#### 1.3.4 4. Efficienza delle Risorse

### 1.4 Architettura Docker

#### 1.4.1 Componenti principali

##### Docker Client

Interfaccia utente per interagire con Docker:

- Comando **docker**: CLI principale
- Invia comandi al Docker Daemon via REST API
- Può connettersi a daemon remoti

```

1 # Esempi di comandi client
2 $ docker run nginx
3 $ docker ps
4 $ docker build -t myapp .
5 $ docker push myapp:latest
  
```

##### Docker Daemon (dockerd)

Il cuore di Docker che gestisce:

- Building, running, distributing container
- Gestione immagini, container, reti, volumi
- Comunicazione con registry per push/pull
- Esposizione REST API per client

## Docker Registry

Repository per immagini Docker:

- **Docker Hub:** Registry pubblico ufficiale
- **Registry privati:** Harbor, Artifactory, AWS ECR, GCP GCR
- **Self-hosted:** Registry Docker open source

### 1.4.2 Oggetti Docker

#### Immagini

Template **read-only** per creare container:

- File system stratificato (layers)
- Definite da un Dockerfile
- Versionabili con tags (latest, v1.0, stable)
- Riutilizzabili e componibili

Listing 1.2: Struttura immagine a layer

1	Layer 5: App code (Python)	10 MB
2	Layer 4: pip install requirements	50 MB
3	Layer 3: Python 3.9	100 MB
4	Layer 2: OS libraries (Ubuntu)	30 MB
5	Layer 1: Base layer	5 MB
6	-----	
7	Total:	195 MB

#### Container

Istanza **eseguibile** di un'immagine:

- Processo isolato con proprio filesystem
- Layer writable sopra l'immagine
- Effimero: può essere fermato, rimosso, ricreato
- Configurabile: variabili ambiente, porte, volumi

#### Volumi

Persistenza dati al di fuori del container:

- Sopravvivono alla cancellazione del container
- Condivisibili tra più container
- Gestiti da Docker (ottimizzazione I/O)



## Reti

Comunicazione tra container e verso l'esterno:

- **Bridge**: Rete privata isolata (default)
- **Host**: Usa network stack dell'host
- **Overlay**: Multi-host networking (Swarm/Kubernetes)
- **None**: Nessun networking

## 1.5 Tecnologie Sottostanti

### 1.5.1 Namespace Linux

Isolamento delle risorse del sistema:

- **PID**: Albero processi isolato
- **Network**: Stack di rete separato
- **Mount**: Filesystem isolato
- **UTS**: Hostname e domain name
- **IPC**: Inter-process communication
- **User**: Mapping UID/GID

### 1.5.2 Control Groups (cgroups)

Limitazione e accounting delle risorse:

- **CPU**: Limiti di utilizzo processore
- **Memoria**: Limiti RAM e swap
- **I/O**: Bandwidth disco
- **Network**: Bandwidth rete

Listing 1.3: Esempio: Limitare risorse container

```
1 # Limita a 1 CPU e 512 MB RAM
2 $ docker run --cpus="1.0" --memory="512m" nginx
```

### 1.5.3 Union File System

Filesystem stratificato:

- **OverlayFS**: Default su Linux moderno
- **AUFS**: Legacy Ubuntu
- **Btrfs/ZFS**: COW filesystem avanzati

**Vantaggi:**

- Condivisione layer tra immagini (risparmio spazio)
- Build veloce (caching layer)
- Pull efficiente (solo layer mancanti)

## 1.6 Storia ed Evoluzione

### 1.6.1 Timeline

- **1979:** chroot (primi concetti di isolamento)
- **2000:** FreeBSD Jails
- **2005:** OpenVZ, Solaris Zones
- **2008:** LXC (Linux Containers)
- **2013:** Docker Inc. lancia Docker
- **2014:** Kubernetes (orchestrazione Google)
- **2015:** Docker Compose
- **2017:** Docker Swarm mode
- **2020:** Docker supporta Windows containers
- **2021:** containerd diventa CNCF graduated project

### 1.6.2 Open Container Initiative (OCI)

Standardizzazione del formato container:

- **Image spec:** Formato immagine universale
- **Runtime spec:** Specifiche esecuzione container
- **Distribution spec:** Distribuzione via registry

**Implementazioni OCI:**

- Docker
- containerd
- CRI-O (Kubernetes)
- Podman (Red Hat)

## 1.7 Casi d'Uso

### 1.7.1 Quando usare i container

**Ideali per:**

- Microservizi e API stateless
- Applicazioni web moderne (MERN, LAMP, MEAN)
- CI/CD e ambienti di sviluppo
- Batch processing e job worker
- Funzioni serverless (AWS Lambda usa container)

**Non ideali per:**

- Applicazioni GUI desktop
- Kernel modules e driver
- Applicazioni che richiedono hardware specifico
- Database con I/O intensivo (meglio VM o bare metal)

### 1.7.2 Esempi reali

#### Caso 1: E-commerce Platform

##### Architettura:

- 10 container frontend (React)
- 20 container backend (Node.js API)
- 5 container cart service (Python)
- 3 container payment gateway
- 2 database (PostgreSQL + Redis)

##### Risultati:

- Deploy 50 volte al giorno (vs 1 volta/settimana)
- Downtime ridotto 99%
- Costi cloud -60%

#### Caso 2: Machine Learning Pipeline

##### Setup:

- Container data ingestion (Kafka)
- Container preprocessing (Spark)
- Container training (TensorFlow GPU)
- Container model serving (Flask API)

##### Vantaggi:

- Riproducibilità esperimenti
- Scalabilità training parallelizzato
- Deployment modelli senza downtime

## Best Practices

### Best Practices Iniziali

1. **Un processo per container:** Non usare supervisord/systemd
2. **Immutabilità:** Mai modificare container in esecuzione
3. **Stateless:** Stato persistente su volumi esterni
4. **Logging:** Output su stdout/stderr, non file
5. **Configurazione:** Usa variabili ambiente, non file config
6. **Sicurezza:** Non eseguire come root se evitabile

## Errori Comuni

### Attenzione

#### Errori da evitare:

- Trattare container come VM (ssh, multiple process)
- Salvare dati importanti nel container filesystem
- Immagini enormi (GB) con software inutile
- Eseguire tutto come root
- Hardcodare configurazione nel Dockerfile
- Non versionare immagini (usare sempre tags)

## Esercizi

1. Disegna un diagramma che confronta l'architettura di VM e container, evidenziando le differenze di layer.
2. Spiega con un esempio concreto come i container risolvono il problema "works on my machine".
3. Identifica 3 applicazioni nella tua scuola/azienda che potrebbero beneficiare della containerizzazione. Motiva la scelta.
4. Calcola il risparmio teorico: hai 50 applicazioni che richiedono 1GB RAM ciascuna. Confronta il costo di:
  - VM (overhead 2GB per VM)
  - Container (overhead 100MB per container)
5. Ricerca: trova 3 aziende famose che usano Docker in produzione e scopri come lo utilizzano.

## Quiz di Verifica

1. **Vero/Falso:** I container condividono il kernel dell'host.

2. **Vero/Falso:** Un container può eseguire Windows su un host Linux.
3. Quale componente Docker gestisce la comunicazione tra client e daemon?
  - a) Registry
  - b) REST API
  - c) Dockerfile
  - d) Namespace
4. Qual è il vantaggio principale dei layer nelle immagini Docker?
5. Quando preferiresti una VM a un container?

## Riepilogo Concetti Chiave

### Concetti Fondamentali

- I **container** sono unità software leggere e portabili
- **Vantaggi vs VM:** Più leggeri, avvio rapido, alta densità
- **Docker** è la piattaforma leader per containerizzazione
- **Architettura:** Client, Daemon, Registry, Objects
- **Tecnologie:** Namespace, cgroups, Union FS
- **Portabilità:** Build once, run anywhere
- **DevOps:** CI/CD, microservizi, scalabilità

## Prossimi Passi

Nel prossimo capitolo esploreremo:

- Installazione Docker su diversi sistemi operativi
- Comandi base: run, ps, images, stop, rm
- Gestione del ciclo di vita dei container
- Debugging e troubleshooting

## Riferimenti

- Docker Official Docs: <https://docs.docker.com>
- OCI Specifications: <https://opencontainers.org>
- Linux Namespaces: <https://man7.org/linux/man-pages/man7/namespaces.7.html>
- cgroups: <https://www.kernel.org/doc/Documentation/cgroup-v2.txt>
- Docker Blog: <https://www.docker.com/blog>
- CNCF: <https://www.cncf.io>



## Capitolo 2

# Docker Basics: Comandi Fondamentali

### Introduzione

Questo capitolo copre i comandi essenziali di Docker per gestire container e immagini. Imparerai a installare Docker, eseguire container, gestire il loro ciclo di vita e risolvere i problemi più comuni.

### Obiettivi di apprendimento

- Installare Docker su Linux, macOS e Windows
- Eseguire container con `docker run`
- Ispezionare container e immagini
- Gestire il ciclo di vita dei container
- Visualizzare log e debuggare problemi
- Pulire risorse inutilizzate

## 2.1 Installazione Docker

### 2.1.1 Linux (Ubuntu/Debian)

Listing 2.1: Installazione su Ubuntu 20.04+

```
1 # Aggiorna repository
2 $ sudo apt-get update
3
4 # Installa dipendenze
5 $ sudo apt-get install ca-certificates curl gnupg lsb-release
6
7 # Aggiungi GPG key ufficiale Docker
8 $ curl -fsSL https://download.docker.com/linux/ubuntu/gpg | \
9     sudo gpg --dearmor -o /usr/share/keyrings/docker-archive-keyring.gpg
10
11 # Configura repository
12 $ echo \
13     "deb [arch=$(dpkg --print-architecture) \
14     signed-by=/usr/share/keyrings/docker-archive-keyring.gpg] \
15     https://download.docker.com/linux/ubuntu \
16     $(lsb_release -cs) stable" | \
17     sudo tee /etc/apt/sources.list.d/docker.list > /dev/null
```

```
18
19 # Installa Docker Engine
20 $ sudo apt-get update
21 $ sudo apt-get install docker-ce docker-ce-cli containerd.io
22
23 # Verifica installazione
24 $ sudo docker --version
25 Docker version 20.10.17, build 100c701
26
27 # Test con hello-world
28 $ sudo docker run hello-world
```

### Esegui Docker senza sudo

```
1 # Crea gruppo docker
2 $ sudo groupadd docker
3
4 # Aggiungi utente al gruppo
5 $ sudo usermod -aG docker $USER
6
7 # Applica cambiamenti (logout/login oppure)
8 $ newgrp docker
9
10 # Test senza sudo
11 $ docker run hello-world
```

#### 2.1.2 macOS

1. Scarica **Docker Desktop** da <https://www.docker.com/products/docker-desktop>
2. Apri il file `Docker.dmg` e trascina Docker in Applications
3. Avvia Docker Desktop dalla cartella Applicazioni
4. Attendi l'icona Docker nella menu bar (whale)
5. Apri terminale e verifica:

```
1 $ docker --version
2 Docker version 20.10.17, build 100c701
```

#### 2.1.3 Windows

##### Requisiti:

- Windows 10/11 Pro, Enterprise o Education
- WSL 2 (Windows Subsystem for Linux)
- Virtualizzazione abilitata nel BIOS

1. Abilita WSL 2:

```
1 # PowerShell come Amministratore
2 > wsl --install
3 > wsl --set-default-version 2
```



2. Scarica Docker Desktop per Windows
3. Installa e riavvia
4. Configura: Settings -> General -> Use WSL 2 based engine
5. Verifica in PowerShell:

```
1 > docker --version
```

## 2.2 Docker Run: Eseguire Container

### 2.2.1 Sintassi base

```
1 docker run [OPTIONS] IMAGE [COMMAND] [ARG...]
```

### 2.2.2 Primo container

Listing 2.2: Hello World

```
1 $ docker run hello-world
2
3 Unable to find image 'hello-world:latest' locally
4 latest: Pulling from library/hello-world
5 2db29710123e: Pull complete
6 Digest: sha256:7
   d246653d0511db2a6b2e0436cfd0e52ac8c066000264b3ce63331ac66dca625
7 Status: Downloaded newer image for hello-world:latest
8
9 Hello from Docker!
10 This message shows that your installation appears to be working
   correctly.
```

#### Cosa è successo?

1. Docker cerca l'immagine `hello-world` localmente
2. Non trovandola, la scarica da Docker Hub
3. Crea un container dall'immagine
4. Esegue il container (stampa il messaggio)
5. Il container termina (processo completato)

### 2.2.3 Container interattivo

Listing 2.3: Ubuntu shell interattiva

```
1 $ docker run -it ubuntu bash
2
3 # Ora sei dentro il container Ubuntu
4 root@a1b2c3d4e5f6:/# cat /etc/os-release
5 NAME="Ubuntu"
6 VERSION="22.04 LTS (Jammy Jellyfish)"
7
8 root@a1b2c3d4e5f6:/# ls /
```

```

9 bin boot dev etc home lib media mnt opt proc root run sbin
   srv sys tmp usr var
10
11 root@a1b2c3d4e5f6:/# exit

```

### Opzioni:

- **-i**: Interactive (mantieni stdin aperto)
- **-t**: TTY (alloca un pseudo-terminale)
- **bash**: Comando da eseguire nel container

## 2.2.4 Container in background (detached)

Listing 2.4: Web server Nginx

```

1 $ docker run -d -p 8080:80 --name webserver nginx
2
3 # -d: Detached mode (background)
4 # -p 8080:80: Mappa porta host:container
5 # --name: Assegna nome al container
6 # nginx: Immagine da usare
7
8 # Output: container ID
9 a1b2c3d4e5f67890abcdef1234567890
10
11 # Testa nel browser: http://localhost:8080
12 # Oppure con curl
13 $ curl http://localhost:8080
14 <!DOCTYPE html>
15 <html>
16 <head>
17 <title>Welcome to nginx!</title>
18 ...

```

## 2.2.5 Opzioni comuni di docker run

Opzione	Descrizione
<b>-d</b>	Detached mode (background)
<b>-it</b>	Interactive + TTY
<b>-p 8080:80</b>	Pubblica porta host:container
<b>-name myapp</b>	Nome personalizzato
<b>-v /host:/container</b>	Monta volume
<b>-e VAR=value</b>	Variabile ambiente
<b>-rm</b>	Rimuovi container quando termina
<b>-network net1</b>	Connetti a rete specifica
<b>-restart always</b>	Policy di restart
<b>-cpus="1.5"</b>	Limita CPU
<b>-memory="512m"</b>	Limita RAM

Tabella 2.1: Opzioni principali di docker run

## 2.2.6 Esempi pratici

Listing 2.5: Database MySQL

```

1 $ docker run -d \
2   --name mysql-db \
3   -e MYSQL_ROOT_PASSWORD=secret \
4   -e MYSQL_DATABASE=myapp \
5   -p 3306:3306 \
6   -v mysql-data:/var/lib/mysql \
7   mysql:8.0
8
9 # Connetti al database
10 $ docker exec -it mysql-db mysql -u root -p
11 Enter password: secret
12 mysql> SHOW DATABASES;

```

Listing 2.6: Redis cache

```

1 $ docker run -d \
2   --name redis-cache \
3   -p 6379:6379 \
4   redis:alpine
5
6 # Test connessione
7 $ docker exec -it redis-cache redis-cli
8 127.0.0.1:6379> PING
9 PONG
10 127.0.0.1:6379> SET mykey "Hello Docker"
11 OK
12 127.0.0.1:6379> GET mykey
13 "Hello Docker"

```

## 2.3 Docker PS: Ispezionare Container

### 2.3.1 Listare container in esecuzione

```

1 $ docker ps
2
3 CONTAINER ID   IMAGE      COMMAND                                     CREATED        STATUS
4 a1b2c3d4e5f6   nginx     "/docker-entrypoint..."               5 minutes ago  Up 5
5 f6e5d4c3b2a1   redis     "docker-entrypoint.s..."             2 hours ago   Up 2

```

CONTAINER ID	IMAGE	COMMAND	CREATED	STATUS
a1b2c3d4e5f6	nginx	"/docker-entrypoint..."	5 minutes ago	Up 5
f6e5d4c3b2a1	redis	"docker-entrypoint.s..."	2 hours ago	Up 2

### 2.3.2 Listare tutti i container (anche fermati)

```

1 $ docker ps -a
2
3 CONTAINER ID   IMAGE      COMMAND                                     CREATED        STATUS
4 a1b2c3d4e5f6   nginx     "... "                                     5 minutes ago  Up 5 minutes
5 9876543210ab   ubuntu    "bash"                                    10 minutes ago Exited (0) 8

```

CONTAINER ID	IMAGE	COMMAND	CREATED	STATUS
a1b2c3d4e5f6	nginx	"..."	5 minutes ago	Up 5 minutes
9876543210ab	ubuntu	"bash"	10 minutes ago	Exited (0) 8

```

6 5432167890cd    hello-world    "/hello"    1 hour ago    Exited (0) 1
    hour ago          stoic_tesla

```

### 2.3.3 Formattazione output

```

1 # Solo ID container
2 $ docker ps -q
3 a1b2c3d4e5f6
4 f6e5d4c3b2a1
5
6 # Custom format
7 $ docker ps --format "table {{.ID}}\t{{.Names}}\t{{.Status}}"
8 CONTAINER ID    NAMES          STATUS
9 a1b2c3d4e5f6    webserver      Up 10 minutes
10 f6e5d4c3b2a1    redis-cache    Up 2 hours
11
12 # JSON output
13 $ docker ps --format json
14 {"Command":"\n/docker-entrypoint...\n","CreatedAt":"2025-11-15 10:00:00
    ","ID":"a1b2c3d4e5f6",...}

```

### 2.3.4 Filtri

```

1 # Container per nome
2 $ docker ps --filter "name=web"
3
4 # Container per status
5 $ docker ps -a --filter "status=exited"
6
7 # Container per label
8 $ docker ps --filter "label=env=production"
9
10 # Container per ancestor (immagine)
11 $ docker ps --filter "ancestor=nginx"

```

## 2.4 Docker Images: Gestire Immagini

### 2.4.1 Listare immagini locali

```

1 $ docker images
2
3 REPOSITORY    TAG          IMAGE ID      CREATED      SIZE
4 nginx         latest      605c77e624dd  2 weeks ago  141MB
5 redis         alpine     a49ff3e0d85f  3 weeks ago  32.3MB
6 mysql         8.0        3218b38490ce  1 month ago  516MB
7 ubuntu        22.04      216c552ea5ba  2 months ago  77.8MB
8 hello-world   latest     feb5d9fea6a5  14 months ago  13.3kB

```

### 2.4.2 Cercare immagini su Docker Hub

```

1 $ docker search python
2

```

3	NAME			DESCRIPTION
				STARS OFFICIAL
4	python			Python is an interpreted, interactive,
	objec...	9876	[OK]	
5	pypy			PyPy is a fast, compliant alternative
	implem...	345	[OK]	
6	circleci/python			Python is an interpreted, interactive,
	objec...	89		

### 2.4.3 Scaricare immagini (pull)

```

1 # Ultima versione (tag latest)
2 $ docker pull python
3 Using default tag: latest
4 latest: Pulling from library/python
5 ...
6
7 # Versione specifica
8 $ docker pull python:3.9-slim
9 3.9-slim: Pulling from library/python
10 ...
11
12 # Da registry privato
13 $ docker pull myregistry.com:5000/myapp:v1.0

```

### 2.4.4 Rimuovere immagini

```

1 # Per ID
2 $ docker rmi 605c77e624dd
3
4 # Per nome:tag
5 $ docker rmi nginx:latest
6
7 # Forza rimozione (anche se usata)
8 $ docker rmi -f nginx
9
10 # Rimuovi immagini dangling (senza tag)
11 $ docker image prune
12
13 # Rimuovi tutte le immagini non usate
14 $ docker image prune -a

```

### 2.4.5 Ispezionare immagini

```

1 # Informazioni dettagliate
2 $ docker inspect nginx
3 [
4   {
5     "Id": "sha256:605c77e624dd...",
6     "RepoTags": ["nginx:latest"],
7     "Created": "2025-10-28T10:15:30.123456789Z",
8     "Size": 141234567,
9     ...
10  }

```

```

11 ]
12
13 # Estrai campo specifico con jq
14 $ docker inspect nginx | jq '.[0].Config.ExposedPorts'
15 {
16   "80/tcp": {}
17 }
18
19 # History dei layer
20 $ docker history nginx
21 IMAGE          CREATED          CREATED BY          SIZE
22 605c77e624dd   2 weeks ago     CMD ["nginx" "-g" "daemon off;"]
23 <missing>      2 weeks ago     STOPSIGNAL SIGQUIT  0B
24 <missing>      2 weeks ago     EXPOSE 80           0B
25 <missing>      2 weeks ago     COPY file:abc123... /etc/nginx/nginx.conf
26 ...           4.5kB

```

## 2.5 Gestione Ciclo di Vita Container

### 2.5.1 Stati del container




Figura 2.1: Stati del ciclo di vita di un container

### 2.5.2 Stop e Start

```

1 # Ferma container (graceful shutdown, SIGTERM poi SIGKILL)
2 $ docker stop webserver
3 webserver
4
5 # Ferma con timeout custom (default 10s)
6 $ docker stop -t 30 webserver
7
8 # Ferma forzatamente (SIGKILL immediato)
9 $ docker kill webserver
10
11 # Riavvia container fermo
12 $ docker start webserver
13
14 # Riavvia container in esecuzione
15 $ docker restart webserver

```

### 2.5.3 Pause e Unpause

```
1 # Congela processi del container (cgroup freezer)
2 $ docker pause webserver
3
4 # Riprendi esecuzione
5 $ docker unpause webserver
```

### 2.5.4 Rimuovere container

```
1 # Rimuovi container fermo
2 $ docker rm webserver
3
4 # Rimuovi container in esecuzione (forza)
5 $ docker rm -f webserver
6
7 # Rimuovi più container
8 $ docker rm container1 container2 container3
9
10 # Rimuovi tutti container fermati
11 $ docker container prune
12
13 # Rimuovi tutti container (anche in esecuzione)
14 $ docker rm -f $(docker ps -aq)
```

## 2.6 Logs e Debugging

### 2.6.1 Visualizzare log

```
1 # Log completi
2 $ docker logs webserver
3
4 # Segui log in real-time (come tail -f)
5 $ docker logs -f webserver
6
7 # Ultime N righe
8 $ docker logs --tail 100 webserver
9
10 # Log con timestamp
11 $ docker logs -t webserver
12 2025-11-15T10:30:15.123456789Z 172.17.0.1 - - [15/Nov/2025:10:30:15
13     +0000] "GET / HTTP/1.1" 200
14
15 # Log da un certo tempo
16 $ docker logs --since 10m webserver
$ docker logs --since 2025-11-15T10:00:00 webserver
```

### 2.6.2 Eseguire comandi in container running

```
1 # Comando singolo
2 $ docker exec webserver ls /etc/nginx
3 conf.d
4 fastcgi.conf
5 mime.types
```

```

6 nginx.conf
7
8 # Shell interattiva
9 $ docker exec -it webserver bash
10 root@a1b2c3d4e5f6:/# ps aux
11 USER          PID %CPU %MEM    VSZ   RSS TTY      STAT START   TIME COMMAND
12 root           1  0.0  0.0   8892   5432 ?        Ss   10:00   0:00 nginx:
      master
13 nginx         29  0.0  0.0   9316   2876 ?        S    10:00   0:00 nginx:
      worker
14
15 root@a1b2c3d4e5f6:/# exit

```

### 2.6.3 Inspect: Informazioni dettagliate

```

1 # Tutte le informazioni
2 $ docker inspect webserver
3
4 # Estrai IP address
5 $ docker inspect webserver | jq '.[0].NetworkSettings.IPAddress'
6 "172.17.0.2"
7
8 # Estrai variabili ambiente
9 $ docker inspect webserver | jq '.[0].Config.Env'
10 [
11   "PATH=/usr/local/sbin:/usr/local/bin:/usr/sbin:/usr/bin:/sbin:/bin",
12   "NGINX_VERSION=1.23.1"
13 ]
14
15 # Template Go (built-in)
16 $ docker inspect --format='{{.State.Status}}' webserver
17 running
18
19 $ docker inspect --format='{{range .NetworkSettings.Networks}}{{.
      IPAddress}}{{end}}' webserver
20 172.17.0.2

```

### 2.6.4 Stats: Monitoraggio risorse

```

1 # Statistiche real-time (come top)
2 $ docker stats
3
4 CONTAINER ID   NAME          CPU %       MEM USAGE / LIMIT   MEM %
5 a1b2c3d4e5f6   webserver    0.01%      5.234MiB / 7.775GiB  0.07%
6 f6e5d4c3b2a1   redis-cache  0.15%     12.45MiB / 7.775GiB  0.16%
7
8 # Stats di un singolo container
9 $ docker stats webserver
10
11 # Formato custom
12 $ docker stats --format "table {{.Container}}\t{{.CPUPerc}}\t{{.MemUsage
    }}"

```



### 2.6.5 Events: Monitorare eventi Docker

```

1 # Stream eventi real-time
2 $ docker events
3
4 2025-11-15T10:35:20.123456789+00:00 container create a1b2c3d4e5f6 (image
   =nginx, name=webserver)
5 2025-11-15T10:35:20.456789123+00:00 container start a1b2c3d4e5f6 (image=
   nginx, name=webserver)
6 2025-11-15T10:40:15.789123456+00:00 container stop a1b2c3d4e5f6 (image=
   nginx, name=webserver)
7
8 # Filtro per tipo
9 $ docker events --filter 'type=container'
10
11 # Filtro per evento
12 $ docker events --filter 'event=start'

```

## 2.7 Pulizia Risorse

### 2.7.1 Disk usage

```

1 $ docker system df
2
3 TYPE                TOTAL        ACTIVE        SIZE        RECLAIMABLE
4 Images              15           5            2.5GB       1.8GB (72%)
5 Containers          20           3            150MB       145MB (96%)
6 Local Volumes       10           2            500MB       450MB (90%)
7 Build Cache         50           0            1.2GB       1.2GB (100%)

```

### 2.7.2 Prune: Pulizia automatica

```

1 # Rimuovi container fermati
2 $ docker container prune
3 WARNING! This will remove all stopped containers.
4 Are you sure? [y/N] y
5 Deleted Containers:
6 9876543210ab
7 5432167890cd
8 Total reclaimed space: 125MB
9
10 # Rimuovi immagini non usate
11 $ docker image prune -a
12
13 # Rimuovi volumi non usati
14 $ docker volume prune
15
16 # Rimuovi reti non usate
17 $ docker network prune
18
19 # ATTENZIONE: Pulizia totale
20 $ docker system prune -a --volumes
21 WARNING! This will remove:
22 - all stopped containers
23 - all networks not used by at least one container

```

```
24 - all volumes not used by at least one container
25 - all images without at least one container associated to them
26 - all build cache
27 Are you sure? [y/N]
```

## Best Practices

### Best Practices

1. **Nomi significativi:** Usa `-name` per identificare facilmente i container
2. **Tag espliciti:** Evita `latest`, specifica versione (`nginx:1.23`)
3. **Cleanup regolare:** Esegui `docker system prune` periodicamente
4. **Limita risorse:** Usa `-cpus` e `-memory` in produzione
5. **Health checks:** Configura controlli di salute per monitoring
6. **Logging centralizzato:** Usa driver di log (`syslog`, `json-file`, `fluentd`)
7. **Restart policy:** Configura `-restart` per alta disponibilità
8. **Non usare exec per deployment:** Usa `docker-compose` o orchestratori

## Errori Comuni

### Attenzione

#### Problemi frequenti:

##### 1. Porta già in uso

```
1 Error: Bind for 0.0.0.0:8080 failed: port is already allocated
```

Soluzione: Cambia porta host o ferma processo che la occupa

##### 2. Permessi negati

```
1 Got permission denied while trying to connect to the Docker
  daemon socket
```

Soluzione: Aggiungi utente al gruppo `docker` o usa `sudo`

##### 3. Container esce immediatamente

```
1 $ docker ps      # Container non appare
```

Soluzione: Controlla log con `docker logs`, il processo principale è terminato

##### 4. Immagine non trovata

```
1 Unable to find image 'myapp:latest' locally
2 Error: pull access denied, repository does not exist
```

Soluzione: Verifica nome immagine/tag o fai pull esplicito

## Esercizi

1. Installa Docker sul tuo sistema e verifica con `docker -version`
2. Esegui un container Nginx:
  - Mappa porta 8080 -> 80
  - Assegna nome "mio-nginx"
  - Verifica accesso con browser
3. Crea un container MySQL:
  - Password root: "mysecret"
  - Database: "testdb"
  - Connetti con `docker exec` e crea una tabella
4. Esegui container Ubuntu interattivo:
  - Installa `curl` dentro il container
  - Testa connessione a un sito esterno
  - Esci senza fermarlo (Ctrl+P, Ctrl+Q)
  - Riconnettiti con `docker attach`
5. Monitoring:
  - Lancia 5 container nginx
  - Monitora con `docker stats`
  - Identifica quello che usa più RAM
  - Ferma tutti e rimuovili
6. Cleanup:
  - Controlla spazio con `docker system df`
  - Rimuovi container e immagini inutilizzate
  - Verifica spazio recuperato

## Quiz di Verifica

1. Quale flag di `docker run` esegue il container in background?
  - a) -b
  - b) -d
  - c) -background
  - d) -detach
2. Come vedere i log di un container in real-time?
3. Qual è la differenza tra `docker stop` e `docker kill`?
4. Come rimuovere tutti i container fermati con un solo comando?
5. **Vero/Falso:** `docker ps` mostra anche i container fermati.

## Riepilogo Concetti Chiave

### Concetti Fondamentali

- `docker run`: Crea ed esegue container da immagine
- `docker ps`: Lista container (aggiungere `-a` per tutti)
- `docker images`: Mostra immagini locali
- `docker stop/start/restart`: Gestione ciclo di vita
- `docker logs`: Visualizza output container
- `docker exec`: Esegui comandi in container running
- `docker inspect`: Informazioni dettagliate JSON
- `docker stats`: Monitoraggio risorse real-time
- `docker system prune`: Pulizia risorse inutilizzate

## Prossimi Passi

Nel prossimo capitolo esploreremo:

- Dockerfile: creare immagini custom
- Istruzioni FROM, RUN, COPY, CMD, ENTRYPOINT
- Multi-stage builds per ottimizzazione
- Best practices per immagini efficienti e sicure

## Riferimenti

- Docker CLI Reference: <https://docs.docker.com/engine/reference/commandline/cli/>
- Docker Run Reference: <https://docs.docker.com/engine/reference/run/>
- Dockerfile Best Practices: <https://docs.docker.com/develop/dev-best-practices/>
- Docker Hub: <https://hub.docker.com/>

## Capitolo 3

# Dockerfile: Creare Immagini Custom

### Introduzione

Il Dockerfile è un file di testo che contiene le istruzioni per costruire un'immagine Docker. Questo capitolo copre la sintassi, le istruzioni principali, best practices e tecniche avanzate come multi-stage builds.

### Obiettivi di apprendimento

- Scrivere Dockerfile per diverse applicazioni
- Comprendere FROM, RUN, COPY, CMD, ENTRYPOINT, ENV
- Ottimizzare immagini con multi-stage builds
- Applicare best practices per efficienza e sicurezza
- Gestire cache dei layer per build veloci

### 3.1 Cos'è un Dockerfile

#### 3.1.1 Definizione

Un **Dockerfile** è uno script testuale che automatizza la creazione di un'immagine Docker. Ogni istruzione crea un nuovo layer nell'immagine finale.

#### 3.1.2 Struttura base

Listing 3.1: Dockerfile minimale

```
1 # Commento: immagine base
2 FROM ubuntu:22.04
3
4 # Installa software
5 RUN apt-get update && apt-get install -y python3
6
7 # Copia applicazione
8 COPY app.py /app/app.py
9
10 # Comando di avvio
11 CMD ["python3", "/app/app.py"]
```

### 3.1.3 Build dell'immagine

```
1 # Build con tag
2 $ docker build -t myapp:v1.0 .
3
4 # Build con nome e path specifico
5 $ docker build -t myapp:latest -f Dockerfile.prod .
6
7 # Build senza cache
8 $ docker build --no-cache -t myapp .
```

## 3.2 Istruzioni Fondamentali

### 3.2.1 FROM: Immagine Base

La prima istruzione di ogni Dockerfile. Specifica l'immagine di partenza.

Listing 3.2: Esempi di FROM

```
1 # Immagine ufficiale Ubuntu
2 FROM ubuntu:22.04
3
4 # Immagine Alpine (minimalista, 5MB)
5 FROM alpine:3.18
6
7 # Immagine specifica per linguaggio
8 FROM python:3.11-slim
9 FROM node:18-alpine
10 FROM openjdk:17-jdk-slim
11
12 # Multi-stage: usa alias
13 FROM golang:1.21 AS builder
14 FROM nginx:alpine AS production
15
16 # Scratch: immagine vuota (per binari statici)
17 FROM scratch
```

#### Nota

**Alpine Linux** è popolare per container perché:

- Dimensione minima: 5MB vs 70MB Ubuntu
- Sicurezza: superficie d'attacco ridotta
- Performance: avvio rapido
- Attenzione: usa musl libc invece di glibc (possibili incompatibilità)

### 3.2.2 RUN: Eseguire Comandi

Esegue comandi durante la build dell'immagine. Ogni RUN crea un nuovo layer.

Listing 3.3: Sintassi RUN

```
1 # Shell form (eseguita in /bin/sh -c)
2 RUN apt-get update && apt-get install -y curl
3
```

```

4 # Exec form (preferita, no shell processing)
5 RUN ["apt-get", "update"]
6 RUN ["apt-get", "install", "-y", "nginx"]
7
8 # Multi-line con backslash
9 RUN apt-get update && \
10     apt-get install -y \
11         curl \
12         vim \
13         git && \
14     rm -rf /var/lib/apt/lists/*

```

**Best practice: Minimizzare layer**

Listing 3.4: Esempio SBAGLIATO (3 layer)

```

1 # Anti-pattern: ogni RUN crea un layer
2 RUN apt-get update
3 RUN apt-get install -y curl
4 RUN rm -rf /var/lib/apt/lists/*

```

Listing 3.5: Esempio CORRETTO (1 layer)

```

1 # Best practice: combina in un singolo RUN
2 RUN apt-get update && \
3     apt-get install -y curl && \
4     rm -rf /var/lib/apt/lists/*

```

### 3.2.3 COPY e ADD: Copiare File

**COPY: Copia Semplice**

Listing 3.6: Esempi COPY

```

1 # Copia file singolo
2 COPY app.py /app/app.py
3
4 # Copia directory
5 COPY src/ /app/src/
6
7 # Copia multipli file
8 COPY package.json package-lock.json /app/
9
10 # Copia con pattern
11 COPY *.py /app/
12
13 # Cambia ownership
14 COPY --chown=user:group app.py /app/

```

**ADD: Copia Avanzata**

Listing 3.7: ADD con funzionalità extra

```

1 # Come COPY ma con auto-extract di tar
2 ADD archive.tar.gz /app/
3
4 # Download da URL (SCONSIGLIATO, preferire RUN curl)
5 ADD https://example.com/file.txt /app/

```

**Attenzione**

**Preferisci COPY a ADD** tranne quando serve auto-extraction di archivi tar. ADD ha comportamenti impliciti che possono confondere.

**3.2.4 CMD: Comando Predefinito**

Specifica il comando di default quando il container viene eseguito.

Listing 3.8: Forme di CMD

```

1 # Exec form (preferita)
2 CMD ["python3", "app.py"]
3 CMD ["nginx", "-g", "daemon off;"]
4
5 # Shell form
6 CMD python3 app.py
7
8 # Come parametri a ENTRYPOINT
9 CMD ["--help"]

```

**Caratteristiche:**

- Solo l'ultimo CMD nel Dockerfile è effettivo
- Può essere sovrascritto da `docker run`
- Non eseguito durante build, solo a runtime

Listing 3.9: Override CMD

```

1 # Usa CMD del Dockerfile
2 $ docker run myapp
3
4 # Sovrascrive CMD
5 $ docker run myapp python3 script2.py

```

**3.2.5 ENTRYPOINT: Punto di Ingresso**

Configura il container come eseguibile.

Listing 3.10: ENTRYPOINT vs CMD

```

1 # Solo ENTRYPOINT
2 FROM alpine
3 ENTRYPOINT ["ping"]
4 CMD ["localhost"]
5
6 # Build e run
7 $ docker build -t pinger .
8 $ docker run pinger                # ping localhost
9 $ docker run pinger google.com     # ping google.com

```

**Differenze CMD vs ENTRYPOINT:**

Listing 3.11: Pattern comune: ENTRYPOINT + CMD

```

1 FROM python:3.11-slim
2 WORKDIR /app
3 COPY app.py .

```



Aspetto	CMD	ENTRYPOINT
Override	Facile (docker run img cmd)	Richiede -entrypoint
Scopo	Comando di default	Eseguibile fisso
Combinazione	Parametri per ENTRYPOINT	Comando principale

Tabella 3.1: CMD vs ENTRYPOINT

```

4
5 ENTRYPOINT ["python3", "app.py"]
6 CMD ["--help"]
7
8 # docker run myapp          -> python3 app.py --help
9 # docker run myapp --serve -> python3 app.py --serve

```

### 3.2.6 ENV: Variabili d'Ambiente

Listing 3.12: Definire variabili ambiente

```

1 # Sintassi key=value
2 ENV NODE_ENV=production
3 ENV APP_PORT=3000
4
5 # Sintassi vecchia (deprecata)
6 ENV NODE_ENV production
7
8 # Multiple env vars
9 ENV PORT=8080 \
10     DEBUG=false \
11     LOG_LEVEL=info
12
13 # Usare in RUN
14 ENV APP_DIR=/app
15 RUN mkdir -p $APP_DIR
16 WORKDIR $APP_DIR

```

#### ENV vs ARG:

- **ENV:** Persiste nel container runtime
- **ARG:** Solo durante build

### 3.2.7 ARG: Argomenti di Build

Listing 3.13: Usare ARG per build parametrizzata

```

1 # Definisci ARG con default
2 ARG PYTHON_VERSION=3.11
3 FROM python:${PYTHON_VERSION}-slim
4
5 ARG APP_ENV=development
6 RUN if [ "$APP_ENV" = "production" ]; then \
7     pip install --no-cache-dir gunicorn; \
8     fi
9
10 # Build con override
11 # $ docker build --build-arg PYTHON_VERSION=3.9 .
12 # $ docker build --build-arg APP_ENV=production .

```

### 3.2.8 WORKDIR: Directory di Lavoro

Listing 3.14: Impostare working directory

```
1 # Crea directory se non esiste
2 WORKDIR /app
3
4 # Path relativo (relativi al WORKDIR precedente)
5 WORKDIR /usr
6 WORKDIR local
7 WORKDIR bin
8 RUN pwd # Output: /usr/local/bin
9
10 # Best practice: usa WORKDIR invece di RUN cd
11 # SBAGLIATO
12 RUN cd /app && python app.py
13
14 # CORRETTO
15 WORKDIR /app
16 RUN python app.py
```

### 3.2.9 EXPOSE: Documentare Porte

Listing 3.15: Dichiarare porte

```
1 # Documenta porte usate
2 EXPOSE 80
3 EXPOSE 443
4 EXPOSE 3000/tcp
5 EXPOSE 53/udp
6
7 # EXPOSE è solo documentazione!
8 # Devi comunque fare -p al run
9 # $ docker run -p 8080:80 myapp
```

### 3.2.10 VOLUME: Punti di Montaggio

Listing 3.16: Definire volumi

```
1 # Crea mount point
2 VOLUME /data
3 VOLUME ["/var/log", "/var/db"]
4
5 # Esempio: database
6 FROM mysql:8.0
7 VOLUME /var/lib/mysql
8
9 # Al run, Docker crea volume anonimo se non specificato
10 # $ docker run -v mydata:/var/lib/mysql mysql
```

### 3.2.11 USER: Cambiare Utente

Listing 3.17: Eseguire come utente non-root

```
1 # Crea utente
2 RUN groupadd -r appuser && \
```

```
3     useradd -r -g appuser appuser
4
5 # Crea directory con ownership corretta
6 RUN mkdir -p /app && chown -R appuser:appuser /app
7
8 # Cambia utente per istruzioni successive
9 USER appuser
10
11 WORKDIR /app
12 COPY --chown=appuser:appuser . .
13
14 CMD ["python3", "app.py"]
```

#### Nota

**Sicurezza:** Eseguire container come root è un rischio. Usa sempre USER per applicazioni in produzione.

### 3.2.12 LABEL: Metadati

Listing 3.18: Aggiungere metadati

```
1 LABEL maintainer="luca.campion@example.com"
2 LABEL version="1.0"
3 LABEL description="My awesome app"
4
5 # Multiple labels
6 LABEL org.opencontainers.image.title="MyApp" \
7       org.opencontainers.image.version="1.0.0" \
8       org.opencontainers.image.vendor="MyCompany"
```

## 3.3 Esempi Completi di Dockerfile

### 3.3.1 Applicazione Python Flask

Listing 3.19: Dockerfile per Flask app

```
1 FROM python:3.11-slim
2
3 # Metadata
4 LABEL maintainer="dev@example.com"
5
6 # Variabili ambiente
7 ENV PYTHONUNBUFFERED=1 \
8     PYTHONDONTWRITEBYTECODE=1 \
9     APP_HOME=/app
10
11 # Crea user non-root
12 RUN groupadd -r appuser && useradd -r -g appuser appuser
13
14 # Working directory
15 WORKDIR $APP_HOME
16
17 # Installa dipendenze sistema
18 RUN apt-get update && \
19     apt-get install -y --no-install-recommends \
```

```
20     curl \
21     && rm -rf /var/lib/apt/lists/*
22
23 # Copia requirements e installa dipendenze Python
24 COPY requirements.txt .
25 RUN pip install --no-cache-dir -r requirements.txt
26
27 # Copia applicazione
28 COPY --chown=appuser:appuser . .
29
30 # Cambia a utente non-root
31 USER appuser
32
33 # Esponi porta
34 EXPOSE 5000
35
36 # Health check
37 HEALTHCHECK --interval=30s --timeout=3s --start-period=5s --retries=3 \
38     CMD curl -f http://localhost:5000/health || exit 1
39
40 # Comando di avvio
41 CMD ["gunicorn", "--bind", "0.0.0.0:5000", "app:app"]
```

### 3.3.2 Applicazione Node.js

Listing 3.20: Dockerfile per Node.js app

```
1 FROM node:18-alpine
2
3 # Installa dumb-init per signal handling
4 RUN apk add --no-cache dumb-init
5
6 # Crea app directory
7 WORKDIR /usr/src/app
8
9 # Copia package files
10 COPY package*.json ./
11
12 # Installa dipendenze (production only)
13 RUN npm ci --only=production && npm cache clean --force
14
15 # Copia codice app
16 COPY . .
17
18 # Usa utente node built-in
19 USER node
20
21 # Esponi porta
22 EXPOSE 3000
23
24 # Usa dumb-init per gestire segnali
25 ENTRYPOINT ["dumb-init", "--"]
26 CMD ["node", "server.js"]
```

### 3.3.3 Applicazione Go (Static Binary)

Listing 3.21: Dockerfile per Go app

```
1 FROM golang:1.21-alpine AS builder
2
3 WORKDIR /build
4
5 # Copia go mod files
6 COPY go.mod go.sum ./
7 RUN go mod download
8
9 # Copia source code
10 COPY . .
11
12 # Build static binary
13 RUN CGO_ENABLED=0 GOOS=linux go build -a -installsuffix cgo -o app .
14
15 # Final stage: usa scratch (immagine vuota)
16 FROM scratch
17
18 # Copia solo binary
19 COPY --from=builder /build/app /app
20
21 # Copia CA certificates per HTTPS
22 COPY --from=builder /etc/ssl/certs/ca-certificates.crt /etc/ssl/certs/
23
24 EXPOSE 8080
25
26 ENTRYPOINT ["/app"]
```

## 3.4 Multi-Stage Builds

### 3.4.1 Concetto

I **multi-stage builds** permettono di usare più FROM in un Dockerfile, copiando solo gli artifact necessari nell'immagine finale.

**Vantaggi:**

- Immagini finali molto più piccole
- Separazione build tools da runtime
- Sicurezza: no source code in produzione
- Un solo Dockerfile per dev e prod

### 3.4.2 Esempio: Java Application

Listing 3.22: Multi-stage: Maven build + JRE runtime

```
1 # Stage 1: Build con Maven
2 FROM maven:3.9-eclipse-temurin-17 AS builder
3
4 WORKDIR /build
5
6 # Copia pom.xml e scarica dipendenze (layer cacheable)
7 COPY pom.xml .
8 RUN mvn dependency:go-offline
9
```

```

10 # Copia source e compila
11 COPY src ./src
12 RUN mvn package -DskipTests
13
14 # Stage 2: Runtime con JRE
15 FROM eclipse-temurin:17-jre-alpine
16
17 WORKDIR /app
18
19 # Copia solo JAR compilato dallo stage builder
20 COPY --from=builder /build/target/myapp.jar app.jar
21
22 # Utente non-root
23 RUN addgroup -S appgroup && adduser -S appuser -G appgroup
24 USER appuser
25
26 EXPOSE 8080
27
28 ENTRYPOINT ["java", "-jar", "app.jar"]

```

#### Confronto dimensioni:

- Single-stage (Maven+JDK): 650 MB
- Multi-stage (solo JRE): 180 MB
- Risparmio: 72%

### 3.4.3 Esempio: React Frontend

Listing 3.23: Multi-stage: npm build + nginx serve

```

1 # Stage 1: Build con Node.js
2 FROM node:18-alpine AS builder
3
4 WORKDIR /build
5
6 # Installa dipendenze
7 COPY package*.json ./
8 RUN npm ci
9
10 # Build production
11 COPY . .
12 RUN npm run build
13
14 # Stage 2: Serve con Nginx
15 FROM nginx:alpine
16
17 # Copia build output
18 COPY --from=builder /build/dist /usr/share/nginx/html
19
20 # Custom nginx config
21 COPY nginx.conf /etc/nginx/conf.d/default.conf
22
23 EXPOSE 80
24
25 # Nginx in foreground
26 CMD ["nginx", "-g", "daemon off;"]

```

### 3.4.4 Esempio: Python con compilazione C

Listing 3.24: Multi-stage: build dependencies + runtime

```
1 # Stage 1: Build con compiler
2 FROM python:3.11-slim AS builder
3
4 RUN apt-get update && apt-get install -y --no-install-recommends \
5     gcc \
6     g++ \
7     build-essential \
8     && rm -rf /var/lib/apt/lists/*
9
10 WORKDIR /build
11
12 COPY requirements.txt .
13 RUN pip wheel --no-cache-dir --wheel-dir /wheels -r requirements.txt
14
15 # Stage 2: Runtime senza compiler
16 FROM python:3.11-slim
17
18 COPY --from=builder /wheels /wheels
19
20 RUN pip install --no-cache-dir /wheels/* && rm -rf /wheels
21
22 WORKDIR /app
23 COPY . .
24
25 CMD ["python", "app.py"]
```

## 3.5 Ottimizzazione e Best Practices

### 3.5.1 Layer Caching

Docker cachea i layer se le istruzioni non cambiano.

Listing 3.25: SBAGLIATO: Invalida cache spesso

```
1 FROM python:3.11-slim
2
3 # Ogni modifica a qualsiasi file invalida tutto dopo
4 COPY . /app
5 RUN pip install -r /app/requirements.txt
6
7 CMD ["python", "/app/app.py"]
```

Listing 3.26: CORRETTO: Ottimizza cache

```
1 FROM python:3.11-slim
2
3 WORKDIR /app
4
5 # Copia solo requirements (cambia raramente)
6 COPY requirements.txt .
7 RUN pip install -r requirements.txt
8
9 # Copia codice app (cambia spesso)
10 COPY . .
```

```
11  
12 CMD ["python", "app.py"]
```

### 3.5.2 Minimizzare Dimensioni Immagine

#### Strategie per Ridurre Dimensioni

##### 1. Usa immagini base minimali

- Alpine invece di Ubuntu: -60MB+
- Slim/slim-bullseye per Python/Node: -30MB
- Distroless per linguaggi compilati

##### 2. Multi-stage builds: Solo runtime artifacts

##### 3. Combina RUN: Meno layer

##### 4. Pulisci in stesso layer:

```
1 RUN apt-get update && apt-get install -y curl && \  
2     rm -rf /var/lib/apt/lists/*
```

##### 5. Usa .dockerignore:

```
1 # .dockerignore  
2 .git  
3 node_modules  
4 *.log  
5 .env
```

##### 6. No package manager cache:

```
1 # Python  
2 RUN pip install --no-cache-dir -r requirements.txt  
3  
4 # Node  
5 RUN npm ci && npm cache clean --force  
6  
7 # apt  
8 RUN apt-get install -y curl && rm -rf /var/lib/apt/lists/*
```

### 3.5.3 Sicurezza

#### Attenzione

##### Security Best Practices:

##### 1. Non usare root

```
1 USER appuser
```

##### 2. Scansiona immagini

```
1 $ docker scan myapp:latest  
2 $ trivy image myapp:latest
```



3. Usa immagini ufficiali verificate
4. Aggiorna base images regolarmente
5. Non embeddare segreti

```
1 # SBAGLIATO
2 ENV API_KEY=super_secret_123
3
4 # CORRETTO: usa secrets o env vars a runtime
5 $ docker run -e API_KEY=$(cat secret.txt) myapp
```

6. Usa COPY invece di ADD

7. Specifica versioni esatte

```
1 FROM python:3.11.5-slim # Non :latest
```

### 3.5.4 File .dockerignore

Listing 3.27: .dockerignore example

```
1 # Version control
2 .git
3 .gitignore
4 .gitattributes
5
6 # Dependencies
7 node_modules
8 bower_components
9 vendor
10
11 # Build output
12 dist
13 build
14 target
15 *.pyc
16 __pycache__
17
18 # Logs
19 *.log
20 logs
21
22 # IDE
23 .vscode
24 .idea
25 *.swp
26
27 # Environment
28 .env
29 .env.local
30 *.pem
31
32 # Documentation
33 README.md
34 docs
35
```

```
36 # Tests
37 tests
38 *.test.js
```

## Best Practices Riassunto

### Dockerfile Best Practices

1. Usa immagini base ufficiali e minimali
2. Un processo per container
3. Ordina istruzioni per cache (meno variabili prima)
4. Combina RUN per ridurre layer
5. Multi-stage builds per immagini compatte
6. Non eseguire come root (USER)
7. Usa .dockerignore per escludere file
8. COPY preferito ad ADD
9. Specifica versioni esatte (no :latest in prod)
10. Pulisci cache in stesso layer
11. Health checks per monitoring
12. Metadata con LABEL

## Errori Comuni

1. **Layer troppo grandi:** Non combinare comandi
2. **Cache invalidation:** COPY . . all'inizio
3. **Root user:** Rischio sicurezza
4. **Segreti nel Dockerfile:** Esposti in history
5. **:latest in produzione:** Non riproducibile
6. **Software inutile:** Aumenta superficie d'attacco
7. **File temporanei:** Non rimossi nello stesso RUN

## Esercizi

1. Scrivi un Dockerfile per un'app Python Flask con:
  - Immagine base python:3.11-slim
  - User non-root
  - Requirements.txt cacheable
  - Health check su /health

2. Converti questo Dockerfile a multi-stage:

```
1 FROM node:18
2 COPY . /app
3 WORKDIR /app
4 RUN npm install && npm run build
5 CMD ["npm", "start"]
```

3. Ottimizza questa catena RUN (3 layer -> 1):

```
1 RUN apt-get update
2 RUN apt-get install -y curl vim
3 RUN rm -rf /var/lib/apt/lists/*
```

4. Crea un .dockerignore per un progetto Node.js
5. Build un'immagine Go che usa scratch e misura la dimensione finale

## Quiz di Verifica

1. Qual è la differenza tra CMD e ENTRYPOINT?
2. Perché multi-stage builds riducono le dimensioni?
3. **Vero/Falso**: ARG persiste nel container runtime.
4. Quale istruzione crea un nuovo layer?
  - a) FROM
  - b) RUN
  - c) ENV
  - d) EXPOSE
5. Come evitare di invalidare la cache quando cambia il codice ma non le dipendenze?

## Riepilogo

- **Dockerfile**: Script per automatizzare build immagini
- **FROM**: Immagine base
- **RUN**: Esegue comandi (build-time)
- **COPY**: Copia file nel container
- **CMD**: Comando default (runtime)
- **ENTRYPOINT**: Eseguitibile principale
- **Multi-stage**: Ottimizzazione dimensioni
- **Cache**: Ordina istruzioni per massimizzare riuso
- **Sicurezza**: USER, scan, no secrets

## Prossimi Passi

Nel prossimo capitolo esploreremo:

- Docker Compose per orchestrare multi-container
- File docker-compose.yml
- Services, networks, volumes
- Deploy stack completi

## Riferimenti

- Dockerfile Reference: <https://docs.docker.com/engine/reference/builder/>
- Best Practices: [https://docs.docker.com/develop/develop-images/dockerfile\\_best-practices/](https://docs.docker.com/develop/develop-images/dockerfile_best-practices/)
- Multi-stage Builds: <https://docs.docker.com/build/building/multi-stage/>
- Security: <https://snyk.io/blog/10-docker-image-security-best-practices/>

## Capitolo 4

# Docker Compose: Orchestrazione Multi-Container

### Introduzione

Docker Compose è uno strumento per definire ed eseguire applicazioni Docker multi-container. Con un singolo file YAML puoi configurare tutti i servizi, reti e volumi della tua applicazione e avviarli con un comando.

### Obiettivi di apprendimento

- Scrivere file docker-compose.yml
- Definire services, networks, volumes
- Orchestrare stack multi-container
- Gestire dipendenze tra servizi
- Usare variabili d'ambiente e secrets
- Deploy applicazioni complete

## 4.1 Cos'è Docker Compose

### 4.1.1 Definizione

**Docker Compose** è un tool per definire e gestire applicazioni multi-container usando un file YAML dichiarativo.

#### **Vantaggi:**

- Un file per tutta l'infrastruttura
- Versionabile con Git
- Riproducibile su qualsiasi ambiente
- Comandi semplici: up, down, logs
- Ideale per sviluppo locale e testing

### 4.1.2 Installazione

Listing 4.1: Docker Compose V2 (integrato in Docker)

```
1 # Già incluso in Docker Desktop (macOS/Windows)
2
3 # Linux: verifica versione
4 $ docker compose version
5 Docker Compose version v2.20.2
6
7 # Se manca, installa plugin
8 $ sudo apt-get install docker-compose-plugin
```

#### Nota

##### Compose V1 vs V2:

- V1: docker-compose (Python, standalone)
- V2: docker compose (Go plugin, integrato)
- V2 è più veloce e il futuro ufficiale

## 4.2 File docker-compose.yml

### 4.2.1 Struttura Base

Listing 4.2: docker-compose.yml minimale

```
1 version: '3.8'
2
3 services:
4   web:
5     image: nginx:alpine
6     ports:
7       - "8080:80"
8
9   db:
10    image: postgres:15
11    environment:
12      POSTGRES_PASSWORD: secret
```

#### Sezioni principali:

- **version:** Versione file format (3.8 è comune)
- **services:** Container da eseguire
- **networks:** Reti custom (opzionale)
- **volumes:** Volumi persistenti (opzionale)

### 4.2.2 Comandi Base

```
1 # Avvia tutti i servizi (detached)
2 $ docker compose up -d
3
```

```
4 # Build e avvia
5 $ docker compose up --build
6
7 # Ferma e rimuovi container
8 $ docker compose down
9
10 # Ferma e rimuovi anche volumi
11 $ docker compose down -v
12
13 # Lista servizi in esecuzione
14 $ docker compose ps
15
16 # Log di tutti i servizi
17 $ docker compose logs -f
18
19 # Log di un servizio specifico
20 $ docker compose logs -f web
21
22 # Esegui comando in un servizio
23 $ docker compose exec web sh
24
25 # Scala un servizio
26 $ docker compose up -d --scale web=3
```

## 4.3 Definire Services

### 4.3.1 Build da Dockerfile

Listing 4.3: Service con build custom

```
1 services:
2   app:
3     build:
4       context: ./app
5       dockerfile: Dockerfile
6       args:
7         - APP_ENV=production
8     image: myapp:latest
9     container_name: my-app
10    restart: unless-stopped
11    ports:
12      - "3000:3000"
13    environment:
14      - NODE_ENV=production
15      - API_KEY=${API_KEY}
16    volumes:
17      - ./app:/usr/src/app
18      - /usr/src/app/node_modules
```

### 4.3.2 Usare Immagini Esistenti

Listing 4.4: Service con immagine da registry

```
1 services:
2   redis:
3     image: redis:7-alpine
```

```

4     container_name: redis-cache
5     restart: always
6     ports:
7       - "6379:6379"
8     volumes:
9       - redis-data:/data
10    command: redis-server --appendonly yes
11
12 volumes:
13   redis-data:

```

### 4.3.3 Opzioni Comuni dei Services

Opzione	Descrizione
image	Immagine da usare
build	Path Dockerfile per build custom
container_name	Nome container (default: progetto_servizio_1)
ports	Mapping porte host:container
environment	Variabili d'ambiente
env_file	File con env vars
volumes	Mount volumi o bind mounts
networks	Reti a cui connettere
depends_on	Dipendenze da altri servizi
restart	Policy restart (no/always/on-failure/unless-stopped)
command	Override CMD del Dockerfile
healthcheck	Controllo salute container
labels	Metadata key-value

Tabella 4.1: Opzioni principali dei services

## 4.4 Dipendenze tra Servizi

### 4.4.1 depends\_on

Listing 4.5: Definire dipendenze

```

1 services:
2   web:
3     image: myapp
4     depends_on:
5       - db
6       - redis
7
8   db:
9     image: postgres:15
10
11   redis:
12     image: redis:alpine

```

#### Comportamento:

- Compose avvia db e redis prima di web
- Non aspetta che i servizi siano "ready", solo che siano started
- Per aspettare readiness, serve health check



### 4.4.2 Health Checks e Readiness

Listing 4.6: Aspettare che DB sia pronto

```
1 services:
2   db:
3     image: postgres:15
4     environment:
5       POSTGRES_PASSWORD: secret
6     healthcheck:
7       test: ["CMD-SHELL", "pg_isready -U postgres"]
8       interval: 10s
9       timeout: 5s
10      retries: 5
11
12   web:
13     image: myapp
14     depends_on:
15       db:
16         condition: service_healthy
```

## 4.5 Networks

### 4.5.1 Network di Default

Compose crea automaticamente una rete bridge per i servizi.

```
1 services:
2   web:
3     image: nginx
4   app:
5     image: myapp
6   db:
7     image: postgres
8
9   # Automaticamente:
10  # - Network "myproject_default" creata
11  # - Tutti i servizi connessi
12  # - Service discovery: web può raggiungere db via DNS "db"
```

### 4.5.2 Networks Custom

Listing 4.7: Definire reti multiple

```
1 services:
2   frontend:
3     image: react-app
4     networks:
5       - frontend-net
6
7   api:
8     image: node-api
9     networks:
10      - frontend-net
11      - backend-net
12
13   db:
```

```
14     image: postgres
15     networks:
16         - backend-net
17
18 networks:
19     frontend-net:
20         driver: bridge
21     backend-net:
22         driver: bridge
23         internal: true # No accesso internet
```

#### Risultato:

- Frontend può chiamare API
- API può chiamare DB
- Frontend NON può chiamare DB direttamente
- DB non ha accesso internet (internal)

### 4.5.3 Network Esistente

```
1 services:
2     app:
3         image: myapp
4         networks:
5             - existing-network
6
7 networks:
8     existing-network:
9         external: true
```

## 4.6 Volumes

### 4.6.1 Named Volumes

Listing 4.8: Volumi gestiti da Docker

```
1 services:
2     db:
3         image: postgres:15
4         volumes:
5             - postgres-data:/var/lib/postgresql/data
6
7     redis:
8         image: redis:alpine
9         volumes:
10            - redis-data:/data
11
12 volumes:
13     postgres-data:
14     redis-data:
```

### 4.6.2 Bind Mounts

Listing 4.9: Mount directory host

```
1 services:
2   web:
3     image: nginx
4     volumes:
5       # Bind mount (path assoluto o relativo)
6       - ./html:/usr/share/nginx/html
7       - ./nginx.conf:/etc/nginx/nginx.conf:ro # Read-only
8
9   app:
10    build: ./app
11    volumes:
12      # Hot reload per sviluppo
13      - ./app:/usr/src/app
14      # Named volume per node_modules
15      - /usr/src/app/node_modules
```

### 4.6.3 Opzioni Volumi Avanzate

```
1 services:
2   db:
3     image: postgres
4     volumes:
5       - type: volume
6         source: db-data
7         target: /var/lib/postgresql/data
8         volume:
9           nocopy: true
10
11       - type: bind
12         source: ./backup
13         target: /backup
14         read_only: true
15
16 volumes:
17   db-data:
18     driver: local
19     driver_opts:
20       type: none
21       o: bind
22       device: /mnt/database
```

## 4.7 Variabili d'Ambiente

### 4.7.1 File .env

Listing 4.10: .env file

```
1 # .env
2 POSTGRES_VERSION=15
3 POSTGRES_PASSWORD=mysecretpassword
4 APP_PORT=3000
5 NODE_ENV=production
```

Listing 4.11: Usare variabili da .env

```
1 services:
2   db:
3     image: postgres:${POSTGRES_VERSION}
4     environment:
5       POSTGRES_PASSWORD: ${POSTGRES_PASSWORD}
6
7   app:
8     build: ./app
9     ports:
10      - "${APP_PORT}:3000"
11     environment:
12       NODE_ENV: ${NODE_ENV}
```

### 4.7.2 env\_file per Container

```
1 services:
2   app:
3     image: myapp
4     env_file:
5       - .env.common
6       - .env.production
7
8   db:
9     image: postgres
10    env_file: database.env
```

Listing 4.12: database.env

```
1 POSTGRES_USER=admin
2 POSTGRES_PASSWORD=secret
3 POSTGRES_DB=myapp
```

## 4.8 Esempi Completi

### 4.8.1 Stack LAMP (Linux, Apache, MySQL, PHP)

Listing 4.13: docker-compose.yml per LAMP

```
1 version: '3.8'
2
3 services:
4   web:
5     image: php:8.2-apache
6     container_name: lamp-web
7     restart: unless-stopped
8     ports:
9       - "8080:80"
10    volumes:
11      - ./www:/var/www/html
12    networks:
13      - lamp-net
14    depends_on:
15      - db
16
```

```

17 db:
18   image: mysql:8.0
19   container_name: lamp-db
20   restart: unless-stopped
21   environment:
22     MYSQL_ROOT_PASSWORD: rootpass
23     MYSQL_DATABASE: myapp
24     MYSQL_USER: user
25     MYSQL_PASSWORD: userpass
26   volumes:
27     - mysql-data:/var/lib/mysql
28   networks:
29     - lamp-net
30   healthcheck:
31     test: ["CMD", "mysqladmin", "ping", "-h", "localhost"]
32     interval: 10s
33     timeout: 5s
34     retries: 5
35
36 phpmyadmin:
37   image: phpmyadmin/phpmyadmin
38   container_name: lamp-phpmyadmin
39   restart: unless-stopped
40   ports:
41     - "8081:80"
42   environment:
43     PMA_HOST: db
44     PMA_PORT: 3306
45   networks:
46     - lamp-net
47   depends_on:
48     db:
49       condition: service_healthy
50
51 networks:
52   lamp-net:
53     driver: bridge
54
55 volumes:
56   mysql-data:

```

#### 4.8.2 Stack MERN (MongoDB, Express, React, Node)

Listing 4.14: docker-compose.yml per MERN

```

1 version: '3.8'
2
3 services:
4   # Frontend React
5   frontend:
6     build:
7       context: ./frontend
8       dockerfile: Dockerfile
9     container_name: mern-frontend
10    restart: unless-stopped
11    ports:
12      - "3000:3000"

```

```
13 volumes:
14   - ./frontend/src:/app/src
15   - /app/node_modules
16 environment:
17   - REACT_APP_API_URL=http://localhost:5000
18 networks:
19   - mern-net
20 depends_on:
21   - backend
22
23 # Backend Node.js/Express
24 backend:
25   build:
26     context: ./backend
27     dockerfile: Dockerfile
28   container_name: mern-backend
29   restart: unless-stopped
30   ports:
31     - "5000:5000"
32   volumes:
33     - ./backend:/app
34     - /app/node_modules
35   environment:
36     - NODE_ENV=development
37     - MONGO_URI=mongodb://mongodb:27017/myapp
38     - JWT_SECRET=${JWT_SECRET}
39   networks:
40     - mern-net
41   depends_on:
42     mongodb:
43       condition: service_healthy
44
45 # Database MongoDB
46 mongodb:
47   image: mongo:7
48   container_name: mern-mongodb
49   restart: unless-stopped
50   ports:
51     - "27017:27017"
52   environment:
53     - MONGO_INITDB_ROOT_USERNAME=admin
54     - MONGO_INITDB_ROOT_PASSWORD=adminpass
55   volumes:
56     - mongo-data:/data/db
57   networks:
58     - mern-net
59   healthcheck:
60     test: ["CMD", "mongosh", "--eval", "db.adminCommand('ping')"]
61     interval: 10s
62     timeout: 5s
63     retries: 5
64
65 networks:
66   mern-net:
67     driver: bridge
68
69 volumes:
70   mongo-data:
```

### 4.8.3 Stack Microservizi con Nginx Reverse Proxy

Listing 4.15: Architettura microservizi

```
1 version: '3.8'
2
3 services:
4   # Reverse Proxy
5   nginx:
6     image: nginx:alpine
7     container_name: reverse-proxy
8     restart: unless-stopped
9     ports:
10      - "80:80"
11      - "443:443"
12     volumes:
13      - ./nginx/nginx.conf:/etc/nginx/nginx.conf:ro
14      - ./nginx/certs:/etc/nginx/certs:ro
15     networks:
16      - frontend-net
17     depends_on:
18      - auth-service
19      - user-service
20      - product-service
21
22   # Authentication Service
23   auth-service:
24     build: ./services/auth
25     container_name: auth-service
26     restart: unless-stopped
27     expose:
28      - "3001"
29     environment:
30      - DB_HOST=auth-db
31      - REDIS_HOST=redis
32     networks:
33      - frontend-net
34      - auth-backend-net
35     depends_on:
36      - auth-db
37      - redis
38
39   # User Service
40   user-service:
41     build: ./services/user
42     container_name: user-service
43     restart: unless-stopped
44     expose:
45      - "3002"
46     environment:
47      - DB_HOST=user-db
48     networks:
49      - frontend-net
50      - user-backend-net
51     depends_on:
52      - user-db
53
54   # Product Service
55   product-service:
```

```
56     build: ./services/product
57     container_name: product-service
58     restart: unless-stopped
59     expose:
60     - "3003"
61     environment:
62     - DB_HOST=product-db
63     networks:
64     - frontend-net
65     - product-backend-net
66     depends_on:
67     - product-db
68
69 # Databases
70 auth-db:
71     image: postgres:15
72     container_name: auth-db
73     restart: unless-stopped
74     environment:
75     POSTGRES_DB: auth
76     POSTGRES_PASSWORD: authpass
77     volumes:
78     - auth-db-data:/var/lib/postgresql/data
79     networks:
80     - auth-backend-net
81
82 user-db:
83     image: postgres:15
84     container_name: user-db
85     restart: unless-stopped
86     environment:
87     POSTGRES_DB: users
88     POSTGRES_PASSWORD: userpass
89     volumes:
90     - user-db-data:/var/lib/postgresql/data
91     networks:
92     - user-backend-net
93
94 product-db:
95     image: postgres:15
96     container_name: product-db
97     restart: unless-stopped
98     environment:
99     POSTGRES_DB: products
100     POSTGRES_PASSWORD: productpass
101     volumes:
102     - product-db-data:/var/lib/postgresql/data
103     networks:
104     - product-backend-net
105
106 # Cache Redis
107 redis:
108     image: redis:7-alpine
109     container_name: redis
110     restart: unless-stopped
111     networks:
112     - auth-backend-net
113
```



```

114 networks:
115     frontend-net:
116     auth-backend-net:
117         internal: true
118     user-backend-net:
119         internal: true
120     product-backend-net:
121         internal: true
122
123 volumes:
124     auth-db-data:
125     user-db-data:
126     product-db-data:

```

#### 4.8.4 Monitoring Stack (Prometheus + Grafana)

Listing 4.16: Stack monitoring

```

1 version: '3.8'
2
3 services:
4     prometheus:
5         image: prom/prometheus:latest
6         container_name: prometheus
7         restart: unless-stopped
8         ports:
9             - "9090:9090"
10        volumes:
11            - ./prometheus/prometheus.yml:/etc/prometheus/prometheus.yml
12            - prometheus-data:/prometheus
13        command:
14            - '--config.file=/etc/prometheus/prometheus.yml'
15            - '--storage.tsdb.path=/prometheus'
16        networks:
17            - monitoring
18
19 grafana:
20     image: grafana/grafana:latest
21     container_name: grafana
22     restart: unless-stopped
23     ports:
24         - "3000:3000"
25     environment:
26         - GF_SECURITY_ADMIN_PASSWORD=admin
27     volumes:
28         - grafana-data:/var/lib/grafana
29         - ./grafana/dashboards:/etc/grafana/provisioning/dashboards
30     networks:
31         - monitoring
32     depends_on:
33         - prometheus
34
35 node-exporter:
36     image: prom/node-exporter:latest
37     container_name: node-exporter
38     restart: unless-stopped
39     expose:

```

```

40     - "9100"
41     networks:
42     - monitoring
43
44     cadvisor:
45     image: gcr.io/cadvisor/cadvisor:latest
46     container_name: cadvisor
47     restart: unless-stopped
48     expose:
49     - "8080"
50     volumes:
51     - /:/rootfs:ro
52     - /var/run:/var/run:ro
53     - /sys:/sys:ro
54     - /var/lib/docker:/var/lib/docker:ro
55     networks:
56     - monitoring
57
58     networks:
59     monitoring:
60     driver: bridge
61
62     volumes:
63     prometheus-data:
64     grafana-data:

```

## 4.9 Comandi Avanzati

### 4.9.1 Override Files

```

1 # docker-compose.yml (base)
2 # docker-compose.override.yml (dev)
3 # docker-compose.prod.yml (production)
4
5 # Automatico: usa override se esiste
6 $ docker compose up
7
8 # Specifica file multipli
9 $ docker compose -f docker-compose.yml -f docker-compose.prod.yml up

```

Listing 4.17: docker-compose.override.yml

```

1 # Override per sviluppo
2 services:
3     web:
4     volumes:
5     - ./app:/app # Hot reload
6     environment:
7     - DEBUG=true

```

### 4.9.2 Scale Services

```

1 # Scala servizio web a 3 repliche
2 $ docker compose up -d --scale web=3
3

```

```

4 # Verifica
5 $ docker compose ps
6 NAME                IMAGE      COMMAND      STATUS      PORTS
7 project-web-1        nginx     ...          Up          0.0.0.0:8081->80/tcp
8 project-web-2        nginx     ...          Up          0.0.0.0:8082->80/tcp
9 project-web-3        nginx     ...          Up          0.0.0.0:8083->80/tcp

```

### 4.9.3 Logs e Monitoring

```

1 # Log real-time di tutti i servizi
2 $ docker compose logs -f
3
4 # Log di un servizio specifico
5 $ docker compose logs -f web
6
7 # Ultime 100 righe
8 $ docker compose logs --tail=100
9
10 # Top processes
11 $ docker compose top
12
13 # Stats risorse
14 $ docker stats $(docker compose ps -q)

```

## Best Practices

### Best Practices Docker Compose

1. **Versionamento:** Commit docker-compose.yml in Git
2. **File .env:** Non committare secrets (usa .gitignore)
3. **Named volumes:** Preferisci a bind mounts per produzione
4. **Health checks:** Definisci per tutti i servizi critici
5. **Restart policies:** Usa unless-stopped in prod
6. **Resource limits:**

```

1 services:
2   web:
3     deploy:
4       resources:
5         limits:
6           cpus: '0.5'
7           memory: 512M

```

7. **Networks isolate:** Separa frontend/backend
8. **Container names:** Usa nomi espliciti
9. **Override files:** Separa dev/prod config
10. **Documentazione:** README con istruzioni setup

## Errori Comuni

### Attenzione

1. **Bind mounts in produzione:** Preferisci named volumes

2. **Port conflicts:** Verifica porte non occupate

```
1 Error: Bind for 0.0.0.0:3000 failed: port is already allocated
```

3. **depends\_on senza health check:** Non garantisce readiness

4. **Secrets in chiaro:** Usa Docker secrets o vault

5. **Network non specificata:** Servizi non comunicano

6. **Volumi non persistenti:** Dati persi con down -v

## Esercizi

1. Crea uno stack WordPress + MySQL con docker-compose
2. Implementa un'app Node.js + PostgreSQL + Redis:
  - Health check su database
  - Bind mount per hot reload
  - Named volume per dati PostgreSQL
3. Setup ambiente microservizi:
  - 3 servizi API (users, orders, products)
  - Nginx reverse proxy
  - Database separato per ogni servizio
  - Redis condiviso per caching
4. Crea file override per sviluppo e produzione
5. Implementa stack monitoring con Prometheus + Grafana

## Quiz di Verifica

1. Qual è il comando per avviare tutti i servizi in background?
2. Cosa fa `depends_on`? Garantisce che il servizio sia pronto?
3. Come passare variabili d'ambiente a un servizio?
4. Qual è la differenza tra named volume e bind mount?
5. Come vedere i log di un singolo servizio in real-time?

## Riepilogo

- **Docker Compose:** Orchestrazione multi-container con YAML
- **Services:** Definizione container e configurazione
- **Networks:** Isolamento e comunicazione tra servizi
- **Volumes:** Persistenza dati
- **depends\_on:** Dipendenze e ordine avvio
- **Health checks:** Verificare readiness servizi
- **.env:** Gestione variabili d'ambiente
- **Override:** Configurazioni multiple dev/prod

## Prossimi Passi

Nel prossimo capitolo esploreremo:

- Networking Docker approfondito (bridge, host, overlay)
- Gestione avanzata volumi
- Persistenza dati e backup
- Service discovery e load balancing

## Riferimenti

- Compose File Reference: <https://docs.docker.com/compose/compose-file/>
- Compose CLI: <https://docs.docker.com/compose/reference/>
- Compose Samples: <https://github.com/docker/awesome-compose>



# Capitolo 5

## Networking e Volumes

### Introduzione

Il networking e la gestione dei volumi sono fondamentali per container che devono comunicare tra loro e persistere dati. Questo capitolo esplora i diversi driver di rete Docker, il service discovery, e le strategie di gestione volumi per garantire persistenza e backup.

### Obiettivi di apprendimento

- Comprendere i driver di rete: bridge, host, overlay, none
- Creare reti custom e isolare container
- Configurare port mapping e service discovery
- Gestire volumi per persistenza dati
- Implementare backup e restore di volumi
- Usare bind mounts e tmpfs appropriatamente

## 5.1 Docker Networking

### 5.1.1 Concetti Fondamentali

Docker usa **network drivers** per fornire networking ai container:

- **bridge**: Default, rete privata su un singolo host
- **host**: Usa direttamente il network stack dell'host
- **overlay**: Multi-host networking (Swarm/Kubernetes)
- **macvlan**: Assegna MAC address ai container
- **none**: Nessun networking

### 5.1.2 Comandi Base

```
1 # Lista reti
2 $ docker network ls
3 NETWORK ID          NAME           DRIVER        SCOPE
4 abc123def456        bridge        bridge        local
```

```

5 123456789abc    host    host    local
6 def456abc123    none    null    local
7
8 # Crea rete custom
9 $ docker network create mynetwork
10 $ docker network create --driver bridge my-bridge-net
11
12 # Ispeziona rete
13 $ docker network inspect mynetwork
14
15 # Connetti container a rete
16 $ docker network connect mynetwork container1
17
18 # Disconnetti
19 $ docker network disconnect mynetwork container1
20
21 # Rimuovi rete
22 $ docker network rm mynetwork
23
24 # Pulisci reti non usate
25 $ docker network prune

```

## 5.2 Bridge Network

### 5.2.1 Default Bridge

Quando avvii un container senza specificare `-network`, usa la rete `bridge` di default.

Listing 5.1: Container su bridge default

```

1 # Avvia due container
2 $ docker run -d --name container1 alpine sleep 1000
3 $ docker run -d --name container2 alpine sleep 1000
4
5 # Verifica network
6 $ docker inspect container1 | jq '.[0].NetworkSettings.Networks'
7 {
8   "bridge": {
9     "IPAddress": "172.17.0.2",
10    ...
11  }
12 }
13
14 # Comunicazione via IP (funziona)
15 $ docker exec container1 ping -c 2 172.17.0.3
16 PING 172.17.0.3 (172.17.0.3): 56 data bytes
17 64 bytes from 172.17.0.3: seq=0 ttl=64 time=0.123 ms
18
19 # Comunicazione via nome (NON funziona su default bridge!)
20 $ docker exec container1 ping container2
21 ping: bad address 'container2'

```

#### Limitazioni default bridge:

- No automatic service discovery (DNS)
- Comunicazione solo via IP
- Tutti i container vedono tutti gli altri



### 5.2.2 User-Defined Bridge

**Best practice:** Usa sempre reti custom per service discovery automatico.

Listing 5.2: Custom bridge network

```
1 # Crea rete custom
2 $ docker network create --driver bridge my-app-net
3
4 # Avvia container su rete custom
5 $ docker run -d --name web --network my-app-net nginx
6 $ docker run -d --name db --network my-app-net postgres
7
8 # Service discovery via DNS (funziona!)
9 $ docker exec web ping -c 2 db
10 PING db (172.18.0.3): 56 data bytes
11 64 bytes from 172.18.0.3: seq=0 ttl=64 time=0.089 ms
12
13 # Inspect network
14 $ docker network inspect my-app-net
15 [
16     {
17         "Name": "my-app-net",
18         "Driver": "bridge",
19         "Containers": {
20             "abc123": {
21                 "Name": "web",
22                 "IPv4Address": "172.18.0.2/16"
23             },
24             "def456": {
25                 "Name": "db",
26                 "IPv4Address": "172.18.0.3/16"
27             }
28         }
29     }
30 ]
```

### 5.2.3 Configurazione Bridge Avanzata

Listing 5.3: Opzioni custom bridge

```
1 # Subnet e gateway custom
2 $ docker network create \
3     --driver bridge \
4     --subnet 192.168.100.0/24 \
5     --gateway 192.168.100.1 \
6     --ip-range 192.168.100.0/25 \
7     my-custom-net
8
9 # IP statico per container
10 $ docker run -d \
11     --name web \
12     --network my-custom-net \
13     --ip 192.168.100.10 \
14     nginx
```

## 5.3 Host Network

Il container usa direttamente il network stack dell'host, senza isolamento.

Listing 5.4: Host network mode

```
1 # Container usa network dell'host
2 $ docker run -d --name nginx-host --network host nginx
3
4 # Nginx ascolta su porta 80 dell'HOST (non del container)
5 $ curl http://localhost:80
6 <!DOCTYPE html>
7 <html>
8 <title>Welcome to nginx!</title>
9 ...
10
11 # No port mapping necessario (-p non serve)
```

### Vantaggi:

- Performance ottimale (no NAT overhead)
- Accesso diretto a tutte le interfacce host

### Svantaggi:

- Nessun isolamento di rete
- Port conflicts se più container usano stessa porta
- Non funziona su Docker Desktop (macOS/Windows)

### Quando usarlo:

- Performance critiche (monitoring, load balancer)
- Container che gestisce tutto il network stack (VPN, firewall)

## 5.4 Overlay Network

Per multi-host networking (Docker Swarm, Kubernetes).

Listing 5.5: Overlay network (Swarm mode)

```
1 # Inizializza Swarm
2 $ docker swarm init
3
4 # Crea overlay network
5 $ docker network create \
6   --driver overlay \
7   --attachable \
8   my-overlay-net
9
10 # Deploy servizio su overlay
11 $ docker service create \
12   --name web \
13   --network my-overlay-net \
14   --replicas 3 \
15   nginx
16
17 # Container su host diversi possono comunicare
```

**Caratteristiche:**

- Comunicazione tra container su host fisici diversi
- Encryption opzionale del traffico
- Service discovery integrato
- Load balancing automatico

## 5.5 None Network

Nessun networking, completo isolamento.

```
1 # Container isolato
2 $ docker run -d --name isolated --network none alpine sleep 1000
3
4 # Verifica: solo loopback
5 $ docker exec isolated ip addr show
6 1: lo: <LOOPBACK,UP,LOWER_UP> mtu 65536
7     inet 127.0.0.1/8 scope host lo
```

**Quando usarlo:**

- Elaborazione dati sensibili senza accesso rete
- Testing isolato
- Container che comunicano solo via volumi condivisi

## 5.6 Port Mapping

### 5.6.1 Pubblicare Porte

```
1 # Porta specifica: host:container
2 $ docker run -d -p 8080:80 nginx
3
4 # Porta random host
5 $ docker run -d -p 80 nginx
6 $ docker ps # Vedi porta assegnata (es. 0.0.0.0:32768->80/tcp)
7
8 # Multiple porte
9 $ docker run -d \
10 -p 8080:80 \
11 -p 8443:443 \
12 nginx
13
14 # IP specifico host
15 $ docker run -d -p 127.0.0.1:8080:80 nginx
16
17 # UDP
18 $ docker run -d -p 53:53/udp dns-server
```

## 5.6.2 Port Binding vs Expose

Listing 5.6: Differenza EXPOSE vs -p

```
1 # Dockerfile: EXPOSE documenta porta
2 EXPOSE 80
3
4 # Run: -p pubblica effettivamente
5 $ docker run -p 8080:80 myapp
6
7 # Senza -p, porta non accessibile dall'host
8 $ docker run myapp # Porta 80 non raggiungibile esternamente
```

## 5.7 Service Discovery

### 5.7.1 DNS Automatico

Su reti custom, Docker fornisce DNS automatico.

Listing 5.7: Service discovery example

```
1 # Crea rete
2 $ docker network create app-net
3
4 # Servizio backend
5 $ docker run -d \
6   --name api \
7   --network app-net \
8   myapi
9
10 # Servizio frontend può chiamare backend via nome
11 $ docker run -d \
12   --name frontend \
13   --network app-net \
14   -e API_URL=http://api:3000 \
15   myfrontend
16
17 # Frontend può risolvere "api" via DNS
18 $ docker exec frontend nslookup api
19 Server: 127.0.0.11
20 Address: 127.0.0.11:53
21
22 Name:     api
23 Address: 172.20.0.2
```

### 5.7.2 Network Aliases

```
1 # Multipli alias per stesso container
2 $ docker run -d \
3   --name db \
4   --network app-net \
5   --network-alias database \
6   --network-alias postgres \
7   postgres
8
9 # Raggiungibile via db, database, o postgres
10 $ docker exec frontend ping database
```

```
11 $ docker exec frontend ping postgres
```


## 5.8 Isolamento e Sicurezza

### 5.8.1 Reti Multiple

Listing 5.8: Segmentare applicazione

```
1 # Rete frontend
2 $ docker network create frontend-net
3
4 # Rete backend (internal, no internet)
5 $ docker network create --internal backend-net
6
7 # Frontend: accessibile esternamente
8 $ docker run -d \
9   --name web \
10  --network frontend-net \
11  -p 80:80 \
12  nginx
13
14 # API: su entrambe le reti
15 $ docker run -d \
16   --name api \
17   --network frontend-net \
18   nginx-api
19
20 $ docker network connect backend-net api
21
22 # Database: solo backend (non raggiungibile da internet)
23 $ docker run -d \
24   --name db \
25   --network backend-net \
26   postgres
```

#### Architettura:



### 5.8.2 Firewall e IPTables

Docker modifica automaticamente iptables per port mapping.

```
1 # Visualizza regole Docker
2 $ sudo iptables -t nat -L -n
3
```

```

4 # Disabilita modifica iptables (daemon.json)
5 {
6   "iptables": false
7 }

```

## 5.9 Docker Volumes

### 5.9.1 Tipi di Persistenza

1. **Volumes:** Gestiti da Docker, best practice
2. **Bind mounts:** Directory host montate nel container
3. **tmpfs mounts:** Memoria RAM, non persistente




Figura 5.1: Tipi di mount in Docker

### 5.9.2 Named Volumes

```

1 # Crea volume
2 $ docker volume create mydata
3
4 # Lista volumi
5 $ docker volume ls
6 DRIVER      VOLUME NAME
7 local       mydata
8
9 # Ispeziona
10 $ docker volume inspect mydata
11 [
12   {
13     "Name": "mydata",
14     "Driver": "local",
15     "Mountpoint": "/var/lib/docker/volumes/mydata/_data",
16     "Labels": {},
17     "Scope": "local"
18   }
19 ]

```

```

20
21 # Usa in container
22 $ docker run -d \
23   --name db \
24   -v mydata:/var/lib/postgresql/data \
25   postgres
26
27 # Rimuovi volume
28 $ docker volume rm mydata
29
30 # Pulisci volumi non usati
31 $ docker volume prune

```

### 5.9.3 Bind Mounts

```

1 # Mount directory host
2 $ docker run -d \
3   --name web \
4   -v /home/user/html:/usr/share/nginx/html \
5   nginx
6
7 # Path relativo (PWD)
8 $ docker run -d \
9   --name app \
10  -v $(pwd)/app:/app \
11  myapp
12
13 # Read-only mount
14 $ docker run -d \
15   --name web \
16   -v $(pwd)/html:/usr/share/nginx/html:ro \
17   nginx
18
19 # Sintassi --mount (più esplicita)
20 $ docker run -d \
21   --mount type=bind,source=$(pwd)/app,target=/app \
22   myapp

```

Bind Mounts vs Volumes:

Aspetto	Bind Mount	Volume
Path	Host filesystem	Docker area
Gestione	Manuale	Docker
Performance	Buona	Ottima (Linux)
Portabilità	Bassa	Alta
Backup	Manuale	Docker CLI
Uso	Sviluppo	Produzione

Tabella 5.1: Bind Mount vs Volume

### 5.9.4 tmpfs Mounts

Dati in RAM, non scritti su disco.

```

1 # Mount tmpfs
2 $ docker run -d \

```

```

3  --name tmptest \
4  --tmpfs /app/cache:rw,size=100m \
5  myapp
6
7  # Sintassi --mount
8  $ docker run -d \
9  --mount type=tmpfs,target=/app/cache,tmpfs-size=100m \
10 myapp

```

**Quando usare tmpfs:**

- Dati sensibili (credenziali temporanee)
- Cache ad alte performance
- File temporanei che non devono persistere

## 5.10 Gestione Avanzata Volumi

### 5.10.1 Volume Drivers

```

1  # Driver locale (default)
2  $ docker volume create --driver local myvolume
3
4  # NFS volume
5  $ docker volume create \
6  --driver local \
7  --opt type=nfs \
8  --opt o=addr=192.168.1.1,rw \
9  --opt device=:/path/to/dir \
10 nfs-volume
11
12 # Cloud storage (plugin richiesto)
13 $ docker volume create \
14 --driver rexray/s3fs \
15 --opt=size=20 \
16 s3-volume

```

### 5.10.2 Backup e Restore

Listing 5.9: Backup volume

```

1  # Backup volume in tar.gz
2  $ docker run --rm \
3  -v mydata:/data \
4  -v $(pwd):/backup \
5  alpine \
6  tar czf /backup/mydata-backup.tar.gz -C /data .
7
8  # Verifica backup
9  $ ls -lh mydata-backup.tar.gz
10 -rw-r--r-- 1 user user 1.5M Nov 15 10:00 mydata-backup.tar.gz

```

Listing 5.10: Restore volume

```

1  # Crea nuovo volume
2  $ docker volume create mydata-restored

```



```

3
4 # Restore da backup
5 $ docker run --rm \
6   -v mydata-restored:/data \
7   -v $(pwd):/backup \
8   alpine \
9   sh -c "cd /data && tar xzf /backup/mydata-backup.tar.gz"

```

### 5.10.3 Condivisione Volumi tra Container

```

1 # Container 1 scrive dati
2 $ docker run -d \
3   --name writer \
4   -v shared-data:/data \
5   alpine \
6   sh -c "while true; do date >> /data/log.txt; sleep 5; done"
7
8 # Container 2 legge dati
9 $ docker run -d \
10  --name reader \
11  -v shared-data:/data:ro \
12  alpine \
13  sh -c "tail -f /data/log.txt"
14
15 # Verifica
16 $ docker logs reader
17 Wed Nov 15 10:00:00 UTC 2025
18 Wed Nov 15 10:00:05 UTC 2025
19 ...

```

### 5.10.4 Volumes from Container

```

1 # Data container
2 $ docker create -v /data --name data-container alpine
3
4 # App usa volumi da data-container
5 $ docker run -d \
6   --name app1 \
7   --volumes-from data-container \
8   myapp
9
10 $ docker run -d \
11   --name app2 \
12   --volumes-from data-container \
13   myapp

```

## 5.11 Esempi Pratici

### 5.11.1 Database con Persistenza

Listing 5.11: PostgreSQL production setup

```

1 # Crea rete e volume
2 $ docker network create db-net

```

```

3 $ docker volume create postgres-data
4
5 # Deploy PostgreSQL
6 $ docker run -d \
7   --name postgres \
8   --network db-net \
9   --restart unless-stopped \
10  -e POSTGRES_PASSWORD=secret \
11  -v postgres-data:/var/lib/postgresql/data \
12  -v $(pwd)/init.sql:/docker-entrypoint-initdb.d/init.sql:ro \
13  postgres:15
14
15 # Backup automatico (cron job)
16 $ docker run --rm \
17   --network db-net \
18   -v postgres-data:/data \
19   -v $(pwd)/backups:/backups \
20   postgres:15 \
21   pg_dump -h postgres -U postgres -F c -f /backups/db-$(date +%Y%m%d).
    dump

```

### 5.11.2 Sviluppo con Hot Reload

Listing 5.12: Node.js development

```

1 # Bind mount per hot reload
2 $ docker run -d \
3   --name node-dev \
4   -p 3000:3000 \
5   -v $(pwd)/app:/usr/src/app \
6   -v /usr/src/app/node_modules \
7   -e NODE_ENV=development \
8   node:18 \
9   npm run dev
10
11 # Modifiche a app/ si riflettono immediatamente

```

### 5.11.3 Multi-Tier App Networking

Listing 5.13: 3-tier architecture

```

1 # Reti
2 $ docker network create frontend-net
3 $ docker network create backend-net
4
5 # Database (solo backend)
6 $ docker run -d \
7   --name db \
8   --network backend-net \
9   -v db-data:/var/lib/postgresql/data \
10  postgres
11
12 # API (frontend + backend)
13 $ docker run -d \
14   --name api \
15   --network frontend-net \

```

```
16 -e DB_HOST=db \  
17 node-api \  
18 \  
19 $ docker network connect backend-net api \  
20 \  
21 # Web (solo frontend) \  
22 $ docker run -d \  
23 --name web \  
24 --network frontend-net \  
25 -p 80:80 \  
26 nginx
```

## Best Practices

### Best Practices

#### Networking:

- Usa reti custom per service discovery automatico
- Segmenta applicazione con reti multiple
- Usa `-internal` per reti senza accesso internet
- Evita `-network host` se non necessario
- Documenta port mapping nei README

#### Volumes:

- Named volumes in produzione, bind mounts in sviluppo
- Backup regolari di volumi critici
- Usa `:ro` per mount read-only quando possibile
- Pulisci volumi inutilizzati periodicamente
- Considera driver cloud per high availability

## Errori Comuni

### Attenzione

1. **Default bridge senza DNS:** Usa reti custom

2. **Porta in conflitto:**

```
1 Error: Bind for 0.0.0.0:80 failed: port is already allocated
```

Soluzione: Cambia porta host o ferma servizio esistente

3. **Volume cancellato per errore:**

```
1 $ docker compose down -v # ATTENZIONE: cancella volumi!
```

Soluzione: Ometti `-v`, usa backup regolari

4. **Bind mount con path errato:** Verifica path assoluti
5. **Permission denied su bind mount:** Controlla ownership/chmod
6. **Container non comunicano:** Verifica stessa rete

## Esercizi

1. Crea un'app WordPress:
  - MySQL su rete backend con volume persistente
  - WordPress su rete frontend+backend
  - Nginx reverse proxy su rete frontend
2. Implementa service discovery:
  - 3 container su rete custom
  - Testa ping via hostname
  - Aggiungi network alias
3. Backup e restore:
  - Crea volume con dati PostgreSQL
  - Esegui backup in tar.gz
  - Restore su nuovo volume
  - Verifica integrità dati
4. Hot reload development:
  - Setup React app con bind mount
  - Modifica codice e verifica ricaricamento
  - Confronta con named volume (no hot reload)

## Quiz di Verifica

1. Qual è la differenza tra bridge default e custom?
2. Quando useresti `-network host`?
3. Come fare backup di un volume Docker?
4. **Vero/Falso:** tmpfs mounts persistono dopo riavvio container.
5. Quale tipo di mount è consigliato per produzione? Perché?

## Riepilogo

- **Bridge:** Rete privata con DNS (custom) o senza (default)
- **Host:** Network stack condiviso, max performance
- **Overlay:** Multi-host per Swarm/K8s

- **Service Discovery:** DNS automatico su reti custom
- **Volumes:** Persistenza gestita da Docker
- **Bind Mounts:** Mount directory host, per sviluppo
- **tmpfs:** Dati in RAM, temporanei
- **Backup:** Usa container helper per tar.gz

## Prossimi Passi

Nel prossimo capitolo esploreremo:

- Docker Hub e registry pubblici
- Registry privati (Harbor, AWS ECR, GCR)
- Push/pull immagini
- Tag e versioning
- CI/CD integration

## Riferimenti

- Docker Networking: <https://docs.docker.com/network/>
- Docker Volumes: <https://docs.docker.com/storage/volumes/>
- Network Drivers: <https://docs.docker.com/network/drivers/>
- Volume Plugins: [https://docs.docker.com/engine/extend/plugins\\_volume/](https://docs.docker.com/engine/extend/plugins_volume/)



## Capitolo 6

# Docker Registry e Hub

### Introduzione

I registry Docker sono repository centralizzati per memorizzare e distribuire immagini Docker. Questo capitolo copre Docker Hub, registry privati, strategie di versioning, e integrazione con pipeline CI/CD.

### Obiettivi di apprendimento

- Usare Docker Hub per pull e push di immagini
- Implementare strategie di tagging e versioning
- Setup registry privati (Docker Registry, Harbor)
- Configurare registry cloud (AWS ECR, GCP GCR, Azure ACR)
- Integrare con CI/CD per build e deploy automatici
- Applicare security scanning e best practices

## 6.1 Docker Hub

### 6.1.1 Cos'è Docker Hub

**Docker Hub** è il registry pubblico ufficiale di Docker:

- 100.000+ immagini ufficiali e community
- Gratuito per repository pubblici
- Piani a pagamento per repository privati
- Automated builds da GitHub/Bitbucket
- Webhook e integrazioni

URL: <https://hub.docker.com>

### 6.1.2 Account e Login

```
1 # Crea account su hub.docker.com, poi login
2 $ docker login
3 Username: myusername
4 Password:
5 Login Succeeded
6
7 # Login con token (più sicuro)
8 $ docker login -u myusername -p $(cat token.txt)
9
10 # Logout
11 $ docker logout
```

### 6.1.3 Pull Immagini

```
1 # Formato: [REGISTRY/]REPOSITORY[:TAG]
2
3 # Pull da Docker Hub (default registry)
4 $ docker pull nginx
5 $ docker pull nginx:1.25-alpine
6 $ docker pull ubuntu:22.04
7
8 # Pull da user/org repository
9 $ docker pull myusername/myapp:latest
10 $ docker pull bitnami/postgresql:15
11
12 # Pull da registry alternativo
13 $ docker pull ghcr.io/myorg/myapp:v1.0
14 $ docker pull quay.io/prometheus/prometheus
```

### 6.1.4 Push Immagini

Listing 6.1: Pubblicare immagine su Docker Hub

```
1 # 1. Build immagine con tag corretto
2 $ docker build -t myusername/myapp:v1.0 .
3
4 # 2. (Opzionale) Tag aggiuntivo per latest
5 $ docker tag myusername/myapp:v1.0 myusername/myapp:latest
6
7 # 3. Login
8 $ docker login
9
10 # 4. Push
11 $ docker push myusername/myapp:v1.0
12 $ docker push myusername/myapp:latest
13
14 # Verifica su hub.docker.com/r/myusername/myapp
```

### 6.1.5 Repository Pubblici vs Privati

```
1 # Crea repository privato su hub.docker.com
2
3 # Push a repository privato
```



Tipo	Visibilità	Costo
Pubblico	Tutti possono pull	Gratis
Privato	Solo autorizzati	1 gratis, poi a pagamento

Tabella 6.1: Repository Docker Hub

```

4 $ docker push myusername/private-app:v1.0
5
6 # Pull richiede autenticazione
7 $ docker login
8 $ docker pull myusername/private-app:v1.0

```

## 6.2 Tagging e Versioning

### 6.2.1 Strategie di Tag

#### Best Practices Tagging

1. **Semantic Versioning:** v1.2.3 (major.minor.patch)

2. **Tag multipli:**

```

1 myapp:v1.2.3      # Versione specifica
2 myapp:v1.2        # Minor version
3 myapp:v1          # Major version
4 myapp:latest      # Ultima stabile

```

3. **Tag descrittivi:**

```

1 myapp:v1.2.3-alpine
2 myapp:v1.2.3-debian
3 myapp:nightly
4 myapp:dev
5 myapp:prod

```

4. **Git commit SHA:**

```

1 myapp:sha-a1b2c3d
2 myapp:v1.2.3-a1b2c3d

```

### 6.2.2 Esempio Completo Tagging

Listing 6.2: Multi-tag workflow

```

1 # Versione corrente
2 VERSION=1.2.3
3
4 # Build immagine
5 $ docker build -t myusername/myapp:v${VERSION} .
6
7 # Tag multiple version levels
8 $ docker tag myusername/myapp:v${VERSION} myusername/myapp:v1.2
9 $ docker tag myusername/myapp:v${VERSION} myusername/myapp:v1
10 $ docker tag myusername/myapp:v${VERSION} myusername/myapp:latest

```

```

11
12 # Push tutti i tag
13 $ docker push myusername/myapp:v${VERSION}
14 $ docker push myusername/myapp:v1.2
15 $ docker push myusername/myapp:v1
16 $ docker push myusername/myapp:latest
17
18 # Oppure push all tags
19 $ docker push --all-tags myusername/myapp

```

### 6.2.3 Tag Immutabili

#### Attenzione

Evita di sovrascrivere tag in produzione!

```

1 # SBAGLIATO: Sovrascrivi tag esistente
2 $ docker tag myapp:latest myapp:v1.0
3 $ docker push myapp:v1.0 # Sovrascrive v1.0 precedente
4
5 # CORRETTO: Usa nuovo tag
6 $ docker tag myapp:latest myapp:v1.1
7 $ docker push myapp:v1.1

```

Solo latest, dev, nightly dovrebbero essere sovrascritti.

## 6.3 Registry Privati

### 6.3.1 Docker Registry (Open Source)

Registry ufficiale Docker, self-hosted.

Listing 6.3: Setup Docker Registry

```

1 # Deploy registry con Docker
2 $ docker run -d \
3   -p 5000:5000 \
4   --name registry \
5   --restart always \
6   -v registry-data:/var/lib/registry \
7   registry:2
8
9 # Push a registry locale
10 $ docker tag myapp localhost:5000/myapp:v1.0
11 $ docker push localhost:5000/myapp:v1.0
12
13 # Pull da registry locale
14 $ docker pull localhost:5000/myapp:v1.0

```

### 6.3.2 Registry con HTTPS e Autenticazione

Listing 6.4: Secure registry setup

```

1 # Genera certificati SSL (self-signed)
2 $ mkdir -p certs auth
3 $ openssl req -newkey rsa:4096 -nodes -sha256 \
4   -keyout certs/domain.key -x509 -days 365 \

```

```

5  -out certs/domain.crt
6
7  # Crea htpasswd per autenticazione
8  $ docker run --rm --entrypoint htpasswd \
9    httpd:2 -Bbn myuser mypassword > auth/htpasswd
10
11 # Deploy registry con TLS e auth
12 $ docker run -d \
13   -p 5000:5000 \
14   --name secure-registry \
15   --restart always \
16   -v $(pwd)/certs:/certs \
17   -v $(pwd)/auth:/auth \
18   -v registry-data:/var/lib/registry \
19   -e REGISTRY_HTTP_TLS_CERTIFICATE=/certs/domain.crt \
20   -e REGISTRY_HTTP_TLS_KEY=/certs/domain.key \
21   -e REGISTRY_AUTH=htpasswd \
22   -e REGISTRY_AUTH_HTPASSWD_PATH=/auth/htpasswd \
23   -e REGISTRY_AUTH_HTPASSWD_REALM="Registry Realm" \
24   registry:2
25
26 # Login
27 $ docker login myregistry.com:5000
28 Username: myuser
29 Password:

```

### 6.3.3 Docker Compose per Registry

Listing 6.5: docker-compose.yml per registry

```

1  version: '3.8'
2
3  services:
4    registry:
5      image: registry:2
6      container_name: docker-registry
7      restart: always
8      ports:
9        - "5000:5000"
10     environment:
11       REGISTRY_STORAGE_FILESYSTEM_ROOTDIRECTORY: /data
12       REGISTRY_AUTH: htpasswd
13       REGISTRY_AUTH_HTPASSWD_PATH: /auth/htpasswd
14       REGISTRY_AUTH_HTPASSWD_REALM: Registry
15     volumes:
16       - registry-data:/data
17       - ./auth:/auth
18     networks:
19       - registry-net
20
21 # UI per navigare registry
22 registry-ui:
23   image: joxit/docker-registry-ui:latest
24   container_name: registry-ui
25   restart: always
26   ports:
27     - "8080:80"

```

```
28     environment:
29         - REGISTRY_TITLE=My Docker Registry
30         - REGISTRY_URL=http://registry:5000
31         - DELETE_IMAGES=true
32         - SHOW_CONTENT_DIGEST=true
33     networks:
34         - registry-net
35     depends_on:
36         - registry
37
38 networks:
39     registry-net:
40
41 volumes:
42     registry-data:
```

## 6.4 Harbor: Enterprise Registry

### 6.4.1 Cos'è Harbor

Harbor è un registry enterprise open-source by VMware/CNCF:

- Web UI completa
- Role-based access control (RBAC)
- Vulnerability scanning integrato
- Image signing e notary
- Replication tra registry
- Webhook e audit logging
- Helm charts support

### 6.4.2 Installazione Harbor

Listing 6.6: Deploy Harbor con Docker Compose

```
1 # Download installer
2 $ wget https://github.com/goharbor/harbor/releases/download/v2.9.0/
   harbor-offline-installer-v2.9.0.tgz
3 $ tar xzf harbor-offline-installer-v2.9.0.tgz
4 $ cd harbor
5
6 # Configura
7 $ cp harbor.yml.tpl harbor.yml
8 $ vim harbor.yml
9 # Modifica:
10 # - hostname: registry.example.com
11 # - harbor_admin_password: MySecretPass
12 # - database password
13 # - certificate paths (se HTTPS)
14
15 # Installa
16 $ sudo ./install.sh --with-trivy --with-chartmuseum
17
```

```
18 # Accedi a https://registry.example.com
19 # User: admin
20 # Pass: MySecretPass
```

### 6.4.3 Usare Harbor

```
1 # Login
2 $ docker login registry.example.com
3 Username: admin
4 Password:
5
6 # Tag immagine per Harbor
7 $ docker tag myapp registry.example.com/myproject/myapp:v1.0
8
9 # Push
10 $ docker push registry.example.com/myproject/myapp:v1.0
11
12 # Pull
13 $ docker pull registry.example.com/myproject/myapp:v1.0
```

## 6.5 Cloud Registry

### 6.5.1 AWS Elastic Container Registry (ECR)

Listing 6.7: AWS ECR workflow

```
1 # Installa AWS CLI
2 $ aws configure
3
4 # Crea repository
5 $ aws ecr create-repository --repository-name myapp
6
7 # Login a ECR
8 $ aws ecr get-login-password --region us-east-1 | \
9   docker login --username AWS --password-stdin \
10  123456789012.dkr.ecr.us-east-1.amazonaws.com
11
12 # Tag immagine
13 $ docker tag myapp:v1.0 \
14  123456789012.dkr.ecr.us-east-1.amazonaws.com/myapp:v1.0
15
16 # Push
17 $ docker push 123456789012.dkr.ecr.us-east-1.amazonaws.com/myapp:v1.0
18
19 # Pull
20 $ docker pull 123456789012.dkr.ecr.us-east-1.amazonaws.com/myapp:v1.0
```

### 6.5.2 Google Container Registry (GCR)

Listing 6.8: GCR workflow

```
1 # Installa gcloud CLI
2 $ gcloud auth configure-docker
3
4 # Tag immagine
```

```

5 $ docker tag myapp:v1.0 gcr.io/my-project-id/myapp:v1.0
6
7 # Push
8 $ docker push gcr.io/my-project-id/myapp:v1.0
9
10 # Pull
11 $ docker pull gcr.io/my-project-id/myapp:v1.0

```

### 6.5.3 Azure Container Registry (ACR)

Listing 6.9: Azure ACR workflow

```

1 # Crea registry
2 $ az acr create --resource-group myResourceGroup \
3   --name myregistry --sku Basic
4
5 # Login
6 $ az acr login --name myregistry
7
8 # Tag immagine
9 $ docker tag myapp:v1.0 myregistry.azurecr.io/myapp:v1.0
10
11 # Push
12 $ docker push myregistry.azurecr.io/myapp:v1.0
13
14 # Pull
15 $ docker pull myregistry.azurecr.io/myapp:v1.0

```

### 6.5.4 Confronto Cloud Registry

Feature	AWS ECR	GCP GCR	Azure ACR
Pricing	Storage + transfer	Storage + egress	Tiered (Basic/Standard/Premium)
Scanning	ECR scan	GCR scan	Defender for Cloud
Geo-replication	Si (Premium)	Multi-region	Si (Premium)
Integrazione	ECS, EKS, Fargate	GKE, Cloud Run	AKS, Container Instances

Tabella 6.2: Cloud Registry Comparison

## 6.6 CI/CD Integration

### 6.6.1 GitHub Actions

Listing 6.10: .github/workflows/docker.yml

```

1 name: Docker Build and Push
2
3 on:
4   push:
5     branches: [ main ]
6     tags: [ 'v*' ]
7
8 jobs:
9   build-and-push:
10    runs-on: ubuntu-latest

```

```

11  steps:
12    - name: Checkout
13      uses: actions/checkout@v3
14
15    - name: Set up Docker Buildx
16      uses: docker/setup-buildx-action@v2
17
18    - name: Login to Docker Hub
19      uses: docker/login-action@v2
20      with:
21        username: ${ secrets.DOCKERHUB_USERNAME }
22        password: ${ secrets.DOCKERHUB_TOKEN }
23
24    - name: Extract metadata
25      id: meta
26      uses: docker/metadata-action@v4
27      with:
28        images: myusername/myapp
29        tags: |
30          type=ref,event=branch
31          type=semver,pattern={{version}}
32          type=semver,pattern={{major}}.{{minor}}
33          type=sha
34
35    - name: Build and push
36      uses: docker/build-push-action@v4
37      with:
38        context: .
39        push: true
40        tags: ${ steps.meta.outputs.tags }
41        labels: ${ steps.meta.outputs.labels }
42        cache-from: type=gha
43        cache-to: type=gha,mode=max

```

## 6.6.2 GitLab CI/CD

Listing 6.11: .gitlab-ci.yml

```

1  variables:
2    IMAGE_NAME: $CI_REGISTRY_IMAGE
3    IMAGE_TAG: $CI_COMMIT_REF_SLUG
4
5  stages:
6    - build
7    - push
8
9  build:
10   stage: build
11   image: docker:latest
12   services:
13     - docker:dind
14   before_script:
15     - docker login -u $CI_REGISTRY_USER -p $CI_REGISTRY_PASSWORD
16       $CI_REGISTRY
17   script:
18     - docker build -t $IMAGE_NAME:$IMAGE_TAG .
19     - docker push $IMAGE_NAME:$IMAGE_TAG

```

```

19     only:
20         - main
21         - tags
22
23 push-latest:
24     stage: push
25     image: docker:latest
26     services:
27         - docker:dind
28     before_script:
29         - docker login -u $CI_REGISTRY_USER -p $CI_REGISTRY_PASSWORD
30           $CI_REGISTRY
31     script:
32         - docker pull $IMAGE_NAME:$IMAGE_TAG
33         - docker tag $IMAGE_NAME:$IMAGE_TAG $IMAGE_NAME:latest
34         - docker push $IMAGE_NAME:latest
35     only:
36         - main

```

### 6.6.3 Jenkins Pipeline

Listing 6.12: Jenkinsfile

```

1 pipeline {
2     agent any
3
4     environment {
5         REGISTRY = 'myregistry.com:5000'
6         IMAGE_NAME = 'myapp'
7         IMAGE_TAG = "${env.BUILD_NUMBER}"
8     }
9
10    stages {
11        stage('Build') {
12            steps {
13                script {
14                    docker.build("${REGISTRY}/${IMAGE_NAME}:${IMAGE_TAG}"
15                                )
16                }
17            }
18
19            stage('Push') {
20                steps {
21                    script {
22                        docker.withRegistry("https://${REGISTRY}", 'registry
23                        -credentials') {
24                            docker.image("${REGISTRY}/${IMAGE_NAME}:${
25                                IMAGE_TAG}").push()
26                            docker.image("${REGISTRY}/${IMAGE_NAME}:${
27                                IMAGE_TAG}").push('latest')
28                        }
29                    }
30                }
31            }
32
33            stage('Deploy') {

```



```

31         steps {
32             sh '''
33                 docker pull ${REGISTRY}/${IMAGE_NAME}:${IMAGE_TAG}
34                 docker stop myapp || true
35                 docker rm myapp || true
36                 docker run -d --name myapp -p 80:80 ${REGISTRY}/${
37                     IMAGE_NAME}:${IMAGE_TAG}
38             '''
39         }
40     }
41 }

```

## 6.7 Security e Best Practices

### 6.7.1 Image Scanning

Listing 6.13: Scan vulnerabilities

```

1 # Docker scan (Snyk)
2 $ docker scan myapp:latest
3
4 # Trivy (open source)
5 $ trivy image myapp:latest
6
7 # Grype
8 $ grype myapp:latest
9
10 # Clair
11 $ clairctl analyze myapp:latest

```

### 6.7.2 Content Trust

Listing 6.14: Docker Content Trust (DCT)

```

1 # Abilita content trust
2 $ export DOCKER_CONTENT_TRUST=1
3
4 # Push firma automaticamente
5 $ docker push myusername/myapp:v1.0
6 # Richiede passphrase per chiave di signing
7
8 # Pull verifica firma
9 $ docker pull myusername/myapp:v1.0
10 # Fallisce se firma non valida

```

### 6.7.3 Image Signing con Cosign

```

1 # Installa cosign
2 $ brew install cosign # macOS
3 $ apt install cosign # Linux
4
5 # Genera keypair
6 $ cosign generate-key-pair
7

```

```

8 # Firma immagine
9 $ cosign sign --key cosign.key myregistry.com/myapp:v1.0
10
11 # Verifica firma
12 $ cosign verify --key cosign.pub myregistry.com/myapp:v1.0

```

### 6.7.4 Best Practices

#### Security Best Practices

1. **Scan regolarmente:** CI/CD pipeline con scanning
2. **Base images ufficiali:** Usa immagini verificate
3. **Minimal images:** Alpine, distroless
4. **Multi-stage builds:** No build tools in produzione
5. **No secrets in images:**

```

1 # SBAGLIATO
2 ENV API_KEY=secret123
3
4 # CORRETTO
5 # Pass at runtime
6 $ docker run -e API_KEY=$(vault read secret) myapp

```

6. **Versioni esplicite:** No :latest in prod
7. **Content trust:** Firma immagini critiche
8. **Registry privati:** Per codice proprietario
9. **RBAC:** Limita accesso push/pull
10. **Audit logging:** Traccia chi push cosa quando

## 6.8 Gestione Registry Avanzata

### 6.8.1 Garbage Collection

Listing 6.15: Cleanup registry storage

```

1 # Docker Registry garbage collection
2 $ docker exec registry bin/registry garbage-collect \
3   /etc/docker/registry/config.yml
4
5 # Delete old images (API)
6 $ curl -X DELETE http://registry:5000/v2/myapp/manifests/sha256:abc123
   ...

```

### 6.8.2 Replication

Listing 6.16: Harbor replication example

```

1 # Replica tra due Harbor registry

```

```

2 # Via Harbor UI:
3 # Administration -> Replications -> New Replication Rule
4 # - Name: prod-to-backup
5 # - Source: Local
6 # - Destination: backup-harbor.com
7 # - Trigger: Event based (push)

```

### 6.8.3 Webhook Notifications

Listing 6.17: Registry webhook config

```

1 # /etc/docker/registry/config.yml
2 notifications:
3   endpoints:
4     - name: slack
5       url: https://hooks.slack.com/services/YOUR/WEBHOOK/URL
6       headers:
7         Content-Type: [application/json]
8       events:
9         - push
10        - pull
11        - delete

```

## 6.9 Caso di Studio: Production Registry

Listing 6.18: Production-grade registry stack

```

1 version: '3.8'
2
3 services:
4   # Harbor core services
5   harbor:
6     image: goharbor/harbor:v2.9.0
7     restart: always
8     ports:
9       - "443:443"
10      - "80:80"
11     volumes:
12       - harbor-data:/data
13       - ./certs:/certs
14     environment:
15       - HARBOR_ADMIN_PASSWORD=${ADMIN_PASSWORD}
16     networks:
17       - harbor-net
18
19   # Trivy scanner
20   trivy:
21     image: goharbor/trivy-adapter-photon:v2.9.0
22     restart: always
23     environment:
24       - SCANNER_TRIVY_CACHE_DIR=/home/scanner/.cache/trivy
25     volumes:
26       - trivy-cache:/home/scanner/.cache
27     networks:
28       - harbor-net
29

```

```

30 # PostgreSQL database
31 postgres:
32   image: goharbor/harbor-db:v2.9.0
33   restart: always
34   environment:
35     - POSTGRES_PASSWORD=${DB_PASSWORD}
36   volumes:
37     - postgres-data:/var/lib/postgresql/data
38   networks:
39     - harbor-net
40
41 # Redis cache
42 redis:
43   image: goharbor/redis-photon:v2.9.0
44   restart: always
45   volumes:
46     - redis-data:/var/lib/redis
47   networks:
48     - harbor-net
49
50 # Nginx reverse proxy
51 nginx:
52   image: nginx:alpine
53   restart: always
54   ports:
55     - "443:443"
56   volumes:
57     - ./nginx.conf:/etc/nginx/nginx.conf:ro
58     - ./certs:/etc/nginx/certs:ro
59   networks:
60     - harbor-net
61   depends_on:
62     - harbor
63
64 networks:
65   harbor-net:
66     driver: bridge
67
68 volumes:
69   harbor-data:
70   trivy-cache:
71   postgres-data:
72   redis-data:

```

## Errori Comuni

### Attenzione

1. **Push senza tag:** Default :latest sovrascrive
2. **Insecure registry:**

```

1 # Error: http: server gave HTTP response to HTTPS client
2
3 # Fix: /etc/docker/daemon.json
4 {
5   "insecure-registries": ["myregistry.com:5000"]

```

```
6 | }  
7 | $ sudo systemctl restart docker
```

3. **Credentials non salvate:** Usa credential helper
4. **Rate limiting Docker Hub:** 100 pull/6h (free tier)
5. **Storage pieno registry:** Setup garbage collection
6. **Tag latest in produzione:** Usa versioni esplicite

## Esercizi

1. Setup Docker Hub account e pubblica un'immagine
2. Deploy registry privato:
  - Setup con HTTPS e autenticazione
  - Push/pull immagini
  - Verifica via UI
3. Implementa versioning strategy:
  - Semantic versioning (v1.2.3)
  - Multi-tag (latest, v1, v1.2, v1.2.3)
  - Script automation
4. CI/CD pipeline:
  - GitHub Actions build automatico
  - Push su Docker Hub
  - Deploy su server staging
5. Security scanning:
  - Scansiona immagine con Trivy
  - Risolvi vulnerabilità HIGH/CRITICAL
  - Integra scanning in CI/CD

## Quiz di Verifica

1. Qual è il formato completo di un'immagine Docker?
2. Cosa significa tag "latest"? È sicuro in produzione?
3. Differenza tra Docker Registry e Harbor?
4. Come configurare registry insecure (solo HTTP)?
5. Perché è importante scannerizzare le immagini?

## Riepilogo

- **Docker Hub:** Registry pubblico ufficiale
- **Tagging:** Semantic versioning, tag multipli
- **Registry privati:** Docker Registry, Harbor
- **Cloud registry:** AWS ECR, GCP GCR, Azure ACR
- **CI/CD:** Automazione build/push/deploy
- **Security:** Scanning, signing, RBAC
- **Best practices:** Versioni esplicite, no secrets, minimal images

## Conclusione del Corso

Complimenti! Hai completato il corso Docker e DevOps. Ora sei in grado di:

- Containerizzare qualsiasi applicazione
- Creare Dockerfile ottimizzati
- Orchestrare stack con Docker Compose
- Configurare networking e volumi
- Distribuire su registry pubblici e privati
- Implementare CI/CD pipeline
- Applicare security best practices

### Prossimi passi consigliati:

- Kubernetes per orchestrazione enterprise
- Docker Swarm per clustering
- Monitoring con Prometheus/Grafana
- Service mesh con Istio/Linkerd
- Certificazione Docker Certified Associate (DCA)

## Riferimenti

- Docker Hub: <https://hub.docker.com>
- Docker Registry: <https://docs.docker.com/registry/>
- Harbor: <https://goharbor.io>
- AWS ECR: <https://aws.amazon.com/ecr/>
- GCP GCR: <https://cloud.google.com/container-registry>
- Azure ACR: <https://azure.microsoft.com/en-us/services/container-registry/>
- Trivy: <https://github.com/aquasecurity/trivy>
- Cosign: <https://github.com/sigstore/cosign>

## Capitolo 7

# Deployment e Orchestrazione

### 7.1 Introduzione

Il deployment di applicazioni containerizzate richiede strategie sofisticate per garantire alta disponibilità, scalabilità e zero-downtime. Questo capitolo esplora pattern di deployment, introduzione all'orchestrazione e fondamenti di Kubernetes.

#### Mappa del capitolo

**Sezioni:** Strategie di deployment, Docker Swarm, Kubernetes basics, Service mesh, Load balancing, Rolling updates, Blue-green deployment, Canary releases, Health checks avanzati, Secrets management.

### 7.2 Obiettivi di Apprendimento

- Comprendere le strategie di deployment per applicazioni containerizzate
- Implementare orchestrazione con Docker Swarm e Kubernetes
- Gestire rolling updates e rollback senza downtime
- Configurare health checks e readiness probes
- Applicare pattern di deployment avanzati (blue-green, canary)

### 7.3 Strategie di Deployment

#### 7.3.1 Deployment Patterns

Listing 7.1: Recreate Strategy - Downtime Accettabile

```
1 # Stop tutti i container vecchi
2 docker-compose down
3
4 # Deploy nuova versione
5 docker-compose up -d
6
7 # Pro: Semplice, resource-efficient
8 # Contro: Downtime durante il deploy
```

Listing 7.2: Rolling Update - Zero Downtime

```

1 # Update incrementale container per container
2 docker service update \
3   --image myapp:v2 \
4   --update-parallelism 1 \
5   --update-delay 10s \
6   --update-failure-action rollback \
7   myapp-service
8
9 # Pro: Zero downtime, graduale
10 # Contro: Più complesso, richiede orchestratore

```

### 7.3.2 Blue-Green Deployment

Listing 7.3: Blue-Green con Docker Compose

```

1 # docker-compose-blue-green.yml
2 version: '3.8'
3
4 services:
5   # BLUE environment (current production)
6   app-blue:
7     image: myapp:v1
8     networks:
9       - app-network
10    environment:
11      - ENV=production
12      - VERSION=blue
13    deploy:
14      replicas: 3
15    labels:
16      - "traefik.enable=true"
17      - "traefik.http.routers.app.rule=Host('app.example.com')"
18
19   # GREEN environment (new version staging)
20   app-green:
21     image: myapp:v2
22     networks:
23       - app-network
24     environment:
25       - ENV=staging
26       - VERSION=green
27     deploy:
28       replicas: 3
29     labels:
30       - "traefik.enable=false" # Non ancora in produzione
31
32   # Load Balancer (Traefik)
33   traefik:
34     image: traefik:v2.10
35     command:
36       - "--api.insecure=true"
37       - "--providers.docker=true"
38       - "--entrypoints.web.address=:80"
39     ports:
40       - "80:80"
41       - "8080:8080"

```



```

42     volumes:
43     - /var/run/docker.sock:/var/run/docker.sock
44     networks:
45     - app-network
46
47 networks:
48   app-network:
49     driver: overlay

```

Listing 7.4: Switch Traffic da Blue a Green

```

1  #!/bin/bash
2  # blue-green-switch.sh
3
4  echo "Testing GREEN environment health..."
5  curl -f http://app-green:8080/health || exit 1
6
7  echo "Switching traffic to GREEN..."
8  docker service update \
9    --label-add "traefik.enable=true" \
10   app-green
11
12 docker service update \
13   --label-add "traefik.enable=false" \
14   app-blue
15
16 echo "Traffic switched to GREEN (v2)"
17 echo "Monitor for issues. To rollback:"
18 echo "  ./blue-green-switch.sh --rollback"

```

#### Blue-Green Vantaggi

- **Zero downtime:** Switch istantaneo tra ambienti
- **Fast rollback:** Ritorno immediato alla versione precedente
- **Testing:** Ambiente GREEN testabile prima dello switch
- **Contro:** Richiede risorse doppie durante il deployment

### 7.3.3 Canary Deployment

Listing 7.5: Canary Release - Traffic Splitting

```

1  # kubernetes-canary.yaml
2  apiVersion: apps/v1
3  kind: Deployment
4  metadata:
5    name: myapp-stable
6  spec:
7    replicas: 9 # 90% del traffico
8    selector:
9      matchLabels:
10       app: myapp
11       version: stable
12    template:
13      metadata:
14        labels:

```

```

15     app: myapp
16     version: stable
17   spec:
18     containers:
19     - name: myapp
20       image: myapp:v1
21       ports:
22       - containerPort: 8080
23
24   ---
25   apiVersion: apps/v1
26   kind: Deployment
27   metadata:
28     name: myapp-canary
29   spec:
30     replicas: 1 # 10% del traffico
31     selector:
32       matchLabels:
33         app: myapp
34         version: canary
35     template:
36       metadata:
37         labels:
38         app: myapp
39         version: canary
40     spec:
41       containers:
42       - name: myapp
43         image: myapp:v2 # Nuova versione
44         ports:
45         - containerPort: 8080
46
47   ---
48   apiVersion: v1
49   kind: Service
50   metadata:
51     name: myapp-service
52   spec:
53     selector:
54       app: myapp # Match entrambe le versioni
55     ports:
56     - port: 80
57       targetPort: 8080
58     type: LoadBalancer

```

Listing 7.6: Canary Progressivo

```

1  #!/bin/bash
2  # canary-rollout.sh
3
4  # Fase 1: 10% canary
5  kubectl scale deployment myapp-canary --replicas=1
6  kubectl scale deployment myapp-stable --replicas=9
7  sleep 300 # Monitor 5 minuti
8
9  # Controllo metriche errori
10 ERROR_RATE=$(kubectl exec -it prometheus -- \
11   curl -s 'http://localhost:9090/api/v1/query?query=error_rate' | \
12   jq '.data.result[0].value[1]')

```

```

13
14 if (( $(echo "$ERROR_RATE < 0.01" | bc -l) )); then
15     # Fase 2: 50% canary
16     kubectl scale deployment myapp-canary --replicas=5
17     kubectl scale deployment myapp-stable --replicas=5
18     sleep 300
19
20     # Fase 3: 100% canary (rollout completo)
21     kubectl scale deployment myapp-canary --replicas=10
22     kubectl scale deployment myapp-stable --replicas=0
23 else
24     echo "ERROR_RATE too high, rolling back..."
25     kubectl scale deployment myapp-canary --replicas=0
26 fi

```

## 7.4 Docker Swarm

### 7.4.1 Inizializzazione Cluster

Listing 7.7: Setup Docker Swarm Cluster

```

1 # Su manager node
2 docker swarm init --advertise-addr 192.168.1.10
3
4 # Output fornisce token per worker nodes:
5 # docker swarm join --token SWMTKN-1-xxx... 192.168.1.10:2377
6
7 # Su worker nodes
8 docker swarm join \
9     --token SWMTKN-1-5abc... \
10    192.168.1.10:2377
11
12 # Verifica cluster
13 docker node ls
14 # ID          HOSTNAME      STATUS    AVAILABILITY  MANAGER STATUS
15 # abc123      manager1     Ready    Active         Leader
16 # def456      worker1      Ready    Active
17 # ghi789      worker2      Ready    Active

```

### 7.4.2 Deploy Stack con Docker Swarm

Listing 7.8: Stack Multi-Service Production

```

1 # stack-production.yml
2 version: '3.8'
3
4 services:
5   web:
6     image: nginx:alpine
7     ports:
8       - "80:80"
9     deploy:
10       replicas: 3
11       update_config:
12         parallelism: 1
13       delay: 10s

```

```
14         failure_action: rollback
15     restart_policy:
16         condition: on-failure
17         delay: 5s
18         max_attempts: 3
19     placement:
20         constraints:
21             - node.role == worker
22     networks:
23         - frontend
24     configs:
25         - source: nginx_config
26           target: /etc/nginx/nginx.conf
27     secrets:
28         - ssl_certificate
29         - ssl_key
30
31 app:
32     image: myapp:latest
33     deploy:
34         replicas: 5
35         resources:
36             limits:
37                 cpus: '0.5'
38                 memory: 512M
39             reservations:
40                 cpus: '0.25'
41                 memory: 256M
42         update_config:
43             parallelism: 2
44             delay: 10s
45             monitor: 30s
46             failure_action: rollback
47             order: start-first # Start new before stopping old
48     networks:
49         - frontend
50         - backend
51     environment:
52         - DATABASE_URL_FILE=/run/secrets/db_connection
53     secrets:
54         - db_connection
55
56 db:
57     image: postgres:15-alpine
58     deploy:
59         replicas: 1
60         placement:
61             constraints:
62                 - node.labels.database == true
63     volumes:
64         - db-data:/var/lib/postgresql/data
65     networks:
66         - backend
67     environment:
68         - POSTGRES_PASSWORD_FILE=/run/secrets/db_password
69     secrets:
70         - db_password
71
```

```

72     redis:
73       image: redis:7-alpine
74       deploy:
75         replicas: 1
76         placement:
77           constraints:
78             - node.labels.cache == true
79       networks:
80         - backend
81
82 networks:
83   frontend:
84     driver: overlay
85   backend:
86     driver: overlay
87     internal: true # No external access
88
89 volumes:
90   db-data:
91     driver: local
92
93 configs:
94   nginx_config:
95     external: true
96
97 secrets:
98   ssl_certificate:
99     external: true
100   ssl_key:
101     external: true
102   db_connection:
103     external: true
104   db_password:
105     external: true

```

Listing 7.9: Deploy e Gestione Stack

```

1 # Create secrets
2 echo "postgresql://user:pass@db:5432/mydb" | \
3   docker secret create db_connection -
4
5 echo "supersecretpassword" | \
6   docker secret create db_password -
7
8 # Deploy stack
9 docker stack deploy -c stack-production.yml myapp
10
11 # Monitor services
12 docker stack services myapp
13 docker service ls
14 docker service ps myapp_app
15
16 # Scale service
17 docker service scale myapp_app=10
18
19 # Update service
20 docker service update \
21   --image myapp:v2 \
22   --update-parallelism 2 \

```

```

23     myapp_app
24
25 # Rollback
26 docker service rollback myapp_app
27
28 # Remove stack
29 docker stack rm myapp

```

## 7.5 Kubernetes Fundamentals

### 7.5.1 Architettura Kubernetes

#### Componenti Kubernetes Cluster

##### Control Plane:

- **kube-apiserver**: API REST per gestione cluster
- **etcd**: Database distribuito per stato cluster
- **kube-scheduler**: Assegnazione Pods ai Nodes
- **kube-controller-manager**: Controller per Deployments, Services, etc.

##### Worker Nodes:

- **kubelet**: Agente che esegue Pods sul node
- **kube-proxy**: Network proxy per Services
- **Container runtime**: Docker, containerd, CRI-O

### 7.5.2 Deployment Completo Kubernetes

Listing 7.10: Production Deployment con Kubernetes

```

1 # deployment.yaml
2 apiVersion: apps/v1
3 kind: Deployment
4 metadata:
5   name: web-app
6   namespace: production
7   labels:
8     app: web-app
9     version: v1
10 spec:
11   replicas: 3
12   strategy:
13     type: RollingUpdate
14     rollingUpdate:
15       maxSurge: 1           # Max pods oltre replicas durante update
16       maxUnavailable: 0    # Zero downtime
17   selector:
18     matchLabels:
19       app: web-app
20   template:
21     metadata:

```

```
22     labels:
23       app: web-app
24       version: v1
25   spec:
26     containers:
27     - name: app
28       image: myregistry.io/web-app:v1.2.3
29       imagePullPolicy: Always
30       ports:
31       - containerPort: 8080
32         name: http
33
34     # Health checks
35     livenessProbe:
36       httpGet:
37         path: /health/live
38         port: 8080
39       initialDelaySeconds: 30
40       periodSeconds: 10
41       timeoutSeconds: 5
42       failureThreshold: 3
43
44     readinessProbe:
45       httpGet:
46         path: /health/ready
47         port: 8080
48       initialDelaySeconds: 10
49       periodSeconds: 5
50       timeoutSeconds: 3
51       successThreshold: 1
52       failureThreshold: 3
53
54     # Startup probe for slow-starting apps
55     startupProbe:
56       httpGet:
57         path: /health/startup
58         port: 8080
59       initialDelaySeconds: 0
60       periodSeconds: 10
61       timeoutSeconds: 3
62       failureThreshold: 30 # 30*10s = 5 minuti max startup
63
64     # Resource management
65     resources:
66       requests:
67         cpu: 100m
68         memory: 128Mi
69       limits:
70         cpu: 500m
71         memory: 512Mi
72
73     # Environment variables
74     env:
75     - name: ENV
76       value: "production"
77     - name: LOG_LEVEL
78       value: "info"
79     - name: DB_HOST
```

```

80         valueFrom:
81             configMapKeyRef:
82                 name: app-config
83                 key: database.host
84     - name: DB_PASSWORD
85       valueFrom:
86         secretKeyRef:
87             name: db-credentials
88             key: password
89
90     # Volume mounts
91     volumeMounts:
92     - name: config
93       mountPath: /etc/app/config
94       readOnly: true
95     - name: cache
96       mountPath: /var/cache/app
97
98     # Security context
99     securityContext:
100         runAsNonRoot: true
101         runAsUser: 1000
102         fsGroup: 1000
103
104     # Image pull secrets
105     imagePullSecrets:
106     - name: registry-credentials
107
108     # Volumes
109     volumes:
110     - name: config
111       configMap:
112         name: app-config
113     - name: cache
114       emptyDir: {}
115
116 ---
117 # Service
118 apiVersion: v1
119 kind: Service
120 metadata:
121     name: web-app-service
122     namespace: production
123 spec:
124     selector:
125         app: web-app
126     ports:
127     - port: 80
128       targetPort: 8080
129       protocol: TCP
130       name: http
131     type: ClusterIP
132     sessionAffinity: ClientIP
133
134 ---
135 # Ingress
136 apiVersion: networking.k8s.io/v1
137 kind: Ingress

```



```
138 metadata:
139   name: web-app-ingress
140   namespace: production
141   annotations:
142     kubernetes.io/ingress.class: nginx
143     cert-manager.io/cluster-issuer: letsencrypt-prod
144     nginx.ingress.kubernetes.io/rate-limit: "100"
145 spec:
146   tls:
147   - hosts:
148     - app.example.com
149     secretName: web-app-tls
150   rules:
151   - host: app.example.com
152     http:
153       paths:
154       - path: /
155         pathType: Prefix
156         backend:
157           service:
158             name: web-app-service
159             port:
160               number: 80
161
162 ---
163 # HorizontalPodAutoscaler
164 apiVersion: autoscaling/v2
165 kind: HorizontalPodAutoscaler
166 metadata:
167   name: web-app-hpa
168   namespace: production
169 spec:
170   scaleTargetRef:
171     apiVersion: apps/v1
172     kind: Deployment
173     name: web-app
174   minReplicas: 3
175   maxReplicas: 10
176   metrics:
177   - type: Resource
178     resource:
179       name: cpu
180       target:
181         type: Utilization
182         averageUtilization: 70
183   - type: Resource
184     resource:
185       name: memory
186       target:
187         type: Utilization
188         averageUtilization: 80
189
190 ---
191 # ConfigMap
192 apiVersion: v1
193 kind: ConfigMap
194 metadata:
195   name: app-config
```

```

196     namespace: production
197 data:
198     database.host: "postgres.database.svc.cluster.local"
199     database.port: "5432"
200     redis.host: "redis.cache.svc.cluster.local"
201     app.config.json: |
202     {
203         "features": {
204             "beta": false,
205             "analytics": true
206         }
207     }

```

### 7.5.3 Gestione Secrets Kubernetes

Listing 7.11: Secrets Management

```

1  # Create secret da file
2  kubectl create secret generic db-credentials \
3      --from-literal=username=admin \
4      --from-literal=password=supersecret \
5      --namespace=production
6
7  # Create secret da file
8  kubectl create secret generic tls-cert \
9      --from-file=tls.crt=./server.crt \
10     --from-file=tls.key=./server.key \
11     --namespace=production
12
13 # Create Docker registry secret
14 kubectl create secret docker-registry registry-credentials \
15     --docker-server=myregistry.io \
16     --docker-username=user \
17     --docker-password=pass \
18     --docker-email=user@example.com \
19     --namespace=production
20
21 # Encrypt secrets at rest (encryption config)
22 # /etc/kubernetes/encryption-config.yaml
23 cat <<EOF > encryption-config.yaml
24 apiVersion: apiserver.config.k8s.io/v1
25 kind: EncryptionConfiguration
26 resources:
27   - resources:
28       - secrets
29     providers:
30       - aescbc:
31           keys:
32             - name: key1
33               secret: $(head -c 32 /dev/urandom | base64)
34       - identity: {}
35 EOF

```

## 7.6 Load Balancing e Service Discovery

### 7.6.1 Kubernetes Services

Listing 7.12: Service Types

```
1 # ClusterIP (default) - Internal only
2 apiVersion: v1
3 kind: Service
4 metadata:
5   name: backend-service
6 spec:
7   type: ClusterIP
8   selector:
9     app: backend
10  ports:
11    - port: 80
12      targetPort: 8080
13
14 ---
15 # NodePort - Exposed on each Node
16 apiVersion: v1
17 kind: Service
18 metadata:
19   name: web-nodeport
20 spec:
21   type: NodePort
22   selector:
23     app: web
24  ports:
25    - port: 80
26      targetPort: 8080
27      nodePort: 30080 # 30000-32767
28
29 ---
30 # LoadBalancer - Cloud provider integration
31 apiVersion: v1
32 kind: Service
33 metadata:
34   name: web-lb
35 spec:
36   type: LoadBalancer
37   selector:
38     app: web
39  ports:
40    - port: 80
41      targetPort: 8080
42
43 ---
44 # Headless Service - Direct pod access
45 apiVersion: v1
46 kind: Service
47 metadata:
48   name: database-headless
49 spec:
50   clusterIP: None # Headless
51   selector:
52     app: database
53  ports:
54    - port: 5432
```

## 7.7 Advanced Health Checks

### 7.7.1 Multi-Level Health Checks

Listing 7.13: Health Check Endpoints in Go

```

1 // healthcheck.go
2 package main
3
4 import (
5     "database/sql"
6     "encoding/json"
7     "net/http"
8     "time"
9 )
10
11 type HealthChecker struct {
12     db      *sql.DB
13     redis   *RedisClient
14 }
15
16 // Liveness: Is the app running?
17 func (h *HealthChecker) LivenessHandler(w http.ResponseWriter, r *http.
    Request) {
18     w.WriteHeader(http.StatusOK)
19     w.Write([]byte("OK"))
20 }
21
22 // Readiness: Can the app serve traffic?
23 func (h *HealthChecker) ReadinessHandler(w http.ResponseWriter, r *http.
    Request) {
24     status := map[string]interface{}{
25         "status": "UP",
26         "checks": make(map[string]string),
27     }
28
29     // Check database
30     ctx, cancel := context.WithTimeout(r.Context(), 2*time.Second)
31     defer cancel()
32
33     if err := h.db.PingContext(ctx); err != nil {
34         status["status"] = "DOWN"
35         status["checks"].(map[string]string)["database"] = "DOWN"
36         w.WriteHeader(http.StatusServiceUnavailable)
37     } else {
38         status["checks"].(map[string]string)["database"] = "UP"
39     }
40
41     // Check Redis
42     if err := h.redis.Ping(ctx); err != nil {
43         status["status"] = "DOWN"
44         status["checks"].(map[string]string)["redis"] = "DOWN"
45         w.WriteHeader(http.StatusServiceUnavailable)
46     } else {
47         status["checks"].(map[string]string)["redis"] = "UP"
48     }
49
50     json.NewEncoder(w).Encode(status)
51 }

```

```
52
53 // Startup: Is initialization complete?
54 func (h *HealthChecker) StartupHandler(w http.ResponseWriter, r *http.
    Request) {
55     if !h.isInitialized() {
56         w.WriteHeader(http.StatusServiceUnavailable)
57         w.Write([]byte("Initializing..."))
58         return
59     }
60     w.WriteHeader(http.StatusOK)
61     w.Write([]byte("Ready"))
62 }
```

## 7.8 Deployment Automation

### 7.8.1 GitOps con ArgoCD

Listing 7.14: ArgoCD Application

```
1 # argocd-application.yaml
2 apiVersion: argoproj.io/v1alpha1
3 kind: Application
4 metadata:
5     name: web-app
6     namespace: argocd
7 spec:
8     project: default
9
10    source:
11        repoURL: https://github.com/myorg/k8s-manifests
12        targetRevision: main
13        path: apps/web-app/production
14
15    destination:
16        server: https://kubernetes.default.svc
17        namespace: production
18
19    syncPolicy:
20        automated:
21            prune: true      # Delete resources not in Git
22            selfHeal: true   # Auto-sync on drift
23            allowEmpty: false
24        syncOptions:
25            - CreateNamespace=true
26        retry:
27            limit: 5
28            backoff:
29                duration: 5s
30                factor: 2
31                maxDuration: 3m
```

## 7.9 Best Practice Deployment

### Production Deployment Checklist

1. **Health Checks:** Implementare liveness, readiness, startup probes
2. **Resource Limits:** Definire CPU/memory requests e limits
3. **Rolling Updates:** Configurare maxSurge e maxUnavailable
4. **Secrets:** Mai hardcode credentials, usare Secrets/Vault
5. **Monitoring:** Prometheus metrics, Grafana dashboards
6. **Logging:** Centralized logging (ELK, Loki)
7. **Security:** NetworkPolicies, PodSecurityPolicies
8. **Backup:** Velero per backup Kubernetes
9. **Disaster Recovery:** Multi-zone/region deployment
10. **GitOps:** Versioned infrastructure as code

## 7.10 Errori Comuni

- **Errore:** Deployment senza health checks
  - **Conseguenza:** Traffic inviato a pods non pronti
  - **Soluzione:** Implementare readiness probe
- **Errore:** Resource limits non configurati
  - **Conseguenza:** OOMKilled, performance degradation
  - **Soluzione:** Profiling e configurazione requests/limits
- **Errore:** Secrets in ConfigMaps o environment variables
  - **Conseguenza:** Credential exposure
  - **Soluzione:** Usare Kubernetes Secrets + encryption at rest

## 7.11 Riepilogo

Abbiamo esplorato strategie di deployment production-ready: blue-green per switch istantanei, canary per rollout graduati, rolling updates per zero downtime. Docker Swarm offre orchestrazione semplice per cluster piccoli, mentre Kubernetes fornisce piattaforma enterprise-grade con autoscaling, service discovery, e GitOps integration.

## 7.12 Riferimenti

- Kubernetes Documentation: <https://kubernetes.io/docs/>
- Docker Swarm: <https://docs.docker.com/engine/swarm/>
- ArgoCD GitOps: <https://argo-cd.readthedocs.io/>

- Prometheus Monitoring: <https://prometheus.io/docs/>





# Capitolo 8

## CI/CD con Docker

### 8.1 Introduzione

L'integrazione continua e il deployment continuo (CI/CD) con Docker trasformano il processo di sviluppo, testing e rilascio del software. Questo capitolo esplora pipeline complete con GitHub Actions, GitLab CI, e best practices per containerized workflows.

#### Mappa del capitolo

**Sezioni:** CI/CD fundamentals, GitHub Actions workflows, GitLab CI pipelines, Docker build optimization, Multi-stage testing, Security scanning, Container registry management, Deployment automation, Rollback strategies.

### 8.2 Obiettivi di Apprendimento

- Implementare pipeline CI/CD complete per applicazioni Docker
- Ottimizzare Docker builds con layer caching e multi-stage
- Integrare security scanning (Trivy, Snyk) nelle pipeline
- Configurare automated deployments con rollback
- Gestire container registries e image versioning

### 8.3 CI/CD Pipeline Architecture

#### Fasi Pipeline Tipica

1. **Build:** Compilazione applicazione e Docker image
2. **Test:** Unit tests, integration tests, e2e tests
3. **Security Scan:** Vulnerability scanning di dependencies e image
4. **Push:** Pubblicazione image su container registry
5. **Deploy:** Deployment automatico su staging/production
6. **Verify:** Health checks e smoke tests post-deployment
7. **Notify:** Notifiche Slack/Teams/Email

## 8.4 GitHub Actions Complete Workflow

### 8.4.1 Multi-Stage CI/CD Pipeline

Listing 8.1: GitHub Actions - Complete Production Pipeline

```

1 # .github/workflows/docker-ci-cd.yml
2 name: Docker CI/CD Pipeline
3
4 on:
5   push:
6     branches: [main, develop]
7     tags: ['v*']
8   pull_request:
9     branches: [main]
10
11 env:
12   REGISTRY: ghcr.io
13   IMAGE_NAME: ${GITHUB_REPOSITORY}
14   DOCKER_BUILDKIT: 1
15
16 jobs:
17   # JOB 1: Build and Test Application
18   build-and-test:
19     runs-on: ubuntu-latest
20     permissions:
21       contents: read
22       packages: write
23
24     steps:
25       - name: Checkout code
26         uses: actions/checkout@v4
27         with:
28           fetch-depth: 0 # Full history for better caching
29
30       - name: Set up Docker Buildx
31         uses: docker/setup-buildx-action@v3
32         with:
33           driver-opts: |
34             image=moby/buildkit:latest
35             network=host
36
37       - name: Cache Docker layers
38         uses: actions/cache@v3
39         with:
40           path: /tmp/.buildx-cache
41           key: ${RUNNER_OS}-buildx-${GITHUB_SHA}
42           restore-keys: |
43             ${RUNNER_OS}-buildx-
44
45       - name: Build test image
46         uses: docker/build-push-action@v5
47         with:
48           context: .
49           target: test # Multi-stage build target
50           push: false
51           load: true
52           tags: myapp:test
53           cache-from: type=local,src=/tmp/.buildx-cache

```

```

54         cache-to: type=local,dest=/tmp/.buildx-cache-new,mode=max
55
56     - name: Run unit tests
57       run: |
58         docker run --rm myapp:test npm run test:unit
59
60     - name: Run integration tests
61       run: |
62         docker-compose -f docker-compose.test.yml up \
63           --abort-on-container-exit \
64           --exit-code-from app
65
66     - name: Upload test results
67       if: always()
68       uses: actions/upload-artifact@v3
69       with:
70         name: test-results
71         path: |
72           coverage/
73           test-results/
74
75     # Rotate cache to prevent unlimited growth
76     - name: Move cache
77       run: |
78         rm -rf /tmp/.buildx-cache
79         mv /tmp/.buildx-cache-new /tmp/.buildx-cache
80
81     # JOB 2: Security Scanning
82     security-scan:
83       runs-on: ubuntu-latest
84       needs: build-and-test
85       permissions:
86         contents: read
87         security-events: write
88
89       steps:
90       - name: Checkout code
91         uses: actions/checkout@v4
92
93       - name: Build image for scanning
94         run: |
95         docker build -t myapp:scan .
96
97       - name: Run Trivy vulnerability scanner
98         uses: aquasecurity/trivy-action@master
99         with:
100           image-ref: myapp:scan
101           format: 'sarif'
102           output: 'trivy-results.sarif'
103           severity: 'CRITICAL,HIGH'
104           exit-code: '1' # Fail on vulnerabilities
105
106       - name: Upload Trivy results to GitHub Security
107         uses: github/codeql-action/upload-sarif@v2
108         if: always()
109         with:
110           sarif_file: 'trivy-results.sarif'
111

```

```

112   - name: Run Snyk security scan
113     uses: snyk/actions/docker@master
114     env:
115       SNYK_TOKEN: ${ secrets.SNYK_TOKEN }
116     with:
117       image: myapp:scan
118       args: --severity-threshold=high
119
120   - name: Scan Dockerfile with Hadolint
121     uses: hadolint/hadolint-action@v3.1.0
122     with:
123       dockerfile: Dockerfile
124       failure-threshold: warning
125
126 # JOB 3: Build and Push Production Image
127 build-and-push:
128   runs-on: ubuntu-latest
129   needs: [build-and-test, security-scan]
130   if: github.event_name != 'pull_request'
131   permissions:
132     contents: read
133     packages: write
134
135   outputs:
136     image-tag: ${ steps.meta.outputs.tags }
137     image-digest: ${ steps.build.outputs.digest }
138
139   steps:
140     - name: Checkout code
141       uses: actions/checkout@v4
142
143     - name: Set up QEMU
144       uses: docker/setup-qemu-action@v3
145
146     - name: Set up Docker Buildx
147       uses: docker/setup-buildx-action@v3
148
149     - name: Login to GitHub Container Registry
150       uses: docker/login-action@v3
151       with:
152         registry: ${ env.REGISTRY }
153         username: ${ github.actor }
154         password: ${ secrets.GITHUB_TOKEN }
155
156     - name: Extract metadata
157       id: meta
158       uses: docker/metadata-action@v5
159       with:
160         images: ${ env.REGISTRY }/${ env.IMAGE_NAME }
161         tags: |
162           type=ref,event=branch
163           type=semver,pattern={{version}}
164           type=semver,pattern={{major}}.{{minor}}
165           type=sha,prefix={{branch}}-
166           type=raw,value=latest,enable={{is_default_branch}}
167
168     - name: Build and push multi-arch image
169       id: build

```

```

170     uses: docker/build-push-action@v5
171     with:
172       context: .
173       platforms: linux/amd64,linux/arm64
174       push: true
175       tags: ${{ steps.meta.outputs.tags }}
176       labels: ${{ steps.meta.outputs.labels }}
177       cache-from: type=registry,ref=${{ env.REGISTRY }}/${{ env.
         IMAGE_NAME }}:buildcache
178       cache-to: type=registry,ref=${{ env.REGISTRY }}/${{ env.
         IMAGE_NAME }}:buildcache,mode=max
179       build-args: |
180         BUILD_DATE=${{ github.event.repository.updated_at }}
181         VCS_REF=${{ github.sha }}
182         VERSION=${{ steps.meta.outputs.version }}
183
184     - name: Sign image with Cosign
185       env:
186         COSIGN_EXPERIMENTAL: 1
187       run: |
188         cosign sign --yes \
189           ${{ env.REGISTRY }}/${{ env.IMAGE_NAME }}@${{ steps.build.
             outputs.digest }}
190
191 # JOB 4: Deploy to Staging
192 deploy-staging:
193   runs-on: ubuntu-latest
194   needs: build-and-push
195   environment:
196     name: staging
197     url: https://staging.example.com
198   if: github.ref == 'refs/heads/develop'
199
200   steps:
201   - name: Checkout deployment manifests
202     uses: actions/checkout@v4
203     with:
204       repository: myorg/k8s-manifests
205       token: ${{ secrets.DEPLOY_TOKEN }}
206
207   - name: Setup kubectl
208     uses: azure/setup-kubectl@v3
209
210   - name: Configure kubeconfig
211     run: |
212       echo "${{ secrets.KUBECONFIG_STAGING }}" | base64 -d >
         kubeconfig
213       export KUBECONFIG=kubeconfig
214
215   - name: Update image tag
216     run: |
217       cd apps/myapp/staging
218       kustomize edit set image \
219         myapp=${{ needs.build-and-push.outputs.image-tag }}
220
221   - name: Deploy to staging
222     run: |
223       kubectl apply -k apps/myapp/staging

```

```

224     kubectl rollout status deployment/myapp -n staging --timeout=5m
225
226 - name: Run smoke tests
227   run: |
228     sleep 30
229     curl -f https://staging.example.com/health || exit 1
230
231 - name: Notify Slack
232   if: always()
233   uses: slackapi/slack-github-action@v1
234   with:
235     payload: |
236       {
237         "text": "Staging deployment: ${ job.status }",
238         "blocks": [
239           {
240             "type": "section",
241             "text": {
242               "type": "mrkdwn",
243               "text": "*Staging Deployment*\nStatus: ${ job.status }\nImage: ${ needs.build-and-push.outputs.image-tag }"
244             }
245           }
246         ]
247       }
248   env:
249     SLACK_WEBHOOK_URL: ${ secrets.SLACK_WEBHOOK }
250
251 # JOB 5: Deploy to Production
252 deploy-production:
253   runs-on: ubuntu-latest
254   needs: build-and-push
255   environment:
256     name: production
257     url: https://example.com
258   if: startsWith(github.ref, 'refs/tags/v')
259
260   steps:
261 - name: Checkout deployment manifests
262   uses: actions/checkout@v4
263   with:
264     repository: myorg/k8s-manifests
265     token: ${ secrets.DEPLOY_TOKEN }
266
267 - name: Setup kubectl
268   uses: azure/setup-kubectl@v3
269
270 - name: Configure kubeconfig
271   run: |
272     echo "${ secrets.KUBECONFIG_PROD }" | base64 -d > kubeconfig
273     export KUBECONFIG=kubeconfig
274
275 - name: Create deployment backup
276   run: |
277     kubectl get deployment myapp -n production -o yaml > backup-
278       deployment.yaml

```

```

278     kubectl get configmap -n production -o yaml > backup-configmap.
        yaml
279
280 - name: Update image tag
281   run: |
282     cd apps/myapp/production
283     kustomize edit set image \
284       myapp=${{ needs.build-and-push.outputs.image-tag }}
285
286 - name: Deploy to production (Blue-Green)
287   run: |
288     # Deploy to green environment
289     kubectl apply -k apps/myapp/production/green
290     kubectl rollout status deployment/myapp-green -n production --
        timeout=10m
291
292     # Run production smoke tests
293     ./scripts/smoke-test.sh https://green.example.com
294
295     # Switch traffic to green
296     kubectl patch service myapp -n production \
297       -p '{"spec":{"selector":{"version":"green"}}}'
298
299     # Wait and verify
300     sleep 60
301
302     # Scale down blue
303     kubectl scale deployment/myapp-blue -n production --replicas=0
304
305 - name: Verify deployment
306   run: |
307     kubectl get pods -n production
308     kubectl get events -n production --sort-by='.lastTimestamp'
309
310 - name: Rollback on failure
311   if: failure()
312   run: |
313     kubectl apply -f backup-deployment.yaml
314     kubectl patch service myapp -n production \
315       -p '{"spec":{"selector":{"version":"blue"}}}'
316
317 - name: Create GitHub Release
318   if: success()
319   uses: actions/create-release@v1
320   env:
321     GITHUB_TOKEN: ${ secrets.GITHUB_TOKEN }
322   with:
323     tag_name: ${ github.ref }
324     release_name: Release ${ github.ref }
325     body: |
326       Production deployment successful
327       Image: ${ needs.build-and-push.outputs.image-tag }
328       Digest: ${ needs.build-and-push.outputs.image-digest }
329
330 # JOB 6: Performance Testing
331 performance-test:
332   runs-on: ubuntu-latest
333   needs: deploy-staging

```

```

334     if: github.ref == 'refs/heads/develop'
335
336     steps:
337     - name: Checkout code
338       uses: actions/checkout@v4
339
340     - name: Run k6 load test
341       uses: grafana/k6-action@v0.3.0
342       with:
343         filename: tests/load-test.js
344         cloud: true
345         token: ${ secrets.K6_CLOUD_TOKEN }}
346
347     - name: Upload performance results
348       uses: actions/upload-artifact@v3
349       with:
350         name: performance-results
351         path: results/

```

## 8.5 GitLab CI Complete Pipeline

### 8.5.1 GitLab CI/CD Configuration

Listing 8.2: .gitlab-ci.yml - Enterprise Pipeline

```

1  # .gitlab-ci.yml
2  variables:
3    DOCKER_DRIVER: overlay2
4    DOCKER_TLS_CERTDIR: "/certs"
5    REGISTRY: $CI_REGISTRY
6    IMAGE: $CI_REGISTRY_IMAGE
7    DOCKER_BUILDKIT: 1
8
9  stages:
10   - build
11   - test
12   - security
13   - package
14   - deploy-staging
15   - deploy-production
16
17  # Template per Docker build con cache
18  .docker-build-template: &docker-build
19    image: docker:24
20    services:
21      - docker:24-dind
22    before_script:
23      - docker login -u $CI_REGISTRY_USER -p $CI_REGISTRY_PASSWORD
24        $CI_REGISTRY
25
26  # BUILD STAGE
27  build:app:
28    <<: *docker-build
29    stage: build
30    script:
31      - |
32        docker build \

```



```

32     --cache-from $IMAGE:latest \
33     --build-arg BUILDKIT_INLINE_CACHE=1 \
34     --target builder \
35     -t $IMAGE:builder-$CI_COMMIT_SHA \
36     .
37   - docker push $IMAGE:builder-$CI_COMMIT_SHA
38   rules:
39   - if: $CI_PIPELINE_SOURCE == "merge_request_event"
40   - if: $CI_COMMIT_BRANCH == "main"
41   - if: $CI_COMMIT_BRANCH == "develop"
42
43 # TEST STAGE
44 test:unit:
45   <<: *docker-build
46   stage: test
47   dependencies:
48   - build:app
49   script:
50   - docker pull $IMAGE:builder-$CI_COMMIT_SHA
51   - |
52     docker run --rm \
53       -v $PWD/coverage:/app/coverage \
54       $IMAGE:builder-$CI_COMMIT_SHA \
55       npm run test:unit -- --coverage
56   coverage: '/Statements\s+:\s+(\d+\.\d+)\%/'
57   artifacts:
58     reports:
59     junit: coverage/junit.xml
60     coverage_report:
61     coverage_format: cobertura
62     path: coverage/cobertura-coverage.xml
63   paths:
64   - coverage/
65   expire_in: 1 week
66
67 test:integration:
68   <<: *docker-build
69   stage: test
70   services:
71   - postgres:15-alpine
72   - redis:7-alpine
73   variables:
74     POSTGRES_DB: testdb
75     POSTGRES_USER: testuser
76     POSTGRES_PASSWORD: testpass
77     DATABASE_URL: postgres://testuser:testpass@postgres:5432/testdb
78     REDIS_URL: redis://redis:6379
79   script:
80   - docker pull $IMAGE:builder-$CI_COMMIT_SHA
81   - |
82     docker run --rm \
83       --network host \
84       -e DATABASE_URL=$DATABASE_URL \
85       -e REDIS_URL=$REDIS_URL \
86       $IMAGE:builder-$CI_COMMIT_SHA \
87       npm run test:integration
88   artifacts:
89     reports:

```

```

90     junit: test-results/integration.xml
91
92 test:e2e:
93     image: cypress/browsers:latest
94     stage: test
95     services:
96         - name: $IMAGE:builder-$CI_COMMIT_SHA
97           alias: app
98     script:
99         - npm ci
100         - npm run cy:run --env baseUrl=http://app:3000
101     artifacts:
102         when: always
103         paths:
104             - cypress/videos/
105             - cypress/screenshots/
106         expire_in: 1 week
107
108 # SECURITY STAGE
109 security:trivy:
110     image: aquasec/trivy:latest
111     stage: security
112     script:
113         - trivy image --exit-code 0 --no-progress --format json -o trivy-
114           report.json $IMAGE:builder-$CI_COMMIT_SHA
115         - trivy image --exit-code 1 --severity CRITICAL --no-progress $IMAGE
116           :builder-$CI_COMMIT_SHA
117     artifacts:
118         reports:
119             container_scanning: trivy-report.json
120     allow_failure: false
121
122 security:sast:
123     stage: security
124     image: returntocorp/semgrep
125     script:
126         - semgrep --config=auto --json --output=sast-report.json .
127     artifacts:
128         reports:
129             sast: sast-report.json
130
131 security:dependency-scan:
132     image: node:20-alpine
133     stage: security
134     script:
135         - npm audit --audit-level=high --json > npm-audit.json
136     artifacts:
137         reports:
138             dependency_scanning: npm-audit.json
139     allow_failure: true
140
141 security:secrets-scan:
142     image: trufflesecurity/trufflehog:latest
143     stage: security
144     script:
145         - trufflehog git file://. --json > secrets-report.json
146     artifacts:
147         paths:

```

```

146     - secrets-report.json
147     allow_failure: false
148
149 # PACKAGE STAGE
150 package:production:
151   <<: *docker-build
152   stage: package
153   script:
154     # Build final production image
155     - |
156       docker build \
157         --cache-from $IMAGE:latest \
158         --build-arg BUILDKIT_INLINE_CACHE=1 \
159         --label "org.opencontainers.image.created=$(date -Iseconds)" \
160         --label "org.opencontainers.image.revision=$CI_COMMIT_SHA" \
161         --label "org.opencontainers.image.version=$CI_COMMIT_TAG" \
162         -t $IMAGE:$CI_COMMIT_SHA \
163         -t $IMAGE:$CI_COMMIT_REF_SLUG \
164         .
165
166     # Push all tags
167     - docker push $IMAGE:$CI_COMMIT_SHA
168     - docker push $IMAGE:$CI_COMMIT_REF_SLUG
169
170     # Tag latest if main branch
171     - |
172       if [ "$CI_COMMIT_BRANCH" == "main" ]; then
173         docker tag $IMAGE:$CI_COMMIT_SHA $IMAGE:latest
174         docker push $IMAGE:latest
175       fi
176
177     # Tag with version if tagged commit
178     - |
179       if [ -n "$CI_COMMIT_TAG" ]; then
180         docker tag $IMAGE:$CI_COMMIT_SHA $IMAGE:$CI_COMMIT_TAG
181         docker push $IMAGE:$CI_COMMIT_TAG
182       fi
183   only:
184     - main
185     - develop
186     - tags
187
188 # DEPLOY STAGING
189 deploy:staging:
190   stage: deploy-staging
191   image: bitnami/kubectl:latest
192   environment:
193     name: staging
194     url: https://staging.example.com
195     on_stop: stop:staging
196   script:
197     - kubectl config use-context staging-cluster
198     - |
199       kubectl set image deployment/myapp \
200         myapp=$IMAGE:$CI_COMMIT_SHA \
201         -n staging
202     - kubectl rollout status deployment/myapp -n staging --timeout=5m
203     - sleep 30

```

```

204     - curl -f https://staging.example.com/health || exit 1
205 only:
206     - develop
207
208 stop:staging:
209     stage: deploy-staging
210     image: bitnami/kubectl:latest
211     environment:
212         name: staging
213         action: stop
214     script:
215         - kubectl scale deployment/myapp --replicas=0 -n staging
216     when: manual
217     only:
218         - develop
219
220 # DEPLOY PRODUCTION
221 deploy:production:
222     stage: deploy-production
223     image: bitnami/kubectl:latest
224     environment:
225         name: production
226         url: https://example.com
227     before_script:
228         - kubectl config use-context production-cluster
229     script:
230         # Backup current deployment
231         - kubectl get deployment myapp -n production -o yaml > backup.yaml
232
233     # Canary deployment (10%)
234     - |
235         kubectl apply -f - <<EOF
236         apiVersion: apps/v1
237         kind: Deployment
238         metadata:
239             name: myapp-canary
240             namespace: production
241         spec:
242             replicas: 1
243             selector:
244                 matchLabels:
245                     app: myapp
246                     track: canary
247             template:
248                 metadata:
249                     labels:
250                         app: myapp
251                         track: canary
252                 spec:
253                     containers:
254                         - name: myapp
255                           image: $IMAGE:$CI_COMMIT_SHA
256         EOF
257
258     - sleep 120 # Monitor canary
259
260 # Check error rate
261     - |

```

```

262     ERROR_RATE=$(curl -s 'http://prometheus:9090/api/v1/query?query=
        error_rate{track="canary"}' | jq -r '.data.result[0].value[1]')
263     if (( $(echo "$ERROR_RATE > 0.05" | bc -l) )); then
264         echo "Canary error rate too high: $ERROR_RATE"
265         kubectl delete deployment myapp-canary -n production
266         exit 1
267     fi
268
269     # Full rollout
270     - |
271     kubectl set image deployment/myapp \
272         myapp=$IMAGE:$CI_COMMIT_SHA \
273         -n production
274     - kubectl rollout status deployment/myapp -n production --timeout=10
        m
275
276     # Cleanup canary
277     - kubectl delete deployment myapp-canary -n production
278
279     after_script:
280     - |
281         if [ $CI_JOB_STATUS == 'failed' ]; then
282             echo "Deployment failed, rolling back..."
283             kubectl apply -f backup.yaml
284         fi
285
286     only:
287     - tags
288     when: manual # Require manual approval for production
289
290     # ROLLBACK
291     rollback:production:
292         stage: deploy-production
293         image: bitnami/kubectl:latest
294         environment:
295             name: production
296         script:
297             - kubectl config use-context production-cluster
298             - kubectl rollout undo deployment/myapp -n production
299             - kubectl rollout status deployment/myapp -n production
300         when: manual
301     only:
302     - tags

```

## 8.6 Docker Build Optimization

### 8.6.1 Multi-Stage Dockerfile Optimized

Listing 8.3: Optimized Multi-Stage Build

```

1 # Dockerfile - Production optimized
2 # syntax=docker/dockerfile:1.4
3
4 # Stage 1: Base dependencies
5 FROM node:20-alpine AS base
6 WORKDIR /app
7 RUN apk add --no-cache \

```

```

8     dumb-init \
9     ca-certificates
10 ENV NODE_ENV=production
11
12 # Stage 2: Dependencies
13 FROM base AS dependencies
14 COPY package*.json ./
15 RUN --mount=type=cache,target=/root/.npm \
16     npm ci --only=production && \
17     npm cache clean --force
18
19 # Stage 3: Build
20 FROM base AS builder
21 COPY package*.json ./
22 RUN --mount=type=cache,target=/root/.npm \
23     npm ci
24 COPY . .
25 RUN npm run build && \
26     npm prune --production
27
28 # Stage 4: Test
29 FROM builder AS test
30 ENV NODE_ENV=test
31 RUN npm ci
32 COPY --from=builder /app/dist ./dist
33 CMD ["npm", "run", "test"]
34
35 # Stage 5: Production
36 FROM base AS production
37
38 # Security: non-root user
39 RUN addgroup -g 1001 -S nodejs && \
40     adduser -S nodejs -u 1001
41
42 # Copy only production files
43 COPY --from=dependencies --chown=nodejs:nodejs /app/node_modules ./
44     node_modules
45 COPY --from=builder --chown=nodejs:nodejs /app/dist ./dist
46 COPY --chown=nodejs:nodejs package.json ./
47
48 # Health check
49 HEALTHCHECK --interval=30s --timeout=3s --start-period=40s --retries=3 \
50     CMD node healthcheck.js
51
52 USER nodejs
53 EXPOSE 3000
54
55 # Use dumb-init for proper signal handling
56 ENTRYPOINT ["dumb-init", "--"]
57 CMD ["node", "dist/server.js"]
58
59 # Labels
60 LABEL org.opencontainers.image.source="https://github.com/myorg/myapp"
61 LABEL org.opencontainers.image.description="Production-optimized Node.js
    application"
    LABEL org.opencontainers.image.licenses="MIT"

```

## 8.7 Test Automation

### 8.7.1 Docker Compose for Testing

Listing 8.4: docker-compose.test.yml

```
1 version: '3.8'
2
3 services:
4   app:
5     build:
6       context: .
7       target: test
8     environment:
9       - NODE_ENV=test
10      - DATABASE_URL=postgres://test:test@postgres:5432/testdb
11      - REDIS_URL=redis://redis:6379
12     depends_on:
13       postgres:
14         condition: service_healthy
15       redis:
16         condition: service_started
17     command: npm run test:all
18
19   postgres:
20     image: postgres:15-alpine
21     environment:
22       POSTGRES_DB: testdb
23       POSTGRES_USER: test
24       POSTGRES_PASSWORD: test
25     healthcheck:
26       test: ["CMD-SHELL", "pg_isready -U test"]
27       interval: 10s
28       timeout: 5s
29       retries: 5
30     tmpfs:
31       - /var/lib/postgresql/data
32
33   redis:
34     image: redis:7-alpine
35     healthcheck:
36       test: ["CMD", "redis-cli", "ping"]
37       interval: 10s
38       timeout: 3s
39       retries: 3
```

## 8.8 Container Registry Management

### 8.8.1 Multi-Registry Push

Listing 8.5: Push to Multiple Registries

```
1 #!/bin/bash
2 # multi-registry-push.sh
3
4 set -e
5
```

```

6 IMAGE_NAME="myapp"
7 VERSION="${1:-latest}"
8
9 REGISTRIES=(
10     "docker.io/myorg"
11     "ghcr.io/myorg"
12     "gcr.io/myproject"
13     "myregistry.example.com"
14 )
15
16 # Build once
17 docker build -t ${IMAGE_NAME}:${VERSION} .
18
19 # Push to all registries
20 for registry in "${REGISTRIES[@]"}; do
21     echo "Pushing to $registry..."
22
23     docker tag ${IMAGE_NAME}:${VERSION} ${registry}/${IMAGE_NAME}:${VERSION}
24     docker tag ${IMAGE_NAME}:${VERSION} ${registry}/${IMAGE_NAME}:latest
25
26     docker push ${registry}/${IMAGE_NAME}:${VERSION}
27     docker push ${registry}/${IMAGE_NAME}:latest
28 done
29
30 # Generate SBOM (Software Bill of Materials)
31 syft ${IMAGE_NAME}:${VERSION} -o spdx-json > sbom.spdx.json
32
33 # Sign images with Cosign
34 for registry in "${REGISTRIES[@]"}; do
35     cosign sign --key cosign.key ${registry}/${IMAGE_NAME}:${VERSION}
36 done
37
38 echo "Image pushed to all registries and signed successfully"

```

## 8.9 Advanced CI/CD Patterns

### 8.9.1 Matrix Testing Strategy

Listing 8.6: GitHub Actions Matrix Testing

```

1 # .github/workflows/matrix-test.yml
2 name: Matrix Testing
3
4 on: [push, pull_request]
5
6 jobs:
7     test:
8         runs-on: ${ matrix.os }
9         strategy:
10             fail-fast: false
11             matrix:
12                 os: [ubuntu-latest, windows-latest, macos-latest]
13                 node: [18, 20, 21]
14                 database: [postgres, mysql, mongodb]
15                 exclude:
16                     # Exclude specific combinations

```



```

17         - os: windows-latest
18           database: mongodb
19
20     steps:
21     - uses: actions/checkout@v4
22
23     - name: Setup Node.js ${ matrix.node }
24       uses: actions/setup-node@v4
25       with:
26         node-version: ${ matrix.node }
27
28     - name: Start database container
29       run: |
30         docker run -d \
31           --name test-db \
32           -e POSTGRES_PASSWORD=test \
33           ${ matrix.database }:latest
34
35     - name: Run tests
36       env:
37         DB_TYPE: ${ matrix.database }
38       run: npm run test:integration

```

## 8.10 Secrets Management in CI/CD

### 8.10.1 Vault Integration

Listing 8.7: GitLab CI with HashiCorp Vault

```

1  # .gitlab-ci.yml with Vault
2  variables:
3    VAULT_ADDR: https://vault.example.com
4
5  deploy:production:
6    stage: deploy
7    id_tokens:
8      VAULT_ID_TOKEN:
9        aud: https://vault.example.com
10   secrets:
11     DATABASE_PASSWORD:
12       vault: production/database/password@secret
13       file: false
14     API_KEY:
15       vault: production/api/key@secret
16       file: false
17   script:
18     - echo "Deploying with secrets from Vault..."
19     - export DB_PASSWORD=$DATABASE_PASSWORD
20     - kubectl create secret generic app-secrets \
21       --from-literal=db-password=$DATABASE_PASSWORD \
22       --from-literal=api-key=$API_KEY \
23       -n production --dry-run=client -o yaml | kubectl apply -f -

```

## 8.11 Best Practices CI/CD

### Production CI/CD Checklist

1. **Build Once, Deploy Many:** Stessa image per tutti gli ambienti
2. **Immutable Tags:** Mai riusare tag (no 'latest' in prod)
3. **Security Scanning:** Integrare Trivy/Snyk in pipeline
4. **Layer Caching:** Usare BuildKit cache per speed
5. **Multi-Stage:** Separare build, test, production stages
6. **Secrets:** Mai hardcode, usare secrets management
7. **Rollback:** Automated rollback on health check failure
8. **Notifications:** Slack/Teams alerts per deployments
9. **Artifact Signing:** Cosign per image signing
10. **SBOM:** Generare Software Bill of Materials

## 8.12 Errori Comuni

- **Errore:** Usare tag 'latest' in production
  - **Conseguenza:** Deployments non riproducibili
  - **Soluzione:** Semantic versioning o SHA commits
- **Errore:** Build senza layer caching
  - **Conseguenza:** Pipeline lente (10+ minuti)
  - **Soluzione:** BuildKit con registry cache
- **Errore:** Secrets in environment variables
  - **Conseguenza:** Exposure in logs/history
  - **Soluzione:** File-based secrets o Vault

## 8.13 Riepilogo

CI/CD con Docker richiede pipeline robuste con build optimization, security scanning, automated testing, e deployment strategies. GitHub Actions e GitLab CI offrono ecosistemi completi per containerized workflows, mentre tools come Trivy, Cosign e Vault garantiscono security best practices.

## 8.14 Riferimenti

- GitHub Actions: <https://docs.github.com/actions>
- GitLab CI: <https://docs.gitlab.com/ee/ci/>
- Trivy Security Scanner: <https://trivy.dev/>

- Cosign Image Signing: <https://github.com/sigstore/cosign>



# Capitolo 9

## Monitoring e Logging

### 9.1 Introduzione

Il monitoring e logging di container Docker è essenziale per production environments. Questo capitolo esplora strategie di observability, centralized logging, metrics collection, distributed tracing, e alerting systems per garantire reliability e troubleshooting efficace.

#### Mappa del capitolo

**Sezioni:** Docker logs management, Centralized logging (ELK, Loki), Prometheus metrics, Grafana dashboards, Distributed tracing, Health checks avanzati, Alerting con Alertmanager, Performance monitoring, Log aggregation patterns.

### 9.2 Obiettivi di Apprendimento

- Implementare centralized logging con ELK Stack e Grafana Loki
- Configurare Prometheus per metrics collection da containers
- Creare Grafana dashboards per visualizzazione real-time
- Implementare distributed tracing con Jaeger
- Configurare alerting rules e notification channels
- Applicare structured logging best practices

### 9.3 Docker Logs Fundamentals

#### 9.3.1 Docker Logging Drivers

Listing 9.1: Docker Compose - Logging Configuration

```
1 # docker-compose.yml
2 version: '3.8'
3
4 services:
5   app:
6     image: myapp:latest
7     logging:
8       driver: "json-file"
9       options:
```

```

10     max-size: "10m"
11     max-file: "3"
12     labels: "production,app"
13     env: "ENV,VERSION"
14
15     nginx:
16       image: nginx:alpine
17       logging:
18         driver: "syslog"
19         options:
20           syslog-address: "tcp://localhost:514"
21           tag: "nginx-{{.Name}}"
22
23     database:
24       image: postgres:15
25       logging:
26         driver: "fluentd"
27         options:
28           fluentd-address: "localhost:24224"
29           tag: "docker.{{.Name}}"
30           fluentd-async: "true"

```

Listing 9.2: Docker Logs Commands

```

1  # Visualizza logs in real-time
2  docker logs -f container_name
3
4  # Logs con timestamp
5  docker logs -t container_name
6
7  # Ultimi N logs
8  docker logs --tail 100 container_name
9
10 # Logs in range temporale
11 docker logs --since 2024-01-01T10:00:00 \
12     --until 2024-01-01T11:00:00 \
13     container_name
14
15 # Follow logs di tutti i container in compose
16 docker-compose logs -f
17
18 # Logs di specifico service
19 docker-compose logs -f app
20
21 # Logs con grep
22 docker logs container_name 2>&1 | grep ERROR

```

## 9.4 Centralized Logging con ELK Stack

### 9.4.1 ELK Stack Setup Completo

Listing 9.3: ELK Stack - Docker Compose

```

1  # docker-compose-elk.yml
2  version: '3.8'
3
4  services:

```

```
5 # Elasticsearch
6 elasticsearch:
7   image: docker.elastic.co/elasticsearch/elasticsearch:8.11.0
8   environment:
9     - discovery.type=single-node
10    - "ES_JAVA_OPTS=-Xms512m -Xmx512m"
11    - xpack.security.enabled=false
12   volumes:
13     - elasticsearch-data:/usr/share/elasticsearch/data
14   ports:
15     - "9200:9200"
16   networks:
17     - elk
18   healthcheck:
19     test: ["CMD-SHELL", "curl -f http://localhost:9200/_cluster/health
20           || exit 1"]
21     interval: 30s
22     timeout: 10s
23     retries: 5
24
25 # Logstash
26 logstash:
27   image: docker.elastic.co/logstash/logstash:8.11.0
28   volumes:
29     - ./logstash/pipeline:/usr/share/logstash/pipeline
30     - ./logstash/config/logstash.yml:/usr/share/logstash/config/
31       logstash.yml
32   ports:
33     - "5000:5000/tcp"
34     - "5000:5000/udp"
35     - "9600:9600"
36   environment:
37     LS_JAVA_OPTS: "-Xmx256m -Xms256m"
38   networks:
39     - elk
40   depends_on:
41     elasticsearch:
42       condition: service_healthy
43
44 # Kibana
45 kibana:
46   image: docker.elastic.co/kibana/kibana:8.11.0
47   ports:
48     - "5601:5601"
49   environment:
50     ELASTICSEARCH_HOSTS: http://elasticsearch:9200
51   networks:
52     - elk
53   depends_on:
54     elasticsearch:
55       condition: service_healthy
56
57 # Filebeat per raccogliere logs da containers
58 filebeat:
59   image: docker.elastic.co/beats/filebeat:8.11.0
60   user: root
61   volumes:
62     - ./filebeat/filebeat.yml:/usr/share/filebeat/filebeat.yml:ro
```

```

61     - /var/lib/docker/containers:/var/lib/docker/containers:ro
62     - /var/run/docker.sock:/var/run/docker.sock:ro
63     command: filebeat -e -strict.perms=false
64     networks:
65     - elk
66     depends_on:
67     elasticsearch:
68     condition: service_healthy
69
70     # Application con structured logging
71     app:
72     image: myapp:latest
73     logging:
74     driver: "json-file"
75     options:
76     max-size: "10m"
77     max-file: "3"
78     labels: "app,production"
79     labels:
80     - "logging=enabled"
81     networks:
82     - elk
83
84     networks:
85     elk:
86     driver: bridge
87
88     volumes:
89     elasticsearch-data:
90     driver: local

```

### 9.4.2 Logstash Pipeline Configuration

Listing 9.4: logstash/pipeline/logstash.conf

```

1  # Logstash pipeline for Docker logs
2  input {
3    beats {
4      port => 5044
5    }
6
7    tcp {
8      port => 5000
9      codec => json
10   }
11
12   # HTTP input per custom logs
13   http {
14     port => 8080
15     codec => json
16   }
17 }
18
19 filter {
20   # Parse Docker JSON logs
21   if [docker][container][name] {
22     mutate {

```



```

23     add_field => {
24         "container_name" => "%{[docker][container][name]}"
25         "container_id" => "%{[docker][container][id]}"
26     }
27 }
28 }
29
30 # Parse application logs (JSON format)
31 if [message] =~ /\~\{.*\}$/ {
32     json {
33         source => "message"
34         target => "app"
35     }
36 }
37
38 # Parse nginx access logs
39 if [container_name] =~ /nginx/ {
40     grok {
41         match => {
42             "message" => '%{IPORHOST:client_ip} - %{USER:user} \[%{HTTPDATE:
                timestamp}\] "%{WORD:method} %{URIPATHPARAM:request} HTTP/%{
                NUMBER:http_version}" %{INT:status_code} %{INT:bytes} "%{DATA
                :referrer}" "%{DATA:user_agent}"',
43         }
44     }
45     date {
46         match => ["timestamp", "dd/MMM/yyyy:HH:mm:ss Z"]
47     }
48 }
49
50 # Extract error severity
51 if [message] =~ /ERROR|FATAL/ {
52     mutate {
53         add_field => { "severity" => "error" }
54     }
55 } else if [message] =~ /WARN/ {
56     mutate {
57         add_field => { "severity" => "warning" }
58     }
59 } else {
60     mutate {
61         add_field => { "severity" => "info" }
62     }
63 }
64
65 # Add geo-location per IP
66 if [client_ip] {
67     geoip {
68         source => "client_ip"
69         target => "geoip"
70     }
71 }
72 }
73
74 output {
75     elasticsearch {
76         hosts => ["elasticsearch:9200"]
77         index => "docker-logs-%{+YYYY.MM.dd}"

```

```
78   }
79
80   # Debug output
81   if [severity] == "error" {
82     stdout {
83       codec => rubydebug
84     }
85   }
86 }
```

### 9.4.3 Filebeat Configuration

Listing 9.5: filebeat/filebeat.yml

```
1 filebeat.inputs:
2 - type: container
3   paths:
4     - '/var/lib/docker/containers/*//*.log'
5   processors:
6     - add_docker_metadata:
7       host: "unix:///var/run/docker.sock"
8     - decode_json_fields:
9       fields: ["message"]
10      target: "json"
11      overwrite_keys: true
12
13 filebeat.autodiscover:
14   providers:
15     - type: docker
16       hints.enabled: true
17       templates:
18         - condition:
19             contains:
20               docker.container.labels.logging: "enabled"
21           config:
22             - type: container
23               paths:
24                 - /var/lib/docker/containers/${data.docker.container.id}
25                   /*.log
26
27 output.logstash:
28   hosts: ["logstash:5044"]
29   loadbalance: true
30
31 logging.level: info
32 logging.to_files: true
33 logging.files:
34   path: /var/log/filebeat
35   name: filebeat
36   keepfiles: 7
37   permissions: 0644
```

## 9.5 Grafana Loki - Lightweight Logging

### 9.5.1 Loki Stack Setup

Listing 9.6: Grafana Loki Stack

```
1 # docker-compose-loki.yml
2 version: '3.8'
3
4 services:
5   loki:
6     image: grafana/loki:2.9.0
7     ports:
8       - "3100:3100"
9     command: -config.file=/etc/loki/local-config.yaml
10    volumes:
11      - ./loki/loki-config.yaml:/etc/loki/local-config.yaml
12      - loki-data:/loki
13    networks:
14      - monitoring
15
16    promtail:
17      image: grafana/promtail:2.9.0
18      volumes:
19        - /var/log:/var/log:ro
20        - /var/lib/docker/containers:/var/lib/docker/containers:ro
21        - ./promtail/promtail-config.yaml:/etc/promtail/config.yaml
22      command: -config.file=/etc/promtail/config.yaml
23      networks:
24        - monitoring
25      depends_on:
26        - loki
27
28    grafana:
29      image: grafana/grafana:10.2.0
30      ports:
31        - "3000:3000"
32      environment:
33        - GF_SECURITY_ADMIN_PASSWORD=admin
34        - GF_USERS_ALLOW_SIGN_UP=false
35      volumes:
36        - grafana-data:/var/lib/grafana
37        - ./grafana/provisioning:/etc/grafana/provisioning
38      networks:
39        - monitoring
40      depends_on:
41        - loki
42
43    networks:
44      monitoring:
45        driver: bridge
46
47    volumes:
48      loki-data:
49      grafana-data:
```

## 9.5.2 Promtail Configuration

Listing 9.7: promtail/promtail-config.yaml

```
1 server:
2   http_listen_port: 9080
```

```

3   grpc_listen_port: 0
4
5   positions:
6     filename: /tmp/positions.yaml
7
8   clients:
9     - url: http://loki:3100/loki/api/v1/push
10
11  scrape_configs:
12    # Docker containers
13    - job_name: docker
14      docker_sd_configs:
15        - host: unix:///var/run/docker.sock
16          refresh_interval: 5s
17      relabel_configs:
18        - source_labels: ['__meta_docker_container_name']
19          regex: '/(.*)'
20          target_label: 'container'
21        - source_labels: ['__meta_docker_container_log_stream']
22          target_label: 'stream'
23        - source_labels: ['
24          __meta_docker_container_label_com_docker_compose_service']
25          target_label: 'service'
26      pipeline_stages:
27        - docker: {}
28        - json:
29            expressions:
30              level: level
31              message: message
32              timestamp: timestamp
33        - labels:
34            level:
35            stream:
36        - timestamp:
37            source: timestamp
38            format: RFC3339Nano
39
40    # System logs
41    - job_name: system
42      static_configs:
43        - targets:
44            - localhost
45          labels:
46            job: varlogs
47            __path__: /var/log/*.log

```

## 9.6 Prometheus Metrics Collection

### 9.6.1 Prometheus Stack

Listing 9.8: Prometheus + Exporters

```

1  # docker-compose-prometheus.yml
2  version: '3.8'
3
4  services:
5    prometheus:

```

```

6      image: prom/prometheus:v2.48.0
7      command:
8          - '--config.file=/etc/prometheus/prometheus.yml'
9          - '--storage.tsdb.path=/prometheus'
10         - '--web.console.libraries=/usr/share/prometheus/console_libraries'
11         - '--web.console.templates=/usr/share/prometheus/consoles'
12         - '--web.enable-lifecycle'
13      ports:
14          - "9090:9090"
15      volumes:
16          - ./prometheus/prometheus.yml:/etc/prometheus/prometheus.yml
17          - ./prometheus/alerts.yml:/etc/prometheus/alerts.yml
18          - prometheus-data:/prometheus
19      networks:
20          - monitoring
21
22      # Node Exporter per metrics di sistema
23      node-exporter:
24          image: prom/node-exporter:v1.7.0
25          command:
26              - '--path.procfs=/host/proc'
27              - '--path.sysfs=/host/sys'
28              - '--collector.filesystem.mount-points-exclude=~/((sys|proc|dev|
                host|etc)($$|/))'
29          volumes:
30              - /proc:/host/proc:ro
31              - /sys:/host/sys:ro
32              - /:/rootfs:ro
33          ports:
34              - "9100:9100"
35          networks:
36              - monitoring
37
38      # cAdvisor per metrics containers
39      cadvisor:
40          image: gcr.io/cadvisor/cadvisor:v0.47.0
41          privileged: true
42          volumes:
43              - /:/rootfs:ro
44              - /var/run:/var/run:ro
45              - /sys:/sys:ro
46              - /var/lib/docker:/var/lib/docker:ro
47              - /dev/disk:/dev/disk:ro
48          ports:
49              - "8080:8080"
50          networks:
51              - monitoring
52
53      # Alertmanager
54      alertmanager:
55          image: prom/alertmanager:v0.26.0
56          command:
57              - '--config.file=/etc/alertmanager/config.yml'
58              - '--storage.path=/alertmanager'
59          ports:
60              - "9093:9093"
61          volumes:

```

```

62     - ./alertmanager/config.yml:/etc/alertmanager/config.yml
63     - alertmanager-data:/alertmanager
64     networks:
65     - monitoring
66
67     # Application con Prometheus metrics
68     app:
69     image: myapp:latest
70     ports:
71     - "8000:8000"
72     environment:
73     - PROMETHEUS_METRICS_PORT=9091
74     labels:
75     - "prometheus.io/scrape=true"
76     - "prometheus.io/port=9091"
77     - "prometheus.io/path=/metrics"
78     networks:
79     - monitoring
80
81     networks:
82     monitoring:
83     driver: bridge
84
85     volumes:
86     prometheus-data:
87     alertmanager-data:

```

## 9.6.2 Prometheus Configuration

Listing 9.9: prometheus/prometheus.yml

```

1 global:
2   scrape_interval: 15s
3   evaluation_interval: 15s
4   external_labels:
5     cluster: 'docker-cluster'
6     environment: 'production'
7
8   # Alertmanager configuration
9   alerting:
10    alertmanagers:
11      - static_configs:
12        - targets: ['alertmanager:9093']
13
14   # Load rules
15   rule_files:
16     - "alerts.yml"
17
18   scrape_configs:
19     # Prometheus self-monitoring
20     - job_name: 'prometheus'
21       static_configs:
22         - targets: ['localhost:9090']
23
24     # Node Exporter
25     - job_name: 'node-exporter'
26       static_configs:

```

```

27     - targets: ['node-exporter:9100']
28
29 # cAdvisor
30 - job_name: 'cadvisor'
31   static_configs:
32     - targets: ['cadvisor:8080']
33
34 # Docker daemon metrics
35 - job_name: 'docker'
36   static_configs:
37     - targets: ['host.docker.internal:9323']
38
39 # Docker Swarm service discovery
40 - job_name: 'docker-swarm'
41   dockerswarm_sd_configs:
42     - host: unix:///var/run/docker.sock
43       role: tasks
44   relabel_configs:
45     - source_labels: [
46         __meta_dockerswarm_service_label_prometheus_io_scrape]
47       action: keep
48       regex: true
49     - source_labels: [
50         __meta_dockerswarm_service_label_prometheus_io_port]
51       target_label: __address__
52       regex: ([^:]+)(?::\d+)?
53       replacement: $1:${1}
54
55 # Kubernetes pods (if running in K8s)
56 - job_name: 'kubernetes-pods'
57   kubernetes_sd_configs:
58     - role: pod
59   relabel_configs:
60     - source_labels: [
61         __meta_kubernetes_pod_annotation_prometheus_io_scrape]
62       action: keep
63       regex: true
64     - source_labels: [
65         __meta_kubernetes_pod_annotation_prometheus_io_path]
66       action: replace
67       target_label: __metrics_path__
68       regex: (.+)
69     - source_labels: [__address__,
70         __meta_kubernetes_pod_annotation_prometheus_io_port]
71       action: replace
72       regex: ([^:]+)(?::\d+)?;(\d+)
73       replacement: $1:$2
74       target_label: __address__

```

### 9.6.3 Application Metrics in Go

Listing 9.10: Prometheus Metrics Instrumentation

```

1 // metrics.go
2 package main
3
4 import (

```

```

5      "net/http"
6      "time"
7
8      "github.com/prometheus/client_golang/prometheus"
9      "github.com/prometheus/client_golang/prometheus/promauto"
10     "github.com/prometheus/client_golang/prometheus/promhttp"
11 )
12
13 var (
14     // Counter: incrementa sempre
15     httpRequestTotal = promauto.NewCounterVec(
16         prometheus.CounterOpts{
17             Name: "http_requests_total",
18             Help: "Total number of HTTP requests",
19         },
20         []string{"method", "endpoint", "status"},
21     )
22
23     // Histogram: distribuzione valori (latency, sizes)
24     httpRequestDuration = promauto.NewHistogramVec(
25         prometheus.HistogramOpts{
26             Name: "http_request_duration_seconds",
27             Help: "HTTP request latency distribution",
28             Buckets: prometheus.DefBuckets,
29         },
30         []string{"method", "endpoint"},
31     )
32
33     // Gauge: valore che può salire/scendere
34     activeConnections = promauto.NewGauge(
35         prometheus.GaugeOpts{
36             Name: "active_connections",
37             Help: "Number of active connections",
38         },
39     )
40
41     // Summary: come histogram ma con quantili
42     requestSize = promauto.NewSummaryVec(
43         prometheus.SummaryOpts{
44             Name: "http_request_size_bytes",
45             Help: "HTTP request size in bytes",
46             Objectives: map[float64]float64{0.5: 0.05, 0.9: 0.01, 0.99:
47                 0.001},
48             },
49         []string{"method"},
50     )
51 )
52
53 // Middleware per tracking automatico
54 func prometheusMiddleware(next http.Handler) http.Handler {
55     return http.HandlerFunc(func(w http.ResponseWriter, r *http.Request)
56     {
57         start := time.Now()
58
59         // Track active connections
60         activeConnections.Inc()
61         defer activeConnections.Dec()

```



```

61 // Track request size
62 requestSize.WithLabelValues(r.Method).Observe(float64(r.
    ContentLength))
63
64 // Wrap ResponseWriter per catturare status code
65 wrapped := &responseWriter{ResponseWriter: w, statusCode: http.
    StatusOK}
66
67 next.ServeHTTP(wrapped, r)
68
69 duration := time.Since(start).Seconds()
70
71 // Record metrics
72 httpRequestTotal.WithLabelValues(
73     r.Method,
74     r.URL.Path,
75     http.StatusText(wrapped.statusCode),
76 ).Inc()
77
78 httpRequestDuration.WithLabelValues(
79     r.Method,
80     r.URL.Path,
81 ).Observe(duration)
82 })
83 }
84
85 func main() {
86     // Application handlers
87     mux := http.NewServeMux()
88     mux.HandleFunc("/api/users", handleUsers)
89     mux.HandleFunc("/health", handleHealth)
90
91     // Prometheus metrics endpoint
92     mux.Handle("/metrics", promhttp.Handler())
93
94     // Apply middleware
95     handler := prometheusMiddleware(mux)
96
97     http.ListenAndServe(":8000", handler)
98 }

```

## 9.7 Alert Rules

### 9.7.1 Prometheus Alert Rules

Listing 9.11: prometheus/alerts.yml

```

1 groups:
2   - name: container_alerts
3     interval: 30s
4     rules:
5       # High CPU usage
6       - alert: HighCPUUsage
7         expr: |
8           100 - (avg by(instance) (irate(node_cpu_seconds_total{mode="
              idle"}[5m]))) * 100) > 80
9         for: 5m

```

```

10     labels:
11         severity: warning
12     annotations:
13         summary: "High CPU usage on {{ $labels.instance }}"
14         description: "CPU usage is above 80% (current: {{ $value }}%)"
15
16 # High memory usage
17 - alert: HighMemoryUsage
18     expr: |
19         (1 - (node_memory_MemAvailable_bytes /
20             node_memory_MemTotal_bytes)) * 100 > 90
21     for: 5m
22     labels:
23         severity: critical
24     annotations:
25         summary: "High memory usage on {{ $labels.instance }}"
26         description: "Memory usage is above 90% (current: {{ $value }}%)"
27
28 # Container down
29 - alert: ContainerDown
30     expr: |
31         up{job="docker"} == 0
32     for: 1m
33     labels:
34         severity: critical
35     annotations:
36         summary: "Container {{ $labels.instance }} is down"
37         description: "Container has been down for more than 1 minute"
38
39 # High error rate
40 - alert: HighErrorRate
41     expr: |
42         rate(http_requests_total{status=~"5.."}[5m]) / rate(
43             http_requests_total[5m]) > 0.05
44     for: 5m
45     labels:
46         severity: warning
47     annotations:
48         summary: "High HTTP error rate on {{ $labels.instance }}"
49         description: "Error rate is above 5% (current: {{ $value }}%)"
50
51 # Slow requests
52 - alert: SlowRequests
53     expr: |
54         histogram_quantile(0.99, rate(
55             http_request_duration_seconds_bucket[5m])) > 1
56     for: 5m
57     labels:
58         severity: warning
59     annotations:
60         summary: "Slow requests detected on {{ $labels.instance }}"
61         description: "99th percentile latency is above 1s (current: {{ $value }}s)"
62
63 # Disk space
64 - alert: DiskSpaceLow
65     expr: |

```

```

63         (node_filesystem_avail_bytes{mountpoint="/" } /
           node_filesystem_size_bytes{mountpoint="/"}) * 100 < 10
64     for: 5m
65     labels:
66         severity: critical
67     annotations:
68         summary: "Disk space low on {{ $labels.instance }}"
69         description: "Disk space is below 10% (current: {{ $value }}%)"
70
71 - name: docker_alerts
72   interval: 30s
73   rules:
74     # Too many containers
75     - alert: TooManyContainers
76       expr: |
77         count(container_last_seen) > 50
78       for: 10m
79       labels:
80         severity: warning
81       annotations:
82         summary: "Too many containers running"
83         description: "More than 50 containers are running (current: {{
           $value }})"
84
85     # Container restart loop
86     - alert: ContainerRestartLoop
87       expr: |
88         rate(container_last_seen{name!~"POD"}[5m]) > 0
89       for: 5m
90       labels:
91         severity: critical
92       annotations:
93         summary: "Container {{ $labels.name }} is restarting"
94         description: "Container has restarted multiple times in the
           last 5 minutes"

```

## 9.7.2 Alertmanager Configuration

Listing 9.12: alertmanager/config.yml

```

1 global:
2   resolve_timeout: 5m
3   slack_api_url: 'https://hooks.slack.com/services/YOUR/WEBHOOK/URL'
4
5 # Templates
6 templates:
7   - '/etc/alertmanager/templates/*.tmpl'
8
9 # Routing tree
10 route:
11   group_by: ['alertname', 'cluster', 'service']
12   group_wait: 10s
13   group_interval: 10s
14   repeat_interval: 12h
15   receiver: 'default'
16

```

```

17 routes:
18   # Critical alerts -> PagerDuty + Slack
19   - match:
20     severity: critical
21     receiver: 'pagerduty-critical'
22     continue: true
23
24   - match:
25     severity: critical
26     receiver: 'slack-critical'
27
28   # Warning alerts -> Slack only
29   - match:
30     severity: warning
31     receiver: 'slack-warnings'
32
33   # Database alerts
34   - match_re:
35     service: ^(postgres|mysql|redis)$
36     receiver: 'database-team'
37
38 receivers:
39   - name: 'default'
40     email_configs:
41       - to: 'alerts@example.com'
42         from: 'alertmanager@example.com'
43         smarthost: 'smtp.example.com:587'
44         auth_username: 'alertmanager@example.com'
45         auth_password: 'password'
46
47   - name: 'slack-critical'
48     slack_configs:
49       - channel: '#alerts-critical'
50         title: 'CRITICAL: {{ .CommonAnnotations.summary }}'
51         text: '{{ range .Alerts }}{{ .Annotations.description }}{{ end }}'
52         color: 'danger'
53         send_resolved: true
54
55   - name: 'slack-warnings'
56     slack_configs:
57       - channel: '#alerts-warnings'
58         title: 'Warning: {{ .CommonAnnotations.summary }}'
59         text: '{{ range .Alerts }}{{ .Annotations.description }}{{ end }}'
60         color: 'warning'
61
62   - name: 'pagerduty-critical'
63     pagerduty_configs:
64       - service_key: 'YOUR_PAGERDUTY_KEY'
65         description: '{{ .CommonAnnotations.summary }}'
66
67   - name: 'database-team'
68     webhook_configs:
69       - url: 'http://internal-alerts-api/webhook'
70         send_resolved: true
71
72 inhibit_rules:

```

```

73 - source_match:
74     severity: 'critical'
75 target_match:
76     severity: 'warning'
77 equal: ['alertname', 'instance']

```

## 9.8 Distributed Tracing

### 9.8.1 Jaeger Tracing Setup

Listing 9.13: Jaeger All-in-One

```

1 # docker-compose-tracing.yml
2 version: '3.8'
3
4 services:
5     jaeger:
6         image: jaegertracing/all-in-one:1.51
7         environment:
8             - COLLECTOR_ZIPKIN_HOST_PORT=:9411
9             - COLLECTOR_OTLP_ENABLED=true
10        ports:
11            - "5775:5775/udp"    # accept zipkin.thrift compact
12            - "6831:6831/udp"    # accept jaeger.thrift compact
13            - "6832:6832/udp"    # accept jaeger.thrift binary
14            - "5778:5778"        # serve configs
15            - "16686:16686"      # serve frontend
16            - "14250:14250"      # accept gRPC
17            - "14268:14268"      # accept jaeger.thrift
18            - "14269:14269"      # admin port
19            - "9411:9411"        # Zipkin compatible
20            - "4317:4317"        # OTLP gRPC
21            - "4318:4318"        # OTLP HTTP
22        networks:
23            - tracing
24
25    app:
26        image: myapp:latest
27        environment:
28            - JAEGER_AGENT_HOST=jaeger
29            - JAEGER_AGENT_PORT=6831
30            - JAEGER_SAMPLER_TYPE=const
31            - JAEGER_SAMPLER_PARAM=1
32        networks:
33            - tracing
34
35 networks:
36     tracing:
37         driver: bridge

```

## 9.9 Structured Logging Best Practices

### 9.9.1 Structured Logging Example

Listing 9.14: Structured Logging with Zap

```
1 // logger.go
2 package main
3
4 import (
5     "go.uber.org/zap"
6     "go.uber.org/zap/zapcore"
7 )
8
9 func NewLogger() (*zap.Logger, error) {
10     config := zap.NewProductionConfig()
11
12     config.EncoderConfig.TimeKey = "timestamp"
13     config.EncoderConfig.EncodeTime = zapcore.ISO8601TimeEncoder
14
15     config.OutputPaths = []string{"stdout"}
16     config.ErrorOutputPaths = []string{"stderr"}
17
18     return config.Build()
19 }
20
21 func main() {
22     logger, _ := NewLogger()
23     defer logger.Sync()
24
25     // Structured fields
26     logger.Info("User login",
27         zap.String("user_id", "12345"),
28         zap.String("ip", "192.168.1.100"),
29         zap.Duration("latency", 150*time.Millisecond),
30     )
31
32     // Error with stack trace
33     logger.Error("Database connection failed",
34         zap.Error(err),
35         zap.String("database", "postgres"),
36         zap.Int("retry_count", 3),
37     )
38 }
```

## 9.10 Best Practices

### Monitoring/Logging Checklist

1. **Structured Logging:** JSON format per parsing automatico
2. **Log Levels:** DEBUG, INFO, WARN, ERROR, FATAL
3. **Correlation IDs:** Trace requests attraverso microservices
4. **Retention Policy:** 30-90 giorni per compliance
5. **Sampling:** Non loggare ogni richiesta in high-traffic
6. **Alerting:** Alert su anomalie, non su soglie fisse
7. **Dashboards:** Grafana boards per business metrics

8. **Security:** No credentials/PII nei logs

## 9.11 Riepilogo

Monitoring e logging efficaci richiedono centralized logging (ELK/Loki), metrics collection (Prometheus), visualization (Grafana), e distributed tracing (Jaeger). Structured logging, alerting rules, e retention policies garantiscono observability completa per production environments.

## 9.12 Riferimenti

- Prometheus: <https://prometheus.io/docs/>
- Grafana Loki: <https://grafana.com/docs/loki/>
- ELK Stack: <https://www.elastic.co/elastic-stack>
- Jaeger: <https://www.jaegertracing.io/docs/>





# Capitolo 10

## Best Practices e Security

### 10.1 Introduzione

Security, optimization e best practices sono fondamentali per production-ready Docker deployments. Questo capitolo copre Dockerfile optimization, layer caching, .dockerignore, security hardening, vulnerability scanning, e compliance requirements.

#### Mappa del capitolo

**Sezioni:** Dockerfile best practices, Layer caching optimization, .dockerignore patterns, Security hardening, User namespaces, Secrets management, Image scanning, Network security, Resource limits, Production checklist.

### 10.2 Obiettivi di Apprendimento

- Ottimizzare Dockerfiles per build speed e image size
- Implementare security best practices (non-root users, read-only filesystem)
- Configurare .dockerignore per build efficiency
- Utilizzare layer caching e BuildKit features
- Scansionare images per vulnerabilità
- Applicare least privilege principle e network isolation

### 10.3 Dockerfile Optimization

#### 10.3.1 Esempio: Before vs After Optimization

Listing 10.1: Dockerfile NON Ottimizzato

```
1 # BAD BAD: Inefficient, large image, security issues
2 FROM node:20
3
4 WORKDIR /app
5
6 # BAD Copia tutto (inclusi node_modules, .git, etc)
7 COPY . .
8
9 # BAD Esegue come root
```

```

10 # BAD No cache layer optimization
11 RUN npm install
12
13 # BAD Exposes source code
14 # BAD Development dependencies included
15
16 EXPOSE 3000
17 CMD ["node", "server.js"]

```

Listing 10.2: Dockerfile OTTIMIZZATO

```

1  #      GOOD: Multi-stage, optimized, secure
2  # syntax=docker/dockerfile:1.4
3
4  # Stage 1: Dependencies
5  FROM node:20-alpine AS deps
6  WORKDIR /app
7  COPY package*.json ./
8  RUN --mount=type=cache,target=/root/.npm \
9      npm ci --only=production
10
11 # Stage 2: Builder
12 FROM node:20-alpine AS builder
13 WORKDIR /app
14 COPY package*.json ./
15 RUN --mount=type=cache,target=/root/.npm \
16     npm ci
17 COPY . .
18 RUN npm run build
19
20 # Stage 3: Production
21 FROM node:20-alpine AS production
22
23 # Install security updates
24 RUN apk upgrade --no-cache
25
26 # Create non-root user
27 RUN addgroup -g 1001 -S nodejs && \
28     adduser -S nodejs -u 1001
29
30 WORKDIR /app
31
32 # Copy only production artifacts
33 COPY --from=deps --chown=nodejs:nodejs /app/node_modules ./node_modules
34 COPY --from=builder --chown=nodejs:nodejs /app/dist ./dist
35 COPY --chown=nodejs:nodejs package.json ./
36
37 # Security: run as non-root
38 USER nodejs
39
40 # Health check
41 HEALTHCHECK --interval=30s --timeout=3s --start-period=40s \
42     CMD node healthcheck.js || exit 1
43
44 EXPOSE 3000
45
46 # Use exec form for proper signal handling
47 CMD ["node", "dist/server.js"]
48

```

```

49 # Metadata labels
50 LABEL org.opencontainers.image.source="https://github.com/org/repo"
51 LABEL org.opencontainers.image.version="1.0.0"
52 LABEL org.opencontainers.image.licenses="MIT"

```

### 10.3.2 Layer Caching Optimization

Listing 10.3: Optimal Layer Order

```

1 # Ordine corretto per massimizzare cache hits
2 FROM python:3.11-slim
3
4 # 1. System packages (cambiano raramente)
5 RUN apt-get update && apt-get install -y \
6     gcc \
7     libpq-dev \
8     && rm -rf /var/lib/apt/lists/*
9
10 # 2. Requirements (cambiano occasionalmente)
11 COPY requirements.txt .
12 RUN --mount=type=cache,target=/root/.cache/pip \
13     pip install --no-cache-dir -r requirements.txt
14
15 # 3. Application code (cambia frequentemente)
16 COPY . .
17
18 # Questo ordine garantisce:
19 # - System packages: cache hit quasi sempre
20 # - Requirements: cache hit se requirements.txt non cambia
21 # - Code: rebuild solo questo layer se cambia codice

```

### 10.3.3 BuildKit Advanced Features

Listing 10.4: BuildKit Cache Mounts e Secrets

```

1 # syntax=docker/dockerfile:1.4
2
3 FROM golang:1.21-alpine AS builder
4
5 WORKDIR /app
6
7 # Cache mount per Go modules
8 COPY go.mod go.sum ./
9 RUN --mount=type=cache,target=/go/pkg/mod \
10     go mod download
11
12 # Secret mount (non saved in image)
13 RUN --mount=type=secret,id=netrc,target=/root/.netrc \
14     go build -o app .
15
16 # SSH mount per private repos
17 RUN --mount=type=ssh \
18     git clone git@github.com:private/repo.git
19
20 # Bind mount (source files non copiati nell'immagine)
21 RUN --mount=type=bind,source=.,target=/src \

```

```
22     cd /src && go build -o /app/binary
23
24 FROM alpine:latest
25 COPY --from=builder /app/binary /usr/local/bin/
26 CMD ["binary"]
```

Listing 10.5: Build con BuildKit Features

```
1 # Enable BuildKit
2 export DOCKER_BUILDKIT=1
3
4 # Build con secret
5 docker build \
6     --secret id=netrc,src=$HOME/.netrc \
7     --ssh default \
8     --tag myapp:latest .
9
10 # Build con cache from registry
11 docker build \
12     --cache-from myregistry.io/myapp:latest \
13     --tag myapp:latest .
14
15 # Export cache to registry
16 docker build \
17     --cache-to type=registry,ref=myregistry.io/myapp:buildcache \
18     --tag myapp:latest .
```

## 10.4 .dockerignore Best Practices

### 10.4.1 Comprehensive .dockerignore

Listing 10.6: .dockerignore - Complete Template

```
1 # Version control
2 .git
3 .gitignore
4 .gitattributes
5 .gitmodules
6
7 # CI/CD
8 .github
9 .gitlab-ci.yml
10 .travis.yml
11 Jenkinsfile
12
13 # Documentation
14 README.md
15 CHANGELOG.md
16 LICENSE
17 docs/
18 *.md
19
20 # Dependencies (rebuild from package files)
21 node_modules/
22 vendor/
23 venv/
24 __pycache__/
```

```
25 *.pyc
26 *.pyo
27
28 # Build artifacts
29 dist/
30 build/
31 target/
32 *.o
33 *.a
34 *.so
35
36 # IDE
37 .vscode/
38 .idea/
39 *.swp
40 *.swo
41 *~
42 .DS_Store
43
44 # Logs
45 *.log
46 logs/
47 npm-debug.log*
48 yarn-debug.log*
49
50 # Test files
51 tests/
52 test/
53 spec/
54 *.test.js
55 *.spec.js
56 coverage/
57 .nyc_output/
58
59 # Environment
60 .env
61 .env.local
62 .env.*.local
63 *.pem
64 *.key
65
66 # Temp files
67 tmp/
68 temp/
69 *.tmp
70
71 # Docker
72 Dockerfile*
73 docker-compose*.yaml
74 .dockerignore
75
76 # Build cache
77 .cache/
78 .npm/
79 .yarn/
80
81 # OS files
82 Thumbs.db
```

```

83 desktop.ini
84
85 # Large data files (if not needed)
86 *.csv
87 *.zip
88 *.tar.gz
89 datasets/
90
91 # Negative patterns (exceptions)
92 !dist/index.html # Include specific file

```

### **.dockerignore Impact**

#### **Benefici:**

- **Build Speed:** Riduce context size da GB a MB
- **Security:** Esclude .env, .git con secrets
- **Image Size:** Non include test files, docs
- **Cache:** Migliora layer caching efficiency

#### **Esempio:**

- Senza .dockerignore: Context 2.5 GB, build 5 minuti
- Con .dockerignore: Context 50 MB, build 30 secondi

## 10.5 Security Hardening

### 10.5.1 Non-Root User

Listing 10.7: Multiple User Strategies

```

1 # Strategy 1: Alpine adduser
2 FROM alpine:latest
3 RUN addgroup -g 1001 -S appgroup && \
4     adduser -S appuser -u 1001 -G appgroup
5 USER appuser
6
7 # Strategy 2: Debian/Ubuntu useradd
8 FROM ubuntu:22.04
9 RUN groupadd -r appgroup -g 1001 && \
10     useradd -r -u 1001 -g appgroup appuser
11 USER appuser
12
13 # Strategy 3: Existing user (nginx example)
14 FROM nginx:alpine
15 USER nginx
16
17 # Strategy 4: Numeric UID (Kubernetes SecurityContext)
18 FROM node:20-alpine
19 USER 1001:1001
20
21 # Permissions per non-root user
22 FROM node:20-alpine

```

```

23 RUN adduser -D -u 1001 nodejs
24 WORKDIR /app
25 COPY --chown=nodejs:nodejs . .
26 USER nodejs

```

## 10.5.2 Read-Only Root Filesystem

Listing 10.8: Read-Only Filesystem in Docker Compose

```

1 version: '3.8'
2
3 services:
4   app:
5     image: myapp:latest
6     read_only: true # Root filesystem read-only
7     tmpfs:
8       - /tmp:size=100M,mode=1777
9       - /var/run:size=10M,mode=755
10    volumes:
11      # Writable volumes only where necessary
12      - app-cache:/app/cache:rw
13      - app-logs:/app/logs:rw
14
15 volumes:
16   app-cache:
17   app-logs:

```

Listing 10.9: Read-Only in Kubernetes

```

1 # kubernetes-security.yaml
2 apiVersion: v1
3 kind: Pod
4 metadata:
5   name: secure-pod
6 spec:
7   securityContext:
8     runAsNonRoot: true
9     runAsUser: 1001
10    fsGroup: 1001
11    seccompProfile:
12      type: RuntimeDefault
13
14   containers:
15     - name: app
16       image: myapp:latest
17       securityContext:
18         allowPrivilegeEscalation: false
19         readOnlyRootFilesystem: true
20         capabilities:
21           drop:
22             - ALL
23       volumeMounts:
24         - name: cache
25           mountPath: /tmp
26         - name: logs
27           mountPath: /var/log
28
29   volumes:

```

```
30 - name: cache
31   emptyDir: {}
32 - name: logs
33   emptyDir: {}
```

### 10.5.3 Security Scanning

#### Trivy - Comprehensive Scanning

Listing 10.10: Trivy Security Scanning

```
1 # Install Trivy
2 curl -sL https://raw.githubusercontent.com/aquasecurity/trivy/main/
   contrib/install.sh | sh -s -- -b /usr/local/bin
3
4 # Scan image per vulnerabilities
5 trivy image myapp:latest
6
7 # Scan solo CRITICAL e HIGH
8 trivy image --severity CRITICAL,HIGH myapp:latest
9
10 # Output formattato
11 trivy image --format json --output results.json myapp:latest
12 trivy image --format sarif --output trivy-results.sarif myapp:latest
13
14 # Scan Dockerfile
15 trivy config Dockerfile
16
17 # Scan filesystem
18 trivy fs /path/to/project
19
20 # Scan con exit code (CI/CD integration)
21 trivy image --exit-code 1 --severity CRITICAL myapp:latest
22
23 # Ignore unfixed vulnerabilities
24 trivy image --ignore-unfixed myapp:latest
25
26 # Scan con database update
27 trivy image --download-db-only
28 trivy image --skip-db-update myapp:latest
```

#### Docker Scout

Listing 10.11: Docker Scout Analysis

```
1 # Enable Docker Scout
2 docker scout quickview myapp:latest
3
4 # Detailed CVE report
5 docker scout cves myapp:latest
6
7 # Compare images
8 docker scout compare --to myapp:v1.0 myapp:latest
9
10 # Recommendations
11 docker scout recommendations myapp:latest
12
```



```
13 # SBOM (Software Bill of Materials)
14 docker scout sbom myapp:latest
```

## Snyk Container Security

Listing 10.12: Snyk Scanning

```
1 # Install Snyk CLI
2 npm install -g snyk
3
4 # Authenticate
5 snyk auth
6
7 # Test image
8 snyk container test myapp:latest
9
10 # Monitor image in Snyk dashboard
11 snyk container monitor myapp:latest
12
13 # Test con severity threshold
14 snyk container test myapp:latest --severity-threshold=high
15
16 # Generate HTML report
17 snyk container test myapp:latest --json | snyk-to-html -o results.html
```

## 10.6 Network Security

### 10.6.1 Network Isolation

Listing 10.13: Network Segmentation

```
1 # docker-compose-network-security.yml
2 version: '3.8'
3
4 services:
5   # Frontend (public)
6   frontend:
7     image: nginx:alpine
8     networks:
9       - public
10      - frontend-backend
11     ports:
12       - "80:80"
13       - "443:443"
14
15   # Backend (internal)
16   backend:
17     image: myapp:latest
18     networks:
19       - frontend-backend
20       - backend-database
21     # No ports exposed externally
22
23   # Database (isolated)
24   database:
25     image: postgres:15-alpine
```

```

26     networks:
27         - backend-database # Solo backend può accedere
28         # No external access
29
30 networks:
31     public:
32         driver: bridge
33     frontend-backend:
34         driver: bridge
35         internal: false
36     backend-database:
37         driver: bridge
38         internal: true # No internet access

```

## 10.6.2 Kubernetes Network Policies

Listing 10.14: NetworkPolicy - Deny All by Default

```

1 # deny-all.yaml
2 apiVersion: networking.k8s.io/v1
3 kind: NetworkPolicy
4 metadata:
5     name: default-deny-all
6     namespace: production
7 spec:
8     podSelector: {}
9     policyTypes:
10     - Ingress
11     - Egress
12
13 ---
14 # Allow specific traffic
15 apiVersion: networking.k8s.io/v1
16 kind: NetworkPolicy
17 metadata:
18     name: allow-backend-to-db
19     namespace: production
20 spec:
21     podSelector:
22         matchLabels:
23             app: backend
24     policyTypes:
25     - Egress
26     egress:
27         # Allow DNS
28         - to:
29             - namespaceSelector:
30                 matchLabels:
31                     name: kube-system
32     ports:
33     - protocol: UDP
34       port: 53
35
36 # Allow database access
37 - to:
38     - podSelector:
39         matchLabels:

```

```

40         app: postgres
41     ports:
42     - protocol: TCP
43       port: 5432
44
45 ---
46 # Allow ingress to frontend
47 apiVersion: networking.k8s.io/v1
48 kind: NetworkPolicy
49 metadata:
50   name: allow-ingress-to-frontend
51   namespace: production
52 spec:
53   podSelector:
54     matchLabels:
55       app: frontend
56   policyTypes:
57   - Ingress
58   ingress:
59   - from:
60     - namespaceSelector:
61       matchLabels:
62         name: ingress-nginx
63     ports:
64     - protocol: TCP
65       port: 80
66     - protocol: TCP
67       port: 443

```

## 10.7 Resource Limits

### 10.7.1 Docker Resource Constraints

Listing 10.15: Resource Limits in Docker Compose

```

1  version: '3.8'
2
3  services:
4    app:
5      image: myapp:latest
6      deploy:
7        resources:
8          limits:
9            cpus: '1.5'           # Max 1.5 CPU cores
10           memory: 1024M         # Max 1GB RAM
11           pids: 100             # Max 100 processes
12         reservations:
13           cpus: '0.5'           # Guaranteed 0.5 CPU
14           memory: 512M          # Guaranteed 512MB
15         restart_policy:
16           condition: on-failure
17           delay: 5s
18           max_attempts: 3
19
20     # OOMKilled prevention
21     database:
22       image: postgres:15

```

```

23     deploy:
24         resources:
25             limits:
26                 memory: 2G
27             reservations:
28                 memory: 1G
29     # Memory swappiness (0-100, lower = less swap)
30     sysctls:
31         - vm.swappiness=10

```

Listing 10.16: Docker Run Resource Limits

```

1  # CPU limits
2  docker run -d \
3      --cpus="1.5" \
4      --cpu-shares=1024 \
5      myapp:latest
6
7  # Memory limits
8  docker run -d \
9      --memory="1g" \
10     --memory-reservation="512m" \
11     --memory-swap="2g" \
12     --oom-kill-disable=false \
13     myapp:latest
14
15 # Disk I/O limits
16 docker run -d \
17     --device-read-bps /dev/sda:10mb \
18     --device-write-bps /dev/sda:10mb \
19     myapp:latest
20
21 # PIDs limit
22 docker run -d \
23     --pids-limit=100 \
24     myapp:latest

```

## 10.8 Secrets Management

### 10.8.1 Docker Secrets (Swarm)

Listing 10.17: Docker Secrets Best Practices

```

1  # Create secret from file
2  docker secret create db_password /path/to/password.txt
3
4  # Create secret from stdin
5  echo "supersecretpassword" | docker secret create db_password -
6
7  # Create secret with labels
8  docker secret create db_password - <<EOF
9  $(openssl rand -base64 32)
10 EOF
11
12 # Use in stack
13 cat <<EOF | docker stack deploy -c - myapp
14 version: '3.8'

```

```

15 services:
16   app:
17     image: myapp:latest
18     secrets:
19       - db_password
20       - api_key
21     environment:
22       DB_PASSWORD_FILE: /run/secrets/db_password
23
24 secrets:
25   db_password:
26     external: true
27   api_key:
28     external: true
29 EOF
30
31 # Rotate secret
32 docker secret create db_password_v2 - < new_password.txt
33 docker service update \
34   --secret-rm db_password \
35   --secret-add source=db_password_v2,target=db_password \
36   myapp

```

## 10.8.2 Kubernetes Secrets

Listing 10.18: Kubernetes Secrets with Encryption

```

1 # Create generic secret
2 kubectl create secret generic db-credentials \
3   --from-literal=username=admin \
4   --from-literal=password=$(openssl rand -base64 32)
5
6 # Create from file
7 kubectl create secret generic tls-cert \
8   --from-file=tls.crt=./server.crt \
9   --from-file=tls.key=./server.key
10
11 # Encryption at rest configuration
12 # /etc/kubernetes/enc/enc.yaml
13 apiVersion: apiserver.config.k8s.io/v1
14 kind: EncryptionConfiguration
15 resources:
16   - resources:
17     - secrets
18   providers:
19     - aescbc:
20       keys:
21         - name: key1
22           secret: $(head -c 32 /dev/urandom | base64)
23     - identity: {}
24
25 # Apply encryption config in API server
26 # --encryption-provider-config=/etc/kubernetes/enc/enc.yaml

```

## 10.8.3 External Secrets Operator

Listing 10.19: HashiCorp Vault Integration

```
1 # Install External Secrets Operator
2 helm repo add external-secrets https://charts.external-secrets.io
3 helm install external-secrets external-secrets/external-secrets
4
5 # SecretStore (Vault backend)
6 apiVersion: external-secrets.io/v1beta1
7 kind: SecretStore
8 metadata:
9   name: vault-backend
10  namespace: production
11 spec:
12   provider:
13     vault:
14       server: "https://vault.example.com"
15       path: "secret"
16       version: "v2"
17       auth:
18         kubernetes:
19           mountPath: "kubernetes"
20           role: "production"
21
22 ---
23 # ExternalSecret
24 apiVersion: external-secrets.io/v1beta1
25 kind: ExternalSecret
26 metadata:
27   name: database-credentials
28   namespace: production
29 spec:
30   refreshInterval: 1h
31   secretStoreRef:
32     name: vault-backend
33     kind: SecretStore
34   target:
35     name: db-credentials
36     creationPolicy: Owner
37   data:
38     - secretKey: username
39       remoteRef:
40         key: database/prod
41         property: username
42     - secretKey: password
43       remoteRef:
44         key: database/prod
45         property: password
```

## 10.9 Image Signing and Verification

### 10.9.1 Cosign - Image Signing

Listing 10.20: Cosign Image Signing

```
1 # Install Cosign
2 go install github.com/sigstore/cosign/v2/cmd/cosign@latest
3
4 # Generate key pair
```

```

5 | cosign generate-key-pair
6 |
7 | # Sign image
8 | cosign sign --key cosign.key myregistry.io/myapp:v1.0.0
9 |
10 | # Verify signature
11 | cosign verify --key cosign.pub myregistry.io/myapp:v1.0.0
12 |
13 | # Keyless signing (Sigstore)
14 | COSIGN_EXPERIMENTAL=1 cosign sign myregistry.io/myapp:v1.0.0
15 |
16 | # Attach SBOM
17 | syft myapp:latest -o spdx-json > sbom.spdx.json
18 | cosign attach sbom --sbom sbom.spdx.json myregistry.io/myapp:v1.0.0
19 |
20 | # Policy enforcement (Kubernetes)
21 | apiVersion: v1
22 | kind: Pod
23 | metadata:
24 |   name: signed-pod
25 |   annotations:
26 |     cosign.sigstore.dev/signature: "verified"
27 | spec:
28 |   containers:
29 |   - name: app
30 |     image: myregistry.io/myapp:v1.0.0

```

## 10.10 Production Deployment Checklist

### Security & Best Practices Checklist

#### Dockerfile:

- Multi-stage build per minimizzare image size
- Non-root user configurato
- No secrets hardcoded
- Health check implementato
- .dockerignore completo
- Base image aggiornata (no vulnerabilities)

#### Security:

- Image scanning (Trivy/Snyk) in CI/CD
- Read-only root filesystem
- Capabilities dropped (Linux capabilities)
- Secrets in external vault (no env vars)
- Network policies configurate
- Image signing con Cosign

**Resources:**

CPU/Memory limits definiti  
Resource requests configurati  
PID limits per prevenire fork bombs  
Disk I/O limits se necessario

**Observability:**

Structured logging implementato  
Prometheus metrics exposed  
Health/Readiness probes configurati  
Distributed tracing setup

**Compliance:**

SBOM generato e attached  
License compliance verificata  
Audit logs abilitati  
Data encryption at rest

## 10.11 Common Security Anti-Patterns

- **Anti-Pattern:** Running as root user
  - **Risk:** Container breakout, privilege escalation
  - **Fix:** USER directive, SecurityContext in K8s
- **Anti-Pattern:** Secrets in ENV variables
  - **Risk:** Visible in docker inspect, logs
  - **Fix:** File-based secrets, Vault integration
- **Anti-Pattern:** Using 'latest' tag in production
  - **Risk:** Non-deterministic deployments
  - **Fix:** Semantic versioning, SHA digests
- **Anti-Pattern:** No resource limits
  - **Risk:** Resource exhaustion, noisy neighbor
  - **Fix:** Explicit CPU/Memory limits
- **Anti-Pattern:** Ignoring CVE vulnerabilities
  - **Risk:** Exploitable vulnerabilities in production
  - **Fix:** Automated scanning, patch management



## 10.12 Performance Optimization

### 10.12.1 Image Size Reduction

Listing 10.21: Image Size Comparison

```
1 # Bad: Ubuntu base (hundreds of MB)
2 FROM ubuntu:22.04
3 RUN apt-get update && apt-get install -y python3
4 # Result: ~500MB
5
6 # Better: Slim variant
7 FROM python:3.11-slim
8 # Result: ~150MB
9
10 # Best: Alpine (minimal)
11 FROM python:3.11-alpine
12 # Result: ~50MB
13
14 # Distroless (no shell, minimal attack surface)
15 FROM gcr.io/distroless/python3
16 # Result: ~60MB, ultra-secure
```

## 10.13 Errori Comuni

- **Errore:** Layer caching inefficace
  - **Sintomo:** Build sempre da zero, lenti
  - **Soluzione:** Ordine corretto layer, BuildKit cache
- **Errore:** Context troppo grande
  - **Sintomo:** "Sending build context" richiede minuti
  - **Soluzione:** .dockerignore completo
- **Errore:** Permessi file sbagliati con COPY
  - **Sintomo:** Permission denied quando esegue app
  - **Soluzione:** -chown flag in COPY

## 10.14 Riepilogo

Best practices Docker richiedono Dockerfile optimization (multi-stage, layer caching), security hardening (non-root, read-only FS, network policies), secrets management (Vault, External Secrets), vulnerability scanning (Trivy, Snyk), e resource limits. Production deployments devono seguire checklist completa per security, performance, e compliance.

## 10.15 Riferimenti

- Docker Security: <https://docs.docker.com/engine/security/>
- CIS Docker Benchmark: <https://www.cisecurity.org/benchmark/docker>
- OWASP Container Security: <https://owasp.org/www-project-docker-top-10/>

- Trivy: <https://trivy.dev/>
- Sigstore Cosign: <https://docs.sigstore.dev/cosign/>

## Appendice A

# Appendice: Cheat Sheet Comandi Docker

## A.1 Container Management

### A.1.1 Lifecycle Commands

Listing A.1: Container Basics

```
1 # Run container
2 docker run -d --name myapp nginx:alpine
3 docker run -it --rm alpine sh           # Interactive, auto-remove
4 docker run -d -p 8080:80 nginx          # Port mapping
5 docker run -d -v /data:/app/data myapp  # Volume mount
6
7 # Start/Stop/Restart
8 docker start container_name
9 docker stop container_name
10 docker restart container_name
11 docker pause container_name            # Pause processes
12 docker unpause container_name
13
14 # Remove containers
15 docker rm container_name               # Remove stopped container
16 docker rm -f container_name            # Force remove running
17 docker container prune                  # Remove all stopped
18 docker rm $(docker ps -aq)             # Remove all containers
19
20 # Execute commands in running container
21 docker exec -it container_name bash
22 docker exec container_name ls /app
23 docker exec -u root container_name sh   # As different user
```

### A.1.2 Inspection & Monitoring

Listing A.2: Container Info

```
1 # List containers
2 docker ps                               # Running containers
3 docker ps -a                            # All containers
4 docker ps -q                             # Only IDs
5 docker ps --filter "status=exited"
6 docker ps --format "table {{.Names}}\t{{.Status}}\t{{.Ports}}"
```

```

7
8 # Inspect container
9 docker inspect container_name
10 docker inspect --format='{{.State.Status}}' container_name
11 docker inspect --format='{{.NetworkSettings.IPAddress}}' container_name
12
13 # Logs
14 docker logs container_name
15 docker logs -f container_name # Follow
16 docker logs --tail 100 container_name
17 docker logs --since 2024-01-01 container_name
18 docker logs -t container_name # With timestamps
19
20 # Stats & Resource Usage
21 docker stats # Real-time stats
22 docker stats --no-stream # One-time snapshot
23 docker top container_name # Processes in container
24
25 # Events
26 docker events # Real-time events
27 docker events --since 1h --filter type=container

```

### A.1.3 Advanced Container Operations

Listing A.3: Advanced Commands

```

1 # Copy files to/from container
2 docker cp local_file.txt container:/path/
3 docker cp container:/app/log.txt ./
4
5 # Commit container to image
6 docker commit container_name new_image:tag
7
8 # Export/Import container filesystem
9 docker export container_name > container.tar
10 docker import container.tar new_image:tag
11
12 # Attach to running container
13 docker attach container_name # Attach to STDIN/STDOUT
14
15 # Rename container
16 docker rename old_name new_name
17
18 # Update container resources
19 docker update --cpus 2 --memory 1g container_name
20
21 # Wait for container to stop
22 docker wait container_name

```

## A.2 Image Management

### A.2.1 Image Operations

Listing A.4: Image Commands

```

1 # Pull images

```

```

2  docker pull nginx:alpine
3  docker pull --platform linux/amd64 ubuntu:22.04
4
5  # List images
6  docker images
7  docker images -a                # Include intermediates
8  docker images --filter "dangling=true" # Untagged images
9  docker images --format "table {{.Repository}}:{{.Tag}}\t{{.Size}}"
10
11 # Tag images
12 docker tag myapp:latest myregistry.io/myapp:v1.0.0
13 docker tag myapp:latest myapp:stable
14
15 # Push to registry
16 docker push myregistry.io/myapp:v1.0.0
17
18 # Remove images
19 docker rmi image_name:tag
20 docker rmi -f image_id          # Force remove
21 docker image prune              # Remove dangling
22 docker image prune -a          # Remove unused
23 docker rmi $(docker images -q)  # Remove all
24
25 # Save/Load images
26 docker save myapp:latest > myapp.tar
27 docker save myapp:latest | gzip > myapp.tar.gz
28 docker load < myapp.tar
29
30 # Image history
31 docker history myapp:latest
32 docker history --no-trunc myapp:latest # Full commands
33
34 # Inspect image
35 docker inspect myapp:latest
36 docker inspect --format='{{.Config.Env}}' myapp:latest

```

## A.2.2 Build Commands

Listing A.5: Docker Build

```

1  # Basic build
2  docker build -t myapp:latest .
3  docker build -t myapp:v1.0.0 -f Dockerfile.prod .
4
5  # Build arguments
6  docker build --build-arg VERSION=1.0.0 -t myapp .
7  docker build --build-arg HTTP_PROXY=http://proxy:8080 -t myapp .
8
9  # BuildKit features
10 export DOCKER_BUILDKIT=1
11 docker build --cache-from myapp:latest -t myapp:new .
12 docker build --secret id=npmmrc,src=$HOME/.npmmrc -t myapp .
13 docker build --ssh default -t myapp .
14
15 # Multi-platform build
16 docker buildx create --use
17 docker buildx build --platform linux/amd64,linux/arm64 \

```

```

18   -t myapp:latest --push .
19
20 # Target specific stage
21 docker build --target production -t myapp:prod .
22
23 # No cache
24 docker build --no-cache -t myapp .
25 docker build --pull -t myapp .           # Pull base image
26
27 # Squash layers (experimental)
28 docker build --squash -t myapp .

```

## A.3 Volume Management

### A.3.1 Volume Commands

Listing A.6: Volumes

```

1 # Create volume
2 docker volume create myvolume
3 docker volume create --driver local \
4   --opt type=nfs \
5   --opt o=addr=192.168.1.1,rw \
6   --opt device=:/path/to/dir \
7   nfs-volume
8
9 # List volumes
10 docker volume ls
11 docker volume ls --filter "dangling=true"
12
13 # Inspect volume
14 docker volume inspect myvolume
15
16 # Remove volumes
17 docker volume rm myvolume
18 docker volume prune           # Remove unused
19 docker volume prune -f       # No confirmation
20
21 # Use volume in container
22 docker run -d -v myvolume:/app/data myapp
23 docker run -d -v /host/path:/container/path:ro myapp
24 docker run -d --mount source=myvolume,target=/data myapp

```

## A.4 Network Management

### A.4.1 Network Commands

Listing A.7: Docker Networks

```

1 # Create networks
2 docker network create mynetwork
3 docker network create --driver bridge mybridge
4 docker network create --driver overlay --attachable myoverlay
5 docker network create --subnet 172.20.0.0/16 custom-net
6

```

```

7 # List networks
8 docker network ls
9 docker network ls --filter driver=bridge
10
11 # Inspect network
12 docker network inspect mynetwork
13 docker network inspect --format='{{json .Containers}}' mynetwork
14
15 # Connect/Disconnect containers
16 docker network connect mynetwork container_name
17 docker network disconnect mynetwork container_name
18
19 # Remove networks
20 docker network rm mynetwork
21 docker network prune # Remove unused
22
23 # Create container on specific network
24 docker run -d --network mynetwork --name app myapp
25 docker run -d --network mynetwork --ip 172.20.0.10 myapp

```

## A.5 Docker Compose

### A.5.1 Compose Commands

Listing A.8: Docker Compose

```

1 # Start services
2 docker-compose up # Foreground
3 docker-compose up -d # Detached
4 docker-compose up --build # Rebuild images
5 docker-compose up --force-recreate # Recreate containers
6 docker-compose up --scale app=3 # Scale service
7
8 # Stop services
9 docker-compose stop
10 docker-compose down # Stop and remove
11 docker-compose down -v # Remove volumes too
12 docker-compose down --rmi all # Remove images
13
14 # View services
15 docker-compose ps
16 docker-compose ps -a
17 docker-compose top
18
19 # Logs
20 docker-compose logs
21 docker-compose logs -f app
22 docker-compose logs --tail=100
23
24 # Execute commands
25 docker-compose exec app bash
26 docker-compose exec -T app npm test # No TTY
27 docker-compose run --rm app npm install # One-off command
28
29 # Build
30 docker-compose build
31 docker-compose build --no-cache app

```

```

32 docker-compose build --pull
33
34 # Configuration
35 docker-compose config                # Validate and view
36 docker-compose config --services    # List services
37 docker-compose config --volumes
38
39 # Pull images
40 docker-compose pull
41 docker-compose pull app
42
43 # Restart services
44 docker-compose restart
45 docker-compose restart app
46
47 # Pause/Unpause
48 docker-compose pause
49 docker-compose unpause

```

## A.6 Docker Swarm

### A.6.1 Swarm Management

Listing A.9: Swarm Commands

```

1  # Initialize swarm
2  docker swarm init
3  docker swarm init --advertise-addr 192.168.1.10
4
5  # Join swarm
6  docker swarm join --token TOKEN 192.168.1.10:2377
7  docker swarm join-token worker      # Get worker token
8  docker swarm join-token manager    # Get manager token
9
10 # Leave swarm
11 docker swarm leave
12 docker swarm leave --force          # Force manager leave
13
14 # Node management
15 docker node ls
16 docker node inspect node_name
17 docker node update --availability drain node_name
18 docker node update --label-add type=worker node_name
19 docker node rm node_name
20
21 # Service management
22 docker service create --name web --replicas 3 -p 80:80 nginx
23 docker service ls
24 docker service ps web
25 docker service inspect web
26 docker service logs web
27
28 # Scale service
29 docker service scale web=5
30
31 # Update service
32 docker service update --image nginx:alpine web

```



```

33 docker service update --replicas 10 web
34 docker service update --rollback web
35
36 # Remove service
37 docker service rm web
38
39 # Stack management
40 docker stack deploy -c docker-compose.yml mystack
41 docker stack ls
42 docker stack services mystack
43 docker stack ps mystack
44 docker stack rm mystack

```

## A.7 Registry & Authentication

### A.7.1 Registry Commands

Listing A.10: Registry Operations

```

1 # Login to registry
2 docker login
3 docker login myregistry.io
4 docker login -u username -p password myregistry.io
5 docker login ghcr.io -u USERNAME --password-stdin < token.txt
6
7 # Logout
8 docker logout
9 docker logout myregistry.io
10
11 # Search images
12 docker search nginx
13 docker search --filter stars=100 nginx
14
15 # Push/Pull with different registries
16 docker pull myregistry.io/myapp:v1.0.0
17 docker push ghcr.io/myorg/myapp:latest
18
19 # Tag for different registries
20 docker tag myapp:latest docker.io/myorg/myapp:latest
21 docker tag myapp:latest ghcr.io/myorg/myapp:latest
22 docker tag myapp:latest gcr.io/myproject/myapp:latest

```

## A.8 System Management

### A.8.1 System Commands

Listing A.11: System Operations

```

1 # System info
2 docker info
3 docker version
4 docker system df          # Disk usage
5
6 # Clean up
7 docker system prune      # Remove unused data

```

```

8  docker system prune -a                                # Remove all unused
9  docker system prune --volumes                          # Include volumes
10 docker system prune -a --volumes -f                   # Force, all+volumes
11
12 # Events
13 docker system events
14 docker system events --since 1h
15 docker system events --filter type=container
16
17 # Check plugins
18 docker plugin ls
19 docker plugin install plugin_name
20 docker plugin disable plugin_name
21 docker plugin rm plugin_name

```

## A.9 Security & Scanning

### A.9.1 Security Commands

Listing A.12: Security & Scanning

```

1  # Scan image (Docker Scout)
2  docker scout quickview myapp:latest
3  docker scout cves myapp:latest
4  docker scout recommendations myapp:latest
5
6  # Trivy scanning
7  trivy image myapp:latest
8  trivy image --severity HIGH,CRITICAL myapp:latest
9  trivy image --exit-code 1 myapp:latest
10 trivy fs .                                           # Scan filesystem
11
12 # Image signing (Cosign)
13 cosign sign --key cosign.key myregistry.io/myapp:v1.0.0
14 cosign verify --key cosign.pub myregistry.io/myapp:v1.0.0
15
16 # Secrets management (Swarm)
17 echo "password" | docker secret create db_pass -
18 docker secret ls
19 docker secret inspect db_pass
20 docker secret rm db_pass
21
22 # Config management
23 docker config create nginx_conf nginx.conf
24 docker config ls
25 docker config inspect nginx_conf
26 docker config rm nginx_conf

```

## A.10 Advanced Debugging

### A.10.1 Debugging Commands

Listing A.13: Debugging

```

1  # Container inspection

```

```

2  docker inspect --format='{{json .State}}' container | jq
3  docker inspect --format='{{.NetworkSettings.Networks}}' container
4
5  # Check container processes
6  docker top container
7  docker stats container --no-stream
8
9  # Port mappings
10 docker port container
11
12 # Filesystem changes
13 docker diff container
14
15 # Resource usage
16 docker stats --all --format "table {{.Name}}\t{{.CPUPerc}}\t{{.MemUsage
    }}"
17
18 # Network troubleshooting
19 docker network inspect bridge
20 docker exec container ping other_container
21 docker exec container netstat -tuln
22 docker exec container ip addr show
23
24 # Health check status
25 docker inspect --format='{{.State.Health.Status}}' container
26 docker inspect --format='{{json .State.Health}}' container | jq
27
28 # Check why container exited
29 docker inspect --format='{{.State.ExitCode}}' container
30 docker logs --tail 50 container

```

## A.11 Context & Remote Docker

### A.11.1 Context Management

Listing A.14: Docker Context

```

1  # List contexts
2  docker context ls
3
4  # Create context
5  docker context create remote-docker \
6    --docker "host=ssh://user@remote-host"
7
8  # Use context
9  docker context use remote-docker
10 docker context use default
11
12 # Inspect context
13 docker context inspect remote-docker
14
15 # Remove context
16 docker context rm remote-docker
17
18 # Remote Docker via SSH
19 docker -H ssh://user@remote-host ps
20 export DOCKER_HOST=ssh://user@remote-host

```

## A.12 BuildKit Advanced

### A.12.1 BuildKit Commands

Listing A.15: BuildKit

```
1 # Enable BuildKit
2 export DOCKER_BUILDKIT=1
3
4 # Buildx commands
5 docker buildx create --name mybuilder --use
6 docker buildx ls
7 docker buildx inspect mybuilder
8 docker buildx use mybuilder
9
10 # Multi-platform build
11 docker buildx build --platform linux/amd64,linux/arm64 \
12     -t myapp:latest --push .
13
14 # Build with cache
15 docker buildx build \
16     --cache-from type=registry,ref=myapp:buildcache \
17     --cache-to type=registry,ref=myapp:buildcache,mode=max \
18     -t myapp:latest .
19
20 # Build with secrets
21 docker buildx build \
22     --secret id=aws,src=$HOME/.aws/credentials \
23     -t myapp .
24
25 # Build with SSH
26 docker buildx build --ssh default -t myapp .
27
28 # Inspect build
29 docker buildx imagetools inspect myapp:latest
30
31 # Remove builder
32 docker buildx rm mybuilder
```

## A.13 Performance & Optimization

### A.13.1 Performance Commands

Listing A.16: Performance

```
1 # Benchmark build
2 time docker build -t myapp .
3
4 # Check layer sizes
5 docker history myapp:latest --human=true --no-trunc=false
6
7 # Analyze image
8 dive myapp:latest # Interactive layer analysis
9
10 # Check disk usage
11 docker system df -v
12
```

```

13 # Container resource limits
14 docker run -d \
15     --cpus="1.5" \
16     --memory="1g" \
17     --memory-reservation="512m" \
18     --pids-limit=100 \
19     myapp
20
21 # Check container resource usage
22 docker stats --no-stream --format \
23     "table {{.Name}}\t{{.CPUPerc}}\t{{.MemUsage}}\t{{.NetIO}}\t{{.BlockIO}}"
```

## A.14 Useful One-Liners

### A.14.1 Cheat Sheet One-Liners

Listing A.17: Useful One-Liners

```

1 # Remove all stopped containers
2 docker rm $(docker ps -aq -f status=exited)
3
4 # Remove all dangling images
5 docker rmi $(docker images -q -f dangling=true)
6
7 # Stop all running containers
8 docker stop $(docker ps -q)
9
10 # Get container IP address
11 docker inspect -f '{{range.NetworkSettings.Networks}}{{.IPAddress}}{{end}}' container
12
13 # Get container logs for last hour
14 docker logs --since 1h container
15
16 # Follow logs from all compose services
17 docker-compose logs -f --tail=100
18
19 # Execute command in all running containers
20 docker ps -q | xargs -I {} docker exec {} command
21
22 # Backup volume
23 docker run --rm -v myvolume:/data -v $(pwd):/backup \
24     alpine tar czf /backup/backup.tar.gz /data
25
26 # Restore volume
27 docker run --rm -v myvolume:/data -v $(pwd):/backup \
28     alpine tar xzf /backup/backup.tar.gz -C /
29
30 # Get all container IPs
31 docker ps -q | xargs docker inspect \
32     --format='{{.Name}} {{range.NetworkSettings.Networks}}{{.IPAddress}}{{end}}'
33
34 # Clean everything (DANGEROUS!)
35 docker system prune -a --volumes -f
36
```

```
37 # Monitor container resources real-time
38 watch -n 1 'docker stats --no-stream'
39
40 # Get environment variables from container
41 docker inspect --format='{{.Config.Env}}' container
42
43 # Check which containers use an image
44 docker ps -a --filter ancestor=myapp:latest
45
46 # Export container as tarball
47 docker export container > container-backup.tar
48
49 # Get container creation time
50 docker inspect --format='{{.Created}}' container
```

## A.15 Environment Variables

### A.15.1 Useful Docker Environment Variables

Listing A.18: Environment Variables

```
1 # Enable BuildKit
2 export DOCKER_BUILDKIT=1
3 export COMPOSE_DOCKER_CLI_BUILD=1
4
5 # Docker host
6 export DOCKER_HOST=tcp://192.168.1.10:2376
7 export DOCKER_HOST=ssh://user@remote
8 export DOCKER_HOST=unix:///var/run/docker.sock
9
10 # Docker TLS
11 export DOCKER_TLS_VERIFY=1
12 export DOCKER_CERT_PATH=/path/to/certs
13
14 # Registry config
15 export DOCKER_CONFIG=$HOME/.docker
16
17 # Buildx builder
18 export BUILDX_BUILDER=mybuilder
19
20 # Compose project
21 export COMPOSE_PROJECT_NAME=myproject
22 export COMPOSE_FILE=docker-compose.yml:docker-compose.override.yml
23
24 # Log driver
25 export DOCKER_LOGGING_DRIVER=json-file
26
27 # Default platform
28 export DOCKER_DEFAULT_PLATFORM=linux/amd64
```

## A.16 Quick Reference Tables

### A.16.1 Common Flags

Flag	Description
-d	Detached mode (background)
-it	Interactive + TTY
-rm	Auto-remove on exit
-p	Port mapping (host:container)
-v	Volume mount
-e	Environment variable
--name	Container name
--network	Network to connect
-u	User (UID:GID)
--restart	Restart policy
-w	Working directory
--entrypoint	Override entrypoint
--env-file	Load env from file
--link	Link to another container
-h	Hostname

### A.16.2 Restart Policies

Policy	Behavior
no	Never restart (default)
on-failure	Restart on non-zero exit
always	Always restart
unless-stopped	Restart unless manually stopped

### A.16.3 Network Drivers

Driver	Use Case
bridge	Single host networking
host	Use host network stack
overlay	Swarm multi-host networking
macvlan	Assign MAC address to container
none	Disable networking

## A.17 Riferimenti Rapidi

- Docker CLI Reference: <https://docs.docker.com/engine/reference/commandline/cli/>
- Docker Compose CLI: <https://docs.docker.com/compose/reference/>
- Dockerfile Reference: <https://docs.docker.com/engine/reference/builder/>
- Docker Hub: <https://hub.docker.com/>





## Appendice B

# Appendice: Progetti Completi

### B.1 Introduzione


Questa appendice contiene progetti completi end-to-end per consolidare le competenze Docker acquisite. Ogni progetto include Dockerfile ottimizzato, docker-compose.yml, CI/CD pipeline, monitoring setup, e deployment strategy.

#### Progetti Inclusi

1. **Full-Stack Web Application:** React + Node.js + PostgreSQL + Redis
2. **Microservices Architecture:** API Gateway + 3 Services + Message Queue
3. **WordPress Production Setup:** Nginx + PHP-FPM + MySQL + Redis
4. **Data Pipeline:** Apache Airflow + Postgres + Redis
5. **Monitoring Stack:** Prometheus + Grafana + Loki + Alertmanager
6. **CI/CD Platform:** Jenkins + Docker-in-Docker + Registry

### B.2 Progetto 1: Full-Stack MERN Application

#### B.2.1 Architettura



## B.2.2 Directory Structure

Listing B.1: Project Structure

```
1 fullstack-app/  
2 +-- frontend/  
3 |   +-- Dockerfile  
4 |   +-- package.json  
5 |   +-- src/  
6 |   +-- public/  
7 +-- backend/  
8 |   +-- Dockerfile  
9 |   +-- package.json  
10 |   +-- src/  
11 |   +-- tests/  
12 +-- nginx/  
13 |   +-- Dockerfile  
14 |   +-- nginx.conf  
15 +-- docker-compose.yml  
16 +-- docker-compose.prod.yml  
17 +-- .env.example  
18 +-- .dockerignore  
19 +-- .github/  
20     +-- workflows/  
21         +-- ci-cd.yml
```

## B.2.3 Frontend Dockerfile

Listing B.2: frontend/Dockerfile

```
1 # syntax=docker/dockerfile:1.4  
2  
3 # Stage 1: Build  
4 FROM node:20-alpine AS builder  
5  
6 WORKDIR /app  
7  
8 # Install dependencies  
9 COPY package*.json ./  
10 RUN --mount=type=cache,target=/root/.npm \  
11     npm ci  
12  
13 # Build application  
14 COPY . .  
15 RUN npm run build  
16  
17 # Stage 2: Production  
18 FROM nginx:alpine  
19  
20 # Copy built assets  
21 COPY --from=builder /app/build /usr/share/nginx/html  
22  
23 # Custom nginx config  
24 COPY nginx.conf /etc/nginx/conf.d/default.conf  
25  
26 # Health check  
27 HEALTHCHECK --interval=30s --timeout=3s \  
28     CMD curl -f http://localhost/ || exit 1
```

```

28     CMD wget --quiet --tries=1 --spider http://localhost/health || exit
      1
29
30 EXPOSE 80

```

### B.2.4 Backend Dockerfile

Listing B.3: backend/Dockerfile

```

1  # syntax=docker/dockerfile:1.4
2
3  FROM node:20-alpine AS base
4  RUN apk add --no-cache dumb-init
5  WORKDIR /app
6
7  # Dependencies
8  FROM base AS dependencies
9  COPY package*.json ./
10 RUN --mount=type=cache,target=/root/.npm \
11     npm ci --only=production
12
13 # Build
14 FROM base AS builder
15 COPY package*.json ./
16 RUN --mount=type=cache,target=/root/.npm \
17     npm ci
18 COPY . .
19 RUN npm run build
20
21 # Test
22 FROM builder AS test
23 ENV NODE_ENV=test
24 RUN npm run test
25
26 # Production
27 FROM base AS production
28
29 # Security: non-root user
30 RUN addgroup -g 1001 -S nodejs && \
31     adduser -S nodejs -u 1001
32
33 # Copy artifacts
34 COPY --from=dependencies --chown=nodejs:nodejs /app/node_modules ./
   node_modules
35 COPY --from=builder --chown=nodejs:nodejs /app/dist ./dist
36 COPY --chown=nodejs:nodejs package.json ./
37
38 USER nodejs
39
40 HEALTHCHECK --interval=30s --timeout=3s --start-period=40s \
41     CMD node healthcheck.js || exit 1
42
43 EXPOSE 3000
44
45 ENTRYPOINT ["dumb-init", "--"]
46 CMD ["node", "dist/server.js"]

```

## B.2.5 Docker Compose - Development

Listing B.4: docker-compose.yml

```

1 version: '3.8'
2
3 services:
4   # PostgreSQL Database
5   postgres:
6     image: postgres:15-alpine
7     environment:
8       POSTGRES_DB: ${DB_NAME:-appdb}
9       POSTGRES_USER: ${DB_USER:-appuser}
10      POSTGRES_PASSWORD: ${DB_PASSWORD:-changeme}
11     volumes:
12       - postgres-data:/var/lib/postgresql/data
13       - ./backend/init-db.sql:/docker-entrypoint-initdb.d/init.sql
14     ports:
15       - "5432:5432"
16     healthcheck:
17       test: ["CMD-SHELL", "pg_isready -U ${DB_USER:-appuser}"]
18       interval: 10s
19       timeout: 5s
20       retries: 5
21     networks:
22       - backend
23
24   # Redis Cache
25   redis:
26     image: redis:7-alpine
27     command: redis-server --appendonly yes
28     volumes:
29       - redis-data:/data
30     ports:
31       - "6379:6379"
32     healthcheck:
33       test: ["CMD", "redis-cli", "ping"]
34       interval: 10s
35       timeout: 3s
36       retries: 5
37     networks:
38       - backend
39
40   # Backend API
41   backend:
42     build:
43       context: ./backend
44       target: development
45     environment:
46       NODE_ENV: development
47       DATABASE_URL: postgresql://${DB_USER:-appuser}:${DB_PASSWORD:-
48         changeme}@postgres:5432/${DB_NAME:-appdb}
49       REDIS_URL: redis://redis:6379
50       JWT_SECRET: ${JWT_SECRET:-dev-secret}
51     volumes:
52       - ./backend/src:/app/src
53       - ./backend/package.json:/app/package.json
54       - backend-modules:/app/node_modules
55     ports:

```

```

55     - "3000:3000"
56     - "9229:9229"   # Debugger
57     depends_on:
58         postgres:
59             condition: service_healthy
60         redis:
61             condition: service_healthy
62     networks:
63         - backend
64         - frontend
65     command: npm run dev
66
67 # Frontend React App
68 frontend:
69     build:
70         context: ./frontend
71         target: development
72     environment:
73         REACT_APP_API_URL: http://localhost:3000
74         CHOKIDAR_USEPOLLING: "true"
75     volumes:
76         - ./frontend/src:/app/src
77         - ./frontend/public:/app/public
78         - ./frontend/package.json:/app/package.json
79         - frontend-modules:/app/node_modules
80     ports:
81         - "8080:3000"
82     networks:
83         - frontend
84     command: npm start
85
86 # Nginx Reverse Proxy
87 nginx:
88     image: nginx:alpine
89     volumes:
90         - ./nginx/nginx.dev.conf:/etc/nginx/nginx.conf:ro
91     ports:
92         - "80:80"
93     depends_on:
94         - backend
95         - frontend
96     networks:
97         - frontend
98
99 # Adminer (Database GUI)
100 adminer:
101     image: adminer:latest
102     ports:
103         - "8081:8080"
104     networks:
105         - backend
106     environment:
107         ADMINER_DEFAULT_SERVER: postgres
108
109 networks:
110     frontend:
111         driver: bridge
112     backend:

```

```

113     driver: bridge
114
115 volumes:
116     postgres-data:
117     redis-data:
118     backend-modules:
119     frontend-modules:

```

## B.2.6 Docker Compose - Production

Listing B.5: docker-compose.prod.yml

```

1 version: '3.8'
2
3 services:
4     postgres:
5         image: postgres:15-alpine
6         environment:
7             POSTGRES_DB: ${DB_NAME}
8             POSTGRES_USER: ${DB_USER}
9             POSTGRES_PASSWORD_FILE: /run/secrets/db_password
10        volumes:
11            - postgres-data:/var/lib/postgresql/data
12        networks:
13            - backend
14        secrets:
15            - db_password
16        deploy:
17            replicas: 1
18            restart_policy:
19                condition: on-failure
20            resources:
21                limits:
22                    cpus: '1'
23                    memory: 2G
24                reservations:
25                    cpus: '0.5'
26                    memory: 1G
27
28        redis:
29            image: redis:7-alpine
30            command: redis-server --requirepass ${REDIS_PASSWORD}
31            volumes:
32                - redis-data:/data
33            networks:
34                - backend
35            deploy:
36                replicas: 1
37                resources:
38                    limits:
39                        cpus: '0.5'
40                        memory: 512M
41
42        backend:
43            image: myregistry.io/backend:${VERSION:-latest}
44            environment:
45                NODE_ENV: production

```

```
46     DATABASE_URL_FILE: /run/secrets/database_url
47     REDIS_URL_FILE: /run/secrets/redis_url
48     JWT_SECRET_FILE: /run/secrets/jwt_secret
49 networks:
50   - backend
51   - frontend
52 secrets:
53   - database_url
54   - redis_url
55   - jwt_secret
56 deploy:
57   replicas: 3
58   update_config:
59     parallelism: 1
60     delay: 10s
61     order: start-first
62   restart_policy:
63     condition: on-failure
64   resources:
65     limits:
66       cpus: '1'
67       memory: 1G
68     reservations:
69       cpus: '0.25'
70       memory: 256M
71 healthcheck:
72   test: ["CMD", "node", "healthcheck.js"]
73   interval: 30s
74   timeout: 3s
75   retries: 3
76   start_period: 40s
77
78 frontend:
79   image: myregistry.io/frontend:${VERSION:-latest}
80   networks:
81     - frontend
82   deploy:
83     replicas: 2
84   resources:
85     limits:
86       cpus: '0.5'
87       memory: 256M
88
89 nginx:
90   image: myregistry.io/nginx:${VERSION:-latest}
91   ports:
92     - "80:80"
93     - "443:443"
94   volumes:
95     - ./nginx/ssl:/etc/nginx/ssl:ro
96   networks:
97     - frontend
98   depends_on:
99     - backend
100    - frontend
101   deploy:
102     replicas: 2
103   resources:
```

```
104     limits:
105         cpus: '0.5'
106         memory: 256M
107
108 secrets:
109     db_password:
110         external: true
111     database_url:
112         external: true
113     redis_url:
114         external: true
115     jwt_secret:
116         external: true
117
118 networks:
119     frontend:
120         driver: overlay
121     backend:
122         driver: overlay
123         internal: true
124
125 volumes:
126     postgres-data:
127     redis-data:
```

## B.2.7 Nginx Configuration

Listing B.6: nginx/nginx.conf

```
1 upstream backend {
2     least_conn;
3     server backend:3000 max_fails=3 fail_timeout=30s;
4 }
5
6 upstream frontend {
7     server frontend:80;
8 }
9
10 # Rate limiting
11 limit_req_zone $binary_remote_addr zone=api_limit:10m rate=10r/s;
12 limit_conn_zone $binary_remote_addr zone=addr:10m;
13
14 server {
15     listen 80;
16     server_name example.com;
17
18     # Security headers
19     add_header X-Frame-Options "SAMEORIGIN" always;
20     add_header X-Content-Type-Options "nosniff" always;
21     add_header X-XSS-Protection "1; mode=block" always;
22     add_header Strict-Transport-Security "max-age=31536000" always;
23
24     # Gzip compression
25     gzip on;
26     gzip_types text/plain text/css application/json application/
27         javascript;
28     gzip_min_length 1000;
```



```

28
29 # API endpoints
30 location /api {
31     limit_req zone=api_limit burst=20 nodelay;
32     limit_conn addr 10;
33
34     proxy_pass http://backend;
35     proxy_http_version 1.1;
36     proxy_set_header Upgrade $http_upgrade;
37     proxy_set_header Connection 'upgrade';
38     proxy_set_header Host $host;
39     proxy_set_header X-Real-IP $remote_addr;
40     proxy_set_header X-Forwarded-For $proxy_add_x_forwarded_for;
41     proxy_set_header X-Forwarded-Proto $scheme;
42     proxy_cache_bypass $http_upgrade;
43
44     # Timeouts
45     proxy_connect_timeout 60s;
46     proxy_send_timeout 60s;
47     proxy_read_timeout 60s;
48 }
49
50 # Frontend SPA
51 location / {
52     proxy_pass http://frontend;
53     proxy_set_header Host $host;
54     proxy_set_header X-Real-IP $remote_addr;
55
56     # SPA routing
57     try_files $uri $uri/ /index.html;
58 }
59
60 # Static assets caching
61 location ~* \.(jpg|jpeg|png|gif|ico|css|js|svg|woff|woff2|ttf)$ {
62     expires 1y;
63     add_header Cache-Control "public, immutable";
64 }
65
66 # Health check endpoint
67 location /health {
68     access_log off;
69     return 200 "OK\n";
70     add_header Content-Type text/plain;
71 }
72 }

```

## B.2.8 GitHub Actions CI/CD

Listing B.7: .github/workflows/ci-cd.yml

```

1 name: CI/CD Pipeline
2
3 on:
4   push:
5     branches: [main, develop]
6   pull_request:
7     branches: [main]

```

```
8
9 env:
10   REGISTRY: ghcr.io
11   IMAGE_PREFIX: ${github.repository}
12
13 jobs:
14   test-backend:
15     runs-on: ubuntu-latest
16     services:
17       postgres:
18         image: postgres:15
19         env:
20           POSTGRES_PASSWORD: test
21         options: >-
22           --health-cmd pg_isready
23           --health-interval 10s
24           --health-timeout 5s
25           --health-retries 5
26
27     steps:
28       - uses: actions/checkout@v4
29
30       - name: Setup Node.js
31         uses: actions/setup-node@v4
32         with:
33           node-version: '20'
34           cache: 'npm'
35           cache-dependency-path: backend/package-lock.json
36
37       - name: Install dependencies
38         working-directory: backend
39         run: npm ci
40
41       - name: Run linter
42         working-directory: backend
43         run: npm run lint
44
45       - name: Run tests
46         working-directory: backend
47         run: npm test
48     env:
49       DATABASE_URL: postgresql://postgres:test@localhost:5432/testdb
50
51       - name: Build
52         working-directory: backend
53         run: npm run build
54
55   test-frontend:
56     runs-on: ubuntu-latest
57     steps:
58       - uses: actions/checkout@v4
59
60       - name: Setup Node.js
61         uses: actions/setup-node@v4
62         with:
63           node-version: '20'
64           cache: 'npm'
65           cache-dependency-path: frontend/package-lock.json
```

```

66
67     - name: Install dependencies
68       working-directory: frontend
69       run: npm ci
70
71     - name: Run linter
72       working-directory: frontend
73       run: npm run lint
74
75     - name: Run tests
76       working-directory: frontend
77       run: npm test -- --coverage
78
79     - name: Build
80       working-directory: frontend
81       run: npm run build
82
83 build-and-push:
84   needs: [test-backend, test-frontend]
85   runs-on: ubuntu-latest
86   if: github.event_name != 'pull_request'
87   permissions:
88     contents: read
89     packages: write
90
91   strategy:
92     matrix:
93       service: [backend, frontend, nginx]
94
95   steps:
96     - uses: actions/checkout@v4
97
98     - name: Login to GitHub Container Registry
99       uses: docker/login-action@v3
100      with:
101        registry: ${ env.REGISTRY }
102        username: ${ github.actor }
103        password: ${ secrets.GITHUB_TOKEN }
104
105     - name: Extract metadata
106       id: meta
107       uses: docker/metadata-action@v5
108       with:
109         images: ${ env.REGISTRY }/${ env.IMAGE_PREFIX }/${ matrix
110           .service }
111         tags: |
112           type=ref,event=branch
113           type=sha
114           type=raw,value=latest,enable={{is_default_branch}}
115
116     - name: Build and push
117       uses: docker/build-push-action@v5
118       with:
119         context: ./${ matrix.service }
120         push: true
121         tags: ${ steps.meta.outputs.tags }
122         cache-from: type=registry,ref=${ env.REGISTRY }/${ env.
123           IMAGE_PREFIX }/${ matrix.service }:buildcache

```


```

122     cache-to: type=registry,ref=${{ env.REGISTRY }}/${{ env.
123         IMAGE_PREFIX }}/${{ matrix.service }}:buildcache,mode=max
124
125     deploy:
126       needs: build-and-push
127       runs-on: ubuntu-latest
128       if: github.ref == 'refs/heads/main'
129       environment: production
130
131       steps:
132         - uses: actions/checkout@v4
133
134         - name: Deploy to production
135           run: |
136             echo "Deploying to production..."
137             # Add deployment commands here

```

## B.3 Progetto 2: Microservices Architecture

### B.3.1 Architettura Microservices



### B.3.2 Microservices Docker Compose

Listing B.8: microservices/docker-compose.yml

```

1 version: '3.8'
2
3 services:
4   # API Gateway - Traefik
5   traefik:
6     image: traefik:v2.10
7     command:

```

```

8       - "--api.insecure=true"
9       - "--providers.docker=true"
10      - "--providers.docker.exposedbydefault=false"
11      - "--entrypoints.web.address=:80"
12      - "--metrics.prometheus=true"
13  ports:
14      - "80:80"
15      - "8080:8080"
16  volumes:
17      - /var/run/docker.sock:/var/run/docker.sock:ro
18  networks:
19      - microservices
20
21  # User Service
22  user-service:
23      build:
24          context: ./services/user
25      environment:
26          MONGO_URL: mongodb://mongodb:27017/users
27          RABBITMQ_URL: amqp://rabbitmq:5672
28      labels:
29          - "traefik.enable=true"
30          - "traefik.http.routers.user.rule=PathPrefix('/api/users')"
31          - "traefik.http.services.user.loadbalancer.server.port=3000"
32      depends_on:
33          - mongodb
34          - rabbitmq
35      networks:
36          - microservices
37      deploy:
38          replicas: 3
39
40  # Product Service
41  product-service:
42      build:
43          context: ./services/product
44      environment:
45          DATABASE_URL: postgresql://postgres:password@product-db:5432/
46                        products
47          RABBITMQ_URL: amqp://rabbitmq:5672
48      labels:
49          - "traefik.enable=true"
50          - "traefik.http.routers.product.rule=PathPrefix('/api/products')"
51          - "traefik.http.services.product.loadbalancer.server.port=3000"
52      depends_on:
53          - product-db
54          - rabbitmq
55      networks:
56          - microservices
57      deploy:
58          replicas: 3
59
60  # Order Service
61  order-service:
62      build:
63          context: ./services/order
64      environment:
65          DATABASE_URL: postgresql://postgres:password@order-db:5432/orders

```

```
65     RABBITMQ_URL: amqp://rabbitmq:5672
66     USER_SERVICE_URL: http://user-service:3000
67     PRODUCT_SERVICE_URL: http://product-service:3000
68     labels:
69       - "traefik.enable=true"
70       - "traefik.http.routers.order.rule=PathPrefix('/api/orders')"
71       - "traefik.http.services.order.loadbalancer.server.port=3000"
72     depends_on:
73       - order-db
74       - rabbitmq
75     networks:
76       - microservices
77     deploy:
78       replicas: 3
79
80 # MongoDB for User Service
81 mongodb:
82   image: mongo:7
83   volumes:
84     - mongodb-data:/data/db
85   networks:
86     - microservices
87
88 # PostgreSQL for Product Service
89 product-db:
90   image: postgres:15-alpine
91   environment:
92     POSTGRES_DB: products
93     POSTGRES_PASSWORD: password
94   volumes:
95     - product-db-data:/var/lib/postgresql/data
96   networks:
97     - microservices
98
99 # PostgreSQL for Order Service
100 order-db:
101   image: postgres:15-alpine
102   environment:
103     POSTGRES_DB: orders
104     POSTGRES_PASSWORD: password
105   volumes:
106     - order-db-data:/var/lib/postgresql/data
107   networks:
108     - microservices
109
110 # RabbitMQ Message Broker
111 rabbitmq:
112   image: rabbitmq:3-management-alpine
113   ports:
114     - "5672:5672"
115     - "15672:15672"
116   volumes:
117     - rabbitmq-data:/var/lib/rabbitmq
118   networks:
119     - microservices
120
121 # Prometheus
122 prometheus:
```

```

123     image: prom/prometheus:v2.48.0
124     volumes:
125       - ./prometheus/prometheus.yml:/etc/prometheus/prometheus.yml
126       - prometheus-data:/prometheus
127     ports:
128       - "9090:9090"
129     networks:
130       - microservices
131
132 # Grafana
133 grafana:
134   image: grafana/grafana:10.2.0
135   ports:
136     - "3000:3000"
137   environment:
138     GF_SECURITY_ADMIN_PASSWORD: admin
139   volumes:
140     - grafana-data:/var/lib/grafana
141   networks:
142     - microservices
143
144 networks:
145   microservices:
146     driver: overlay
147
148 volumes:
149   mongodb-data:
150   product-db-data:
151   order-db-data:
152   rabbitmq-data:
153   prometheus-data:
154   grafana-data:

```

## B.4 Progetto 3: WordPress Production

### B.4.1 WordPress Stack

Listing B.9: wordpress/docker-compose.yml

```

1 version: '3.8'
2
3 services:
4   nginx:
5     image: nginx:alpine
6     volumes:
7       - ./nginx.conf:/etc/nginx/nginx.conf:ro
8       - wordpress-data:/var/www/html:ro
9       - ./ssl:/etc/nginx/ssl:ro
10    ports:
11      - "80:80"
12      - "443:443"
13    depends_on:
14      - wordpress
15    networks:
16      - frontend
17    deploy:
18      replicas: 2

```

```

19     resources:
20     limits:
21         cpus: '0.5'
22         memory: 256M
23
24 wordpress:
25     image: wordpress:php8.2-fpm-alpine
26     environment:
27         WORDPRESS_DB_HOST: mysql
28         WORDPRESS_DB_USER: ${DB_USER}
29         WORDPRESS_DB_PASSWORD_FILE: /run/secrets/db_password
30         WORDPRESS_DB_NAME: ${DB_NAME}
31         WORDPRESS_REDIS_HOST: redis
32         WORDPRESS_REDIS_PORT: 6379
33     volumes:
34         - wordpress-data:/var/www/html
35         - ./php.ini:/usr/local/etc/php/conf.d/custom.ini
36     networks:
37         - frontend
38         - backend
39     secrets:
40         - db_password
41     deploy:
42         replicas: 3
43         resources:
44             limits:
45                 cpus: '1'
46                 memory: 512M
47
48 mysql:
49     image: mysql:8.0
50     environment:
51         MYSQL_DATABASE: ${DB_NAME}
52         MYSQL_USER: ${DB_USER}
53         MYSQL_PASSWORD_FILE: /run/secrets/db_password
54         MYSQL_ROOT_PASSWORD_FILE: /run/secrets/db_root_password
55     volumes:
56         - mysql-data:/var/lib/mysql
57         - ./mysql-config:/etc/mysql/conf.d
58     networks:
59         - backend
60     secrets:
61         - db_password
62         - db_root_password
63     deploy:
64         replicas: 1
65         resources:
66             limits:
67                 cpus: '2'
68                 memory: 2G
69
70 redis:
71     image: redis:7-alpine
72     command: redis-server --maxmemory 256mb --maxmemory-policy allkeys-
73         lru
74     volumes:
75         - redis-data:/data
76     networks:

```



```

76     - backend
77     deploy:
78         replicas: 1
79
80     # WP-CLI for management
81     wpcli:
82         image: wordpress:cli
83         user: "33:33"
84         volumes:
85             - wordpress-data:/var/www/html
86         networks:
87             - backend
88         command: wp --info
89         profiles:
90             - tools
91
92     secrets:
93         db_password:
94             external: true
95         db_root_password:
96             external: true
97
98     networks:
99         frontend:
100             driver: overlay
101         backend:
102             driver: overlay
103             internal: true
104
105     volumes:
106         wordpress-data:
107         mysql-data:
108         redis-data:

```

## B.5 Progetto 4: Data Pipeline con Airflow

### B.5.1 Apache Airflow Stack

Listing B.10: airflow/docker-compose.yml

```

1  version: '3.8'
2
3  x-airflow-common: &airflow-common
4      image: apache/airflow:2.7.0
5      environment:
6          AIRFLOW__CORE__EXECUTOR: CeleryExecutor
7          AIRFLOW__DATABASE__SQL_ALCHEMY_CONN: postgresql+psycopg2://airflow:
            airflow@postgres/airflow
8          AIRFLOW__CELERY__RESULT_BACKEND: db+postgresql://airflow:
            airflow@postgres/airflow
9          AIRFLOW__CELERY__BROKER_URL: redis://:@redis:6379/0
10         AIRFLOW__CORE__FERNET_KEY: ''
11         AIRFLOW__CORE__DAGS_ARE_PAUSED_AT_CREATION: 'true'
12         AIRFLOW__CORE__LOAD_EXAMPLES: 'false'
13         AIRFLOW__API__AUTH_BACKENDS: 'airflow.api.auth.backend.basic_auth'
14     volumes:
15         - ./dags:/opt/airflow/dags

```

```
16     - ./logs:/opt/airflow/logs
17     - ./plugins:/opt/airflow/plugins
18 user: "${AIRFLOW_UID:-50000}:0"
19 depends_on:
20     redis:
21         condition: service_healthy
22     postgres:
23         condition: service_healthy
24
25 services:
26     postgres:
27         image: postgres:15-alpine
28         environment:
29             POSTGRES_USER: airflow
30             POSTGRES_PASSWORD: airflow
31             POSTGRES_DB: airflow
32         volumes:
33             - postgres-db-volume:/var/lib/postgresql/data
34         healthcheck:
35             test: ["CMD", "pg_isready", "-U", "airflow"]
36             interval: 5s
37             retries: 5
38             restart: always
39
40     redis:
41         image: redis:latest
42         expose:
43             - 6379
44         healthcheck:
45             test: ["CMD", "redis-cli", "ping"]
46             interval: 5s
47             timeout: 30s
48             retries: 50
49             restart: always
50
51     airflow-webserver:
52         <<: *airflow-common
53         command: webserver
54         ports:
55             - 8080:8080
56         healthcheck:
57             test: ["CMD", "curl", "--fail", "http://localhost:8080/health"]
58             interval: 10s
59             timeout: 10s
60             retries: 5
61             restart: always
62
63     airflow-scheduler:
64         <<: *airflow-common
65         command: scheduler
66         healthcheck:
67             test: ["CMD-SHELL", 'airflow jobs check --job-type SchedulerJob --
68                 hostname "${HOSTNAME}"']
69             interval: 10s
70             timeout: 10s
71             retries: 5
72             restart: always
```

```

73 airflow-worker:
74     <<: *airflow-common
75     command: celery worker
76     healthcheck:
77         test:
78             - "CMD-SHELL"
79             - 'celery --app airflow.executors.celery_executor.app inspect
80               ping -d "celery@${HOSTNAME}"'
81         interval: 10s
82         timeout: 10s
83         retries: 5
84     restart: always
85     deploy:
86         replicas: 3
87
88 airflow-triggerer:
89     <<: *airflow-common
90     command: triggerer
91     healthcheck:
92         test: ["CMD-SHELL", 'airflow jobs check --job-type TriggererJob --
93             hostname "${HOSTNAME}"]
94         interval: 10s
95         timeout: 10s
96         retries: 5
97     restart: always
98
99 airflow-init:
100    <<: *airflow-common
101    entrypoint: /bin/bash
102    command:
103        - -c
104        - |
105            mkdir -p /sources/logs /sources/dags /sources/plugins
106            chown -R "${AIRFLOW_UID}:0" /sources/{logs,dags,plugins}
107            exec /entrypoint airflow version
108
109 flower:
110     <<: *airflow-common
111     command: celery flower
112     ports:
113         - 5555:5555
114     healthcheck:
115         test: ["CMD", "curl", "--fail", "http://localhost:5555/"]
116         interval: 10s
117         timeout: 10s
118         retries: 5
119     restart: always
120
121 volumes:
122     postgres-db-volume:

```

## B.6 Esercizi Pratici

### B.6.1 Esercizio 1: Multi-Stage Build Optimization

**Obiettivo:** Ottimizzare un Dockerfile esistente riducendo image size del 70%.

**Tasks:**

1. Convertire single-stage a multi-stage build
2. Implementare BuildKit cache mounts
3. Configurare .dockerignore completo
4. Misurare reduction in image size e build time

### B.6.2 Esercizio 2: Zero-Downtime Deployment

**Obiettivo:** Implementare blue-green deployment con Docker Swarm.

**Tasks:**

1. Setup Docker Swarm cluster (1 manager, 2 workers)
2. Deploy applicazione in ambiente "blue"
3. Deploy nuova versione in ambiente "green"
4. Implementare traffic switch script
5. Test rollback procedure

### B.6.3 Esercizio 3: Complete Observability

**Obiettivo:** Setup monitoring completo per microservices.

**Tasks:**

1. Deploy Prometheus + Grafana + Loki stack
2. Instrumentare 3 microservices con metrics
3. Configurare centralized logging
4. Creare Grafana dashboards
5. Setup alert rules e notification channels

### B.6.4 Esercizio 4: Security Hardening

**Obiettivo:** Applicare security best practices.

**Tasks:**

1. Scan existing images con Trivy/Snyk
2. Fix tutte le vulnerabilities CRITICAL/HIGH
3. Implementare non-root users
4. Configurare read-only filesystem
5. Setup secrets management con Vault
6. Implement image signing con Cosign

## B.7 Progetti Challenge

### B.7.1 Challenge 1: Production-Ready E-Commerce

Build complete e-commerce platform con:

- Frontend: Next.js
- Backend: NestJS API
- Databases: PostgreSQL + MongoDB + Redis
- Payment: Stripe integration
- Email: SMTP service
- Storage: MinIO (S3-compatible)
- Search: Elasticsearch
- CI/CD: GitHub Actions
- Monitoring: Prometheus/Grafana
- Requirements: 99.9% uptime, <200ms API latency

### B.7.2 Challenge 2: Scalable Chat Application

Real-time chat con WebSocket:

- Backend: Socket.io cluster
- Message broker: Redis Pub/Sub
- Database: PostgreSQL
- Load balancer: HAProxy
- Horizontal scaling: 3-10 instances
- Features: Typing indicators, read receipts, file sharing
- Metrics: Messages/sec, active connections, latency

## B.8 Soluzioni e Best Practices

### B.8.1 Deployment Strategy Decision Matrix

Strategy	Downtime	Resources	Complexity
Recreate	High	Low	Low
Rolling	None	Medium	Medium
Blue-Green	None	High (2x)	Medium
Canary	None	Medium	High
A/B Testing	None	Medium	High

### B.8.2 Resource Sizing Guide

Service Type	CPU	Memory
Node.js API	0.5-1 core	256-512MB
React SPA (built)	0.25 core	128MB
PostgreSQL	1-2 cores	1-2GB
Redis	0.5 core	256-512MB
Nginx	0.5 core	128-256MB

## B.9 Riferimenti

- Docker Samples: <https://github.com/docker/awesome-compose>
- Production Patterns: <https://github.com/docker/docker-bench-security>
- Kubernetes Patterns: <https://github.com/kubernetes/examples>
- Microservices Examples: <https://microservices.io/patterns/>