

1.-

```
public class BufferBroadcastUn {

    protected Object espai;
    protected boolean[] disponible;
    protected Lock lock;
    protected Condition productor, consumidor;
    protected int num_consumidores, consumits;

    public BufferBroadcastUn(int num_consumidores){
        disponible = new boolean[num_consumidores];
        lock = new ReentrantLock();
        productor = lock.newCondition();
        consumidor = lock.newCondition();
        this.num_consumidores = num_consumidores;
        consumits = num_consumidores;
    }

    public void putValue(Object val){
        lock.lock();
        if(consumits < num_consumidores){
            productor.await();
        }
        espai = val;
        consumits = 0;
        for(int i=0; i<disponible.length; i++){
            disponible[i] = true;
        }
        consumidor.signalAll();
        lock.unlock();
    }

    public Object getValue(int id){
        Object tmp;
        lock.lock();
        if(!disponible[id]){
            consumidor.await();
        }
        tmp = espai;
        disponible[id] = false;
        consumits++;
        if(consumits==num_consumidores){
            productor.signal();
        }
        lock.unlock();
        return tmp;
    }

}
```

2.-

// Client

```

class BufferBroadcastUnStub {

    MySocket s;

    BufferBroadcastUn() {
        s = new MySocket(localhost, 50000);
    }

    void putValue(Object v) {
        s.println("putValue");
        s.writeObject(v);
        s.readLine(); // sync
    }

    Object getValue(int id) {
        s.println("getValue");
        s.writeInt(id);
        return s.readObject(); // sync
    }
}

class Producer extends Thread {

    BufferBroadcastUnStub b;

    Producer(BufferBroadcastUnStub b) {
        this.b = b;
    }

    public void run() {
        while (true) {
            System.out.println("about to produce...");
            // v = ...
            b.putValue(v);
        }
    }
}

class Consumer extends Thread {

    BufferBroadcastUnStub b;
    int id;

    Consumer(BufferBroadcastUnStub b, int id) {
        this.b = b;
        this.id = id;
    }

    public void run() {
        while (true) {
            Object v = b.getValue(id);
            System.out.println("about to consume...");
        }
    }
}

```

```

        // ... = v
    }
}

class TestBufferBroadcastUnClient {

    final BufferBroadcastUnStub b = new BufferBroadcastUnStub();

    // producer
    new Producer(b).start();

    // consumers
    for (int i = 0; i < N; i++)
        new Consumer(b, i).start();
}

```

```

// Server
class BufferBroadcastUnSkel extends Thread {

    BufferBroadcastUn b;
    MySocket s;

    BufferBroadcastUnSkel(BufferBroadcastUn b, MySocket s) {
        this.b = b;
        this.s = s;
    }

    public void run() {
        while (true) {

            String op = s.readLine();

            if ("putValue".equals(op)) {
                b.putValue(s.readObject());
                s.println();
            } else if ("getValue".equals(op)) {
                s.writeObject(b.getValue(s.readInt()));
            } else {
                // error
            }
        }
    }
}

```

```

class TestBufferBroadcastUnServer {

    MyServerSocket ss = new MyServerSocket(50000);
    BufferBroadcastUn b = new BufferBroadcastUn();

    while (true) {
        MySocket s = ss.accept();
    }
}

```

```

        new BufferBroadcastUnSkel(b, s).start();
    }
}

```

3.-

```

- public void sendData(byte[] data, int data_off, int data_len) throws IOException {
    log.debug("%1$s->sendData(data.length=%2$d,data(0)=0x%3$x)", this, data_len,
data[data_off]);
    int n = 0;
    while (data_len > n) {
        int len = data_len - n;
        if (len > sndMSS) len = sndMSS;
        TCPSegment segment = new TCPSegment();
        segment.setSourcePort(localPort);
        segment.setDestinationPort(remotePort);
        segment.setFlags(TCPSegment.PSH);
        segment.setData(data, data_off + n, len);
        sendSegment(segment);
        n += len;
    }
}

```

4.-

```

- state = LISTEN;

- try {
    // wait some client to connect to me
    while (acceptQueue.empty()) appCV.await();

- while (state != ESTABLISHED) appCV.await(); // wait SYN is received

- ntcb.initActive(sourceAddr, rseg.getSourcePort(), ESTABLISHED);

- appCV.signalAll();

- state = ESTABLISHED;
  appCV.signalAll();

```

5.-

TCP provides a flow-control service to its applications to eliminate the possibility of the sender overflowing the receiver's buffer.

Flow control is thus a speed-matching service, matching the rate at which the sender is sending against the rate at which the receiving application is reading.

Flow control is different from congestion control:

We suppose throughout this section that the TCP implementation is such that the TCP receiver discards out-of-order segments.

TCP provides flow control by having the sender maintain a variable called the receive window.

Informally, the receive window is used to give the sender an idea of how much free buffer space is available at the receiver.

Let's investigate the receive window in the context of a file transfer. Suppose that Host A is sending a large file to Host B over a TCP connection. Host B allocates a receive buffer to this connection; denote its size by `RcvBuffer`. From time to time, the application process in Host B reads from the buffer.

Define the following variables:

- 1.-`LastByteRead`: the number of the last byte in the data stream read from the buffer by the application process in B
- 2.-`LastByteRcvd`: the number of the last byte in the data stream that has arrived from the network and has been placed in the receive buffer at B

Because TCP is not permitted to overflow the allocated buffer, we must have:

$$\text{LastByteRcvd} - \text{LastByteRead} \leq \text{RcvBuffer}$$

The receive window, denoted `rwnd` is set to the amount of spare room in the buffer:

$$\text{rwnd} = \text{RcvBuffer} - (\text{LastByteRcvd} - \text{LastByteRead})$$

Host B tells Host A how much spare room it has in the connection buffer by placing its current value of `rwnd` in the receive window field of every segment it sends to A.

Initially, Host B sets `rwnd = RcvBuffer`.

Host A in turn keeps track of two variables:

`LastByteSent` and `LastByteAcked`

`LastByteSent - LastByteAcked`: is the amount of unacknowledged data that A has sent into the connection.

By keeping the amount of unacknowledged data less than the value of `rwnd`, Host A is assured that it is not overflowing the receive buffer at Host B.

Thus, Host A makes sure throughout the connection's life that

$\text{LastByteSent} - \text{LastByteAcked} \leq \text{rwnd}$

Minor technical problem:

Suppose Host B's receive buffer becomes full so that

$\text{rwnd} = 0$

After advertising $\text{rwnd} = 0$ to Host A, also suppose that B has nothing to send to A!!

Now consider what happens. As the application process at B empties the buffer, TCP does not send new segments with new rwnd values to Host A; indeed, TCP sends a segment to Host A only if it:

- has data to send
- has an acknowledgment to send.

Therefore, Host A is never informed that some space has opened up in Host B's receive buffer-Host A is blocked and can transmit no more data!

To solve this problem, the TCP specification requires Host A to continue to send segments with one data byte when B's receive window is zero. These segments will be acknowledged by the receiver. Eventually the buffer will begin to empty and the acknowledgments will contain a nonzero rwnd value.