

Recipe Pos Tagger*

Mehmet Özgen

Department of Computer Engineering
Hacettepe University
Ankara, Turkey
mehmet.ozgen@hacettepe.com

Gönenç Ercan

Department of Computer Engineering
Hacettepe University
Ankara, Turkey
gonenc.ercan@hacettepe.edu.tr

İbrahim Ardic

Department of Computer Engineering
Hacettepe University
Ankara, Turkey
ibrahim.ardic@hacettepe.edu.tr

Pınar Duygulu Şahin

Department of Computer Engineering
Hacettepe University
Ankara, Turkey
pduygulu@hacettepe.edu.tr

ABSTRACT

A set of instructions is needed to systematically determine the steps of a task. The accuracy of this task is usually understood as the result of the work done. In this context, the correctness of instruction to action mapping is important in the recipes to be done consistently. In this work, we proposed a model by learning with the language processing techniques (Word2Vect, CRF++) of the work steps specified in the field which is specific to the field to reveal action order in the unclear situations. Furthermore, we build a parser that extract actions, ingredients and tools from given recipes and generate an action graph from parser results which accuracy is about 76 percent.

CCS CONCEPTS

• **Information systems** → **Document structure**; *Content analysis and feature selection*; **Document collection models**;

KEYWORDS

Information Retrieval, Natural Language Processing, weakly-labelled data, text analysis, big data

ACM Reference Format:

Mehmet Özgen, İbrahim Ardic, Gönenç Ercan, and Pınar Duygulu Şahin. 2018. Recipe Pos Tagger. In *Proceedings of The 41st International ACM SIGIR Conference on Research and Development in Information Retrieval (SIGIR'18)*. ACM, New York, NY, USA, Article 4, 4 pages.

1 INTRODUCTION

Computers have become increasingly more ambitious and popular, along with improvements in artificial intelligence and machine learning, to extract new information from sources such as text and video for people, or even to learn new tasks. These tasks are far more important than being taught, for example, when a robot is taught, when the need for care is directed or when the detail and ordering

of the work is very important (such as the repair of an airplane part). However, an event in each of these texts, how the work is done, the workflow can have various differences or mistakes in the final reading and understanding of formal differences in texts. Part of speech (POS) tagging is the key topic for information retrieval for extracting the valuable information that is used for classification, clustering etc. from any natural languages.

In this paper, it is aimed to automatically model the steps of a certain task by using text data which is easily accessible from the internet and to create methods and tool that can help people since there are many recipe documents and videos available on the internet, in this paper, working area is selected as cooking recipes. POS tagging is important that it constructs a description a set of instructions of a recipes which forms content based text analysis of our work.

In this paper we describe a rule-based tagger which performs as well as taggers based upon probabilistic models. The rule-based tagger overcomes the limitations common in rule-based approaches to language processing: it is robust, and the rules are automatically acquired. In addition, the tagger has many advantages over stochastic taggers, including: a vast reduction in stored information required, the perspicuity of a small set of meaningful rules as opposed to the large tables of statistics needed for stochastic taggers, ease of finding and implementing improvements to the tagger, and better portability from one tag set or corpus genre to another.

2 RELATED WORKS

Algorithmic processing of training texts and / or commands expressed in natural language has long been an interesting question [5]. In this problem, the artificial intelligence agent (such as a robot) is trying to learn the operations corresponding to symbols that are expressed in a field. The system is expected to automatically interact with definitions in the physical world as symbols to interact with objects and objects. We obtained through www.allrecipes.com.

[3] have developed a system that can act according to the expressions expressed in natural language in the system they developed. Based on the reinforced learning methods, the system can translate the sentences into natural language by using the information in the location (such as the objects on the wall) and the state flow that is modeled. As can be seen from these studies in the literature,

*Produces the permission block, and copyright information

Permission to make digital or hard copies of part or all of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. Copyrights for third-party components of this work must be honored. For all other uses, contact the owner/author(s).

SIGIR'18, July 2018, Ann Arbor, MI, USA

© 2018 Copyright held by the owner/author(s).

reinforcement learning techniques are used in problems where the current situation can be modeled more clearly.

A slightly different problem is [6] developed a similar method for solving problems expressed in mathematical texts. According to this method, the system is mapping the problem described in the text to a set of equations and producing the result. To learn the method, we use a training set marked at different levels. Equations that can be created in the system can be given or can be learned only when the last answer is given. In the method they developed, the solution is defined as diagrams, and a probability model that maps the information given in the text to the diagram is developed. Of course, it is necessary that the structure of the questionnaire is similar and that all of them can be transferred to the equation diagram.

Recipes can also be thought of as a set of steps that must be followed. From this point of view, there are common aspects to the problems described above. The most important difference is that it is difficult to convert the media knowledge to a reward function to provide reinforcement learning. The biggest reason for this is that it is difficult to model the correct sequence of operations that can be done while cooking. To overcome this problem in the processing of recipes, three different basic approaches are striking. The first is knowledge-based methods that are dependent on previously created knowledge vocabulary, the second is those using supervised learning methods, and the third is unsupervised learning and extracting a specific model from the data in the compilation. The first approach involves all the recipes, contents, tools and processes, and methods that can show the relationship between them. In the second approach, it is necessary to generate the data with the equivalent of the text for the training compilation. In the third category, transductive learning is performed according to the solutions given, ie it is not possible to classify the given samples and to process new ones.

2.1 Information Based Methods

[12] describes a method of generating flow diagrams from recipe texts, extracting recipe statements as material, processing and finishing conditions. Based on this information, a flow diagram is created. This method requires pre-tagged sentences and a dictionary that holds all of these tags.

Another problem that may be related is the creation of an information dictionary. [4] foods and their relationships with a Wiki-style method. Its approach basically consists of 6 hierarchies; diet and mealtime according to different features categorize the food. With this approach it is possible to adapt a new recipe or an existing recipe.

Although food-related ontology is increasingly detailed, these methods often fail to adapt to dynamic language and variety. Thus, when ontology methods are used alone, successful results are achieved for some data sets, but success is often low. Moreover, in order to adapt these methods to a different language, ontologies should be structured in accordance with other languages.

2.2 Supervised Learning Methods

One of the most important features of tutorial learning techniques is the target description model. Basically, the information that this

model needs to be able to show is where the processes described in the steps are done on which materials and where the output of this step is used. Some of these associations show in the tree structure [7], while some researchers show it in a non-cyclic manner [9]. It is possible that this notation can both express all the recipes and learn it automatically. [7] defined a representation in the tree data structure that stores food items and their relationships over the description steps. This demonstration can show which step of the recipes is related to which steps and materials.

[9] sees text in recipes as a Markov Decision Process problem by expanding semantic role labeling. It holds two things between the process and the material. The purpose of this relationship is to demonstrate the processes within the training that cause these situations to occur.

[10] created a labeling tool by showing recipes as non-cyclic charts in their initial work. With this tool, the recipe created a graph that indicates the skis over the text. The given Japanese recipes first extract the word segmentation, locate the words in the clan's tasks, label the named entities, and finally construct the predicate-argument structure.

In order to resolve the uncertainties in the contents, [1] tagged about 180,000 sentences for labeling and edited the tags of the words in the table of contents using the Conditional Random Fields method.

2.3 Unsupervised Learning Methods

In 2015, [8] has developed a method of learning without a teacher for the processing of recipes. Unlike previous works, this method learns the linkages of the line by using different parameters according to the variables in the system and using the expectation maximization method. Since this model is constructed according to the definition in the drawing, it is not possible to learn the features of an extragalactic recipe. In this respect, it is a transduction method, all the recipes to be processed have to be obtained at the model learning time. Moreover, the generated data model has a high number of implicit variables because it defines both the verbs, the contents, and the content of the contents in relation to the steps as one of the parameters of the model. When such high numbered models are learned, they can be found in a high number of local maxima, which prevents the optimum model from being found. It is intended to remove them as to which action is associated with the material, removing the flow of the recipe as a whole. These methods are inspired by semantic spaces used in text mining and meaning spaces that show word meaning relations. By using these material spaces, it is possible to determine which materials can be replaced instead of which materials. [11] used a similar method to define a method of learning materials for different types of food. Latent Dirichlet Allocation (LDA) and Deep Belief Networks (DBN) are used in the method. It has been seen that the output of the system can group materials according to the foods in different kitchens. A similar study has been proposed by [2] to produce safer food recommendations in meals. In this method, Singular Value Decomposition (SVD) method, which is widely used for extracting word meaning relations, is used.

3 EXPERIMENTAL SETUP

As seen in the literature, there are many methods aiming at revealing the relationship between the description texts and the contents of the description texts, the sequence of the process flow and the situations that occur during the actions and showing them with the models by many different methods. The texts should be easily perceivable by the computer by passing about 18000 recipes we obtained through www.alrecipes.com through certain operations.

Using NLTK libraries, each of the recipes was first converted into a clean text by separating individual recipes and separating them into words, punctuation, and meaningless words. (names, categories, contents, descriptions, and comments). Then each recipe is divided into sentences for labelling.

Algorithm 1: Data Retrieval and Preprocessing Overview

Function *ReadProcessData* *CvsFiles data*

```

forall the eachRecipe c in data do
    (ingredients, direction) = readDataFromCSVfile(c)
    ingreNewTag = calculateTAGWithCRF(ingredients)
    tokenizedD = tokenizeSentence(direction)
    taggedD = calculateTagsWithPOSTag(tokenizedD)
    taggedDirection = updateTag(taggedD, ingreNewTag)

```

This section we prepare data for the process, firstly, read data from csv file which is generated before and divide data into two parts, direction and ingredients. Using the NLTK library, labeling was done according to the culled state (VB, NN, ADJ, etc.) that each of the belts passed. As a result of the labeling made, "I can chopped green chile peppers" in the table of contents is labeled as below in TABLE 1. It was observed that 450 of 171.224 labeled samples were separated and tested and 89 percentage correctly tagged.

As can be seen in Table 1, it does not allow me to know that the word "life" is a unit of measure, "1" actually tells the quantity, and that the words "green" and "choped" are actually interpretations of a "papers" word.

The challenge of parsing the recipe is to be able to distinguish content components from component cues. Erica Greene (2016) has trained 171,244 sets (labeled as UNIT, QUANTITY, COMMENT and OTHER) with the very specific set of CRF ++ (Conditional Random Fields) method she has created to solve this problem and has been able to label the contents portion probabilistically with a newly given description. Let us have the sentence "1 teaspoon sugar". The model is using 171,224 tagged data to learn a model that can predict the tag sequence for any sentence we have given to it, even though we have never seen this component count before. It approaches this by modeling the conditional probability of a set of labels.

```

p (UNIT UNIT UNIT| "1 teaspoon sugar")
p (QUANTITY UNIT UNIT| "1 teaspoon sugar")
p (UNIT QUANTITY UNIT| "1 teaspoon sugar")

```

Table 1: Tags

chop	green	chile	peppers
VB	NN	NN	NN

```

p (UNIT UNIT QUANTITY "1 teaspoon sugar")
p (UNIT QUANTITY QUANTITY "1 teaspoon sugar")
p (QUANTITY QUANTITY QUANTITY | "1 teaspoon sugar")
p (UNIT QUANTITY NAME| "1 teaspoon sugar")

```

Secondly, tag direction and ingredients with the help of NLTK and CRF++ libraries. Tagging direction according to NLTK libraries is not satisfied in order to generate action graph. For this reason, update and change tags after NLTK process is finished.

Algorithm 2: Pos Tagging Overview

Function *updateTags* *Direction taggedDirection*

```

forall the sentence in taggedDirection do
    updateVerbs(sentence)
    updateTools(sentence)
    updateIngredients(sentence)
    findRelatedVerbsPair(direction)

```

As mentioned above, it calculates all the probabilities that can be labeled "1 teaspoon sugar". The beauty of the linear-chain CRF model makes some conditional independence assumptions that allow us to use dynamic programming to efficiently search the area of all possible label sequences. As a result, we have re-tagged our data with Erica Greene (2016), and the result is shown in TABLE 2. The results are shown in Table 2, which shows the best label sequence at a time that is linear with the number of second.

After, tags are updated according to neighbor tags, if the tag is "VB" and the neighbor tag is "DET" (determiners), two words are concatenated by the algorithm and tagged by "PRED". The CRF++ algorithm is tagged each word separately but the same tag, these are concatenated. That is depicted on the TABLE 3 and TABLE 4.

Finding action pairs with proximity values are required for graph generation. Generally, actions are sequential in the recipes, however, actions can be done parallel or some actions take duration while doing. So that, "preheat- PRED" is related with "bake for- PRED". This results show the relation between "preheat- PRED" and "bake for- PRED". In order to link "preheat- PRED" and "bake for- PRED" in the graph, we look at the similarity of the cosine with the actions.

Table 2: Tags

chop	green	chile	peppers
VB	CMMT	NAME	NAME

Table 3: Tags

put	the	peppers	into	the	pan
VB	DET	NAME	ADP	DET	TOOLS

Table 4: Tags

put	the peppers	into the pan
PRED	INGREDIENTS	NON IGRE SPAN

3.1 Calculation of Proximity

Kiddon et al. (2015), some words are not in the table of contents, but more than one is meant. (Eg mixture, them) Kiddon et al. (2015) defines this as a hidden object. He has created a probabilistic model to make hidden objects clear. In order to reveal these hidden objects, we present a relationship between the words 'NAME' in this action and its contents. In fact, each word is represented as a vector and we calculate the cosine similarity between them.

Using the Word2Vec library that displays 3.5 billion words created by a working group led by Tomas Mikolov (Google) as a 300-dimensional vector vocabulary, the words that pass through the intellectual part and are labeled 'NAME' have been converted into a 300-dimensional vector.

In the recipe sentence set, phrases without any word labeled 'NAME' are removed. When the words labeled as 'PRED' are extracted, all the words are converted into 300 dimensional vectors and the averages are taken. Because the other words around the word tagged by "VB" can also provide us with information about what materials the hidden object contains. If you only go through the actions, you will be made a comment by looking at the similarity of only two calves. However, the sentence can sometimes contain words that characterize the words in the contents. Let's take a look at "Cook the mixture until caramelized". It is labeled as "cook-PRED". When we look at the similarity of the cosine with the contents, it is seen that almost all of them resemble to each other. However, when the complex average of sentence is taken, "caramelized" word is included. And the result is more similar to "Onion" and "sugar". Taking the average of the blame for this reason actually brings us closer to the right conclusion. On the other hand, actions are generally sequential, some actions related with other actions. "preheat" is the action which is related with "bake for" action. Because after "preheat the oven", "bake for the mixture". this "preheat" action should be before the "bake for" action. "pre-heat" action result is related with "bake for" action. In order to find this relation and similarity about whole direction in the direction, we use Word2Vec library for finding cosine similarity between the actions. If the similarity bigger than threshold value that we select, the pairs and the similarity value are held in the list. Then the list is used for linking the action nodes in the graph.

Algorithm 3: Graph Generation and Validation

```

Function generateGraph taggedRecipe recipe, verbPairs, pairs
  actionNodeList = []
  forall the sentence in recipe do
    actionN = generateSentNode(sentence)
    actionNodeList.append(actionN)
  forall the action in actionNodeList do
    linkTheAction(action, pairs)

```

4 RESULTS

5 CONCLUSIONS

This paragraph will end the body of this sample document. Remember that you might still have Acknowledgments or Appendices;

brief samples of these follow. There is still the Bibliography to deal with; and we will make a disclaimer about that here: with the exception of the reference to the \LaTeX book, the citations in this paper are to articles which have nothing to do with the present subject and are used as examples only.

ACKNOWLEDGMENTS

REFERENCES

- [1] [n. d.]. Our Tagged Ingredients Data is Now on GitHub. <https://open.blogs.nytimes.com/author/erica-greene/>. ([n. d.]). Accessed: 2018-01-17.
- [2] P Achananuparp and I Weber. 2016. Extracting food substitutes from food diary via distributional similarity. CoRR, abs/1607.08807. (2016).
- [3] David L Chen and Raymond J Mooney. 2011. Learning to Interpret Natural Language Navigation Instructions from Observations.
- [4] Emmanuelle Gaillard, Emmanuel Nauer, Marie Lefevre, and Amélie Cordier. 2012. Interactive Cooking Adaptation Knowledge Discovery for the TAAABLE Case-Based Reasoning System. In *Workshop Cooking with Computer-Conference ECAI 2012*. 19–28.
- [5] Stevan Harnad. 1990. The Symbol Grounding Problem. *Physica D: Nonlinear Phenomena* 42 (1990), 335–346. [https://doi.org/10.1016/0167-2789\(90\)90087-6](https://doi.org/10.1016/0167-2789(90)90087-6)
- [6] Mohammad Javad Hosseini, Hannaneh Hajishirzi, Oren Etzioni, and Nate Kushman. 2014. Learning to Solve Arithmetic Word Problems with Verb Categorization.. In *EMNLP*. 523–533.
- [7] Jermsak Jermsurawong and Nizar Habash. 2015. Predicting the Structure of Cooking Recipes. In *Proceedings of the 2015 Conference on Empirical Methods in Natural Language Processing*. Association for Computational Linguistics, Lisbon, Portugal, 781–786. <http://aclweb.org/anthology/D15-1090>
- [8] Chloé Kiddon, Ganesa Thandavam Ponnuraj, Luke Zettlemoyer, and Yejin Choi. 2015. Mise en place: Unsupervised interpretation of instructional recipes. In *Proceedings of the 2015 Conference on Empirical Methods in Natural Language Processing*. 982–992.
- [9] Jon Malmaud, Earl J Wagner, Nancy Chang, and Kevin Murphy. 2014. Cooking with semantics. In *Proceedings of the ACL 2014 Workshop on Semantic Parsing*. 33–38.
- [10] Shinsuke Mori, Hirokuni Maeta, Yoko Yamakata, and Tetsuro Sasada. 2014. Flow Graph Corpus from Recipe Texts.. In *LREC*. 2370–2377.
- [11] V Nedovic. 2013. Learning recipe ingredient space using generative probabilistic models. In *Proceedings of Cooking with Computers Workshop (CwC)*, Vol. 1. 13–18.
- [12] Kirstin Walter, Mirjam Minor, and Ralph Bergmann. 2011. Workflow extraction from cooking recipes. In *Proceedings of the ICCBR 2011 Workshops*. 207–216.