cansas1d SASentry

From canSAS

block diagrams



■ parent: SASroot

Name	Type	occurrence	Description	Attributes
Title	string	[11]	Title of this SASentry .	
Run	string	[1unbounded]	Run identification for this SASentry . For many facilities, this is an integer. Use multiple instances of Run as needed. Note: How to correlate this with SASdata and SASinstrument configurations has not yet been defined. name is an optional string attribute to identify this particular Run . Could use this to associate (correlate) multiple SASdata elements with Run elements. (Give them the same <i>short-Run-identifier</i> .)	name="{short- Run-identifier}"
{any}	container	[0unbounded]	Any element(s) not defined in the cansas1d/1.0 standard can be placed at this point. See {any} for more details.	xmlns:{foreign- prefix}="{foreign- namespace}"
SASdata	container	[1unbounded]	Reduced 1-D SAS data for this SASentry. Use multiple SASdata elements to represent multiple	name="{short- Run-identifier}"

1 of 2 5/28/2009 2:01 PM

			frames. Use this to associate (correlate) multiple SASdata elements with Run elements. (Give them the same name.)	
{any}	container	[0unbounded]	at this point. See Jamy for more	xmlns:{foreign- prefix}="{foreign- namespace}"
SASsample	container	[11]	Description of the sample.	name="{short- SASsample- identifier}"
SASinstrument	container	[11]	Description of the instrument	
SASprocess	container	[0unbounded]	Description of a processing or analysis step.	name="{short- SASprocess- identifier}"
SASnote	container	[1unbounded]	Free form description of anything not covered by other elements.	name="{short- SASnote- identifier}"

 $\underline{Retrieved\ from\ "http://www.smallangles.net/wgwiki/index.php/cansas1d_SASentry"}$

■ This page was last modified 20:43, 25 April 2008.

2 of 2