Cheat Sheet for EE464

$$FormFactor = \frac{V_{rms}}{V_{avg}}$$
$$CrestFactor = \frac{V_{peak}}{V_{rms}}$$
$$DistortionFactor = \frac{I_{1rms}}{I_{rms}}$$

ϕ : *phase difference between fundamentals of current and voltage*

$$DisplacementPowerFactor = \cos(\phi)$$
$$TruePowerFactor = \frac{P}{S} = DPF\frac{I_{1,RMS}}{I_{RMS}}$$
$$THD = \sqrt{(\frac{I_{rms}}{I_{1rms}})^2 - 1}$$

Converters

$$V_o = V_s\left(\frac{D}{1-D}\right)\left(\frac{N_2}{N_1}\right) \qquad \frac{\Delta V_o}{V_o} = \frac{D}{RCf} \qquad (L_m)_{\min} = \frac{(1-D)^2R}{2f}\left(\frac{N_1}{N_2}\right)^2$$

$$I_{L_{m,\max}} = I_{L_m} + \frac{\Delta i_{L_m}}{2} \qquad L_m = \frac{V_sDT}{\Delta i_{L_m}} = \frac{V_sD}{\Delta i_{L_m}f}$$

$$= \frac{V_sD}{(1-D)^2R}\left(\frac{N_2}{N_1}\right)^2 + \frac{V_sDT}{2L_m}$$

$$I_{L_{m,\min}} = I_{L_m} - \frac{\Delta i_{L_m}}{2} \quad \text{equate this to zero for dcm boundary}$$

$$= \frac{V_sD}{(1-D)^2R}\left(\frac{N_2}{N_1}\right)^2 - \frac{V_sDT}{2L_m}$$

$$\Delta V_{o,\mathrm{ESR}} = \Delta i_C r_C = I_{L_{m,\max}}\left(\frac{N_1}{N_2}\right) r_C$$

$$(\Delta i_{L_m})_{\text{closed}} = \frac{V_sDT}{L_m} = \frac{V_o(1-D)T}{L_m}\left(\frac{N_1}{N_2}\right) = (\Delta i_{L_m})_{\text{open}}$$

Figure 1: Flyback Formulas

$$V_o = V_sD\left(\frac{N_2}{N_1}\right) \qquad \frac{\Delta V_o}{V_o} = \frac{1-D}{8L_xCf^2}$$

$$\Delta V_{o,\mathrm{ESR}} = \Delta i_C r_C = \Delta i_{L_x} r_C = \left[\frac{V_o(1-D)}{L_xf}\right] r_C$$

$$\Delta i_{L_m} = \frac{V_sDT}{L_m}$$

Figure 2: Forward (single switched) Converter Formulas

$$V_o = 2V_s\left(\frac{N_S}{N_P}\right)D \qquad \frac{\Delta V_o}{V_o} = \frac{1-2D}{32L_xCf^2}$$

$$\Delta V_{o,ESR} = \Delta i_{L_x} r_C = \left[\frac{V_o\left(\frac{1}{2}-D\right)}{L_xf}\right] r_C$$

Figure 3: Push Pull Formulas



Figure 4: Sepic and Cuk Converter Schematics

$$SwitchUtilization = \frac{Po}{Psw} = \frac{Io.Vo}{q.Vswmax.Iswmax} \qquad (1)$$

Inverters

$$m_f = \frac{f_s}{f_1}, m_a = \frac{V_{control}}{V_{triangle}}$$

$$V_o = V_s\left(\frac{D}{1-D}\right) \qquad \Delta V_{C_1} = \frac{I_oDT}{C} = \frac{V_oD}{RC_1f}$$

$$\Delta i_{L_1} = \frac{V_sDT}{L_1} = \frac{V_sD}{L_1f} \qquad \Delta V_o = \Delta V_{C_2} = \frac{V_oD}{RC_2f}$$

$$\Delta i_{L_2} = \frac{V_sDT}{L_2} = \frac{V_sD}{L_2f} \qquad C_1 = \frac{D}{R(\Delta V_{C_1}/V_o)f}$$

$$C_2 = \frac{D}{R(\Delta V_o/V_o)f}$$

Figure 5: Sepic Converter Formulas

$$V_o = -V_s\left(\frac{D}{1-D}\right) \qquad \frac{\Delta V_o}{V_o} = \frac{1-D}{8L_2C_2f^2}$$

$$\Delta v_{C_1} \approx \frac{1}{C_1}\int_{DT}^{T} I_{L_1}d(t) = \frac{I_{L1}}{C_1}(1-D)T = \frac{V_s}{RC_1f}\left(\frac{D^2}{1-D}\right)$$

$$\Delta v_{C_1} \approx \frac{V_oD}{RC_1f}$$

$$\Delta i_{L1} = \frac{V_sDT}{L_1} = \frac{V_sD}{L_1f} \qquad \Delta i_{L_2} = \frac{V_sDT}{L_2} = \frac{V_sD}{L_2f}$$

$$L_{1,\min} = \frac{(1-D)^2R}{2Df} \qquad L_{2,\min} = \frac{(1-D)R}{2f}$$

Figure 6: Cuk Converter Formulas

Switch Selection

Peak Switch Current

$$\hat{I}_{sw} = \frac{1}{(1-D)}\frac{N_2}{N_1}I_o + \frac{N_1}{N_2}\frac{(1-D)T_s}{2L_m}V_o$$

Peak Switch Voltage

$$\hat{V}_{sw} = V_d + \frac{N_1}{N_2}V_o = \frac{V_d}{(1-D)}$$

Figure 7: Flyback switch considerations

$$V_o = 2V_s\left(\frac{N_S}{V_P}\right)D \qquad V_o = V_s\left(\frac{N_S}{N_p}\right)D$$

Full Bridge **Half Bridge**

Figure 8: Full and Half Bridge Relations



Figure 9: Bipolar Switching



Figure 10: Unipolar switching

$m_a < 1 : linear, m_a > 1 : overmodulation$



Figure 11: Bipolar Switching



Figure 12: Unipolar switching

Cuk Converter

$$Vc1 = Vo + Vd \tag{2}$$

Transformer Analysis

$$V_{rms} = \frac{2\pi}{\sqrt{2}}.N_2.f.B_{max}.A \tag{3}$$