

Package ‘rccShiny’

May 4, 2017

Type Package

Version 1.0.0

Title Shiny apps for RCC

Description Creates shiny apps used as a complement to the annual reports from the cancer quality registries in Sweden.

Depends R (>= 3.3.3)

Imports DT (>= 0.2),
gplots (>= 3.0.1),
Hmisc (>= 4.0.2),
plyr (>= 1.8.4),
shiny (>= 1.0.2),
sp (>= 1.2.4)

Encoding UTF-8

LazyData TRUE

License GPL (>= 3)

RoxygenNote 6.0.1

Author Fredrik Sandin, RCC Uppsala-Örebro

Maintainer Lina Benson <lina.enqvist-benson@sll.se>

Repository bitbucket.org/cancercentrum/rccshiny

Date 2017-05-xx

R topics documented:

rccShiny	2
rccShinyData	5
Index	6

Description

returns shiny apps used as a complement to the annual reports from the cancer quality registries in Sweden.

Usage

```
rccShiny(data = NULL, outcome = "outcome", outcomeTitle = outcome,
  folder = "ind", folderLinkText = outcomeTitle, path = getwd(),
  titleTextBeforeSubtitle = NULL, titleTextAfterSubtitle = NULL,
  comment = "", description = c("(beskrivning saknas)",
    "(description missing)"), geoUnitsHospital = "sjukhus",
  geoUnitsCounty = "landsting", geoUnitsRegion = "region",
  geoUnitsFromLKF = FALSE, regionSelection = TRUE,
  regionLabel = c("Begränsa till region", "Limit to region"),
  period = "period", periodLabel = c("Diagnosår", "Year of diagnosis"),
  userInputList = NULL, targetValues = NULL, funnelplot = FALSE,
  targetValuesSortDescending = NULL, hideLessThan = 5, language = c("sv"),
  npcrGroupPrivateOthers = TRUE)
```

Arguments

data	data frame containing the variables used in the app.
outcome	vector with the name(s) of the variable(s) of interest, for example a "kvalitetsindikator". Default is "outcome".
outcomeTitle	label(s) of the outcome(s). Must be the same length as argument outcome. Default is argument outcome (name(s) of the outcome(s) in the dataset).
folder	name of folder where the results are placed.
folderLinkText	short name used in html link??? glunkiglunk. Fredrik: HJÄLP SÖKES!
path	searchpath to folder. Default is working directory.
titleTextBeforeSubtitle	optional text placed before the subtitles in the tabs.
titleTextAfterSubtitle	optional text placed after the subtitles in the tabs.
comment	optional comment printed under the sidebar panel.
description	description shown in the tab Beskrivning/Description.
geoUnitsHospital	optional character vector with hospital names. At least one geoUnit needs to be given. To be implemented: Hospital codes.
geoUnitsCounty	optional numeric vector with county codes. Can be either county of residence for the patient or the county the hospital belongs to. See details for valid values. At least one geoUnit needs to be given. To be implemented: Codes for county of hospital are fetched automatically from hospital codes.

geoUnitsRegion	optional numeric vector with region codes (1=Stockholm, 2=Uppsala-Örebro, 3=Sydöstra, 4=Södra, 5=Västra, 6=Norra). At least one geoUnit needs to be given. To be implemented: Codes for region of hospital are fetched automatically from hospital codes.
geoUnitsFromLKF	if geoUnitsCounty is county of residence for the patient (LKF). If FALSE and a hospital is chosen by the user in the sidebar panel the output is highlighted for the respective county/region that the hospital belongs to. Default is FALSE.
regionSelection	adds a widget to the sidebar panel with the option to show only one region at a time. Default is TRUE.
regionLabel	used if regionSelection = TRUE. Label of widget shown in the sidebar panel. Default is c("Begränsa till region", "Limit to region").
period	numeric vector with time periods, for example year of diagnosis. Default is "period".
periodLabel	label for the period widget in the sidebar panel. Default is c("Diagnosår", "Year of diagnosis").
userInputList	list with variables (other than period and geoUnits) to be shown in sidebar panel. Arguments to the list are: var (variable name in dataset), label (label shown over widget in sidebar panel), choices (which values of var should be shown, min, max for continuous variables).
targetValues	optional vector of 1-2 targetvalues ("målnivåer") to be plotted in the tab Jämförelse/Comparison. Only applicable for dichotomous variables.
funnelplot	adds a widget to the sidebar panel with the option to show a funnel plot in the tab Jämförelse/Comparison. Only applicable for dichotomous variables. Default is FALSE. Currently not implemented and always set to TRUE.
targetValuesSortDescending	should the bars in tab Jämförelse/Comparison be plotted in descending order. Default is TRUE.
hideLessThan	optional value under which groups (cells) are suppressed. Default is 5 and all values < 5 are set to 5.
language	vector giving the language for the app. Possible values are "sv" and "en". Default is "sv". See details.
npcrGroupPrivateOthers	Applicable for NPCR only. FREDRIK: vad ska stå? Ska default vara TRUE?

Details

Valid values for geoUnitsCounty are:

geoUnitsFromLKF	!geoUnitsFromLKF	Text
1	10,11	Stockholm
3	12	Uppsala
4	13	Södermanland
5	21	Östergötland
6	22	Jönköping
7	23	Kronoberg
8	24,25	Kalmar
9	26	Gotland
10	27	Blekinge

12	28,30,41	Skåne
13	42	Halland
14	50,51,52,53	Västra Götaland
17	54	Värmland
18	55	Örebro
19	56	Västmanland
20	57	Dalarna
21	61	Gävleborg
22	62	Västernorrland
23	63	Jämtland
24	64	Västerbotten
25	65	Norrbottn
-	91,92,93,94,95,96	Övriga/privata - region

If language = c("sv", "en") the following applies to arguments: outcomeTitle, titleTextBeforeSubtitle, titleTextAfterSubtitle, comment, description, regionLabel, label in list userInputList: if there are two values the first is used in the swedish version and the second in the english version. These must be given in order sv, en. If there is only one value this is recycled in both versions. The following applies to arguments outcome, geoUnitsHospital, geoUnitsCounty, geoUnitsRegion, period, var in list userInputList: in the english version rccShiny will use the variable name with the suffix _en (for example "outcome_en") if this exists and otherwise recycle the swedish variable name.

Value

A folder path/apps/svlen/folder containing: global.R, server.R, ui.R, data/data.RData, docs/description.html.

Author(s)

Fredrik Sandin, RCC Uppsala-Örebro

Examples

```
rccShiny(
  data = rccShinyData,
  folder = "Indikator1",
  path = "C:/Users/5521/test_rccShiny",
  outcome = paste0("outcome",1:3),
  outcomeTitle = c("Dikotom", "Kontinuerlig", "Kategorisk"),
  comment = "Skovde och Lidköping tillhör Skaraborg",
  description = "Att tanka på vid tolkning ...",
  userInputList = list(
    list(
      var = "age",
      label = "Ålder vid diagnos"
    ),
    list(
      var = "stage",
      label = "Stadium",
      choices = c("I", "II")
    )
  ),
  funnelplot = TRUE
)
## Not run:
library(shiny)
```

```

runApp("C:/Users/5521/test_rccShiny/apps/sv/Indikator1")

## End(Not run)

# For Swedish/English version
rccShinyData$outcome1_en <- rccShinyData$outcome1
rccShiny(
  data = rccShinyData,
  folder = "Indikator2",
  outcome = "outcome1",
  outcomeTitle = c("Kontaktsjukskoterska", "Contact nurse"),
  titleTextBeforeSubtitle = c("Nagot pÅ¥ svenska", "Something in English"),
  description = c("Superbra att ha!", "Supergood to have!"),
  userInputList = list(
    list(
      var = "age",
      label = c("Alder vid diagnos", "Age at diagnosis"),
      choices = c(0,120)
    )
  ),
  targetValues = c(95,99),
  language = c("sv", "en")
)

```

rccShinyData

Testdata for RCC shiny apps

Description

Data set used in the examples given in the function rccShiny.

Usage

```
rccShinyData
```

Format

A data frame with 20000 rows and 9 variables:

sjukhus a character vector containing hospitals names.

landsting a numeric vector containing codes for the 'landsting' for the respective hospitals.

region a numeric vector containing codes (1-6) for the region for the respective hospitals.

period year of diagnosis (2012-2016).

age patients age at diagnosis.

outcome1 dichotomous outcome (logical: TRUE/FALSE).

outcome2 continuous outcome (numeric).

outcome3 categorical outcome with 5 levels (factor).

stage patients stage at diagnosis.

Index

*Topic **datasets**
rccShinyData, [5](#)

rccShiny, [2](#)
rccShinyData, [5](#)