SIMATS ENGINEERING
ASSESSMENT TOOL 1

COURSE NAME: CSA07 **COURSE CODE:** Computer Networks

COURSE OUTCOME COVERED

CO1: *Apply the functions of OSI layer in enabling reliable data transmission across networks. (BL2, BL3)*

Assessment Tool Weightage: 40%

Annexure A

SHORT ANSWER TEST

Code of Conduct:

I Candace Carol P.C (1965200103) *(Name / Reg No) certify that this submission is my original work and that I have adhered to the guidelines specified for this assessment.*
I understand that any violation of academic integrity rules will result in disciplinary action.

Signature of the student: Candace

Criteria	Weightage	Q1 10marks	Q2 10marks	Q3 10marks	Q4 10marks
Understanding of Concepts	25%	2	2	2	2
Explanation	25%	2	2	2	1
Application	20%	2	2	1	–
Organization	15%	2	2	–	–
Accuracy	10%	–	–	–	–
Clarity	5%	–	–	–	–

Total Marks 24 /40

Signature of the Faculty

vivo V20 SE

Short Answer Test

1. A company needs to transfer a **150 MB** design file from a client computer to a remote server over a network with a bandwidth of **50 Mbps**. The Transport Layer divides the file into **1500-byte segments**, while the Data Link Layer encapsulates each segment into frames by adding **40 bytes of header and trailer**. Calculate the total number of segments and frames transmitted, the total transmission overhead introduced by the Data Link Layer, and estimate the total transmission time (ignoring propagation delay). Explain how the Transport and Data Link layers ensure reliable communication.

2. A Transport Layer protocol uses a **sliding window size of 6 frames**. Each frame carries **1024 bytes** of user data. If the sender transmits **48 frames**, calculate the number of transmission windows required. If one frame in every window is lost and must be retransmitted, determine the total number of retransmissions. Explain how flow control improves communication efficiency.

3. A **12,000-byte** IP packet is transmitted through a router where the Maximum Transmission Unit (MTU) is **1500 bytes**. Assuming each fragment requires a **20-byte IP header**, calculate the total number of fragments created and the total header overhead introduced. Explain how the Network Layer ensures successful delivery of fragmented packets to the destination.

4. A Transport Layer protocol uses a **sliding window size of 6 frames**. Each frame carries **1024 bytes** of user data. If the sender transmits **48 frames**, calculate the number of transmission windows required. If one frame in every window is lost and must be retransmitted, determine the total number of retransmissions. Explain how flow control improves communication efficiency.

5. A multimedia application transfers a **600 MB** video file. The Session Layer inserts a synchronization checkpoint after every **60 MB** of transmitted data. During transmission, a failure occurs after **390 MB** has been transferred. Determine the number of checkpoints created before failure and calculate the amount of data that must be retransmitted after recovery. Explain the importance of synchronization in the Session Layer.

6. Before transmission, the Presentation Layer compresses a **900 MB** file by **40%**. The compressed data is encrypted, adding **5%** overhead to the compressed size. Calculate the compressed file size, the encrypted file size, and the total percentage reduction compared to the original file. Explain how the Presentation Layer improves transmission efficiency and security.

7. An FTP application transfers **3 GB** of data over a network with an effective throughput of **120 Mbps**. The Application Layer divides the data into requests of

vivo V20 SE

3 MB each. Calculate the total number of requests generated and estimate the total transmission time in seconds. Discuss how the Application Layer provides reliable services to users.

8.A packet experiences the following processing delays at different OSI layers: Application Layer = **4 ms**, Transport Layer = **3 ms**, Network Layer = **5 ms**, Data Link Layer = **2 ms**, and Physical Layer = **1 ms**. The propagation delay is **18 ms**, and the transmission delay is **12 ms**. Calculate the total end-to-end delay experienced by the packet and explain how each layer contributes to the communication process.

9.A network transfers **80 MB** of useful data using frames of **1600 bytes**, where each frame contains **80 bytes** of protocol overhead added by different OSI layers. Calculate the total number of frames required, the total overhead transmitted, and the transmission efficiency as a percentage. Explain how protocol overhead affects network performance.

10.A hospital transfers a patient's medical record of **240 MB** through an IoT-enabled healthcare network. The Presentation Layer compresses the data by **30%**, the Transport Layer divides the compressed data into **1400-byte segments**, and the Data Link Layer adds **60 bytes** of overhead to each frame. Calculate the compressed file size, the total number of segments transmitted, the total protocol overhead introduced, and the final amount of data transmitted across the Physical Layer. Explain how multiple OSI layers work together to ensure secure and reliable communication.

RUBRICS FOR CALCULATION

Criteria	Weightage	Level 4 – Exemplary	Level 3 – Proficient	Level 2 – Developing	Level 1 – Beginning
Understanding of Concepts	25%	Demonstrates a thorough, accurate understanding of concepts	Good understanding with minor gaps	Basic understanding with some misconceptions	Poor understanding; major misconceptions
Explanation	25%	Detailed, well-explained answers with relevant examples	Clear explanation with adequate details	Limited explanation; lacks depth	Poor or unclear explanation

vivo V20 SE

Application	20%	Effectively applies concepts with strong analytical ability	Applies concepts with minor errors	Limited application with weak analysis	No application or incorrect analysis
Organizatio n	15%	Well-structured answers with logical flow and coherence	Organized with minor issues in flow	Basic structure, lacks clarity	Poor organization, incoherent answers
Accuracy	10%	Completely accurate and covers all required points	Mostly accurate with minor omissions	Partially correct with missing points	Incorrect answers with major gaps
Clarity	5%	Clear, neat, professiona l presentatio n	Understanda ble with minor issues	Limited clarity, readability issues	Poorly written, difficult to understand

vivo V20 SE

CO1 – AT1

SHORT ANSWER TEST.

24

Candate Code: P.C
1905200103
SLOT: C
CSA0709

1. A company needs to transfer a 150 MB design file from a client computer to a remote server over a network with a bandwidth of 50 Mbps. The transport layer divides the file into 1500 - byte segments, while the Data link layer encapsulates each segment into frames by adding 40 bytes of header and trailer. calculate the total number of segments and Data link frames transmitted, the total transmission time (ignoring propogation delay). Explain how the transport and Data link layers ensure reliable communication.

2. A transport layer protocol uses a sliding window size of 6 frames. Each frame carries 1024 bytes of user data. if the sender transmits 48 frames. Calculate the number of transmission windows required. if one frame in every window is lost and must be retransmitted, determine the total number of retransmissions. Explain how flow control improves communication efficiency.

vivo V20 SE

3. A 12,000-byte IP packet is transmitted through a router where the maximum transmission unit (MTU) is 1500 bytes. Assuming each fragment requires a 20-byte IP header, calculate the total number of fragments created and the total header overhead introduced. Explain how the network layer ensures successful delivery of fragmented packets to the destination.

~~Answer~~

4. A Transport layer protocol uses a sliding window size of 6 frames. Each frame can 1024 bytes of user data. If the sender transmits 48 frames, calculate the number of transmission windows required. If one frame in every window is lost and must be retransmitted, determine the total number of retransmission. Explain how flow control improves communication efficiency. Explain how flow control improves communi-cation efficiency.

Explanation:

Transport Layer ensures reliable delivery using acknowledgements. Data link layer provides framing and error detection.

2. Sliding window protocol

Given:

window size = 6

Total frames = 48

data / Frame = 1024 bytes

- windows : 48/6 = 8
- Retransmission:

  8 x 1 = 8 frames

- Total data:

  48 x 1024 = 49,152 bytes

Explanation:

Flow control prevents the sender from overwhelming the receiver and improves efficiency.

vivo V20 SE

Answer the following questions:

1. File transmission, segments Frames and overhead.

give:

* File size = 150MB
* Bandwidth = 50MBPS
* segment = 1500 ~~MBPS~~ bytes
* Data link headers and trailers = 40 bytes

Calculation

Calculate the total numbers of segments

Assuming 1MB = 10 bytes,

File size = 150×10^6 = 150,000,000 bytes

Number of x

* segments:

150,000,000/1500 = 100,000

* Frames: 100,000
* Total overhead:

100,000 × 40 = 4MB

* Transmission time:

154,000,000.

vivo V20 SE

IP Fragmentation

Given : Packet = 12,000 bytes
MTU = 1500 bytes.
header = 20 bytes

* Data per fragment :
  1500 - 20 = 1480 bytes
* original data :
  1200 - 20 = 11,980 bytes
* Fragments : [11980 / 1480] = 9
* Total header overhead :
  9 x 20 = 180 bytes
* Additional overhead :
  180 - 20 = 160 bytes.

Explanation : the Network Layer fragments large packets to fit the MTU and reassembles them at the destination.

4. Sliding window protocol
given

* window : 48 / 6 = 8
* Retransmission :

8 x 1 = 8 frames

~~Total data : 49,152 bytes~~

~~Explanation~~ : sliding windows ~~allow the~~

5. A multimedia application transfers a 600 MB video file. The session layer inserts a synchronization checkpoint after every 60 MB of transmitted data. During transmission, a failure occurs after 390 MB of transmitted Data. During transmission, a failure occurs after 340 MB has been transferred. Determine the number of checkpoints created before failure and calculate the amount of data that must be retransmitted after recovery. Explain the importance of synchronization in the session layer.

Answer:

Given File = 600 MB

checkpoint interval = 60 MB

Transferred.

~~After transmission~~ = 340 MB

~~After transmitted~~ ~~= 340 MB~~.

1. number of checkpoints :

390/60 = 6

2. Data to retransmit :

Last checkpoint = 6 × 60 = 360MB

390 − 360 = 30MB

Explanation :

The session layer uses checkpoints to resume transmission after a failure, saving time and reducing retransmission.