

Manufactured Solution for 2D compressible Euler equations for hypersonic flows with Nitrogen dissociation using Maple*

Kemelli C. Estacio-Hiroms

August 2, 2010

Abstract

The Method of Manufactured Solutions is a valuable approach for code verification, providing means to verify how accurately the numerical method solves the equations of interest. The method generates a related set of governing equations by applying the differential operator for the governing equations to an analytical solution chosen *a priori* to generate source terms, which are added the RHS of the original set of equations. Then, the modified set of equations may be discretized and solved numerically, so its solution may be compared to the exact solution. A choice of analytical solutions for the flow variables of the 2D Compressible Euler equations for chemically reacting hypersonic flows and their respective source terms are presented in this document.

1 2D Euler Equations

The conservation of mass, momentum, and total energy for a compressible fluid composed of a chemically reacting mixture of gases N and N₂ in thermal nonequilibrium, may be written as:

$$\frac{\partial \rho_N}{\partial t} + \nabla \cdot (\rho_N \mathbf{u}) = \dot{\omega}_N, \quad (1)$$

$$\frac{\partial \rho_{N_2}}{\partial t} + \nabla \cdot (\rho_{N_2} \mathbf{u}) = \dot{\omega}_{N_2}, \quad (2)$$

$$\frac{\partial \rho \mathbf{u}}{\partial t} + \nabla \cdot (\rho \mathbf{u} \mathbf{u}) = -\nabla p, \quad (3)$$

$$\frac{\partial \rho E}{\partial t} + \nabla \cdot (\rho \mathbf{u} H) = 0, \quad (4)$$

where ρ_s is the density of species s (s is either N or N₂), $\rho = \sum_s \rho_s$ is the mixture density, $\mathbf{u} = (u, v)$ is the mixture velocity, E is the total energy per unit mass, and p is the pressure.

Although Park's model (Park, 1990), a well established approach, involves one extra temperature equation due to vibrational/electronic energy, in the present work only one temperature is considered and the effects of vibrational/electronic energy are neglected.

The total enthalpy, H , may be expressed in terms of the total energy, density, and pressure:

$$H = E + \frac{p}{\rho},$$

and the total energy, E , is composed of internal and kinetic components:

$$E = e^{\text{int}} + \frac{\mathbf{u} \cdot \mathbf{u}}{2},$$

where, the total internal energy, e^{int} , has contribution from each of the distinct energy *modes*:

$$e^{\text{int}} = e^{\text{trans}} + e^{\text{rot}} + e^{\text{vib}} + e^{\text{elec}} + h^0 \quad (5)$$

$$= \sum_{s=1}^{ns} c_s e_s^{\text{trans}} + \sum_{s=\text{mol}} c_s e_s^{\text{rot}} + \sum_{s=\text{mol}} c_s e_s^{\text{vib}} + \sum_{s=1}^{ns} c_s e_s^{\text{elec}} + \sum_{s=1}^{ns} c_s h_s^0, \quad (6)$$

*Work based on Roy, Smith, and Ober (2002); Kirk, Amar, Stogner, Schultz, and Oliver (2009).

where $c_s = (\rho_s/\rho)$ is the mass fraction of species s . The first four terms on the right of Equation (6) represent the energy due to molecular/atomic translation, molecular rotation, molecular vibration, and electronic excitation. The final term is the heat of formation of the mixture and accounts for the energy stored in chemical bonds (Ait-Ali-Yahia, 1996; Kirk et al., 2009).

Under the approximation that the translational and rotational states of the may be assumed fully populated, translational/rotational energy for each species may be expressed as:

$$e_s^{\text{trans}} + e_s^{\text{rot}} = e_s^{\text{tr}} = C_{v,s}^{\text{tr}} T, \quad (7)$$

where the translational/rotational specific heat, $C_{v,s}^{\text{tr}}$ is given by

$$C_{v,s}^{\text{tr}} = \begin{cases} \frac{5}{2}R_s & \text{for molecules,} \\ \frac{3}{2}R_s & \text{for atoms.} \end{cases} \quad (8)$$

where R_s is the species gas constant, and $R_s = R/M_s$ where R is the universal gas constant and M_s is the species molar mass. The combined term e_s^{tr} in Equation (7) represents the energy due to random thermal translational/rotational motion of a given species.

Moreover, recalling that the vibrational and electronic energy terms have been neglected, the internal energy is given by:


$$e^{\text{int}} = \sum_{s=1}^{ns} \rho_s C_{v,s}^{\text{tr}} T + \sum_{s=1}^{ns} \rho_s h_s^0, \quad (9)$$

Regardless of the thermal state of the mixture, once the translational/rotational temperature T is determined the thermodynamic pressure of the mixture is readily obtained from Dalton's law of partial pressures:

$$p = \sum_{s=1}^{ns} p_s = \sum_{s=1}^{ns} \rho_s R_s T. \quad (10)$$

1.1 Chemical Kinetics

The rate of production/destruction of the individual species, $\dot{\omega}_s$, is required to close the species continuity equations. For the dissociating Nitrogen flow ($\text{N}_2 \rightleftharpoons 2\text{N}$) case, let us consider the chemical reactions which occur among the five principal components of dissociating air – N_2 , O_2 , NO , N , O – but neglecting three species in order to perform this 2-species problem. For this mixture, the chemical reaction that occur is:



This reaction can occur in either the forward or backward direction, as denoted by the bidirectional arrow. The reaction is presented such that they are endothermic in the forward direction (Kirk et al., 2009), and \mathcal{M} denotes a generic collision partner, which may be any of the species present in the flow, and is unaltered by the reaction. The rate of each reaction is therefore a sum of the forward and backward rates, k_f and k_b :

$$\begin{aligned} \mathcal{R}_1 &= \sum_{m \in \mathcal{M}} \left(k_{b_1 m} \frac{\rho_{\text{N}}}{M_{\text{N}}} \frac{\rho_{\text{N}}}{M_{\text{N}}} \frac{\rho_{\text{m}}}{M_{\text{m}}} - k_{f_1 m} \frac{\rho_{\text{N}_2}}{M_{\text{N}_2}} \frac{\rho_{\text{m}}}{M_{\text{m}}} \right) \\ &= k_{b_1 \text{N}} \frac{\rho_{\text{N}}^3}{M_{\text{N}}^3} - k_{f_1 \text{N}} \frac{\rho_{\text{N}_2} \rho_{\text{N}}}{2M_{\text{N}}^2} + k_{b_1 \text{N}_2} \frac{\rho_{\text{N}}^2 \rho_{\text{N}_2}}{2M_{\text{N}}^3} - k_{f_1 \text{N}_2} \frac{\rho_{\text{N}_2}^2}{4M_{\text{N}}^2}. \end{aligned}$$

recalling that $M_{\text{N}_2} = 2M_{\text{N}}$.

The species source terms

$$\dot{\omega}_s = M_s \sum_{r=1}^{nr} (\alpha_{sr} - \beta_{sr}) (\mathcal{R}_{br} - \mathcal{R}_{fr}), \quad (11)$$

where α_{sr} and β_{sr} are the stoichiometric coefficients for reactants and products of species s and where nr is the number of reactions can now be expressed in terms of the individual reaction rates as follows:

$$\begin{aligned} \dot{\omega}_{\text{N}_2} &= M_{\text{N}_2} (\mathcal{R}_1) = 2M_{\text{N}} \mathcal{R}_1, \\ \dot{\omega}_{\text{N}} &= M_{\text{N}} (-2\mathcal{R}_1) = -2M_{\text{N}} \mathcal{R}_1. \end{aligned}$$

Note that these source terms sum identically to zero, as required by conservation of mass (Kessler and Awruch, 2004).

2 Manufactured Solution

Roy et al. (2002) propose the general form of the primitive solution variables to be a function of sines and cosines:

$$\phi(x, y) = \phi_0 + \phi_x f_s\left(\frac{a_{\phi x} \pi x}{L}\right) + \phi_y f_s\left(\frac{a_{\phi y} \pi y}{L}\right), \quad (12)$$

where $\phi = \rho_N, \rho_{N_2}, u, v$ or p , and $f_s(\cdot)$ functions denote either sine or cosine function. Note that in this case, ϕ_x and ϕ_y are constants and the subscripts do not denote differentiation.

Therefore, the manufactured analytical solution for each one of the variables in Euler equations are:

$$\begin{aligned} \rho_N(x, y) &= \rho_{N0} + \rho_{Nx} \sin\left(\frac{a_{\rho Nx} \pi x}{L}\right) + \rho_{Ny} \cos\left(\frac{a_{\rho Ny} \pi y}{L}\right), \\ \rho_{N_2}(x, y) &= \rho_{N_20} + \rho_{N_2x} \cos\left(\frac{a_{\rho N_2x} \pi x}{L}\right) + \rho_{N_2y} \sin\left(\frac{a_{\rho N_2y} \pi y}{L}\right), \\ u(x, y) &= u_0 + u_x \sin\left(\frac{a_{ux} \pi x}{L}\right) + u_y \cos\left(\frac{a_{uy} \pi y}{L}\right), \\ v(x, y) &= v_0 + v_x \cos\left(\frac{a_{vx} \pi x}{L}\right) + v_y \sin\left(\frac{a_{vy} \pi y}{L}\right), \\ p(x, y) &= p_0 + p_x \cos\left(\frac{a_{px} \pi x}{L}\right) + p_y \sin\left(\frac{a_{py} \pi y}{L}\right). \end{aligned} \quad (13)$$

Recalling that $\rho = \sum_s \rho_s$, the manufactured analytical solution for the density of the mixture is:

$$\begin{aligned} \rho(x, y) &= \rho_N + \rho_{N_2} \\ &= \rho_{N0} + \rho_{N_20} + \rho_{Nx} \sin\left(\frac{a_{\rho Nx} \pi x}{L}\right) + \rho_{N_2x} \cos\left(\frac{a_{\rho N_2x} \pi x}{L}\right) + \rho_{Ny} \cos\left(\frac{a_{\rho Ny} \pi y}{L}\right) + \rho_{N_2y} \sin\left(\frac{a_{\rho N_2y} \pi y}{L}\right). \end{aligned} \quad (14)$$

Roy et al. (2002) present the constants used in the manufactured solutions for the 2D supersonic and subsonic cases, together with the source term for the 2D mass conservation equation. The resulting source terms for the 2D Euler flow with Nitrogen dissociation described by Equations (1) – (4) are obtained through symbolic manipulation using the software Maple and are presented in the following sections.

3 Euler mass conservation equation for Nitrogen atom

The mass conservation equation for Nitrogen atom (N), written as an operator, is:

$$L = \frac{\partial \rho_N}{\partial t} + \nabla \cdot (\rho_N \mathbf{u}) - \dot{\omega}_N \quad (15)$$

Analytically differentiating Equation (13) for ρ_N , u and v using operator L defined above together with suitable substitution for source term $\dot{\omega}_N$ gives the source term Q_{ρ_N} :

$$\begin{aligned} Q_{\rho_N} = & \frac{a_{\rho N x} \pi \rho_{N x}}{L} \cos\left(\frac{a_{\rho N x} \pi x}{L}\right) \left[u_0 + u_x \sin\left(\frac{a_{u x} \pi x}{L}\right) + u_y \cos\left(\frac{a_{u y} \pi y}{L}\right) \right] + \\ & - \frac{a_{\rho N y} \pi \rho_{N y}}{L} \sin\left(\frac{a_{\rho N y} \pi y}{L}\right) \left[v_0 + v_x \cos\left(\frac{a_{v x} \pi x}{L}\right) + v_y \sin\left(\frac{a_{v y} \pi y}{L}\right) \right] + \\ & + \frac{a_{u x} \pi u_x}{L} \cos\left(\frac{a_{u x} \pi x}{L}\right) \left[\rho_{N 0} + \rho_{N x} \sin\left(\frac{a_{\rho N x} \pi x}{L}\right) + \rho_{N y} \cos\left(\frac{a_{\rho N y} \pi y}{L}\right) \right] + \\ & + \frac{a_{v y} \pi v_y}{L} \cos\left(\frac{a_{v y} \pi y}{L}\right) \left[\rho_{N 0} + \rho_{N x} \sin\left(\frac{a_{\rho N x} \pi x}{L}\right) + \rho_{N y} \cos\left(\frac{a_{\rho N y} \pi y}{L}\right) \right] + \\ & + \frac{2k_{b1N}}{M_N^2} \left[\rho_{N 0} + \rho_{N x} \sin\left(\frac{a_{\rho N x} \pi x}{L}\right) + \rho_{N y} \cos\left(\frac{a_{\rho N y} \pi y}{L}\right) \right]^3 + \\ & + \frac{k_{b1N_2}}{M_N^2} \left[\rho_{N_2 0} + \rho_{N_2 x} \cos\left(\frac{a_{\rho N_2 x} \pi x}{L}\right) + \rho_{N_2 y} \sin\left(\frac{a_{\rho N_2 y} \pi y}{L}\right) \right] \left[\rho_{N 0} + \rho_{N x} \sin\left(\frac{a_{\rho N x} \pi x}{L}\right) + \rho_{N y} \cos\left(\frac{a_{\rho N y} \pi y}{L}\right) \right]^2 + \\ & - \frac{k_{f1N}}{M_N} \left[\rho_{N_2 0} + \rho_{N_2 x} \cos\left(\frac{a_{\rho N_2 x} \pi x}{L}\right) + \rho_{N_2 y} \sin\left(\frac{a_{\rho N_2 y} \pi y}{L}\right) \right] \left[\rho_{N 0} + \rho_{N x} \sin\left(\frac{a_{\rho N x} \pi x}{L}\right) + \rho_{N y} \cos\left(\frac{a_{\rho N y} \pi y}{L}\right) \right] + \\ & - \frac{k_{f1N_2}}{2M_N} \left[\rho_{N_2 0} + \rho_{N_2 x} \cos\left(\frac{a_{\rho N_2 x} \pi x}{L}\right) + \rho_{N_2 y} \sin\left(\frac{a_{\rho N_2 y} \pi y}{L}\right) \right]^2. \end{aligned} \quad (16)$$

4 Euler mass conservation equation for Nitrogen molecule

The mass conservation equation for Nitrogen N₂ molecule, written as an operator, is:

$$L = \frac{\partial \rho_{N_2}}{\partial t} + \nabla \cdot (\rho_{N_2} \mathbf{u}) - \dot{\omega}_{N_2} \quad (17)$$

Analytically differentiating Equation (13) for ρ_{N_2} , u and v using operator L defined above together with suitable substitution for source term $\dot{\omega}_{N_2}$ gives the source term $Q_{\rho_{N_2}}$:

$$\begin{aligned}
Q_{\rho_{N_2}} = & -\frac{a_{\rho N_2 x} \pi \rho_{N_2 x}}{L} \sin\left(\frac{a_{\rho N_2 x} \pi x}{L}\right) \left[u_0 + u_x \sin\left(\frac{a_{ux} \pi x}{L}\right) + u_y \cos\left(\frac{a_{uy} \pi y}{L}\right) \right] + \\
& + \frac{a_{\rho N_2 y} \pi \rho_{N_2 y}}{L} \cos\left(\frac{a_{\rho N_2 y} \pi y}{L}\right) \left[v_0 + v_x \cos\left(\frac{a_{vx} \pi x}{L}\right) + v_y \sin\left(\frac{a_{vy} \pi y}{L}\right) \right] + \\
& + \frac{a_{ux} \pi u_x}{L} \cos\left(\frac{a_{ux} \pi x}{L}\right) \left[\rho_{N_2 0} + \rho_{N_2 x} \cos\left(\frac{a_{\rho N_2 x} \pi x}{L}\right) + \rho_{N_2 y} \sin\left(\frac{a_{\rho N_2 y} \pi y}{L}\right) \right] + \\
& + \frac{a_{vy} \pi v_y}{L} \cos\left(\frac{a_{vy} \pi y}{L}\right) \left[\rho_{N_2 0} + \rho_{N_2 x} \cos\left(\frac{a_{\rho N_2 x} \pi x}{L}\right) + \rho_{N_2 y} \sin\left(\frac{a_{\rho N_2 y} \pi y}{L}\right) \right] + \\
& - \frac{2k_{b1N}}{M_N^2} \left[\rho_{N0} + \rho_{Nx} \sin\left(\frac{a_{\rho Nx} \pi x}{L}\right) + \rho_{Ny} \cos\left(\frac{a_{\rho Ny} \pi y}{L}\right) \right]^3 + \\
& - \frac{k_{b1N_2}}{M_N^2} \left[\rho_{N_2 0} + \rho_{N_2 x} \cos\left(\frac{a_{\rho N_2 x} \pi x}{L}\right) + \rho_{N_2 y} \sin\left(\frac{a_{\rho N_2 y} \pi y}{L}\right) \right] \left[\rho_{N0} + \rho_{Nx} \sin\left(\frac{a_{\rho Nx} \pi x}{L}\right) + \rho_{Ny} \cos\left(\frac{a_{\rho Ny} \pi y}{L}\right) \right]^2 + \\
& + \frac{k_{f1N}}{M_N} \left[\rho_{N_2 0} + \rho_{N_2 x} \cos\left(\frac{a_{\rho N_2 x} \pi x}{L}\right) + \rho_{N_2 y} \sin\left(\frac{a_{\rho N_2 y} \pi y}{L}\right) \right] \left[\rho_{N0} + \rho_{Nx} \sin\left(\frac{a_{\rho Nx} \pi x}{L}\right) + \rho_{Ny} \cos\left(\frac{a_{\rho Ny} \pi y}{L}\right) \right] + \\
& + \frac{k_{f1N_2}}{2M_N} \left[\rho_{N_2 0} + \rho_{N_2 x} \cos\left(\frac{a_{\rho N_2 x} \pi x}{L}\right) + \rho_{N_2 y} \sin\left(\frac{a_{\rho N_2 y} \pi y}{L}\right) \right]^2.
\end{aligned} \tag{18}$$

5

Euler momentum equation

For the generation of the analytical source term Q_u for the x momentum equation, Equation (3) is written as an operator L :

$$L = \frac{\partial(\rho u)}{\partial t} + \frac{\partial(\rho u^2)}{\partial x} + \frac{\partial(\rho uv)}{\partial y} + \frac{\partial(p)}{\partial x}. \tag{19}$$

which, when operated in to Equations (13) and (14), provides source term Q_u :

$$\begin{aligned}
Q_u = & -\frac{a_{px}\pi p_x}{L} \sin\left(\frac{a_{px}\pi x}{L}\right) + \\
& + \frac{a_{\rho N_x}\pi \rho_{N_x}}{L} \cos\left(\frac{a_{\rho N_x}\pi x}{L}\right) \left[u_0 + u_x \sin\left(\frac{a_{ux}\pi x}{L}\right) + u_y \cos\left(\frac{a_{uy}\pi y}{L}\right)\right]^2 + \\
& - \frac{a_{\rho N_y}\pi \rho_{N_y}}{L} \sin\left(\frac{a_{\rho N_y}\pi y}{L}\right) \left[v_0 + v_x \cos\left(\frac{a_{vx}\pi x}{L}\right) + v_y \sin\left(\frac{a_{vy}\pi y}{L}\right)\right] \left[u_0 + u_x \sin\left(\frac{a_{ux}\pi x}{L}\right) + u_y \cos\left(\frac{a_{uy}\pi y}{L}\right)\right] + \\
& - \frac{a_{\rho N_{2x}}\pi \rho_{N_{2x}}}{L} \sin\left(\frac{a_{\rho N_{2x}}\pi x}{L}\right) \left[u_0 + u_x \sin\left(\frac{a_{ux}\pi x}{L}\right) + u_y \cos\left(\frac{a_{uy}\pi y}{L}\right)\right]^2 + \\
& + \frac{a_{\rho N_{2y}}\pi \rho_{N_{2y}}}{L} \cos\left(\frac{a_{\rho N_{2y}}\pi y}{L}\right) \left[v_0 + v_x \cos\left(\frac{a_{vx}\pi x}{L}\right) + v_y \sin\left(\frac{a_{vy}\pi y}{L}\right)\right] \left[u_0 + u_x \sin\left(\frac{a_{ux}\pi x}{L}\right) + u_y \cos\left(\frac{a_{uy}\pi y}{L}\right)\right] + \\
& + 2\frac{a_{ux}\pi u_x}{L} \cos\left(\frac{a_{ux}\pi x}{L}\right) \left[\rho_{N0} + \rho_{N_x} \sin\left(\frac{a_{\rho N_x}\pi x}{L}\right) + \rho_{N_y} \cos\left(\frac{a_{\rho N_y}\pi y}{L}\right) + \rho_{N_{20}} + \rho_{N_{2x}} \cos\left(\frac{a_{\rho N_{2x}}\pi x}{L}\right) + \rho_{N_{2y}} \sin\left(\frac{a_{\rho N_{2y}}\pi y}{L}\right)\right] \cdot \\
& \cdot \left[u_0 + u_x \sin\left(\frac{a_{ux}\pi x}{L}\right) + u_y \cos\left(\frac{a_{uy}\pi y}{L}\right)\right] + \\
& - \frac{a_{uy}\pi u_y}{L} \sin\left(\frac{a_{uy}\pi y}{L}\right) \left[\rho_{N0} + \rho_{N_x} \sin\left(\frac{a_{\rho N_x}\pi x}{L}\right) + \rho_{N_y} \cos\left(\frac{a_{\rho N_y}\pi y}{L}\right) + \rho_{N_{20}} + \rho_{N_{2x}} \cos\left(\frac{a_{\rho N_{2x}}\pi x}{L}\right) + \rho_{N_{2y}} \sin\left(\frac{a_{\rho N_{2y}}\pi y}{L}\right)\right] \cdot \\
& \cdot \left[v_0 + v_x \cos\left(\frac{a_{vx}\pi x}{L}\right) + v_y \sin\left(\frac{a_{vy}\pi y}{L}\right)\right] + \\
& + \frac{a_{vy}\pi v_y}{L} \cos\left(\frac{a_{vy}\pi y}{L}\right) \left[\rho_{N0} + \rho_{N_x} \sin\left(\frac{a_{\rho N_x}\pi x}{L}\right) + \rho_{N_y} \cos\left(\frac{a_{\rho N_y}\pi y}{L}\right) + \rho_{N_{20}} + \rho_{N_{2x}} \cos\left(\frac{a_{\rho N_{2x}}\pi x}{L}\right) + \rho_{N_{2y}} \sin\left(\frac{a_{\rho N_{2y}}\pi y}{L}\right)\right] \cdot \\
& \cdot \left[u_0 + u_x \sin\left(\frac{a_{ux}\pi x}{L}\right) + u_y \cos\left(\frac{a_{uy}\pi y}{L}\right)\right]
\end{aligned} \tag{20}$$

Analogously, for the generation of the analytical source term Q_v for the y momentum equation, Equation (3) is written as an operator L :

$$L = \frac{\partial(\rho v)}{\partial t} + \frac{\partial(\rho uv)}{\partial x} + \frac{\partial(\rho v^2)}{\partial y} + \frac{\partial(p)}{\partial y} \tag{21}$$

and then applied to Equations (13) and (14). It yields:

$$\begin{aligned}
Q_v = & \frac{a_{py}\pi p_y}{L} \cos\left(\frac{a_{py}\pi y}{L}\right) + \\
& + \frac{a_{\rho N_x}\pi \rho_{N_x}}{L} \cos\left(\frac{a_{\rho N_x}\pi x}{L}\right) \left[v_0 + v_x \cos\left(\frac{a_{vx}\pi x}{L}\right) + v_y \sin\left(\frac{a_{vy}\pi y}{L}\right) \right] \left[u_0 + u_x \sin\left(\frac{a_{ux}\pi x}{L}\right) + u_y \cos\left(\frac{a_{uy}\pi y}{L}\right) \right] + \\
& - \frac{a_{\rho N_y}\pi \rho_{N_y}}{L} \sin\left(\frac{a_{\rho N_y}\pi y}{L}\right) \left[v_0 + v_x \cos\left(\frac{a_{vx}\pi x}{L}\right) + v_y \sin\left(\frac{a_{vy}\pi y}{L}\right) \right]^2 + \\
& - \frac{a_{\rho N_{2x}}\pi \rho_{N_{2x}}}{L} \sin\left(\frac{a_{\rho N_{2x}}\pi x}{L}\right) \left[v_0 + v_x \cos\left(\frac{a_{vx}\pi x}{L}\right) + v_y \sin\left(\frac{a_{vy}\pi y}{L}\right) \right] \left[u_0 + u_x \sin\left(\frac{a_{ux}\pi x}{L}\right) + u_y \cos\left(\frac{a_{uy}\pi y}{L}\right) \right] + \\
& + \frac{a_{\rho N_{2y}}\pi \rho_{N_{2y}}}{L} \cos\left(\frac{a_{\rho N_{2y}}\pi y}{L}\right) \left[v_0 + v_x \cos\left(\frac{a_{vx}\pi x}{L}\right) + v_y \sin\left(\frac{a_{vy}\pi y}{L}\right) \right]^2 + \\
& + \frac{a_{ux}\pi u_x}{L} \cos\left(\frac{a_{ux}\pi x}{L}\right) \left[\rho_{N0} + \rho_{N_x} \sin\left(\frac{a_{\rho N_x}\pi x}{L}\right) + \rho_{N_y} \cos\left(\frac{a_{\rho N_y}\pi y}{L}\right) + \rho_{N_{20}} + \rho_{N_{2x}} \cos\left(\frac{a_{\rho N_{2x}}\pi x}{L}\right) + \rho_{N_{2y}} \sin\left(\frac{a_{\rho N_{2y}}\pi y}{L}\right) \right] \cdot \\
& \cdot \left[v_0 + v_x \cos\left(\frac{a_{vx}\pi x}{L}\right) + v_y \sin\left(\frac{a_{vy}\pi y}{L}\right) \right] + \\
& - \frac{a_{vx}\pi v_x}{L} \sin\left(\frac{a_{vx}\pi x}{L}\right) \left[\rho_{N0} + \rho_{N_x} \sin\left(\frac{a_{\rho N_x}\pi x}{L}\right) + \rho_{N_y} \cos\left(\frac{a_{\rho N_y}\pi y}{L}\right) + \rho_{N_{20}} + \rho_{N_{2x}} \cos\left(\frac{a_{\rho N_{2x}}\pi x}{L}\right) + \rho_{N_{2y}} \sin\left(\frac{a_{\rho N_{2y}}\pi y}{L}\right) \right] \cdot \\
& \cdot \left[u_0 + u_x \sin\left(\frac{a_{ux}\pi x}{L}\right) + u_y \cos\left(\frac{a_{uy}\pi y}{L}\right) \right] + \\
& + \frac{2a_{vy}\pi v_y}{L} \cos\left(\frac{a_{vy}\pi y}{L}\right) \left[\rho_{N0} + \rho_{N_x} \sin\left(\frac{a_{\rho N_x}\pi x}{L}\right) + \rho_{N_y} \cos\left(\frac{a_{\rho N_y}\pi y}{L}\right) + \rho_{N_{20}} + \rho_{N_{2x}} \cos\left(\frac{a_{\rho N_{2x}}\pi x}{L}\right) + \rho_{N_{2y}} \sin\left(\frac{a_{\rho N_{2y}}\pi y}{L}\right) \right] \cdot \\
& \cdot \left[v_0 + v_x \cos\left(\frac{a_{vx}\pi x}{L}\right) + v_y \sin\left(\frac{a_{vy}\pi y}{L}\right) \right]
\end{aligned} \tag{22}$$

6 Euler energy equation

The total energy equation is written as an operator:

$$L = \frac{\partial \rho E}{\partial t} + \frac{\partial \rho u H}{\partial x} + \frac{\partial \rho v H}{\partial y} \tag{23}$$

where

$$E = e^{\text{int}} + \frac{u^2 + v^2}{2} \quad \text{and} \quad H = E + \frac{p}{\rho},$$

with e^{int} and p as defined in Equations (9) and (10), respectively.

Source term Q_E is obtained by operating L on Equations (13) and (14):

7 Comments

Source terms Q_{ρ_N} , $Q_{\rho_{N_2}}$, Q_u , Q_v and Q_E have been generated by replacing the analytical Expressions (13) and (14) into respective Equations (1) – (4), followed by the usage of Maple commands for collecting, sorting and factorizing the terms. Files containing C codes for the source terms have also been generated. They are: Euler_2d_chemistry_rho_N.code.C, Euler_2d_chemistry_rho_N2.code.C, Euler_2d_chemistry_u.code.C, Euler_2d_chemistry_v.code.C, and Euler_2d_chemistry_E.code.C,.

An example of the automatically generated C file from the source term for the mass conservation equation of N_2 is:

```
#include <math.h>

double SourceQ_rho_N2 (double x, double y, double p_0, double p_x, double p_y, double rho_N_0,
    double rho_N_x, double rho_N_y, double rho_N2_0, double rho_N2_x, double rho_N2_y, double u_0,
    double u_x, double u_y, double v_0, double v_x, double v_y, double a_px, double a_py,
    double a_rho_N_x, double a_rho_N_y, double a_rho_N2_x, double a_rho_N2_y, double a_ux,
    double a_uy, double a_vx, double a_vy, double L, double M_N, double k_b1N, double k_f1N,
    double k_b1N2, double k_f1N2)
{
    double Q_rho_N2;
    Q_rho_N2 = -rho_N2_x * sin(a_rho_N2_x * PI * x / L) * a_rho_N2_x * PI *
        (u_0 + u_x * sin(a_ux * PI * x / L) + u_y * cos(a_uy * PI * y / L)) / L +
        rho_N2_y * cos(a_rho_N2_y * PI * y / L) * a_rho_N2_y * PI *
        (v_0 + v_x * cos(a_vx * PI * x / L) + v_y * sin(a_vy * PI * y / L)) / L +
        u_x * cos(a_ux * PI * x / L) * a_ux * PI *
        (rho_N2_0 + rho_N2_x * cos(a_rho_N2_x * PI * x / L) + rho_N2_y * sin(a_rho_N2_y * PI * y / L)) / L +
        v_y * cos(a_vy * PI * y / L) * a_vy * PI *
        (rho_N2_0 + rho_N2_x * cos(a_rho_N2_x * PI * x / L) + rho_N2_y * sin(a_rho_N2_y * PI * y / L)) / L -
        0.2e1 * k_b1N *
        pow(rho_N_0 + rho_N_x * sin(a_rho_N_x * PI * x / L) + rho_N_y * cos(a_rho_N_y * PI * y / L), 0.3e1) *
        pow(M_N, -0.2e1) - k_b1N2 *
        (rho_N2_0 + rho_N2_x * cos(a_rho_N2_x * PI * x / L) + rho_N2_y * sin(a_rho_N2_y * PI * y / L)) *
        pow(rho_N_0 + rho_N_x * sin(a_rho_N_x * PI * x / L) + rho_N_y * cos(a_rho_N_y * PI * y / L), 0.2e1) *
        pow(M_N, -0.2e1) + k_f1N *
        (rho_N2_0 + rho_N2_x * cos(a_rho_N2_x * PI * x / L) + rho_N2_y * sin(a_rho_N2_y * PI * y / L)) *
        (rho_N_0 + rho_N_x * sin(a_rho_N_x * PI * x / L) + rho_N_y * cos(a_rho_N_y * PI * y / L)) / M_N +
        k_f1N2 * pow(rho_N2_0 + rho_N2_x * cos(a_rho_N2_x * PI * x / L) +
            rho_N2_y * sin(a_rho_N2_y * PI * y / L), 0.2e1) / M_N / 0.2e1;
    return(Q_rho_N2);
}
```

Finally, the gradients of the analytical solutions (12) have also been computed and their respective C codes are presented in Euler_2d_chemistry_manuf_solutions_grad.code.C. Therefore,

$$\begin{aligned}
 \nabla \rho_N &= \begin{bmatrix} \frac{a_{\rho N x} \pi \rho_{N x}}{L} \cos\left(\frac{a_{\rho N x} \pi x}{L}\right) \\ -\frac{a_{\rho N y} \pi \rho_{N y}}{L} \sin\left(\frac{a_{\rho N y} \pi y}{L}\right) \end{bmatrix}, & \nabla \rho_{N_2} &= \begin{bmatrix} \frac{a_{\rho N_2 x} \pi \rho_{N_2 x}}{L} \sin\left(\frac{a_{\rho N_2 x} \pi x}{L}\right) \\ -\frac{a_{\rho N_2 y} \pi \rho_{N_2 y}}{L} \cos\left(\frac{a_{\rho N_2 y} \pi y}{L}\right) \end{bmatrix}, \\
 \nabla p &= \begin{bmatrix} -\frac{a_{p x} \pi p_x}{L} \sin\left(\frac{a_{p x} \pi x}{L}\right) \\ \frac{a_{p y} \pi p_y}{L} \cos\left(\frac{a_{p y} \pi y}{L}\right) \end{bmatrix}, & \nabla \rho &= \nabla(\rho_N) + \nabla(\rho_{N_2}), \\
 \nabla u &= \begin{bmatrix} \frac{a_{u x} \pi u_x}{L} \cos\left(\frac{a_{u x} \pi x}{L}\right) \\ -\frac{a_{u y} \pi u_y}{L} \sin\left(\frac{a_{u y} \pi y}{L}\right) \end{bmatrix} & \text{and} & \nabla v &= \begin{bmatrix} -\frac{a_{v x} \pi v_x}{L} \sin\left(\frac{a_{v x} \pi x}{L}\right) \\ \frac{a_{v y} \pi v_y}{L} \cos\left(\frac{a_{v y} \pi y}{L}\right) \end{bmatrix}
 \end{aligned} \tag{26}$$

are written in C language as:

```

grad_rho_an_N[0] = rho_N_x * cos(a_rho_N_x * pi * x / L) * a_rho_N_x * pi / L;
grad_rho_an_N[1] = -rho_N_y * sin(a_rho_N_y * pi * y / L) * a_rho_N_y * pi / L;
grad_rho_an_N2[0] = -rho_N2_x * sin(a_rho_N2_x * pi * x / L) * a_rho_N2_x * pi / L;
grad_rho_an_N2[1] = rho_N2_y * cos(a_rho_N2_y * pi * y / L) * a_rho_N2_y * pi / L;
grad_rho_an[0] = rho_N_x * cos(a_rho_N_x * pi * x / L) * a_rho_N_x * pi / L -
    rho_N2_x * sin(a_rho_N2_x * pi * x / L) * a_rho_N2_x * pi / L;
grad_rho_an[1] = -rho_N_y * sin(a_rho_N_y * pi * y / L) * a_rho_N_y * pi / L +
    rho_N2_y * cos(a_rho_N2_y * pi * y / L) * a_rho_N2_y * pi / L;
grad_p_an[0] = -p_x * sin(a_px * pi * x / L) * a_px * pi / L;
grad_p_an[1] = p_y * cos(a_py * pi * y / L) * a_py * pi / L;
grad_u_an[0] = u_x * cos(a_ux * pi * x / L) * a_ux * pi / L;
grad_u_an[1] = -u_y * sin(a_uy * pi * y / L) * a_uy * pi / L;
grad_v_an[0] = -v_x * sin(a_vx * pi * x / L) * a_vx * pi / L;
grad_v_an[1] = v_y * cos(a_vy * pi * y / L) * a_vy * pi / L;

```

References

- Ait-Ali-Yahia, D. (1996). *Hypersonic Thermo-Chemical Equilibrium and Nonequilibrium Flows Using Adapted Grids*. Ph. D. thesis, Concordia University, Canada.
- Kessler, M. P. and A. M. Awruch (2004). Analysis of hypersonic flows using finite elements with Taylor-galerkin scheme. *Int. J. Numer. Meth. Fluids* 44, 1355–1376.
- Kirk, B., A. Amar, R. Stogner, K. Schultz, and T. Oliver (2009). The hyflow hypersonic flow simulation toolkit. Technical report, NASA Lyndon B. Johnson Space Center and The University of Texas at Austin.
- Park, C. (1990). *Nonequilibrium Hypersonic Aerothermodynamics*. John Wiley & Sons.
- Roy, C., T. Smith, and C. Ober (2002). Verification of a compressible CFD code using the method of manufactured solutions. In *AIAA Fluid Dynamics Conference and Exhibit*, Number AIAA 2002-3110.