

İTÜ

Computer Security

Intrusion Detection Systems

Dr. Şerif Bahtiyar
bahtiyars@itu.edu.tr

1

Before Starting

US bans sale of Huawei, ZTE tech amid security fears



The US has **banned** the **sale** and **import** of new communications equipment from **five** Chinese companies, including **Huawei** and **ZTE**, amid **concerns over national security**.

<https://www.bbc.com/news/world-us-canada-63764450>

11.12.2024


Intrusion Detection Systems

2

2

Before Starting

ChatGPT tool could be abused by scammers and hackers



A **ChatGPT** feature allowing users to **easily build** their own **artificial-intelligence assistants** can be used to create **tools** for **cyber-crime**, a BBC News investigation has revealed.

<https://www.bbc.com/news/technology-67614065>

11.12.2024

Intrusion Detection Systems

3

3

Outline

- Problems in Networks
- Intruders
- Intrusion Detection
- Intrusion Analysis
- Host-Based Intrusion Detection
- Network-Based Intrusion Detection
- Distributed Adaptive Intrusion Detection
- Honeypots



11.12.2024

Intrusion Detection Systems

4

4

Problems in Networks

Some **security problems** in networks **depend** on **hostile** or **unwanted trespass** by user or software.

- **User trespass**: **unauthorized logon**, acquisition of privileges beyond those have been authorized
- **Software trespass**: virus, worm, Trojan....



11.12.2024

Intrusion Detection Systems

5

5

Intruders

- **Intruders** are referred as **hacker** or **cracker**.
- **Classes of intruders origin**:
 - **Masquerader**: **not authorized** to use resources but **penetrate access control** to exploit a legitimate user's account (**outsider**)
 - **Misfeasor**: A **legitimate user** who **misuses** his or her privileges (**insider**)
 - **Clandestine user**: A user who seizes supervisory control and uses this to **evade auditing and access controls** (**outsider or insider**)
- Intruder **attacks** range from **benign** to the **serious**.

11.12.2024

Intrusion Detection Systems

6

6

Intruders

Classes of intruders by motivation:

- **Cyber Criminals** are either **individuals** or **members** of an organized crime group with a **goal of financial reward**.
- **Activists** are either **individuals** or **members** of a larger group of outsider attackers, who are **motivated by social or political** causes. (known as **hacktivists**)
- **State sponsored organizations** are **groups of hackers sponsored by governments** to conduct **espionage** or **sabotage** activities. (known as **Advanced Persistent Threats, APTs**)
- **Others** are hackers who have many **classical hack motivations**, such as hobby hackers.

11.12.2024

Intrusion Detection Systems

7

7

Intruders

Classes of intruders by skill levels:

- **Apprentice**: Hackers with **minimal technical skill** who primarily use **existing attack tools**.
- **Journeyman**: Hackers with **sufficient technical skills** to **modify and extend attack toolkits** to use newly discovered vulnerabilities or to focus on different target groups.
- **Master**: Hackers with **high-level technical skills** capable of **discovering brand new categories** of vulnerabilities or writing **new powerful attack toolkits**.

11.12.2024

Intrusion Detection Systems

8

8

Intruders

Intruder Behavior

Target Acquisition and Information Gathering

Initial Access

Privilege Escalation

Information Gathering

Maintaining Access and Covering Tracks

11.12.2024

Intrusion Detection Systems

9

9

Intruders

Some examples of hacker behavior patterns

- Select **target** using **IP** lookup tools, **NSLookup**
- **Map** network for accessible **services**, **NMAP**
- **Identify** vulnerable **services**
- **Guess** passwords, **pcAnywhere**
- **Install remote** administration tools, **DameWare**

11.12.2024

Intrusion Detection Systems

10

10

Intruders

Some intrusions

- **Remote** root compromise
- **Web** server defacement
- **Password** cracking or guessing
- Copying **credit card numbers** from a database
- Running a **sniffer**



11.12.2024

Intrusion Detection Systems

11

11

Intruders

Hackers

- Those who **hack into systems** often motivated by thrill of access and status
 - Hacking community is a strong **meritocracy**
 - **Status** is determined by **level of competence**
- **Benign** intruders **consume resources** and may **decrease performance**
- There is **no way to know** whether an intruder will be **benign** or **malign**
- **IDS, IPS, and VPN** are used to **counter**



11.12.2024

Intrusion Detection Systems

12

12

Intruders

Criminals

- **Organized** group of **hackers**
- May be **employed** by a **cooperation** and **government**
- Common **target** is a **credit card file** at an e-commerce server
- The **difference** between **traditional** hacker and **criminal** hacker
 - **Traditional** hackers **look for targets of opportunity**
 - **Criminal** hackers have **specific targets**
- Once penetrated **act quickly** and **get out**
- IDS and IPS are **less effective**
- **Sensitive data** **need strong** protection



11.12.2024

Intrusion Detection Systems

13

13

Intruders

Some criminal enterprise behavior

- Act quickly and precisely to make **harder to detect**
- **Exploit perimeter** via vulnerable ports
- Use Trojan horses to **leave backdoors for reentry**
- Use sniffer to **capture** passwords
- Make **few or no** mistake

11.12.2024

Intrusion Detection Systems

14

14

Intruders

Insider Attacks

- Most **difficult** to detect and prevent
- Employees have **access** and **knowledge**
- May be **motivated** by revenge
 - When employment **terminated**
 - Taking customer data when move to **competitor**
- **IDS** and **IPS** may **help** but needs least privilege, monitor logs, strong authentication, after termination delete access,...



11.12.2024

Intrusion Detection Systems

15

15

Intruders

Examples of insider behavior

- Create network **accounts for themselves** and **friends**
- **Access** accounts and applications they **wouldn't normally use** for their daily jobs.
- Conduct secret instant messaging **chat**
- Visit **web sites** that provide to dissatisfied employees
- Perform **large** downloads and copying
- Access the network during **off hours**

11.12.2024

Intrusion Detection Systems

16

16

Intruders

Intrusion Techniques

- **Objective** is to **gain access** or **increase privileges**
- **Initial attacks** **exploits vulnerabilities** to execute code to get backdoor, such as buffer overflow
- **Gain** protected information such as passwords

11.12.2024


Intrusion Detection Systems

17

17

Intrusion Detection

- **Security Intrusion:** A **security event** or a **combination** of multiple security events that constitutes a **security incident** in which an **intruder gains**, or attempts to gain, **access** to a system **without having authorization** to do so.
- **Intrusion Detection:** A **security service** that **monitors** and **analyzes** system events for the purpose of finding, and providing real-time or near real time warning of, attempts to **access system** resources in an **unauthorized** manner.



11.12.2024

Intrusion Detection Systems

18

18

Intrusion Detection

IDS classification

- **Host-based IDS**: monitors **single host** characteristics and activities
- **Network-based IDS**: monitors **network** traffic and activity

IDS logical components

- **Sensors**: **collect** data (log files, network packets, system call traces,...)
- **Analyzers**: **determine** if an **intrusion** has occurred by receiving data from sensors.
- **User interface**: **view** output of system and **control** IDS

11.12.2024

Intrusion Detection Systems

19

19

Intrusion Detection

IDS principles

- **Detect quickly** enough to identify intruder-> **less damage**
- **Deterrent** (caydırıcı) -> **prevent intrusions**
- Determine intrusion **techniques** -> **strengthen** intrusion prevention

11.12.2024

Intrusion Detection Systems

20

20

Intrusion Detection




Figure 8.1 Profiles of Behavior of Intruders and Authorized Users

11.12.2024

Intrusion Detection Systems

21

21

Intrusion Detection

Assumes **intruder** behavior **differs** from **legitimate** user

- Expect **overlap**
- **Observe** deviations from history
- **Problems**
 - **False positives** (authorized users identified as intruders)
 - **False negatives** (intruders not identified)

11.12.2024

Intrusion Detection Systems

22

22

Intrusion Detection

IDS requirements

- Run **continually**
- Be **fault** tolerant
- **Resist** subversion
- Impose **minimal** overhead
- **Configured** according to security policy
- **Adapt** changes in system and users
- **Monitor** large number of hosts
- **Graceful** degradation of service (damaged components have less effects on IDS)
- **Dynamic** reconfiguration (no need restart)

11.12.2024

Intrusion Detection Systems

23

23

Intrusion Analysis

Audit Records

- A fundamental **tool** for intrusion detection
- **Variants**
 - **Native**: provided by **OS** and **collects** information on **user activity**
 - **Advantage**: **no additional** software is needed
 - **Disadvantage**: may **not contain** the needed information
 - **Detection-specific**: **IDS specific**
 - **Advantage**: vendor **independent** and **ported** to a other systems
 - **Disadvantage**: extra **overhead**

11.12.2024

Intrusion Detection Systems

24

24

Intrusion Analysis

Anomaly detection (statistically anomaly detection)

- **Threshold detection**
 - involves **counting** the number of occurrence of a specific event over an interval of time
 - **crude** and **ineffective** for **sophisticated** attacks
 - may be **useful** in conjunction **with** more **sophisticated techniques**.
- **Profile based**
 - Characterizes **past** behaviors of users or groups
 - Detect significant **deviations**
 - Uses analysis of **audit records**, such as **gather metrics** (counter and interval time), **analyze** (mean and standard deviation, markov process, time series)

11.12.2024

Intrusion Detection Systems

25

25

Intrusion Analysis

Signature Detection

- Detects intrusions by **observing events** and **applying** a set of **rules**
- **Approaches**
 - **Rule-based anomaly detection**
 - **Historical records** are analyzed to identify **usage patterns** and generate **automatically rules**
 - Does **not require knowledge** of security vulnerabilities (**statistically anomaly detection require!**)
 - **Rule-based penetration identification**
 - Use **rules** for identifying **known penetrations and weaknesses**
 - Often by **analyzing attack script** from Internet
 - **Supplemented** with rules from security **experts**

11.12.2024

Intrusion Detection Systems


26

26

Intrusion Analysis

Base-rate fallacy

If the actual number of **intrusions** is **low** compared to the number of **legitimate uses** of a system, then the **false alarm** rate will be **high** unless the test is **extremely discriminating**.



11.12.2024


Intrusion Detection Systems

27

27

Host-Based Intrusion Detection

- **Host-based IDSs** add a **specialized layer** of security software to **monitor** system activity to **detect** suspicious behavior.



- The primary **benefit** of host-based IDS is to **detect** both **external** and **internal** intrusions.

11.12.2024

Intrusion Detection Systems

28

28

Host-Based Intrusion Detection

Host-Based IDS Approaches

- **Anomaly detection**: defines normal/expected behavior
 - Threshold detection
 - Profile based
 - **Effective** against **masqueraders** but **not** for **misfeasors**
- **Signature detection**: defines proper behavior
 - May be used against **misfeasors**

11.12.2024

Intrusion Detection Systems

29

29

Host-Based Intrusion Detection

- Traditionally, **host-based IDS** focuses on **single** system stand-alone facilities -> **needs** to defend **distributed** collection of host in an organization.
- A more **effective** defense can be achieved by **coordination** and **cooperation** among **IDSs** across the network.
- **Design issues of distributed host-based IDS**
 - **Different** audit record formats
 - **Collection** point of network (confidentiality and integrity must be preserved)
 - Centralized versus decentralized **architecture**

11.12.2024

Intrusion Detection Systems

30

30

Host-Based Intrusion Detection




Figure 8.2 Architecture for Distributed Intrusion Detection
11.12.2024 Intrusion Detection Systems

31

31

Host-Based Intrusion Detection




Figure 8.3 Agent Architecture
11.12.2024 Intrusion Detection Systems

32

32

Network-Based Intrusion Detection

- A Network-Based IDS (NIDS)
 - monitors traffic at **selected points** on a network
 - examines the **traffic** packet by packet in **real time** or close to real time to **detect** intrusion patterns
 - examines **network, transport, and application level protocol activity**
- Host-Based IDS versus Network-Based IDS
 - NIDS examines packet traffic **directed toward** **potentially vulnerable** computer system on a network.
 - A **host-based** system examines **user** and **software** activity on a host.

11.12.2024

Intrusion Detection Systems

33

33

Network-Based Intrusion Detection

- Comprises on a number of sensors
 - **Inline** sensor (possibly a part of a network device)
 - **Passive** sensor (monitors copy of traffic)
- Logging of alerts: When a sensor **detects** a potential **violation**, it sends an **alert** and **logs** information related to the event. -> NIDS **analysis** module uses this information.

11.12.2024

Intrusion Detection Systems

34

34

Network-Based Intrusion Detection




Figure 8.5 Example of NIDS Sensor Deployment
11.12.2024 Intrusion Detection Systems

35

35

Network-Based Intrusion Detection

Intrusion Detection Techniques

- Signature Detection
 - Application layer (DHCP, DNS, FTP,...)
 - Transport layer (TCP, UDP, ..)
 - Network layer (IP, ICMP,..)
 - Unexpected application services
 - Policy violations (inappropriate Web sites)
- Anomaly Detection
 - Denial-of-service (DoS) attacks
 - Scanning
 - Worms

11.12.2024

Intrusion Detection Systems

36

36

Distributed Adaptive Intrusion Detection

- The **concept** of communicating IDSs has evolved to schemes that involve **distributed** systems that **cooperate** to **identify intrusions** and to **adapt** to changing attack profiles.
- In an **adaptive cooperative system**, a local node uses a **peer-to-peer "gossip"** protocol to inform other machines of its suspicion, in the form of probability that the network is under attack.

11.12.2024

Intrusion Detection Systems

37

37

Distributed Adaptive Intrusion Detection




Figure 8.6 Overall Architecture of an Autonomic Enterprise Security System

11.12.2024

Intrusion Detection Systems

38

38

Honeypots

Honeypots are **decoy** systems that are designed to **lure** a potential **attacker** away from critical systems.



Honeypots

- Filled with **fabricated** information
- A **legitimate** user of the system **wouldn't** access.
- Instrumented** with sensitive **monitors** and event **loggers**
- Information has **no productive** value

11.12.2024

Intrusion Detection Systems

39

39

Honeypots

- If a honeypot **initiates outbound communication**, the system has probably been **compromised**.
- Honeypots are designed to**
 - Divert** an **attacker** from accessing critical systems
 - Collect** information about the **attacker's activity**
 - Encourage** the attacker to **stay** on the system **long enough** for administrators to respond

11.12.2024

Intrusion Detection Systems

40

40

Honeypots

Classification of Honeypots

- Low interaction honeypots**
 - Consists of software package
 - Emulates particular IT services
 - Does not execute full version of services
- High interaction honeypots**
 - Is a real system
 - Full OS, services and applications

11.12.2024

Intrusion Detection Systems

41

41

Honeypots




Figure 8.8 Example of Honeypot Deployment

11.12.2024

Intrusion Detection Systems

42

42

Summary

- Intrusions
- Intrusion detection approaches
- Honeypots

11.12.2024

Intrusion Detection Systems

43