## Turbulence HW1

## Yu Cang 018370210001

October 9, 2018

## 1 EXERCISE1

Let

$$\Phi = \iiint_{\Omega} \phi dv \tag{1.1}$$

where  $\phi$  is the passive scalar, and  $\Omega$  is the control volume.

Then the change of  $\Phi$  is due to the gradiant diffusion through boundary of  $\Omega$ , which can be written as

$$\frac{D}{Dt}\Phi = \iint_{\partial\Omega} \Gamma \nabla \phi d\vec{S} \tag{1.2}$$

where  $\Gamma$  indicates the diffusivity, with unit of  $m^2/s$ .

The material derivative of  $\Phi$  in Euler field is given as follows using RTT

$$\frac{D}{Dt}\Phi = \iiint_{\Omega} \frac{\partial \phi}{\partial t} dv + \oiint_{\partial \Omega} \phi \vec{U} \cdot d\vec{S}$$
 (1.3)

When field of  $\phi$  is assumed to be smooth enough, the divergence theorem can be applied, which yields

$$\iiint_{\Omega} \frac{\partial \phi}{\partial t} dv + \iiint_{\Omega} \nabla \cdot (\phi \vec{U}) dv = \iiint_{\Omega} \nabla \cdot (\Gamma \nabla \phi) dv \tag{1.4}$$

namely

$$\frac{\partial \phi}{\partial t} + \nabla \cdot (\phi \vec{U}) = \nabla \cdot (\Gamma \nabla \phi) \tag{1.5}$$

The equation can be further simplified when the flow is assumed to be both incompressible and constant-property.

$$\frac{\partial \phi}{\partial t} + \vec{U} \cdot \nabla \phi = \Gamma \nabla^2 \phi \tag{1.6}$$

which can be written in material derivative format as

$$\frac{D}{Dt}\phi = \Gamma \nabla^2 \phi \tag{1.7}$$

## 2 EXERCISE2

Let X and Y be 2 sequences of random numbers, the correlation coefficient of these 2 random variables is calculated as

$$\rho_{XY} = \frac{cov(X,Y)}{\sqrt{E[X^2]E[Y^2]}} \tag{2.1}$$

the covariance of X and Y is calculated as

$$cov(X,Y) = E[(X - E[X])(Y - E[Y])] = E[XY] - E[X]E[Y]$$
 (2.2)

With E[XY], E[X], E[Y],  $E[X^2]$ ,  $E[Y^2]$  provided, the correlation coefficient can be therefore calculated. And numerical experiment has been done with 500 times trial.




Figure 2.1: Covariance of random numbers

- 3 Exercise3
- 4 Exercise4