

```

--
=====
=====
-- SECTION 1: SCHEMAS (application-relevant)
--
=====
=====
-- public: your application schema (Holy Grills)
-- extensions: extension objects
-- Platform-managed schemas (auth, storage,
realtime, cron, net, vault,
-- graphql, pgbouncer, supabase_migrations,
information_schema, pg_catalog,
-- pg_toast) are provisioned automatically by
Supabase on any new project.
-- They do NOT need to be recreated manually via
migration.

CREATE SCHEMA IF NOT EXISTS public;
CREATE SCHEMA IF NOT EXISTS extensions;

--
=====
=====
-- SECTION 2: EXTENSIONS
--
=====
=====
CREATE EXTENSION IF NOT EXISTS "uuid-ossf"
WITH SCHEMA extensions;
CREATE EXTENSION IF NOT EXISTS "pgcrypto"
WITH SCHEMA extensions;
CREATE EXTENSION IF NOT EXISTS "pg_trgm"
WITH SCHEMA extensions;
CREATE EXTENSION IF NOT EXISTS "citext"
WITH SCHEMA extensions;

```

```
CREATE EXTENSION IF NOT EXISTS "pg_stat_statements"
WITH SCHEMA extensions;
CREATE EXTENSION IF NOT EXISTS "pg_net"
WITH SCHEMA public;
CREATE EXTENSION IF NOT EXISTS "pg_cron";          -
- schema: pg_catalog (platform-managed placement)
-- supabase_vault is provisioned by the platform
automatically; do not
-- attempt to CREATE EXTENSION supabase_vault
manually on a fresh project.

-- NOTE: pg_net is installed in the `public` schema
on this project.
-- Supabase's current default is the `extensions`
schema for new projects.
-- If your Python code or SQL functions reference
net.* unqualified,
-- confirm search_path includes the correct schema
after cloning, or the
-- calls will fail to resolve.
```