

UNIPOLAR STEPPER MOTOR DRIVER IC

Check for Samples: [DRV8805](#)

FEATURES

- **4-Channel Protected Low-Side Driver**
 - Four NMOS FETs With Overcurrent Protection
 - Integrated Inductive Catch Diodes
- **Indexer/Translator for Unipolar Stepper Motors**
 - Simple Step/Direction Interface
 - Three Step Modes (2-Phase Full-Step, 1-2-Phase Half-Step, 1-Phase Wave Drive)
- **DW Package: 1.5-A (Single Channel On) / 800-mA (Four Channels On) Maximum Drive Current per Channel (at 25°C)**
- **PWP Package: 2-A (Single Channel On) / 1-A (Four Channels On) Maximum Drive Current per Channel (at 25°C, With Proper PCB Heatsinking)**

- **8.2-V to 60-V Operating Supply Voltage Range**
- **Thermally Enhanced Surface Mount Package**

APPLICATIONS

- **Gaming Machines**
- **General Unipolar Stepper Motor Drivers**

DESCRIPTION

The DRV8805 provides an integrated solution for driving unipolar stepper motors. It includes four low side drivers with overcurrent protection and provides built-in diodes to clamp turn-off transients generated by the motor windings.

Indexer logic to control a unipolar stepper motor using a simple step/direction interface is also integrated. Three stepping modes are supported: 2 phase (full-step), 1-2 phase (half-step), and 1-phase (wave drive).

In the SOIC (DW) package, the DRV8805 can supply up to 1.5-A (one channel on) or 800-mA (all channels on) continuous output current per channel, at 25°C. In the HTSSOP (PWP) package, it can supply up to 2-A (one channel on) or 1-A (four channels on) continuous output current per channel, at 25°C with proper PCB heatsinking.

Internal shutdown functions are provided for over current protection, short circuit protection, under voltage lockout and overtemperature and faults are indicated by a fault output pin.

The DRV8805 is available in a 20-pin thermally-enhanced SOIC package and a 16-pin HTSSOP package (Eco-friendly: RoHS & no Sb/Br).

ORDERING INFORMATION⁽¹⁾

| PACKAGE ⁽²⁾ | | ORDERABLE PART NUMBER | TOP-SIDE MARKING |
|------------------------|--------------|-----------------------|------------------|
| (SOIC) - DW | Reel of 2000 | DRV8805DWR | DRV8805 |
| | Tube of 25 | DRV8805DW | DRV8805 |
| (HTSSOP) - PWP | Reel of 2000 | DRV8805PWPR | DRV8805 |
| | Tube of 90 | DRV8805PWP | DRV8805 |

(1) For the most current packaging and ordering information, see the Package Option Addendum at the end of this document, or see the TI web site at www.ti.com.

(2) Package drawings, thermal data, and symbolization are available at www.ti.com/packaging.



Please be aware that an important notice concerning availability, standard warranty, and use in critical applications of Texas Instruments semiconductor products and disclaimers thereto appears at the end of this data sheet.

PowerPAD is a trademark of Texas Instruments.

DEVICE INFORMATION

Functional Block Diagram






Table 1. TERMINAL FUNCTIONS

| NAME | PIN (SOIC) | PIN (HTSSOP) | I/O ⁽¹⁾ | DESCRIPTION | EXTERNAL COMPONENTS OR CONNECTIONS |
|------------------|------------------------|-----------------|--------------------|----------------------|--|
| POWER AND GROUND | | | | | |
| GND | 5, 6, 7, 14, 15, 16 | 5, 12, PPAD | - | Device ground | All pins must be connected to GND. |
| VM | 1 | 1 | - | Device power supply | Connect to motor supply (8.2 V - 60 V). |
| CONTROL | | | | | |
| nENBL | 10 | 8 | I | Enable input | Active low enables outputs – internal pulldown |
| RESET | 11 | 9 | I | Reset input | Active-high reset input initializes internal logic – internal pulldown |
| STEP | 18 | 14 | I | Step input | Rising edge advances motor to next step – internal pulldown |
| DIR | 17 | 13 | I | Direction input | Level controls direction of rotation – internal pulldown |
| SM0 | 13 | 11 | I | Step mode | Sets step mode – see step modes section for details – internal pulldowns |
| SM1 | 12 | 10 | | | |
| STATUS | | | | | |
| nFAULT | 20 | 16 | OD | Fault | Logic low when in fault condition (overtemp, overcurrent) |
| nHOME | 19 | 15 | OD | Home | Logic low when indexer is at home position – weak internal pullup to 3.3 V |
| OUTPUT | | | | | |
| OUT1 | 3 | 3 | O | Output 1 | Connect to load 1 |
| OUT2 | 4 | 4 | O | Output 2 | Connect to load 2 |
| OUT3 | 8 | 6 | O | Output 3 | Connect to load 3 |
| OUT4 | 9 | 7 | O | Output 4 | Connect to load 4 |
| VCLAMP | 2 | 2 | - | Output clamp voltage | Connect to VM supply, or zener diode to VM supply |

(1) Directions: I = input, O = output, OD = open-drain output

**DW (WIDE SOIC) PACKAGE
(TOP VIEW)**

**PWP (HTSSOP) PACKAGE
(TOP SIDE)**


ABSOLUTE MAXIMUM RATINGS

over operating free-air temperature range (unless otherwise noted) ⁽¹⁾ ⁽²⁾

| | | VALUE | UNIT |
|-------------------|--|-------------------------------|------|
| VM | Power supply voltage range | –0.3 to 65 | V |
| VOU _{Tx} | Output voltage range | –0.3 to 65 | V |
| VCLAMP | Clamp voltage range | –0.3 to 65 | V |
| nHOME, nFAULT | Output current | 20 | mA |
| | Peak clamp diode current | 2 | A |
| | DC or RMS clamp diode current | 1 | A |
| | Digital input pin voltage range | –0.5 to 7 | V |
| nHOME, nFAULT | Digital output pin voltage range | –0.5 to 7 | V |
| | Peak motor drive output current, $t < 1 \mu\text{s}$ | Internally limited | A |
| | Continuous total power dissipation | See Dissipation Ratings table | |
| T _J | Operating virtual junction temperature range | –40 to 150 | °C |
| T _{stg} | Storage temperature range | –60 to 150 | °C |

- (1) Stresses beyond those listed under absolute maximum ratings may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under recommended operating conditions is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.
- (2) All voltage values are with respect to network ground terminal.

THERMAL INFORMATION

| THERMAL METRIC | | DRV8805 | DRV8805 | UNITS |
|-------------------|---|---------|---------|-------|
| | | DW | PWP | |
| | | 20 PINS | 16 PINS | |
| θ_{JA} | Junction-to-ambient thermal resistance ⁽¹⁾ | 67.7 | 39.6 | °C/W |
| θ_{JCTop} | Junction-to-case (top) thermal resistance ⁽²⁾ | 32.9 | 24.6 | |
| θ_{JB} | Junction-to-board thermal resistance ⁽³⁾ | 35.4 | 20.3 | |
| ψ_{JT} | Junction-to-top characterization parameter ⁽⁴⁾ | 8.2 | 0.7 | |
| ψ_{JB} | Junction-to-board characterization parameter ⁽⁵⁾ | 34.9 | 20.1 | |
| θ_{JCbott} | Junction-to-case (bottom) thermal resistance ⁽⁶⁾ | N/A | 2.3 | |

- (1) The junction-to-ambient thermal resistance under natural convection is obtained in a simulation on a JEDEC-standard, high-K board, as specified in JESD51-7, in an environment described in JESD51-2a.
- (2) The junction-to-case (top) thermal resistance is obtained by simulating a cold plate test on the package top. No specific JEDEC-standard test exists, but a close description can be found in the ANSI SEMI standard G30-88.
- (3) The junction-to-board thermal resistance is obtained by simulating in an environment with a ring cold plate fixture to control the PCB temperature, as described in JESD51-8.
- (4) The junction-to-top characterization parameter, ψ_{JT} , estimates the junction temperature of a device in a real system and is extracted from the simulation data for obtaining θ_{JA} , using a procedure described in JESD51-2a (sections 6 and 7).
- (5) The junction-to-board characterization parameter, ψ_{JB} , estimates the junction temperature of a device in a real system and is extracted from the simulation data for obtaining θ_{JA} , using a procedure described in JESD51-2a (sections 6 and 7).
- (6) The junction-to-case (bottom) thermal resistance is obtained by simulating a cold plate test on the exposed (power) pad. No specific JEDEC standard test exists, but a close description can be found in the ANSI SEMI standard G30-88.

RECOMMENDED OPERATING CONDITIONS

| | | MIN | NOM | MAX | UNIT |
|-------------|--|-----|-----|-----|------|
| V_M | Power supply voltage range | 8.2 | | 60 | V |
| V_{CLAMP} | Output clamp voltage range ⁽¹⁾ | 0 | | 60 | V |
| I_{OUT} | Continuous output current, single channel on, $T_A = 25^\circ\text{C}$, SOIC package ⁽²⁾ | | | 1.5 | A |
| | Continuous output current, four channels on, $T_A = 25^\circ\text{C}$, SOIC package ⁽²⁾ | | | 0.8 | |
| | Continuous output current, single channel on, $T_A = 25^\circ\text{C}$, HTSSOP package ⁽²⁾ | | | 1.5 | |
| | Continuous output current, four channels on, $T_A = 25^\circ\text{C}$, HTSSOP package ⁽²⁾ | | | 0.8 | |

(1) V_{CLAMP} is used only to supply the clamp diodes. It is not a power supply input.

(2) Power dissipation and thermal limits must be observed.

ELECTRICAL CHARACTERISTICS

$T_A = 25^\circ\text{C}$, over recommended operating conditions (unless otherwise noted)

| PARAMETER | | TEST CONDITIONS | MIN | TYP | MAX | UNIT |
|---|--------------------------------------|---|-----|------|-----|------|
| POWER SUPPLIES | | | | | | |
| I _{VM} | VM operating supply current | V _M = 24 V | | 1.6 | 2.1 | mA |
| V _{UVLO} | VM undervoltage lockout voltage | V _M rising | | | 8.2 | V |
| LOGIC-LEVEL INPUTS (SCHMITT TRIGGER INPUTS WITH HYSTERESIS) | | | | | | |
| V _{IL} | Input low voltage | | | 0.6 | 0.7 | V |
| V _{IH} | Input high voltage | | 2 | | | V |
| V _{HYS} | Input hysteresis | | | 0.45 | | V |
| I _{IL} | Input low current | V _{IN} = 0 | -20 | | 20 | μA |
| I _{IH} | Input high current | V _{IN} = 3.3 V | | | 100 | μA |
| R _{PD} | Pulldown resistance | | | 100 | | kΩ |
| nFAULT OUTPUT (OPEN-DRAIN OUTPUT) | | | | | | |
| V _{OL} | Output low voltage | I _O = 5 mA | | | 0.5 | V |
| I _{OH} | Output high leakage current | V _O = 3.3 V | | | 1 | μA |
| nHOME OUTPUT (OPEN-DRAIN OUTPUT WITH WEAK INTERNAL PULLUP) | | | | | | |
| V _{OL} | Output low voltage | I _O = 5 mA | | | 0.5 | V |
| V _{OH} | Output high voltage | I _O = 100 μA, V _M = 24 V | | 3.3 | | V |
| I _{OH} | Output high leakage current | V _O = 3.3 V | | | 1 | μA |
| LOW-SIDE FETS | | | | | | |
| R _{DS(ON)} | FET on resistance | V _M = 24 V, I _O = 700 mA, T _J = 25°C | | 0.5 | | Ω |
| | | V _M = 24 V, I _O = 700 mA, T _J = 85°C | | 0.75 | 0.8 | |
| I _{OFF} | Off-state leakage current | | -50 | | 50 | μA |
| HIGH-SIDE DIODES | | | | | | |
| V _F | Diode forward voltage | V _M = 24 V, I _O = 700 mA, T _J = 25°C | | 1.2 | | V |
| I _{OFF} | Off-state leakage current | V _M = 24 V, T _J = 25°C | -50 | | 50 | μA |
| OUTPUTS | | | | | | |
| t _R | Rise time | V _M = 24 V, I _O = 700 mA, Resistive load | 50 | | 300 | ns |
| t _F | Fall time | V _M = 24 V, I _O = 700 mA, Resistive load | 50 | | 300 | ns |
| PROTECTION CIRCUITS | | | | | | |
| I _{OCP} | Overcurrent protection trip level | | 2.3 | | 3.8 | A |
| t _{OCP} | Overcurrent protection deglitch time | | | 3.5 | | μs |
| t _{RETRY} | Overcurrent protection retry time | | | 1.2 | | ms |
| t _{TSD} | Thermal shutdown temperature | Die temperature ⁽¹⁾ | 150 | 160 | 180 | °C |

(1) Not production tested.

TIMING REQUIREMENTS

over operating free-air temperature range (unless otherwise noted)⁽¹⁾

| NO. | PARAMETER | DESCRIPTION | MIN | MAX | UNIT |
|-----|--------------------------------|---|-----|-----|---------------|
| 1 | f_{STEP} | Step frequency | | 250 | kHz |
| 2 | $t_{\text{WH}}(\text{STEP})$ | Pulse duration, STEP high | 1.9 | | μs |
| 3 | $t_{\text{WL}}(\text{STEP})$ | Pulse duration, STEP low | 1.9 | | μs |
| 4 | $t_{\text{SU}}(\text{STEP})$ | Setup time, DIR, SMx to STEP rising | 1 | | μs |
| 5 | $t_{\text{H}}(\text{STEP})$ | Hold time, DIR, SMx to STEP rising | 1 | | μs |
| 6 | $t_{\text{OE}}(\text{ENABLE})$ | Enable time, nENBL to output low | | 50 | ns |
| 7 | $t_{\text{PD}}(\text{L-H})$ | Propagation delay time, STEP to OUTx, low to high | | 500 | ns |
| 8 | $t_{\text{PD}}(\text{H-L})$ | Propagation delay time, STEP to OUTx, high to low | | 500 | ns |
| - | t_{RESET} | RESET pulse width | 20 | | μs |

(1) Not production tested.




Figure 1. DRV8805 Timing Requirements

FUNCTIONAL DESCRIPTION

Output Drivers

The DRV8805 contains four protected low-side drivers. Each output has an integrated clamp diode connected to a common pin, VCLAMP.

VCLAMP can be connected to the main power supply voltage, VM. It can also be connected to a zener or TVS diode to VM, allowing the switch voltage to exceed the main supply voltage VM. This connection can be beneficial when driving loads that require very fast current decay, such as unipolar stepper motors.

In all cases, the voltage on the outputs must not be allowed to exceed the maximum output voltage specification.

Indexer Operation

The DRV8805 integrates an indexer to allow motor control with a simple step and direction interface. Logically, the indexer is shown in [Figure 2](#).




Figure 2. Indexer Operation

Step Modes

The SM0 and SM1 pins select the stepping mode of the translator as shown in [Table 2](#).

Table 2. Step Modes

| SM1 | SM0 | MODE |
|-----|-----|---------------------------------|
| 0 | 0 | 2-phase drive (full step) |
| 0 | 1 | 1-2 phase drive (half step) |
| 1 | 0 | 1-phase excitation (wave drive) |
| 1 | 1 | Reserved |

In all modes, during a fault condition, the STEP input will be ignored. See the Protection Circuits section below.

The sequence of the outputs is shown in [Table 3](#) through [Table 5](#).

Table 3. 2-Phase Excitation (Full-Step)

| Function | Step | RESET | DIR | STEP | nHOME | OUT1 | OUT2 | OUT3 | OUT4 |
|-------------|------|-------|-----|------|--------|--------|--------|--------|--------|
| Reset | 1 | 1 | X | X | 0 | ON | OFF | OFF | ON |
| CW | 2 | 0 | 1 | ↑ | 1 | ON | ON | OFF | OFF |
| CW | 3 | 0 | 1 | ↑ | 1 | OFF | ON | ON | OFF |
| CW | 4 | 0 | 1 | ↑ | 1 | OFF | OFF | ON | ON |
| CW to home | 1 | 0 | 1 | ↑ | 0 | ON | OFF | OFF | ON |
| CCW | 4 | 0 | 0 | ↑ | 1 | OFF | OFF | ON | ON |
| CCW | 3 | 0 | 0 | ↑ | 1 | OFF | ON | ON | OFF |
| CCW | 2 | 0 | 0 | ↑ | 1 | ON | ON | OFF | OFF |
| CCW to home | 1 | 0 | 0 | ↑ | 0 | ON | OFF | OFF | ON |
| Hold | X | 0 | X | ↑ | no chg | no chg | no chg | no chg | no chg |

Table 4. 1-2-Phase Excitation (Half-Step)

| Function | Step | RESET | DIR | STEP | nHOME | OUT1 | OUT2 | OUT3 | OUT4 |
|-------------|------|-------|-----|------|--------|--------|--------|--------|--------|
| Reset | 1 | 1 | X | X | 0 | ON | OFF | OFF | OFF |
| CW | 2 | 0 | 1 | ↑ | 1 | ON | ON | OFF | OFF |
| CW | 3 | 0 | 1 | ↑ | 1 | OFF | ON | OFF | OFF |
| CW | 4 | 0 | 1 | ↑ | 1 | OFF | ON | ON | OFF |
| CW | 5 | 0 | 1 | ↑ | 1 | OFF | OFF | ON | OFF |
| CW | 6 | 0 | 1 | ↑ | 1 | OFF | OFF | ON | ON |
| CW | 7 | 0 | 1 | ↑ | 1 | OFF | OFF | OFF | ON |
| CW | 8 | 0 | 1 | ↑ | 1 | ON | OFF | OFF | ON |
| CW to home | 1 | 0 | 1 | ↑ | 0 | ON | OFF | OFF | OFF |
| CCW | 8 | 0 | 0 | ↑ | 1 | ON | OFF | OFF | ON |
| CCW | 7 | 0 | 0 | ↑ | 1 | OFF | OFF | OFF | ON |
| CCW | 6 | 0 | 0 | ↑ | 1 | OFF | OFF | ON | ON |
| CCW | 5 | 0 | 0 | ↑ | 1 | OFF | OFF | ON | OFF |
| CCW | 4 | 0 | 0 | ↑ | 1 | OFF | ON | ON | OFF |
| CCW | 3 | 0 | 0 | ↑ | 1 | OFF | ON | OFF | OFF |
| CCW | 2 | 0 | 0 | ↑ | 1 | ON | ON | OFF | OFF |
| CCW to home | 1 | 0 | 0 | ↑ | 0 | ON | OFF | OFF | OFF |
| Hold | X | 0 | X | ↑ | no chg | no chg | no chg | no chg | no chg |

Table 5. 1-Phase Excitation (Wave Drive)

| Function | Step | RESET | DIR | STEP | nHOME | OUT1 | OUT2 | OUT3 | OUT4 |
|-------------|------|-------|-----|------|--------|--------|--------|--------|--------|
| Reset | 1 | 1 | X | X | 0 | ON | OFF | OFF | OFF |
| CW | 2 | 0 | 1 | ↑ | 1 | OFF | ON | OFF | OFF |
| CW | 3 | 0 | 1 | ↑ | 1 | OFF | OFF | ON | OFF |
| CW | 4 | 0 | 1 | ↑ | 1 | OFF | OFF | OFF | ON |
| CW to home | 1 | 0 | 1 | ↑ | 0 | ON | OFF | OFF | OFF |
| CCW | 4 | 0 | 0 | ↑ | 1 | OFF | OFF | OFF | ON |
| CCW | 3 | 0 | 0 | ↑ | 1 | OFF | OFF | ON | OFF |
| CCW | 2 | 0 | 0 | ↑ | 1 | OFF | ON | OFF | OFF |
| CCW to home | 1 | 0 | 0 | ↑ | 0 | ON | OFF | OFF | OFF |
| Hold | X | 0 | X | ↑ | no chg | no chg | no chg | no chg | no chg |

nENBL and RESET Operation

The nENBL pin enables or disables the output drivers. nENBL must be low to enable the outputs. nENBL does not affect the operation of the serial interface logic. Note that nENBL has an internal pulldown.

The RESET pin, when driven active high, resets the internal logic. The indexer is reset to the home state. All inputs are ignored while RESET is active. Note that RESET has an internal pulldown. An internal power-up reset is also provided, so it is not required to drive RESET at power-up.

Protection Circuits

The DRV8805 is fully protected against undervoltage, overcurrent and overtemperature events.

Overcurrent Protection (OCP)

An analog current limit circuit on each FET limits the current through the FET by removing the gate drive. If this analog current limit persists for longer than the t_{OCP} deglitch time (approximately 3.5 μ s), the driver will be disabled and the nFAULT pin will be driven low. The driver will remain disabled for the t_{RETRY} retry time (approximately 1.2 ms), then the fault will be automatically cleared. The fault will be cleared immediately if either RESET pin is activated or VM is removed and re-applied.

Thermal Shutdown (TSD)

If the die temperature exceeds safe limits, all output FETs will be disabled and the nFAULT pin will be driven low. The STEP input will be ignored. Once the die temperature has fallen to a safe level, operation will automatically resume.

Undervoltage Lockout (UVLO)

If at any time the voltage on the VM pin falls below the undervoltage lockout threshold voltage, all circuitry in the device will be disabled, and internal logic will be reset. Operation will resume when VM rises above the UVLO threshold.

THERMAL INFORMATION

Thermal Protection

The DRV8805 has thermal shutdown (TSD) as described above. If the die temperature exceeds approximately 150°C, the device will be disabled until the temperature drops to a safe level.

Any tendency of the device to enter TSD is an indication of either excessive power dissipation, insufficient heatsinking, or too high an ambient temperature.

Power Dissipation

Power dissipation in the DRV8805 is dominated by the power dissipated in the output FET resistance, or $R_{DS(ON)}$. Average power dissipation of each FET when running a static load can be roughly estimated by [Equation 1](#):

$$P = R_{DS(ON)} \cdot (I_{OUT})^2 \quad (1)$$

where P is the power dissipation of one FET, $R_{DS(ON)}$ is the resistance of each FET, and I_{OUT} is equal to the average current drawn by the load. Note that at start-up and fault conditions this current is much higher than normal running current; these peak currents and their duration also need to be taken into consideration. When driving more than one load simultaneously, the power in all active output stages must be summed.

The maximum amount of power that can be dissipated in the device is dependent on ambient temperature and heatsinking.

Note that $R_{DS(ON)}$ increases with temperature, so as the device heats, the power dissipation increases. This must be taken into consideration when sizing the heatsink.

Heatsinking

The DRV8805DW package uses a standard SOIC outline, but has the center pins internally fused to the die pad in order to more efficiently remove heat from the device. The two center leads on each side of the package should be connected together to as large a copper area on the PCB as is possible to remove heat from the device. If the copper area is on the opposite side of the PCB from the device, thermal vias are used to transfer the heat between top and bottom layers.

In general, the more copper area that can be provided, the more power can be dissipated.

The DRV8805PWP package uses an HTSSOP package with an exposed PowerPAD™. The PowerPAD package uses an exposed pad to remove heat from the device. For proper operation, this pad must be thermally connected to copper on the PCB to dissipate heat. On a multi-layer PCB with a ground plane, this can be accomplished by adding a number of vias to connect the thermal pad to the ground plane. On PCBs without internal planes, copper area can be added on either side of the PCB to dissipate heat. If the copper area is on the opposite side of the PCB from the device, thermal vias are used to transfer the heat between top and bottom layers.

For details about how to design the PCB, refer to TI Application Report [SLMA002](#), "PowerPAD Thermally Enhanced Package" and TI Application Brief [SLMA004](#), "PowerPAD Made Easy", available at www.ti.com.

PACKAGING INFORMATION

| Orderable Device | Status ⁽¹⁾ | Package Type | Package Drawing | Pins | Package Qty | Eco Plan ⁽²⁾ | Lead/ Ball Finish | MSL Peak Temp ⁽³⁾ | Samples (Requires Login) |
|------------------|-----------------------|--------------|-----------------|------|-------------|----------------------------|----------------------|------------------------------|-----------------------------|
| DRV8805DW | ACTIVE | SOIC | DW | 20 | 25 | Green (RoHS & no Sb/Br) | CU NIPDAU | Level-2-260C-1 YEAR | |
| DRV8805DWR | ACTIVE | SOIC | DW | 20 | 2000 | Green (RoHS & no Sb/Br) | CU NIPDAU | Level-2-260C-1 YEAR | |
| DRV8805PWP | ACTIVE | HTSSOP | PWP | 16 | 90 | Green (RoHS & no Sb/Br) | CU NIPDAU | Level-3-260C-168 HR | |
| DRV8805PWPR | ACTIVE | HTSSOP | PWP | 16 | 2000 | Green (RoHS & no Sb/Br) | CU NIPDAU | Level-3-260C-168 HR | |

⁽¹⁾ The marketing status values are defined as follows:

ACTIVE: Product device recommended for new designs.

LIFEBUY: TI has announced that the device will be discontinued, and a lifetime-buy period is in effect.

NRND: Not recommended for new designs. Device is in production to support existing customers, but TI does not recommend using this part in a new design.

PREVIEW: Device has been announced but is not in production. Samples may or may not be available.

OBSOLETE: TI has discontinued the production of the device.

⁽²⁾ Eco Plan - The planned eco-friendly classification: Pb-Free (RoHS), Pb-Free (RoHS Exempt), or Green (RoHS & no Sb/Br) - please check <http://www.ti.com/productcontent> for the latest availability information and additional product content details.

TBD: The Pb-Free/Green conversion plan has not been defined.

Pb-Free (RoHS): TI's terms "Lead-Free" or "Pb-Free" mean semiconductor products that are compatible with the current RoHS requirements for all 6 substances, including the requirement that lead not exceed 0.1% by weight in homogeneous materials. Where designed to be soldered at high temperatures, TI Pb-Free products are suitable for use in specified lead-free processes.



Pb-Free (RoHS Exempt): This component has a RoHS exemption for either 1) lead-based flip-chip solder bumps used between the die and package, or 2) lead-based die adhesive used between the die and leadframe. The component is otherwise considered Pb-Free (RoHS compatible) as defined above.

Green (RoHS & no Sb/Br): TI defines "Green" to mean Pb-Free (RoHS compatible), and free of Bromine (Br) and Antimony (Sb) based flame retardants (Br or Sb do not exceed 0.1% by weight in homogeneous material)

⁽³⁾ MSL, Peak Temp. -- The Moisture Sensitivity Level rating according to the JEDEC industry standard classifications, and peak solder temperature.

Important Information and Disclaimer: The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.

TAPE AND REEL INFORMATION
REEL DIMENSIONS

TAPE DIMENSIONS


| | |
|----|---|
| A0 | Dimension designed to accommodate the component width |
| B0 | Dimension designed to accommodate the component length |
| K0 | Dimension designed to accommodate the component thickness |
| W | Overall width of the carrier tape |
| P1 | Pitch between successive cavity centers |

TAPE AND REEL INFORMATION

*All dimensions are nominal

| Device | Package Type | Package Drawing | Pins | SPQ | Reel Diameter (mm) | Reel Width W1 (mm) | A0 (mm) | B0 (mm) | K0 (mm) | P1 (mm) | W (mm) | Pin1 Quadrant |
|-------------|--------------|-----------------|------|------|--------------------|--------------------|---------|---------|---------|---------|--------|---------------|
| DRV8805DWR | SOIC | DW | 20 | 2000 | 330.0 | 24.4 | 10.8 | 13.0 | 2.7 | 12.0 | 24.0 | Q1 |
| DRV8805PWPR | HTSSOP | PWP | 16 | 2000 | 330.0 | 12.4 | 6.9 | 5.6 | 1.6 | 8.0 | 12.0 | Q1 |

TAPE AND REEL BOX DIMENSIONS




*All dimensions are nominal

| Device | Package Type | Package Drawing | Pins | SPQ | Length (mm) | Width (mm) | Height (mm) |
|-------------|--------------|-----------------|------|------|-------------|------------|-------------|
| DRV8805DWR | SOIC | DW | 20 | 2000 | 367.0 | 367.0 | 45.0 |
| DRV8805PWPR | HTSSOP | PWP | 16 | 2000 | 367.0 | 367.0 | 35.0 |

DW (R-PDSO-G20)


PLASTIC SMALL OUTLINE



- NOTES: A. All linear dimensions are in inches (millimeters). Dimensioning and tolerancing per ASME Y14.5M-1994.
B. This drawing is subject to change without notice.
C. Body dimensions do not include mold flash or protrusion not to exceed 0.006 (0,15).
D. Falls within JEDEC MS-013 variation AC.

DW (R-PDSO-G20)


PLASTIC SMALL OUTLINE



- NOTES:
- A. All linear dimensions are in millimeters.
 - B. This drawing is subject to change without notice.
 - C. Refer to IPC7351 for alternate board design.
 - D. Laser cutting apertures with trapezoidal walls and also rounding corners will offer better paste release. Customers should contact their board assembly site for stencil design recommendations. Refer to IPC-7525
 - E. Customers should contact their board fabrication site for solder mask tolerances between and around signal pads.

PWP (R-PDSO-G16)

PowerPAD™ PLASTIC SMALL OUTLINE



- NOTES:
- A. All linear dimensions are in millimeters.
 - B. This drawing is subject to change without notice.
 - C. Body dimensions do not include mold flash or protrusions. Mold flash and protrusion shall not exceed 0.15 per side.
 - D. This package is designed to be soldered to a thermal pad on the board. Refer to Technical Brief, PowerPad Thermally Enhanced Package, Texas Instruments Literature No. SLMA002 for information regarding recommended board layout. This document is available at www.ti.com <<http://www.ti.com>>.
 - E. See the additional figure in the Product Data Sheet for details regarding the exposed thermal pad features and dimensions.
 - E. Falls within JEDEC MO-153

PowerPAD is a trademark of Texas Instruments.


PWP (R-PDSO-G16) PowerPAD™ SMALL PLASTIC OUTLINE

THERMAL INFORMATION

This PowerPAD™ package incorporates an exposed thermal pad that is designed to be attached to a printed circuit board (PCB). The thermal pad must be soldered directly to the PCB. After soldering, the PCB can be used as a heatsink. In addition, through the use of thermal vias, the thermal pad can be attached directly to the appropriate copper plane shown in the electrical schematic for the device, or alternatively, can be attached to a special heatsink structure designed into the PCB. This design optimizes the heat transfer from the integrated circuit (IC).

For additional information on the PowerPAD package and how to take advantage of its heat dissipating abilities, refer to Technical Brief, PowerPAD Thermally Enhanced Package, Texas Instruments Literature No. SLMA002 and Application Brief, PowerPAD Made Easy, Texas Instruments Literature No. SLMA004. Both documents are available at www.ti.com.

The exposed thermal pad dimensions for this package are shown in the following illustration.




4206332-7/AC 07/12

NOTE: A. All linear dimensions are in millimeters

PowerPAD is a trademark of Texas Instruments

PWP (R-PDSO-G16)

PowerPAD™ PLASTIC SMALL OUTLINE



- NOTES:
- A. All linear dimensions are in millimeters.
 - B. This drawing is subject to change without notice.
 - C. Customers should place a note on the circuit board fabrication drawing not to alter the center solder mask defined pad.
 - D. This package is designed to be soldered to a thermal pad on the board. Refer to Technical Brief, PowerPad Thermally Enhanced Package, Texas Instruments Literature No. SLMA002, SLMA004, and also the Product Data Sheets for specific thermal information, via requirements, and recommended board layout. These documents are available at www.ti.com <<http://www.ti.com>>. Publication IPC-7351 is recommended for alternate designs.
 - E. Laser cutting apertures with trapezoidal walls and also rounding corners will offer better paste release. Customers should contact their board assembly site for stencil design recommendations. Example stencil design based on a 50% volumetric metal load solder paste. Refer to IPC-7525 for other stencil recommendations.
 - F. Customers should contact their board fabrication site for solder mask tolerances between and around signal pads.

PowerPAD is a trademark of Texas Instruments.

IMPORTANT NOTICE

Texas Instruments Incorporated and its subsidiaries (TI) reserve the right to make corrections, enhancements, improvements and other changes to its semiconductor products and services per JESD46C and to discontinue any product or service per JESD48B. Buyers should obtain the latest relevant information before placing orders and should verify that such information is current and complete. All semiconductor products (also referred to herein as "components") are sold subject to TI's terms and conditions of sale supplied at the time of order acknowledgment.

TI warrants performance of its components to the specifications applicable at the time of sale, in accordance with the warranty in TI's terms and conditions of sale of semiconductor products. Testing and other quality control techniques are used to the extent TI deems necessary to support this warranty. Except where mandated by applicable law, testing of all parameters of each component is not necessarily performed.

TI assumes no liability for applications assistance or the design of Buyers' products. Buyers are responsible for their products and applications using TI components. To minimize the risks associated with Buyers' products and applications, Buyers should provide adequate design and operating safeguards.

TI does not warrant or represent that any license, either express or implied, is granted under any patent right, copyright, mask work right, or other intellectual property right relating to any combination, machine, or process in which TI components or services are used. Information published by TI regarding third-party products or services does not constitute a license to use such products or services or a warranty or endorsement thereof. Use of such information may require a license from a third party under the patents or other intellectual property of the third party, or a license from TI under the patents or other intellectual property of TI.

Reproduction of significant portions of TI information in TI data books or data sheets is permissible only if reproduction is without alteration and is accompanied by all associated warranties, conditions, limitations, and notices. TI is not responsible or liable for such altered documentation. Information of third parties may be subject to additional restrictions.

Resale of TI components or services with statements different from or beyond the parameters stated by TI for that component or service voids all express and any implied warranties for the associated TI component or service and is an unfair and deceptive business practice. TI is not responsible or liable for any such statements.

Buyer acknowledges and agrees that it is solely responsible for compliance with all legal, regulatory and safety-related requirements concerning its products, and any use of TI components in its applications, notwithstanding any applications-related information or support that may be provided by TI. Buyer represents and agrees that it has all the necessary expertise to create and implement safeguards which anticipate dangerous consequences of failures, monitor failures and their consequences, lessen the likelihood of failures that might cause harm and take appropriate remedial actions. Buyer will fully indemnify TI and its representatives against any damages arising out of the use of any TI components in safety-critical applications.

In some cases, TI components may be promoted specifically to facilitate safety-related applications. With such components, TI's goal is to help enable customers to design and create their own end-product solutions that meet applicable functional safety standards and requirements. Nonetheless, such components are subject to these terms.

No TI components are authorized for use in FDA Class III (or similar life-critical medical equipment) unless authorized officers of the parties have executed a special agreement specifically governing such use.

Only those TI components which TI has specifically designated as military grade or "enhanced plastic" are designed and intended for use in military/aerospace applications or environments. Buyer acknowledges and agrees that any military or aerospace use of TI components which have **not** been so designated is solely at the Buyer's risk, and that Buyer is solely responsible for compliance with all legal and regulatory requirements in connection with such use.

TI has specifically designated certain components which meet ISO/TS16949 requirements, mainly for automotive use. Components which have not been so designated are neither designed nor intended for automotive use; and TI will not be responsible for any failure of such components to meet such requirements.

Products

| | |
|------------------------|--|
| Audio | www.ti.com/audio |
| Amplifiers | amplifier.ti.com |
| Data Converters | dataconverter.ti.com |
| DLP® Products | www.dlp.com |
| DSP | dsp.ti.com |
| Clocks and Timers | www.ti.com/clocks |
| Interface | interface.ti.com |
| Logic | logic.ti.com |
| Power Mgmt | power.ti.com |
| Microcontrollers | microcontroller.ti.com |
| RFID | www.ti-rfid.com |
| OMAP Mobile Processors | www.ti.com/omap |
| Wireless Connectivity | www.ti.com/wirelessconnectivity |

Applications

| | |
|-------------------------------|--|
| Automotive and Transportation | www.ti.com/automotive |
| Communications and Telecom | www.ti.com/communications |
| Computers and Peripherals | www.ti.com/computers |
| Consumer Electronics | www.ti.com/consumer-apps |
| Energy and Lighting | www.ti.com/energy |
| Industrial | www.ti.com/industrial |
| Medical | www.ti.com/medical |
| Security | www.ti.com/security |
| Space, Avionics and Defense | www.ti.com/space-avionics-defense |
| Video and Imaging | www.ti.com/video |

TI E2E Community

e2e.ti.com