

AUTH CANON

2026-03-18

Dexter Hadley, MD/PhD

Hadley Lab CANONIC

Abstract

AUTH gates scope access identity is the KYC anchor, scope-level readers/writers declared in CANON.md, fail-closed by default.

hadleylab.org Governed Research. Every claim cited.

Contents

- **AUTH_IS_SCOPE_GATE** access is gated at scope granularity; every scopes CANON.md declares its readers and writers explicitly.
- **IDENTITY_IS_KYC_ANCHOR** identity resolves through the KYC anchor; session tokens are server-side, not client-only.
- **FAIL_CLOSED** PRIVATE scope with no matching reader denies by default; every surface with privacy: PRIVATE declares auth: required.
- **AUTH_EVENTS_LEDGERED** login, logout, grant, and deny events are all ledgered for audit. ## Constraints

MUST: Scope-level access readers/writers declared
MUST: Fail-closed PRIVATE scope with no matching
MUST: Session tokens server-side (not client-only)
MUST: Ledger all auth events (login, logout, grant
MUST: Every surface with privacy: PRIVATE declares
MUST NOT: Store tokens in client localStorage
MUST NOT: Gate public (SHOP) projections
MUST NOT: Hardcode user lists outside CANON.md
MUST NOT: Serve PRIVATE content without authenticated

AUTH | CANON | SERVICES