

DEBUG CANON

2026-03-18

Dexter Hadley, MD/PhD

Hadley Lab CANONIC

Abstract

DEBUG is the governed runtime ledger every error structured, every warning keyed, every event TTL-bounded, no ephemeral console logs.

hadleylab.org Governed Research. Every claim cited.

Contents

- **STRUCTURED_LOGS_ONLY** every runtime function uses a governed logger; no bare `console.*` in production.
- **FIXED_EVENT_SHAPE** every log event is a structured record with fixed fields (ts, surface, fn, level, code, ctx); codes are declared in the instance Code Registry.
- **APPEND_ONLY_TTL_BOUNDED** events land in an append-only keyed store (LEDGER_KV prefix debug:) with bounded retention; no unbounded history. ## Constraints

MUST: Every runtime function uses a governed logger.

MUST: Every log event is a structured record with .

MUST: Every code referenced by a function is declared.

MUST: Every event lands in an append-only keyed store.

MUST: Every event has bounded retention via TTL.

MUST: Logger sink failures MUST NOT propagate to the user.

MUST NOT: Bypass the ledger for errors on production systems.

MUST NOT: Log PII beyond what governance explicitly permits.

MUST NOT: Extend debug TTL for events with economic consequences.

DEBUG / CANON / SERVICES