

Gyproc® DuraLine®



Gyproc® DuraLine®

Gyproc® DuraLine® is a durable and high impact resistant gypsum board for internal drywall system as GypWall™ ROBUST. Its gypsum core is also incorporated with fiber glass and additional fire protective additives. GypWall™ ROBUST is as straight and durable impact resistant partition system that is the superior alternative to traditional brick walls. A high impact resistant internal system that is ideal for homes and high traffic commercial areas where strong and robust wall are required.

KEY BENEFITS



**Robustness
Guarantee**



**Sound
Insulation**



**Fire
Protection**



**Fixing
Capability**



Stability



**Superior
Aesthetic &
Design**



**Recycling
Certified**



**Environmentally
Friendly**

PRODUCT SPECIFICATION

- Thickness 13 mm (Thailand Plant), 16 mm & 19 mm (Malaysia Plant)
- Edge Type Recessed Edge (RE) 
- Nominal Size 1200x2400 mm, 1220x2440 mm
- Weight 11.5 kg/m²
- Appearance mustard yellow liner paper for 13 mm
white liner paper for 16 and 19 mm
gray liner paper on back side

PERFORMANCE

- Classified as Class O material in accordance to building regulation
- Up to 1-hour and 2-hours fire rating (GypWall™ ROBUST system) in accordance to BS 476: Part 22
- Non-combustible in accordance to BS 476: Part 4
- Low fire propagation in accordance to BS 476: Part 6
- Class 1 surface spread of flame in accordance to BS 476: Part 7
- Achieved SEVERE duty (GypWall ROBUST system) in accordance to BS 5234: Part 2

THERMAL INSULATION

- Thermal conductivity (λ) = 0.24 W/mk
- Thermal resistance (R) = 0.05 m² K/W

HANDLING AND WORKABILITY

- Crack-free
- Seamless and smooth finishing

STANDARDS

- BS EN 520 : 2004 + A1 : 2009
- ASTM C1396
- AS/NZ 2588

