

Garbage Collector

markbits_limit	0x307e3f891000
dynamic_mark_ref_bits	Dynamic memory starts at 0x307e3f800000 0x302000000000, so
size	
relocatable_mark_ref_bits	0x307e3f800000
size	
global_mark_ref_bits	Each 64-bit node in this maps to 64 0x307e00000000 nodes of memory (i.e. bitvector)
size	8 GiB
dynamic_refidx	0x307dfe3f8000
size	
global_refidx	0x307dfe000000
size	20 MiB global_mark_ref_bits - global_refidx
relocatab_limit	0x307bfe009008
global_reloctab	Each 64-bit node in this maps to 64 0x307bfe000000 nodes of memory (i.e. bitvector)
GCrelocptr	
managed_static_refidx	pmcl-kernel.c/create_reserved_area 0x12462c000 (random address from mmap)
size	0x1fc000
managed_static_refbits	pmcl-kernel.c/create_reserved_area 0x104a2c000 (random address from mmap)
size	0x1fc00000
active_dynamic_area	AREA_DYNAMIC pmcl-kernel.c/allocate_dynamic_area()
low_addr	0x302000000000
high_addr	0x302000480000
younger	NULL
older	g1_area memory.c/egc_control()
refbits	
refidx	
markbits	dynamic_mark_ref_bits
static_dnodes	0 pmcl-kernel.c/init_consing_areas()
static_used	0 pmcl-kernel.c/init_consing_areas()
threshold	2 MiB pmcl-kernel.c/default_g0_threshold
g1_area	AREA_DYNAMIC
low_addr	0x302000000000 pmcl-kernel.c/init_consing_areas()
high_addr	0x302000000000 pmcl-kernel.c/init_consing_areas()
younger	active_dynamic_area pmcl-kernel.c/init_consing_areas()
older	g2_area pmcl-kernel.c/init_consing_areas()
refbits	
refidx	
markbits	
static_dnodes	
static_used	
threshold	4 MiB pmcl-kernel.c/init_consing_areas()
g2_area	AREA_DYNAMIC
low_addr	0x302000000000 pmcl-kernel.c/init_consing_areas()
high_addr	0x302000000000 pmcl-kernel.c/init_consing_areas()
younger	g1_area pmcl-kernel.c/init_consing_areas()
older	tenured_area pmcl-kernel.c/init_consing_areas()
refbits	
refidx	
markbits	
static_dnodes	
static_used	
threshold	8 MiB pmcl-kernel.c/init_consing_areas()
tenured_area	AREA_DYNAMIC

low_addr	0x302000000000	pmcl-kernel.c/init_consing_areas()
high_addr	0x302000000000	pmcl-kernel.c/init_consing_areas()
younger	g2_area	pmcl-kernel.c/init_consing_areas()
older	NULL	
refbits	dynamic_mark_ref_bits	pmcl-kernel.c/init_consing_areas()
refidx	dynamic_refidx	pmcl-kernel.c/init_consing_areas()
markbits		
static_dnodes	active_dynamic_area->static_dnodes	pmcl-kernel.c/init_consing_areas()
static_used	active_dynamic_area->static_used	pmcl-kernel.c/init_consing_areas()
managed_static_area	AREA_MANAGED_STATIC	
low_addr	0x300040000000	
high_addr	0x300040569000	
younger		
older		
refbits	global_mark_ref_bits	pmcl-kernel.c/init_consing_areas()
refidx	global_refidx	pmcl-kernel.c/init_consing_areas()
markbits		
static_dnodes		
static_used		