

# MU5IN075

## Network Analysis and Mining

### 5. Random Graph Models II

Esteban Bautista-Ruiz, Lionel Tabourier

LIP6 – CNRS and Sorbonne Université

`first_name.last_name@lip6.fr`

October 12, 2021

1/12

## Notion of uniform generation

Until now 3 random models, **2 different families of models**:

1. Erdős-Rényi
2. Watts-Strogatz, Barabási-Albert

Why are they fundamentally different?

1. ER: there is a **target set** (graphs with fixed density)  
all graphs have the same probability to be produced
2. BA, WS: no explicit target set. . .

⇒ ER model is **uniform** (or homogeneous)

2/12

## Notion of uniform generation

Until now 3 random models, **2 different families of models**:

1. Erdős-Rényi
2. Watts-Strogatz, Barabási-Albert

Why are they fundamentally different?

1. ER: there is a **target set** (graphs with fixed density)  
all graphs have the same probability to be produced
2. BA, WS: no explicit target set. . .

⇒ ER model is **uniform** (or homogeneous)

2/12

## Notion of uniform generation

Until now 3 random models, **2 different families of models**:

1. Erdős-Rényi
2. Watts-Strogatz, Barabási-Albert

Why is it important?

Because we cannot say that a BA is a *standard* SF graph  
or that a WS is a *standard* graph with small-world properties

⇒ **more relevant to have uniform graph generation**

2/12

## Notion of uniform generation

Until now 3 random models, **2 different families of models**:

1. Erdős-Rényi
2. Watts-Strogatz, Barabási-Albert

Why is it important?

Because we cannot say that a BA is a *standard* SF graph  
or that a WS is a *standard* graph with small-world properties

⇒ more relevant to have uniform graph generation

## Outline

- 1 Uniform graph generation with fixed degree distribution
  - Configuration model and variants
  - A few words on switching methods
  - The bipartite case

## The configuration model

Degree distribution

$p_1, p_2, p_3, \dots$

Draw nodes degree according to the distribution

→ degree sequence

1 2 4 3 2 1 3

Associate to any node half-edges (stubs)

Draw random pairs of stubs and connect them

Deal with possible loops or multi-edges

## The configuration model

Degree distribution

$p_1, p_2, p_3, \dots$

Draw nodes degree according to the distribution

→ degree sequence

1 2 4 3 2 1 3

Associate to any node half-edges (stubs)

Draw random pairs of stubs and connect them

Deal with possible loops or multi-edges

## The configuration model

Degree distribution

$p_1, p_2, p_3, \dots$

Draw nodes degree according to the distribution

→ degree sequence

1 2 4 3 2 1 3

Associate to any node half-edges (stubs)



Draw random pairs of stubs and connect them

Deal with possible loops or multi-edges

4/12

## The configuration model

Degree distribution

$p_1, p_2, p_3, \dots$

Draw nodes degree according to the distribution


→ degree sequence

1 2 4 3 2 1 3

Associate to any node half-edges (stubs)



Draw random pairs of stubs and connect them



Deal with possible loops or multi-edges

4/12

## The configuration model

Degree distribution

$p_1, p_2, p_3, \dots$

Draw nodes degree according to the distribution


→ degree sequence

1 2 4 3 2 1 3

Associate to any node half-edges (stubs)



Draw random pairs of stubs and connect them



Deal with possible loops or multi-edges

4/12

## Implementing the configuration model

Table : node  $i$  occurs exactly  $d^o(i)$  times

|   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 0 | 1 | 1 | 2 | 2 | 2 | 2 | 3 | 3 | 3 | 4 | 4 | 5 | 6 | 6 | 6 |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|

**Algorithm 1:** Generating a graph with fixed degree sequence

$i = 2m$

**while**  $i > 0$  **do**

$u = \text{random}(0, i - 1)$

    swap boxes  $u$  and  $i - 1$

$v = \text{random}(0, i - 2)$

    swap boxes  $v$  and  $i - 2$

$i = i - 2$

    edge  $(u, v)$  created\*

**end**

\* to be discussed...

5/12



## Deal with possible loops or multi-edges

**Answer 1: generation with rejection**Loop or multi-edge generated, **restart the generation process**

6/12

## Deal with possible loops or multi-edges

- advantage: **uniform generation**
- drawback: **can be long...**



|      |  |       |
|------|--|-------|
| 2180 | average number of trials (1000 nodes): | 17300 |
| 1.2s | average generation time (1000 nodes):  | 8.1s  |

**Quiz:** for what kind of distribution can it be long?

6/12



## Deal with possible loops or multi-edges

**Answer 2: suppress loops or multiple edges**When a loop or a multiedge is generated, **exclude it**



6/12

## Deal with possible loops or multi-edges

- advantage: **fast**
- drawback: **does not have the exact degree sequence**




after loops and multi-edges deletion, become:



6/12


## Deal with possible loops or multi-edges

**Answer 3: reconnect**When a loop or a multiedge is generated, **switch to destroy it**


6/12

## Deal with possible loops or multi-edges

- advantage: **relatively fast, have the exact sequence**
- drawback: not uniform = **biased**




number of triangles for 1000 graphs




6/12

## Deal with possible loops or multi-edges

- advantage: **relatively fast, have the exact sequence**
- drawback: not uniform = **biased**



number of triangles for 1000 graphs



6/12

## Properties – Comparison

|               | real          | fixed d.d. |
|---------------|---------------|------------|
| density       | low           | ?          |
| connectedness | giant comp.   | ?          |
| distances     | low           | ?          |
| degree        | heterogeneous | ?          |
| clustering    | high          | ?          |
| communities   | yes           | ?          |

7/12

## Properties – Comparison

|               | real          | fixed d.d.    |
|---------------|---------------|---------------|
| density       | low           | low           |
| connectedness | giant comp.   | giant comp.   |
| distances     | low           | low           |
| degree        | heterogeneous | heterogeneous |
| clustering    | high          | lower         |
| communities   | yes           | no            |

→ heterogeneous degree **only partly accounts** for the c.c.  
→ see practical work

7/12

## Other implementation: switching method

### Principle

- start from a graph with the given degree sequence
- iterate **switching of edge ends**
- after a *sufficient amount* of switches, the graph produced is a **random element of the set of graphs**

8/12

## Other implementation: switching method

### Why does it work?

- The degree of any node remains unchanged  
so we keep the degree sequence unchanged
- The process is a Markov chain
  - can be seen as a **random walk** in the set of graphs (defined by this degree sequence)
  - after a while, we visit all elements with the same probability (not proved here)
  - if we make enough switches, we obtain a random graph with this degree sequence

9/12

## Other implementation: switching method

### Why does it work?


- The degree of any node remains unchanged  
so we keep the degree sequence unchanged
- The process is a Markov chain
  - can be seen as a **random walk** in the set of graphs (defined by this degree sequence)
  - after a while, we visit all elements with the same probability (not proved here)
  - if we make enough switches, we obtain a random graph with this degree sequence

9/12

## Other implementation: switching method

## When to stop switchings?

Measuring some features (ex: clustering) during the process until these features do not evolve any more...




credits image: I.Miklós and J.Podani

10/12

## Graph with fixed degree sequence: the bipartite case

Newman, Watts, Strogatz - PNAS, 2002

- **Bipartite graph**: two distinct types of nodes  $U$  and  $V$   
→ links between  $U$  and  $V$
- **Projection**: if  $u_1$  and  $u_2$  connected to  $v$  in bipartite  
→  $u_1$  and  $u_2$  are connected in the  $U$ -projection



bipartite data richer, but not always available

11/12

## Graph with fixed degree sequence: the bipartite case

Newman, Watts, Strogatz - PNAS, 2002

Underlying bipartite structure ⇒ cliques in the projection

## Bipartite configuration model

- fixed degree sequence for nodes  $X$ :  $d_1^X, d_2^X, \dots, d_{n_X}^X$
- fixed degree sequence for nodes  $Y$ :  $d_1^Y, d_2^Y, \dots, d_{n_Y}^Y$
- random connections

→ no possible self-loops, but multiedges still a problem

11/12

## Graph with fixed degree sequence: the bipartite case

Newman, Watts, Strogatz - PNAS, 2002

Experimental results - comparison of the projections:

|                       | average degree |       | clustering coef. |       |
|-----------------------|----------------|-------|------------------|-------|
| projected network     | Model          | Real  | Model            | Real  |
| Company directors     | 14.53          | 14.44 | 0.590            | 0.588 |
| Movie actors          | 125.6          | 113.4 | 0.084            | 0.199 |
| Physics collaboration | 16.74          | 9.27  | 0.192            | 0.452 |

Conclusions:

- more realistic clustering  
than ER, or usual configuration model on unipartite networks
- still no large-scale structure  
visible on scientific collaboration networks

11/12

## Graph with fixed degree sequence: the bipartite case

Newman, Watts, Strogatz - *PNAS*, 2002

Experimental results - comparison of the projections:

| projected network     | average degree |       | clustering coef. |       |
|-----------------------|----------------|-------|------------------|-------|
|                       | Model          | Real  | Model            | Real  |
| Company directors     | 14.53          | 14.44 | 0.590            | 0.588 |
| Movie actors          | 125.6          | 113.4 | 0.084            | 0.199 |
| Physics collaboration | 16.74          | 9.27  | 0.192            | 0.452 |

Conclusions:

- more realistic clustering  
than ER, or usual configuration model on unipartite networks
- still no large-scale structure  
visible on scientific collaboration networks

## Perspective: more models

- Fix other constraints beyond degree distribution? but how?
- Exponential Random Graphs
- Stochastic Block Model
- Spatial models
- ...

→ still many open research questions