Diffusion Models: From Adding Noise to Generating Images
Understanding Denoising-Based Generation through DDPM and LDM

[Full name 1] – [Student ID 1] [Full name 2] – [Student ID 2]
[Full name 3] – [Student ID 3]
University of Science (HCMUS), VNU-HCM
CS420 – Artificial Intelligence

Abstract

How can learning to remove noise enable a model to generate new images? This report explains how Gaussian forward corruption, a learned reverse model, and noise-prediction training define an iterative generator. We review two complementary papers: Denoising Diffusion Probabilistic Models (DDPM) establishes a practical pixel-space formulation, while Latent Diffusion Models (LDM) moves denoising into a learned compressed representation. We introduce the original 2015 diffusion framework, then distinguish DDPM's noise-prediction parameterization from direct reverse-parameter estimation. Starting from the variational objective, we explain DDPM's simplified loss, distinguish training from sampling, and illustrate forward noising with a complete scalar calculation and an original five-level image sequence. With pretrained checkpoints, we measure median sampling times of 6.10 *s for pixel DDPM and* 2.44 *s for LDM on LSUN Churches under our settings. Across five ImageNet classes, saved intermediate states show how image structure emerges during denoising. We discuss these observations alongside published evidence on quality, efficiency, and conditioning.*

1. Introduction

Adding noise destroys image structure, yet learning to remove it can support generation. Across many images and noise levels, a denoiser learns shared statistical structure. A generative process uses this information to produce samples rather than recover one particular corrupted photograph.

Our guiding question is: *How can learning to remove noise enable a model to generate new images?* Our learning objective is to *explain forward noising and reverse denoising, including why latent diffusion reduces computational demands*. These goals organize the report around two complementary papers. DDPM [6] develops the earlier diffusion framework [11] through effective noise-prediction training. LDM [10] asks how to retain that process while reducing repeated computation at image resolution.

We first explain the 2015 probabilistic construction: forward corruption, a learned reverse model, sampling, and variational training. We then isolate DDPM's noise-prediction parameterization and simplified objective. A brief score-matching connection follows the method rather than serving as its prerequisite. We then examine LDM's encoder, decoder, and latent representation. Our experiments time pretrained pixel and latent generators on LSUN Churches and trace sampling and forward noising across five ImageNet classes. We compare the observations with published results and discuss the scope of class labels and text prompts.

2. Background and Paper Review

2.1. Generative versus discriminative models

The fundamental distinction between discriminative and generative models lies in what they aim to learn from data. A discriminative model learns to predict a target y given an observation x, typically by estimating $p_\omega(y \mid x)$ or learning a decision boundary between classes. For instance, a cat classifier only needs to identify features that distinguish cats from other objects, without explicitly modeling the distribution of natural images. In contrast, a generative model aims to capture the underlying data distribution, such as $p_\theta(x)$ or the conditional distribution $p_\theta(x \mid y)$. Rather than merely distinguishing categories, it must model the statistical structure and variability of the data, including factors such as shape, texture, lighting, and spatial relationships. This enables the model to generate new samples that resemble the training data, potentially conditioned on labels or text descriptions. Consequently, generative modeling generally requires capturing richer information about the data than is necessary for classification.

2.2. Qualitative Comparison of Generative Models

GANs, autoregressive models, and diffusion models differ in how they learn and sample the data distribution. A *GAN*

trains a generator to transform random noise into images while a discriminator learns to distinguish generated images from real ones [3]. Sampling typically takes one generator pass, but training requires balancing the two competing networks. An *autoregressive model* generates an image one pixel or token at a time, predicting each from the previously generated values [15]. This gives an explicit factorization of the image distribution, although sequential generation can be costly. A *diffusion model* learns to reverse gradual noise corruption and generates an image by repeatedly denoising an initially random state [6]. It refines the whole state across multiple steps, requiring repeated network evaluations during sampling. Figure 8 in Appendix E compares the generative mechanisms of these three families.

2.3. Historical context

The foundations of diffusion-based generative modeling were established by Sohl-Dickstein et al. [11], who introduced a probabilistic framework inspired by nonequilibrium thermodynamics. Their approach consists of a forward diffusion process that gradually destroys the structure of the data by adding noise, followed by a learned reverse process that reconstructs samples from noise. By decomposing a complex generative transformation into a sequence of small, tractable transitions, this framework enables likelihood-based training and probabilistic inference. However, generating samples requires many sequential reverse steps, making inference computationally expensive.

An alternative perspective was developed by Song and Ermon [13] through score-based generative modeling. Instead of directly modeling the data probability density, their approach estimates its score function, defined as the gradient of the log-density. To address difficulties in estimating scores when data lie near low-dimensional manifolds, they introduced multiple levels of Gaussian noise and trained a noise-conditional score network. Samples are then generated using annealed Langevin dynamics, which progressively moves samples toward high-density regions as the noise level decreases.

Ho et al. [6] subsequently introduced Denoising Diffusion Probabilistic Models (DDPM), establishing a connection between diffusion probabilistic modeling and denoising score matching. Their formulation parameterizes the reverse process through a neural network that predicts the Gaussian noise added at each diffusion timestep.

Despite their strong generative performance, conventional diffusion models operate directly in high-dimensional pixel space, resulting in substantial training and sampling costs. To address this limitation, Rombach et al. [10] proposed Latent Diffusion Models (LDM). This architecture incorporates cross-attention mechanisms to support flexible conditioning, including text-guided image generation.

3. Method: From the 2015 Framework to DDPM

The first three subsections explain the Gaussian diffusion framework of Sohl-Dickstein et al. (2015) [11]. We then isolate DDPM's choices of reverse parameterization and training objective [6]. We use x_t and the later $\alpha_t, \bar{\alpha}_t$ notation throughout so that the two formulations can be compared directly.

3.1. 2015: forward process, Gaussian noise, and schedule

A clean image $x_0 \in \mathbb{R}^D$ is gradually corrupted by a Gaussian Markov chain. The Gaussian branch of the 2015 model uses [11, Sec. 2.1, Table C.1]

$$q(x_t \mid x_{t-1}) = \mathcal{N}\Big(\sqrt{1-\beta_t}\, x_{t-1},\, \beta_t \mathbf{I}\Big), \tag{1}$$

$$x_t = \sqrt{1-\beta_t}\, x_{t-1} + \sqrt{\beta_t}\, \varepsilon^{(t)},$$

$$\varepsilon^{(t)} \sim \mathcal{N}(0, \mathbf{I}), \qquad \alpha_t = 1 - \beta_t, \quad \bar{\alpha}_t = \prod_{j=1}^{t} \alpha_j.$$

Here D counts normalized image coordinates, $\mathbf{I}$ is the identity matrix, and $t \in \{1, \dots, T\}$ is a step index, not physical time. The innovations $\varepsilon^{(t)}$ are independent across steps and coordinates. The dimensionless variance $\beta_t \in (0, 1)$ simultaneously attenuates the previous signal by $\sqrt{1-\beta_t}$ and sets the new noise standard deviation $\sqrt{\beta_t}$. The schedule $(\beta_1, \dots, \beta_T)$ controls how rapidly structure is lost.

The standard Gaussian is stationary under this kernel: if a state has covariance $\mathbf{I}$ and is standard normal, the next state's covariance is $(1-\beta_t)\mathbf{I} + \beta_t \mathbf{I} = \mathbf{I}$. Repeated small steps can therefore transform a complex image distribution toward a simple Gaussian prior. In the 2015 Gaussian experiments, β_1 is fixed to a small value while $\beta_2, \dots, \beta_T$ are learned through the variational bound; the paper also notes that a fixed schedule can work comparably [11, Sec. 2.4.1]. The Gaussian kernel's form is known even when its rates are optimized.

Repeated Gaussian composition gives, with $\bar{\alpha}_0 = 1$,

$$x_t = \sqrt{\bar{\alpha}_t}\, x_0 + \sqrt{1-\bar{\alpha}_t}\, \varepsilon, \qquad \varepsilon \sim \mathcal{N}(0, \mathbf{I}). \tag{2}$$

This is the same Gaussian marginal later used by DDPM, written in its notation; it is not a new forward-process invention. The aggregate noise ε differs from an individual innovation $\varepsilon^{(t)}$. For small $\bar{\alpha}_T$, the terminal distribution approaches standard normal; a finite schedule need not make that equality exact.

3.2. 2015: learned reverse process and sampling

Let $p_{\text{data}}(x_0)$ denote the unknown data distribution. The original diffusion model learns a finite reverse Markov

chain, starting from a simple Gaussian prior $p(x_T) = \mathcal{N}(0, \mathbf{I})$ [11, Sec. 2.2]:

$$p_\theta(x_{0:T}) = p(x_T) \prod_{t=1}^{T} p_\theta(x_{t-1} \mid x_t),$$
$$p_\theta(x_{t-1} \mid x_t) = \mathcal{N}(\mu_\theta(x_t, t), \Sigma_\theta(x_t, t)). \quad (3)$$

Although the true reverse conditional depends on the unknown data distribution and is not necessarily Gaussian, sufficiently small diffusion steps motivate approximating each reverse transition with a Gaussian distribution.

For learned intermediate transitions, neural functions f_μ and f_Σ parameterize the mean $\mu_\theta(x_t, t)$ and covariance $\Sigma_\theta(x_t, t)$, respectively. The mean specifies the expected previous state, while the covariance captures uncertainty in the reverse transition. Unlike DDPM's later noise-prediction parameterization, the original model directly estimates these reverse-distribution parameters. The DDPM formulation is discussed in Section 3.4.

To generate a sample, the model draws $x_T \sim \mathcal{N}(0, \mathbf{I})$ and iteratively applies the reverse transitions:

$$x_{t-1} = \mu_\theta(x_t, t) + \Sigma_\theta(x_t, t)^{1/2} u_t, \quad u_t \sim \mathcal{N}(0, \mathbf{I}). \quad (4)$$

For diagonal covariance, the matrix square root corresponds to elementwise standard deviations. The original formulation additionally specifies a boundary convention for the final transition at $t = 1$ [11, App. B.2], detailed in Appendix C.5. Through these successive stochastic transitions, the model transforms Gaussian noise into samples approximating p_{data}, without requiring a clean input image.

Figure 1 summarizes the forward corruption process and the learned reverse sampling process: structure is progressively destroyed in the forward direction, while generation starts from noise and samples successive reverse transitions.

3.3. 2015: Variational Objective and Its Loss Terms

The learning objective is to maximize the probability assigned to real images. Since the exact likelihood integrates over all intermediate states, Sohl-Dickstein et al. optimize a variational lower bound [11, Sec. 2.4]:

$$\mathbb{E}_{p_{\text{data}}}[\log p_\theta(x_0)] \geq K_{2015} = -\sum_{t=2}^{T} \mathcal{D}_t + C_\beta. \quad (5)$$

Equivalently, the loss to minimize is the *negative* bound:

$$\mathcal{L}_{2015} = -K_{2015} = \sum_{t=2}^{T} \mathcal{D}_t - C_\beta,$$
$$\mathcal{D}_t = \mathbb{E}_q[\mathrm{D}_{\mathrm{KL}}(q(x_{t-1} \mid x_t, x_0) \| p_\theta(x_{t-1} \mid x_t))]. \quad (6)$$

Here $\mathbb{E}_q$ averages over training images and the relevant forward states. The target posterior is tractable because x_0 is known:

$$q(x_{t-1} \mid x_t, x_0) = \mathcal{N}(\tilde{\mu}_t, \tilde{\beta}_t \mathbf{I}), \qquad t > 1. \quad (7)$$

Each KL penalizes errors in both the reverse mean and covariance. C_β collects entropy terms under the original paper's normalization and endpoint convention. It is constant in the reverse-network weights for a fixed schedule, but must be retained when learning β_t. Appendix C.5 gives these terms and the Gaussian KL.

Three components of the variational loss. To connect this framework to DDPM, write the negative-log-likelihood bound using DDPM's endpoint decoder and notation [6, Eq. 5]:

$$L_{\text{VLB}} = \underbrace{\mathbb{E}_q[\mathrm{D}_{\mathrm{KL}}(q(x_T \mid x_0) \| p(x_T))]}_{L_T} + \sum_{t=2}^{T} \underbrace{\mathbb{E}_q[\mathrm{D}_{\mathrm{KL}}(q(x_{t-1} \mid x_t, x_0) \| p_\theta(x_{t-1} \mid x_t))]}_{L_{t-1}} + \underbrace{\mathbb{E}_q[-\log p_\theta(x_0 \mid x_1)]}_{L_0}. \quad (8)$$

The expectation is distributed over the terms for readability; $\mathbb{E}[-\log p_\theta(x_0)] \leq L_{\text{VLB}}$. L_T measures mismatch between terminal forward noise and the prior. L_{t-1} matches each learned reverse transition to its posterior target. L_0 is the final image reconstruction/decoder likelihood loss. The 2015 formulation uses a prescribed stationary-kernel endpoint; its boundary contributions are incorporated in C_β. Thus Eq. (8) is DDPM's presentation of the inherited variational framework, rather than the original paper's literal formula. We next transform the intermediate L_{t-1} terms.

3.4. DDPM: From Gaussian KL to Noise Prediction

Starting from Eq. (8), Ho et al. [6] make two choices. First, they fix the forward schedule, so L_T is constant during training, and fix the intermediate reverse covariance to $\Sigma_\theta = \sigma_t^2 \mathbf{I}$. The expected Gaussian KL L_{t-1} then reduces to a weighted mean-matching error:

$$L_{t-1} = \mathbb{E}\left[\frac{\|\tilde{\mu}_t - \mu_\theta(x_t, t)\|_2^2}{2\sigma_t^2}\right] + C. \quad (9)$$

Second, instead of predicting $\tilde{\mu}_t$ directly, DDPM exploits the closed-form forward process in Eq. (2), where $x_t = \sqrt{\bar{\alpha}_t} x_0 + \sqrt{1 - \bar{\alpha}_t}\varepsilon$. Since the added Gaussian noise ε is known during training, the reverse mean can be parameterized using a noise-prediction network:

$$\mu_\theta(x_t, t) = \frac{1}{\sqrt{\alpha_t}}\left(x_t - \frac{\beta_t}{\sqrt{1 - \bar{\alpha}_t}}\varepsilon_\theta(x_t, t)\right). \quad (10)$$




Figure 1. Two directions of diffusion, introduced in [11] and retained in [6]. An original synthetic scene illustrates progressive Gaussian corruption (blue). Generation starts from fresh noise and samples learned reverse transitions (orange). Reverse arrows are conceptual: no trained-model output or exact recovery of this scene is implied.

Substituting this parameterization into Eq. (9) transforms the mean-matching objective into a weighted noise-prediction loss:

$$L_{t-1} = \mathbb{E}\left[w_t \|\varepsilon - \varepsilon_\theta(x_t, t)\|_2^2\right] + C. \tag{11}$$

Here

$$w_t = \frac{\beta_t^2}{2\sigma_t^2 \alpha_t (1-\bar{\alpha}_t)}, \qquad t > 1. \tag{12}$$

The additive C is independent of θ under these fixed-variance choices. Appendix C.6 gives the substitution in full.

Thus, noise prediction does not replace the underlying variational framework. Instead, it provides an alternative parameterization of the reverse mean, connecting diffusion training to denoising score matching.

3.5. DDPM: Simplified Noise-Prediction Objective

Equation (11) is still an intermediate contribution to the variational bound. DDPM then changes the training objective: it drops the weights w_t and uses the following surrogate [6, Eq. 14]:

$$L_{\text{simple}} = \mathbb{E}_{t,x_0,\varepsilon}\left[\|\varepsilon - \varepsilon_\theta(x_t, t)\|_2^2\right]. \tag{13}$$

During training, a clean image x_0, a timestep $t \sim \text{Uniform}\{1, \ldots, T\}$, and $\varepsilon \sim \mathcal{N}(0, \mathbf{I})$ are used to construct x_t. The network then learns to predict the injected noise from x_t and t.

Removing w_t changes the relative importance of different noise levels. Ho et al. report that this reweighting improves sample quality, particularly by reducing the emphasis on low-noise reconstruction, although optimizing the original variational bound provides better likelihood estimates [6, Secs. 3.4, 4.1–4.2].

The closed-form forward process also enables efficient training: each update evaluates only one randomly selected timestep. This reduces per-update work compared with unrolling the entire chain; dropping w_t changes training weights rather than the number of sampling evaluations.

L_{simple} is therefore not numerically the full L_{VLB}: L_T is fixed, the intermediate terms are reweighted, and the $t = 1$ noise-MSE term approximates the endpoint decoder treatment described by Ho et al. The exact likelihood bound retains L_0; Appendix C.6 explains that boundary detail.

3.6. DDPM sampling and its score interpretation

After training, draw $x_T \sim \mathcal{N}(0, \mathbf{I})$ and run $t = T, T-1, \ldots, 1$. At each step evaluate ε_θ, compute Eq. (10), and sample [6, Algorithm 2]

$$x_{t-1} = \mu_\theta(x_t, t) + \sigma_t u, \qquad u \sim \mathcal{N}(0, \mathbf{I}). \tag{14}$$

Fresh sampling noise is used at intermediate steps; DDPM's final step omits it. Predicted noise determines the reverse *mean*; u is a new random draw. The algorithm does not simply subtract a noise vector from the current image, nor require a corrupted real image as input. The 2015 framework already supplied the prior-to-data reverse chain; DDPM changes the prediction target, variance choice, and training weights.

There is also a score interpretation of this parameterization [6, Sec. 3.2]. Let $q_t(x_t)$ be the marginal distribution of noisy data at timestep t. Then

$$s_\theta(x_t, t) := -\frac{\varepsilon_\theta(x_t, t)}{\sqrt{1-\bar{\alpha}_t}} \approx \nabla_{x_t} \log q_t(x_t). \tag{15}$$

At the ideal MSE optimum $\varepsilon_\theta = \mathbb{E}[\varepsilon \mid x_t, t]$, this is exact under the assumptions in Appendix C.4. It estimates the *noisy* marginal score, not the clean-data gradient at every

noise level. No explicit score-evaluation step is added to the algorithm. In conditional LDM, the same interpretation applies to noisy latents given the condition. Appendix C.2 provides optional score background; its role is explanatory rather than a prerequisite for the probabilistic construction above.

3.7. A complete one-dimensional calculation

For one step $t = 1$, choose normalized $x_0 = 0.8$, variance $\beta_1 = 0.1$, and Gaussian realization $\varepsilon = -0.5$. This larger variance makes the arithmetic visible; the image schedule below uses smaller steps. Equation (1) gives

$$\begin{aligned} \alpha_1 &= 1 - 0.1 = 0.9, \\ \sqrt{\alpha_1}\, x_0 &= \sqrt{0.9}\,(0.8) = 0.758947, \\ \sqrt{\beta_1}\, \varepsilon &= \sqrt{0.1}\,(-0.5) = -0.158114, \\ x_1 &= 0.758947 - 0.158114 = \boxed{0.600833}. \end{aligned}$$

Thus $q(x_1 \mid x_0 = 0.8) = \mathcal{N}(0.758947, 0.1)$: its mean is 0.758947, variance 0.1, and standard deviation $\sqrt{0.1} = 0.316228$. Across independent draws, $\mathbb{E}[x_1 \mid x_0] = \sqrt{0.9}\, x_0$ since $\mathbb{E}[\varepsilon] = 0$. The realization 0.600833 differs from that expectation; the conditional variance is β_1.

3.8. Five noise levels on an original small image

Our original 28×28 geometric house has foreground $+1$ and background -1, without an external dataset. The script `code/make_figures.py` simulates one Markov trajectory using Eq. (1) with independent noise at every step. It uses NumPy's default generator, seed 420, $T = 1000$, and the linear schedule $\beta_t = 10^{-4} + (t-1)(0.02 - 10^{-4})/999$, following DDPM's schedule choice [6, Sec. 4].

The last column is a schedule-based signal-to-noise coefficient ratio, also a per-coordinate variance ratio for unit-variance data. This illustrates corruption, not learned denoising or generation.

4. LDM: Latent Space and Efficient Generation

4.1. Why move from pixels to a latent representation?

The diffusion framework supplies a way to generate images, but repeatedly processing a high-resolution pixel grid is expensive. LDM separates learning a useful image representation from learning its generative distribution [10, Secs. 3.1–3.2]. Its first stage compresses images; its second stage applies diffusion to the resulting spatial tensors. The central question is how much computation can be removed while preserving information needed for convincing reconstruction.

A latent is a learned feature representation, not a smaller JPEG or a text description. For RGB input $x_0 \in \mathbb{R}^{H \times W \times 3}$, let $\tilde{z} \in \mathbb{R}^{h \times w \times c}$, where $h = H/f$, $w = W/f$, $f \geq 1$ is the spatial downsampling factor, and c is the latent channel count. For example, an LDM configuration with $f = 4, c = 3$ maps $256 \times 256 \times 3$ to $64 \times 64 \times 3$ [10, Table 8]. This reduces the number of spatial positions by 16, but the end-to-end runtime and memory depend on more than the state shape.

4.2. VAE encoder, decoder, and the compression trade-off

We emphasize LDM's KL-regularized, VAE-like autoencoder. Its encoder predicts a distribution over representations of an input image [8, 10]:

$$\begin{aligned} q_\phi(\tilde{z} \mid x_0) &= \mathcal{N}\big(\mu_\phi(x_0), \operatorname{diag}(\sigma_\phi^2(x_0))\big)\,, \\ \tilde{z} &= \mu_\phi(x_0) + \sigma_\phi(x_0) \odot \xi, \quad \xi \sim \mathcal{N}(0, \mathbf{I}), \\ \hat{x}_0 &= D_\psi(\tilde{z}). \end{aligned} \tag{16}$$

ϕ, ψ are encoder and decoder parameters. The encoder outputs latent means μ_ϕ and positive standard deviations σ_ϕ; diag forms a diagonal covariance and $\odot$ denotes element-wise multiplication. The decoder D_ψ reconstructs an image $\hat{x}_0$. Reparameterization places randomness in ξ, enabling gradient-based training. This posterior noise is different from the diffusion noise added in the second stage.

The encoder must retain spatial and perceptual information; the decoder must learn how to turn it back into image detail. Reconstruction quality therefore limits what the complete generator can preserve. Excessive compression may erase fine text, small objects, or textures that later diffusion cannot faithfully restore.

Regularization makes the representation suitable for modeling, but the first stage is not merely a textbook VAE with pixel reconstruction loss. LDM uses perceptual and patch-adversarial reconstruction objectives with a weak KL penalty [10, Sec. 3.1]. Perceptual loss compares visual features; adversarial training encourages locally realistic texture. A textbook VAE objective is given in Appendix D.1 to distinguish these choices. The original paper also studies VQ regularization, so LDM is broader than this KL/VAE variant. Neither weak KL regularization nor successful reconstruction makes clean encoded latents exactly standard normal. The diffusion prior must still learn their distribution.

4.3. Diffusion training and sampling in latent space

After the autoencoder is trained, its parameters are fixed while the latent denoiser is trained. Let $z_0 = a\tilde{z}$, with optional fixed scale $a > 0$ to match latent magnitudes to the noise schedule; $a = 1$ means no rescaling. Diffusion acts on $d_z = hwc$ latent coordinates:

$$z_t = \sqrt{\bar{\alpha}_t}\, z_0 + \sqrt{1 - \bar{\alpha}_t}\, \varepsilon_z, \quad \varepsilon_z \sim \mathcal{N}(0, \mathbf{I}_{d_z}), \tag{17}$$

$$L_{\mathrm{LDM}} = \mathbb{E}_{x_0, y, t, \xi, \varepsilon_z}\left[\|\varepsilon_z - \varepsilon_\theta(z_t, t, \tau_\eta(y))\|_2^2\right]. \tag{18}$$



Figure 2. Original forward-noising illustration at five timesteps. The same trajectory is shown throughout. Values are clipped to $[-1, 1]$ only for display; stored arrays and calculations remain unclipped. The equation and schedule follow [6].

Table 1. Coefficients computed by the supplied script. Signal and noise columns refer to Eq. (2), not measured image quality.

t	$\bar{\alpha}_t$	Signal $\sqrt{\bar{\alpha}_t}$	Noise SD $\sqrt{1-\bar{\alpha}_t}$	$\bar{\alpha}_t/(1-\bar{\alpha}_t)$
0	1.000000	1.000000	0.000000	∞
50	0.971016	0.985401	0.170248	33.5015
200	0.659039	0.811812	0.583919	1.9329
500	0.078587	0.280334	0.959902	0.0853
1000	0.000040	0.006353	0.999980	0.000040

The condition y may be a text prompt, encoded by τ_η with parameters η. The time-conditioned denoiser, typically a U-Net, returns a tensor of the same shape as z_t. The conditional objective follows LDM [10, Eq. 3], here making stochastic encoding explicit. Posterior-mean encoding omits ξ.

For generation, start with latent Gaussian noise and repeatedly apply a compatible reverse sampler using the conditional predictor. Decode the final latent once as $D_\psi(z_0/a)$, undoing the training scale. Pure text-to-image generation needs no real input image or image encoder. The encoder is needed to form training representations, whereas the decoder converts a generated representation into pixels. Figure 3 makes these roles explicit.

4.4. Conditioning and the complete pipeline

LDM uses cross-attention to make denoising depend on a condition such as text [10, Sec. 3.3]. Spatial image features supply queries; prompt-token embeddings supply keys and values. Learned attention weights retrieve text information useful for the current features. Thus a prompt changes the denoising predictions throughout the sampling loop; it is not pasted onto the decoded image. The matrix formulation and an optional toy calculation are confined to Appendix D.2.

Classifier-free guidance can strengthen conditional influence by using $\varepsilon_u + s(\varepsilon_c - \varepsilon_u)$, where $\varepsilon_u, \varepsilon_c$ are unconditional and conditional predictions and $s \geq 0$ is the guidance scale [5]. Here $s = 1$ is ordinary conditional sampling. Stronger guidance can trade diversity for conditional fidelity; it does not guarantee correct counting, spatial relations, or attribute binding. Standard CFG uses two denoiser evaluations per step. Details are in Appendix D.3.

The two papers therefore address complementary questions: DDPM learns how iterative denoising can generate an image distribution; LDM learns a representation in which that iteration is less expensive. Compression reduces repeated spatial work. Faster samplers such as DDIM instead reduce the number of evaluations [12]; the two ideas can be combined without treating them as the same speedup.

5. Results and Discussion

5.1. Experimental configuration

We ran inference with four released checkpoints. Table 2 records the settings for the two tasks. The checkpoint URLs, class IDs, sampling code, and timing records are in Appendix B.

5.2. Pixel versus latent diffusion on LSUN Churches

We timed generation from the initial noise draw to the final RGB tensor, with GPU synchronization. The LDM timing includes its decoder. Model loading, one warm-up image per model, and PNG export are outside the timed interval. For visual quality, we inspect recognizable church features and the clarity of outlines and fine detail across all four timed samples.

The latent pipeline achieved a $2.50\times$ speedup by median latency and used more peak tensor memory (Table 3). Both




Figure 3. Original latent diffusion pipeline, based on [10, Fig. 3 and Sec. 3]. The VAE is learned first and frozen for diffusion training; its decoder runs after the denoising loop. Pure text-to-image generation does not require a real input image or the image encoder.

Table 2. Colab configuration for the two experiments. Both runs used pretrained weights, a Tesla T4 with PyTorch `2.14.1+cu130`, batch size one, 256×256 RGB output, and 50 DDIM updates with $\eta = 0$.

Setting	LSUN Churches	ImageNet
Pixel checkpoint	Google `ddpm-ema-church-256`	OpenAI ADM `256x256_diffusion.pt`
Latent checkpoint	CompVis LDM-KL-8 (`lsun_churches.zip`)	CompVis `cin256-v2` (VQ, $f = 4$)
Conditioning	Unconditional for both models	Class label for both models, with CFG $s = 3.0$ for LDM
Precision	FP32 for both models	ADM uses FP16 in the U-Net torso with FP32 diffusion states. LDM uses FP32
Seeds and samples	Seeds 2026–2029, four timed images per model after warm-up	Seed 2026, one image per class and model for five shared classes
Outputs analyzed	Sampling time, peak allocation, and visual quality	Final images and saved forward and reverse states

Table 3. Comparison on LSUN Churches under the settings in Table 2. Latency is the median of four images. Peak allocation is PyTorch's peak CUDA tensor allocation.

Criterion	Pixel DDPM	LDM-KL-8
Denoising state	$256 \times 256 \times 3$	$32 \times 32 \times 4$
Latency (s/image)	6.10	2.44
Peak allocation (GiB)	0.75	1.68
Visual quality	Clear steeple in seed 2028. Darker seed 2029 obscures details.	Clear facades in seeds 2027–2029. Seed 2026 shows a distant complex.



Figure 4. All eight timed LSUN Churches samples, grouped by seed. Each model draws its initial noise in its own state space.

produced recognizable church imagery (Figure 4). The sample count, checkpoints, and implementations limit conclusions to the tested pipelines.

5.3. ImageNet samples and denoising trajectories

In the ImageNet run, ADM denoised an RGB state and CompVis denoised a $64 \times 64 \times 3$ latent. Figure 5 shows

all ten outputs for golden retriever, tabby cat, school bus, monarch butterfly, and volcano (Table 2). We assess recognizable class features and coherence of shape.

Reverse sampling starts from a Gaussian draw. At each update the denoiser predicts noise, the sampler estimates the clean state, and that estimate helps compute the next state. At update 25, the clean estimates already show the retriever's head and muzzle, while the updated states still carry visible noise (Figure 6). In a separate forward pass, we start from each model's final state and add Gaussian noise using its schedule. The retriever's features gradually disappear. Appendix F shows both directions for all five labels.

Both bus samples show yellow bodies and rows of windows. The volcano appears as a lava scene in ADM and as a slope with a plume in LDM. The different outputs illustrate variation under the same label. One sample per class and different guidance settings limit the comparison to the examples shown.

5.4. Published evidence on quality and speed

For a quantitative comparison within one task, Rombach et al. [10, Table 6] report 0.26 versus 0.97 samples/s at 256^2 and FID@2k 24.74 versus 15.21 after six epochs for pixel LDM-1 and latent LDM-4 (KL with attention), respectively, in Places inpainting. FID compares generated and reference feature distributions [4]. These figures describe the paper's inpainting setup.

DDPM objective ablation. On unconditional CIFAR-10, Ho et al. [6, Tables 1–2] report training-reference FID of 13.51 for the variational objective and 3.17 for the simplified objective with epsilon prediction and fixed isotropic variance. The reported NLL upper bound changes from 3.70 to 3.75 bits per dimension.




Figure 5. Our ImageNet samples for five shared class labels. The top row uses pixel-space ADM and the bottom row uses latent diffusion.




Figure 6. Inside DDIM update 25 for the golden retriever. Read each row from the noisy input through the predicted noise and clean estimate to the updated state. ADM noise is displayed in RGB. The LDM heatmap shows the root mean square of the guided noise across latent channels. The other LDM panels show decoded states.

5.5. Prompt control, training data, copyright, and bias

Prompt-based control. A text prompt such as *a red bus beside a blue car* specifies objects, attributes, and a spatial relation. Cross-attention supplies the text condition to the denoiser. Classifier-free guidance can strengthen conditioning at the cost of diversity [5, 10]. LSUN generation was unconditional. ImageNet conditioning used class IDs, so our samples show class control only. A prompt-adherence test would check object presence, color binding, and the requested relation over repeated seeds.

Training data. The church checkpoints specialize in church imagery. The ImageNet checkpoints use a fixed class vocabulary. Dataset coverage limits the evidence a model sees for rare subjects and their variations. In text-to-image training, captions also determine which attributes and relations receive language supervision.

Bias. Bianchi et al. [1] found demographic stereotypes in images generated from ordinary prompts. Measuring this effect would require comparable prompts and multiple seeds across groups. Our Colab runs contain no such group comparison.

Copyright and memorization. Carlini et al. [2] extracted memorized training images from diffusion models. This motivates documenting data provenance and checking for close matches to training images. Permissions for training materials and rights in generated outputs are separate questions. The U.S. Copyright Office report discusses training under U.S. copyright law [14].

6. Conclusion

Learning to remove noise enables generation by fitting a sequence of reverse conditional distributions. The 2015 diffusion framework supplies forward Gaussian corruption, learned reverse mean/covariance functions, and variational training against tractable posterior targets. Starting from a new Gaussian draw and composing the reverse transitions then produces an image sample. DDPM retains this construction while fixing variance choices, parameterizing the reverse mean through predicted noise, and simplifying the training objective. Its published ablation supports a sample-quality benefit from that objective choice, distinct from likelihood optimization or fewer sampling steps. The score connection explains the parameterization without adding a separate computational stage.

LDM preserves this denoising principle in a learned representation. The ImageNet traces show recognizable structure emerging in both spaces. In our LSUN Churches run, the latent pipeline had lower sampling latency and higher peak tensor allocation. These measurements apply to the tested checkpoints. Text control and the effects of training data require evaluation beyond class-conditioned image examples.

References

[1] Federico Bianchi, Pratyusha Kalluri, Esin Durmus, Faisal Ladhak, Myra Cheng, Debora Nozza, Tatsunori Hashimoto, Dan Jurafsky, James Zou, and Aylin Caliskan. Easily accessible text-to-image generation amplifies demographic stereotypes at large scale. In *Proceedings of the ACM Conference on Fairness, Accountability, and Transparency*, 2023.

[2] Nicholas Carlini, Jamie Hayes, Milad Nasr, Matthew Jagielski, Vikash Sehwag, Florian Tramèr, Borja Balle, Daphne Ippolito, and Eric Wallace. Extracting training data from diffusion models. In *32nd USENIX Security Symposium*, 2023.

[3] Ian Goodfellow, Jean Pouget-Abadie, Mehdi Mirza, Bing Xu, David Warde-Farley, Sherjil Ozair, Aaron Courville, and Yoshua Bengio. Generative adversarial nets. In *Advances in Neural Information Processing Systems*, 2014.

[4] Martin Heusel, Hubert Ramsauer, Thomas Unterthiner, Bernhard Nessler, and Sepp Hochreiter. GANs trained by a two time-scale update rule converge to a local nash equilibrium. In *Advances in Neural Information Processing Systems*, 2017.

[5] Jonathan Ho and Tim Salimans. Classifier-free diffusion guidance. arXiv:2207.12598, 2022. A short version appeared at a NeurIPS 2021 workshop.

[6] Jonathan Ho, Ajay Jain, and Pieter Abbeel. Denoising diffusion probabilistic models. In *Advances in Neural Information Processing Systems*, pages 6840–6851, 2020.

[7] IEEE. ICCV 2025 Author Kit, 2025. Official author kit; style and bibliography files distributed with the project.

[8] Diederik P. Kingma and Max Welling. Auto-encoding variational bayes. In *International Conference on Learning Representations*, 2014.

[9] OpenAI. Codex, 2026. AI assistance for drafting, LaTeX, code, and source checking; see Appendix B.

[10] Robin Rombach, Andreas Blattmann, Dominik Lorenz, Patrick Esser, and Björn Ommer. High-resolution image synthesis with latent diffusion models. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 2022. arXiv v2, April 2022; includes supplementary material.

[11] Jascha Sohl-Dickstein, Eric Weiss, Niru Maheswaranathan, and Surya Ganguli. Deep unsupervised learning using nonequilibrium thermodynamics. In *Proceedings of the 32nd International Conference on Machine Learning*, pages 2256–2265, 2015.

[12] Jiaming Song, Chenlin Meng, and Stefano Ermon. Denoising diffusion implicit models. In *International Conference on Learning Representations*, 2021.

[13] Yang Song and Stefano Ermon. Generative modeling by estimating gradients of the data distribution. In *Advances in Neural Information Processing Systems*, 2019.

[14] U.S. Copyright Office. Copyright and artificial intelligence, part 3: Generative AI training. Technical report, U.S. Copyright Office, 2025. Pre-publication version; consulted November 5, 2026. A U.S. policy analysis, not a statement of Vietnamese law.

[15] Aäron van den Oord, Nal Kalchbrenner, and Koray Kavukcuoglu. Pixel recurrent neural networks. In *Proceedings of the 33rd International Conference on Machine Learning*, pages 1747–1756, 2016.

[16] Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N. Gomez, Łukasz Kaiser, and Illia Polosukhin. Attention is all you need. In *Advances in Neural Information Processing Systems*, 2017.

[17] Pascal Vincent. A connection between score matching and denoising autoencoders. *Neural Computation*, 23(7):1661–1674, 2011.

A. Requirement-to-Evidence Map

This map concerns the written report. The assignment's separate slide, oral-presentation, balanced-participation, and Q&A requirements require presentation deliverables and cannot be fulfilled by a report alone. The main text occupies pages 1–10; references and appendices are separate.

Table 4. Coverage of the supplied CS420 S06 seminar brief.

Task	Required content	Location / evidence
1	Generative versus discriminative; GAN, autoregressive, diffusion	Sections 2.1, 2.2; Figure 8 (Appendix E)
2	Forward process, beta schedule, Gaussian noise, noise predictor, reverse sampling; both-direction diagram	Section 3; Eqs. (1)–(14); Figure 1
3	Manual 1D forward step, symbols, stochastic expectation	Section 3.7; $x_1 = 0.600833$; conditional mean and variance
4	Small image at five noise levels; optional pretrained demonstration	Section 3.8; Figure 2; Table 1; executable code and arrays. Figures 5 and 6 show pretrained generation
5	VAE encoder/decoder, latent operations, cross-attention, pipeline	Sections 4.2–4.4; Eqs. (16)–(18); Figure 3
6	Speed, quality, prompt control, data, copyright, bias; explicit pixel/latent comparison	Tables 2 and 3; Figure 4; Sections 5.3 and 5.5

Required representations. Equation (1) is the Gaussian forward transition; Eq. (13) is the simplified noise-prediction objective. The worked example gives a complete substitution, result, and interpretation. Appendix C records ranges, units, and modeling assumptions.

Paper reading and synthesis. DDPM's forward/reverse method and contribution are reviewed in Section 3, distinguishing the 2015 foundation from DDPM's parameterization and loss choices. LDM's representation, method, conditioning, contributions, and differences are developed in Section 4. Section 5.4 identifies the published sources for the DDPM objective ablation and LDM inpainting comparison. The report includes Abstract, Introduction, Background/Paper Review, Method/Worked Example, Results and Discussion, Conclusion, and References. English is used according to the commissioning instruction, which overrides the brief's Vietnamese-language request.

B. Reproducibility, Evaluation Protocol, and Attribution

B.1. Reproduce the original illustration

The Overleaf project already contains the generated figure; Python is not needed to compile the report. To regenerate it locally:

```
python -m pip install -r code/requirements.txt
python code/make_figures.py
latexmk -pdf -interaction=nonstopmode -halt-on-
    error main.tex
```

The figure uses a synthetic geometric image, not MNIST or another dataset. The script records the seed, schedule coefficients, library versions, scalar example, and benchmark-ratio arithmetic in `figures/analysis.json`. It saves unclipped frames, timesteps, the schedule, and cumulative coefficients in `noise_arrays.npz`, and summary coefficients in `noise_levels.csv`. The delivered run used NumPy 2.3.5 and ReportLab 4.4.9. The sequence is one sampled Markov path; identical seeds and library versions reproduce it. No image-generation checkpoint is involved.

B.2. Reproduce the Colab runs

The project includes the Colab notebook and run records in `code/colab/`. The notebook records checkpoint URLs and class IDs. The LSUN records contain the individual timings, peak allocation, seeds, and checkpoint hashes. The ImageNet record identifies the checkpoints and guidance settings. The five trajectories in Appendix F are saved outputs of those models. The runs used pretrained weights.

B.3. A proposed prompt and runtime study

Select and record exact checkpoint identifiers, revisions, dataset licenses, hardware, software versions, numerical precision, resolution, and batch size. Keep each fixed within a comparison and record warm-up policy. For latent models, measure text encoding, denoising, decoding, and end-to-end latency separately, and record peak allocated memory over the entire pipeline.

Use paired prompts such as *a red cube to the left of a blue sphere* and *a green cube to the left of a blue sphere*; separately swap the spatial relation. Predefine at least 20 seeds per condition and inspect all samples. Vary sampling steps and guidance in separate sweeps. Report object presence, color binding, relation correctness, and diversity; do not select only attractive examples. This is a proposed evaluation design, not empirical evidence of a model's prompt capability.

B.4. Provenance and AI assistance

Figures 1, 3, and 7 are original TikZ schematics explaining cited methods; no paper figure is reproduced. Figure 2 and Table 1 are generated by the supplied code. Tables 2 and 3 and the Colab figures use the saved run records and outputs. Section 5.4 attributes the published DDPM and LDM values to the original papers. Figure 8 is an illustration included with the project, with method sources in its caption.

The document uses the requested ICCV 2025 author kit [7], with its official style and bibliography files. It uses 10-point type, two columns, and US Letter paper, following the new template request. The author block retains HCMUS and CS420 information and three name/ID placeholders. Template provenance is included in the project.

OpenAI Codex [9] assisted with drafting, equations, code, diagram construction, source checking, and LaTeX preparation. Preparation checks included consulting the original DDPM/LDM equations and DDPM Tables 1–2 and LDM Table 6, recalculating the numerical examples and ratios, and compiling and visually reviewing the PDF. The named student authors should review and accept the final manuscript and replace the author placeholders before submission.

C. Notation, Assumptions, and Additional Derivation

C.1. Ranges and units

Images are normalized and dimensionless. Clean pixels in the illustration lie in $[-1, 1]$; noisy states, latent values, and predicted noise are real-valued and need not stay within that interval. There is no physical time unit in the diffusion index.

Table 5. Notation used in the equations; meanings are also introduced beside the corresponding equations in the main text.

Symbols	Meaning, range, and units
$x_0, x_t, \hat{x}_0$	Clean/noisy/reconstructed image; vector in $\mathbb{R}^D$ or an equivalent image tensor; normalized intensity units
D, H, W, h, w, c, d_z	Positive integer dimensions. $D = 3HW$ for RGB, $d_z = hwc$; H, W count pixels, h, w count latent positions
t, T, j	Integer timestep, terminal step, and product index; $1 \le t \le T$, $1 \le j \le t$
$\beta_t, \alpha_t, \bar{\alpha}_t$	Dimensionless schedule coefficients; $0 < \beta_t < 1$, $\alpha_t = 1 - \beta_t$, $0 < \bar{\alpha}_t \le 1$
$q, p_\theta, p_{\text{data}}$	Fixed forward transition, learned reverse/generative distribution, and data distribution, respectively
$\rho, \tilde{x}, q_\rho, s$	Positive Gaussian perturbation SD, perturbed image, noisy marginal, and score in Appendix C.2; s there is a vector field, distinct from the scalar CFG scale
$K_{2015}, \mathcal{D}_t, C_\beta$	Original log-likelihood lower bound, expected posterior KL, and schedule-dependent entropy terms
$\mathcal{L}_{2015}, L_{\text{VLB}}$	Minimized negative 2015 bound and full DDPM variational negative-log-likelihood bound, in nats
L_T, L_{t-1}, L_0	Expected prior KL, intermediate posterior-to-model KL, and final decoder negative log likelihood, in nats
$w_t, \tilde{\beta}_t, \tilde{\mu}_t$	Positive loss weight; forward-posterior variance and mean, for $t > 1$; see Appendix C.6
$\mathcal{N}(\mu, \Sigma), \mathbf{I}$	Gaussian with mean μ and covariance Σ; identity covariance of the relevant dimension
$\varepsilon, \varepsilon_z, u, \xi$	Independent standard-normal draws in their respective sampling operations; each coordinate has mean 0 and variance 1
Σ_θ	Learned positive diagonal reverse covariance in the 2015 image model; fixed to $\sigma_t^2 \mathbf{I}$ in the DDPM setup discussed
$\sigma_t, \mu_\phi, \sigma_\phi$	Reverse noise standard deviation $\sigma_t \ge 0$; VAE posterior mean and positive standard deviations
$\theta, \phi, \psi, \eta, \omega$	Trainable parameter arrays of denoiser, VAE encoder, decoder, condition encoder, and illustrative classifier
$\tilde{z}, z_0, z_t, f, a$	Raw/clean-scaled/noisy latent; spatial factor $f \ge 1$, with H, W divisible by f; fixed dimensionless scale $a > 0$
$y, \tau_\eta(y), F, C$	Condition, encoded condition, U-Net features, and token embedding matrix. Continuous embeddings are real-valued
n, m, d_u, d_y, d_a, d_v	Positive integer counts and widths for cross-attention; see Appendix D.2 for all matrix shapes
Q, K, V, A, O	Query, key, value, attention-weight, and output matrices; $A_{ij} \in [0, 1]$ and $\sum_j A_{ij} = 1$
$s, w, p_{\text{drop}}, \varnothing$	CFG scale $s \ge 0$, alternative scale $w = s - 1$, dropout probability in $(0, 1)$, and null condition
$K, r, \mathcal{T}$	In the cost model only, K counts updates (not attention keys), r counts evaluations/update, and $\mathcal{T}$ is seconds
$L_{\text{simple}}, L_{\text{LDM}}$	Expected summed squared noise-prediction errors; dimensionless squared normalized-coordinate units
$\mathbb{E}, \|\cdot\|_2, \mathrm{D}_{\text{KL}}$	Expectation, Euclidean norm, and KL divergence; natural logarithms make KL and negative log likelihood use nats

C.2. Optional background: scores and Gaussian perturbation

For a smooth positive density p, define its score as

$$s(x) = \nabla_x \log p(x). \tag{19}$$

This vector gives the direction of steepest local increase in log density, not a scalar image-quality rating. For $p(x) = \mathcal{N}(0,1)$, $\log p(x) = -x^2/2 + C$ and $s(x) = -x$. Score-based sampling combines density-directed drift with randomness. For example, a discretized Langevin update is [13]

$$v^{(k+1)} = v^{(k)} + \frac{\delta}{2} s(v^{(k)}) + \sqrt{\delta}\,\zeta^{(k)}. \tag{20}$$

Here $v^{(k)}$ is the current state, k counts updates, $\delta > 0$ is a step size, and $\zeta^{(k)} \sim \mathcal{N}(0, \mathbf{I})$ are independent draws. The stochastic term supports distributional exploration rather than only mode seeking. Finite-step sampling is approximate; convergence requires suitable step-size limits and regularity conditions. This supplies context for the score-based literature rather than an additional algorithm required by the DDPM construction in the main text.

Gaussian smoothing addresses difficulties in estimating scores when data concentrate near low-dimensional subsets of image space [13]. A simple additive example is

$$\tilde{x} = x_0 + \rho\varepsilon, \quad x_0 \sim p_{\text{data}}, \quad \varepsilon \sim \mathcal{N}(0, \mathbf{I}), \quad \rho > 0. \tag{21}$$

ρ is a noise standard deviation. Its known Gaussian conditional $q_\rho(\tilde{x} \mid x_0) = \mathcal{N}(x_0, \rho^2\mathbf{I})$ has score $-\varepsilon/\rho$. The marginal $q_\rho(\tilde{x})$ averages over clean data; learning its score requires the conditional-to-marginal identity below. Different noise levels define different smoothed distributions. DDPM instead scales the clean signal as well, as in Eq. (2).

C.3. Why the forward marginal is available in closed form

Assume independent standard-normal innovations $\varepsilon^{(1)}, \varepsilon^{(2)}$ and let x_0 be fixed. Applying Eq. (1) twice gives

$$\begin{aligned} x_1 &= \sqrt{\alpha_1}x_0 + \sqrt{\beta_1}\varepsilon^{(1)}, \\ x_2 &= \sqrt{\alpha_2\alpha_1}x_0 + \sqrt{\alpha_2\beta_1}\varepsilon^{(1)} + \sqrt{\beta_2}\varepsilon^{(2)}. \end{aligned}$$

The two independent noise terms have total variance $\alpha_2\beta_1 + \beta_2 = \alpha_2(1-\alpha_1) + (1-\alpha_2) = 1 - \alpha_2\alpha_1$. A sum of independent Gaussians is Gaussian. Repeating this argument yields Eq. (2), with mean $\sqrt{\bar{\alpha}_t}x_0$ and covariance $(1-\bar{\alpha}_t)\mathbf{I}$ [6].

Gaussian innovations are independent across coordinates and steps, but the noisy images themselves have correlations inherited from x_0. When $\bar{\alpha}_T$ is close to zero, dependence on the starting image is weak and a standard-normal starting prior is a useful approximation. A finite schedule need not make it exactly equal to that prior. The learned Gaussian reverse transition is a modeling approximation motivated by small forward steps; no finite network is assumed to know the exact reverse conditional.

C.4. Denoising score matching and the MSE optimum

Fix a nonzero noise level and write $x_t = a_t x_0 + b_t\varepsilon$ with $a_t, b_t > 0$, $\varepsilon \sim \mathcal{N}(0, \mathbf{I})$ independent of x_0. The additive example of Appendix C.2 uses $a_t = 1, b_t = \rho$; DDPM uses $a_t = \sqrt{\bar{\alpha}_t}$ and $b_t = \sqrt{1-\bar{\alpha}_t}$. These a_t coefficients are unrelated to the fixed latent scale a. Let q_t be the marginal over noisy data. Gaussian smoothing makes it positive and smooth; assume sufficient integrability to exchange integration and differentiation. Then

$$\begin{aligned} q_t(x_t) &= \int p_{\text{data}}(x_0) q(x_t \mid x_0)\, dx_0, \\ \nabla \log q_t(x_t) &= \int q(x_0 \mid x_t, t) \nabla \log q(x_t \mid x_0)\, dx_0. \end{aligned} \tag{22}$$

The conditional Gaussian has score

$$\nabla \log q(x_t \mid x_0) = -\frac{x_t - a_t x_0}{b_t^2} = -\frac{\varepsilon}{b_t}. \tag{23}$$

Taking its posterior expectation in Eq. (22) gives

$$\nabla \log q_t(x_t) = -\frac{\mathbb{E}[\varepsilon \mid x_t, t]}{b_t}. \tag{24}$$

This is the conditional-to-marginal identity underlying denoising score matching [13, 17].

For any vector-valued predictor g and finite second-moment target Y, condition on an input X. With $m(X) = \mathbb{E}[Y \mid X]$, expand

$$\begin{aligned} \mathbb{E}[\|Y - g(X)\|^2 \mid X] = \mathbb{E}[\|Y - m(X)\|^2 \mid X] \\ + \|m(X) - g(X)\|^2. \end{aligned} \tag{25}$$

The cross term vanishes because $\mathbb{E}[Y - m(X) \mid X] = 0$. Thus the ideal MSE predictor is $m(X)$. Setting $Y = \varepsilon$ and $X = (x_t, t)$ justifies the interpretation in Section 3.6. A finite trained network only approximates that optimum.

If $\varepsilon_\theta = -b_t s_\theta$, a conditional-target score loss satisfies

$$\mathbb{E}\|s_\theta + \varepsilon/b_t\|^2 = \frac{1}{b_t^2}\mathbb{E}\|\varepsilon - \varepsilon_\theta\|^2 \tag{26}$$

at a fixed t. Across timesteps, weights must be accounted for: unweighted noise MSE corresponds to weighting this score loss by b_t^2. The two unweighted losses should not be identified without that factor. The identity is used only for $b_t > 0$, not at the clean endpoint.

C.5. The original 2015 bound and learned covariance

For a Gaussian diffusion model, the general trajectory lower bound is

$$\mathbb{E}[\log p_\theta(x_0)] \geq \mathbb{E}_q[\log p_\theta(x_{0:T}) - \log q(x_{1:T} \mid x_0)]. \tag{27}$$

Sohl-Dickstein et al. [11, Sec. 2.4, App. B] rewrite this, under their normalization and stationary-kernel endpoint conventions, as

$$\begin{aligned} K_{2015} &= -\sum_{t=2}^{T} \mathcal{D}_t + C_\beta, \\ \mathcal{D}_t &= \mathbb{E}_q\left[\mathrm{D}_{\mathrm{KL}}\left(q(x_{t-1} \mid x_t, x_0) \| p_\theta(x_{t-1} \mid x_t)\right)\right], \\ C_\beta &= H_q(X_T \mid X_0) - H_q(X_1 \mid X_0) - H_\pi(X_T). \end{aligned} \tag{28}$$

H denotes differential entropy in nats and $\pi = \mathcal{N}(0, \mathbf{I})$. The stationary-prior cross-entropy simplification uses the paper's normalization of the data. For the isotropic Gaussian forward chain, $H_q(X_t \mid X_0) = \frac{D}{2}\log[2\pi e(1-\bar{\alpha}_t)]$. These terms depend on the schedule; treating C_β as constant is valid with respect to reverse parameters at a fixed schedule, not when optimizing the forward rates.

In particular, the 2015 endpoint is prescribed as

$$p(x_0 \mid x_1) = T_\pi(x_0 \mid x_1; \beta_1) = \mathcal{N}(\sqrt{1-\beta_1}x_1, \beta_1\mathbf{I}), \tag{29}$$

where T_π is the stationary Gaussian kernel. This removes the learned endpoint term from its KL sum. It should not be confused with DDPM's endpoint likelihood convention or its final noiseless display update.

For $q = \mathcal{N}(\tilde{\mu}_t, \tilde{\beta}_t\mathbf{I})$ and learned diagonal $p_\theta = \mathcal{N}(\mu_\theta, \mathrm{diag}(v_{\theta,1}, \ldots, v_{\theta,D}))$, with $v_{\theta,i} > 0$, the per-example KL is

$$\begin{aligned} \mathrm{D}_{\mathrm{KL}}(q\|p_\theta) = \frac{1}{2}\sum_{i=1}^{D}\Bigg[&\log\frac{v_{\theta,i}}{\tilde{\beta}_t} - 1 \\ &+ \frac{\tilde{\beta}_t + (\tilde{\mu}_{t,i} - \mu_{\theta,i})^2}{v_{\theta,i}}\Bigg]. \end{aligned} \tag{30}$$

Learning covariance therefore changes more than a mean-MSE target. Only after fixing reverse variance do the variance-dependent pieces become constant in θ, giving the mean-MSE expression used in DDPM's parameterization argument. The explicit Gaussian posterior parameters are given next.

C.6. From the variational bound to weighted noise MSE

DDPM retains the joint generator and Gaussian forward construction with a fixed schedule [6, Secs. 2–3]:

$$\begin{aligned} p_\theta(x_{0:T}) &= p(x_T)\prod_{t=1}^{T} p_\theta(x_{t-1} \mid x_t), \\ q(x_{1:T} \mid x_0) &= \prod_{t=1}^{T} q(x_t \mid x_{t-1}). \end{aligned} \tag{31}$$

Jensen's inequality bounds negative log likelihood by $L = \mathbb{E}_q[\log q(x_{1:T} \mid x_0) - \log p_\theta(x_{0:T})]$. Here L is the L_{VLB} introduced in Eq. (8). Rearranging gives

$$\begin{aligned} L = \mathbb{E}\Bigg[&\mathrm{D}_{\mathrm{KL}}(q(x_T \mid x_0)\|p(x_T)) \\ &+ \sum_{t=2}^{T}\mathrm{D}_{\mathrm{KL}}\left(q(x_{t-1} \mid x_t, x_0)\|p_\theta(x_{t-1} \mid x_t)\right) \\ &- \log p_\theta(x_0 \mid x_1)\Bigg]. \end{aligned} \tag{32}$$

The terminal term is fixed when the schedule and prior are fixed. The endpoint term is a reconstruction/decoder likelihood; DDPM's original implementation uses a discretized decoder for image integers. It is not simply another intermediate Gaussian KL.

For $t > 1$, conditioning on x_0 yields a Gaussian posterior with

$$\begin{aligned} \tilde{\beta}_t &= \frac{1-\bar{\alpha}_{t-1}}{1-\bar{\alpha}_t}\beta_t, \\ \tilde{\mu}_t &= \frac{\sqrt{\bar{\alpha}_{t-1}}\beta_t}{1-\bar{\alpha}_t}x_0 + \frac{\sqrt{\alpha_t}(1-\bar{\alpha}_{t-1})}{1-\bar{\alpha}_t}x_t. \end{aligned} \tag{33}$$

With fixed reverse variance $\sigma_t^2 > 0$, the Gaussian KL is $\mathbb{E}[\|\tilde{\mu}_t - \mu_\theta\|^2/(2\sigma_t^2)] + C$. Substituting $x_0 = (x_t - \sqrt{1-\bar{\alpha}_t}\varepsilon)/\sqrt{\bar{\alpha}_t}$ gives

$$\tilde{\mu}_t = \frac{1}{\sqrt{\alpha_t}}\left(x_t - \frac{\beta_t}{\sqrt{1-\bar{\alpha}_t}}\varepsilon\right). \tag{34}$$

Replacing ε by ε_θ defines the model mean in Eq. (10); subtracting the two means gives

$$w_t = \frac{\beta_t^2}{2\sigma_t^2\alpha_t(1-\bar{\alpha}_t)}. \tag{35}$$

These are DDPM's Eqs. 8–12. The simplified objective omits this coefficient for intermediate steps; its $t = 1$ term is related to the endpoint decoder using the approximation explained in DDPM Section 3.4. Consequently L_{simple} is a reweighted surrogate, not numerically the original variational bound. The CIFAR-10 results in Section 5.4 empirically motivate that change.

C.7. Why the score determines the reverse mean

Apply the marginal-score identity to a single Gaussian forward step:

$$\nabla \log q_t(x_t) = -\frac{x_t - \sqrt{\alpha_t}\mathbb{E}[x_{t-1} \mid x_t, t]}{\beta_t}. \tag{36}$$

Therefore its true reverse conditional mean is

$$\mathbb{E}[x_{t-1} \mid x_t, t] = \frac{x_t + \beta_t \nabla \log q_t(x_t)}{\sqrt{\alpha_t}}. \tag{37}$$

Using the estimated DDPM score $-\varepsilon_\theta(x_t, t)/\sqrt{1-\bar{\alpha}_t}$ gives the reverse mean in Eq. (10). The conditional-mean identity is exact under the stated assumptions, but it does not make the full reverse conditional Gaussian. Its higher moments and possible multimodality are not specified by the mean alone. DDPM uses a Gaussian approximation motivated by small forward steps and learns an approximate score.

C.8. Why noise prediction is useful without knowing the true noise

For a fixed x_t and t, the vector minimizing expected squared prediction error is $\mathbb{E}[\varepsilon \mid x_t, t]$ (and, in a conditional model, $\mathbb{E}[\varepsilon \mid x_t, t, y]$). Thus a trained predictor estimates a statistical direction shared by plausible clean examples, not an oracle that recovers every random draw. Its corresponding clean-state estimate is

$$\hat{x}_0(x_t, t) = \frac{x_t - \sqrt{1-\bar{\alpha}_t}\varepsilon_\theta(x_t, t)}{\sqrt{\bar{\alpha}_t}}. \tag{38}$$

This follows by rearranging Eq. (2); prediction errors remain and can be magnified at small $\bar{\alpha}_t$. The reverse sampler uses predictions over many levels rather than treating one estimate as guaranteed recovery. The same argument applies in latent space, followed by the learned decoder.

C.9. Two training stages and their different roles

Stage one updates encoder ϕ and decoder ψ to preserve useful image information in a regularized representation. Stage two fixes them and trains denoiser θ with Eq. (18). The original LDM conditional formulation jointly optimizes the condition encoder and denoiser [10, Sec. 3.3]; particular later implementations may instead keep the text encoder fixed.

The distinction matters: improving the denoiser cannot guarantee exact recovery of details that the first stage systematically discards. Conversely, a high-quality autoencoder does not itself provide the conditional latent distribution needed for generation. The VAE prior regularizer and the learned diffusion prior play different roles.

D. Supporting Autoencoder and Conditioning Details




Figure 7. Original single-head cross-attention schematic, based on [10, 16]. Multi-head attention learns several such projections and combines their outputs.

D.1. Textbook VAE objective and the LDM distinction

A textbook negative evidence lower bound for a VAE is [8]

$$\begin{aligned}\mathcal{J}_{\mathrm{VAE}} = \mathbb{E}_{q_\phi(\tilde{z}|x_0)}[-\log p_\psi(x_0 \mid \tilde{z})] \\ + \mathrm{D}_{\mathrm{KL}}(q_\phi(\tilde{z} \mid x_0)\|\mathcal{N}(0, \mathbf{I}))\,.\end{aligned} \tag{39}$$

The decoder likelihood $p_\psi(x_0 \mid \tilde{z})$ rewards reconstruction; the nonnegative KL term regularizes the approximate posterior toward the prior. Natural logarithms give nats. This explains the VAE interpretation, but LDM's perceptual/adversarial first-stage objective with weak KL regularization is not identical to this pixel-likelihood objective [10, Sec. 3.1].

D.2. Cross-attention: how language reaches the denoiser

Use a *row-vector* convention. At one U-Net layer, flatten its feature map into $F \in \mathbb{R}^{n\times d_u}$, where n is the number of spatial positions and d_u is its channel width. Let $C = \tau_\eta(y) \in \mathbb{R}^{m\times d_y}$ contain m token embeddings of width d_y. One cross-attention head computes [10, 16]

$$Q = FW_Q, \quad K = CW_K, \quad V = CW_V, \tag{40}$$

$$A = \mathrm{softmax}\left(\frac{QK^\top}{\sqrt{d_a}}\right), \qquad O = AV. \tag{41}$$

The learned projections have shapes $W_Q \in \mathbb{R}^{d_u\times d_a}$, $W_K \in \mathbb{R}^{d_y\times d_a}$, and $W_V \in \mathbb{R}^{d_y\times d_v}$. Thus $Q \in \mathbb{R}^{n\times d_a}$ contains *queries from image features*, $K \in \mathbb{R}^{m\times d_a}$ contains *keys from text*, and $V \in \mathbb{R}^{m\times d_v}$ contains text values. d_a, d_v are positive integer head widths. A superscript $\top$ denotes transposition. Softmax acts across the m tokens for each spatial row, making $A \in \mathbb{R}^{n\times m}$ nonnegative with row sums of one. $O \in \mathbb{R}^{n\times d_v}$ supplies text-dependent features that are projected back into the U-Net's residual stream.

A numerical attention example

Take one spatial query $Q = (1, 0)$, two keys $K_1 = (\sqrt{2}, 0)$, $K_2 = (0, 0)$, and $d_a = d_v = 2$. The scaled logits are $(1, 0)$, so $A = (e/(e + 1), 1/(e + 1)) \approx (0.7311, 0.2689)$, where e is Euler's number. For $V_1 = (1, 0)$ and $V_2 = (0, 1)$, the output is $O \approx (0.7311, 0.2689)$. This original toy example shows weighted retrieval, not an observed attention map from an actual model.

D.3. Prompt control and classifier-free guidance

Cross-attention supplies the condition; *classifier-free guidance* (CFG) adjusts how strongly a conditional prediction influences sampling [5]. Train the same network with the condition replaced by a null condition $\varnothing$ with probability $p_{\mathrm{drop}} \in (0, 1)$. At inference define

$$\begin{aligned}\varepsilon_u &= \varepsilon_\theta(z_t, t, \tau_\eta(\varnothing)), \\ \varepsilon_c &= \varepsilon_\theta(z_t, t, \tau_\eta(y)), \\ \varepsilon_{\mathrm{cfg}} &= \varepsilon_u + s(\varepsilon_c - \varepsilon_u).\end{aligned} \tag{42}$$

$s \geq 0$ is a dimensionless guidance scale. Here $s = 0$ uses the unconditional prediction, $s = 1$ gives ordinary conditional sampling, and $s > 1$ extrapolates in the conditional direction. The CFG paper writes the equivalent expression $(1 + w)\varepsilon_c - w\varepsilon_u$; its parameter is $w = s - 1$. Stating the convention prevents confusing two scales with different numerical baselines.

For an original scalar illustration, $\varepsilon_u = 0.2$, $\varepsilon_c = 0.1$ and $s = 3$ give $\varepsilon_{\mathrm{cfg}} = -0.1$. Guidance is therefore an extrapolation, not a convex average. Substituting it into the reverse update changes the generation trajectory. Greater guidance can improve conditional fidelity while reducing diversity; it does not ensure monotonically better quality [5]. Standard CFG requires two denoiser evaluations per step, often batched together, adding compute and potentially peak memory.

For a proposed prompt-control experiment, including fixed seeds and separate attribute/relation changes, see Appendix B.

E. Qualitative Comparison of Generative Models




Figure 8. Overview of GAN, autoregressive, and diffusion models. Related methods are described in [3, 6, 15]. The labels describe typical behavior rather than universal performance guarantees.

F. ImageNet Forward and Reverse Trajectories

Each panel follows one class for both models. Read each reverse row from the initial noise through updates $10, 20, 30, 40$ to the final image at update 50. Each forward row starts from that final state and shows noising at $t = 0, 50, 150, 300, 600, 1000$. ADM states are in pixel space. LDM states are decoded from latent space for display.




Figure 9. Golden retriever (ImageNet class 207).




Figure 10. Tabby cat (ImageNet class 281).




Figure 11. School bus (ImageNet class 779).




Figure 12. Monarch butterfly (ImageNet class 323).




Figure 13. Volcano (ImageNet class 980).