

Roadmap

C:

```
car *c = malloc(sizeof(car));
c->miles = 100;
c->gals = 17;
float mpg = get_mpg(c);
free(c);
```

Java:

```
Car c = new Car();
c.setMiles(100);
c.setGals(17);
float mpg =
    c.getMPG();
```


Assembly
language:

```
get_mpg:
    pushq    %rbp
    movq     %rsp, %rbp
    ...
    popq     %rbp
    ret
```

Machine
code:

```
0111010000011000
100011010000010000000010
1000100111000010
110000011111101000011111
```

Computer
system:



Processes

Memory & data
Integers & floats
Machine code & C
x86 assembly
Procedures & stacks
Arrays & structs
Memory & caches
Processes
Virtual memory
Memory allocation
Java vs. C

OS:



Section 8: Processes

- What is a process
- Creating processes
- Fork-Exec

What is a process?


- Why are we learning about processes?
 - Processes are another *abstraction* in our computer system – the process abstraction provides an *interface* between the program and the underlying CPU + memory.
- What do processes have to do with exceptional control flow?
 - Exceptional control flow is the mechanism that the OS uses to enable multiple processes to run on the same system.
- What is a program? A processor? A process?

Processes

- **Definition: A *process* is an instance of a running program**
 - One of the most important ideas in computer science
 - Not the same as “program” or “processor”
- **Process provides each program with *two key abstractions*:**
 - Logical control flow
 - Each process seems to have exclusive use of the CPU
 - Private virtual address space
 - Each process seems to have exclusive use of main memory
- **Why are these illusions important?**
- **How are these illusions maintained?**
 - Process executions interleaved (multi-tasking)
 - Address spaces managed by virtual memory system – next course topic


Concurrent Processes

- Two processes *run concurrently* (are concurrent) if their instruction executions (flows) overlap in time
- Otherwise, they are *sequential*
- Examples:
 - Concurrent: A & B, A & C
 - Sequential: B & C



User View of Concurrent Processes

- Control flows for concurrent processes are physically disjoint in time
 - CPU only executes instructions for one process at a time
- However, we can think of concurrent processes as executing in parallel



Context Switching

- Processes are managed by a shared chunk of OS code called the *kernel*
 - Important: the kernel is not a separate process, but rather runs as part of a user process
- Control flow passes from one process to another via a *context switch*... (how?)

