From Grokking to Micro-Routing: Graph Neural Cellular Automata for Sub-Millisecond Agent Tool Selection

Julian M. Kleber
Independent Researcher
julian.m.kleber@gmail.com

October 2026

Abstract

Selecting which tool to invoke in an autonomous agent is a micro-routing decision, yet current harnesses dispatch every turn through multi-billion-parameter LLMs. We introduce **Graph Neural Cellular Automata (GNCA)**, a 35.3k–59.2k parameter System-1 reflex router that selects tools via recurrent message passing on a relational trace graph. In **Lean 4**, we machine-check nine formal theorems certifying discrete topologies, continuous trained recurrence operators, and algorithmic simulation duality with zero axioms, including star-vs-chain diameter separation ($O(1)$ vs $\Omega(V)$), continuous row-softmax convex boundedness, trained damped recurrence dyadic contraction, and a simulation-and-compression duality proving that K cellular steps on a tree graph exact-simulate any depth-K binary decision tree while compressing parameters by 307× relative to the 18.2M-parameter Hermes Random Forest. GNCA executes batch-1 CPU forward passes in **0.35**–**0.66** ms (42.1 ms decode latency for local LLMs). Across four 3-seed benchmarks on unified CUDA hardware, GNCA achieves $\mathbf{87.09 \pm 1.57}$% test top-1 on **API-Bank** (outperforming API-Bank Random Forest at 80.13 ± 0.55%, $p = 0.0002$, and HistGradientBoosting at 84.75 ± 0.59%, $p = 0.0036$), $\mathbf{76.30 \pm 1.85}$% test top-1 on **ToolBench** (vs 74.33 ± 1.12% ToolBench Random Forest), and $\mathbf{76.83 \pm 0.60}$% test top-1 on **BFCL v4** (vs 74.18 ± 0.96% BFCL Random Forest, $p = 0.0022$). On **Hermes** (3,530 test turns), 10k-step class-weighted GNCA trades top-1 (64.64%–66.19% curated test top-1) for 2.15× higher rare-tool macro-F1 (0.608 vs 0.283), while unweighted label-smoothed Tree GNCA reaches 67.37% curated test top-1 at 10k steps, 68.07% curated test top-1 over a 200k grokking progression, and $\mathbf{68.92 \pm 0.47}$% curated test top-1 across 3 seeds vs 67.88% curated test top-1 for Random Forest and 69.47% curated test top-1 for HistGradientBoosting.

1. Introduction

Autonomous software agents operate as iterative closed-loop systems: observing environment feedback (compiler diagnostics, file diffs, test logs) and synthesizing next actions. In biological nervous systems, routine motor actions do not require deliberative processing in the cerebral cortex; a low-level reflex arc in the spinal cord coordinates rapid responses in milliseconds. In contrast, modern AI agents dispatch every mundane operation through massive, multi-billion-parameter autoregressive models. This design causes critical bottlenecks:

1. **Latency and Memory Pressure.** Generating tokens sequentially causes high latency and heavy memory traffic, slowing down agent loops.
2. **Context Window Bloat.** Intermediate steps fill context windows with repetitive JSON schema and syntax clutter.
3. **Rigid 1D Assumptions.** Prior cellular models restrict computation to 1D lattices. Signals crawl one step at a time like a game of telephone, ignoring that agent execution traces form hierarchical trees.

Neural Cellular Automata (NCAs) [1] offer an alternative computational paradigm based on local, self-organizing update rules. Historically, NCAs were studied in continuous 2D grids for biological morphogenesis, texture generation, and self-repair. However, their core inductive biases (iterative spatial message passing across discrete cells governed by uniform update rules) align naturally with structured sequential decision processes. Like biological cells communicating with their immediate neighbors to form complex tissues, NCA cells update their local states in parallel without global bottlenecking. Recent investigations (e.g., Mittal et al. [5]) probed token-level text NCAs, but their application to structured multi-action tool execution has remained limited to rigid sequential chains.

Contributions. In this paper, I extend Neural Cellular Automata beyond 1D topologies into a graph framework for hierarchical agent routing (fixed star and tree topologies plus optional continuous architecture search). My core contributions are fourfold.

- **Multi-Benchmark Graph Cellular Routing.** I formulate GNCA, replacing 1D convolutional stencils with relational graph message passing across a 59.2k-parameter cellular update rule (307× smaller than an 18.2M-parameter Hermes Random Forest). Across four multi-seed benchmarks, GNCA achieves $\mathbf{87.09 \pm 1.57}$% test top-1 on **API-Bank** (+6.97 pp over API-Bank Random Forest, $p = 0.0002$;

+2.35 pp over HistGradientBoosting, $p = 0.0036$), $\mathbf{76.30 \pm 1.85}\%$ test top-1 on **ToolBench** (+1.98 pp over ToolBench Random Forest), $\mathbf{76.83 \pm 0.60}\%$ test top-1 on **BFCL v4** (+2.65 pp over BFCL Random Forest, $p = 0.0022$), and $\mathbf{68.92 \pm 0.47}\%$ curated test top-1 in 3-seed unweighted label-smoothed evaluation on **Hermes** (68.07% curated test top-1 over the 200k grokking schedule; 66.19% curated test top-1 and 2.15× higher rare-tool macro-F1 under 10k class weighting).

- **Machine-Checked Proofs of Topologies and Trained Continuous Operators.** In Lean 4, I formally verify nine theorems certifying discrete structural topologies, continuous trained recurrence operators, and algorithmic duality with zero unproven axioms (1D lattice subsumption, tree subsumption, permutation equivariance, star-vs-chain diameter separation $O(1)$ vs $\Omega(V)$, decision-tree simulation duality, trained damped recurrence dyadic contraction, continuous row-softmax convex boundedness, and top-k discretization spanning preservation). I complement these formal proofs with an empirical bridge measuring 76.63% partition agreement ($\kappa = 0.5628$) between the trained sigmoidal GNCA and binary decision trees on 3,530 held-out Hermes test turns, and a 3-seed spectrally normalized contractive training study verifying dyadic contraction ($\rho = 0.427 < 0.50$) on 100% of test turns.
- **Dual-System Architecture & Calibrated Risk-Coverage Routing.** I introduce a System-1/System-2 agent harness with risk-gated dynamic schema pruning, combining normalized prediction entropy with the node-mean root-mean-square cellular step norm. Across 3,530 held-out test turns (3 seeds), the composite uncertainty score achieves 0.730 ± 0.008 error-detection AUROC and increases retained System-1 accuracy from 69.10% to 90.48% along the selective risk-coverage frontier.
- **Multi-Seed Factorial Ablations & Controlled Router Diagnostics.** I conduct a 3-seed factorial ablation on unified CUDA hardware isolating recurrence depth $K \in \{2, 4, 8\}$, loss weighting (class-weighted vs label-smoothed), topology, cross-turn carry, and dynamic halting, alongside matched-actuator router ablations on $N = 692$ BFCL v4 test turns and exploratory end-to-end pilot diagnostics.

2. Related Work

Neural Cellular Automata and Reasoning. Mordvintsev et al. [1] introduced Growing Neural Cellular Automata, demonstrating self-organizing pattern morphogenesis and damage recovery. Subsequent work extended NCAs to multi-scale hierarchical structures [2] and decentralized algorithmic reasoning [4]. Grattarola et al. [3] introduced Learning Graph Cellular Automata (LGCA), showing that GNNs can execute cellular update rules over fixed, predefined graphs (e.g., Voronoi meshes). In language representation, Mittal et al. [5] and Lee et al. [6] demonstrated that cellular rules can learn 1D token representations.

Technical Differentiation from LGCA and Message-Passing GNNs. While LGCA [3] demonstrated that graph neural networks can execute cellular transition rules over fixed spatial meshes, GNCA departs along four technical axes:

1. **Relational Trace Graphs vs. Geometric Meshes:** LGCA operates on physical or coordinate-based meshes with static connectivity. GNCA formulates agent micro-routing over dynamic dialogue traces with heterogeneous functional roles ($V = 5$ cells): goal hub (node 0), conversation history trace ($1 \le i \le 3$), and tool outcome leaf (node 4), discovered through continuous DARTS bilevel optimization.
2. **Weight Tying & Tree Simulation Duality:** Multi-layer GNNs parameterize L independent weight matrices $W^{(l)}$ ($O(L \cdot d^2)$ parameters) and frequently suffer from oversmoothing and oversquashing. In contrast, GNCA ties a single cellular transition operator across all steps K, implementing an algorithmic duality that exact-simulates depth-K binary decision trees while compressing parameter storage by 307× to 59.2k parameters (Theorems 5 and 6).
3. **Machine-Checked Dynamical Guarantees in Lean 4:** LGCA provides no formal convergence bounds on internal states. Under 1-Lipschitz spectral normalization and convex damping, GNCA proves in Lean 4 that continuous damped updates satisfy dyadic contraction ($2 \cdot d(T(x), T(y)) \le d(x, y)$, Theorem 7) and row-stochastic softmax boundedness (Theorem 8), certifying exponential perturbation decay on the deployed router.
4. **System-1 Reflex Routing & Selective Escalation:** Unlike generative spatial synthesis, GNCA solves high-frequency, sub-millisecond agent tool dispatch (0.35–0.66 ms) paired with a calibrated step-norm and entropy risk score (s_{esc}) for selective escalation to System-2 LLM deliberation.

Tool Calling, Agent Harnesses, and Pre-Routing. Tool use in autonomous systems is evaluated on benchmarks like the Berkeley Function Calling Leaderboard (BFCL) [7] and SWE-bench. Production agent harnesses execute many typed System-1 decisions per task [10]. Singla et al. [9] showed that pre-inference action routing cuts prompt latency and token overhead by half. Expanding on these findings, real agents must handle three coupled tasks, namely detecting irrelevance to abstain gracefully, binding argument slots to workspace entities, and coordinating multi-turn plans.

Architecture Meta-Learning & Graph Bottlenecks. Standard GNNs frequently suffer from *oversmoothing* (representations collapsing to uniformity with

depth), *oversquashing* (information bottlenecking from high-degree neighborhoods), and *underreaching* (insufficient message passing depth to bridge distant nodes). By casting topology selection as bilevel architecture meta-learning (optional) or fixed star/tree wiring, the framework targets sparse relational graphs that balance local message passing with long-range goal broadcasting.

3. Task Formulation & Architecture

3.1. Real-World Operational Context & Action Formulation

In real-world software engineering agents (e.g., executing in IDE or terminal sandboxes), selecting the next action is not an isolated token prediction problem over a flat prompt. Instead, the agent operates in an interactive closed loop situated within an operational context state $\mathbf{s}_t$.

$$\mathbf{s}_t = (\mathbf{g}_{\text{intent}},\ \mathbf{w}_{\text{env}},\ \tau_{\text{hist}},\ \mathcal{T}_{\text{reg}}) \in \mathcal{X}_{\text{ctx}} \tag{1}$$

The four context channels capture the heterogeneous dependencies of practical workflows.

1. **High-Level Intent ($\mathbf{g}_{\text{intent}}$).** The user goal, issue specification, or immediate task turn defining the overarching objective.
2. **Workspace & Environment State ($\mathbf{w}_{\text{env}}$).** File paths, working directory depth, git branch/clean status, compiler and test exit codes, and runtime error diagnostics.
3. **Causal Trajectory History (τ_{hist}).** Chronological sequence of prior tool calls and execution feedback $\tau_{\text{hist}} = \{(u_{t-k}, r_{t-k})\}_{k=1}^{L-1}$ over an L-step causal window. Here $u_{t-k} \in \mathcal{V}$ is the invoked tool and r_{t-k} contains execution diagnostics (output length, error flag, stdout/stderr status).
4. **Tool Registry & Schema Constraints ($\mathcal{T}_{\text{reg}}$).** Candidate tool signatures $|\mathcal{V}|$, argument constraints, and permission boundaries (read-only introspection vs state-mutating shell execution).

From this context $\mathbf{s}_t$, the agent synthesizes a four-part action tuple.

$$\mathbf{a}_t = (y_{\text{tool}},\ \mathbf{y}_{\text{arg}},\ g_{\text{abstain}},\ s_{\text{esc}}) \tag{2}$$

Here $y_{\text{tool}} \in \mathcal{V}$ is the discrete tool identifier chosen from vocabulary $|\mathcal{V}| = 13$ (e.g., file reading, file editing, shell command execution, directory listing, and conversational response). The vector $\mathbf{y}_{\text{arg}} \in \mathcal{A}$ predicts structured argument slots mapping workspace entities. The calibrated scalar gate $g_{\text{abstain}} \in [0, 1]$ indicates whether the agent should abstain from external tool execution. Finally, $s_{\text{esc}} \in [0, 2]$ provides a predictive execution risk score governing System-2 LLM fallback when $s_{\text{esc}} > \theta_{\text{esc}}$.

3.2. Beyond 1D: Graph Neural Cellular Automata

Standard 1D NCAs constrain message passing strictly to immediate sequence neighbors $\{i-1, i, i+1\}$, forcing contextual signals to crawl sequentially across $\Omega(V)$ steps. In agent workflows, however, the root goal and environmental diagnostics must directly modulate every historical turn, while recursive tool subtrees branch hierarchically.

Topology of Employed Algorithms. Figure 1 illustrates the spatial information-flow topology of each algorithm evaluated in this work. In 1D lattices (Figure 1a), messages crawl along a chain, creating an information bottleneck where the goal cell at index 0 requires $V-1 = 4$ cellular steps to reach the most recent action turn $t-1$. In contrast, Star GNCA (Figure 1b) introduces a centralized broadcast hub, collapsing the goal-to-cell diameter to 1 hop for all nodes. Tree GNCA (Figure 1c) organizes the causal history into a hierarchical call-tree DAG where recent execution turns $(t-2, t-1)$ are siblings subordinate to earlier subtask actions $(t-4)$, reflecting the branching structure of real agent execution trees. Meta-Learned GNCA (Figure 1d) treats edge weights as continuous differentiable parameters $\alpha \in \mathbb{R}^{5\times5}$, converging to a sparse directed tree backbone. In comparison, non-cellular baselines lack spatial recurrence: the Flat MLP (Figure 1e) flattens all cells into a monolithic 730-dimensional vector, while Random Forest (Figure 1f) and HistGradientBoosting (Figure 1g) fit large ensembles of independent decision trees. As summarized in the hop-distance matrix (Figure 1h), Star and Tree topologies ensure rapid goal signal propagation across all cells within 1–2 steps, enabling the weight-tied cellular rule to synthesize global context without parameter bloat.

I map the operational context $\mathbf{s}_t$ to an expressive relational graph $\mathcal{G} = (\mathcal{V}_{\text{graph}}, \mathcal{E}, A)$ with $|\mathcal{V}_{\text{graph}}| = V = 5$ nodes over a causal window $L = 5$.

- **Node 0 (Intent & Environment Hub).** Anchors the global intent $\mathbf{g}_{\text{intent}}$ concatenated with workspace diagnostic scalars $\mathbf{w}_{\text{env}}$.
- **Nodes $1 \dots 4$ (Causal Trajectory Cells).** Chronological execution turns (u_{t-k}, r_{t-k}), capturing both the historical operation and runtime feedback.

Each node maintains a compact 16-number scratchpad ($h_i^{(t)} \in \mathbb{R}^{16}$, initialized to $\mathbf{0}$). Across $K = 4$ fast recurrence cycles, nodes exchange state updates over the graph topology to reach rapid consensus without global matrix bottlenecking.

Continuous Spatial Perception. Let $A \in \mathbb{R}^{V\times V}$ denote a **row-stochastic** adjacency ($A_{ij} \geq 0$, $\sum_{j=1}^{V} A_{ij} = 1$ for all i). Adjacency A can be fixed or continuously parameterized via row-wise softmax(α/τ). Each cell carries a concatenated observation-hidden vector $x_i^{(t)} \in \mathbb{R}^C$ with $C = D + H$, where hidden width H=16. Stacking $x_i^{(t)}$ yields observation matrix $x^{(t)} \in \mathbb{R}^{V\times C}$. Neighbor aggregation is a left multiply by A for low-pass consensus.

$$\bar{x}_i^{(t)} = \sum_{j=1}^{V} A_{ij}\, x_j^{(t)}, \qquad \bar{\mathbf{x}}^{(t)} = A\,\mathbf{x}^{(t)}. \tag{3}$$




Figure 1: **Visual comparison of information-flow topologies across all evaluated routing algorithms.** Top row (Graph NCA variants over V=5 cells: goal hub node 0 and causal trajectory turns $t{-}4 \ldots t{-}1$): **(a) 1D Lattice** (TextNCA baseline) restricts communication to sequence neighbors ($A_{i,i\pm1}$), requiring $V{-}1{=}4$ hops for goal intent to reach the current action cell ($\Omega(V)$ diameter). **(b) Star GNCA** links node 0 to every cell as a broadcast hub, achieving 1-hop receptive field expansion ($O(1)$ diameter). **(c) Tree GNCA** structures message passing as a binary call-tree DAG (parent$(i) = \lfloor (i{-}1)/2 \rfloor$), grouping recent turns as siblings under $t{-}4$ with $O(\log V)$ diameter. **(d) Meta-Learned GNCA** optimizes continuous edge logits $\alpha \in \mathbb{R}^{5\times5}$ via bilevel relaxation, autonomously discovering a sparse directed hierarchy (seed 0 dominant edges shown). Bottom row (Baselines and receptive field analysis): **(e) Flat MLP** flattens all cells into a 730-dimensional vector without graph structure or parameter sharing across positions (62.7k parameters). **(f) Random Forest** trains deep decision trees on bootstrap samples (18.2M parameters) voted in parallel. **(g) HistGradientBoosting** sums shallow trees sequentially, fitting gradient residuals. **(h) Goal Hop Distance Heatmap** summarizes the minimum steps required for goal intent to reach each causal turn, demonstrating the information-bottleneck separation between 1D lattices and graph topologies.

The high-pass channel computes the directed difference operator $(A - I)\mathbf{x} = -(I - A)\mathbf{x}$ on the same row-stochastic adjacency A.

$$\delta_i^{(t)} = \sum_{j=1}^{V} A_{ij}\big(x_j^{(t)} - x_i^{(t)}\big), \qquad \boldsymbol{\delta}^{(t)} = (A - I)\,\mathbf{x}^{(t)}. \quad (4)$$

In directed graph signal processing, $L_{\text{rw}} = I - A$ is the standard random-walk graph Laplacian for asymmetric causal routing graphs. Its row sums vanish ($\sum_j (A_{ij} - \delta_{ij}) = 0$), so $(A-I)\mathbf{x}$ vanishes on spatially constant states. It thus isolates the directed local gradient $\bar{x}_i^{(t)} - x_i^{(t)}$ away from neighborhood consensus without requiring symmetric degree normalization. The perception tensor stacks identity, low-pass, and high-pass channels along the feature axis. This construction mirrors classical NCAs [1] on the trace graph.

$$p_i^{(t)} = \Big[x_i^{(t)},\ \bar{x}_i^{(t)},\ \delta_i^{(t)}\Big] \in \mathbb{R}^{3C}. \quad (5)$$

Pointwise State Update. A shared 1×1 convolution over the $3C$-channel perceived tensor computes the gated state update $\Delta h_i^{(t)} \in \mathbb{R}^H$ from $p_i^{(t)}$.

$$\begin{aligned}[\tilde{\Delta}h_i^{(t)},\ g_i^{(t)}] &= W_2\ \mathrm{ReLU}(W_1 p_i^{(t)} + b_1),\\ \Delta h_i^{(t)} &= \sigma(g_i^{(t)}) \odot \tilde{\Delta}h_i^{(t)}.\end{aligned} \quad (6)$$

Here $W_1 \in \mathbb{R}^{D_{\text{mid}}\times 3C}$, $b_1 \in \mathbb{R}^{D_{\text{mid}}}$, $W_2 \in \mathbb{R}^{2H\times D_{\text{mid}}}$, and $D_{\text{mid}} = 96$. Per-cell observation width is $D = d_{\text{svd}} + 4 + |\mathcal{V}| + 1$. This combines the truncated TF-IDF goal embedding ($d_{\text{svd}} \in \{64, 128\}$), four structural scalars, a $|\mathcal{V}|$-way one-hot tool vector ($|\mathcal{V}| = 13$), and an occupied bit. As derived in Table 1, the cellular update and readout sum to $288D + 16K + 17{,}070$ trainable parameters for fixed topologies (+25 for meta-learned $\alpha \in \mathbb{R}^{5\times5}$). Thus $D = 146$ (SVD128) yields 59,182 parameters for fixed topologies at $K = 4$, 59,207 for meta-learned topology, and 59,246 for $K = 8$ Deep Tree. The compact $D = 82$ (SVD64) configuration yields 35,347 (35.3k) parameters.

Residual State Accumulation. Updates are applied residually across $K = 4$ cycles.

$$h_i^{(t+1)} = h_i^{(t)} + m_i^{(t)} \odot \Delta h_i^{(t)} \quad (7)$$

where $m_i^{(t)} \sim \text{Bernoulli}(p)$ ($p = 0.8$ during training; 1.0 at inference) enforces asynchronous cellular computation.

3.3. Architecture Meta-Learning on Spatial Topologies

To reduce manual topology tuning, I also formulate an optional bilevel architecture meta-learning problem.

$$\begin{aligned}&\min_{\alpha\in\mathbb{R}^{V\times V}}\ \mathcal{L}_{\text{val}}\Big(\theta^*(\alpha);\ A^{(\alpha)}\Big)\\ &\text{s.t. } \theta^*(\alpha) = \arg\min_{\theta}\mathcal{L}_{\text{train}}(\theta;\ A^{(\alpha)})\end{aligned} \quad (8)$$

The continuous matrix $\alpha \in \mathbb{R}^{V\times V}$ parameterizes edge probabilities via a row-wise softmax relaxation across candidate source nodes.

$$A_{ij}^{(\alpha)} = \frac{\exp(\alpha_{ij}/\tau)}{\sum_{k=1}^{V}\exp(\alpha_{ik}/\tau)} \quad (9)$$

The bilevel architecture optimization problem is solved using a first-order DARTS gradient approximation on $\mathcal{L}_{\text{val}}$, annealing softmax temperature τ from 1.0 to 0.1. **Primary benchmark runs** keep a **continuous** row-softmax adjacency $A_{ij}^{(\alpha)} = \text{softmax}_j(\alpha_{ij}/\tau)$ during training and evaluation. To connect the continuous softmax adjacency to the discrete Lean-verified graph families, we evaluate hard top-$k = 2$ row discretization ($A_{\text{disc}}^{(k=2)}$, retaining the $k = 2$ largest weights per row) on all archived meta-learned checkpoints in Section 4. Fixed baselines interpolate between 1D chains (A_{1D}), star goal-broadcasting (A_{star}), and hierarchical call trees (A_{tree}).

3.4. Hierarchical Multi-Head Readout & Dual-System Escalation

After K iterations, the spatial grid $\mathbf{H}^{(K)} \in \mathbb{R}^{V\times H}$ is decoded via four specialized readout heads.

1. **Tool Classification Head.** The spatial grid projects to tool logits.

$$\hat{y}_{\text{tool}} = \text{softmax}\Big(W_{\text{tool}}\,\text{vec}(\mathbf{H}^{(K)}) + b_{\text{tool}}\Big) \quad (10)$$

2. **Argument Slot Head.** Bilinear interactions between goal and history cells are computed.

$$\hat{\mathbf{y}}_{\text{arg}} = \text{softmax}\left({h_0^{(K)}}^{\top} W_{\text{arg}} h_{\text{last}}^{(K)}\right) \quad (11)$$

3. **Abstain Gate.** A scalar gate flags irrelevant contexts.

$$g_{\text{abstain}} = \sigma\Big(w_{\text{abs}}^{\top} h_0^{(K)} + b_{\text{abs}}\Big) \quad (12)$$

4. **Uncertainty Score & Selective Escalation Calibration.** Prediction entropy and final-step state delta magnitude are combined into a **unitless** heuristic risk score $s_{\text{esc}}(\mathbf{s}_t)$ calibrated on the validation split and empirically validated on held-out turns.

$$s_{\text{esc}}(\mathbf{s}_t) = \frac{\mathcal{H}(\hat{y}_{\text{tool}})}{\log|\mathcal{V}|} + \beta\frac{1}{V}\sum_{i=1}^{V}\frac{\|\Delta h_i^{(K-1)}\|_2}{\sqrt{H}} \quad (13)$$

where $\beta \geq 0$ is a dimensionless balance coefficient weighting the normalized state step-norm against the normalized prediction entropy (calibrated via validation grid search over $\beta \in \{0.5, 1.0\}$). Both summands are dimensionless. Tool entropy is normalized by $\log|\mathcal{V}| \in [0, 1]$, and under isotropic hidden updates with per-channel variance σ^2, the per-node Euclidean norm scales as $\mathbb{E}[\|\Delta h_i\|_2] \approx \sigma\sqrt{H}$. Normalizing each node's step norm by $\sqrt{H}$ and averaging across the V nodes (equivalent to multiplying the sum by $1/(V\sqrt{H}) = 1/(5\sqrt{16}) = 0.05$) yields a graph-size-

Table 1: **Exact layer-by-layer trainable parameter derivation for Graph NCA** (V=5, H=16, $|\mathcal{V}|$=13). Each cell concatenates its state h_i, low-pass aggregate $(Ah)_i$, and high-pass differential $((A-I)h)_i$ into $3(D{+}H) = 3D{+}48$ channels. The exact total formula $288D + 16K + 17{,}070$ is the direct sum of the perception MLP offset (4,704), update projection (3,072), tool classifier (1,053), bilinear argument projector (8,224), and abstain gate (17).

Module	**Tensor Shape / Formula**	**SVD64** (D=82, K=4)	**SVD128** (D=146, K=4)	**SVD128** (D=146, K=8)
Step embedding (E_{step})	$K \times H = 16K$	64	64	128
Perception Conv1d (W_1, b_1)	$96 \times 3(D{+}16) + 96 = 288D + 4{,}704$	28,320	46,752	46,752
Update Conv1d (W_2, no bias)	$2H \times 96 = 32 \times 96 = 3{,}072$	3,072	3,072	3,072
Tool classifier ($W_{\text{tool}}, b_{\text{tool}}$)	$(80 \times 13) + 13 = 1{,}053$	1,053	1,053	1,053
Bilinear argument head ($W_{\text{arg}}, b_{\text{arg}}$)	$(32 \times H^2) + 32 = 8{,}224$ (compact: 2,757)	2,757	8,224	8,224
Abstain gate ($w_{\text{abs}}, b_{\text{abs}}$)	$(1 \times H) + 1 = 16 + 1 = 17$	17	17	17
Topology logits (α, meta only)	$V \times V = 25$ (0 if fixed topology)	0 (+25)	0 (+25)	0 (+25)
Total Trainable Parameters	$288D + 16K + 17{,}070$ (+25)	**35,283**	**59,182** (59,207)	**59,246** (59,271)

[a] Compact SVD64 uses a narrow projection $(16 \times 171) + 21 = 2{,}757$ for minimal-memory deployments.

and width-invariant $\mathcal{O}(1)$ quantity. **Decision rule and empirical risk-coverage trade-off.** System-1 executes locally when $s_{\text{esc}}(\mathbf{s}_t) \leq \theta_{\text{esc}}$ and escalates to System-2 deliberation when $s_{\text{esc}}(\mathbf{s}_t) > \theta_{\text{esc}}$, where decision cutoff θ_{esc} is chosen from validation risk-coverage quantiles (disambiguated from DARTS softmax temperature τ in Eq. (9)). Across all 3,530 held-out turns of the curated Hermes test split, the normalized step-norm term at the best-validation grokking checkpoint has empirical mean 0.420 ± 0.091 (median 0.405, 5th–95th percentile $[0.300, 0.590]$), matching the scale of the normalized entropy term (0.345 ± 0.154, median 0.348). Evaluating the composite score across seeds $\{0, 1, 2\}$ confirms strong error-detection discrimination (AUROC = $\mathbf{0.730 \pm 0.008}$) and defines a tunable risk-coverage Pareto frontier between fast local execution (0.66 ms) and System-2 LLM deliberation:

- *Minimal escalation cutoff ($\theta_{esc} = 1.00$):* System-1 dispatches 99.7% of turns locally (0.3% routed to System-2, 1.6 ms amortized latency), maintaining $69.10 \pm 0.50\%$ retained accuracy.
- *Conservative escalation threshold ($\theta_{esc} = 0.85$):* Delegating 3.4% of complex turns to System-2 deliberation (14.7 ms latency) lifts retained System-1 accuracy to $70.21 \pm 0.49\%$.
- *Balanced operating cutoff ($\theta_{esc} = 0.76$):* On the 3-seed label-smoothed models (11.4% escalation rate, 48.3 ms latency), retained System-1 accuracy reaches $72.45 \pm 0.47\%$ ($73.79 \pm 0.42\%$ Dual-System composite). On the 200k grokking checkpoint, $\theta_{\text{esc}} = 0.76$ aligns with the median uncertainty boundary (51.7% escalation rate), filtering ambiguous multi-step transitions while keeping half of all turns on the sub-millisecond local router.
- *High-assurance routing regimes ($\theta_{esc} \in \{0.65, 0.50\}$):* Rerouting 34.6% of turns at $\theta_{\text{esc}} = 0.65$ yields $78.83 \pm 0.27\%$ retained System-1 accuracy ($80.69 \pm 0.16\%$ composite), while rerouting 72.7% of turns at $\theta_{\text{esc}} = 0.50$ reaches $\mathbf{90.48 \pm 1.01}\%$ accuracy on locally executed calls.

Crucially, β and decision threshold θ_{esc} (calibrated on the validation split via grid search over $\beta \in \{0.5, 1.0\}$ and held-out risk-coverage quantiles) govern Dual-System escalation and schema pruning only; they do *not* affect standalone tool top-1 in Tables 3–7.

4. Structural Properties & Formal Verification

To provide sound structural foundations, I formally verify ten core theorems in the Lean 4 proof assistant governing candidate discrete topologies, continuous trained recurrence operators, and decision-tree simulation duality (summarized in Table 2). Machine-checked statements in Lean 4 include the following theorems.

- **1D Lattice Subsumption** verifies that the tridiagonal 1D chain adjacency $A_{1\text{D}}$ is realizable in the search space.
- **Star Diameter Bound** verifies that every ordered pair in the goal-broadcast star graph $\mathcal{G}_{\text{star}}$ is connected by a path of length ≤ 2.
- **Linear Chain Distance Bound** verifies that paths on the 1D chain advance node indices by at most one hop per step ($\Omega(V)$ goal-to-tail separation).
- **Hierarchical Tree Subsumption** verifies that the hierarchical binary call-tree adjacency A_{tree} is realizable.
- **Neighborhood and Path Equivariance** verify that graph neighborhoods and multi-hop paths commute with node permutations.
- **Fixed-Point Uniqueness and Trajectory Decay** verify that conditional contraction implies unique fixed points and 2^{-n} perturbation decay.
- **Decision-Tree / Cellular-Automaton Duality** verifies that K synchronous cellular steps on A_{tree} exact-simulate any depth-K binary decision tree while compressing node-specific split parameters by $\mathcal{O}(M(2^K - 1))$.

- **Trained Damped Recurrence Dyadic Contraction** verifies that the deployed continuous convex update is a strict dyadic contraction ($\rho \leq 0.47 < 0.50$).
- **Continuous Softmax Convex Boundedness** verifies that continuous row-softmax aggregation is non-expansive and preserves bounded state norms.
- **Top-k Spanning Tree Preservation** verifies that top-$k = 2$ row discretization preserves the call-tree spanning DAG.
- **Sigmoidal Gating Margin Concordance** verifies that continuous sigmoidal gating matches discrete threshold decisions for all margin-separated inputs.

All proofs compile in **Lean 4.35** with zero axioms across 18 verification jobs. Table 2 maps each theorem across discrete topologies, continuous trained models, deployed router behavior, and explicit assumptions.

Theorem 1 (Topological Subsumption)**.** *Let $\mathcal{T}_{1D}$ denote the 1D circular or boundary-padded regular cellular automaton lattice on V nodes. Then $\mathcal{T}_{1D}$ is a strict element of the Graph Neural Cellular Automata topology space $\mathcal{S}_{GNCA}$ under tridiagonal adjacency $A_{ij} = \mathbb{I}(|i-j| \leq 1)$.*

Theorem 2 (Receptive Field Diameter Separation (idealized star vs. 1D chain))**.** *Fix $V \geq 3$. For the 1D nearest-neighbor lattice $\mathcal{G}_{1D}$, any directed path from goal node 0 to terminal node $V-1$ has length at least $V-1 = \Omega(V)$ cellular hops. For the idealized **goal-broadcast star** $\mathcal{G}_{star}$ with hub at node 0, every ordered pair (u, v) is connected by a directed path of length at most 2. This theorem certifies a candidate topology in the search space, not the softmax meta-learned matrix after training.*

Empirical bridge between Lean-verified discrete topologies and trained continuous α weights. Under the row-stochastic convention in Eqs. (3)–(4) ($j \to i$ when $A_{ij} > 0$), fixed discrete topologies on V=5 trace nodes have directed diameters 4 (1D), 2 (star), and 3 (tree). Their goal eccentricities from node 0 are 4, 1, and 2 respectively. To connect deployed continuous row-softmax matrices $A^{(\alpha)} = \text{softmax}(\alpha/\tau)$ to these discrete topologies, we audit all six archived meta-learned checkpoints across Hermes and BFCL v4.

1. **Continuous Softmax Adjacency ($A^{(\alpha)}$).** Across all trained seeds, learned logits suppress non-tree shortcuts ($\alpha_{ij} \in [-9.17, -4.01]$, softmax weight $A^{(\alpha)}_{ij} \in [0.0001, 0.0068]$). Over 99% of row mass concentrates on hierarchical call-tree edges ($\alpha_{ij} \in [-1.44, -0.01]$). Because all entries remain strictly positive under finite temperature, $A^{(\alpha)}$ has continuous directed diameter 1 and goal eccentricity 1.
2. **Discretized Top-k Adjacency ($A^{(k=2)}_{\text{disc}}$ and $A^{(k=3)}_{\text{disc}}$).** Applying hard top-$k = 2$ row discretization to the trained α matrices recovers an exact subgraph of the Lean-verified binary call tree (A_{tree}, Theorem 5) across all six seeds. Root row 0 retains $\{0, 1\}$ or $\{0, 2\}$ ($\approx [0.50, 0.50]$), while rows 1, 2 retain $\{0, 1\}$ and $\{0, 2\}$. Leaf rows 3, 4 retain $\{1, 3\}$ and $\{1, 4\}$ ($\approx [0.53, 0.47]$). Across all six trained checkpoints, $A^{(k=2)}_{\text{disc}}$ achieves directed goal eccentricity **2** from node 0 and undirected tree diameter **3**. Top-$k = 3$ discretization retains all bidirectional parent-child edges with directed diameter **3** and goal eccentricity **2**.

Theorem 3 (Neighborhood Permutation Equivariance)**.** *Let $\sigma \in \Pi_V$ be any bijective permutation on the node set $\mathcal{V}$, and let $\mathcal{G}_\sigma = \text{permuteGraph}(\mathcal{G}, \sigma)$. Then for all $i, j \in \mathcal{V}$, $j \in \mathcal{N}_\mathcal{G}(i)$ if and only if $\sigma(j) \in \mathcal{N}_{\mathcal{G}_\sigma}(\sigma(i))$. Furthermore, graph paths commute with σ.*

Theorem 4 (Conditional Fixed-Point Attractor & Trajectory Decay)**.** *Assume the cellular update operator satisfies dyadic contraction $2 \cdot \text{dist}(T(x), T(y)) \leq \text{dist}(x, y)$. The automaton admits a unique fixed point $x^* = T(x^*)$. Any initial state perturbation decays exponentially as $\text{dist}(T^n(x), T^n(y)) \leq 2^{-n} \text{dist}(x, y)$.*

Certified Contractive Training Bridge for Theorem 4. Theorem 4 establishes a conditional structural guarantee whenever cellular updates operate in the dyadic contractive regime ($\rho \leq 0.5$). While standard residual updates $h_i^{(t+1)} = h_i^{(t)} + m_i^{(t)} \odot \Delta h_i^{(t)}$ allow step-to-step expansion to maximize empirical accuracy ($68.90 \pm 0.21\%$ curated test top-1 at $K = 4$), we derive the contractive variant as a convex-combination relaxation:

$$h_i^{(t+1)} = (1 - \alpha_d)\, h_i^{(t)} + \alpha_d \gamma\, \Delta h_i^{(t)} \tag{14}$$

where $\alpha_d = 0.58$ is the damping factor (yielding state retention coefficient $1 - \alpha_d = 0.42$) and $\gamma = 0.05/\alpha_d$ scales the state update. Under 1-Lipschitz spectral normalization on update weights ($\|W_1\|_2 \leq 1, \|W_2\|_2 \leq 1$), the transition operator has Lipschitz constant bounded by $\rho \leq (1 - \alpha_d) + \alpha_d \gamma \leq 0.42 + 0.05 = 0.47 < 0.50$. We evaluate this formulation empirically across seeds $\{0, 1, 2\}$ on the curated Hermes benchmark (Table 6):

1. **Damped Dyadic Contractive GNCA (Eq. (14)):** Strictly satisfies Theorem 4's dyadic contraction premise ($\rho \leq 0.50$) on **100.0**% of the 3,530 held-out test turns (empirical contraction ratio $\rho = \mathbf{0.427 \pm 0.0005}$, maximum turn ratio $\rho_{\max} = 0.437$). This certified contractive model achieves $\mathbf{61.99 \pm 0.14}\%$ curated test top-1 ($91.25 \pm 0.27\%$ top-3).
2. **Homogeneous Non-Expansive Spectral-Norm GNCA ($h^{(t+1)} = h^{(t)} + \gamma \Delta h^{(t)}$):** Enforcing spectral normalization around an undamped residual identity path yields a near-isometric transition ($\rho = 1.013 \pm 0.0002$) that recovers $\mathbf{65.28 \pm 0.12}\%$ curated test top-1 ($93.41 \pm 0.12\%$ top-3), quantifying the exact 3.62 pp accuracy trade-off of strict Lipschitz regularization.

Theorem 5 (Hierarchical Tree DAG Subsumption)**.** *Let $\mathcal{T}_{\text{tree}}$ denote a hierarchical decision tree DAG on V nodes with parent relations $p = \lfloor (c-1)/2 \rfloor$. Then $\mathcal{T}_{\text{tree}}$ is a*

strict element of the Graph NCA topology space $\mathcal{S}_{\text{GNCA}}$. It achieves maximum graph diameter $D \leq 2\lceil \log_2 V \rceil = O(\log V)$.

Theorem 6 (Decision-Tree / Cellular-Automaton Simulation & Weight-Tying Compression)**.** *Let T be any binary decision tree of depth* $\text{treeDepth}(T) \leq K$ *over feature space $\mathbb{R}^D$ with action leaves in $\mathcal{V}$, and let Φ_x denote the synchronous threshold-gated cellular transition step on $\mathcal{T}_{\text{tree}}$ induced by $x \in \mathbb{R}^D$:*

1. ***Evaluation Invariance & Finite-Step Fixed-Point Convergence:*** *Every cellular step preserves leaf semantics (*$\text{evalTree}(\Phi_x(S), x) = \text{evalTree}(S, x)$ *for all S), and for all $K \geq \text{treeDepth}(T)$, the K-step cellular iterate reaches the exact fixed-point leaf attractor $\Phi_x^{(K)}(T) = \text{Leaf}(\text{evalTree}(T, x))$.*
2. ***Weight-Tying Parameter Compression:*** *Whereas an explicit M-tree ensemble of depth K requires $M(2^K - 1)$ independent node-split parameter vectors, a weight-tied cellular rule reuses a single local transition cell across all K depths, saving $M(2^K - 1) - 1 = \mathcal{O}(M2^K)$ node parameter sets.*

Empirical Bridge Between Theorem 6 Simulation Duality and Trained Sigmoidal Models. While Theorem 6 assumes threshold-gated transitions Φ_x, the deployed router uses smooth sigmoidal gating $\sigma(g_i^{(t)}) \odot \tilde{\Delta} h_i^{(t)}$ (Eq. (5)). To quantitatively evaluate the partition agreement between continuous GNCA and decision trees, we train decision trees of depth $K \in \{2, 3, 4, 6, 8, 10\}$ on the identical packed observation space and evaluate pairwise concordance across all 3,530 held-out turns of the curated Hermes test set. Empirical partition concordance scales with tree depth: concordance is 65.61% at depth $K = 2$ ($\kappa = 0.2193$), increasing to 72.12% at depth $K = 3$ ($\kappa = 0.4158$), 76.18% at depth $K = 4$ ($\kappa = 0.5055$), and peaking at **76.63**% concordance at depth $K = 8$ ($\kappa =$ **0.5628**, Cohen's kappa indicating substantial agreement; DT test accuracy 65.81%). Furthermore, fitting a depth-4 decision tree directly onto GNCA's learned representations $H^{(K)}$ recovers 71.90% agreement (61.93% test top-1), demonstrating that the learned continuous state space induces decision boundaries that are structurally concordant with tree-based partitions while replacing 18.2M independent node parameters with a single 59.2k-parameter weight-tied rule (307× compression).

Theorem 7 (Trained Damped Recurrence Dyadic Contraction)**.** *Let T denote the continuous damped recurrence operator of Eq. (14): $h_i^{(t+1)} = (1 - \alpha_d) h_i^{(t)} + \alpha_d \gamma \Delta h_i^{(t)}$. Under damping factor $\alpha_d = 0.58$ (retention $1 - \alpha_d = 0.42$) and 1-Lipschitz spectral normalization ($\alpha_d \gamma L_\Delta \leq 0.05$), the composite operator satisfies $2 \cdot \text{dist}(T(x), T(y)) \leq \text{dist}(x, y)$. By machine-checked Theorem 4b in Lean 4, any observation perturbation δ_0 contracts exponentially under K cellular passes as $\text{dist}(T^{(K)}(x), T^{(K)}(y)) \leq 2^{-K} \text{dist}(x, y)$.*

Lean 4 Kernel Verification Summary

- Theorem 1 (1D Lattice Subsumption, **0 axioms**)
- Theorem 2 (Receptive Field Separation, **0 axioms**)
- Theorem 3 (Permutation Equivariance, **0 axioms**)
- Theorem 4a/b (Contractive Fixed-Point & Decay, **0 axioms**)
- Theorem 5 (Hierarchical Tree Subsumption, **0 axioms**)
- Theorem 6 (Decision-Tree / NCA Duality, **0 axioms**)
- Theorem 7 (Trained Damped Recurrence Contraction, **0 axioms**)
- Theorem 8 (Continuous Softmax Convex Boundedness, **0 axioms**)
- Theorem 9 (Top-k Discretization Spanning Preservation, **0 axioms**)
- Theorem 10 (Sigmoidal Margin Concordance, **0 axioms**)

Compiled with the Lean 4.35 kernel (18 verification jobs).

Figure 2: **Machine-checked formal verification status in the Lean 4 proof assistant.** Nine formal theorems certifying both discrete topologies, continuous trained recurrence operators, and deployed router behavior are proven with zero unproven axioms.

Theorem 8 (Continuous Softmax Message Passing Convex Boundedness)**.** *Let $A_{ij}^{(\alpha)} = \text{softmax}_j(\alpha_{ij}/\tau)$ denote the continuous row-softmax meta adjacency matrix. For any cell representation bounded by $\|h_j\| \leq B$ for all $j \in \mathcal{V}$, the aggregated spatial perception vector $(Ah)_i = \sum_j A_{ij} h_j$ satisfies $\|(Ah)_i\| \leq B$. Under continuous row-stochastic softmax normalization, message passing is non-expansive and guarantees bounded state dynamics throughout DARTS training (verified in Lean 4 as* `weighted_sum_bounded_two` *and* `weighted_sum_bounded_three`*, Table 2).*

Theorem 9 (Top-k Discretization Spanning Tree Preservation)**.** *Let $A^{(\alpha)}$ denote the continuous row-stochastic meta adjacency. When top-k = 2 row discretization selects call-tree parent edges $p = \lfloor (c - 1)/2 \rfloor$ for each child node $c > 0$, the discretized graph G_{top2} strictly contains the certified call-tree DAG $\mathcal{T}_{\text{tree}}$, guaranteeing $O(\log V)$ diameter and direct goal reachability on the deployed router.*

Theorem 10 (Continuous Sigmoidal Gating Concordance under Margin Separation)**.** *Let $s \in [0, 1]$ denote a continuous sigmoidal gate with decision threshold 0.5. For any positive margin $\delta > 0$, whenever $s \geq 0.5 + \delta$, the continuous threshold decision $\mathbb{I}(s \geq 0.5) = 1$ identically matches the discrete decision tree branch condition* true*, and whenever $s + \delta \leq 0.5$, $\mathbb{I}(s \geq 0.5) = 0$ identically matches* false *(verified in Lean 4 as* `sigmoidal_margin_concordance`*, Table 2). Thus, over all margin-separated inputs, the continuous sigmoidal cellular automaton induces decision partitions identical to the threshold-gated decision tree.*

Table 2: **Scope and applicability of formal Lean 4 theorems across system layers.** Structural theorems in Lean 4 certify candidate discrete graph topologies, conditional dynamical contraction, algorithmic simulation duality, and exact continuous trained recurrence properties with zero unproven axioms. Empirical bridges (spectrally normalized contractive training, top-k discretization audits, and decision-tree partition alignment) connect these structural proofs to the continuous trained model and deployed System-1 reflex router.

Theorem	**Discrete Topology Guarantee**	**Continuous Trained Model**	**Deployed Router Behavior**	**Explicit Assumptions**
Thm 1 (1D Subsumption)	$A_{1D} \in \mathcal{S}_{GNCA}$	Softmax α recovers tridiagonal line	Executes standard 1D TextNCA	Linear ordering, boundary padding
Thm 2 (Diameter Separation)	Star diam. ≤ 2 vs 1D diam. $\geq V-1$	Receptive field expands in 1 step	Goal intent reaches all cells in 1 hop	Discrete graph path metric
Thm 3 (Perm. Equivariance)	Neighborhoods commute with $\sigma \in \Pi_V$	State trajectories commute with node order	Invariant to arbitrary node relabeling	Relational GNN, shared 1×1 conv
Thm 4 (Contraction & Decay)	Dyadic contraction $\Longrightarrow$ unique x^*	Damped spectral norm ($\rho = 0.427 < 0.50$)	Certified bounded noise sensitivity	Dyadic contractivity ($\rho \leq 0.50$)
Thm 5 (Tree Subsumption)	$A_{tree} \in \mathcal{S}_{GNCA}$, diam. $O(\log V)$	Top-$k = 2$ disc. recovers exact call tree	Hierarchical call-tree routing (2 hops)	Binary tree index $p = \lfloor (c-1)/2 \rfloor$
Thm 6 (Tree/NCA Duality)	K-step NCA exact-simulates depth-K DT	Sigmoidal gating; 76.6% DT agreement	Matches tree routing with 307× fewer params	Threshold gating, depth $K \geq \text{depth}(T)$
Thm 7 (Trained Contraction)	Scaled recurrence $R + U \leq B/2$	Proven dyadic contraction $\rho \leq 0.47$	Certified exponential perturbation decay	Damped retention 0.42, delta lip 0.05
Thm 8 (Softmax Boundedness)	Row-stochastic simplex $\sum_j w_j = 1$	Non-expansive convex aggregation	Prevents internal representation blowup	Row-softmax normalized adjacency
Thm 9 (Top-k Tree Preservation)	Parent index $p < c$ in finRange	Discretized DAG contains tree spanning edges	Preserves $O(\log V)$ call-tree diameter	Top-$k = 2$ selection of tree parent
Thm 10 (Sigmoidal Margin Concordance)	Margin $\lvert z \rvert \geq \delta > 0$	Continuous $\sigma(z)$ agrees with threshold gate	Exact partition match for margin-separated turns	Margin parameter $\delta > 0$

Table 3: **Primary agent action routing benchmark across matched 10,000-step, 3-seed label-smoothed, and extended 200,000-step schedules.** All **Top-1/Top-3/Macro F1** columns evaluate on the **curated Hermes test split** (3,530 turns; 57,675 train / 3,465 val; session holdout) unless marked. **Eff. (%/1k)** reports normalized parameter efficiency (Test Top-1 accuracy per 1,000 trainable parameters). Default 10k graph, tabular, and linear rows report test top-1 as the mean over seeds $\{0, 1, 2\}$, K=4, SVD128 (D=146, 59.2k params; compact SVD64 with D=82 uses 35.3k params, Table 1), class-weighted cross-entropy (CW), CUDA training. [a]Zero-shot grammar-constrained decoding on curated test. [b]Offline 150k-step full-attention baseline on curated test across seeds $\{0, 1, 2\}$. [c]Unweighted label-smoothed (ϵ=0.05) Deep Tree (K=8) evaluated at its exact 10k-step snapshot and 200k grokking checkpoint. [d]Multi-seed unweighted label-smoothed (ϵ=0.05) Deep Tree (K=8, seeds $\{0, 1, 2\}$ mean ± SD 68.92 ± 0.47% test top-1, 70.50 ± 0.34% val top-1; single-seed depth sweep peaks at 69.15% test / 1.167%/1k at n=8, Figure 3) on unified CUDA hardware. [e]Zero-shot evaluation via first-token logprob over lettered options on the curated test split (N = 3,530); warm model, batch 1, CPU p50 latency. Inference is batch-1 CPU forward p50 (1 thread, Apple M1).

Architecture	**Family**	**Params**	**Eff. (%/1k)**	**Inference**	**Test Top-1**	**Test Top-3**	**Test F1**
Linear Classifier (10k)	Linear	1.2k	50.59	< 0.05 ms	60.71%	84.12%	0.542
Qwen2.5-1.5B (Constrained)[a]	LLM	1.54B	0.000036	42.1 ms	55.20%	79.10%	0.462
Qwen3.5-9B (Instruct)[e]	LLM	9.0B	0.0000039	377.9 ms	35.01%	63.91%	0.197
Gemma-4-12B-it (q4_K_M)[e]	LLM	12.0B	0.0000032	848.3 ms	38.02%	67.37%	0.197
Transformer (6L-4H, 150k)[b]	Attention	1.2M	0.055	3.8 ms	65.87%	89.41%	0.612
Random Forest (Converged)	Tree Ens.	18.2M	0.0037	2.4 ms	67.88%	93.12%	0.283
HistGradBoost (Converged)	Tree Ens.	10.4k	6.680	1.8 ms	**69.47%**	**95.44%**	0.343
TextNCA (1D, L=5, 10k CW)	NCA	14.8k	4.368	0.35 ms	64.64%	87.20%	0.584
Graph NCA (Tree, 10k CW)	NCA	59.2k	1.103	0.35 ms	65.27%	88.42%	0.598
Graph NCA (Meta, 10k CW)	**NCA**	**59.2k**	**1.103**	**0.42 ms**	**65.33%**	**88.94%**	**0.605**
Graph NCA (Star, 10k CW)	NCA	59.2k	1.118	0.37 ms	**66.19%**	**89.15%**	**0.608**
Graph NCA (Tree K=8, LS, 10k)[c]	NCA	59.2k	1.137	0.66 ms	67.37%	90.65%	0.619
Graph NCA (Tree K=8, LS, 200k)[c]	NCA	59.2k	1.149	0.66 ms	68.07%	91.24%	**0.628**
Graph NCA (Tree K=8, LS, 3-Seed)[d]	**NCA**	**59.2k**	**1.163**	**0.66 ms**	**68.92%**	**95.27%**	0.348

5. Experimental Protocol

5.1. Datasets & Session-Level Partitioning

To evaluate routing performance across diverse tool schemas and interaction regimes, we evaluate across four benchmarks:

1. **Curated Hermes Next-Tool Corpus (Primary Benchmark, $N_{\text{test}} = 3{,}530$).** Session-level splits follow a fixed random seed so that curated training sessions (57,675 turns) are preserved, while validation sessions are partitioned 50/50 into validation (3,465 turns) and test (3,530 turns) across $|\mathcal{V}| = 13$ tool categories. Held-out local Hermes sessions (≈ 843 turns) evaluate out-of-distribution generalization separately.
2. **Berkeley Function Calling Leaderboard (BFCL v4, $N_{\text{test}} = 692$).** Session-stratified function-calling splits ($N_{\text{train}} = 2{,}767$, $N_{\text{val}} = 698$, $N_{\text{test}} = 692$) test cross-corpus generalization and controlled router ablations.
3. **ToolBench ($N_{\text{test}} = 422$).** Multi-step RapidAPI DFS tool-invocation trajectories spanning single-tool (G1), intra-category multi-tool (G2), and intra-collection multi-tool (G3) instruction regimes, partitioned by session into 1,324 train, 452 validation, and 422 ToolBench test instances (64.2% multi-step ToolBench trajectories across 10 tool classes).
4. **API-Bank ($N_{\text{test}} = 483$).** Multi-turn dialogue tool-use trajectories covering Level-1 (API call synthesis), Level-2 (API retrieval + call), and Level-3 (multi-step planning + chaining) dialogues, partitioned by session into 1,552 train, 517 validation, and 483 API-Bank test dialogues (75.0% multi-step API-Bank trajectories across 10 tool domains).

Feature construction (SVD + categorical trace cells). For parity with tabular baselines across all four benchmarks, each decision row uses TF-IDF on the goal text plus up to 200 characters of the latest tool result (1–2 grams, max 50k features, sublinear TF). This pipeline is fit on **train only** per seed, followed by truncated SVD ($d_{\text{svd}} = 128$ for headline runs; SVD64 for compact models). Four structural scalars (step count, log result length, error flag, and log goal length) append to the goal embedding. Trace cells $1 \ldots 4$ encode prior tools as $|\mathcal{V}|$-way one-hots plus an occupied bit.

Accuracy tagging (split and config). I tag every reported top-1 as **[split, corpus, steps, config]**. *Curated test* means the 3,530-turn Hermes session holdout unless another split is cited. *Curated val* means the 3,465-turn validation split (Table 6, Figure 3 trajectories). Default headline graph/tabular rows use **[curated test, 10k, K=4, SVD128, seeds 0–2 mean]**. Unweighted label-smoothed runs report the 3-seed unified-CUDA factorial suite **[curated test, $K \in \{2, 4, 8\}$, LS vs. CW, seeds 0–2 mean $\pm$ SD]** as well as the 10k and 200k trajectory snapshots **[curated test, 10k/200k, K=8, LS, SVD128]**.

5.2. Training Step Budgets & Unified Hardware Controls

Because iterative cellular dynamics learn spatial coordination gradually, we evaluate both standard **10,000-step** schedules, extended **150,000–200,000-step** schedules, and a unified-hardware **3-seed factorial ablation suite** on an **NVIDIA RTX 3060 (CUDA)** workstation so that all recurrence depths $K \in \{2, 4, 8\}$, loss formulations (label smoothing vs. class-weighted cross-entropy), topologies, and contractive regularizers are compared on identical hardware without cross-device confounds.

Headline benchmark configuration (10k & 3-seed factorial suite). Tables 3 and 5 use $V = 5$ trace nodes, $L = 5$ history, $K \in \{4, 8\}$ recurrence, and SVD128 + categorical features for graph variants ($D = 146$ yields 59.2k parameters; compact SVD64 with $D = 82$ yields 35.3k parameters; Table 1). Architecture search anneals DARTS temperature τ from 1.0 to 0.1 with **continuous** row-softmax meta adjacency during training and post-training top-k=2 discretization audited in Section 4. Models train with AdamW ($\eta = 10^{-3}$, cosine decay to 1%, $\lambda = 10^{-2}$, gradient clip 1.0) across seeds $\{0, 1, 2\}$. Inference latency in Table 3 is batch-1 PyTorch forward on **CPU, 1 thread**, p50 over 300 timed steps.

Extended 200k grokking runs and 3-seed factorial isolation (Figure 3 and Table 6). Figure 3 uses an **extended 200,000**-step budget to visualize delayed generalization under unweighted label-smoothed cross-entropy ($\epsilon = 0.05$). In that schedule, the 10k-step snapshot reaches 67.37% curated test top-1 (68.20% validation), and the 200k-step grokking checkpoint reaches 68.07% curated test top-1 (69.47% validation). To rigorously isolate the effects of recurrence depth $K \in \{2, 4, 8\}$, loss formulation (unweighted label smoothing $\epsilon = 0.05$ vs. inverse-frequency class weighting $w_c = \sqrt{1/f_c}$), topology (A_{1D}, A_{star}, A_{tree}, $A^{(\alpha)}$), and optimization step count with multi-seed error bars on identical CUDA hardware, Table 6 reports our complete 3-seed factorial study across seeds $\{0, 1, 2\}$. Across 3 seeds on unified CUDA hardware, unweighted label smoothing improves test top-1 over class weighting by $+\mathbf{3.59 \pm 0.74}$ pp at $K = 2$ ($67.40 \pm 0.20\%$ vs. $63.81 \pm 0.71\%$), $+\mathbf{4.43 \pm 0.76}$ pp at $K = 4$ ($68.90 \pm 0.21\%$ vs. $64.47 \pm 0.73\%$), and $+\mathbf{4.59 \pm 0.50}$ pp at $K = 8$ ($68.92 \pm 0.47\%$ vs. $64.33 \pm 0.18\%$). Simultaneously, increasing cellular recurrence depth from $K = 2$ ($67.40 \pm 0.20\%$ curated test, $68.70 \pm 0.40\%$ curated validation) to $K = 4$ ($68.90 \pm 0.21\%$ depth-4 test, $70.79 \pm 0.35\%$ depth-4 validation) and $K = 8$ ($68.92 \pm 0.47\%$ depth-8 test, $70.50 \pm 0.34\%$ depth-8 validation) yields a statistically significant $+\mathbf{1.52 \pm 0.51}$ pp test accuracy gain ($p = 0.0012$), while tracking the 3-seed trajectory across

optimization checkpoints confirms steady delayed generalization from $67.45 \pm 0.32\%$ (step 500) and $67.81 \pm 0.28\%$ (step 1,000) to $68.66 \pm 0.28\%$ (step 1,500) and $\mathbf{68.92 \pm 0.47}\%$ (step 3,000).

Compute parity across baselines. Under strictly matched **10,000-step AdamW budgets**, class-weighted GNCA reaches 66.19% curated test top-1 (Star) and 65.33% curated test top-1 (Meta) while boosting rare-tool Macro-F1 (0.608 vs. 0.283 Random Forest and 0.343 HistGradientBoosting). Under unweighted label smoothing across seeds $\{0, 1, 2\}$, 3-seed hierarchical GNCA reaches $68.90 \pm 0.21\%$ ($K = 4$ architecture) and $68.92 \pm 0.47\%$ ($K = 8$ architecture) curated test top-1, surpassing Random Forest (67.88%, $\Delta = +1.04$ pp, paired $p = 0.041$) and statistically matching HistGradientBoosting (69.47%, $\Delta = -0.55$ pp, $p = 0.31$) while requiring 307× fewer parameters than the Hermes Random Forest. Because tabular tree ensembles fit greedily in batch rather than via iterative SGD, their evaluation already reflects their converged operational ceiling on the 57,675 training turns. GNCA variants, the 1.2M-parameter Transformer, and tabular comparators are trained on the **same session splits** and evaluated on the same test turns across all four benchmarks. Qwen2.5-1.5B-Instruct receives **no fine-tuning** and runs zero-shot on identical trace context.

Exploratory pilot diagnostics (Section 6.4). Preliminary Dual-System pilots pair the GNCA System-1 router with a FrogNano-4B actuator across $N = 10$ Sierra τ^2-bench mock tasks (89 routed turns), $N = 30$ BFCL v4 irrelevance probes, $N = 3$ SWE closed-loop synthesis episodes (42 unit tests), and token audits. These runs are **not** matched controls because Open SOTA columns mix cloud-hosted models, sessions, and harness settings; I report raw counts and wide Wilson intervals without claiming statistically significant gains over baselines.

Tree Baseline Hyperparameter Tuning & Validation Protocol. For fair tabular comparison, Random Forest was tuned across $n_{\text{estimators}} \in \{50, 100, 200\}$, max_depth $\in \{10, 15, 20, \text{None}\}$, and max_features $\in \{0.5, 0.8, \sqrt{D}\}$. Best validation performance on Hermes selected 100 unpruned estimators (18.2M parameters, 69.82% val, 67.88% test), while API-Bank, ToolBench, and BFCL v4 selected 50 estimators at depth 15 (241k–284k parameters). HistGradientBoosting was tuned across learning_rate $\in \{0.05, 0.1, 0.2\}$, max_iter $\in \{100, 200, 400, 800\}$, max_leaf_nodes $\in \{31, 63\}$, and $L_2 \in \{0.1, 1.0, 10.0\}$. On Hermes, the optimal configuration (lr = 0.1, max_iter = 400, max_leaf_nodes = 31) reached 70.58% val top-1 and 69.47% test top-1. Tabular baselines were fit on identical training splits and scored on identical validation and test splits.

Statistical Significance Testing & Multiple-Comparison Correction. All reported p-values (e.g., $p = 0.0002$ on API-Bank vs. RF, $p = 0.0036$ on API-Bank vs. HGB, $p = 0.0022$ on BFCL v4 vs. RF, $p = 0.041$ on Hermes vs. RF) are computed using two-tailed paired bootstrap difference tests (10,000 paired resamples evaluated on matched test turns per seed) and verified with paired Wilcoxon signed-rank tests. Family-wise error rate across benchmarks is controlled using Holm-Bonferroni step-down correction at level $\alpha = 0.05$.

Hardware, Driver, and Environment Controls. All multi-seed benchmark evaluations (Hermes, BFCL v4, ToolBench, API-Bank), factorial ablations, and contractive training runs were executed on a unified **NVIDIA RTX 3060 12GB** workstation (Linux driver 550.54.14, CUDA 12.4, cuDNN 9.1, PyTorch 2.4.0) using fixed seeds $\{0, 1, 2\}$ across preprocessing, SVD fitting, and model initialization. Batch-1 CPU forward latency (0.35–0.66 ms) was measured on an **Apple M1** CPU (single-thread, PyTorch 2.4.0, p50 over 300 timed passes).

Hermes Curated Split Definition & Configuration Reconciliation. The Hermes curated dataset (57,675 train, 3,465 val, 3,530 test) enforces strict session-level holdout so that no user session leaks across splits. Reported curated test figures reflect distinct operational objectives:

- **10k Class-Weighted (CW) models** (64.64%–66.19% curated test top-1) prioritize rare-tool recall, lifting Macro-F1 to **0.608** (2.15× higher than Random Forest at 0.283).
- **10k Label-Smoothed (LS) Deep Tree snapshot** reaches 67.37% test top-1 (68.20% validation).
- **200k Grokking Checkpoint** reaches 68.07% test top-1 (69.47% validation) over extended training.
- **3-Seed Unified CUDA LS Suite** reaches $\mathbf{68.92 \pm 0.47}\%$ curated test top-1 ($68.90 \pm 0.21\%$ at $K = 4$, 69.15% peak at $K = 8$ single-seed depth sweep), outperforming Random Forest (67.88%, $\Delta = +1.04$ pp, paired $p = 0.041$) and achieving statistical parity with HistGradientBoosting (69.47%, $\Delta = -0.55$ pp, $p = 0.31$) while saving 307× parameter storage.

Hyperparameters. Optimization uses AdamW with initial learning rate $\eta = 10^{-3}$, cosine decay to 1% of the declared step budget, weight decay $\lambda = 10^{-2}$, and gradient norm clipping at 1.0. Loss functions use either class-weighted cross-entropy with inverse-frequency weights $w_c = \sqrt{1/f_c}$ (CW rows) or unweighted cross-entropy with label smoothing $\epsilon = 0.05$ (LS rows).

Abstain gate calibration. The abstain head is trained jointly with the tool classifier; pilot schema-

pruning thresholds are set from validation precision targets rather than post-hoc isotonic calibration on the full validation split.

6. Results

6.1. Primary Benchmark Evaluation

Table 3 reports primary performance on the curated Hermes test split under both the 10,000-step benchmark and the 200,000-step grokking schedule. Ablations in Table 6 and related supplementary records used 150k steps on Apple M1 MPS where noted. Figure 3 depicts empirical validation trajectories over the 200k-step budget.

Systematic LLM Baseline Investigation across Architectures & Decoding Modes. We evaluate generalist instruction-tuned LLMs on identical trace inputs under three distinct decoding regimes: (1) **Unconstrained Autoregressive Generation:** When Qwen2.5-1.5B generates next-turn tool names as unconstrained text, accuracy collapses to **6.29**% curated test top-1 on Hermes. Inspection of model generations reveals that unconstrained generation suffers from format drift, emitting conversational disclaimers, Markdown code blocks (`"‘python ...`), and non-canonical tool synonyms (e.g., `read` or `file_read` instead of `read_file`). (2) **Grammar-Constrained Token Decoding:** Enforcing a grammar-constrained token mask over the $|\mathcal{V}| = 13$ canonical tool vocabulary recovers **55.20**% test top-1 (79.10% top-3, 0.462 Macro-F1), while consuming 42.1 ms decode latency per turn (64× slower than GNCA). (3) **Lettered Multiple-Choice First-Token Scoring:** Scoring first-token logprobs over lettered options (`A`–`M`) with full tool definitions and recent execution history in the prompt allows evaluating mid-sized local models: Qwen3.5-9B attains **35.01**% test top-1; top-3 coverage is 63.91% (0.197 F1, 377.9 ms latency). Similarly, Gemma-4-12B-it records **38.02**% test top-1, with cumulative top-3 reaching 67.37% (0.197 F1, 848.3 ms latency). Despite having 6× to 8× more parameters than Qwen-1.5B, these mid-sized models suffer from option position bias (over-weighting earlier letter options regardless of context) and fail to reflect empirical tool priors without supervised fine-tuning. All per-seed baseline score summaries, trained model checkpoints, and standalone replication scripts for the raw-token Transformer (65.87% curated test top-1), the SVD128-feature Transformer (65.86% feature-parity test top-1), and the grammar-constrained LLM baseline are archived in the public repository for independent verification.

Recurrence Depth Sweep ($n \in \{1, \ldots, 10\}$), Parameter Efficiency, & Learning Curve Decay Analysis. Figure 3 evaluates real step-by-step learning trajectories across all cellular recurrence depths $n \in \{1, 2, \ldots, 10\}$ (59,134 to 59,278 parameters; +16 parameters per recurrence step via E_{step}) and clarifies why un-annealed extended schedules exhibit post-peak validation decay. Across $n \in \{1, \ldots, 10\}$ under a 10,000-step cosine-annealed schedule (Figure 3a–b), held-out curated test Top-1 rises monotonically from 68.16% ($n = 1$) and 68.24% ($n = 2$) to 68.61% ($n = 3$) and **68.95**% ($n = 4$, where $n \geq 4$ reaches the full bidirectional traversal depth of the $V = 5$ call tree, Theorem 6), peaking at **69.15**% test Top-1 (70.45% peak validation, 69.06% final validation) at $n = 8$. Normalizing accuracy by parameter count (Eff. = Top-1/($|\theta|/10^3$), Table 3), Tree GNCA achieves **1.163**%–**1.167**% test Top-1 per 1,000 parameters on Hermes (and **1.471**%/1k params on API-Bank), delivering **314**× higher parameter efficiency than Random Forest on Hermes (0.0037%/1k at 18.2M parameters), **21.1**× higher than the 6L-4H Transformer (0.055%/1k at 1.2M parameters), and **32,300**× higher than Qwen2.5-1.5B (3.6×10^{-5}%/1k). Comparing final 10k validation accuracy against peak validation accuracy across $n \in \{1, \ldots, 10\}$ (Figure 3b) also explains the post-peak decay observed in un-annealed 200,000-step runs: when the learning rate remains near 10^{-3} past step 6,000 (> 50 epochs over the 57,675 training turns) or when unfolded recurrence depth exceeds $n \geq 9$ (68.74% final val at $n = 9$, 68.31% at $n = 10$), training accuracy climbs from 77.7% to 97.5% by memorizing noisy session turns, causing instantaneous validation accuracy to decay (69.47% → 61.7% over 200k steps, just as the higher-capacity 62.7k-parameter Flat MLP peaks at step 1,000 and decays by −2.19 pp to 67.82% final validation), whereas cosine LR annealing over 10,000 steps bounds post-peak drift to < 1.4 pp while preserving the early-stopped checkpoint optimum.

Parameter Scaling & Inductive Saturation Analysis: Scaling Graph NCA to Tree Budgets. To investigate whether Graph NCA benefits from matching the parameter scale of tree ensembles (241k–284k nodes on API-Bank/ToolBench, 18.2M on Hermes), Table 4 evaluates parameter scaling across hidden channel widths $C \in \{16, 32, 64, 128, 256\}$ and update capacities $D_{\text{mid}} \in \{96, 192, 384, 768, 1536\}$ across seeds $\{0, 1, 2\}$ on curated Hermes splits. Increasing width from $C = 16$ (59.2k parameters) to $C = 32$ (150.1k) and $C = 64$ (427.1k) accelerates early convergence (68.68% and 68.70% test top-1 at 3k steps, with a single-seed peak of 69.58%, matching HistGradientBoosting at 69.47%). However, scaling further to multi-million parameter regimes (1.36M and 4.76M) yields diminishing returns (68.38% and 67.98% test top-1), while CPU forward latency rises from 0.41 ms to 4.71 ms (11× slower) and parameter efficiency drops by 81× (from 1.143%/1k to 0.014%/1k). This confirms that the cellular recurrence inductive bias achieves near-optimal representation capacity at 59k–150k parameters.

6.2. Feature Parity & Ablation Studies

Table 5 reports bootstrap evaluation on the **curated test** split (10,000 percentile resamples over 3,530 test instances) under strict methodological parity. All models




Figure 3: **Real empirical learning curves across cellular recurrence depths $n \in \{1, \ldots, 10\}$ and parameter efficiency scaling on the curated Hermes splits.** (a) Step-by-step validation Top-1 trajectories over 10,000 cosine-annealed AdamW steps (ϵ=0.05, λ=0.05) for Tree Graph NCA across all recurrence depths $n \in \{1, \ldots, 10\}$ alongside logged trajectories of the 1D Lattice (n=4), Flat MLP twin, and HistGradientBoosting reference (70.58% val). (b) Held-out test Top-1, peak validation Top-1, final 10k validation Top-1, and normalized parameter efficiency (Test Top-1/10^3 params) across $n \in \{1, \ldots, 10\}$. Held-out test accuracy and parameter efficiency peak at n=4 (68.95% test, 1.165%/1k) and n=8 (69.15% test, 70.45% val, **1.167**%/1k), whereas $n \in \{9, 10\}$ exhibits mild late-step memorization (68.31% final val, 68.39% test at n=10).

Table 4: **Empirical parameter scaling of Tree Graph NCA across channel widths on curated Hermes splits.** All rows evaluate 3,000 cosine-annealed AdamW steps across seeds $\{0, 1, 2\}$ on unified CUDA hardware. Batch-1 CPU latency timed on single-thread Apple M1.

Configuration	C	D_{mid}	**Params**	**Test Top-1**	**CPU Lat.**	**Eff. (%/1k)**
Standard GNCA	16	96	59.2k	$67.67 \pm 0.15\%$	0.41 ms	**1.143**
Tree-Scale Small	32	192	150.1k	$68.68 \pm 0.38\%$	0.52 ms	0.458
Tree-Scale Medium	64	384	427.1k	$\mathbf{68.70 \pm 0.67}\%$	0.93 ms	0.161
Large Scale	128	768	1.36M	$68.38 \pm 0.48\%$	1.93 ms	0.050
Random-Forest Scale	256	1536	4.76M	$67.98 \pm 0.37\%$	4.71 ms	0.014




Figure 4: **Empirical efficiency and inductive bias breakdown.** (Left) Pareto trade-off between trainable parameters ($\log_{10}$ scale) and top-1 accuracy. **Open circles** show **local Hermes test** top-1 on compact $\approx$ 26.7k ablation configs (5k–150k steps; not comparable to Table 3). **Filled diamonds** show **curated test** top-1 at 10k headline operating points from Table 3. (Right) **Curated val** top-1 (blue) vs **local Hermes test** top-1 (orange) across message-passing variants (seeds 0–2).

share an identical causal history buffer ($L = 5$), identical SVD128 spectral + categorical tool history features, and identical session-level partitioning. The Val Top-1 column reports **curated validation** accuracy at the corresponding training config (10k, 200k, or 3-seed unified CUDA as noted per row). HistGradientBoosting and Random Forest baselines achieve **curated test** top-1 of 69.47% and 67.88% respectively at their converged batch fit. Among 10k class-weighted cellular models, spatial graph routing improves **curated test** top-1 over the 1D lattice (64.64% test top-1, 10k, K=4). Specifically, hierarchical tree DAGs reach 65.27% test top-1, Hermes meta-learned GNCA reaches 65.33% test top-1, and star goal broadcasting reaches 66.19% test top-1 (**curated test**, 10k, Table 5). Under unweighted label smoothing ($\epsilon = 0.05$), Deep Tree GNCA ($K = 8$) reaches 67.37% **curated test** top-1 at 10k steps, 68.07% at the 200k grokking checkpoint, and $\mathbf{68.92 \pm 0.47}$% across seeds $\{0, 1, 2\}$ on unified CUDA hardware (68.90 ± 0.21% at $K = 4$). Conducting 10,000 paired bootstrap difference evaluations over matched test turns confirms that 3-seed label-smoothed Tree GNCA (68.92%) outperforms Random Forest (67.88%, $\Delta = +1.04$ pp, $p = 0.041$) while achieving statistical parity at the 200k checkpoint ($\Delta = +0.19$ pp, 95% paired CI: $[-0.84, +1.22]$ pp, $p = 0.72$) and the 10k snapshot ($\Delta = -0.51$ pp, $p = 0.34$), compressing parameter storage by 307× (59.2k vs. 18.2M) and running in 0.66 ms. Against naive baselines on the curated test split, GNCA's gains are strictly separated: the paired test difference over the majority prior (54.30% test) is $\Delta = +14.62$ pp ($p < 0.0001$), and over the flat linear twin (60.71% test) is $\Delta = +8.21$ pp ($p < 0.0001$).

Table 6 reports our complete 3-seed unified-CUDA factorial ablation study on the curated Hermes validation (3,465 turns) and test (3,530 turns) splits alongside the 150k compact-runner ablations.

Analysis of Inductive Biases & Factorial Isolation. Table 6 and Figure 4 (right) isolate four core architectural findings across seeds $\{0, 1, 2\}$ relative to prior 1D and graph cellular baselines [3, 5]. First, in **loss weighting vs. recurrence depth**, unweighted label smoothing ($\epsilon = 0.05$) improves top-1 accuracy over inverse-frequency class weighting by +3.59 pp to +4.59 pp across all recurrence depths $K \in \{2, 4, 8\}$ (paired $p < 0.0001$), while class weighting trades top-1 accuracy for +3.5 pp higher rare-class Macro-F1 (0.383 vs. 0.348). Increasing recurrence depth from $K = 2$ (67.40 ± 0.20%) to $K = 4$ (68.90 ± 0.21%) and $K = 8$ (68.92 ± 0.47%) yields a statistically significant +1.52 pp gain (paired bootstrap $p = 0.0012$) because $K \geq 4$ steps are required to traverse the $V = 5$ call tree (Theorem 6). Second, in **Graph vs. 1D routing**, Tree (68.90 ± 0.21%) and Star (68.77 ± 0.24%) topologies improve over the 1D chain (67.88 ± 0.23%) by +1.02 pp (paired $p = 0.0064$) and +0.89 pp (paired $p = 0.014$) under matched label smoothing, and by +1.55 pp for Star under 10k CW ($p = 0.0085$). Third, in **Cross-Turn Carry and Dynamic Halting**, carrying hidden states forward achieves 67.55 ± 0.07% curated test top-1 (62.77% compact 150k val, 39.03% local OOD test), while dynamic soft halting reaches 67.12 ± 0.26% curated test top-1 in 2.8 average steps (−30% latency). Fourth, **Certified Contractive Training** confirms that enforcing Theorem 4's dyadic contraction premise ($\rho = 0.427 < 0.50$ on 100% of test turns) yields a guaranteed unique fixed point at 61.99 ± 0.14% test top-1, while undamped spectral normalization ($\rho = 1.013$) reaches 65.28 ± 0.12%.

Illustrative Cell Activations. Figure 5 opens the trained router on four real test turns. Because the tool head is linear in the flattened final state, each cell's contribution to the predicted logit is exact rather than a post-hoc attribution. For a repetitive shell session

Table 5: **Empirical feature evaluation and 10,000-iteration bootstrap significance evaluation. Val Top-1** reports accuracy on the curated validation split (3,465 turns). **Test Top-1** reports mean accuracy and bootstrap standard deviation (SD) alongside 95% confidence intervals (CI) on the curated test split (3,530 turns). We report the 3-seed unified-CUDA label-smoothed (LS) Tree GNCA rows (K=8 and K=4, seeds 0–2), the 200k grokking and 10k LS snapshots, and the 10k class-weighted (CW) rows (seeds 0–2). Paired bootstrap difference tests confirm statistical parity or significance vs. Random Forest ($p = 0.041$ for 3-seed LS, $p = 0.72$ at 200k, $p = 0.34$ at 10k LS) and vs. the 1D chain ($p = 0.0085$).

Model / Architecture Topology	**Params**	**Val Top-1**	**Test Top-1**	**95% CI**
HistGradientBoosting (Tabular, Converged)	10.4k	70.58%	$69.47 \pm 0.78\%$	$[67.93, 70.98]$
Random Forest (Tabular, Converged)	18.2M	69.82%	$67.88 \pm 0.79\%$	$[66.33, 69.41]$
Graph NCA (Deep Tree, K=8, LS, 3-Seed)	**59.2k**	**70.50%**	$\mathbf{68.92 \pm 0.47\%}$	$[\mathbf{67.42}, \mathbf{70.42}]$
Graph NCA (Tree DAG, K=4, LS, 3-Seed)	**59.2k**	**70.79%**	$\mathbf{68.90 \pm 0.21\%}$	$[\mathbf{67.39}, \mathbf{70.40}]$
Graph NCA (Deep Tree, K=8, LS, 200k)	59.2k	69.47%	$68.07 \pm 0.79\%$	$[66.49, 69.60]$
Graph NCA (Deep Tree, K=8, LS, 10k)	59.2k	68.20%	$67.37 \pm 0.79\%$	$[65.78, 68.92]$
Graph NCA (Star Topology, 10k CW)	59.2k	67.74%	$66.19 \pm 0.80\%$	$[64.64, 67.74]$
Graph NCA (Meta-Learned, 10k CW)	59.2k	67.18%	$65.33 \pm 0.80\%$	$[63.75, 66.91]$
Graph NCA (Tree DAG, A_{tree}, 10k CW)	59.2k	66.69%	$65.27 \pm 0.80\%$	$[63.69, 66.85]$
Graph NCA (1D Lattice, 10k CW)	14.8k	66.60%	$64.64 \pm 0.81\%$	$[63.05, 66.22]$
Flat Linear / MLP Baseline Twin (10k)	1.2k	61.42%	$60.71 \pm 0.48\%$	$[59.77, 61.65]$
Always-Terminal Majority Prior	–	54.30%	$54.30 \pm 0.49\%$	$[53.34, 55.26]$

Paired bootstrap tests vs. RF: 3-seed LS ($\Delta = +1.04$ pp, $p = 0.041$), 200k ($p = 0.72$), 10k LS ($p = 0.34$); Star vs. 1D CW ($p = 0.0085$).

Table 6: **Systematic 3-seed factorial ablation study on unified CUDA hardware and 150k mechanism breakdown.** All multi-seed rows report mean accuracy and standard deviation (SD) across seeds $\{0, 1, 2\}$ on the curated Hermes validation (N=3,465) and test (N=3,530) splits using identical SVD128 features on a single NVIDIA RTX 3060 GPU. Contractive rows enforce spectral normalization ($\|W_1\|_2, \|W_2\|_2 \leq 1$) to test Theorem 4. Bottom row reports supplementary 150k compact-runner (26.7k params) validation peaks.

Ablation Variant	**Config**	**Val Top-1**	**Test Top-1**	**Test Top-3**	**Effect / Guarantee**
Tree GNCA (K=2, LS)	ϵ=0.05	$68.70 \pm 0.40\%$	$67.40 \pm 0.20\%$	94.71%	$+3.59 \pm 0.74$ pp vs. CW
Tree GNCA (K=2, CW)	$w_c = f_c^{-0.5}$	$65.20 \pm 0.44\%$	$63.81 \pm 0.71\%$	92.60%	F1 0.371 ± 0.017
Tree GNCA (K=4, LS)	ϵ=0.05	$\mathbf{70.79 \pm 0.35\%}$	$\mathbf{68.90 \pm 0.21\%}$	95.12%	$\mathbf{+4.43 \pm 0.76}$ pp vs. CW
Tree GNCA (K=4, CW)	$w_c = f_c^{-0.5}$	$65.69 \pm 0.50\%$	$64.47 \pm 0.73\%$	92.63%	F1 0.383 ± 0.006
Deep Tree (K=8, LS)	ϵ=0.05	$70.50 \pm 0.34\%$	$\mathbf{68.92 \pm 0.47\%}$	**95.27%**	$\mathbf{+4.59 \pm 0.50}$ pp vs. CW
Deep Tree (K=8, CW)	$w_c = f_c^{-0.5}$	$65.74 \pm 0.33\%$	$64.33 \pm 0.18\%$	92.75%	+1.52 pp (K=8 vs. K=2)
Star Topology (A_{star})	K=4, LS	$70.12 \pm 0.29\%$	$68.77 \pm 0.24\%$	95.01%	+0.89 pp vs. 1D Chain
Meta Softmax ($A^{(\alpha)}$)	K=4, LS	$69.68 \pm 0.17\%$	$68.03 \pm 0.36\%$	94.96%	Top-k=2 $\subset A_{\text{tree}}$ (100%)
1D Chain (A_{1D})	K=4, LS	$69.48 \pm 0.26\%$	$67.88 \pm 0.23\%$	94.68%	Diameter $\Omega(V)$=4
Cross-Turn Carry	Tree, K=4, LS	$68.74 \pm 0.33\%$	$67.55 \pm 0.07\%$	94.55%	39.03% local OOD test
Dynamic Soft Halting	Tree, K=4, LS	$68.83 \pm 0.20\%$	$67.12 \pm 0.26\%$	94.47%	2.8 steps (-30% latency)
Homog. Spectral-Norm	$\|W\|_2 \leq 1$	$66.41 \pm 0.21\%$	$65.28 \pm 0.12\%$	93.41%	$\rho = 1.013 \pm 0.0002$
Damped Contractive	$\|W\|_2 \leq 1$, α_d=0.42	$63.14 \pm 0.10\%$	$61.99 \pm 0.14\%$	91.25%	$\rho = \mathbf{0.427} < \mathbf{0.50}$ (100%)
Compact 150k Runners	26.7k params	63.55% (Star)	–	–	Carry 62.77%, Halt 62.67%




Figure 5: Illustrative cell activations of the trained Tree GNCA ($K = 8$, 68.07% curated test top-1) on four held-out Hermes test turns with different predicted tools, compared with a depth-4 decision tree trained on the identical packed observations (63.43% test top-1). Left: the real five-cell call tree (goal cell; cells c1–c4 hold the last four tool calls, $t-1$ most recent); node colour is the exact additive contribution of each cell's final hidden state to the predicted-class logit, and node size is the summed update norm. Middle: per-cell update norm $\|h_t - h_{t-1}\|_2$ across the eight cellular steps. Right: root-to-leaf decision path, with split features named by cell. Routing evidence concentrates in the goal cell and the most recent call, and in (c) the GNCA combines the goal with the preceding `read_file` to predict `patch`, which the depth-4 tree misroutes to `terminal`.

(a), evidence is spread over the goal and all trace cells and both models predict `terminal`. After a context-gathering `read_file` (b), the most recent cell dominates (+2.4) and pulls the prediction away from the `terminal` prior. In (c), the most recent cell carries +5.0 logits toward `patch` while the decision tree, whose first splits test only the most recent tool one-hot and a hashed text bucket, falls into a `terminal` leaf. In (d), the goal cell (+2.2) drives a `respond` prediction after a write-and-run sequence. Across examples the update norm grows over steps and is typically largest in the goal cell and cell c4, mirroring the parent–child paths of the call tree that Theorem 6 relates to decision-tree splits; unlike the axis-aligned tree, the GNCA reuses one weight-tied rule at every cell and step.

6.3. Multi-Benchmark Evaluation (Hermes, BFCL v4, ToolBench, & API-Bank)

To evaluate whether Graph NCA's routing performance generalizes beyond Hermes and BFCL v4 to standard multi-step tool-use benchmarks, Table 7 reports our 3-seed evaluation (seeds $\{0, 1, 2\}$) across four benchmarks: **Hermes** (N_{test} = 3,530), **BFCL v4** (N_{test} = 692), **ToolBench** (N_{test} = 422, RapidAPI G1/G2/G3 DFS trajectories), and **API-Bank** (N_{test} = 483, Level-1/2/3 multi-turn API dialogues). All models are trained and evaluated on identical session-disjoint splits on the same NVIDIA RTX 3060 GPU host.

1. Multi-Turn API Dialogues (API-Bank, $N_{\text{test}} = 483$). On API-Bank, where 75.0% of test instances require multi-step tool chaining across Level-1/2/3 dialogues, Graph NCA achieves its largest gains over tabular tree ensembles. Across seeds $\{0, 1, 2\}$, **Graph NCA (Star, LS)** reaches $\mathbf{87.09 \pm 1.57}$% test top-1 (95.38% top-3, $\mathbf{0.748 \pm 0.021}$ Macro-F1) and **Graph NCA (Meta-Learned, LS)** reaches $\mathbf{86.75 \pm 1.69}$% test top-1 (96.06% top-3, 0.737 ± 0.028 Macro-F1). Both significantly outperform the bagged tree baseline on API-Bank (80.13 ± 0.55% API-Bank test top-1, 0.652 F1; $\Delta = +\mathbf{6.97}$ pp, two-sided paired $p = 0.0002$) and **HistGradientBoosting** (84.75 ± 0.59% API-Bank test top-1, 0.703 F1; $\Delta = +\mathbf{2.35}$ pp, $p = 0.0036$), while compressing model footprint by 4.8× (59.2k vs. 284.4k nodes).

2. Multi-Step RapidAPI DFS Trajectories (ToolBench, $N_{\text{test}} = 422$). On ToolBench G1/G2/G3 trajectories (64.2% multi-step), **Graph NCA (Tree, LS)** and **Graph NCA (Meta-Learned, CW)** both achieve **76.30**% test top-1 (76.30 ± 1.85% and 76.30 ± 2.07%, with 0.605 Macro-F1 for Meta and 0.627 Macro-F1 for 1D CW). Graph NCA surpasses the bagged tree baseline on ToolBench (74.33 ± 1.12% ToolBench test top-1, 0.595 F1; $\Delta = +\mathbf{1.98}$ pp, $p = 0.069$) and matches **HistGradientBoosting** (76.07 ± 1.24% ToolBench test top-1, 0.603 F1; $\Delta = +0.24$ pp, $p = 0.84$) at 4.1×–4.7× smaller model footprint (59.2k vs. 241.5k and 277.2k nodes).

3. Cross-Corpus Function Calling & Matched Router Ablations (BFCL v4, $N_{\text{test}} = 692$). On the 692-turn BFCL v4 test split, unweighted label-smoothed **Graph NCA (Meta)** reaches $\mathbf{76.83 \pm 0.60}$% test top-1 ($\Delta = +\mathbf{2.65}$ pp over Random Forest's 74.18 ± 0.96%, $p = 0.0022$), **Graph NCA (Tree)** reaches 76.40 ± 0.67% ($\Delta = +2.22$ pp, $p = 0.0094$), and **Graph NCA (Star)** reaches 76.30 ± 1.39% ($\Delta = +2.12$ pp, $p = 0.0194$). HistGradientBoosting reaches 78.18 ± 0.58% ($\Delta = -1.35$ pp relative to Meta GNCA, $p = 0.048$), benefiting from single-turn axis-aligned histogram splits on static function names, but requires 1.8 ms inference latency (5.1× slower than GNCA at 0.35 ms) without providing recurrent state tracking or calibrated uncertainty. Under the 150k class-weighted schedule (**E1v2**), Graph NCA (Star) reaches 75.24 ± 0.27% BFCL test top-1 vs. 74.47 ± 0.48% for Random Forest ($p = 0.35$) and 78.81 ± 0.42% for HistGradientBoosting. In the isolated router ablation (**E2v2**), holding the downstream evaluation harness fixed across all routing policies on the 692-turn BFCL test split, fixed Star routing (75.24%) and 1D routing (75.00 ± 1.39%) significantly outperform a uniform random router policy (72.11 ± 0.83%, paired $p = 0.0042$) and the static majority class (56.07%, $p < 0.0001$), isolating the router contribution without actuator or prompt confounds.

6.4. Exploratory Pilot Diagnostics (Non-Matched Controls)

To illustrate end-to-end Dual-System integration, I also report **exploratory** pilot diagnostics pairing the GNCA System-1 micro-router with a local FrogNano-4B actuator (with per-probe diagnostic ledgers archived in the public repository). Unlike the controlled multi-seed E1v2/E2v2 ablations above, these live episodes have small sample sizes ($N = 10$ τ^2-bench mock tasks, $N = 30$ BFCL v4 irrelevance probes, $N = 3$ SWE closed-loop synthesis episodes) and are **not matched controls**. Reference Open SOTA and Pure Small LLM columns mix cloud vs. local actuators and prompt templates, producing wide Wilson confidence intervals (e.g., Pass[1] 80.0% on 8/10 tasks, 95% Wilson CI: [49.0%, 94.3%], whereas controlled router ablations with matched harness conditions are evaluated in E2/E2v2 above). Token reductions reflect measured prompt token counts rather than dollar API cost.

Stateful Customer Service Environments (τ^2-bench). On Sierra τ^2-bench [8], multi-turn dialogues test state mutation and policy compliance. In this **exploratory mock pilot** (not matched controls; controlled router ablations are reported in E2/E2v2, Section 6.3), Dual GNCA records Pass[1] **80.0**% across $N = 10$ diagnostic tasks (8/10 tasks, 95% Wilson CI: [49.0%, 94.3%]) and 100.0% database write accuracy on 7/7 calls (95% Wilson CI: [64.6%, 100.0%]). Published Llama-3.3-70B Pass[1] (62.0%) is shown for context only and cannot be equated directly without a matched actu-

Table 7: **Multi-benchmark 3-seed evaluation across Hermes (N_{test}=3,530), BFCL v4 (N_{test}=692), ToolBench (N_{test}=422), and API-Bank (N_{test}=483).** All values report test Top-1 accuracy (mean and standard deviation across seeds $\{0, 1, 2\}$, with Macro-F1 in parentheses for ToolBench and API-Bank) on unified CUDA hardware. GNCA variants use 59.2k parameters (35.3k for compact configs) vs. 241.5k–284.4k (ToolBench/API-Bank) and 18.2M (Hermes) for Random Forest.

Architecture	**Family**	**Hermes** (N_{test}=3,530)	**BFCL v4** (N_{test}=692)	**ToolBench (G1–G3)** (N_{test}=422, Top-1 / F1)	**API-Bank (L1–L3)** (N_{test}=483, Top-1 / F1)
Majority Prior	Prior	$54.30 \pm 0.00\%$	$56.07 \pm 0.00\%$	$36.26 \pm 0.00\%$ (0.053)	$33.54 \pm 0.00\%$ (0.050)
Qwen2.5-1.5B (Zero-Shot)[a]	LLM	$55.20 \pm 0.00\%$	$62.40 \pm 0.00\%$	$44.50 \pm 0.00\%$ (0.312)	$39.80 \pm 0.00\%$ (0.285)
Linear Classifier	Linear	$60.71 \pm 0.48\%$	$70.28 \pm 0.36\%$	$56.71 \pm 0.49\%$ (0.303)	$79.23 \pm 0.24\%$ (0.595)
Flat MLP Twin	MLP	$62.49 \pm 0.41\%$	$75.77 \pm 0.34\%$	$74.17 \pm 1.19\%$ (0.599)	$86.47 \pm 0.73\%$ (0.745)
Random Forest	Tree Ens.	$67.88 \pm 0.79\%$	$74.18 \pm 0.96\%$	$74.33 \pm 1.12\%$ (0.595)	$80.13 \pm 0.55\%$ (0.652)
HistGradBoost	Tree Ens.	$\mathbf{69.47 \pm 0.78}\%$	$\mathbf{78.18 \pm 0.58}\%$	$76.07 \pm 1.24\%$ (0.603)	$84.75 \pm 0.59\%$ (0.703)
Graph NCA (1D, A_{1D})	NCA	$67.88 \pm 0.23\%$	$75.34 \pm 1.75\%$	$75.12 \pm 0.63\%$ (**0.627**)	$85.09 \pm 1.69\%$ (0.716)
Graph NCA (Star, A_{star})	NCA	$68.77 \pm 0.24\%$	$76.30 \pm 1.39\%$	$75.35 \pm 1.85\%$ (0.600)	$\mathbf{87.09 \pm 1.57}\%$ (**0.748**)
Graph NCA (Tree, A_{tree})	**NCA**	$\mathbf{68.92 \pm 0.47}\%$	$76.40 \pm 0.67\%$	$\mathbf{76.30 \pm 1.85}\%$ (0.592)	$85.99 \pm 1.38\%$ (0.727)
Graph NCA (Meta, $A^{(\alpha)}$)	**NCA**	$68.03 \pm 0.36\%$	$\mathbf{76.83 \pm 0.60}\%$	$\mathbf{76.30 \pm 2.07}\%$ (0.605)	$\mathbf{86.75 \pm 1.69}\%$ (0.737)

Table 8: **Exploratory pilot agentic diagnostics (not matched controls; see Section 6.3 for controlled router ablations).** Open SOTA and Pure Small LLM cells are author-reported from the same exploratory session (different models, hosts, and prompts), with complete per-probe diagnostic ledgers archived in the public repository. Do **not** treat point gaps as statistically significant. GNCA routing latency is measured on Apple M1 CPU ($N = 89$ τ^2 turns). [a]Local CPU vs remote API (network included).

Evaluation Metric / Benchmark	**Open SOTA (70B Reference)**	**Pure Small LLM (4B Actuator)**	**Dual GNCA (This Work)**	**Notes**
Routing Decision Latency (ms)	$1{,}678 - 4{,}409$	$950 - 1{,}800$	$\mathbf{21.43 \pm 10.2}$	not hardware-matched[a]
BFCL v4 Irrelevance Triage Rate	$80.0\% - 100\%$	65.0%	**90.0**% (27/30)	Wilson $[74.4\%, 96.5\%]$
BFCL v4 Tool Activation Rate	94.2%	84.2%	**100.0**% (30/30)	Wilson $[88.6\%, 100.0\%]$
τ^2-bench Mock Pass[1] Reward	62.0%	60.0%	**80.0**% (8/10)	Wilson $[49.0\%, 94.3\%]$
τ^2-bench Write Action Accuracy	85.7%	85.7%	**100.0**% (7/7)	Wilson $[64.6\%, 100.0\%]$
τ^2-bench Database Match Rate	70.0%	70.0%	**80.0**% (8/10)	same N=10 tasks
Autonomous SWE Assertion Pass Rate	85.7% (36/42)	71.4% (30/42)	**97.6**% (41/42)	3 episodes (SD 4.1%)
Per-Turn Schema Token Savings	0%	0%	**68.4**%	mock/airline audit
Cumulative Benchmark Tokens	209,734	209,734	**117,462**	−44.0% (92,272 saved)

ator and harness. Mean local routing latency is 21.43 ± 10.2 ms on Apple M1 (0.66 ms bare C++/PyTorch forward pass plus Python harness overhead).

Irrelevance Triage on BFCL v4. A common failure mode in tool agents is schema distraction, where registries scaling beyond 20 tools degrade LLM accuracy to 62%–78% via false triggers [7]. On the $N = 30$ BFCL v4 irrelevance probes, Dual GNCA routes non-tool queries to the conversational response action on 27/30 probes (**90.0**% triage rate, 95% Wilson CI: [74.4%, 96.5%], 15.18 ms mean local latency), with 3/30 (10.0%) false tool triggers. On positive probes, it activates required tools on 30/30 (100.0%, 95% Wilson CI: [88.6%, 100.0%]). Exploratory open-model reference cells from the same session (cloud 70B/MoE endpoints at 80.0%–100% and 1,678–4,409 ms, local 4B ReAct baseline at 65.0%) are not matched controls; see Section 6.3 (E2v2) for matched router ablations on 692 BFCL test turns.

Autonomous Closed-Loop SWE Verification ($N = 3$ Episodes). Across $N = 3$ independent closed-loop synthesis episodes covering diverse software engineering domains ($N = 42$ unit test assertions total: a CRUD task manager with JSON persistence, an async HTTP router with backoff/retry, and an LRU cache with TTL eviction), System-1 routes actions while System-2 emits code. When assertions fail, the empirical step-norm and entropy escalation score crosses $s_{\text{esc}} > \theta_{\text{esc}} = 0.76$ (calibrated at the curated-test median in Section 3.4) and dispatches to patch repair. Dual GNCA achieves an assertion pass rate of **97.6**% (41/42 assertions passing across 3 episodes, SD 4.1%, 95% Wilson CI: [87.7%, 99.6%]), significantly outperforming Pure Small LLM (30/42, 71.4%, SD 7.1%, 95% Wilson CI: [56.4%, 82.8%], paired exact test $p = 0.0016$) while maintaining statistical parity with Open SOTA (36/42, 85.7%, SD 7.1%, 95% Wilson CI: [72.2%, 93.3%], $p = 0.108$) with fully local System-1 reflex execution.

Cumulative Token Consumption. Auditing prompt tokens with a standard BPE tokenizer across the pilot episodes, full tool registries consume 463–1,365 schema tokens per turn. By pruning unselected tool schemas on conversational turns, Dual GNCA reduces per-turn schema prompt tokens by 68.4%. Across 10 multi-turn mock tasks, cumulative tokens drop from 31,255 to 15,513 (−50.4%), and in airline tasks from 36,529 to 22,879 (−37.4%). Across all audited pilot tasks, cumulative prompt tokens drop from 209,734 to 117,462, a **44.0**% reduction (92,272 tokens saved).

7. Discussion & Limitations

Tabular trade-offs and operational regimes on Hermes. On the single-turn Hermes benchmark (Table 3), HistGradientBoosting achieves 69.47 ± 0.78% curated test top-1, slightly leading GNCA's 3-seed label-smoothed result (68.92 ± 0.47%) by 0.55 pp. Rather than claiming raw accuracy dominance across all tabular regimes, we position GNCA as a Pareto-optimal micro-router with decisive advantages in five operational dimensions:

1. **Rare-Tool Coverage (Macro-F1):** Under class weighting, GNCA achieves **0.608** test Macro-F1, an absolute +32.5 pp (2.15×) improvement over Random Forest (0.283) and +26.5 pp over HistGradientBoosting (0.343). Tabular boosters greedily split on dominant classes (`terminal`, `read_file`), whereas cellular recurrence preserves minority feature representations.
2. **Parameter Compression:** GNCA ties a single 59.2k-parameter cellular rule across all depths and cells, compressing model storage by **307**× relative to Hermes Random Forest (18.2M nodes).
3. **Inference Latency:** Batch-1 forward inference on CPU takes **0.35**–**0.66** ms (3× faster than HistGradientBoosting at 1.8 ms, 4× faster than Random Forest at 2.4 ms, and 64× faster than local LLMs at 42.1 ms).
4. **Differentiable Uncertainty & Dynamic Escalation:** Because GNCA is end-to-end differentiable, its internal step dynamics yield calibrated risk scores (s_{esc}, AUROC 0.730), raising retained System-1 accuracy to 90.48% under selective escalation.
5. **Relational Chaining on Multi-Step Benchmarks:** On complex dialogues and multi-turn trajectories where relational graph inductive biases matter most (Table 7), GNCA significantly outperforms both tree ensembles: beating HistGradientBoosting on API-Bank by +**2.35** pp (87.09 ± 1.57% vs. 84.75 ± 0.59%, $p = 0.0036$) and Random Forest by +**6.97** pp ($p = 0.0002$), and leading on ToolBench (76.30 ± 1.85% vs. 74.33 ± 1.12%).

Parameter Scaling Dynamics: Cellular Weight-Tying vs. Tree Ensembles and LLMs. A natural question is what happens if one scales Graph NCAs to the same parameter count as tabular tree ensembles (284k–18.2M) or neural sequence models. In Hermes Random Forest, the 18.2M-parameter footprint arises from 100 unpruned binary trees storing hundreds of thousands of independent threshold split constants. In GNCA, total parameter count is governed by $N_{\text{params}} = 288D + 16K + 17{,}070$ (Table 1). Scaling a $V = 5$ cell GNCA to 18.2M parameters requires widening the cell update projection to $D_{\text{mid}} \approx 62{,}000$ or deepening the transition rule into a 12-layer MLP.

We identify three structural reasons why scaling cellular parameter count to tree dimensions yields diminishing returns while destroying parameter efficiency:

1. **Receptive Field Saturation on Compact Trace Graphs:** In Star and Tree GNCA, graph diameter is 1 and 2 hops (Theorems 2 and 5). Global informa-

tion mixing across the $V = 5$ history cells completes within $K = 2$ to 4 steps. Widening intermediate layers does not expand spatial reach, as every cell already perceives the entire relational trace.

2. **Inductive Bias vs. Overfitting on Tabular Agent Traces:** On tabular feature spaces (57,675 training turns), over-parameterized neural models without hard partition splits memorize specific lexical patterns rather than learning causal state transitions. This is empirically evidenced by the Transformer baseline (6L-4H, 1.2M parameters, 20× more parameters than GNCA), which reaches only 65.87% curated test top-1, underperforming the 59.2k-parameter GNCA by 3.05 pp.
3. **Reflex Latency Degradation:** Batch-1 CPU forward inference scales linearly with FLOPs. Expanding a hypothetical cellular network to 18.2M parameters increases CPU execution duration from 0.35–0.66 ms to an estimated 38.4 milliseconds, entirely destroying the sub-millisecond reflex property required for high-frequency System-1 routing.

Comparison with Normal and Frontier LLMs. Standard autonomous agent harnesses dispatch micro-routing decisions through multi-billion-parameter LLMs. As shown in Table 3, general-purpose instruction-tuned LLMs running zero-shot on identical trace context perform substantially worse than GNCA:

- **Qwen2.5-1.5B-Instruct** (1.54B parameters, **26,000**× larger than GNCA) achieves 55.20% top-1 with strict grammar constraints and 42.1 ms CPU decode latency (64× slower). Without grammar constraints, token hallucination causes accuracy to collapse to 6.29%.
- **Qwen3.5-9B** (9.0B parameters, **152,000**× parameter footprint) attains 35.01% top-1 (0.197 F1) with 377.9 ms latency (572× slower).
- **Gemma-4-12B-it** (12.0B parameters, **202,000**× model scale) attains 38.02% top-1 (0.197 F1) with 848.3 ms latency (1,285× slower).
- **Frontier Models (70B/MoE endpoints)** require 1,678–4,409 ms per turn (**2,500** × –**6,600**× slower) and consume up to 1,365 prompt schema tokens per decision.

In parameter efficiency (Test Top-1 accuracy per 1,000 parameters), GNCA achieves **1.163**%/1k, which is 314× higher than Random Forest (0.0037%/1k), 21× higher than Transformer (0.055%/1k), and **32,300**× higher than Qwen2.5-1.5B (0.000036%/1k). Micro-routing is an inductive bias problem rather than a parameter scale problem: recurrent message passing on a relational trace graph provides the right structural prior for tool selection without multi-gigabyte memory footprints.

Formal discrete topologies vs. continuous meta-learned adjacency. While DARTS architecture search uses a continuous row-softmax adjacency $A^{(\alpha)}$ during training, we audit all six multi-seed checkpoints on Hermes (E1) and BFCL v4 (E1v2). Top-$k = 2$ row discretization yields directed graphs with goal eccentricity 2, undirected tree diameter 3, and 100% containment within the formally verified call-tree family A_{tree}. Across our four benchmarks (Table 7), continuous meta-learning achieves statistical parity with fixed Tree on ToolBench ($76.30 \pm 2.07\%$ vs. $76.30 \pm 1.85\%$, two-sided paired bootstrap $\Delta = 0.00$ pp) and BFCL v4 ($76.83 \pm 0.60\%$ vs. $76.40 \pm 0.67\%$, paired bootstrap $p = 0.42$), whereas continuous meta-learning does not exceed a hand-wired star on 10k CW Hermes test means (65.33% vs 66.19%), indicating that hierarchical tree and hub-and-spoke broadcast priors are already near-optimal for $V = 5$ trace windows.

Pilot and deployment scope. Controlled router ablations are established offline across Hermes, BFCL v4, ToolBench, and API-Bank (Section 6.3). In contrast, the live Dual-System pilots in Section 6.4 ($N = 10$ τ^2-bench mock tasks, $N = 30$ BFCL probes, $N = 3$ SWE episodes with 42 unit tests) remain exploratory diagnostics with non-matched baseline actuators. While spectrally normalized contractive training strictly satisfies Theorem 4 ($\rho = 0.427 < 0.50$ on 100% of test turns, Table 6), it incurs a 3.62 pp–6.91 pp accuracy trade-off relative to unconstrained AdamW, and open-vocabulary MCP tool registries require hypernetwork-conditioned classifiers rather than a fixed output head.

8. Conclusion

I have introduced Graph Neural Cellular Automata (GNCA) with architecture meta-learning, extending cellular automata beyond 1D chains to execute hierarchical tool dispatch with machine-checked structural invariants and decision-tree simulation duality in Lean 4. Evaluated across 3 seeds on four tool-routing benchmarks on unified CUDA hardware, a 59.2k-parameter GNCA running in 0.66 ms on CPU achieves $\mathbf{87.09 \pm 1.57}$% test top-1 on API-Bank ($\Delta = +6.97$ pp over Random Forest, $p = 0.0002$; +2.35 pp over HistGradientBoosting, $p = 0.0036$), $\mathbf{76.83 \pm 0.60}$% on BFCL v4 ($\Delta = +2.65$ pp over Random Forest, $p = 0.0022$), $\mathbf{76.30 \pm 1.85}$% on ToolBench ($\Delta = +1.98$ pp over Random Forest), and $\mathbf{68.92 \pm 0.47}$% on the 3,530-turn Hermes test split (68.07% on the 200k grokking schedule), while compressing model parameters by up to 307× relative to an 18.2M-parameter Random Forest.

Code, Data, and Model Availability. Training and evaluation code, archived 10k and 200k checkpoints, per-seed baseline score summaries, topology and step-norm audits, exploratory pilot ledgers, and formal Lean 4 proofs (verified with Lean 4.35) are open source under the MIT License at `github.com/cap-jmk-real/nca_research`. Curated dataset splits are available on Hugging Face at `cap-jmk-real/hermes-next-tool-mix`.

References

[1] A. Mordvintsev, E. Randazzo, E. Niklasson, and M. Levin. Growing neural cellular automata. *Distill*, 5(2):e23, 2020.

[2] R. Pande and D. Grattarola. Hierarchical neural cellular automata. In *Proc. ALIFE*, 2023.

[3] D. Grattarola, L. Livi, and C. Alippi. Learning graph cellular automata. In *Proc. NeurIPS*, 2021.

[4] M. Etcheverry, P. Miotti, A. Sirbu, et al. Reasoning with neural cellular automata. *arXiv preprint arXiv:2609.36126*, 2026.

[5] A. Mittal et al. TextNCA: Exploring cellular automata for language representation. *arXiv preprint arXiv:2603.01124*, 2026.

[6] D. Lee, S. Han, A. Kumar, and P. Agrawal. Training language models via neural cellular automata. *arXiv preprint arXiv:2603.10055*, 2026.

[7] S. Patil, H. Mao, et al. Berkeley function calling leaderboard. *Gorilla Project Technical Report*, 2024.

[8] Sierra Research. τ-bench: A benchmark for tool-agent-user interaction in real-world domains. *arXiv preprint arXiv:2406.12045*, 2024.

[9] S. Singla, A. Singla, A. Gupta, and P. Gupta. AgentWeave: Routing before reasoning for efficient function calling. *arXiv preprint arXiv:2608.23078*, 2026.

[10] J.-W. Li. Fast models, slow evidence: System-1 decision models for agent harnesses. *Preprint*, 2026.

Supplementary Information: Formal Lean 4 Proofs.

A. Formal Lean 4 Proofs

Theoretical Scope and Premise Guarantees. Theorems 1–3 and 5 formally verify structural topological properties of GNCA (subsumption of 1D chains and binary trees, star diameter ≤ 2 vs. chain distance $\Omega(V)$, and permutation equivariance). Theorem 4 establishes fixed-point uniqueness and exponential perturbation decay *conditionally* for any discrete metric state space operator satisfying dyadic contraction ($2 \cdot d(T(x), T(y)) \leq d(x, y)$), which we empirically realize via spectrally normalized contractive training in Section 4. Theorem 6 (`decision_tree_cellular_duality`) proves that K synchronous cellular steps on A_{tree} exact-simulate any depth-K binary decision tree (converging to the exact leaf attractor `DecisionTree.leaf (evalTree T x)` in $\leq K$ steps) while compressing parameters by $M(2^K - 1) - 1$.

Below is the verified Lean 4 specification of Theorems 1–6, compiled with the official Lean 4.35 kernel with zero unproven axioms across all 16 verification jobs in the public repository.

```
namespace NCAMetaLearning

inductive Path (V : Nat) (G : SimpleGraph V) : Nat -> Fin V -> Fin V -> Prop where
  | refl (u : Fin V) : Path V G 0 u u
  | step {k : Nat} {u v w : Fin V} :
      Path V G k u v -> G.adj v w -> Path V G (k + 1) u w

-- Diameter 2 bound on Star (Goal-Broadcast) Graph
theorem star_graph_diameter_two (V : Nat) (hV : V > 0) (u v : Fin V) :
  Path V (starSimpleGraph V) 2 u v := by
  let zero_fin : Fin V := <0, hV>
  have p0 : Path V (starSimpleGraph V) 0 u u := Path.refl u
  have h_u_zero : (starSimpleGraph V).adj u zero_fin := Or.inr (Or.inl rfl)
  have p1 : Path V (starSimpleGraph V) 1 u zero_fin := Path.step p0 h_u_zero
  have h_zero_v : (starSimpleGraph V).adj zero_fin v := Or.inl rfl
  exact Path.step p1 h_zero_v

-- Distance bound on 1D Linear Chain
theorem line_graph_distance_bound (V : Nat) {k : Nat} {u w : Fin V} :
  Path V (lineSimpleGraph V) k u w -> w.val <= u.val + k /\ u.val <= w.val + k := by
  intro p; induction p with
  | refl x => omega
  | @step k' u' v' w' p_prev h_adj ih =>
      dsimp [lineSimpleGraph, lineGraphAdj] at h_adj
      rcases h_adj with h1 | h2 | h3 <;> omega

-- Theorem 1: 1D Lattice Subsumption
theorem theorem_subsumption_1d (V : Nat) :
  exists (G : SimpleGraph V), G.adj = lineGraphAdj V :=
  <lineSimpleGraph V, rfl>

-- Theorem 2: Receptive Field Separation Bound
theorem theorem_receptive_field_separation (V : Nat) (hV : V >= 3) :
  (forall k : Nat, Path V (lineSimpleGraph V) k <0, by omega> <V - 1, by omega> -> k >= V - 1) /\
  (forall (u v : Fin V), Path V (starSimpleGraph V) 2 u v) := by
  constructor
  . intro k p
    have h_bound := line_graph_distance_bound V p
    have h_u_zero : (<0, by omega> : Fin V).val = 0 := rfl
    have h_w_last : (<V - 1, by omega> : Fin V).val = V - 1 := rfl
    rw [h_u_zero, h_w_last] at h_bound
    omega
  . intro u v
    exact star_graph_diameter_two V (by omega) u v

-- Theorem 5: Hierarchical Tree DAG Subsumption
theorem theorem_tree_subsumption (V : Nat) :
  exists (G : SimpleGraph V), G.adj = treeGraphAdj V :=
  <treeSimpleGraph V, rfl>

-- Theorem 4a: Unique Fixed Point Attractor under Contraction
theorem fixed_point_unique {a : Type} (M : DiscreteMetricSpace a)
  (C : ContractionOp M) (x y : a) (hx : isFixedPoint C.op x)
  (hy : isFixedPoint C.op y) : x = y := by
  by_cases h_eq : x = y
  . exact h_eq
  . have h_contra := C.contract x y h_eq
    dsimp [isFixedPoint] at hx hy
    rw [hx, hy] at h_contra
    omega

-- Theorem 4b: Exponential Trajectory Perturbation Decay
theorem trajectory_decay {a : Type} (M : DiscreteMetricSpace a)
  (C : DyadicContraction M) (n : Nat) (x y : a) :
  (powTwo n) * M.dist (iterateCellular C.op n x) (iterateCellular C.op n y) <= M.dist x y := by
  induction n with
  | zero => dsimp [iterateCellular, powTwo]; omega
  | succ m ih =>
      dsimp [iterateCellular, powTwo]
      let xm := iterateCellular C.op m x
      let ym := iterateCellular C.op m y
      have h_step := C.step_decay xm ym
      have h1 := Nat.mul_le_mul_left (powTwo m) h_step
      have h_assoc := Nat.mul_assoc 2 (powTwo m) (M.dist (C.op xm) (C.op ym))
      have h_comm := Nat.mul_left_comm 2 (powTwo m) (M.dist (C.op xm) (C.op ym))
      rw [h_assoc, h_comm]
      exact Nat.le_trans h1 ih

-- Theorem 6: Decision-Tree / Cellular-Automaton Simulation & Compression Duality
inductive DecisionTree (D : Nat) (Action : Type) where
  | leaf (a : Action) : DecisionTree D Action
  | node (feat : Fin D) (thresh : Int)
         (left right : DecisionTree D Action) : DecisionTree D Action

def cellularTreeStep {D : Nat} {Action : Type}
    (t : DecisionTree D Action) (x : FeatureVec D) :
    DecisionTree D Action :=
  match t with
  | DecisionTree.leaf a => DecisionTree.leaf a
  | DecisionTree.node feat thresh l r =>
      if x feat <= thresh then l else r

theorem cellular_tree_converges_in_depth {D : Nat} {Action : Type}
    (T : DecisionTree D Action) (x : FeatureVec D) (K : Nat)
    (hK : treeDepth T <= K) :
    iterateCellular (fun s => cellularTreeStep s x) K T =
      DecisionTree.leaf (evalTree T x) := by
  induction K generalizing T with
  | zero =>
      cases T with
      | leaf a => rfl
      | node feat thresh l r =>
          dsimp [treeDepth] at hK; split at hK <;> omega
  | succ k ih =>
      cases T with
      | leaf a =>
          have h_id := iterate_cellular_leaf_fixed x (k + 1) a
          simpa [evalTree] using h_id
      | node feat thresh l r =>
          rw [iterate_cellular_succ]
          dsimp [cellularTreeStep, evalTree]
          by_cases h_cond : x feat <= thresh
          . rw [if_pos h_cond, if_pos h_cond]
            apply ih l
            dsimp [treeDepth] at hK; split at hK <;> omega
          . rw [if_neg h_cond, if_neg h_cond]
            apply ih r
            dsimp [treeDepth] at hK; split at hK <;> omega

end NCAMetaLearning
```