Beyond 1D Grid Automata: Architecture Meta-Learning for Graph Neural Cellular Automata in Agent Execution Traces

Julian M. Kleber
Independent Researcher
ORCID: 0000-0001-5518-0932
julian.m.kleber@gmail.com

October 2026

Abstract

Autonomous software agents cycle through observation, internal reasoning, tool dispatch, and argument synthesis. While autoregressive Large Language Models (LLMs) excel at broad natural language planning, invoking multi-billion-parameter decoders for fine-grained routing and repetitive parameter extraction introduces severe latency bottlenecks, memory congestion, and token expense. In this paper, we demonstrate that Neural Cellular Automata (NCAs) can generalize far beyond rigid 1D lattices to serve as a high-throughput substrate for **hierarchical tool selection, argument slot binding, and execution verification**. We introduce **Graph Neural Cellular Automata (GNCA)** parameterized via continuous **architecture meta-learning**, enabling dynamic discovery of optimal spatial interaction topologies $\mathcal{G} = (\mathcal{V}, \mathcal{E}, A_\alpha)$ that bridge user goals, call stacks, and argument slots. To establish the mathematical foundations of this generalization, we formulate three core theorems governing topological subsumption, receptive field diameter separation, and permutation equivariance, and verify all proofs formally in the **Lean 4** interactive theorem prover with zero unproven axioms. Adhering to a strict 150,000-step AdamW training floor on curated agent execution traces, GNCA achieves 65.18% top-1 routing accuracy, matching full transformer baselines ($65.87 \pm 2.0\%$) and flat linear twins (60.71%), while outperforming compact autoregressive decoders (Qwen2.5-1.5B-Instruct at 6.29%). Across 10,000 bootstrap resamples and 21 registered experiment records, we show that meta-learned cellular graph dynamics provide an expressive, parameter-efficient substrate capable of sub-millisecond agent decision routing.

1 Introduction

Autonomous software agents operate as iterative closed-loop systems: observing environment feedback (compiler diagnostics, file diffs, test logs) and synthesizing next actions. In standard production deployments, this decision is almost universally handed to a causal language model. However, delegating every fine-grained step to a multi-billion-parameter LLM imposes critical bottlenecks:

1. **Latency & Memory Overhead:** Generating tokens autoregressively incurs high time-to-first-token and memory bandwidth pressure, throttling execution loops.
2. **Context Bloat:** Intermediate execution steps congest context windows with repetitive JSON formatting and syntax boilerplate.
3. **Rigid 1D Assumptions:** Initial cellular routing models restrict computation to 1D regular lattices ($L = 5$), ignoring that agent execution DAGs, call stacks, and tool arguments form multi-scale hierarchical relational structures.

Neural Cellular Automata (NCAs) [1] offer an alternative computational paradigm based on local, self-organizing update rules. While traditionally studied in continuous 2D domains for biological morphogenesis, texture generation, and self-repair, the core inductive biases of NCAs—iterative spatial message passing across discrete cells governed by uniform update rules—align naturally with structured sequential decision processes. Recent investigations (e.g., Mittal et al. [2]) probed token-level text NCAs, but their application to structured multi-action tool execution has remained limited to rigid sequential chains.

Contributions. In this paper, we extend Neural Cellular Automata beyond 1D topologies into a meta-learned graph framework for hierarchical agent routing. Specifically:

- We formulate **Graph Neural Cellular Automata (GNCA)**, replacing fixed 1D convolutional stencils with continuous **architecture meta-learning** over spatial interaction topologies $\mathcal{G} = (\mathcal{V}, \mathcal{E}, A_\alpha)$.
- We formulate a **hierarchical multi-head architecture** that jointly predicts the tool identifier, argument slot entity bindings, explicit abstain/irrelevance signals, and an uncertainty escalation threshold.

- We provide **machine-checked formal proofs in Lean 4** verifying that 1D lattices are strict topological submanifolds of GNCAs, proving an exponential diameter separation ($O(1)$ vs $\Omega(V)$ steps), and proving permutation equivariance of neighborhood perception.
- Across 21 registered experiment records and 10,000 bootstrap iterations on curated traces under a strict 150,000-step AdamW floor, GNCA matches full Transformer baselines (65.18% vs 65.87%) while executing in sub-millisecond wall time.

2 Related Work

Neural Cellular Automata. Mordvintsev et al. [1] introduced Growing Neural Cellular Automata, demonstrating that localized 1×1 convolutions combined with fixed Sobel filters can learn self-organizing pattern morphogenesis and damage recovery. Subsequent work extended NCAs to voxel synthesis and policy learning. Mittal et al. [2] introduced TextNCA for autoregressive token modeling. Our framework departs fundamentally from token generation: we construct a dynamic cellular graph representing agent execution states to perform hierarchical action and argument dispatch.

Tool Calling & Function Execution Benchmarks. Modern tool use is benchmarked via datasets such as the Berkeley Function Calling Leaderboard (BFCL) [3], NESTFUL, and SWE-bench. A central insight of these benchmarks is that action dispatch cannot be reduced to predicting a tool name: an agent must handle **irrelevance** (knowing when to abstain and output natural text), **argument slot binding** (mapping environment entities to function parameters), and **multi-turn coordination**.

Architecture Meta-Learning & Graph Bottlenecks. Standard GNNs frequently suffer from *oversmoothing* (representations collapsing to uniformity with depth), *oversquashing* (information bottlenecking from high-degree neighborhoods), and *underreaching* (insufficient message passing depth to bridge distant nodes). By casting topology optimization as bilevel architecture meta-learning, our framework discovers sparse relational graphs that balance local message passing with long-range goal broadcasting.

3 Task Formulation & Architecture

3.1 Hierarchical Action Formulation

Rather than treating next-tool selection as a flat 1-of-K classification problem, we formulate agent dispatch as synthesizing an action tuple:

$$\mathbf{a}_T = (y_{\text{tool}},\ \mathbf{y}_{\text{arg}},\ g_{\text{abstain}},\ \tau_{\text{escalate}}) \tag{1}$$

where:

- $y_{\text{tool}} \in \mathcal{V}$: Discrete tool identifier chosen from vocabulary $|\mathcal{V}| = 13$ (e.g., `read_file`, `edit_file`, `run_command`, `list_dir`, and terminal completion `respond`).
- $\mathbf{y}_{\text{arg}} \in \mathcal{A}$: Structured argument slot predictions, mapping discrete entity slots (e.g., target file indices in the active workspace context, subcommand buckets, or line range boundaries).
- $g_{\text{abstain}} \in [0, 1]$: Calibrated scalar logit indicating whether the agent should abstain from calling tools (handling irrelevance queries or conversational queries).
- $\tau_{\text{escalate}} \in [0, 1]$: Predictive execution risk and uncertainty score for routing turns to high-capacity frontier models or human verifiers.

3.2 Beyond 1D: Graph Neural Cellular Automata

In standard 1D NCAs, cell interactions are constrained to nearest neighbors $\{i-1, i, i+1\}$ along a rigid sequence grid. In agent workflows, however, execution traces exhibit multi-scale relational dependencies: the root goal directly conditions argument extraction, while recursive sub-agent tools branch hierarchically.

We generalize the cellular substrate to an arbitrary relational graph $\mathcal{G} = (\mathcal{V}, \mathcal{E}, A)$, where $|\mathcal{V}| = V$ nodes represent the goal anchor, historical execution states, and candidate argument slots. Each cell $i \in \mathcal{V}$ maintains a mutable state $h_i^{(t)} \in \mathbb{R}^H$ ($H = 16$), initialized to $h_i^{(0)} = \mathbf{0}$.

Continuous Spatial Perception. Given an adjacency matrix $A \in \mathbb{R}^{V \times V}$ and normalized graph Laplacian $L = I - D^{-1/2} A D^{-1/2}$, the spatial perception vector $p_i^{(t)} \in \mathbb{R}^{3H}$ aggregates local neighborhood features:

$$p_i^{(t)} = \left[h_i^{(t)},\ \sum_{j \in \mathcal{N}(i)} A_{ij} W_p h_j^{(t)},\ \sum_{j \in \mathcal{N}(i)} L_{ij} h_j^{(t)} \right] \tag{2}$$

where $W_p \in \mathbb{R}^{H \times H}$ is a shared linear projection.

Pointwise State Update. The perceived vector $p_i^{(t)}$ is concatenated with the cell's fixed observation $x_i \in \mathbb{R}^D$, forming $z_i^{(t)} = [p_i^{(t)}; x_i] \in \mathbb{R}^{3H+D}$. A shared pointwise update network computes the state delta $\Delta h_i^{(t)} \in \mathbb{R}^H$:

$$\Delta h_i^{(t)} = W_2\ \text{GELU}(W_1 z_i^{(t)} + b_1) + b_2 \tag{3}$$

where $W_1 \in \mathbb{R}^{D_{\text{mid}} \times (3H+D)}$, $W_2 \in \mathbb{R}^{H \times D_{\text{mid}}}$, and $D_{\text{mid}} = 64$.

Residual State Accumulation. Updates are applied residually across $K = 4$ cycles:

$$h_i^{(t+1)} = h_i^{(t)} + m_i^{(t)} \odot \Delta h_i^{(t)} \tag{4}$$

where $m_i^{(t)} \sim \text{Bernoulli}(p)$ ($p = 0.8$ during training; 1.0 at inference) enforces asynchronous cellular computation.




Figure 1: **Architectural schematic and topological comparison.** (a) Traditional 1D cellular automata restrict message passing to adjacent linear neighbors, requiring $\Omega(V)$ updates for global goal integration. (b) Our meta-learned Graph NCA framework relaxes topology via bilevel optimization ($A_{ij} = \sigma(W_\theta x_i^\top x_j)$), enabling direct goal-broadcasting with diameter ≤ 2 ($O(1)$ receptive field) and permutation-equivariant cellular state updates.

3.3 Architecture Meta-Learning on Spatial Topologies

To discover the optimal cellular interaction topology without manual heuristic tuning, we formulate a bilevel architecture meta-learning problem:

$$\begin{aligned} &\min_{\alpha \in \mathcal{A}} \mathcal{L}_{\text{val}}\left(\theta^*(\alpha);\ A_\alpha\right) \\ &\text{s.t. } \theta^*(\alpha) = \arg\min_{\theta} \mathcal{L}_{\text{train}}(\theta;\ A_\alpha) \end{aligned} \tag{5}$$

where the continuous architecture vector $\alpha \in \mathbb{R}^{|\mathcal{E}|}$ parameterizes the adjacency matrix via a softened softmax relaxation:

$$A_{ij}^{(\alpha)} = \frac{\exp(\alpha_{ij}/\tau)}{\sum_{k \in \mathcal{N}(i)} \exp(\alpha_{ik}/\tau)} \tag{6}$$

This search space continuously interpolates between a 1D linear chain (A_{1D}), a star goal-broadcast topology (A_{star}), and a hierarchical call-tree DAG (A_{tree}).

3.4 Hierarchical Multi-Head Readout

After K iterations, the spatial grid $\mathbf{H}^{(K)} \in \mathbb{R}^{V \times H}$ is decoded via four specialized readout heads:

1. **Tool Classification Head:**

$$\hat{y}_{\text{tool}} = \text{softmax}\left(W_{\text{tool}}\, \text{vec}(\mathbf{H}^{(K)}) + b_{\text{tool}}\right) \tag{7}$$

2. **Argument Slot Head:** Computes bilinear cross-cell interactions between the goal cell and active history cells:

$$\hat{\mathbf{y}}_{\text{arg}} = \text{softmax}\left(h_0^{(K)\top} W_{\text{arg}} h_{\text{last}}^{(K)}\right) \tag{8}$$

3. **Abstain / Irrelevance Gate:**

$$g_{\text{abstain}} = \sigma\left(w_{\text{abs}}^\top h_0^{(K)} + b_{\text{abs}}\right) \tag{9}$$

4. **Uncertainty & Escalation Score:** Evaluates Shannon entropy across tool logits and state variance across update steps:

$$\tau_{\text{escalate}} = \frac{\mathcal{H}(\hat{y}_{\text{tool}})}{\log|\mathcal{V}|} + \beta \frac{1}{V} \sum_{i=1}^{V} \|\Delta h_i^{(K-1)}\|_2 \tag{10}$$

4 Theoretical Foundations & Formal Verification

To guarantee mathematical rigor and verify that expanding 1D NCAs into meta-learned graph topologies preserves stability and expressivity, we establish three core theorems. All definitions and proofs have been formalised and verified in **Lean 4.35** with zero axioms.

Theorem 1 (Topological Subsumption)**.** *Let $\mathcal{T}_{\text{1D}}$ denote the 1D circular or boundary-padded regular cellular automaton lattice on V nodes. Then $\mathcal{T}_{\text{1D}}$ is a strict element of the Graph Neural Cellular Automata topology space $\mathcal{S}_{\text{GNCA}}$ under tridiagonal adjacency $A_{ij} = \mathbb{I}(|i-j| \leq 1)$.*

Theorem 2 (Receptive Field Diameter Separation)**.** *For any 1D local NCA with nearest-neighbor radius $r = 1$ over $V \geq 3$ nodes, propagating information from the goal node 0 to terminal node $V-1$ requires at least $k \geq V-1 = \Omega(V)$ cellular steps. In contrast, under the meta-learned goal-broadcasting star topology $\mathcal{G}_{\text{star}}$, any pair of nodes (u, v) has a path length of at most 2, achieving global receptive field integration in $O(1)$ steps.*

Theorem 3 (Neighborhood Permutation Equivariance)**.** *Let $\sigma \in \Pi_V$ be any bijective permutation on the node set $\mathcal{V}$, and let $\mathcal{G}_\sigma = \text{permuteGraph}(\mathcal{G}, \sigma)$. Then for all $i, j \in \mathcal{V}$, $j \in \mathcal{N}_{\mathcal{G}}(i) \iff \sigma(j) \in \mathcal{N}_{\mathcal{G}_\sigma}(\sigma(i))$, and graph paths commute with σ.*

Theorem 4 (State Contraction & Exponential Stability)**.** *Under a cellular update operator satisfying dyadic*

Lean 4 Kernel Verification Summary:

- `theorem_subsumption_1d`: **Verified (0 axioms)**
- `theorem_receptive_field_separation`: **Verified (0 axioms)**
- `theorem_tree_subsumption`: **Verified (0 axioms)**
- `neighborhood_equivariance`: **Verified (0 axioms)**
- `path_equivariance`: **Verified (0 axioms)**
- `fixed_point_unique`: **Verified (0 axioms)**
- `trajectory_decay`: **Verified (0 axioms)**

Lean package: `formal_proofs/NCAMetaLearning`

Figure 2: Formal verification status in the Lean 4 proof assistant.

Table 1: Primary evaluation on curated agent traces (13-tool vocabulary) under the 150k AdamW budget.

Architecture	Model Family	Parameters	Inference	Top-1 Acc	Top-3 Acc	Macro F1
Linear Classifier	Convex Baseline	1.2k	< 0.05 ms	60.71%	84.12%	0.542
Qwen2.5-1.5B-Instruct	Autoregressive LLM	1.54B	42.1 ms	6.29%	14.80%	0.048
Transformer (6L-4H)	Full Attention	1.2M	3.8 ms	**65.87%**	**89.41%**	**0.612**
TextNCA (1D Local, $L = 5$)	Cellular Automaton	14.8k	0.42 ms	63.51%	87.20%	0.584
Graph NCA (Meta-Learned)	**Cellular Automaton**	**15.4k**	**0.48 ms**	**65.18%**	**88.94%**	**0.605**

contraction $2 \cdot \mathrm{dist}(T(x), T(y)) \leq \mathrm{dist}(x, y)$*, the automaton admits at most one unique fixed point* $x^* = T(x^*)$ *(`fixed_point_unique`), and any initial state perturbation* δ_0 *decays exponentially:* $\mathrm{dist}(T^n(x), T^n(y)) \leq 2^{-n}\,\mathrm{dist}(x, y)$ *(`trajectory_decay`).*

Theorem 5 (Hierarchical Tree DAG Subsumption)**.** *Let* $\mathcal{T}_{\text{tree}}$ *denote a hierarchical decision tree DAG on* V *nodes with parent relations* $p = \lfloor (c-1)/2 \rfloor$*. Then* $\mathcal{T}_{\text{tree}}$ *is a strict element of the Graph NCA topology space* $\mathcal{S}_{\text{GNCA}}$ *(`theorem_tree_subsumption`), achieving maximum graph diameter* $D \leq 2\lceil \log_2 V \rceil = O(\log V)$*.*

5 Experimental Protocol

5.1 Datasets & Session-Level Partitioning

We evaluate on curated agent execution traces totaling 23,741 interaction turns across 13 tool categories. Crucially, all partitions are established at the **session level**: no session ID is shared between training and test splits, preventing trajectory memorization.

5.2 The 150k-Step Training Floor

Because iterative cellular dynamics learn spatial coordination gradually, premature evaluation (< 10k steps) produces misleading comparisons. We enforce a strict **150,000 AdamW step floor** on all comparative runs.

Hyperparameters. Optimization uses AdamW with initial learning rate $\eta = 10^{-3}$, cosine decay to 1%, weight decay $\lambda = 10^{-2}$, gradient norm clipping at 1.0, and class-weighted cross-entropy with inverse-frequency weights $w_c = \sqrt{1/f_c}$.




Figure 3: **Empirical training and validation trajectories across the 150k AdamW step budget.** Curated validation top-1 accuracy plotted against training steps for Graph NCA (mix13 champion), Long-Range ($k = 2$), 1D Regular Lattice, Flat MLP baseline, and Always-Terminal heuristic. Shaded ribbons denote $\pm 1\sigma$ standard deviation across 3 independent evaluation seeds.

Table 2: Feature parity under identical session-level test splits ($L = 5$, 10,000 bootstrap resamples).

Model / Feature Backbone	Top-1 (Mean ± SD)	95% Bootstrap CI
TextNCA (48-d Hash)	$63.51 \pm 0.51\%$	[62.51, 64.51]
TextNCA (128-d SVD)	$65.16 \pm 0.43\%$	[64.32, 66.01]
Graph NCA (Hierarchical Tree DAG, A_{tree})	$64.82 \pm 0.45\%$	[63.95, 65.69]
Graph NCA (Meta-Learned)	$\mathbf{65.18 \pm 0.44\%}$	**[64.34, 66.03]**
HistGradientBoosting (Strict Session Parity)	$61.24 \pm 0.48\%$	[60.30, 62.18]
Flat MLP Baseline Twin	$60.71 \pm 0.48\%$	[59.77, 61.65]
Always-Terminal Prior	$54.30 \pm 0.49\%$	[53.34, 55.26]

6 Results

6.1 Primary Benchmark Evaluation

Table 1 reports primary performance on curated agent traces under the 150k AdamW budget across candidate architectures. Figure 3 depicts empirical validation accuracy across 150k steps.

6.2 Feature Parity & Ablation Studies

Table 2 reports bootstrap evaluation across 10,000 resamples on the test split. All compared models share the identical causal history buffer ($L = 5$), observation masking, and session-level held-out split to strictly prevent cross-session leakage. Tabular tree models (such as `HistGradientBoosting`) achieve 69.47% when evaluated on random turn splits, but drop to 61.24% under strict session-level holdout parity. In contrast, Graph NCAs extended with hierarchical tree routing (A_{tree}) achieve 64.82%, while continuous meta-learning discovers optimal sparse connectivity reaching 65.18%.

Table 3 summarizes the 150k-step ablations isolating the structural components of the cellular update.




Figure 4: **Empirical efficiency and inductive bias breakdown.** (Left) Pareto trade-off between model parameters ($\log_{10}$ scale) and held-out local Hermes top-1 accuracy. Graph NCA achieves 39.0–40.1% top-1 with only 26.7k parameters (< 0.5 ms latency), outperforming 1.5B autoregressive LLMs (6.3%) by 6.2× while reducing parameter footprint by 57,000×. (Right) Inductive bias ablation breakdown: curated validation top-1 accuracy (blue) vs out-of-distribution local Hermes test top-1 accuracy (orange) across message-passing variants with standard error bars.

Table 3: Ablations under 150,000-step training budgets.

Ablation Variant	Primary EXP	Val Top-1	Peak Step
Meta-Learned Graph Topology	`EXP-1006-001`	**65.18%**	10,000
Goal Broadcast (Star)	`EXP-1006-001`	63.55%	10,000
Carry (Cross-Turn State)	`EXP-1006-003`	62.77%	5,000
Halt (Dynamic Early Stop)	`EXP-1006-005`	62.67%	10,000
Baseline (1D Local Only)	`EXP-1006-001`	62.60%	10,000
Flat Baseline Twin	`EXP-1006-001`	62.49%	15,000

Analysis of Inductive Biases. Figure 4 (right) compares curated validation accuracy against out-of-distribution local Hermes test performance across all cellular configurations.

1. **Meta-Learned Topology:** By learning sparse continuous edge weights A_α via bilevel optimization, the model bridges the root goal with active execution states in $O(1)$ steps, outperforming 1D local chains by +2.58 pp.
2. **Cross-Turn Carry:** Carrying hidden states forward across turns (62.77% val, 39.03% local) maintains temporal continuity on long iterative debugging trajectories.
3. **Dynamic Soft Halting:** Achieves 62.67% with an average of only 2.8 effective iteration cycles, reducing execution latency by $\approx 30\%$.

7 Discussion & Limitations

By expanding NCAs into a meta-learned graph decision substrate with machine-checked mathematical guarantees, we show that neural cellular automata can replace autoregressive decoders for deterministic agent actions while retaining mathematical interpretability.

Limitations. While slot-filling and entity binding operate efficiently, open-ended code diff generation still requires autoregressive fallback. Furthermore, scaling beyond $V > 50$ cells will require hierarchical clustering to avoid quadratic attention overhead.

8 Conclusion

We have introduced Graph Neural Cellular Automata (GNCA) with architecture meta-learning, showing that cellular automata extend far beyond rigid 1D chains to execute hierarchical tool dispatch, argument slot binding, and uncertainty escalation with machine-checked Lean 4 guarantees. Enforcing a 150k training floor, GNCA reaches 65.18% top-1 accuracy on curated agent benchmarks, matching Transformer baselines while slashing computational overhead.

Code, Data, and Model Availability. All models, datasets, and machine-checked Lean 4 proof packages are publicly available: **Formal Proofs:** `formal_proofs/NCAMetaLearning`; **Primary Model:** `cap-jmk-real/textnca-next-tool`; **Baseline Model:** `cap-jmk-real/baseline-next-tool`; **Dataset:** `cap-jmk-real/hermes-next-tool-mix`; **Source Code:** `https://github.com/cap-jmk-real/nca_research`.

References

[1] A. Mordvintsev, E. Randazzo, E. Niklasson, and M. Levin. Growing neural cellular automata. *Distill*, 5(2):e23, 2020.

[2] A. Mittal et al. TextNCA: Exploring Cellular Automata for Language Representation. *arXiv preprint arXiv:2603.01124*, 2026.

[3] S. Patil, H. Mao, et al. Berkeley Function Calling Leaderboard. *Gorilla Project Technical Report*, 2024.

Supplementary Information: Formal Lean Proofs

Below is the verified Lean 4 specification of Theorems 1–4, compiled with the official Lean 4.35 kernel with zero axioms.

```
namespace NCAMetaLearning

structure SimpleGraph (V : Nat) where
  adj : Fin V -> Fin V -> Prop
  symm : forall (i j : Fin V), adj i j <-> adj j i

def lineGraphAdj (V : Nat) : Fin V -> Fin V -> Prop :=
  fun i j => (i.val + 1 = j.val) \/ (j.val + 1 = i.val) \/ (i.val = j.val)

theorem theorem_subsumption_1d (V : Nat) :
  exists (G : SimpleGraph V), G.adj = lineGraphAdj V :=
  <lineSimpleGraph V, rfl>

theorem theorem_receptive_field_separation (V : Nat) (hV : V >= 3) :
  (forall k : Nat, Path V (lineSimpleGraph V) k <0, by omega> <V - 1, by omega> -> k >= V - 1) /\
  (forall (u v : Fin V), Path V (starSimpleGraph V) 2 u v) := by
  constructor
  . intro k p
    have h_bound := line_graph_distance_bound V p
    have h_u_zero : (<0, by omega> : Fin V).val = 0 := rfl
    have h_w_last : (<V - 1, by omega> : Fin V).val = V - 1 :=
     rfl
    rw [h_u_zero, h_w_last] at h_bound
    omega
  . intro u v
    exact star_graph_diameter_two V (by omega) u v

-- Hierarchical Tree DAG Subsumption Theorem
theorem theorem_tree_subsumption (V : Nat) :
  exists (G : SimpleGraph V), G.adj = treeGraphAdj V :=
  <treeSimpleGraph V, rfl>

-- Unique Fixed Point Attractor under Contraction
theorem fixed_point_unique {a : Type} (M : DiscreteMetricSpace a)
  (C : ContractionOp M) (x y : a) (hx : isFixedPoint C.op x)
  (hy : isFixedPoint C.op y) : x = y := by
  by_cases h_eq : x = y
  . exact h_eq
  . have h_contra := C.contract x y h_eq
    dsimp [isFixedPoint] at hx hy
    rw [hx, hy] at h_contra
    omega

-- Exponential Trajectory Perturbation Decay
theorem trajectory_decay {a : Type} (M : DiscreteMetricSpace a)
  (C : DyadicContraction M) (n : Nat) (x y : a) :
  (powTwo n) * M.dist (iterateCellular C.op n x)
                      (iterateCellular C.op n y) <= M.dist x y := by
  induction n with
  | zero =>
      dsimp [iterateCellular, powTwo]; omega
  | succ m ih =>
      dsimp [iterateCellular, powTwo]
      have h_step := C.step_decay (iterateCellular C.op m x) (iterateCellular C.op m y)
      have h1 : (powTwo m) * (2 * M.dist (C.op (iterateCellular C.op m x))
                                         (C.op (iterateCellular C.op m y))) <=
                (powTwo m) * M.dist (iterateCellular C.op m x)
                                    (iterateCellular C.op m y) :=
         Nat.mul_le_mul_left (powTwo m) h_step
      have h_assoc := Nat.mul_assoc 2 (powTwo m) (M.dist (C.op (iterateCellular C.op m x))
                                                         (C.op (iterateCellular C.op m y)))
      have h_comm := Nat.mul_left_comm 2 (powTwo m) (M.dist (C.op (iterateCellular C.op m x))
                                                            (C.op (iterateCellular C.op m y)))
      rw [h_assoc, h_comm]
      exact Nat.le_trans h1 ih

end NCAMetaLearning
```

Verification Instructions. To reproduce and verify the complete formal proof suite:

1. Install Lean 4 via elan: `elan toolchain install leanprover/lean4:v4.35.0`
2. In repository root, navigate to `formal_proofs/`
3. Run test suite: `lake build`.
4. Execute binary: `.lake/build/bin/ncametalearning`.
5. Confirm all 14 kernel jobs complete with zero axioms.