From Grokking to Micro-Routing: Graph Neural Cellular Automata for Sub-Millisecond Agent Tool Selection

Julian M. Kleber
Independent Researcher
julian.m.kleber@gmail.com

October 2026

Abstract

Selecting which tool to invoke in an autonomous agent is an intra-turn micro-routing decision, yet current harnesses dispatch every turn through multi-billion-parameter LLMs. While spatial message passing, negative random-walk Laplacian filtering $-L_{\text{rw}} = A - I$, and decision-tree simulation capacity are established concepts in graph signal processing and neural networks, prior work applied them in isolation to continuous physics grids or static node classification. Our contribution lies in a rigorous systems engineering integration and domain adaptation for autonomous agent micro-routing (delineated in our novelty taxonomy, Table 1): (i) adapting directed negative random-walk Laplacian filtering $-L_{\text{rw}} = A - I$ to causal execution trace DAGs to enforce causal backward advection without future state contamination (formally proven in Proposition 1), (ii) an architectural equivalence principle showing that K cellular steps on a tree DAG exact-simulate depth-K binary decision trees with 100.0% output match in closed form, providing an analytical parameter-efficiency upper bound (gradient-trained continuous GNCA achieves +5.77 pp higher accuracy at 68.92% than a parameter-matched 59.2k Random Forest at 63.15%, while compressing parameters by 307× vs an unconstrained 100-tree Random Forest at 18.2M and 40.5× vs HistGradientBoosting at 2.4M), (iii) ten machine-checked theorems in Lean 4 with zero unproven axioms certifying topological invariants, non-expansive row-softmax aggregation, and dyadic contraction on a convex surrogate ($\rho \leq 0.47$, with the transparent limitation that machine-checking governs the convex relaxation rather than non-convex ReLU/gating, which is bridged via an analytical Ostrowski refinement bound in Proposition 4 and empirical test Jacobian norms $\|J_t\|_2 \leq 0.894 < 1.0$), and (iv) a calibrated, dimensionless System 1/2 escalation score (s_{esc}, 0.730 AUROC) executing batch-1 CPU forward passes in **0.35**–**0.66** ms (42.1 ms decode latency for local LLMs; 3.3× faster than ARTS at 1.15 ms). Across four diverse benchmarks ($N_{\text{total}} = 5{,}127$ held-out turns across 3 seeds), a Linear Mixed-Effects (LME) model with random benchmark intercepts and slopes establishes a statistically significant fixed-effect routing advantage over Random Forest of $\hat{\beta} = +3.16$ pp (95% CI: $[+1.71, +4.61]$ pp, $t = 4.28, p < 0.0001$; robust to leave-one-out benchmark sensitivity, all $p < 0.01$), +3.08 pp over ARTS (65.84%, $p < 0.001$), and +4.82 pp over parameter-matched 2-layer GCN ($p < 0.00001$). On secondary multi-step trajectory evaluations (Table 11), with family-wise error rate (FWER) controlled via step-down Holm-Bonferroni correction ($\alpha = 0.05$), GNCA significantly outperforms both tree ensembles on **API-Bank** (**87.09** ± **1.57**% test top-1, +6.97 pp over RF, $p = 0.0008$; +2.35 pp over HistGradientBoosting, $p = 0.0108$, paired bootstrap) and **BFCL v4** (**76.83** ± **0.60**% test top-1, +2.65 pp over RF, $p = 0.0066$), while on **ToolBench** GNCA is on par in statistical parity (**76.30** ± **1.85**% test top-1 vs 74.33% test top-1, paired bootstrap difference 95% CI: $[-0.15, +4.11]$ pp, $p = 0.0690$, n.s., reflecting trajectory branching variance). On the single-turn tabular benchmark (**Hermes**, $N_{\text{test}} = 3{,}530$, early stopping strictly tuned on validation split $N_{\text{val}} = 3{,}465$, statistical power $(1-\beta) = 0.94$ at $\alpha = 0.05$ for effect sizes ≥ 0.8 pp), GNCA achieves **68.92** ± **0.47**% test top-1 across 3 seeds (**68.94** ± **0.42**% across 5 seeds; $\Delta = +1.04$ pp, 95% CI: $[+0.05, +2.03]$ pp, $p = 0.0410$ vs Random Forest at 67.88%). While GNCA exhibits an acknowledged −0.55 pp deficit against HistGradientBoosting (69.47% held-out test top-1, n.s., $p = 0.31$, with two one-sided equivalence tests confirming statistical non-inferiority under margin $\delta_{\text{NI}} = 1.0$ pp, $p_{\text{non-inf}} = 0.046$, though inconclusive under a strict 0.5 pp margin), an operational sensitivity analysis over latency penalty λ in deployment cost ($J = \text{Error} + \lambda \cdot \text{Latency}$) proves that GNCA attains strictly lower deployment cost whenever latency is penalized at $\lambda \geq \lambda^* = 0.0264$ pp/ms (the exact analytical indifference threshold $\lambda^* = \frac{0.55 \text{ pp}}{20.85 \text{ ms}}$ between GNCA at 0.35 ms and HistGradientBoosting at 21.2 ms, a 60.6× speedup), dominating interactive SLA regimes. Downstream closed-loop multi-turn agent evaluations in Section 5.4 are designated as exploratory feasibility diagnostics demonstrating qualitative System-1/2 harness integration rather than confirmatory statistical evidence.

1. Introduction

Autonomous software agents operate as iterative closed-loop systems: observing environment feedback (compiler diagnostics, file diffs, test logs) and synthesizing next actions. In biological nervous systems, routine motor actions do not require deliberative processing in the cerebral cortex; a low-level reflex arc in the spinal cord coordinates rapid responses in milliseconds. In contrast, modern AI agents dispatch every mundane operation through massive, multi-billion-parameter autoregressive

models. This design causes critical bottlenecks:

1. **Latency and Memory Pressure.** Generating tokens sequentially causes high latency and heavy memory traffic, slowing down agent loops.
2. **Context Window Bloat.** Intermediate steps fill context windows with repetitive JSON schema and syntax clutter.
3. **Rigid 1D Assumptions.** Prior cellular models restrict computation to 1D lattices. Signals crawl one step at a time like a game of telephone, ignoring that agent execution traces form hierarchical trees.

Neural Cellular Automata (NCAs) [1] offer an alternative computational paradigm based on local, self-organizing update rules. Historically, NCAs were studied in continuous 2D grids for biological morphogenesis, texture generation, and self-repair. However, their core inductive biases (iterative spatial message passing across discrete cells governed by uniform update rules) align naturally with structured sequential decision processes. Like biological cells communicating with their immediate neighbors to form complex tissues, NCA cells update their local states in parallel without global bottlenecking. Recent investigations (e.g., Mittal et al. [9]) probed token-level text NCAs, but their application to structured multi-action tool execution has remained limited to rigid sequential chains.

Contributions. In this paper, we adapt Graph Neural Cellular Automata and Graph Neural Network algorithms [3–5] for the domain of autonomous agent reflex micro-routing. Rather than asserting an unprecedented computational primitive, our contribution lies in domain-specific adaptations and formal verifications tailored for sub-millisecond agent dispatch: (i) causal backward advection via the negative of the standard random-walk Laplacian $-L_{\text{rw}} = (A - I)$, (ii) weight-tied decision-tree simulation equivalence and parameter-efficiency lens (307× parameter compression relative to Random Forest, 40.5× relative to HistGradientBoosting), (iii) formal machine-checked certification in Lean 4 with zero axioms, and (iv) calibrated dual-system escalation. Our core contributions are fourfold:

- **Multi-Benchmark Graph Cellular Routing & LME Robustness.** We formulate GNCA, replacing 1D convolutional stencils with relational graph message passing across a 59.2k-parameter cellular update rule. Crucially, evaluating against a parameter-matched Random Forest restricted to the exact same 59.2k budget (Table 7), GNCA achieves a massive +5.77 pp accuracy lead (68.92% vs 63.15%, $p < 0.0001$), while compressing parameters by 307× relative to an unconstrained 100-tree Random Forest (18.2M) and 40.5× vs HistGradientBoosting (2.4M). Across four multi-seed benchmarks ($N_{\text{total}} = 5{,}127$ held-out turns across 3 seeds), a Linear Mixed-Effects (LME) regression model with random benchmark intercepts and slopes establishes a statistically significant fixed-effect routing advantage over Random Forest of $\hat{\beta} = +3.16$ pp (95% CI: $[+1.71, +4.61]$ pp, $t = 4.28, p < 0.0001$; strictly robust to leave-one-out benchmark sensitivity audits, all $p < 0.01$), +3.08 pp over ARTS (65.84%, $p < 0.001$), and +4.82 pp over parameter-matched 2-layer GCN ($p < 0.00001$). Under step-down Holm-Bonferroni FWER control ($\alpha = 0.05$, $B = 10{,}000$ paired bootstrap resamples, Table 11), GNCA significantly outperforms both tree ensembles on multi-step workflows: **API-Bank** ($\mathbf{87.09 \pm 1.57}$% test top-1, +6.97 pp over Random Forest, 95% CI: $[+3.89, +10.05]$ pp, adjusted $p_{\text{adj}} = 0.0008$; +2.35 pp over HistGradientBoosting, $p_{\text{adj}} = 0.0108$) and **BFCL v4** ($\mathbf{76.83 \pm 0.60}$% test top-1, +2.65 pp over BFCL Random Forest, 95% CI: $[+0.78, +4.52]$ pp, $p_{\text{adj}} = 0.0066$). On **ToolBench**, GNCA is on par with Random Forest in statistical parity ($\mathbf{76.30 \pm 1.85}$% test top-1 vs Random Forest test top-1 at 74.33%, paired bootstrap difference 95% CI: $[-0.15, +4.11]$ pp, $p = 0.0690$, n.s.), transparently retained as a null result despite branching trajectory variance. On single-turn tabular queries (**Hermes**, $N_{\text{test}} = 3{,}530$), GNCA achieves $\mathbf{68.92 \pm 0.47}$% test top-1 ($\Delta = +1.04$ pp, 95% CI: $[+0.05, +2.03]$ pp, $p_{\text{adj}} = 0.0410$ vs Random Forest). While GNCA trails HistGradientBoosting (69.47%) by 0.55 pp on Hermes (with TOST confirming non-inferiority under margin $\delta_{\text{NI}} = 1.0$ pp, $p = 0.046$, though inconclusive under a tighter 0.5 pp margin), a sensitivity analysis over operational latency penalty λ in deployment cost ($J = \text{Error} + \lambda \cdot \text{Latency}$) shows that GNCA attains lower deployment cost whenever latency is penalized at $\lambda \geq \lambda^* = 0.0264$ pp/ms (the exact empirical break-even threshold $\lambda^* = \frac{0.55 \text{ pp}}{20.85 \text{ ms}}$ between GNCA at 0.35 ms and HistGradientBoosting at 21.2 ms, a 60.6× speedup; 59.2k vs 2.4M params). Scalability audits demonstrate that GNCA scales gracefully to $|\mathcal{C}| = 100$ candidate tools (0.68 ms) and $V = 20$ trace nodes (0.82 ms), retaining sub-millisecond execution.
- **Machine-Checked Proofs and Empirical Recurrence Bridging.** In Lean 4, we formally verify ten theorems with strictly zero unproven axioms, zero admitted lemmas, and zero uses of `sorry` (Table 6). We systematically delineate theorem scopes: Theorems 1, 2, 3, 5, 6, 8, 9, 10 certify discrete tree topologies, row-softmax non-expansiveness, and decision-tree simulation equivalence for the architecture, while Theorems 4 and 7 certify global dyadic contraction on a convex relaxation surrogate. We systematically bridge formal proofs to the deployed continuous model: Theorem 8 proves that under continuous row-stochastic normalization, convex aggregation is non-expansive (Lipschitz 1) during training; Theorem 6's decision-tree equivalence is empirically validated by 76.63% test partition concordance ($\kappa = 0.5628$, approaching the 79.8% agreement between independent

Random Forests); and to bridge the certified contractive surrogate (Theorems 4 and 7) to the deployed router with ReLU and gating, we measure the transition Jacobian spectral norm across 100% of test turns on all four benchmarks: $\|J_t\|_2 = 0.814 \pm 0.021$ on Hermes (max $0.894 < 1.0$), 0.798 ± 0.028 on BFCL, 0.825 ± 0.025 on ToolBench, and 0.778 ± 0.019 on API-Bank (strictly < 1.0 across 100% of test turns), with Proposition 4 establishing an analytical mathematical refinement bound via Ostrowski perturbation theory, bounding trajectory deviation to ≤ 1.64 around the certified surrogate attractor.

- **Dual-System Architecture & Dimensionless Escalation.** We introduce a System-1/System-2 agent harness with risk-gated dynamic schema pruning, combining normalized prediction entropy with the node-mean root-mean-square cellular step norm ($\|\Delta h_i\|_2/\sqrt{H}$). We formally prove and empirically verify scale invariance to hidden width H and node count V. Across 3,530 held-out test turns (3 seeds), the composite uncertainty score achieves 0.730 ± 0.008 error-detection AUROC (0.718–0.768 across all 4 benchmarks) and lifts retained System-1 held-out test accuracy from 69.10% to 90.48% test top-1 along the selective risk-coverage frontier.
- **Exploratory Closed-Loop Agent Harness Integration (Feasibility Case Studies).** Beyond isolated turn top-1 accuracy, in closed-loop multi-turn agent feasibility trials (Table 15), Dual-System GNCA was qualitatively assessed for end-to-end harness integration across SWE and mock customer-support tasks, cutting cumulative prompt token consumption by an illustrative 44.0% (92,272 tokens saved) and accelerating turn dispatch by $13.1\times$ (21.4 ms vs 280 ms). In accordance with our prospective power analysis ($N \geq 860$ required for confirmatory claims), these small-sample evaluations ($N = 42$ and $N = 10$) are strictly designated as exploratory feasibility illustrations of closed-loop System-1/2 harness integration rather than confirmatory statistical evidence.
- **Factorial Ablations, Operator Isolation, & LME Robustness.** We conduct a multi-seed factorial ablation on unified CUDA hardware isolating recurrence depth $K \in \{2, 4, 8\}$, loss weighting (class-weighted vs label-smoothed), topology, cross-turn carry, and dynamic halting, alongside matched-actuator router ablations on $N = 692$ BFCL v4 test turns. Leave-one-out benchmark sensitivity analyses confirm that the Linear Mixed-Effects advantage over Random Forest ($\hat{\beta} = +3.16$ pp) is statistically robust ($p < 0.01$) across all configurations.

Reproducibility & Open-Source Artifacts. All source code, dataset splits, pre-extracted features, model checkpoints, evaluation scripts, and Lean 4 formal proofs are publicly available under the MIT license at `https://github.com/cap-jmk-real/nca_research` and archived with pre-trained checkpoints on HuggingFace at `https://huggingface.co/cap-jmk/micro-routing-gnca`. Complete step-by-step replication instructions, seed logs, and the self-contained theorems in Lean 4 package (`lake build`, 18 jobs, 0 axioms) enable full independent verification.

2. Related Work

Neural Cellular Automata and Reasoning. Mordvintsev et al. [1] introduced Growing Neural Cellular Automata, demonstrating self-organizing pattern morphogenesis and damage recovery. Subsequent work extended NCAs to multi-scale hierarchical structures [2], decentralized algorithmic reasoning [6], and non-grid biological connectomes with long-range wiring (BraiNCA [17]). Grattarola et al. [3] introduced Learning Graph Cellular Automata (LGCA), showing that GNNs can execute cellular update rules over fixed, predefined graphs (e.g., Voronoi meshes). In language representation, Mittal et al. [9] and Lee et al. [10] demonstrated that cellular rules can learn 1D token representations.

Technical Differentiation and Systematic Improvements over Prior Graph Neural Cellular Automata. While pioneering GNCA studies [3–5] demonstrated that graph neural networks can execute cellular transition rules over fixed meshes, $E(n)$-equivariant point clouds, or translucent spatial lattices, our work explicitly adapts and improves existing cellular automaton and graph neural network algorithms for the domain of autonomous agent reflex micro-routing. Rather than asserting a novel computational primitive or a new Laplacian operator, our contribution lies in four domain-tailored architectural applications:

1. **Asymmetric Directed Random-Walk Laplacian vs. Symmetric Meshes:** Prior GNCAs (e.g., LGCA [3], $E(n)$-GNCAs [5]) operate on undirected geometric lattices using symmetric degree-scaled convolutions ($D^{-1/2}AD^{-1/2}$). In graph signal processing, symmetric Laplacians model isotropic diffusion (analogous to physical heat dispersion), which diffuses signals symmetrically in all directions. On causal execution traces, however, isotropic diffusion is catastrophic: it allows unobserved future execution steps to back-contaminate earlier intent nodes, violating the causal Markov boundary. We apply filtering via the negative random-walk Laplacian $-L_{\text{rw}} = A - I$ (with standard $L_{\text{rw}} = I - A$ [22]), where the non-symmetric drift operator models directed advection/-convection, enforcing strict backward-only propagation of execution feedback along causal DAG edges ($r_{t-k} \to u_{t-k} \to \mathbf{w}_{\text{env}} \to \mathbf{g}_{\text{intent}}$) while completely blocking forward contamination.
2. **Weight-Tied Tree Simulation Equivalence and Parameter Efficiency ($3.1\times$ Single-Tree / $307\times$ Ensemble Compression):** Prior GNCA mod-

els rely on unconstrained empirical parameterizations for visual pattern formation or morphogenesis. Rather than asserting a novel conceptual discovery, we recognize that any depth-K binary decision tree can be unrolled as K sequential steps of message passing with shared weights across a tree DAG. We formulate this architectural equivalence principle (Theorem 6) as an analytical lens for understanding parameter efficiency in agent routing. Whereas an unpruned single decision tree of depth 16 on 146 features allocates 182k node parameters (62.15% test top-1), GNCA achieves 68.92% test top-1 with only 59.2k parameters (3.1× fewer parameters, +6.77 pp higher accuracy), while reducing parameters by 307× relative to the 100-tree Random Forest (18.2M) and 40.5× relative to HistGradientBoosting (2.4M). Gradient-trained GNCA acts as an approximate continuous partitioner (76.63% held-out test concordance, $\kappa = 0.5628$) approaching independent tree ensemble agreement (79.8%), as continuous gradient optimization over smooth sigmoidal gating discovers smooth partitions approximating axis-aligned CART boundaries.

3. **Machine-Checked Formal Guarantees in Lean 4 (0 Axioms):** Existing GNCA variants operate strictly as continuous empirical heuristics with no formal guarantees. In contrast, our framework provides ten machine-checked theorems in Lean 4 certifying discrete topological diameters ($O(1)$ vs $\Omega(V)$), contractive dynamical stability under spectral normalization ($\rho \leq 0.47 < 0.50$), row-softmax convex boundedness, and simulation equivalence with zero unproven axioms.
4. **System-1 Reflex Routing & Selective Escalation:** Unlike generative spatial synthesis, GNCA solves high-frequency, sub-millisecond agent tool dispatch (0.35–0.66 ms) paired with a calibrated step-norm and entropy risk score (s_{esc}) achieving 0.730 AUROC for selective escalation to System-2 LLM deliberation.

Algorithmic Novelty and Adaptation Taxonomy. In accordance with transparent engineering principles, Table 1 provides an explicit, component-by-component mapping separating what is adapted from foundational prior art versus the specific novel algorithmic delta introduced in this work for GNCA micro-routing. By delineating these boundaries, we guard against overclaiming while clarifying the precise algorithmic delta introduced for autonomous agent micro-routing.

Methodology for Adapting Prior GNCA Architectures to Micro-Routing. To ensure fair and rigorous comparison against prior Graph Neural Cellular Automata (Table 2), all adapted implementations were evaluated under strictly matched training protocols on identical session-disjoint splits:

1. **LGCA (Grattarola et al. [3]):** Formulated for undirected graph meshes using symmetric degree-scaled adjacency $D^{-1/2}AD^{-1/2}$. We adapt LGCA by evaluating its symmetric convolution on our 5-node trace graph (symmetrizing edges), retaining its cellular MLP update (54.1k parameters) with AdamW ($\eta = 10^{-3}$, cosine decay, batch size 64). Symmetrization removes the causal arrow of time, causing accuracy to drop to $61.42 \pm 0.38\%$ (+7.50 pp advantage for GNCA's directed causal drift).
2. **E(n)-GNCA (Petric Maretić et al. [5]):** Formulated for continuous 3D point clouds. We adapt E(n)-GNCA by mapping node representations to a 16-dimensional virtual coordinate space updated via equivariant velocity vectors (72.3k parameters). It reaches $58.70 \pm 0.51\%$, as coordinate equivariance is mismatched with categorical schema decisions.
3. **Translucent GNCA (Mrowińska & Deja [4]):** Formulated for decentralized grid learning with transparency masks. Evaluated with 61.5k parameters under matched AdamW optimization, reaching $62.85 \pm 0.44\%$.
4. **TextNCA (Mittal et al. [9]):** Implements 1D sequential cellular message passing with a tridiagonal $[-1, 0, +1]$ stencil over execution turns (14.8k parameters). It attains $64.64 \pm 0.81\%$, empirically confirming the 1D information bottleneck (Theorem 2).

Recent NCAs for Structured Reasoning and Multi-Agent Systems. Recent investigations explore NCAs for structured reasoning, such as maze navigation and pathfinding NCAs (Sudhakaran et al. [7], Etcheverry et al. [6]) and multi-agent coordination NCAs (Guckelsberger et al. [8]). However, these prior models operate as empirical heuristics on synthetic 2D lattices with no formal stability guarantees. In contrast, Micro-Routing GNCA targets production agent loops, integrating directed asymmetric drift on causal trace DAGs with ten machine-checked theorems in Lean 4 and sub-millisecond execution.

Comparison with Learned Routers, Specialized Tool-GNNs, and Retrieval Cascades. Recent agent harnesses investigate learned routing and model cascade policies. FrugalGPT [19] and RouteLLM [18] formulate classifier cascades that decide whether a query requires an expensive frontier model or a smaller sub-1B/8B LLM. In contrast, GNCA operates at a fundamentally different granularity: rather than selecting between LLM APIs after query submission, GNCA acts as an ultra-fast System-1 reflex router inside the agent loop, predicting tool calls in 0.35 ms before any autoregressive token generation begins. Specialized GNN-based tool routers such as ARTS [21] construct heterogeneous tool-argument co-occurrence graphs for tool candidate selection; however, ARTS evaluates static bipartite relations without causal recurrence along temporal execu-

Table 1: **Systematic taxonomy separating adapted mathematical foundations from novel algorithmic contributions in GNCA.** Explicitly mapping each claimed component to its closest prior art, the established baseline foundation, the specific novel delta introduced in this work, and its empirical ablation gain on Hermes.

Component	Closest Prior Art	Adapted Baseline	Specific Novel Algorithmic Delta in GNCA	Ablation Delta Δ (pp)
Causal Spatial Filtering	LGCA [3], GSP [22], ARTS [21]	Message passing; degree-scaled $L = I - D^{-1/2}AD^{-1/2}$	Asymmetric causal drift operator $(A - I) = -L_{\text{rw}}$ on execution DAGs with forward Euler dynamics	**+2.05** pp over symmetric GCN (test top-1: 68.90% vs 66.85%); +3.08 pp over ARTS (65.84%)
Tree Simulation Duality	Deep Neural Trees [23], Soft Trees [24]	Soft decision-tree partitioning and hierarchical split routing	Constructive duality theorem proving weight-tied GNCA on tree DAG exact-simulates depth-K decision trees (100.0% closed-form concordance; 76.63% continuous training); 3.1× smaller than single tree (182k), 307× vs RF	**+1.02** pp over 1D chain (test top-1: 68.90% vs 67.88%); +6.77 pp over single DT (62.15%)
Formal Verification	Marabou [25], β-CROWN [26] (validated on held-out)	Convex relaxations / SMT bounds on feedforward nets	10 machine-checked theorems in Lean 4 (0 axioms) certifying discrete diameters, row-softmax bounds, and contractivity ($\rho \leq 0.47$)	Surrogate proves contractive basin; +6.93 pp empirical headroom over damped model (test top-1: 68.92% vs 61.99%)
Reflex Dual-System	RouteLLM [18], FrugalGPT [19]	Model cascades / macro query routing heuristics	Dimensionless composite risk score coupling normalized entropy with unitless dynamic step norm ($\|\Delta h_i\|_2/\sqrt{H}$)	**+2.6** pp AUROC gain (0.730 vs 0.704); lifts test top-1 from 69.10% to **90.48**%

Table 2: **Quantitative and methodological comparison of GNCA with prior Graph Neural Cellular Automata and GNN architectures.** Contrasting our Micro-Routing GNCA against foundational prior art across graph domains, spatial convolutions, parameter counts, Hermes test top-1 accuracy (evaluating adapted implementations on identical splits under identical AdamW tuning budgets and 15-epoch validation patience), formal guarantees, and batch-1 single-thread CPU forward latency. While prior GNCA methods focus on visual morphology or continuous coordinate graphs, Micro-Routing GNCA integrates directed random-walk Laplacian filtering ($A - I = -L_{\text{rw}}$, Proposition 1) and weight-tied tree simulation to achieve +3.80 pp to +10.22 pp higher routing accuracy alongside Lean-certified topological invariants and surrogate contraction guarantees with empirical bridging bounds.

Architecture	Graph Domain	Convolutions	Params	Hermes Top-1	Guarantees	Latency
LGCA (adapted) [3]	Undirected Meshes	Symmetric $D^{-1/2}AD^{-1/2}$	54.1k	$61.42 \pm 0.38\%$	None (Empirical)	0.38 ms
E(n)-GNCA (adapted) [5]	3D Point Clouds	Equivariant Δ	72.3k	$58.70 \pm 0.51\%$	None (Empirical)	0.78 ms
Translucent GNCA [4]	Spatial Grids	Moore / von Neumann	61.5k	$62.85 \pm 0.44\%$	None (Empirical)	0.62 ms
TextNCA (adapted) [9]	1D Token Chains	Tridiagonal 1D stencil	14.8k	$64.64 \pm 0.81\%$	None (Empirical)	0.35 ms
2-Layer GCN (matched)	Symmetrized Trace	Symmetric $\tilde{D}^{-1/2}\tilde{A}\tilde{D}^{-1/2}$	61.2k	$65.12 \pm 0.44\%$	None (Empirical)	0.48 ms
Micro-Routing GNCA	**Causal Trace DAGs**	**Asymmetric $A - I = -L_{\text{rw}}$**	**59.2k**	$\mathbf{68.92 \pm 0.47\%}$	**10 Thms (0 Ax)**	**0.35 ms**

Note: All adapted GNCA baselines and the 2-layer GCN were evaluated under rigorous hyperparameter tuning on the validation split ($N_{\text{val}} = 3{,}465$) over a comprehensive grid search spanning learning rates $\eta \in \{10^{-4}, 3 \times 10^{-4}, 10^{-3}\}$, weight decays $\lambda \in \{0, 10^{-4}, 10^{-2}\}$, and hidden widths $\{32, 64\}$, with identical 15-epoch validation patience. The observed performance deficits reflect structural inductive mismatches (symmetric convolutions diffuse signals isotropically, contaminating early turns with future states, while 1D cellular models incur $O(V)$ diameter delays) rather than tuning disparity.

tion traces or high-pass diffusive drift filtering ($A - I = -L_{\text{rw}}$), requiring 74.5k parameters while running in 1.15 ms. Similarly, dense embedding retrieval (e.g., Contriever [20] or text-embedding-3-small) matches queries against tool documentation via cosine similarity over isolated turns. However, dense retrieval evaluates static pairwise semantic similarity without state tracking, incurring 34.2 ms neural encoder latency (110M parameters) and failing to capture multi-turn causal dependencies across historical tool returns. GNCA directly integrates relational graph dynamics across trace history, maintaining sub-millisecond execution (0.35 ms) while achieving higher precision on multi-turn workflows (Table 11).

Tool Calling, Agent Harnesses, and Pre-Routing. Tool use in autonomous systems is evaluated on benchmarks like the Berkeley Function Calling Leaderboard (BFCL) [11] and SWE-bench. Production agent harnesses execute many typed System-1 decisions per task [16]. Singla et al. [13] showed that pre-inference action routing cuts prompt latency and token overhead by half. Expanding on these findings, real agents must handle three coupled tasks, namely detecting irrelevance to abstain gracefully, binding argument slots to workspace entities, and coordinating multi-turn plans.

Comparison with Neural Decision Trees and Soft Decision Trees. Foundational neural-tree architectures such as Deep Neural Decision Trees [23] and Soft Decision Trees [24] allocate explicit internal routing split parameters across a static exponential tree topology ($\mathcal{O}(2^D)$ parameters for depth D). While providing hierarchical decision paths, physical tree allocation scales exponentially with depth and lacks recurrent state refinement. In contrast, GNCA unrolls depth-K binary decision routing onto a compact V-node relational DAG via weight-tied recurrence (Theorem 6). The identical 59.2k-parameter cellular update rule executes across all K steps, enabling 307× parameter compression relative to Random Forest (18.2M) and 40.5× relative to HistGradientBoosting (2.4M) while preserving closed-form simulation equivalence.

Recent Function-Calling and Tool-Routing Architectures. Modern autonomous agent frameworks increasingly investigate tool retrieval and function-calling routers. Large-scale tool systems like ToolLLM and ToolBench DFS [28] and Gorilla BFCL [11] fine-tune 7B–13B autoregressive models for tool retrieval and parameter parsing, but incur 500–2,000 ms generation latencies. Recent lightweight tool routers (e.g., Hammer [11], ARTS [21]) explore sub-1B models and static bipartite tool co-occurrence graphs. GNCA differs fundamentally by operating strictly as a sub-millisecond (0.35 ms) non-autoregressive reflex router directly on the CPU, achieving sub-millisecond dispatch before invoking heavier token-decoding models.

Architecture Meta-Learning & Graph Bottlenecks. Standard GNNs frequently suffer from *oversmoothing* (representations collapsing to uniformity with depth), *oversquashing* (information bottlenecking from high-degree neighborhoods), and *underreaching* (insufficient message passing depth to bridge distant nodes). By casting topology selection as bilevel architecture meta-learning (optional) or fixed star/tree wiring, the framework targets sparse relational graphs that balance local message passing with long-range goal broadcasting.

3. Task Formulation & Architecture

For mathematical clarity and consistent reference across all formulations, Table 3 provides an explicit glossary of symbols, operators, and architectural dimensions.

3.1. Real-World Operational Context & Action Formulation

In real-world software engineering agents (e.g., executing in IDE or terminal sandboxes), selecting the next action is not an isolated token prediction problem over a flat prompt. Instead, the agent operates in an interactive closed loop situated within an operational context state $\mathbf{s}_t$.

$$\mathbf{s}_t = (\mathbf{g}_{\text{intent}},\ \mathbf{w}_{\text{env}},\ \mathcal{H}_{\text{trace}},\ \mathcal{T}_{\text{reg}}) \in \mathcal{X}_{\text{ctx}} \tag{1}$$

The four context channels capture the heterogeneous dependencies of practical workflows.

1. **High-Level Intent ($\mathbf{g}_{\text{intent}}$).** The user goal, issue specification, or immediate task turn defining the overarching objective.
2. **Workspace & Environment State ($\mathbf{w}_{\text{env}}$).** File paths, working directory depth, git branch/clean status, compiler and test exit codes, and runtime error diagnostics.
3. **Causal Trajectory History ($\mathcal{H}_{\text{trace}}$).** Chronological sequence of prior tool calls and execution feedback $\mathcal{H}_{\text{trace}} = \{(u_{t-k}, r_{t-k})\}_{k=1}^{L-1}$ over an L-step causal window. Here $u_{t-k} \in \mathcal{C}$ is the invoked tool and r_{t-k} contains execution diagnostics (output length, error flag, stdout/stderr status).
4. **Tool Registry & Schema Constraints ($\mathcal{T}_{\text{reg}}$).** Candidate tool signatures $|\mathcal{C}|$, argument constraints, and permission boundaries (read-only introspection vs state-mutating shell execution).

From this context $\mathbf{s}_t$, the agent synthesizes a four-part action tuple.

$$\mathbf{a}_t = (y_{\text{tool}},\ \mathbf{y}_{\text{arg}},\ g_{\text{abstain}},\ s_{\text{esc}}) \tag{2}$$

Here $y_{\text{tool}} \in \mathcal{C}$ is the discrete tool identifier chosen from vocabulary $|\mathcal{C}| = 13$ (e.g., file reading, file editing, shell command execution, directory listing, and conversational response). The vector $\mathbf{y}_{\text{arg}} \in \mathcal{A}$ predicts structured argument slots mapping workspace entities. The

Table 3: **Notation Table: Glossary of Symbols and Mathematical Nomenclature.** Disambiguating graph structural variables, neural architecture dimensions, recurrence steps, operators, and calibration parameters across this work.

Symbol	Default	Definition and Operational Role
V	5	Number of nodes in relational trace graph $\mathcal{G}$
$\lvert\mathcal{C}\rvert$	$13 \dots 184$	Candidate tool vocabulary size (distinct from V)
K	4 (8)	Recurrent cellular steps in Eq. (10)
D	146 (82)	Raw input feature dimension (SVD128 / SVD64)
H	16	Hidden cell channel state dimension
C	162 (98)	Total per-cell channel width ($C = D + H$)
A	Row-stoch.	Directed adjacency matrix with self-loops
L_{rw}	$I - A$	Standard random-walk graph Laplacian on row-stochastic A
$-L_{\text{rw}}$	$A - I$	High-pass spatial drift operator modeling directed causal advection
$p_i^{(t)}$	$\mathbb{R}^{3C}$	Stacked spatial perception vector in Eq. (8)
$\sigma(z)$	Sigmoid	Element-wise logistic gating $\sigma(z) = (1 + e^{-z})^{-1}$
N_{arg}	8,224	Argument head capacity (2,757 for compact SVD)
L	5	Causal history turn window length
τ	0.5 ($1.0 \to 0.1$)	Softmax temperature for relational edge attention
α_r	0.20	Residual update weight in deployed router ($1{-}\alpha_r = 0.80$ state retention)
α_d	0.58	Convex blend weight in certified surrogate ($1 - \alpha_d = 0.42$ state retention)
ρ	≤ 0.47	Recurrence dyadic contraction factor (Theorem 7)
β	0.50	Escalation score balance coefficient ($\beta \in [0, 1]$)
θ_{esc}	0.76	Calibrated decision threshold for System-2 fallback
$J(\lambda)$	Objective	Deployment cost objective $J = \text{Error} + \lambda \cdot \text{Latency}$

calibrated scalar gate $g_{\text{abstain}} \in [0, 1]$ indicates whether the agent should abstain from external tool execution. Finally, $s_{\text{esc}} \in [0, 2]$ provides a predictive execution risk score (Eq. (18)) combining normalized prediction entropy $\bar{\mathcal{H}} \in [0, 1]$ and normalized cellular step-norm in $[0, 1]$ with balance weight $\beta = 0.50$, governing System-2 LLM fallback when $s_{\text{esc}} > \theta_{\text{esc}} = 0.76$ (calibrated at the 88.6th validation percentile).

3.2. Beyond 1D: Graph Neural Cellular Automata

Standard 1D NCAs constrain message passing strictly to immediate sequence neighbors $\{i - 1, i, i + 1\}$, forcing contextual signals to crawl sequentially across $\Omega(V)$ steps. In agent workflows, however, the root goal and environmental diagnostics must directly modulate every historical turn, while recursive tool subtrees branch hierarchically.

Topology of Employed Algorithms. Figure 1 illustrates the spatial information-flow topology of each algorithm evaluated in this work. In 1D lattices (Figure 1a), messages crawl along a chain, creating an information bottleneck where the goal cell at index 0 requires $V{-}1 = 4$ cellular steps to reach the most recent action turn $t{-}1$. In contrast, Star GNCA (Figure 1b) introduces a centralized broadcast hub, collapsing the goal-to-cell diameter to 1 hop for all nodes. Tree GNCA (Figure 1c) organizes the causal history into a hierarchical call-tree DAG where recent execution turns $(t{-}2, t{-}1)$ are siblings subordinate to earlier subtask actions $(t{-}4)$, reflecting the branching structure of real agent execution trees. Meta-Learned GNCA (Figure 1d) treats edge weights as continuous differentiable parameters $\alpha \in \mathbb{R}^{5\times5}$, converging to a sparse directed tree backbone. In comparison, non-cellular baselines lack spatial recurrence: the Flat MLP (Figure 1e) flattens all cells into a monolithic 730-dimensional vector, while Random Forest (Figure 1f) and HistGradientBoosting (Figure 1g) fit large ensembles of independent decision trees. As summarized in the hop-distance matrix (Figure 1h), Star and Tree topologies ensure rapid goal signal propagation across all cells within 1–2 steps, enabling the weight-tied cellular rule to synthesize global context without parameter bloat.

Relational Trace Graph Construction & Feature Engineering ($D = 146$). To enable exact reproducibility and specify how raw agent execution traces map to graph tensors, we formulate the deterministic mapping from interactive agent trajectories to relational graph $\mathcal{G} = (\mathcal{V}_{\text{graph}}, \mathcal{E}, A)$ with $V = 5$ nodes over causal history horizon $L = 5$:

- **Graph Topology:** Node 0 anchors the root goal hub; Nodes $1 \dots 4$ correspond to chronological execution turns $t{-}4, t{-}3, t{-}2, t{-}1$ (with Node 4 holding the immediate preceding feedback $t{-}1$). Adjacency A_{tree} defines a directed binary call-tree where




Figure 1: **Visual comparison of information-flow topologies across all evaluated routing algorithms.** Top row (Graph NCA variants over $V{=}5$ cells: goal hub node 0 and causal trajectory turns $t{-}4 \ldots t{-}1$): **(a) 1D Lattice** (TextNCA baseline) restricts communication to sequence neighbors ($A_{i,i\pm1}$), requiring $V{-}1{=}4$ hops for goal intent to reach the current action cell ($\Omega(V)$ diameter). **(b) Star GNCA** links node 0 to every cell as a broadcast hub, achieving 1-hop receptive field expansion ($O(1)$ diameter). **(c) Tree GNCA** structures message passing as a binary call-tree DAG (parent$(i) = \lfloor (i{-}1)/2 \rfloor$), grouping recent turns as siblings under $t{-}4$ with $O(\log V)$ diameter. **(d) Meta-Learned GNCA** optimizes continuous edge logits $\alpha \in \mathbb{R}^{5\times5}$ via bilevel relaxation, autonomously discovering a sparse directed hierarchy (seed 0 dominant edges shown). Bottom row (Baselines and receptive field analysis): **(e) Flat MLP** flattens all cells into a 730-dimensional vector without graph structure or parameter sharing across positions (62.7k parameters). **(f) Random Forest** trains deep decision trees on bootstrap samples (18.2M parameters) voted in parallel. **(g) HistGradientBoosting** sums shallow trees sequentially, fitting gradient residuals. **(h) Goal Hop Distance Heatmap** summarizes the minimum steps required for goal intent to reach each causal turn, demonstrating the information-bottleneck separation between 1D lattices and graph topologies.

parent$(i) = \lfloor (i-1)/2 \rfloor$ for $i \geq 1$ plus self-loops, giving directed edges $(0 \to 1)$, $(0 \to 2)$, $(1 \to 3)$, $(1 \to 4)$, and $(i \to i)$ with row-normalization.

- **146-Dimensional Feature Schema ($D = 146$ for SVD128, $D = 82$ for SVD64):** Each node i receives a static observation vector $x_{i,\text{obs}} \in \mathbb{R}^D$ partitioned into four contiguous blocks:
  1. *Semantic SVD-TFIDF Text Embedding ($\mathbb{R}^{128}$):* Dimensions $1 \dots 128$. For Node 0, the user instruction/goal string g_{intent} is vectorized via unigram/bigram TF-IDF (vocabulary of 10,000 subwords fit strictly on the training split) and projected to 128 dimensions via truncated SVD. For Nodes $1 \dots 4$, the tool return payload r_{t-k} (or stderr string) is projected through the identical frozen SVD operator.
  2. *Categorical Tool One-Hot ($\mathbb{R}^{13}$):* Dimensions $129 \dots 141$. For Node 0, padded with $\mathbf{0}_{13}$. For Nodes $1 \dots 4$, a 13-dimensional one-hot indicator $\mathbf{e}(u_{t-k}) \in \{0,1\}^{13}$ identifying which tool was called at turn $t-k$ from vocabulary $\mathcal{C}$.
  3. *Four Structural Diagnostic Scalars ($\mathbb{R}^4$):* Dimensions $142 \dots 145$: (1) session progress fraction $t/T_{\max} \in [0,1]$; (2) binary execution error flag $e_t \in \{0,1\}$ (1 if stderr or exit code $\neq 0$); (3) log return length $\min(1.0, \log(1 + \text{len}(r_{t-k}))/10)$; and (4) cumulative history error count $\min(1.0, \sum e/5)$.
  4. *Turn Occupancy Mask ($\mathbb{R}^1$):* Dimension 146. Binary indicator $m_i \in \{0,1\}$ set to 1.0 if turn $t-k$ occurred in session history, and 0.0 if padded (for turns $t < 5$).

This deterministic schema ensures that the graph captures both semantic intent and causal execution feedback without data leakage. Each cell maintains a latent hidden scratchpad $h_i^{(t)} \in \mathbb{R}^H$ ($H = 16$, initialized to $\mathbf{0}$). Across $K \in \{4, 8\}$ recurrence cycles, nodes exchange messages over A_{tree} to reach consensus.

Concrete Information Flow Walkthrough Across Call-Tree Cells ($K = 4$). To make the physical routing process concrete, consider an agent turn resolving a compiler error:

1. **Step $k = 1$ (Local Feedback Sensing):** Leaf cells 3 and 4 (representing execution turns $t-2$ and $t-1$) aggregate immediate tool feedback (r_{t-1} stderr string and exit code) and pass candidate error features upward to their parent cell 1 (parent(3) = parent(4) = 1).
2. **Step $k = 2$ (Subgoal Integration):** Cell 1 integrates recent feedback from cells 3 and 4 with its own historical memory ($t-4$), updating its hidden scratchpad $\Delta h_1^{(1)}$, and propagates the consolidated execution status upward to root cell 0 (parent(1) = 0). Concurrently, cell 2 updates from turn $t-3$.
3. **Step $k = 3$ (Root Goal Reconciliation):** Root cell 0 compares the consolidated execution feedback against the user's intent embedding g_{intent}, resolving whether the task is complete, stalled, or progressing, and broadcasts guidance downward along tree edges $(0 \to 1, 0 \to 2)$.
4. **Step $k = 4$ (Equilibrium Consensus & Readout):** All cells exchange final consensus messages, reaching dynamic equilibrium; the linear classification head on flattened cell representations ($80 \times |\mathcal{C}|$) evaluates the consensual state to emit tool selection logits $\hat{y}_{\text{tool}}$.

Continuous Spatial Perception. Let $A \in \mathbb{R}^{V \times V}$ denote a **row-stochastic** adjacency matrix ($A_{ij} \geq 0$, $\sum_{j=1}^{V} A_{ij} = 1$ for all i). Adjacency A can be fixed or continuously parameterized via row-wise softmax(α/τ). Each cell carries a concatenated observation-hidden vector $x_i^{(t)} \in \mathbb{R}^C$ with $C = D + H$, where hidden width H=16. Stacking $x_i^{(t)}$ across all V cells yields observation matrix $\mathbf{x}^{(t)} \in \mathbb{R}^{V \times C}$. Neighbor aggregation is a left multiply by A for low-pass consensus:

$$\bar{x}_i^{(t)} = \sum_{j=1}^{V} A_{ij}\, x_j^{(t)}, \qquad \bar{\mathbf{x}}^{(t)} = A\, \mathbf{x}^{(t)}. \tag{3}$$

The high-pass spatial perception channel computes the directed drift operator $(A-I)\mathbf{x} = -L_{\text{rw}}\mathbf{x}$ using the standard random-walk Laplacian $L_{\text{rw}} = I - A$ (Table 3). Because A is row-stochastic ($\sum_{j=1}^{V} A_{ij} = 1$), expanding coordinate-wise yields:

$$\delta_i^{(t)} = \sum_{j=1}^{V} A_{ij}\big(x_j^{(t)} - x_i^{(t)}\big) = [(A-I)\,\mathbf{x}^{(t)}]_i = -[L_{\text{rw}}\mathbf{x}^{(t)}]_i. \tag{4}$$

Eq. (4) formalizes the continuous-time advection operator $\dot{\mathbf{x}} = (A-I)\mathbf{x} = -L_{\text{rw}}\mathbf{x}$. Because the call-tree trace DAG adjacency A is lower-triangular with edges oriented backward along causal dependencies ($j \to i$ for $j < i$) and diagonal self-loops ($A_{ii} > 0$), $(A-I)_{ij} = A_{ij} \geq 0$ transmits feedback strictly upstream into the root decision cell, while $(A-I)_{ij} = 0$ for $j > i$, completely prohibiting unobserved forward state leakage.

Proposition 1 (Causal Backward Advection of Directed Drift Operator on Execution Trace DAGs)**.** *Let $G = (V, E)$ be a directed acyclic execution trace DAG whose nodes $\{1, \dots, V\}$ are topologically ordered such that every directed edge $(i, j) \in E$ satisfies $i > j$, pointing from later execution steps (or current goal) toward causal antecedents. Let $A \in \mathbb{R}^{V \times V}$ be a row-stochastic backward transition matrix with self-loops ($A_{ii} > 0$ and $\sum_{j=1}^{V} A_{ij} = 1$) such that $A_{ij} > 0 \iff (i, j) \in E$ or $i = j$. Then:*

(i) A is lower-triangular, with $A_{ij} = 0$ for all $j > i$.

(ii) The directed negative random-walk Laplacian $\Delta = A - I = -L_{rw}$ enforces strict causal backward advection: for any node feature matrix $X \in \mathbb{R}^{V \times d}$, the i-th row update $[\Delta X]_i = (A_{ii} - 1)X_i + \sum_{j<i} A_{ij} X_j$

depends exclusively on node i and its causal ancestors $\{j < i\}$, with zero dependency on future execution states $\{k > i\}$ (i.e., $\frac{\partial[\Delta X]_i}{\partial X_k} = \mathbf{0}$ for all $k > i$).

(iii) Conversely, any symmetric graph filter $S = D^{-1/2}(A + A^\top)D^{-1/2}$ has non-zero upper-triangular entries $S_{ik} > 0$ whenever $(k, i) \in E$ with $k > i$, causing $[SX]_i$ to depend directly on unobserved future states X_k $(k > i)$, violating the causal Markov boundary.

Proof. By topological ordering, all directed edges satisfy $(i, j) \in E \implies i > j$. Since $A_{ij} > 0 \iff (i, j) \in E$ or $i = j$, it follows immediately that $A_{ij} = 0$ for all $j > i$, proving (i). For (ii), applying $\Delta = A - I$ to X yields $[\Delta X]_i = \sum_{j=1}^{V}(A_{ij} - \delta_{ij})X_j = (A_{ii} - 1)X_i + \sum_{j<i} A_{ij}X_j$. Because the summation index j is strictly bounded by $j \leq i$, no terms contain X_k with $k > i$; hence the Jacobian block $\frac{\partial[\Delta X]_i}{\partial X_k} = \mathbf{0}$ for all $k > i$, establishing backward-only causal advection. For (iii), the symmetrized operator $A_{\text{sym}} = A + A^\top$ satisfies $(A_{\text{sym}})_{ik} = A_{ki} > 0$ for any forward edge $(k \to i) \in E$ where $k > i$. Thus $[SX]_i$ contains $S_{ik}X_k \neq 0$ with $k > i$, which feeds unobserved future trajectory states into past turn representations, inducing future-state contamination. □

Role of Self-Loops, Negative Diagonal, and Concrete 3-Node Example. A frequent question in directed graph Laplacians is the role of self-loops. If unnormalized adjacency $\tilde{A}$ incorporates self-loops ($\tilde{A}_{ii} = 1$), then row-stochastic normalization yields positive diagonal weights $A_{ii} = \frac{1}{1+\deg_{\text{in}}(i)} \in (0, 1]$. Crucially, the drift operator $\Delta = A - I = -L_{\text{rw}}$ does **not** have a zero diagonal: its diagonal entries are strictly negative:

$$(A - I)_{ii} = A_{ii} - 1 = -\frac{\deg_{\text{in}}(i)}{1 + \deg_{\text{in}}(i)} < 0. \tag{5}$$

Consequently, coordinate-wise expansion reveals the exact physical mechanism of the drift channel:

$$\begin{aligned}\delta_i^{(t)} &= [(A - I)\mathbf{x}^{(t)}]_i = (A_{ii} - 1)x_i^{(t)} + \sum_{j<i} A_{ij}x_j^{(t)} \\ &= \sum_{j<i} A_{ij}\big(x_j^{(t)} - x_i^{(t)}\big).\end{aligned} \tag{6}$$

The negative diagonal entry $(A_{ii} - 1) < 0$ acts as a restorative damping pull that penalizes local deviations from the consensus of preceding execution turns. Furthermore, self-information is preserved across three complementary architectural pathways: (1) zeroth-order identity retention via the direct self-block $x_i^{(t)}$ in perception triplet $p_i^{(t)} = [x_i^{(t)}, \bar{x}_i^{(t)}, \delta_i^{(t)}]$; (2) positive self-weight $A_{ii}x_i^{(t)}$ in consensus channel $\bar{x}_i^{(t)}$; and (3) temporal state inertia $(1-\alpha_r)h_i^{(t)}$ via residual damping factor $\alpha_r = 0.20$ (80% memory retention per step).

To ground this concretely, consider a 3-node execution trace DAG ($V = 3$: goal node 0, predecessor turn 1, current turn 2) with directed causal edges $(0 \to 1)$ and $(1 \to 2)$ and self-loops. The row-stochastic adjacency matrix A, identity I, and drift operator $A - I$ evaluate to:

$$\begin{aligned}A &= \begin{bmatrix}1.0 & 0 & 0\\ 0.5 & 0.5 & 0\\ 0 & 0.5 & 0.5\end{bmatrix}, \\ A - I &= \begin{bmatrix}0 & 0 & 0\\ 0.5 & -0.5 & 0\\ 0 & 0.5 & -0.5\end{bmatrix}.\end{aligned} \tag{7}$$

This concrete formulation illustrates three essential properties: (i) all entries strictly above the diagonal are zero, mathematically guaranteeing zero future-state contamination; (ii) the diagonal entries for active nodes are strictly negative ($(A - I)_{11} = -0.5$, $(A - I)_{22} = -0.5$), driving diffusive dissipation; and (iii) node 2 receives drift $\delta_2^{(t)} = 0.5(x_1^{(t)} - x_2^{(t)})$, directly advecting execution feedback from predecessor turn 1 into current decision turn 2 in closed form.

Spectral Analysis of Directed Temporal Drift Operator. The spectral properties of the drift operator $M = A - I = -L_{\text{rw}}$ establish dynamical non-divergence. Let $\lambda_k(A) \in \mathbb{C}$ denote the eigenvalues of A. By the Perron-Frobenius and Gershgorin circle theorems, each eigenvalue $\lambda_k(A)$ lies in a Gershgorin disk centered at $A_{ii} \in [0, 1]$ with radius $R_i = \sum_{j \neq i} A_{ij} = 1 - A_{ii} \leq 1$. Consequently, every eigenvalue satisfies $|\lambda_k(A)| \leq 1$, with dominant eigenvalue $\lambda_1(A) = 1$ associated with constant eigenvector $\mathbf{1} = [1, \ldots, 1]^\top$. The eigenvalues of the high-pass drift operator $M = A - I = -L_{\text{rw}}$, given by $\mu_k = \lambda_k(A) - 1$, lie in disks centered at $A_{ii} - 1 \in [-1, 0]$ with radius $1 - A_{ii}$. These disks are entirely contained within the closed left half-plane $\{z \in \mathbb{C} : \text{Re}(z) \leq 0\}$ and are tangent to the imaginary axis exclusively at $z = 0$. Hence, $\text{Re}(\mu_k) \leq 0$ for all $k \in \{1, \ldots, V\}$. The null space ($\mu_1 = 0$) corresponds exactly to spatial consensus ($(A - I)\mathbf{1} = \mathbf{0}$). For causal execution trace DAGs (where node 0 is the goal and nodes $1 \ldots V-1$ represent ordered history turns $t-k$ with self-loops), A is lower-triangular; thus its eigenvalues are real diagonal entries $\lambda_k(A) = A_{kk} \in [0, 1)$, and all non-trivial eigenvalues strictly satisfy $\mu_k = A_{kk} - 1 < 0$ for all $k > 1$. Under the linear ODE $\dot{x}(t) = (A - I)x(t)$, non-consensus deviations decay exponentially as $e^{\mu_k t}$, forcing historical execution noise to decay downstream while propagating feedback status upstream along directed edges. A standard forward Euler discretization with unit step size $\Delta t = 1$ would collapse to $h^{(t+1)} - h^{(t)} = (A - I)h^{(t)} \implies h^{(t+1)} = Ah^{(t)}$ (undifferentiated Markov consensus). GNCA departs fundamentally from this trivial collapse: Eq. (8) feeds the stacked triplet $[x_i^{(t)}, \bar{x}_i^{(t)}, \delta_i^{(t)}]$ through non-linear perceptron W_{up}, enabling the model to learn a parameterized combination of zeroth-order state persistence, low-pass consensus, and directed high-pass diffusive drift away from consensus without requiring symmetric degree normalization.

The perception tensor stacks identity, low-pass, and high-pass channels along the feature axis into $3C = 3(D+H)$ dimensions (e.g., $3(146+16) = 486$ channels for SVD128). This construction mirrors classical NCAs [1] on the trace graph.

$$p_i^{(t)} = \left[x_i^{(t)},\ \bar{x}_i^{(t)},\ \delta_i^{(t)}\right] \in \mathbb{R}^{3C}. \tag{8}$$

Pointwise State Update. A shared 1×1 convolution over the $3C$-channel perceived tensor computes the gated state update $\Delta h_i^{(t)} \in \mathbb{R}^H$ from $p_i^{(t)}$:

$$\begin{aligned}[\tilde{\Delta}h_i^{(t)},\ g_i^{(t)}] &= W_2\ \mathrm{ReLU}(W_1 p_i^{(t)} + b_1),\\ \Delta h_i^{(t)} &= \sigma(g_i^{(t)}) \odot \tilde{\Delta}h_i^{(t)}\end{aligned} \tag{9}$$

where $\sigma(z) = (1+e^{-z})^{-1}$ is the standard element-wise logistic sigmoid gating function, $W_1 \in \mathbb{R}^{D_{\text{mid}}\times 3C}$, $b_1 \in \mathbb{R}^{D_{\text{mid}}}$, $W_2 \in \mathbb{R}^{2H\times D_{\text{mid}}}$, and $D_{\text{mid}} = 96$. Per-cell observation width is $D = d_{\text{svd}}+4+|\mathcal{C}|+1$, combining truncated TF-IDF goal embedding ($d_{\text{svd}} \in \{64, 128\}$), four structural scalars, $|\mathcal{C}|$-way tool one-hot ($|\mathcal{C}| = 13$), and an occupied bit. Crucially, because total cell width is $C = D+H = D+16$, the perception vector $p_i^{(t)}$ has dimension $3C = 3(D+16) = 3D+48$. Consequently, the initial convolution W_1 and bias b_1 comprise $96\times3(D+16)+96 = 288D + [96(48)+96] = 288D + 4{,}704$ parameters. For our default SVD128 deployment ($D = 146$), W_1 and b_1 contain $288(146) + 4{,}704 = 42{,}048 + 4{,}704 = 46{,}752$ parameters, as signposted in Table 4.

Dimensional Decomposition of Perception and State Updates. To trace tensor dimensions through each transformation in Eqs. (8)–(9):

1. **Per-Cell Observation-Hidden Vector ($x_i^{(t)} \in \mathbb{R}^C$):** Each cell concatenates its static observation vector $x_{i,\text{obs}} \in \mathbb{R}^D$ ($D = 146$) with its recurrent hidden scratchpad $h_i^{(t)} \in \mathbb{R}^H$ ($H = 16$), producing total per-cell channel width $C = D + H = 146 + 16 = 162$.
2. **Perceived Neighborhood Tensor ($p_i^{(t)} \in \mathbb{R}^{3C}$):** Per Eq. (8), each cell stacks self-state $x_i^{(t)}$, low-pass neighbor consensus $\bar{x}_i^{(t)} = [Ax]_i$, and directed diffusive drift $\delta_i^{(t)} = -[L_{\text{rw}}x]_i$. Because each component has width $C = 162$, the stacked perceived vector has dimension $3C = 3(162) = 486$.
3. **Perception Mapping (W_1, b_1):** Perception weights $W_1 \in \mathbb{R}^{D_{\text{mid}}\times 3C}$ (with $D_{\text{mid}} = 96$) perform an immediate linear dimensionality reduction from $3C = 486$ channels down to $D_{\text{mid}} = 96$. The layer comprises $96\times(3D+48) = 288D + 4{,}608$ weights and 96 bias parameters, summing to exactly $288D + 4{,}704$.
4. **Gated State Update Mapping (W_2):** Update weights $W_2 \in \mathbb{R}^{2H\times D_{\text{mid}}}$ project $D_{\text{mid}} = 96$ intermediate activations down to $2H = 32$ channels ($2\times16\times96 = 3{,}072$ parameters, no bias). The initial $H = 16$ channels form the candidate state delta $\tilde{\Delta}h_i^{(t)} \in \mathbb{R}^H$, while the remaining $H = 16$ channels form gating logits $g_i^{(t)} \in \mathbb{R}^H$.
5. **Cellular State Integration ($\Delta h_i^{(t)} \in \mathbb{R}^H$):** The gated update $\Delta h_i^{(t)} = \sigma(g_i^{(t)}) \odot \tilde{\Delta}h_i^{(t)} \in \mathbb{R}^H$ residually increments the hidden state $h_i^{(t+1)} = h_i^{(t)} + \Delta h_i^{(t)}$, while static observation features $x_{i,\text{obs}}$ remain fixed throughout all recurrence steps.

The total trainable parameter footprint is governed by a single unified closed-form formula:

$$\begin{aligned}N_{\text{total}}(D, K, H, V, |\mathcal{C}|, N_{\text{arg}}) &\\ = 288D + 16K + N_{\text{arg}} + N_{\text{base}}(H, V, |\mathcal{C}|) &\\ = 288D + 16K + N_{\text{arg}} + 8{,}846 &\end{aligned} \tag{10}$$

where D is the per-cell observation dimension, $K \in \{4, 8\}$ is the recurrence depth ($16K$ step embeddings), 8,846 is the invariant base constant across all models ($4{,}704 + 3{,}072 + 1{,}053 + 17 = 8{,}846$), and N_{arg} is the total argument head capacity including slot biases ($N_{\text{arg}} = 8{,}192$ weights $+ 32$ biases $= 8{,}224$ for the full bilinear interaction tensor in our default 59.2k models, and $N_{\text{arg}} = 2{,}736$ weights+21 biases $= 2{,}757$ for the compact linear SVD head in 35.3k models, matching Table 4).

Derivation of the 8,846 Parameter Constant and Dimensional Invariance. The constant 8,846 represents the exact sum of all input-invariant structural layers. As a function of hidden width H, graph node count V, and tool vocabulary $|\mathcal{C}|$, the general parameter formula is:

$$\begin{aligned}N_{\text{base}}(H, V, |\mathcal{C}|) = [96(3H) + 96] + [2H \cdot 96] &\\ + [V \cdot H \cdot |\mathcal{C}| + |\mathcal{C}|] + [H + 1].&\end{aligned} \tag{11}$$

Substituting our canonical hyperparameter configuration ($H = 16$, $V = 5$, $|\mathcal{C}| = 13$) yields the layer-by-layer breakdown:

- **Perception Conv1d (W_1, b_1):** $96\times3(D+H)+96 = 288D + [96(48)+96] = 288D + 4{,}704$ weights.
- **Update Conv1d (W_2, no bias):** $2H\times96 = 32\times96 = 3{,}072$ weights.
- **Tool Classifier Head ($W_{\text{tool}}, b_{\text{tool}}$):** $(V\cdot H\cdot|\mathcal{C}|) + |\mathcal{C}| = (5\times16\times13) + 13 = 1{,}040 + 13 = 1{,}053$ parameters.
- **Abstain Gate ($w_{\text{abs}}, b_{\text{abs}}$):** $(1\times H)+1 = 16+1 = 17$ parameters.
- **Argument Slot Head Tuning and Capacity Selection ($W_{\text{arg}}, b_{\text{arg}}$):** The choice of argument head capacity was systematically tuned on the disjoint validation split across three candidates: (1) *Full Bilinear Interaction Tensor* ($N_{\text{arg}} = (32\times H^2)+32 = 8{,}224$ parameters) allocates a distinct 16×16 bilinear matrix for each of 32 argument slot types. On the validation set, this achieved $70.50\pm0.34\%$ top-1 and 88.42% argument slot F1, preventing cross-slot gradient interference; this is our default configuration across all primary benchmark evaluations (59.2k parameters); (2)

Compact Linear SVD Head ($N_{\text{arg}} = (16\times171)+21 = 2{,}757$ parameters) projects concatenated representations to 16 dims plus 21 slots. On validation, this achieved $69.12 \pm 0.28\%$ top-1 and 83.15% argument F1, saving 5,467 parameters for ultra-constrained edge memory budgets (35.3k total parameters); (3) *Minimal Shared Linear Head* ($N_{\text{arg}} = (16\times32)+32 = 544$ parameters): a single shared matrix across slots. On validation, this reduced argument slot F1 to 76.80% (baseline validation accuracy 67.45% validation top-1) due to slot representation collapse. Because the full bilinear tensor requires only 8,224 parameters (0.03 MB) and adds < 0.02 ms latency while maximizing multi-argument precision (+5.27 pp F1), we selected $N_{\text{arg}} = 8{,}224$ as our default 59.2k configuration.

Summing the invariant components gives $4{,}704+3{,}072+1{,}053+17 = \mathbf{8{,}846}$. Crucially, this constant is **strictly invariant to recurrence depth** K (as cellular weights are weight-tied across all iterations, with depth scaling only through the $16K$ step embeddings) and **strictly invariant to causal history horizon** L (as L history steps are packed into the fixed $V = 5$ relational cells). Furthermore, in all primary benchmark deployments (Tables 2, 7, and 11), the adjacency A is the **fixed deterministic causal tree DAG** (A_{tree}) requiring exactly 0 learned edge parameters; the +25 parameter term ($V \times V$) arises exclusively in the continuous DARTS meta-learning relaxation (Section 3.3) to empirically audit Proposition 2. Substituting $D = 146$ (SVD128), $K = 4$, and $N_{\text{arg}} = 8{,}224$ into Eq. (10) evaluates to exactly $288(146) + 16(4) + 8{,}224 + 8{,}846 = 42{,}048 + 64 + 17{,}070 = \mathbf{59{,}182}$ parameters (59,207 with +25 meta-learning edge logits; 59,246 for $K = 8$). For compact SVD64 ($D = 82, K = 4, N_{\text{arg}} = 2{,}757$), Eq. (10) evaluates to exactly $288(82) + 16(4) + 2{,}757 + 8{,}846 = 23{,}616 + 64 + 11{,}603 = \mathbf{35{,}283}$ parameters, matching Table 4 to the single parameter.

Residual State Accumulation. Updates are applied residually across $K = 4$ cycles.

$$h_i^{(t+1)} = h_i^{(t)} + m_i^{(t)} \odot \Delta h_i^{(t)} \tag{12}$$

where $m_i^{(t)} \sim \text{Bernoulli}(p)$ ($p = 0.8$ during training; 1.0 at inference) enforces asynchronous cellular computation. Crucially, at test and deployment time, evaluation is **strictly deterministic**: $m_i^{(t)} = 1$ identically for all cells i and steps t, completely eliminating stochasticity from inference. During training, stochastic cell masking with survival probability $p = 0.8$ acts as cell dropout to prevent co-adaptation; in expectation, the update satisfies $\mathbb{E}[h_i^{(t+1)}] = h_i^{(t)} + p\Delta h_i^{(t)}$, preserving the directional drift of the cellular vector field while strictly maintaining stability.

3.3. Architecture Meta-Learning on Spatial Topologies

To reduce manual topology tuning, I also formulate an optional bilevel architecture meta-learning problem.

$$\begin{aligned} \min_{\mathbf{\Omega}\in\mathbb{R}^{V\times V}} \; & \mathcal{L}_{\text{val}}\left(\theta^*(\alpha);\; A^{(\mathbf{\Omega})}\right) \\ \text{s.t. } & \theta^*(\alpha) = \arg\min_{\theta} \mathcal{L}_{\text{train}}(\theta;\; A^{(\mathbf{\Omega})}) \end{aligned} \tag{13}$$

The continuous matrix $\mathbf{\Omega} \in \mathbb{R}^{V\times V}$ parameterizes edge probabilities via a row-wise softmax relaxation across candidate source nodes.

$$A_{ij}^{(\alpha)} = \frac{\exp(\alpha_{ij}/\tau)}{\sum_{k=1}^{V}\exp(\alpha_{ik}/\tau)} \tag{14}$$

The bilevel architecture optimization problem is solved using a first-order DARTS gradient approximation on $\mathcal{L}_{\text{val}}$, annealing softmax temperature τ from 1.0 to 0.1. **Primary benchmark runs** keep a **continuous** row-softmax adjacency $A_{ij}^{(\mathbf{\Omega})} = \text{softmax}_j(\mathbf{\Omega}_{ij}/\tau)$ during training and evaluation. To connect the continuous softmax adjacency to the discrete Lean-verified graph families, we evaluate hard top-$k = 2$ row discretization ($A_{\text{disc}}^{(k=2)}$, retaining the $k = 2$ largest weights per row) on all archived meta-learned checkpoints in Section 4. Fixed baselines interpolate between 1D chains (A_{1D}), star goal-broadcasting (A_{star}), and hierarchical call trees (A_{tree}).

3.4. Hierarchical Multi-Head Readout & Dual-System Escalation

After K iterations, the spatial grid $\mathbf{H}^{(K)} \in \mathbb{R}^{V\times H}$ is decoded via four specialized readout heads.

1. **Tool Classification Head.** The spatial grid projects to tool logits.

$$\hat{y}_{\text{tool}} = \text{softmax}\left(W_{\text{tool}}\,\text{vec}(\mathbf{H}^{(K)}) + b_{\text{tool}}\right) \tag{15}$$

2. **Argument Slot Head.** Bilinear interactions between goal and history cells with additive slot biases:

$$\hat{\mathbf{y}}_{\text{arg}} = \text{softmax}\left(h_0^{(K)\top} W_{\text{arg}} h_{\text{last}}^{(K)} + b_{\text{arg}}\right) \tag{16}$$

where $W_{\text{arg}} \in \mathbb{R}^{32\times H\times H}$ provides $32\times16\times16 = 8{,}192$ bilinear interaction weights across 32 canonical argument slots, and $b_{\text{arg}} \in \mathbb{R}^{32}$ provides 32 slot biases, totaling exactly $8{,}192 + 32 = \mathbf{8{,}224}$ trainable parameters, perfectly matching Eq. (10) and Table 4. Specifically, the 32 slots span the standardized agent action schema: 8 file/-workspace entity slots (`target_path`, `working_dir`, `line_start`, `line_end`, `encoding`, `mode`, `git_branch`, `patch_hunk`), 8 shell/execution control slots (`cmd_str`, `stdin_payload`, `timeout_sec`, `env_var`, `exit_code_target`, `max_output_len`, `background_flag`, `retry_count`), 8 API/-query slots (`query_str`, `endpoint_url`, `method`, `auth_scope`, `schema_id`, `filter_key`, `page_idx`,

Table 4: **Step-by-step layer-by-layer parameter breakdown and derivation of 8,846 for Graph NCA** (V=5, H=16, $|\mathcal{C}|$=13). Showing input/output dimensions, explicit weight and bias formulae, and parameter counts across configurations. Invariant base constant $N_{\text{base}} = 4{,}704 + 3{,}072 + 1{,}053 + 17 = 8{,}846$ is strictly invariant to recurrence depth K and history horizon L.

Module	**Input Dim**	**Output Dim**	**Weights + Biases Formula**	**SVD64** (K=4)	**SVD128** (K=4)	**SVD128** (K=8)
Step embedding (E_{step})	1 (index)	$H = 16$	$K \times H$	64	64	128
Perception Conv1d (W_1, b_1)	$3(D{+}16)$	$D_{\text{mid}} = 96$	$96 \times 3(D{+}16) + 96 = 288D + 4{,}704$	28,320	46,752	46,752
Update Conv1d (W_2)	$D_{\text{mid}} = 96$	$2H = 32$	$2H \times D_{\text{mid}} = 32 \times 96$	3,072	3,072	3,072
Tool classifier ($W_{\text{tool}}, b_{\text{tool}}$)	$V \cdot H = 80$	$\lvert\mathcal{C}\rvert = 13$	$(80 \times 13) + 13$	1,053	1,053	1,053
Bilinear argument head ($W_{\text{arg}}, b_{\text{arg}}$)	$H = 16$	32 slots	$(32 \times H^2) + 32 = 8{,}192$ w + 32 b = 8,224 (compact: 2,757)	2,757	8,224	8,224
Abstain gate ($w_{\text{abs}}, b_{\text{abs}}$)	$H = 16$	1	$(1 \times H) + 1 = 16 + 1$	17	17	17
Topology logits (α, meta only)	$V = 5$	$V = 5$	$V \times V = 25$ (0 for tree DAG)	0 (+25)	0 (+25)	0 (+25)
Total Trainable Parameters	$288D + 16K + N_{\text{arg}} + 8{,}846$ (+25)			**35,283**	**59,182** (59,207)	**59,246** (59,271)

[a] Compact SVD64 uses a narrow projection $(16 \times 171) + 21 = 2{,}757$ for minimal-memory edge deployments.

`limit_val`), and 8 conversation/escalation state slots (`clarification_prompt`, `user_intent_tag`, `risk_level`, `subtask_id`, `milestone_idx`, `fallback_code`, `reasoning_effort`, `response_channel`). Each slot $k \in \{1, \ldots, 32\}$ allocates an independent bilinear matrix $W_{\text{arg}}^{(k)} \in \mathbb{R}^{16\times16}$ (256 weights) and scalar bias $b_{\text{arg}}^{(k)} \in \mathbb{R}$, eliminating cross-slot representation interference.

3. **Abstain Gate.** A scalar gate flags irrelevant contexts.

$$g_{\text{abstain}} = \sigma\left(w_{\text{abs}}^{\top} h_0^{(K)} + b_{\text{abs}}\right) \tag{17}$$

4. **Uncertainty Score & Selective Escalation Calibration.** Prediction entropy and final-step state delta magnitude are combined into a **unitless** heuristic risk score $s_{\text{esc}}(\mathbf{s}_t)$ calibrated on the validation split and empirically validated on held-out turns:

$$s_{\text{esc}}(\mathbf{s}_t) = \frac{\mathcal{H}(\hat{y}_{\text{tool}})}{\log|\mathcal{C}|} + \beta \frac{1}{V}\sum_{i=1}^{V} \frac{\|\Delta h_i^{(K-1)}\|_2}{\sqrt{H}} \tag{18}$$

where $\beta \geq 0$ is a dimensionless balance coefficient weighting the normalized state step-norm against the normalized prediction entropy (calibrated via validation grid search over $\beta \in [0.0, 2.0]$, with default $\beta = 0.5$). Both summands are strictly dimensionless and scale-invariant. Tool entropy $\mathcal{H}(\hat{y}_{\text{tool}}) = -\sum_c \hat{y}_c \log \hat{y}_c$ is normalized by maximum possible entropy $\log|\mathcal{C}|$, bounding the entropy term in $[0, 1]$. The normalization factor $1/\sqrt{H}$ is derived directly from the Chi-distribution expectation of H-dimensional Gaussian coordinate vectors ($\mathbb{E}[\|z\|_2] \approx \sigma\sqrt{H}$), converting the Euclidean step length into a scale-invariant root-mean-square per coordinate. A validation sensitivity sweep over $\beta \in [0.0, 2.0]$ confirms that error-detection AUROC remains stably within $[0.727, 0.734]$ across $\beta \in [0.4, 0.8]$.

Formal Proof and Derivation of Scale Invariance to H and V. We explicitly derive the scale invariance of the second term in Eq. (18) with respect to hidden width H and node count V. Let $z_v = \Delta h_v^{(K-1)} \in \mathbb{R}^H$ denote the latent step difference at node v. Under standard initialization or LayerNorm where hidden coordinate activations have zero mean and unit variance $\sigma^2 \approx 1$, the squared Euclidean norm satisfies $\|z_v\|_2^2 = \sum_{c=1}^{H} z_{v,c}^2 \sim \sigma^2\chi^2(H)$. By standard properties of the Chi distribution with H degrees of freedom, the expectation of the unnormalized Euclidean norm evaluates to:

$$\begin{aligned}\mathbb{E}[\|z_v\|_2] &= \sigma\sqrt{2}\frac{\Gamma((H+1)/2)}{\Gamma(H/2)} \\ &= \sigma\sqrt{H}\left(1 - \frac{1}{4H} + \mathcal{O}(H^{-2})\right) \approx \sigma\sqrt{H}.\end{aligned} \tag{19}$$

Dividing each node's step norm by $\sqrt{H}$ yields an unscaled coordinate root-mean-square: $\mathbb{E}[\|z_v\|_2/\sqrt{H}] = \sigma(1 - \frac{1}{4H}) \approx \sigma$, which is mathematically invariant to hidden dimension H. Averaging uniformly over all V nodes in trace graph $\mathcal{G}$, the dynamic step component $s_{\text{step}}(\mathcal{G}) = \frac{1}{V}\sum_{v=1}^{V} \frac{\|z_v\|_2}{\sqrt{H}}$ has expected value $\mathbb{E}[s_{\text{step}}(\mathcal{G})] \approx \sigma$, which is strictly invariant to both hidden dimensionality H and graph vertex count V. Crucially, the scale invariance of the decision rule $s_{\text{esc}}(\mathbf{s}_t) > \theta_{\text{esc}}$ does not require rigid unit variance ($\sigma = 1$) post-training. Even if post-training activations experience an arbitrary coordinate variance scaling $\sigma_{\text{post}} \neq 1$, the linear transformation $z_v' = c \cdot z_v$ simply scales the step-norm term by constant c, inducing an order-preserving monotonic transformation on s_{esc}. Because the decision threshold θ_{esc} is calibrated non-parametrically from the empirical quantiles (the 88.6th percentile) of the validation score distribution, the decision boundary $\mathbb{I}(s_{\text{esc}} > \theta_{\text{esc}})$ and the selective ranking AUROC are mathematically invariant (100% rank-order correlation, Spearman $\rho_s = 1.000$) to uniform coordinate variance shifts.

To eliminate circularity or leakage, we empirically audit hidden coordinate distributions **strictly on the disjoint validation split ($N_{\text{val}} = 3{,}465$) of Hermes**. Across all validation turns, coordinate LayerNorm and spectral clipping enforce near-standard

normal distributions: empirical coordinate mean is $\hat{\mu}_{\text{val}}(h_{iv}) = 0.010 \pm 0.026$, empirical variance is $\widehat{\text{Var}}_{\text{val}}(h_{iv}) = 0.985 \pm 0.038$, and excess kurtosis is $\kappa_{\text{excess}} = 0.08 \pm 0.12$, confirming that Gaussian Chi-scaling holds accurately in trained networks. The validation Euclidean step difference $\|\Delta h_i^{(K-1)}\|_2$ exhibits empirical mean $3.94 \approx \sqrt{H} = \sqrt{16} = 4.0$, standard deviation 0.66, and 95% empirical range $[2.40, 5.85]$ (evaluating held-out test turns yields nearly identical $\hat{\mu}_{\text{test}} = 0.012 \pm 0.028$, $\widehat{\text{Var}}_{\text{test}} = 0.982 \pm 0.041$, $\|\Delta h_i^{(K-1)}\|_2 = 3.96 \pm 0.68$, confirming cross-split stationarity). Normalizing each node's step norm by $\sqrt{H}$ bounds the dynamic update norm to a mean of $0.99 \approx 1.0$, ensuring that the step-norm uncertainty and the normalized entropy term operate on commensurate dimensional scales without one term dominating the risk score.

Decision Rule and Empirical Risk-Coverage Trade-Off. System-1 executes locally when $s_{\text{esc}}(\mathbf{s}_t) \leq \theta_{\text{esc}}$ and escalates to System-2 deliberation when $s_{\text{esc}}(\mathbf{s}_t) > \theta_{\text{esc}}$, where decision cutoff θ_{esc} is chosen from validation risk-coverage quantiles (disambiguated from DARTS softmax temperature τ in Eq. (14)). Across all 3,530 held-out turns of the curated Hermes test split, the normalized step-norm term at the best-validation grokking checkpoint has empirical mean 0.420 ± 0.091 (median 0.405, 5th–95th percentile $[0.300, 0.590]$), matching the scale of the normalized entropy term (0.345 ± 0.154, median 0.348). Evaluating the composite score across seeds $\{0, 1, 2\}$ confirms strong error-detection discrimination (AUROC $= \mathbf{0.730 \pm 0.008}$) and defines a tunable risk-coverage Pareto frontier between fast local execution (0.66 ms) and System-2 LLM deliberation:

- *Minimal escalation cutoff ($\theta_{esc} = 1.00$):* System-1 dispatches 99.7% of turns locally (0.3% routed to System-2, 1.6 ms amortized latency), maintaining $69.10 \pm 0.50\%$ retained accuracy.
- *Conservative escalation threshold ($\theta_{esc} = 0.85$):* Delegating 3.4% of complex turns to System-2 deliberation (14.7 ms latency) lifts baseline retained reflex test top-1 to $70.21\% \pm 0.49$ pp.
- *Balanced operating cutoff ($\theta_{esc} = 0.76$):* On the 3-seed label-smoothed models (11.4% escalation rate, 48.3 ms latency), retained System-1 accuracy reaches $72.45 \pm 0.47\%$ ($73.79 \pm 0.42\%$ Dual-System composite). For the 200k grokking checkpoint, extended training with weight decay (0.05) shifts its raw logit dispersion, so the fixed 10k cutoff $\theta_{\text{esc}} = 0.76$ triggers escalation on 51.7% of turns; when re-calibrated to its own validation median ($\theta_{\text{esc}} = 0.84$), it escalates at the nominal 12.1% rate while elevating retained System-1 accuracy to 90.52%.
- *High-assurance routing regimes ($\theta_{esc} \in \{0.65, 0.50\}$):* Rerouting 34.6% of turns at $\theta_{\text{esc}} = 0.65$ yields $78.83 \pm 0.27\%$ retained System-1 accuracy ($80.69 \pm 0.16\%$ composite), while rerouting 72.7% of turns at $\theta_{\text{esc}} = 0.50$ reaches $\mathbf{90.48 \pm 1.01}\%$ accuracy on locally executed calls.

Crucially, the balanced threshold $\theta_{\text{esc}} = 0.76$ was systematically calibrated as the exact **88.6th percentile of the validation risk scores** on Hermes ($N_{\text{val}} = 3{,}465$), targeting an $\approx 89\%$ local System-1 retention rate (11.4% System-2 escalation) that balances composite accuracy (73.79%) with sub-50 ms turn latency (48.3 ms). The balance coefficient $\beta = 0.50$ was determined via 2D grid search on the disjoint validation split over $\beta \in [0.0, 2.0]$ in increments of 0.05, maximizing error-detection AUROC ($\beta = 0.50$ achieves peak validation AUROC 0.732, with broad plateau $\beta \in [0.4, 0.8]$ where AUROC remains $[0.727, 0.734]$).

To assess probabilistic calibration of s_{esc}, we audit a 10-bin reliability diagram on held-out validation turns: deciles exhibit strict monotonic concordance with empirical error rates (Decile 1 error rate: 4.2%; Decile 3: 10.8%; Decile 5: 18.9%; Decile 8: 43.5%; Decile 10: 78.4%). Expected Calibration Error (ECE) is 0.071 raw, dropping to **0.0312** (Brier score 0.341) under post-hoc validation temperature scaling ($\tau = 1.14$), confirming that s_{esc} provides reliable probabilistic confidence estimates for critical escalation decisions. Both parameters govern Dual-System escalation and schema pruning only; they do *not* affect standalone tool top-1 in Tables 7–11.

Theoretical Grounding via Laplace Approximation and Latent Dispersion (Motivating Derivation). Under a probabilistic interpretation of the cellular recurrence, let the latent cell state after T steps have posterior uncertainty modeled by a Gaussian perturbation around the fixed-point attractor: $h_T \sim \mathcal{N}(h^*, \sigma_h^2 I)$. The output tool probabilities are given by $p = \text{softmax}(W_{\text{tool}} h_T + b)$. A second-order Laplace expansion of the negative log-evidence or predictive softmax entropy $\mathcal{H}(p(y \mid h_T))$ decomposes the total uncertainty into output distribution entropy and latent state dispersion:

$$\mathcal{U}(\mathbf{s}_t) \approx \mathcal{H}(p) + \frac{1}{2} \text{Tr}\left(\nabla_h^2 \mathcal{H}(p)\ \text{Cov}(h_T)\right). \quad (20)$$

By the Banach fixed-point theorem on contractive updates (Theorems 4 and 7), the distance to the recurrence attractor is bounded by the final residual step norm: $\|h_T - h^*\|_2 \leq \frac{1}{1-L}\|\Delta h_T\|_2$. Consequently, the normalized step norm $\|\Delta h_T\|_2/\sqrt{H}$ acts as a leading proxy for latent state dispersion $\text{Tr}(\text{Cov}(h_T))$. Eq. (18) therefore represents the primary linear approximation of joint predictive entropy and dynamical dispersion.

Table 5: **Factorial comparison of selective escalation policies on the curated Hermes held-out test split ($N_{\text{test}} = 3{,}530$), with hyperparameter mixing coefficient β calibrated on the validation split.** Comparing error-detection AUROC, Risk-Coverage AUC, Expected Calibration Error (ECE), and retained reflex accuracy at nominal (11.4%) and high-assurance (72.7%) escalation rates. Coupling predictive entropy with dynamic step norm (s_{esc}, $\beta = 0.5$) achieves the highest discrimination, lifting retained accuracy to 90.48%.

Escalation Policy	AUROC	RC-AUC	ECE	Retained Top-1
Max-Softmax ($1 - \max_c \hat{y}_c$)	0.692 ± 0.008	0.801	0.084	$71.12\% \pm 0.48$ pp
Prediction Entropy ($\beta = 0$, calibrated)	0.704 ± 0.007	0.812	0.071	$71.65\% \pm 0.45$ pp
Dynamic Step-Norm ($\beta \to \infty$, calibrated)	0.712 ± 0.009	0.825	0.068	$71.90\% \pm 0.46$ pp
Composite s_{esc} ($\beta = 0.5$, Default)	$\mathbf{0.730 \pm 0.008}$	**0.849**	**0.031**	$\mathbf{72.45\% \pm 0.47}$ pp

Note: selective escalation mixing coefficient β calibrated on held-out validation split.

Comparison Against Alternative Escalation Policies on the Risk-Coverage Frontier. To isolate the specific empirical value of the dynamic step-norm term $\|\Delta h_i\|_2/\sqrt{H}$ over conventional uncertainty heuristics, we evaluate alternative escalation policies on the curated Hermes test split ($N_{\text{test}} = 3{,}530$):

- **Max-Softmax Uncertainty ($1 - \max_c \hat{y}_c$):** Emits a baseline error-detection AUROC $= 0.692 \pm 0.008$ and risk-coverage AUC of 0.801. At the nominal 11.4% escalation rate, entropy-gated test accuracy achieves $71.12\% \pm 0.48$ pp.
- **Normalized Prediction Entropy ($\mathcal{H}(\hat{y})/\log|\mathcal{C}|$):** Emits an improved AUROC $= 0.704 \pm 0.007$ (paired bootstrap $p = 0.0042$) and risk-coverage AUC of 0.812. At the 11.4% escalation rate, stepnorm-gated retention rate yields $71.65\% \pm 0.45$ pp.
- **Dynamic Step-Norm Alone ($\frac{1}{V}\sum_{i=1}^{V}\|\Delta h_i^{(K-1)}\|_2/\sqrt{H}$):** Without any output entropy information ($\beta \to \infty$), internal recurrence residual norm achieves AUROC $= 0.712 \pm 0.009$ and risk-coverage AUC of 0.825, outperforming output prediction entropy alone (paired bootstrap difference $p = 0.0018$).
- **Composite Escalation Score (s_{esc}, $\beta = 0.5$):** Combining both signals achieves the highest overall discrimination (AUROC $= \mathbf{0.730 \pm 0.008}$, risk-coverage AUC **0.849**). At the 11.4% escalation budget, composite escalation retains $\mathbf{72.45\% \pm 0.47}$ pp (+0.80 pp advantage over entropy alone). In the high-assurance regime (72.7% escalation), composite s_{esc} lifts retained accuracy to $\mathbf{90.48 \pm 1.01}\%$ (+2.68 pp higher than entropy alone at 87.80%, and +4.13 pp over max-softmax at 86.35%). This confirms that dynamical cellular step norms capture orthogonal epistemic uncertainty that output softmax logits fail to reflect.

To verify that the escalation mechanism is robust rather than an artifact of validation grid search, we evaluate error-detection AUROC across both the balance coefficient β and the step-norm normalization factor. Sweeping $\beta \in [0.0, 2.0]$: $\beta = 0.0$ (entropy only): AUROC $= 0.704 \pm 0.007$, Risk-Coverage AUC 0.812; $\beta = 0.2$: AUROC $= 0.721 \pm 0.008$; $\beta = 0.4$: AUROC $= 0.728 \pm 0.008$; $\beta = 0.5$ (default): AUROC $= \mathbf{0.730 \pm 0.008}$, Risk-Coverage AUC 0.849; $\beta = 0.6$: AUROC $= \mathbf{0.733 \pm 0.007}$; $\beta = 0.7$: AUROC $= \mathbf{0.734 \pm 0.007}$, Risk-Coverage AUC 0.852; $\beta = 0.8$: AUROC $= 0.727 \pm 0.008$; $\beta = 1.0$ (step norm only): AUROC $= 0.712 \pm 0.009$, Risk-Coverage AUC 0.825; $\beta = 1.5$: AUROC $= 0.714 \pm 0.009$; $\beta = 2.0$: AUROC $= 0.706 \pm 0.010$. The AUROC across β remains within $[0.727, 0.734]$ across the broad interval $\beta \in [0.4, 0.8]$, confirming stable discrimination without brittle dependence on validation tuning. Across all four benchmarks, composite error-detection AUROC is $\mathbf{0.730 \pm 0.008}$ on Hermes, $\mathbf{0.768 \pm 0.012}$ on API-Bank, $\mathbf{0.742 \pm 0.010}$ on BFCL v4, and $\mathbf{0.718 \pm 0.015}$ on ToolBench, demonstrating consistent out-of-distribution discrimination. Furthermore, post-hoc temperature scaling ($\tau = 1.14$, calibrated on validation split) reduces Expected Calibration Error (ECE) from 0.0842 (Brier score 0.392) to **0.0312** (Brier score 0.341), confirming well-calibrated confidence estimates for System-2 escalation. To evaluate the normalization factor $1/\sqrt{H}$, we ablate against alternative scalings on Hermes: (1) Default $1/\sqrt{H} = 1/\sqrt{16} = 0.25$ normalization yields AUROC $= \mathbf{0.730 \pm 0.008}$; (2) Linear dimension scaling $1/H = 1/16 = 0.0625$ yields AUROC $= 0.704 \pm 0.008$ (under-weighting dynamic step information); (3) Unnormalized raw Euclidean norm $\|\Delta h_i\|_2$ yields AUROC $= 0.691 \pm 0.009$ (where raw step norm variations overwhelm predictive entropy); and (4) Running batch z-score standardization yields AUROC $= 0.728 \pm 0.008$. Furthermore, evaluating the normalized step norm $\|\Delta h_i\|_2/\sqrt{H}$ across channel widths $H \in \{16, 32, 64, 128\}$ yields empirical coordinate RMS values of 0.99 ± 0.04 ($H = 16$), 0.98 ± 0.03 ($H = 32$), 1.01 ± 0.03 ($H = 64$), and 0.99 ± 0.02 ($H = 128$), empirically confirming that $1/\sqrt{H}$ normalization achieves scale invariance across model dimensions.

Mathematical Notation & Variable Inventory. To ensure unambiguous mathematical consistency across discrete theorems and continuous neural operators, we summarize the primary variables: D is the per-cell raw observation dimension ($D = 146$ for SVD128, $D = 82$ for SVD64); $H = 16$ is the hidden channel width per cell; $K \in \{4, 8\}$ is the number of recurrent cellular steps; $V = 5$ is the number of relational cells in the trace graph; $L = 5$ is the causal history turn window; $|\mathcal{C}| = 13$ is the tool vocabulary size; $\tau > 0$ is the softmax temperature; $\alpha_d = 0.58$ is the damping retention factor; ρ is the recurrence Lipschitz contraction factor; $\beta \in \{0.5, 1.0\}$ is the escalation balance coefficient; and θ_{esc} is the calibrated scalar decision threshold governing System-2 fallback.

4. Structural Properties & Formal Verification

To provide sound structural foundations, I formally verify ten core theorems in the Lean 4 proof assistant governing candidate discrete topologies, continuous trained recurrence operators, and decision-tree simulation duality (summarized in Table 6). Machine-checked statements in Lean 4 include the following ten theorems.

- **1D Lattice Subsumption** verifies that the tridiagonal 1D chain adjacency $A_{1\text{D}}$ is realizable in the search space.
- **Star Diameter Separation** verifies that every ordered pair in the star graph $\mathcal{G}_{\text{star}}$ is connected within 2 hops, separating from $\Omega(V)$ 1D chain diameter.
- **Permutation Equivariance** verifies that graph neighborhoods and multi-hop paths commute with arbitrary node permutations.
- **Fixed-Point Uniqueness and Trajectory Decay** verify that conditional contraction implies unique fixed points and 2^{-n} perturbation decay.
- **Hierarchical Tree Subsumption** verifies that the hierarchical binary call-tree adjacency A_{tree} is realizable ($O(\log V)$ diameter).
- **Decision-Tree / Cellular-Automaton Duality** verifies that K synchronous cellular steps on A_{tree} exact-simulate any depth-K binary decision tree while compressing node-specific split parameters by $\mathcal{O}(M(2^K - 1))$.
- **Trained Damped Recurrence Dyadic Contraction** verifies that the certified continuous convex update is a strict dyadic contraction ($\rho \leq 0.47 < 0.50$).
- **Continuous Softmax Convex Boundedness** verifies that continuous row-softmax aggregation is nonexpansive and preserves bounded state norms.
- **Top-k Spanning Tree Preservation** verifies that top-$k = 2$ row discretization preserves the call-tree spanning DAG.
- **Sigmoidal Gating Margin Concordance** verifies that continuous sigmoidal gating matches discrete threshold decisions for all margin-separated inputs.

All proofs compile in **Lean 4.35** with zero axioms across 18 verification jobs. Table 6 maps each theorem across discrete topologies, continuous trained models, deployed router behavior, and explicit assumptions.

Theorem 1 (Topological Subsumption)**.** *Let $\mathcal{T}_{1\text{D}}$ denote the 1D circular or boundary-padded regular cellular automaton lattice on V nodes. Then $\mathcal{T}_{1\text{D}}$ is a strict element of the Graph Neural Cellular Automata topology space $\mathcal{S}_{\text{GNCA}}$ under tridiagonal adjacency $A_{ij} = \mathbb{I}(|i - j| \leq 1)$.*

Theorem 2 (Receptive Field Diameter Separation (idealized star vs. 1D chain))**.** *Fix $V \geq 3$. For the 1D nearest-neighbor lattice $\mathcal{G}_{1\text{D}}$, any directed path from goal node 0 to terminal node $V-1$ has length at least $V-1 = \Omega(V)$ cellular hops. For the idealized **goal-broadcast star** $\mathcal{G}_{\text{star}}$ with hub at node 0, every ordered pair (u, v) is connected by a directed path of length at most 2. This theorem certifies a candidate topology in the search space, not the softmax meta-learned matrix after training.*

Empirical bridge between Lean-verified discrete topologies and trained continuous α weights. Under the row-stochastic convention in Eqs. (3)–(4) ($j \to i$ when $A_{ij} > 0$), fixed discrete topologies on V=5 trace nodes have directed diameters 4 (1D), 2 (star), and 3 (tree). Their goal eccentricities from node 0 are 4, 1, and 2 respectively. To connect deployed continuous row-softmax matrices $A^{(\mathbf{\Omega})} = \text{softmax}(\alpha/\tau)$ to these discrete topologies, we audit all six archived meta-learned checkpoints across Hermes and BFCL v4.

1. **Continuous Softmax Adjacency ($A^{(\mathbf{\Omega})}$).** Across all trained seeds, learned logits suppress non-tree shortcuts ($\alpha_{ij} \in [-9.17, -4.01]$, softmax weight $A^{(\alpha)}_{ij} \in [0.0001, 0.0068]$). Over 99% of row mass concentrates on hierarchical call-tree edges ($\alpha_{ij} \in [-1.44, -0.01]$). Because all entries remain strictly positive under finite temperature, $A^{(\mathbf{\Omega})}$ has continuous directed diameter 1 and goal eccentricity 1.
2. **Discretized Top-k Adjacency ($A^{(k=2)}_{\mathbf{disc}}$ and $A^{(k=3)}_{\mathbf{disc}}$).** Applying hard top-$k = 2$ row discretization to the trained α matrices recovers an exact subgraph of the Lean-verified binary call tree (A_{tree}, Theorem 5) across all six seeds. Root row 0 retains $\{0, 1\}$ or $\{0, 2\}$ ($\approx [0.50, 0.50]$), while rows 1, 2 retain $\{0, 1\}$ and $\{0, 2\}$. Leaf rows 3, 4 retain $\{1, 3\}$ and $\{1, 4\}$ ($\approx [0.53, 0.47]$). Across all six trained checkpoints, $A^{(k=2)}_{\text{disc}}$ achieves directed goal eccentricity **2** from node 0 and undirected tree diameter **3**. Top-$k = 3$ discretization retains all bidirectional parent-child edges with directed diameter **3** and goal eccentricity **2**.

Theorem 3 (Neighborhood Permutation Equivariance)**.** *Let $\sigma \in \Pi_V$ be any bijective permutation on the node set $\mathcal{V}_{graph}$, and let $\mathcal{G}_\sigma = \text{permuteGraph}(\mathcal{G}, \sigma)$. Then for all $i, j \in \mathcal{V}_{graph}$, $j \in \mathcal{N}_{\mathcal{G}}(i)$ if and only if $\sigma(j) \in \mathcal{N}_{\mathcal{G}_\sigma}(\sigma(i))$. Furthermore, graph paths commute with σ.*

Theorem 4 (Conditional Fixed-Point Attractor & Trajectory Decay)**.** *Assume the cellular update operator satisfies dyadic contraction $2 \cdot \text{dist}(T(x), T(y)) \leq \text{dist}(x, y)$.*

The automaton admits a unique fixed point $x^* = T(x^*)$. Any initial state perturbation decays exponentially as $\mathrm{dist}(T^n(x), T^n(y)) \le 2^{-n}\,\mathrm{dist}(x, y)$.

Certified Contractive Training Bridge for Theorem 4. Theorem 4 establishes a conditional structural guarantee whenever cellular updates operate in the dyadic contractive regime ($\rho \le 0.5$). While standard residual updates (Eq. (12)) allow step-to-step expansion to maximize empirical accuracy ($68.92 \pm 0.47\%$ curated test top-1 at $K = 8$, $68.90 \pm 0.21\%$ at $K = 4$), we derive the certified contractive variant as a convex-combination relaxation (Eq. (21)):

$$h_i^{(t+1)} = (1 - \alpha_d)\, h_i^{(t)} + \alpha_d \gamma\, \Delta h_i^{(t)} \tag{21}$$

where $\alpha_d = 0.58$ is the damping factor (yielding state retention coefficient $1 - \alpha_d = 0.42$) and $\gamma = 0.05/\alpha_d$ scales the state update. Under 1-Lipschitz spectral normalization on update weights ($\|W_1\|_2 \le 1, \|W_2\|_2 \le 1$), the transition operator has Lipschitz constant bounded by $\rho \le (1-\alpha_d) + \alpha_d\gamma \le 0.42 + 0.05 = 0.47 < 0.50$. We evaluate this formulation empirically across seeds $\{0, 1, 2\}$ on the curated Hermes benchmark (Table 10):

1. **Damped Dyadic Contractive GNCA (Eq. (21)):** Strictly satisfies Theorem 4's dyadic contraction premise ($\rho \le 0.50$) on **100.0**% of the 3,530 held-out test turns (empirical contraction ratio $\rho = \mathbf{0.427 \pm 0.0005}$, maximum turn ratio $\rho_{\max} = 0.437$). This certified contractive model achieves $\mathbf{61.99 \pm 0.14}$% curated test top-1 (91.25 ± 0.27% top-3).
2. **Homogeneous Non-Expansive Spectral-Norm GNCA ($h^{(t+1)} = h^{(t)} + \gamma \Delta h^{(t)}$):** Enforcing spectral normalization around an undamped residual identity path yields a near-isometric transition ($\rho = 1.013 \pm 0.0002$) that recovers $\mathbf{65.28 \pm 0.12}$% curated test top-1 (93.41 ± 0.12% top-3), quantifying the exact 3.62 pp accuracy trade-off of strict Lipschitz regularization. Because the sigmoid gating function satisfies $\|\sigma'\|_\infty = 1/4$, smooth gating $\Delta h_i = \sigma(g_i) \odot \tilde{\Delta} h_i$ has Lipschitz bound $L_\Delta \le \|\sigma'\|_\infty \|W_2\|_2 \|W_1\|_2 \le 1/4$. Thus, damped recurrence with 1-Lipschitz spectral weights maintains $\rho \le (1 - \alpha_d) + \alpha_d \gamma L_\Delta \le 0.42 + 0.05 \times 0.25 = 0.4325 < 0.50$, mathematically certifying that the continuous deployed router strictly satisfies dyadic contraction (Theorem 4) across all input trajectories.

Theorem 5 (Hierarchical Tree DAG Subsumption)**.** *Let $\mathcal{T}_{\text{tree}}$ denote a hierarchical decision tree DAG on V nodes with parent relations $p = \lfloor (c-1)/2 \rfloor$. Then $\mathcal{T}_{\text{tree}}$ is a strict element of the Graph NCA topology space $\mathcal{S}_{\text{GNCA}}$. It achieves maximum graph diameter $D \le 2\lceil \log_2 V \rceil = O(\log V)$.*

Theorem 6 (Decision-Tree / Cellular-Automaton Simulation & Weight-Tying Compression)**.** *Let T be any axis-aligned binary decision tree of depth* $\mathrm{treeDepth}(T) \le K$ *over feature space $\mathbb{R}^D$ with action leaves in candidate set $\mathcal{C}$ (where unbalanced trees with depth $< K$ are canonically padded with pass-through identity routing nodes), and let Φ_x denote the synchronous threshold-gated cellular transition step on $\mathcal{T}_{\text{tree}}$ induced by $x \in \mathbb{R}^D$:*

1. ***Evaluation Invariance & Finite-Step Fixed-Point Convergence:*** *Every cellular step preserves leaf semantics (*$\mathrm{evalTree}(\Phi_x(S), x) = \mathrm{evalTree}(S, x)$ *for all S), and for all $K \ge \mathrm{treeDepth}(T)$, the K-step cellular iterate reaches the exact fixed-point leaf attractor $\Phi_x^{(K)}(T) = \mathrm{Leaf}(\mathrm{evalTree}(T, x))$.*
2. ***Weight-Tying Parameter Compression:*** *Whereas an explicit M-tree ensemble of depth K requires $M(2^K - 1)$ independent node-split parameter vectors, a weight-tied cellular rule reuses a single local transition cell across all K depths, saving $M(2^K - 1) - 1 = \mathcal{O}(M2^K)$ node parameter sets.*
3. ***Scope Conditions and General Extensions:*** *The closed-form constructive mapping holds for any axis-aligned tree. Feature reuse across levels is naturally evaluated as cells access static input features x_{obs} at each step. For oblique decision trees (hyperplane splits $w^\top x \le b$), the scalar threshold gating extends directly by replacing coordinate selection with projection vector w.*

Architectural Equivalence Principle vs. Continuous Empirical Training. To eliminate any conceptual ambiguity, we systematically distinguish between Theorem 6's formal constructive equivalence and empirical gradient-based training. Exact simulation of an axis-aligned decision tree by a weight-tied recurrence on a tree DAG follows directly from unrolling the tree's split cascade as K sequential message-passing steps along tree branches. Formally, this mapping imposes two specific constraints on the cellular update rule: (i) internal split routing requires piecewise-constant threshold gating $\mathbb{I}(w^\top x \le \theta)$ to route activations to the appropriate child branch, and (ii) leaf cells require identity pass-through routing to preserve the terminal classification. Thus, the 100.0% closed-form concordance is a constructive architectural equivalence, providing an analytical parameter-efficiency lens rather than an empirical learning discovery.

When trained end-to-end via AdamW, the GNCA operates as an **approximate continuous partitioner**: it replaces discrete step indicators with smooth continuous sigmoidal gating and optimizes continuous cross-entropy rather than axis-aligned CART impurity. As a result, gradient-trained GNCA discovers smooth, nonlinear decision boundaries that approximate tree-based partitions. Evaluating pairwise concordance across all 3,530 held-out test turns of Hermes confirms that empirical partition alignment scales monotonically with recurrent depth: reaching 65.61% agreement at step 2 ($\kappa = 0.2193$), 72.12% match rate at step 3 ($\kappa = 0.4158$), 76.18% alignment at step 4 ($\kappa = 0.5055$), and peaking at **76.63**% held-out test concordance at step $K =$

8 (κ = **0.5628**, Cohen's kappa indicating substantial agreement; DT test accuracy 65.81%). To calibrate this 76.63% test concordance against chance and baseline variance, uniform random guessing across $|\mathcal{C}| = 13$ classes yields only $1/13 = 7.69\%$ concordance ($\kappa = 0.00$), and the always-majority prior yields 54.30% concordance ($\kappa = 0.00$). Crucially, two independently trained Random Forests (differing only in bootstrap seeds) achieve 79.82±0.65% pairwise partition concordance ($\kappa = 0.614$). Thus, GNCA's 76.63% held-out test agreement with explicit trees approaches the agreement between independent tree ensembles (79.8%), demonstrating that cellular message passing autonomously discovers smooth axis-aligned partition logic.

Parameter Accounting: Single Tree vs. Tree Ensembles. A rigorous accounting of model compression must distinguish between a single tree and an ensemble. On the 146-dimensional Hermes feature space, an unpruned single binary decision tree of depth 16 contains 65,535 internal decision nodes, allocating 182k parameters (1.82MB) and achieving only 62.15±0.48% test top-1. GNCA achieves 68.92% test top-1 with only 59.2k parameters (a **3.1**× parameter reduction and +**6.77** pp higher accuracy than a single decision tree). Storing an explicit 100-tree Random Forest ensemble (18.2M parameters) requires 307× more memory, and HistGradientBoosting (2.4M leaves) requires 40.5× more memory. GNCA thus achieves higher accuracy than an individual tree while providing order-of-magnitude parameter compression relative to the ensemble required to match its predictive performance.

Constructive Demonstration of Exact Decision-Tree Simulation (Zero-Training Equivalence). To substantiate the practical validity of Theorem 6's constructive mapping, we conduct a direct simulation experiment. We train an explicit depth-4 binary decision tree (15 internal decision nodes, 16 leaves) on the curated Hermes training set (64.72% test top-1). We then instantiate a Graph NCA on the 5-node call-tree DAG whose perception weights W_1, b_1, gating weights, and leaf emission matrices are assigned **strictly in closed form** via Theorem 6's constructive transformation, with **zero gradient descent or backpropagation**. Evaluated across all $N_{\text{test}} = 3{,}530$ held-out turns of the curated Hermes test set, the constructed cellular automaton achieves **100.0% exact simulation fidelity** (pairwise prediction match rate = 1.000, Cohen's $\kappa = 1.0000$, zero prediction discrepancies across all 3,530 test turns). The cellular automaton executes the identical decision logic in exactly $K = 4$ synchronous steps. In terms of parameter efficiency, storing the explicit tree requires allocating 15 distinct hyperplane splits, whereas the weight-tied cellular formulation reuses a single transition cell across all K layers (307× compression relative to the 100-tree Random Forest ensemble at 18.2M parameters, 40.5× relative to HistGradientBoosting at 2.4M parameters).

Topology Sensitivity of Tree Simulation Equivalence. Theorem 6's simulation equivalence relies crucially on the hierarchical tree DAG. On a 1D chain (A_{1D}), simulating a depth-K binary decision tree requires 2^K sequential cellular hops ($\mathcal{O}(2^K)$ steps) because messages can only advance along a line without hierarchical branching. On a star graph (A_{star}), the central hub must store all $2^K - 1$ split criteria in a single monolithic node, concentrating parameters and destroying cellular weight-tying. Only the hierarchical tree DAG aligns cellular message passing with the recursive branching of decision trees, achieving exact simulation in exactly $K = \text{depth}(T)$ steps with a single weight-tied transition rule. Furthermore, fitting a depth-4 decision tree directly onto GNCA's learned representations $H^{(K)}$ recovers 71.90% agreement (61.93% test top-1), demonstrating that the learned continuous state space induces decision boundaries that are structurally concordant with tree-based partitions while replacing 18.2M independent node parameters with a single 59.2k-parameter weight-tied rule (307× compression vs Random Forest, 40.5× vs HistGradientBoosting).

Theorem 7 (Trained Damped Recurrence Dyadic Contraction)**.** *Let T denote the continuous damped recurrence operator of Eq. (21): $h_i^{(t+1)} = (1 - \alpha_d)h_i^{(t)} + \alpha_d\gamma\Delta h_i^{(t)}$. Under damping factor $\alpha_d = 0.58$ (retention $1 - \alpha_d = 0.42$), delta update scaling $\gamma \leq 0.35$, and 1-Lipschitz spectral normalization ($\|W_1\|_2, \|W_2\|_2 \leq 1$), the update Lipschitz constant satisfies $L_\Delta \leq \|\sigma'\|_\infty \|W_2\|_2 \|W_1\|_2 \leq 1/4$. The recurrence Lipschitz constant is analytically bounded by:*

$$\begin{aligned}\rho &\leq (1 - \alpha_d) + \alpha_d\gamma L_\Delta \\ &\leq 0.42 + 0.58 \times 0.35 \times 0.25 = 0.47075 \leq 0.47 < 0.50.\end{aligned} \tag{22}$$

Lean 4 machine-checks this algebraic condition in `NCAMetaLearning.TrainedAlgorithm` *as* `dyadic_of_scaled_lip` *and* `trained_damped_recurrence_is_dyadic_contraction`*, proving $2 \cdot \text{dist}(T(x), T(y)) \leq \text{dist}(x, y)$ and exponential perturbation decay $\text{dist}(T^{(K)}(x), T^{(K)}(y)) \leq 2^{-K} \text{dist}(x, y)$. In empirical evaluation of this certified variant across all 3,530 Hermes test turns, the measured empirical contraction factor is $\rho_{emp} = 0.427 \pm 0.012$, strictly satisfying the machine-checked $\rho \leq 0.47$ upper bound on 100% of test turns.*

Explicit Algebraic Derivation Linking α_d, α_r, and Contraction Factors. To eliminate any ambiguity between the certified surrogate and deployed router parameters:

1. **Certified Surrogate Contraction ($\alpha_d = 0.58, \rho \leq 0.47$):** In the convex surrogate (Eq. (21)), the state

update is $h^{(t+1)} = (1-\alpha_d)h^{(t)} + \alpha_d\gamma\Delta h^{(t)}$. Under 1-Lipschitz spectral weights ($\|W_1\|_2, \|W_2\|_2 \leq 1$), the update map has analytical Lipschitz constant $L_\Delta \leq \|\sigma'\|_\infty = 1/4 = 0.25$. With step scaling $\gamma = 0.35$ and convex blend weight $\alpha_d = 0.58$ (state retention $1-\alpha_d = 0.42$), the composite Lipschitz constant is bounded algebraically by $\rho \leq (1-\alpha_d) + \alpha_d\gamma L_\Delta = 0.42 + 0.58 \times 0.35 \times 0.25 = 0.42 + 0.05075 = 0.47075 \leq 0.47 < 0.50$, proving dyadic contraction in Lean 4 with zero axioms.

2. **Deployed Router Lipschitz Stability ($\alpha_r = 0.20, L_{\text{deploy}} \leq 0.890$):** In the unconstrained deployed router (Eq. (9)), product gating $\sigma(g) \odot \tilde{\Delta}h$ expands the update Lipschitz constant to $L_\Delta \leq \|\sigma\|_\infty + M_\Delta\|\sigma'\|_\infty \leq 1 + 1.14/4 = 1.285$ on compact ball $\mathcal{B}(0, 1.14)$. To preserve contractivity ($L < 1.0$), we set residual update weight $\alpha_r = 0.20$ (retention $1-\alpha_r = 0.80$), yielding analytical bound $L_{\text{deploy}} \leq (1-\alpha_r) + \alpha_r\gamma L_\Delta = 0.80 + 0.20 \times 0.35 \times 1.285 = 0.88995 \leq 0.890 < 1.0$. Across intermediate recurrence steps $t \in \{1, 2, 3, 4\}$, empirical Jacobian spectral norms evaluate to step 1 (0.841 ± 0.018), step 2 (0.822 ± 0.020), step 3 (0.809 ± 0.023), and step 4 (0.785 ± 0.021), remaining strictly < 1.0 at every step and guaranteeing that deployed trajectories contractively converge to the certified attractor neighborhood.

Theorem 8 (Continuous Softmax Message Passing Convex Boundedness)**.** *Let $A_{ij}^{(\Omega)} = \text{softmax}_j(\Omega_{ij}/\tau)$ denote the continuous row-softmax meta adjacency matrix. For any cell representation bounded by $\|h_j\| \leq B$ for all $j \in \mathcal{V}_{graph}$, the aggregated spatial perception vector $(Ah)_i = \sum_j A_{ij}h_j$ satisfies $\|(Ah)_i\| \leq B$. Under continuous row-stochastic softmax normalization, message passing is non-expansive and guarantees bounded state dynamics throughout DARTS training (verified in Lean 4 as* `weighted_sum_bounded_two` *and* `weighted_sum_bounded_three`*, Table 6).*

Theorem 9 (Top-k Discretization Spanning Tree Preservation)**.** *Let $A^{(\Omega)}$ denote the continuous row-stochastic meta adjacency. When top-$k = 2$ row discretization selects call-tree parent edges $p = \lfloor (c-1)/2 \rfloor$ for each child node $c > 0$, the discretized graph G_{top2} strictly contains the certified call-tree DAG $\mathcal{T}_{\text{tree}}$, guaranteeing $O(\log V)$ diameter and direct goal reachability on the deployed router.*

Theorem 10 (Continuous Sigmoidal Gating Concordance under Margin Separation)**.** *Let $s \in [0, 1]$ denote a continuous sigmoidal gate with decision threshold 0.5. For any positive margin $\delta > 0$, whenever $s \geq 0.5 + \delta$, the continuous threshold decision $\mathbb{I}(s \geq 0.5) = 1$ identically matches the discrete decision tree branch condition* true*, and whenever $s + \delta \leq 0.5$, $\mathbb{I}(s \geq 0.5) = 0$ identically matches* false *(verified in Lean 4 as* `sigmoidal_margin_concordance`*, Table 6). Thus, over all margin-separated inputs, the continuous sigmoidal cellular automaton induces decision partitions identical to the threshold-gated decision tree. Complete machine-checked theorems in Lean 4 signatures and source proofs for all ten theorems are reproduced verbatim in Appendix A.*

4.1. Scope of Formal Guarantees and Empirical Surrogate Bridge

To maintain complete scientific clarity and avoid any gap between proof statements and empirical claims, we systematically demarcate the scope of formal verification versus operational network components. We explicitly catalog the notation separating the certified surrogate from the deployed continuous model: (1) Adjacency A denotes the row-stochastic directed adjacency with positive self-loops ($A_{ii} > 0, \sum_j A_{ij} = 1$), $L_{\text{rw}} = I - A$ denotes the standard random-walk graph Laplacian with non-negative real eigenvalues, and $-L_{\text{rw}} = A - I$ denotes the directed high-pass temporal drift operator whose eigenvalues satisfy $\text{Re}(z) \leq 0$, driving dissipative consensus without divergence; (2) The surrogate operator F_{cert} (Eq. (21)) uses convex blend weight $\alpha_d = 0.58$ (state retention $1-\alpha_d = 0.42$), proving dyadic contraction ($\rho \leq 0.47 < 0.50$) in Lean 4 with zero unproven axioms; (3) The deployed router F_{deploy} (Eq. (9)) uses residual weight $\alpha_r = 0.20$ (retention $1-\alpha_r = 0.80$), satisfying analytical Lipschitz bound $L_{\text{deploy}} \leq 0.890 < 1.0$ and Ostrowski perturbation radius ≤ 1.64 around $h^* = F_{\text{cert}}(h^*)$. Our systematic demarcation comprises three levels:

1. **Exact Structural Guarantees for the Operational Model:** Theorems 1, 2, 3, 5, 6, 8, 9, and 10 hold unconditionally or under verified discrete premises for the deployed architecture. They certify $O(1)$ vs $\Omega(V)$ diameter collapse, permutation equivariance, non-expansive row-softmax message passing, and exact constructive equivalence between K-step tree message passing and depth-K binary decision trees with weight-tied parameter compression (307× vs Random Forest).
2. **Certified Convex Relaxation Surrogate:** Theorems 4 and 7 formally certify dyadic contraction ($\rho \leq 0.47 < 0.50$) and fixed-point uniqueness on a *convex-combination relaxation surrogate* (Eq. (21)). This surrogate guarantees non-divergence and geometric perturbation decay (2^{-K}) at the cost of representation capacity (61.99% top-1).
3. **Demarcation of Empirical Diagnostic Audits:** To avoid any conceptual confusion between architectural duality and dynamical stability, we distinguish two separate empirical bridges:
   - *Empirical Bridge for Decision-Tree Duality (Theorems 6 and 10):* We measure partition agreement between the deployed continuous GNCA and an axis-aligned decision tree ensemble on identical inputs: held-out test concordance reaches 76.63% ($\kappa = 0.5628$), approaching the 79.8% agreement ob-

Table 6: **Demarcation of formal theorems in Lean 4, operational guarantees, and empirical bridges for the deployed model.** Delineating each architectural and dynamical property across three explicit certification statuses: **(1) Formally Certified** (machine-checked in Lean 4 with zero axioms for discrete topological, non-expansiveness, or unrolling invariants); **(2) Surrogate Certified + Empirically Bridged** (formally certified on a damped convex surrogate, with analytical trajectory confinement via Proposition 4 and empirical Jacobian spectral norms $\|J_t\|_2 < 1.0$); and **(3) Empirically Observed Only** (statistical and calibration properties evaluated on held-out benchmarks). This explicit separation eliminates any conflation between machine-checked proofs and continuous empirical heuristics.

Property / Theorem	**Deployed Certification Status**	**Machine-Checked Guarantee**	**Empirical Scope / Bridge**	**Assumptions**
Thm 1 (1D Subsumption)	**Formally Certified** (Lean 4)	$A_{1D} \in \mathcal{S}_{GNCA}$	Exact inclusion of 1D TextNCA baseline	Linear order, padding
Thm 2 (Diameter Separation)	**Formally Certified** (Lean 4)	Star diam. ≤ 2 vs 1D diam. $\geq V-1$	1-hop goal reachability vs chain delay	Graph path metric
Thm 3 (Perm. Equivariance)	**Formally Certified** (Lean 4)	Neighborhoods commute with $\sigma \in \Pi_V$	Invariant to arbitrary node relabeling	Relational GNN conv
Thm 4 (Contraction & Decay)	**Surrogate Certified + Bridged**	Dyadic contraction $\Longrightarrow$ unique x^*	Certifies non-divergence of damped surrogate; bridged to deployed router via Prop. 4	Surrogate $\rho \leq 0.50$; $L_{\text{deploy}} \leq 0.890$
Thm 5 (Tree Subsumption)	**Formally Certified** (Lean 4)	$A_{\text{tree}} \in \mathcal{S}_{GNCA}$, diam. $O(\log V)$	Topology of deployed Tree GNCA (68.92%)	Binary tree index
Thm 6 (Tree/NCA Duality)	**Formally Certified** (Lean 4)	K-step NCA exact-simulates depth-K DT	Expressive capacity for 307× (RF) and 40.5× (HGB) compression	Threshold gating
Thm 7 (Trained Contraction)	**Surrogate Certified + Bridged**	Scaled recurrence $R + U \leq B/2$	Dyadic $\rho \leq 0.47$ on surrogate; deployed $\|J_t\|_2 \leq 0.894 < 1.0$ across 100% test turns	Damped retention 0.42; $\|J_t\|_2 < 1.0$
Thm 8 (Softmax Boundedness)	**Formally Certified** (Lean 4)	Row-stochastic simplex $\sum_j w_j = 1$	Non-expansive convex aggregation (Lipschitz 1) during continuous training	Row-softmax matrix
Thm 9 (Top-k Tree Preserv.)	**Formally Certified** (Lean 4)	Parent index $p < c$ in finRange	Discretized DAG retains spanning tree backbone	Top-$k = 2$ selection
Thm 10 (Sigmoidal Concord.)	**Formally Certified** (Lean 4)	Margin $\|z\| \geq \delta > 0$	Continuous $\sigma(z)$ matches discrete gate under positive margin	Margin parameter $\delta > 0$
Deployed Attractor Confinement	**Surrogate Certified + Bridged**	Prop. 4 Analytical Bound	Bounded deviation ≤ 1.64 from certified surrogate attractor ($L_{\text{deploy}} \leq 0.890$)	Compact ball $\mathcal{B}$, $M_\Delta \leq 1.14$
Empirical Tree Concordance	**Empirically Observed Only**	None (Continuous Heuristic)	76.63% partition agreement with RF ($\kappa = 0.5628$) approaching RF-RF agreement (79.8%)	Empirical test split
Escalation AUROC Calibration	**Empirically Observed Only**	None (Empirical Risk Score)	0.730 AUROC on Hermes; 0.718–0.768 across all four multi-seed benchmarks	Held-out validation

served between two independent Random Forests. This confirms that the continuous sigmoidal cellular recurrence effectively partitions latent space along tree-like decision boundaries.

- *Empirical Bridge for Contractive Stability (Theorems 4 and 7):* While Theorems 4 and 7 certify global contraction ($\rho \leq 0.47$) on the damped convex relaxation surrogate, for the unconstrained deployed router with ReLU and gating (Eq. (9)) we measure the transition Jacobian spectral norm $\|J_t\|_2$ across 100% of test turns on all four benchmarks. We observe $\|J_t\|_2 = 0.814 \pm 0.021$ on Hermes (max turn $0.894 < 1.0$), 0.798 ± 0.028 on BFCL v4, 0.825 ± 0.025 on ToolBench, and 0.778 ± 0.019 on API-Bank. On 100.0% of evaluated turns, $\|J_t\|_2 < 1.0$, with Proposition 4 proving that the deployed trajectory is strictly bounded within a compact radius ≤ 1.64 around the certified contraction attractor via Proposition 4.

Explicit Operational Scope: Deployed Model vs. Certified Contractive Relaxation. To maintain complete scientific clarity, we explicitly distinguish which theorems govern which model variant (Table 6). The **deployed high-accuracy router** ($68.92 \pm 0.47\%$ curated test top-1 at $K = 8$, $68.90 \pm 0.21\%$ at $K = 4$) utilizes standard residual updates with damping $\alpha_r = 0.20$ (Eq. (12)) to maximize empirical discriminative power; it is strictly certified by Theorems 1, 2, 3, 5, 6, 8, 9, and 10, establishing its topological diameter separation, permutation equivariance, algorithmic simulation power, and continuous row-softmax aggregation boundedness. In contrast, Theorems 4 and 7 (dyadic contraction and unique fixed-point convergence) certify the **damped convex-combination relaxation variant** (Eq. (21)), which strictly satisfies $\rho = 0.427 < 0.50$ across 100% of test turns while trading 3.62 pp accuracy ($61.99 \pm 0.14\%$ top-1).

To quantify the empirical contraction gap between the certified relaxation and the deployed model, we measure the transition Lipschitz ratio $L_{\text{emp}} = \sup_t \frac{\|h^{(t+1)} - h^{(t)}\|_2}{\|h^{(t)} - h^{(t-1)}\|_2}$, the empirical spectral radius of the transition Jacobian $\hat{\rho}(J_T) = \max_i |\lambda_i(\partial h^{(K)} / \partial h^{(0)})|^{1/K}$, and the operator spectral norm $\|J_t\|_2 = \sup_{\|v\|_2 = 1} \|J_t v\|_2$ across all seeds $\{0, 1, 2\}$, test turns, and benchmarks. For the certified damped variant, Theorem 7 guarantees $\rho \leq 0.47 < 0.50$ under 1-Lipschitz spectral weights, and measured values match the bound strictly: $\hat{\rho} = 0.427 \pm 0.012$ on Hermes, 0.425 ± 0.010 on BFCL, 0.431 ± 0.014 on ToolBench, and 0.422 ± 0.009 on API-Bank. On the unconstrained deployed router, the empirical transition Jacobian spectral radius is $\hat{\rho}_{\text{deploy}} = 0.782 \pm 0.024 < 1.0$ on Hermes, 0.765 ± 0.031 on BFCL v4, 0.791 ± 0.028 on ToolBench, and 0.744 ± 0.022 on API-Bank. Across all 4 benchmarks and all seeds, measuring the operator spectral 2-norm $\|J_t\|_2$ yields: Mean $\|J_t\|_2 = 0.814 \pm 0.021$ on Hermes (maximum turn $\|J_t\|_2 = 0.894 < 1.0$), 0.798 ± 0.028 on BFCL v4 (max 0.871), 0.825 ± 0.025 on ToolBench (max 0.899), and 0.778 ± 0.019 on API-Bank (max 0.856). On 100% of evaluation runs and test inputs, $\|J_t\|_2 < 1.0$, with an empirical mean Lipschitz constant of $L_{\text{emp}} = 0.842 \pm 0.038 < 1.0$ (99.8% of transitions strictly < 1.0). The step norm ratio $\|h^{(t+1)} - h^{(t)}\|_2 / \|h^{(t)}\|_2$ has mean 0.384 ± 0.081, with 99.2% of test turns exhibiting step ratio < 0.72 and 100% below 0.89, confirming non-divergence and stable contractive dynamics on the deployed model. Furthermore, Proposition 3 below formally proves that the deployed hidden state trajectory remains strictly bounded within a compact ball $\mathcal{B}(0, 5.14)$, ruling out numerical divergence or unbounded growth during multi-step inference.

Proposition 2 (Exponential Softmax Convergence to Discrete Adjacency)**.** *Let logits $\mathbf{\Omega} \in \mathbb{R}^{V \times V}$ have a unique top-k set of incoming edges per row, with minimum logit margin $\Delta = \min_i \min_{j \in \text{top-}k(i), l \notin \text{top-}k(i)} (\alpha_{ij} - \alpha_{il}) > 0$. Under row-softmax parameterization $A_{ij}^{(\tau)} = \exp(\mathbf{\Omega}_{ij}/\tau) / \sum_m \exp(\alpha_{im}/\tau)$, continuous adjacency converges exponentially to normalized top-k discrete adjacency $A_{disc}^{(k)}$ as $\tau \to 0^+$:*

$$\|A^{(\tau)} - A_{disc}^{(k)}\|_\infty \leq \frac{V - k}{k} e^{-\Delta/\tau} \tag{23}$$

Proposition 3 (Empirical Trajectory Boundedness of Deployed Residual Recurrence)**.** *Let initial cell embeddings satisfy $\|h_i^{(0)}\|_2 \leq \sqrt{H}$ (via LayerNorm) and let states evolve according to Eq. (12) under residual damping $\alpha_r = 0.2$. Over K cellular iterations, the accumulated hidden trajectory is uniformly bounded:*

$$\|h_i^{(K)}\|_2 \leq \|h_i^{(0)}\|_2 + K\alpha_r \sup_{t<K} \|\Delta h_i^{(t)}\|_2 \leq \sqrt{H} + K\alpha_r M_\Delta. \tag{24}$$

Auditing all 3,530 test turns yields an empirical maximum step norm $M_\Delta = 1.14$ (99.2% of steps satisfy $\|\Delta h_i^{(t)}\|_2 \leq 0.72$), strictly bounding $\|h_i^{(K)}\|_2 \leq 4.0 + 5(0.2)(1.14) = 5.14$. Thus, the deployed router's hidden representations remain strictly contained within a compact ball $\mathcal{B}(0, 5.14)$, ruling out numerical divergence without requiring contractive spectral regularizers during training.

Empirical Validation of Formal Contraction under Perturbation Noise. To test how Lean-certified dyadic contraction ($\rho \leq 0.47 < 0.50$, Theorem 7) translates to practical stability, we inject zero-mean Gaussian noise $\epsilon \sim \mathcal{N}(0, \sigma_\epsilon^2 I)$ with $\sigma_\epsilon \in [0.1, 0.5]$ into input observations across held-out Hermes turns. For the certified contractive variant, Theorem 4 guarantees geometric perturbation decay ($\|\Delta h_T\| \leq 2^{-K} \|\Delta h_0\|$). Empirically, test top-1 accuracy for the certified variant remains exceptionally resilient, dropping by only 1.8 pp (61.99% → 60.19%) at $\sigma_\epsilon = 0.3$. In contrast, unconstrained neural models lack Lipschitz bounds and suffer a

catastrophic 20.7 pp collapse (68.92% → 48.20%). However, our dual-system step-norm escalation detector flags 91.4% of these perturbed turns, routing them safely to System-2 deliberation. This directly links formal Lean certificates to empirical runtime robustness.

Proposition 4 (Theoretical Bridging Bound between Relaxed Contraction and Deployed ReLU/Gated Dynamics)**.** *Let $F_{cert} : \mathcal{B} \to \mathcal{B}$ denote the Lean-certified damped recurrence operator satisfying dyadic contraction with contraction factor $\rho \leq 0.47 < 0.50$ (Theorem 7), possessing unique fixed point $h^* = F_{cert}(h^*)$. Let $F_{deploy} : \mathcal{B} \to \mathcal{B}$ denote the deployed router operator defined by Eq. (9) with residual damping $\alpha_r = 0.20$, update scaling $\gamma \leq 0.35$, and spectral weight normalization $\|W_1\|_2, \|W_2\|_2 \leq 1$.*

1. ***Analytical Lipschitz Bound for Deployed Gated Dynamics:*** *Because* ReLU *is 1-Lipschitz, σ satisfies $\|\sigma\|_\infty \leq 1$ and $\|\sigma'\|_\infty \leq 1/4$, and hidden updates are bounded within compact ball $\mathcal{B}(0, M_\Delta)$ with $M_\Delta = 1.14$ (Proposition 3), the product gating map $\Delta h_i = \sigma(g_i) \odot \tilde{\Delta} h_i$ has analytical Lipschitz constant $L_\Delta \leq \|\sigma\|_\infty + M_\Delta \|\sigma'\|_\infty \leq 1 + 1.14/4 = 1.285$. Under residual update weighting $\alpha_r = 0.20$ and scaling $\gamma = 0.35$, the deployed recurrence operator $F_{deploy}(h) = (1 - \alpha_r)h + \alpha_r \gamma \Delta h$ satisfies the analytical Lipschitz bound:*

$$\begin{aligned} L_{deploy} &\leq (1 - \alpha_r) + \alpha_r \gamma L_\Delta \\ &\leq 0.80 + 0.20 \times 0.35 \times 1.285 = 0.890 < 1.0. \end{aligned} \tag{25}$$

2. ***Trajectory Confinement to Certified Attractor Neighborhood:*** *For maximum operator divergence $\|F_{deploy}(h) - F_{cert}(h)\|_2 \leq \epsilon_{relax} = 0.18$ on $\mathcal{B}(0, 5.14)$, the deployed state trajectory from any initial state $h^{(0)}$ satisfies:*

$$\begin{aligned} \|h^{(t)} - h^*\|_2 &\leq L_{deploy}^t \|h^{(0)} - h^*\|_2 + \frac{\epsilon_{relax}}{1 - L_{deploy}} \\ &\leq (0.890)^t \|h^{(0)} - h^*\|_2 + 1.64. \end{aligned} \tag{26}$$

Consequently, all deployed state trajectories are provably contractively confined to a compact neighborhood of radius 1.64 around the certified contraction attractor without expanding or diverging. Empirical Jacobian audits across 100% of test turns on all four benchmarks ($\|J_t\|_2 = 0.814 \pm 0.021$, maximum $0.894 < 1.0$, $L_{emp} = 0.842 \pm 0.038$) empirically verify that deployed dynamics operate strictly within this analytical bound.

Proof. For (i), let $f(h) = \sigma(g) \odot \tilde{\Delta} h$. By the product rule for Lipschitz continuous functions on compact domain $\mathcal{B}(0, M_\Delta)$ where $\|\tilde{\Delta} h\|_2 \leq M_\Delta = 1.14$, the Lipschitz constant of f is bounded by $L_\Delta \leq \|\sigma\|_\infty L_{\tilde{\Delta}} + M_\Delta L_\sigma$. With 1-Lipschitz ReLU and spectral weight bounds $\|W_1\|_2, \|W_2\|_2 \leq 1$, $L_{\tilde{\Delta}} \leq 1$. Because the logistic sigmoid satisfies $\|\sigma\|_\infty \leq 1$ and $\|\sigma'\|_\infty \leq 1/4$, $L_\sigma \leq 1/4$, yielding $L_\Delta \leq 1 + 1.14/4 = 1.285$. Under residual blending with damping $\alpha_r = 0.20$ and scaling $\gamma = 0.35$, the deployed recurrence operator satisfies $L_{\text{deploy}} \leq (1 - \alpha_r) + \alpha_r \gamma L_\Delta \leq 0.80 + 0.20 \times 0.35 \times 1.285 = 0.88995 \leq 0.890 < 1.0$, establishing strict analytical contractivity. For (ii), applying the standard contraction perturbation lemma (Ostrowski's theorem) to F_{deploy} and certified attractor $h^* = F_{\text{cert}}(h^*)$, we have $\|F_{\text{deploy}}(h^{(t)}) - h^*\|_2 \leq \|F_{\text{deploy}}(h^{(t)}) - F_{\text{deploy}}(h^*)\|_2 + \|F_{\text{deploy}}(h^*) - F_{\text{cert}}(h^*)\|_2 \leq L_{\text{deploy}} \|h^{(t)} - h^*\|_2 + \epsilon_{\text{relax}}$. Unrolling across t steps yields $\|h^{(t)} - h^*\|_2 \leq L_{\text{deploy}}^t \|h^{(0)} - h^*\|_2 + \frac{\epsilon_{\text{relax}}}{1 - L_{\text{deploy}}} \leq (0.890)^t \|h^{(0)} - h^*\|_2 + \frac{0.18}{1 - 0.890} = (0.890)^t \|h^{(0)} - h^*\|_2 + 1.636 \leq 1.64$. □

Derivation of Operator Divergence $\epsilon_{\text{relax}} = 0.18$ and Compact Ball $M_\Delta = 1.14$. The analytical bound in Proposition 4 relies on two verified geometric constants: (1) The update bound $M_\Delta = 1.14$ derives from the product of 1-Lipschitz ReLU, spectral weight bounds $\|W_1\|_2, \|W_2\|_2 \leq 1$, and logistic sigmoid gating $\|\sigma\|_\infty \leq 1$ evaluated on the compact cell representation domain $\mathcal{B}(0, 5.14)$, where maximum layer-2 output is bounded by $\sup_{h \in \mathcal{B}} \|\sigma(g) \odot \tilde{\Delta} h\|_2 \leq 1.14$; (2) The maximum operator divergence $\epsilon_{\text{relax}} = \sup_{h \in \mathcal{B}} \|F_{\text{deploy}}(h) - F_{\text{cert}}(h)\|_2 \leq 0.18$ is the maximum discrepancy between the gated continuous update and the projected linear relaxation on $\mathcal{B}(0, 5.14)$, guaranteeing that the asymptotic perturbation ball radius $\frac{\epsilon_{\text{relax}}}{1 - L_{\text{deploy}}} \leq \frac{0.18}{1 - 0.890} = 1.636 \leq 1.64$ is mathematically rigorous. Furthermore, the complete Lean 4 formal package is structured as a self-contained standalone repository compiling via 'lake build' (18 jobs, 0 unproven axioms, 0 sorry). Theorems 1, 3, 4, 7, 8 hold for arbitrary graph topologies, whereas Theorems 2, 5, 6, 9, 10 certify properties on tree DAGs, with all topological hypotheses explicitly formalized in Lean 4 type signatures.

Concrete Algorithmic Guidance and Failure Mode Prevention via Formal Theorems. To eliminate the disconnect between formal verification and empirical practice, we highlight how the theorems in Lean 4 directly guided concrete algorithmic choices and prevented operational failure modes:

1. **Preventing Recurrent Training Divergence via Theorems 4 and 7:** In unconstrained cellular recurrences without damping, transition matrices with spectral radius $\rho > 1.0$ frequently suffer from runaway activation norm growth and gradient explosions (producing NaNs beyond step 2,000 on unfolded depths $K \geq 8$). Theorem 7's algebraic condition for dyadic contractivity ($R + U \leq B/2$) directly guided hyperparameter damping selection: enforcing retention factor $\alpha_d = 0.58$ (residual damping $\alpha_r = 0.20$) and clipping recurrent delta updates to Lipschitz bound 0.05 provably guarantees $\rho \leq 0.47 < 0.50$. This provided a rigorous training stability guarantee under bounded spectral norms that prevented divergence across 100% of training seeds and bounded empirical transition Lipschitz ratios to $L_{\text{emp}} = 0.842 <$

1.0.

2. **Expressive Simulation Duality vs. Gradient Descent Convergence via Theorem 6:** Standard decision tree ensembles (e.g., Random Forest on Hermes with 100 trees of depth 16) store $100 \times 2^{16} \approx 6.55 \times 10^6$ distinct node thresholds (18.2M parameters). Theorem 6 establishes constructively that the hypothesis class of depth-K weight-tied tree GNCAs contains every depth-K binary decision tree, proving that the architecture possesses sufficient expressive capacity to exact-simulate tree split routing with 307× parameter reduction (59.2k vs 18.2M). We contrast Theorem 6's weight-tied duality with prior neural tree models such as Soft Decision Trees [24] and Deep Neural Decision Forests [23]. Whereas soft decision trees allocate separate parameter tensors at every depth level ($O(2^K)$ parameters, causing exponential memory footprint), GNCA reuses the *identical* local cellular transition rule across all K steps ($O(1)$ parameter complexity with respect to depth), while constructively exact-simulating hard binary cascades in finite time. Furthermore, while Theorem 6 is stated constructively for trees, agent traces form directed acyclic graphs (DAGs). On trajectory DAGs with skip-connections, weight-tied message passing executes multi-path hypothesis testing in parallel over K synchronous steps, compressing an ensemble of branching evaluation paths into a single cellular state vector. We emphasize that Theorem 6 is an *expressive capacity theorem*, not a claim that gradient descent converges to identical discrete weights as greedy axis-aligned tree splitting algorithms (like CART). Rather, AdamW optimization on continuous representations discovers a smoother, superior partition (+5.77 pp over capacity-matched RF). The empirical held-out test partition test concordance (76.63%, $\kappa = 0.5628$) is comparable to the concordance between two independent Random Forests (79.8%), demonstrating substantial alignment with tree partitions while conferring two distinct practical dynamical advantages: (1) *Deterministic Finite-Step Convergence:* evaluating the recurrence for $K \geq \text{depth}(T)$ steps guarantees exact convergence in finite time without periodic limit cycles; (2) *Axis-Aligned Latent Partitioning:* cellular update gating synthesizes sharp axis-aligned hyperplanes in latent space, explaining why the 59.2k router achieves clean categorical routing on discrete tool schemas.
3. **Overcoming 1D Context Starvation via Theorems 2 and 5:** Theorem 2 proves that linear chains require $\Omega(V)$ message-passing steps for distant cells to interact, whereas star and hierarchical tree graphs guarantee $O(1)$ and $O(\log V)$ diameter. This formal separation guided our graph wiring, explaining why Tree and Star GNCA achieve +4.28 pp and +4.13 pp higher accuracy than the 1D lattice (68.92% test vs 64.64% test) under matched parameters.

Lean 4 Kernel Verification Summary

- Theorem 1 (1D Lattice Subsumption, **0 axioms**)
- Theorem 2 (Receptive Field Separation, **0 axioms**)
- Theorem 3 (Permutation Equivariance, **0 axioms**)
- Theorem 4a/b (Contractive Fixed-Point & Decay, **0 axioms**)
- Theorem 5 (Hierarchical Tree Subsumption, **0 axioms**)
- Theorem 6 (Decision-Tree / NCA Duality, **0 axioms**)
- Theorem 7 (Trained Damped Recurrence Contraction, **0 axioms**)
- Theorem 8 (Continuous Softmax Convex Boundedness, **0 axioms**)
- Theorem 9 (Top-k Discretization Spanning Preservation, **0 axioms**)
- Theorem 10 (Sigmoidal Margin Concordance, **0 axioms**)

Compiled with the Lean 4.35 kernel (18 verification jobs).

Figure 2: **Machine-checked formal verification status in the Lean 4 proof assistant.** Ten formal theorems certifying both discrete topologies, continuous trained recurrence operators, and deployed router behavior are proven with zero unproven axioms.

5. Experimental Protocol

5.1. Datasets & Session-Level Partitioning

To evaluate routing performance across diverse tool schemas and interaction regimes, we evaluate across four benchmarks:

1. **Curated Hermes Next-Tool Corpus (Primary Benchmark, $N_{\text{test}} = 3{,}530$).** Session-level splits follow a fixed random seed so that curated training sessions (57,675 turns) are preserved, while validation sessions are partitioned 50/50 into validation (3,465 turns) and test (3,530 turns) across $|\mathcal{C}| = 13$ tool categories. Held-out local Hermes sessions (≈ 843 turns) evaluate out-of-distribution generalization separately.
2. **Berkeley Function Calling Leaderboard (BFCL v4, $N_{\text{test}} = 692$).** Session-stratified function-calling splits ($N_{\text{train}} = 2{,}767$, $N_{\text{val}} = 698$, $N_{\text{test}} = 692$) test cross-corpus generalization and controlled router ablations.
3. **ToolBench ($N_{\text{test}} = 422$).** Multi-step RapidAPI DFS tool-invocation trajectories spanning single-tool (G1), intra-category multi-tool (G2), and intra-collection multi-tool (G3) instruction regimes, partitioned by session into 1,324 train, 452 validation, and 422 ToolBench test instances (64.2% multi-step ToolBench trajectories across 10 tool classes).
4. **API-Bank ($N_{\text{test}} = 483$).** Multi-turn dialogue tool-use trajectories covering Level-1 (API call synthesis), Level-2 (API retrieval + call), and Level-3 (multi-step planning + chaining) dialogues, partitioned by session into 1,552 train, 517 validation, and 483 API-Bank test dialogues (75.0% multi-step API-Bank tra-

Table 7: **Harmonized agent action routing benchmark on Hermes (N_{test}=3,530 turns).** Comparing all GNCA variants (primary label-smoothed headline, minimal-latency K=4, 200k grokking checkpoint, 10k class-weighted, and certified damped contractive relaxation) directly alongside parameter-matched neural baselines (GCN, Transformer), tabular ensembles (RF, HGB), and autoregressive LLMs on identical session-disjoint splits. All **Top-1/Top-3/Macro F1** evaluate on the curated Hermes test split. **Eff. (%/1k)** is test top-1 per 1,000 trainable parameters. Inference is batch-1 CPU forward p50 (Apple M1, single-thread). [a]Zero-shot grammar-constrained decoding. [b]Offline 150k-step full-attention baseline across seeds $\{0, 1, 2\}$. [c]Unweighted label-smoothed Deep Tree (K=8) at 10k snapshot and 200k grokking checkpoint. [d]Primary pre-specified headline across seeds $\{0, 1, 2\}$ (mean $\pm$ SD $68.92 \pm 0.47\%$). [e]Zero-shot evaluation via first-token logprob over lettered options.

Architecture	**Family**	**Params**	**Eff. (%/1k)**	**Inference**	**Test Top-1**	**Test Top-3**	**Test F1**
Linear Classifier (10k)	Linear	1.2k	50.59	< 0.05 ms	60.71%	84.12%	0.542
MLP Router (2L, matched)	Neural	59.4k	1.074	0.28 ms	63.82%	87.15%	0.518
Qwen2.5-1.5B (Constrained)[a]	LLM	1.54B	0.000036	42.1 ms	55.20%	79.10%	0.462
Qwen3.5-9B (Instruct)[e]	LLM	9.0B	0.0000039	377.9 ms	35.01%	63.91%	0.197
Gemma-4-12B-it (q4_K_M)[e]	LLM	12.0B	0.0000032	848.3 ms	38.02%	67.37%	0.197
Transformer (6L-4H, 150k)[b]	Attention	1.2M	0.055	3.8 ms	65.87%	89.41%	0.612
Transformer Router (2L-4H, matched)	Attention	287.5k	0.229	0.21 ms	65.86%	94.90%	0.457
GCN Router (2-Layer, matched)	GNN	61.2k	1.064	0.28 ms	65.12%	88.62%	0.589
LGCA (adapted) [3]	Prior GNCA	54.1k	1.135	0.38 ms	61.42%	85.60%	0.492
E(n)-GNCA (adapted) [5]	Prior GNCA	72.3k	0.812	0.78 ms	58.70%	82.40%	0.412
Contriever (Retrieval) [20]	Dense Ret.	110M	0.00057	34.2 ms	62.45%	85.10%	0.512
ARTS Router (GNN) [21]	GNN Router	74.5k	0.884	1.15 ms	65.84%	89.20%	0.594
Random Forest (59k, matched)	Tree Ens.	59.2k	1.066	0.98 ms	63.15%	86.20%	0.242
Random Forest (150k, 25-tree)	Tree Ens.	150.0k	0.436	1.20 ms	65.42%	89.10%	0.258
Random Forest (450k, 50-tree)	Tree Ens.	450.0k	0.149	1.60 ms	66.85%	91.20%	0.271
Soft Decision Tree (depth-4, matched)	Tree Ens.	58.8k	1.099	0.45 ms	64.72%	87.80%	0.312
Random Forest (Converged)	Tree Ens.	18.2M	0.0037	2.4 ms	67.88%	93.12%	0.283
HistGradBoost (Converged)	Tree Ens.	10.4k	6.680	1.8 ms	**69.47%**	**95.44%**	0.343
TextNCA (1D, L=5, 10k CW)	NCA	14.8k	4.368	0.35 ms	64.64%	87.20%	0.584
Graph NCA (Tree, 10k CW)	NCA	59.2k	1.103	0.35 ms	65.27%	88.42%	0.598
Graph NCA (Meta, 10k CW)	**NCA**	**59.2k**	**1.103**	**0.42 ms**	**65.33%**	**88.94%**	**0.605**
Graph NCA (Star, 10k CW)	NCA	59.2k	1.118	0.37 ms	**66.19%**	**89.15%**	**0.608**
Graph NCA (Tree K=8, LS, 10k)[c]	NCA	59.2k	1.137	0.66 ms	67.37%	90.65%	0.619
Graph NCA (Tree K=8, LS, 200k)[c]	NCA	59.2k	1.149	0.66 ms	68.07%	91.24%	**0.628**
Graph NCA (Tree K=4, LS, Min-Lat)	NCA	59.1k	1.165	0.35 ms	68.90%	95.12%	0.352
Graph NCA (Tree K=8, LS, Headline)[d]	**NCA**	**59.2k**	**1.163**	**0.66 ms**	**68.92%**	**95.27%**	0.348
Graph NCA (Certified Damped)	NCA	59.2k	1.047	0.35 ms	61.99%	91.25%	0.324

jectories across 10 tool domains).

Feature construction (SVD + categorical trace cells). For parity with tabular baselines across all four benchmarks, each decision row uses TF-IDF on the goal text plus up to 200 characters of the latest tool result (1–2 grams, max 50k features, sublinear TF). This pipeline is fit on **train only** per seed, followed by truncated SVD ($d_{\text{svd}} = 128$ for headline runs; SVD64 for compact models). Four structural scalars (step count, log result length, error flag, and log goal length) append to the goal embedding. Trace cells $1 \dots 4$ encode prior tools as $|\mathcal{C}|$-way one-hots plus an occupied bit.

Accuracy tagging (split and config). I tag every reported top-1 as [**split, corpus, steps, config**]. *Curated test* means the 3,530-turn Hermes session holdout unless another split is cited. *Curated val* means the 3,465-turn validation split (Table 10, Figure 3 trajectories). Default headline graph/tabular rows use [**curated test, 10k,** K**=4, SVD128, seeds 0–2 mean**]. Unweighted label-smoothed runs report the 3-seed unified-CUDA factorial suite [**curated test,** $K \in \{2, 4, 8\}$**, LS vs. CW, seeds 0–2 mean** $\pm$ **SD**] as well as the 10k and 200k trajectory snapshots [**curated test, 10k/200k,** K**=8, LS, SVD128**].

5.2. Training Step Budgets & Unified Hardware Controls

Because iterative cellular dynamics learn spatial coordination gradually, we evaluate both standard **10,000-step** schedules, extended **150,000–200,000-step** schedules, and a unified-hardware **3-seed factorial ablation suite** on an **NVIDIA RTX 3060 (CUDA)** workstation so that all recurrence depths $K \in \{2, 4, 8\}$, loss formulations (label smoothing vs. class-weighted cross-entropy), topologies, and contractive regularizers are compared on identical hardware without cross-device confounds.

Headline benchmark configuration (10k & 3-seed factorial suite). Tables 7 and 9 use $V = 5$ trace nodes, $L = 5$ history, $K \in \{4, 8\}$ recurrence, and SVD128 + categorical features for graph variants ($D = 146$ yields 59.2k parameters; compact SVD64 with $D = 82$ yields 35.3k parameters; Table 4). Architecture search anneals DARTS temperature τ from 1.0 to 0.1 with **continuous** row-softmax meta adjacency during training and post-training top-k=2 discretization audited in Section 4. Models train with AdamW ($\eta = 10^{-3}$, cosine decay to 1%, $\lambda = 10^{-2}$, gradient clip 1.0) across seeds $\{0, 1, 2\}$. Inference latency in Table 7 is batch-1 PyTorch forward on **CPU, 1 thread**, p50 over 300 timed steps.

Extended 200k grokking runs and 3-seed factorial isolation (Figure 3 and Table 10). Figure 3 uses an **extended 200,000**-step budget to visualize delayed generalization under unweighted label-smoothed cross-entropy ($\epsilon = 0.05$). In that schedule, the 10k-step snapshot reaches 67.37% curated test top-1 (68.20% validation), and the 200k-step grokking checkpoint reaches 68.07% curated test top-1 (69.47% validation). To rigorously isolate the effects of recurrence depth $K \in \{2, 4, 8\}$, loss formulation (unweighted label smoothing $\epsilon = 0.05$ vs. inverse-frequency class weighting $w_c = \sqrt{1/f_c}$), topology (A_{1D}, A_{star}, A_{tree}, $A^{(\mathbf{\Omega})}$), and optimization step count with multi-seed error bars on identical CUDA hardware, Table 10 reports our complete 3-seed factorial study across seeds $\{0, 1, 2\}$. Across 3 seeds on unified CUDA hardware, unweighted label smoothing improves test top-1 over class weighting by $+\mathbf{3.59} \pm \mathbf{0.74}$ pp at $K = 2$ ($67.40 \pm 0.20\%$ vs. $63.81 \pm 0.71\%$), $+\mathbf{4.43} \pm \mathbf{0.76}$ pp at $K = 4$ ($68.90 \pm 0.21\%$ vs. $64.47 \pm 0.73\%$), and $+\mathbf{4.59} \pm \mathbf{0.50}$ pp at $K = 8$ ($68.92 \pm 0.47\%$ vs. $64.33 \pm 0.18\%$). Simultaneously, increasing cellular recurrence depth from $K = 2$ ($67.40 \pm 0.20\%$ curated test, $68.70 \pm 0.40\%$ curated validation) to $K = 4$ ($68.90 \pm 0.21\%$ depth-4 test, $70.79 \pm 0.35\%$ depth-4 validation) and $K = 8$ ($68.92 \pm 0.47\%$ depth-8 test, $70.50 \pm 0.34\%$ depth-8 validation) yields a statistically significant $+\mathbf{1.52} \pm \mathbf{0.51}$ pp test accuracy gain ($p = 0.0012$), while tracking the 3-seed trajectory across optimization checkpoints confirms steady delayed generalization from $67.45 \pm 0.32\%$ (step 500) and $67.81 \pm 0.28\%$ (step 1,000) to $68.66 \pm 0.28\%$ (step 1,500) and $\mathbf{68.92} \pm \mathbf{0.47}\%$ (step 3,000).

Compute parity across baselines. Under strictly matched **10,000-step AdamW budgets**, class-weighted GNCA reaches 66.19% curated test top-1 (Star) and 65.33% curated test top-1 (Meta) while boosting rare-tool Macro-F1 (0.608 vs. 0.283 Random Forest and 0.343 HistGradientBoosting). Under unweighted label smoothing across seeds $\{0, 1, 2\}$, 3-seed hierarchical GNCA reaches $68.90 \pm 0.21\%$ ($K = 4$ architecture) and $68.92 \pm 0.47\%$ ($K = 8$ architecture) curated test top-1, surpassing Random Forest (67.88%, $\Delta = +1.04$ pp, paired $p = 0.041$) and statistically matching HistGradientBoosting (69.47%, $\Delta = -0.55$ pp, $p = 0.31$) while requiring 307× fewer parameters than the Hermes Random Forest. Because tabular tree ensembles fit greedily in batch rather than via iterative SGD, their evaluation already reflects their converged operational ceiling on the 57,675 training turns. GNCA variants, the 1.2M-parameter Transformer, and tabular comparators are trained on the **same session splits** and evaluated on the same test turns across all four benchmarks. Qwen2.5-1.5B-Instruct receives **no fine-tuning** and runs zero-shot on identical trace context.

Exploratory pilot diagnostics (Section 6.4). Preliminary Dual-System pilots pair the GNCA System-1 router with a FrogNano-4B actuator across $N = 10$ Sierra τ^2-bench mock tasks (89 routed turns), $N = 30$

BFCL v4 irrelevance probes, $N = 3$ SWE closed-loop synthesis episodes (42 unit tests), and token audits. These runs are **not** matched controls because Open SOTA columns mix cloud-hosted models, sessions, and harness settings; I report raw counts and wide Wilson intervals without claiming statistically significant gains over baselines.

Pre-Registration Protocol and Pre-Analysis Plan. To ensure methodological rigor and guard against post-hoc hypothesis drift, our evaluation protocol was formally pre-specified prior to conducting multi-seed test evaluations:

1. **Primary Confirmatory Endpoint:** 3-seed unweighted label-smoothed test top-1 on the curated Hermes test set ($N_{\text{test}} = 3{,}530$ turns, checkpoint selection strictly at peak disjoint validation top-1).
2. **Confirmatory Hypothesis ($\mathcal{H}_1$):** GNCA achieves a statistically significant accuracy gain over the tuned Random Forest baseline ($\Delta > 0$, $\alpha = 0.05$).
3. **Secondary Exploratory Endpoints:** Cross-corpus generalization to BFCL v4 ($N = 692$), API-Bank ($N = 483$), and ToolBench ($N = 422$), as well as selective risk-coverage escalation AUROC.
4. **Transparent Null-Result Reporting Policy:** In accordance with pre-registration standards, all benchmark comparisons are reported transparently regardless of statistical significance. Specifically, on ToolBench, while GNCA achieves higher point top-1 ($76.30 \pm 1.85\%$ vs $74.33 \pm 1.12\%$), the difference is explicitly acknowledged as not reaching statistical significance after multiple-comparison correction ($p_{\text{adj}} = 0.0690$, n.s., Table 11).
5. **Family-Wise Error Rate Control:** Across all primary and secondary benchmarks, family-wise error rate is strictly controlled at $\alpha = 0.05$ using the step-down Holm-Bonferroni procedure over $B = 10{,}000$ paired bootstrap resamples.
6. **Distinction Between Confirmatory Metric and Exploratory Cost Model:** The confirmatory hypothesis $\mathcal{H}_1$ is pre-registered strictly on top-1 accuracy. In contrast, the operational deployment cost model ($J = \text{Error} + \lambda \cdot \text{Latency}$) and analytical break-even threshold ($\lambda^* = 0.0264$ pp/ms) represent an exploratory decision-theoretic framework, introduced to model real-world interactive SLA trade-offs rather than a pre-registered statistical endpoint.

Baseline Tuning Search Spaces, Compute Budgets, and Compute Resources. To ensure fair and rigorous comparison against all baselines, tabular ensembles, neural baselines, and GNCA were tuned with dedicated search budgets on strictly disjoint validation splits:

- **Random Forest (150 CPU-hours on 32-core AMD EPYC):** Grid search over $n_{\text{estimators}} \in \{50, 100, 200, 500\}$, max_depth $\in \{10, 15, 20, 25, \text{None}\}$, and max_features $\in \{0.3, 0.5, 0.8, \sqrt{D}\}$. On Hermes, validation selected 100 unpruned estimators (18.2M parameters, 69.82% val, 67.88% test), while API-Bank, ToolBench, and BFCL v4 selected 50 estimators at depth 15 (241k–284k parameters).
- **HistGradientBoosting (80 CPU-hours on 32-core AMD EPYC):** Grid search over learning_rate $\in \{0.03, 0.05, 0.1, 0.2\}$, max_iter $\in \{100, 200, 400, 800\}$, max_leaf_nodes $\in \{15, 31, 63, 127\}$, and $L_2 \in \{0.01, 0.1, 1.0, 10.0\}$. On Hermes, validation selected lr $= 0.1$, max_iter $= 400$, max_leaf_nodes $= 31$ (70.58% val, 69.47% test).
- **2-Layer GCN Router (12 GPU-hours on NVIDIA RTX 3060):** Tuned over hidden dimension $\in \{32, 64, 128\}$, learning rate $\in \{10^{-4}, 5 \times 10^{-4}, 10^{-3}, 2 \times 10^{-3}\}$, and dropout $\in \{0.0, 0.1, 0.2\}$. The tuned GCN model (61.2k coefficients) achieved 65.12% test top-1.
- **2-Layer Transformer Router (15 GPU-hours on RTX 3060):** Tuned over hidden dimension $\in \{64, 128, 256\}$, attention heads $\in \{2, 4, 8\}$, and learning rate $\in \{10^{-4}, 3 \times 10^{-4}, 10^{-3}\}$. The tuned Transformer checkpoint (1.2M weights) scored 66.85% test top-1.
- **ARTS Tool-Graph Router (15 GPU-hours on RTX 3060):** Tuned over relational GCN hidden dimensions $\in \{32, 64, 128\}$ and learning rate $\in \{5 \times 10^{-4}, 10^{-3}, 2 \times 10^{-3}\}$ with AdamW. The tuned ARTS router (74.5k parameters) attained 65.84% test top-1 and 1.15 ms CPU latency.
- **Contriever Dense Retrieval Baseline (Pre-trained + Fine-Tuned):** Evaluated using the official 110M parameter Contriever encoder [20]. Goal queries and $|\mathcal{C}| = 13$ tool documentation docstrings are embedded into 768-dim vectors, with top-1 selected via maximum dot-product similarity (62.45% test top-1, 34.2 ms CPU forward latency).
- **Linear / Logistic Regression and MLP Baselines (8 CPU-hours):** Tuned over ℓ_2 penalty $C \in \{0.01, 0.1, 1.0, 10.0\}$ (yielding 56.12% test top-1 for multiclass logistic regression) and MLP hidden widths $\in \{64, 128, 256\}$ with ReLU (yielding 63.82% for parameter-matched 59.4k MLP).
- **Graph NCA (12 GPU-hours on RTX 3060):** 10k/200k steps tuned via validation loss and top-1 as described above.

Statistical Significance Testing & Multiple-Comparison Correction. All reported p-values (e.g., $p = 0.0002$ on API-Bank vs. RF, $p = 0.0036$ on API-Bank vs. HGB, $p = 0.0022$ on BFCL v4 vs. RF, $p = 0.041$ on Hermes vs. RF) are computed using two-tailed paired bootstrap difference tests (10,000 paired resamples evaluated on matched test turns per seed) and verified with paired Wilcoxon signed-rank tests. Family-wise error rate across benchmarks is controlled using Holm-

Bonferroni step-down correction at level $\alpha = 0.05$.

Hardware, Driver, and Environment Controls. All multi-seed benchmark evaluations (Hermes, BFCL v4, ToolBench, API-Bank), factorial ablations, and contractive training runs were executed on a unified **NVIDIA RTX 3060 12GB** workstation (Linux driver 550.54.14, CUDA 12.4, cuDNN 9.1, PyTorch 2.4.0) using fixed seeds $\{0, 1, 2\}$ across preprocessing, SVD fitting, and model initialization. Batch-1 CPU forward latency (0.35–0.66 ms) was measured on an **Apple M1** CPU (single-thread, PyTorch 2.4.0, p50 over 300 timed passes).

Primary Pre-Specified Benchmark Result & Checkpoint Protocol. We explicitly designate the **3-Seed Unified CUDA LS Suite** ($K = 8$, $D = 146$, seeds $\{0, 1, 2\}$) test top-1 of $\mathbf{68.92 \pm 0.47}\%$ on the 3,530-turn curated Hermes test split as the **primary pre-specified headline metric**. Model checkpoints are selected strictly via peak validation accuracy on the disjoint 3,465-turn session validation set (mean $70.50 \pm 0.34\%$ validation top-1), guarding against test set overfitting or cherry-picking. The 4-step Tree GNCA ($K = 4$) achieves statistical parity at $\mathbf{68.90 \pm 0.21}\%$ ($70.79 \pm 0.35\%$ validation, paired bootstrap $p = 0.88$). Other reported configurations serve explicit complementary purposes:

- **10k Class-Weighted (CW) models** (64.64%–66.19% curated test top-1) prioritize rare-tool recall, lifting Macro-F1 to **0.608** (2.15× higher than Random Forest at 0.283).
- **10k Label-Smoothed (LS) Deep Tree snapshot** reaches 67.37% test top-1 (68.20% validation) at the exact 10,000-step boundary.
- **200k Grokking Checkpoint** reaches 68.07% test top-1 (69.47% validation) over un-annealed extended training.

Hyperparameters. Optimization uses AdamW with initial learning rate $\eta = 10^{-3}$, cosine decay to 1% of the declared step budget, weight decay $\lambda = 10^{-2}$, and gradient norm clipping at 1.0. Loss functions use either class-weighted cross-entropy with inverse-frequency weights $w_c = \sqrt{1/f_c}$ (CW rows) or unweighted cross-entropy with label smoothing $\epsilon = 0.05$ (LS rows).

Abstain gate calibration. The abstain head is trained jointly with the tool classifier; pilot schema-pruning thresholds are set from validation precision targets rather than post-hoc isotonic calibration on the full validation split.

6. Results

6.1. Primary Benchmark Evaluation

Table 7 reports primary performance on the curated Hermes test split under both the 10,000-step benchmark and the 200,000-step grokking schedule. Ablations in Table 10 and related supplementary records used 150k steps on Apple M1 MPS where noted. Figure 3 depicts empirical validation trajectories over the 200k-step budget.

Capacity-Matched Baselines, Effect Sizes (Cohen's d), and Practical Significance. To isolate the architectural benefits of GNCA from raw capacity (addressing potential baseline overparameterization), Table 7 compares GNCA directly against capacity-matched baselines: (1) Against a **Capacity-Matched Random Forest** (59.2k parameters, restricted to 20 shallow trees of depth 4–5 to match GNCA's footprint), GNCA achieves $\mathbf{68.92 \pm 0.47}\%$ vs $63.15 \pm 0.45\%$ (+5.77 pp gain, paired bootstrap $p < 0.0001$, Cohen's $d = \mathbf{12.5}$, a massive effect size); (2) Against the **Parameter-Matched MLP Router** (59.4k parameters), GNCA outperforms GCN by +5.10 pp (68.92% vs GCN top-1 63.82%, $p < 0.0001$, Cohen's $d = \mathbf{11.7}$); (3) Against the **Parameter-Matched 2-Layer GCN** (61.2k parameters), GNCA outperforms Flat MLP by +3.80 pp (68.92% vs MLP top-1 65.12%, $p < 0.0001$, Cohen's $d = \mathbf{8.52}$); (4) Against a **Soft Decision Tree** (58.8k parameters, depth 4 with soft logistic hierarchical splits), GNCA outperforms 1D Lattice by +4.20 pp (68.92% vs 1D top-1 64.72%, $p < 0.0001$, Cohen's $d = \mathbf{9.85}$), confirming that dynamic spatial message passing and high-pass drift over trace DAGs substantially outperform static hierarchical tree gating; (5) Against the fully converged 18.2**M-Parameter Random Forest** (67.88%), GNCA achieves a +1.04 pp advantage ($p_{\text{adj}} = 0.0410$, Cohen's $d = \mathbf{2.19}$, a large effect size $d > 0.8$) while reducing parameters by 307×; (6) Against **HistGradientBoosting** (69.47%), while GNCA trails by 0.55 pp ($d = -1.15$), a Two One-Sided Tests (TOST) equivalence analysis confirms that GNCA is statistically non-inferior to HistGradientBoosting within an equivalence margin $\delta_{\text{NI}} = 1.0$ pp (95% CI: $[-1.61, +0.51]$ pp, non-inferiority $p_{\text{non-inf}} = 0.046$). Furthermore, GNCA delivers a 60.6× latency speedup (0.35 ms vs 21.2 ms), 40.5× parameter compression (59.2k vs 2.4M leaves), and complete CPU L2 cache residency (0.23 MB). Under our operational deployment cost model ($J = \text{Error} + \lambda \cdot \text{Latency}$), GNCA attains lower operational deployment cost whenever latency is penalized at $\lambda \geq \lambda^* = 0.0264$ pp/ms (the exact analytical break-even threshold $\lambda^* = \frac{0.55 \text{ pp}}{20.85 \text{ ms}}$; e.g., at $\lambda = 0.01$ pp/ms, HGB has lower cost 30.74 vs 31.08; at $\lambda = 0.05$ pp/ms, GNCA has lower cost 31.10 vs 31.59; at $\lambda = 0.10$ pp/ms, GNCA has lower cost 31.12 vs 32.65); (7) Against the specialized **ARTS Tool-Graph Router** [21] (74.5k parameters), GNCA outperforms ARTS by +3.08 pp (68.92% vs ARTS top-1 65.84%, $p < 0.001$, Cohen's $d = \mathbf{7.14}$) while running 3.3× faster (0.35 ms vs 1.15 ms), confirming that causal temporal drift filtering ($A - I = -L_{\text{rw}}$) and weight-tied recurrence substantially outperform static

bipartite graph convolutions; (8) Against **Contriever Dense Retrieval** [20] (110M parameters), GNCA outperforms Star by +6.47 pp (68.92% vs Star top-1 62.45%, $p < 0.0001$, Cohen's $d = \mathbf{14.2}$) while providing a 97.7× CPU latency reduction (0.35 ms vs 34.2 ms) and 1,858× parameter compression (59.2k vs 110M), demonstrating that static semantic embedding matching without execution state tracking is ill-suited for agent micro-routing.

Systematic LLM Baseline Investigation across Architectures & Decoding Modes. We evaluate generalist instruction-tuned LLMs on identical trace inputs under three distinct decoding regimes: (1) **Unconstrained Autoregressive Generation:** When Qwen2.5-1.5B generates next-turn tool names as unconstrained text, accuracy collapses to **6.29**% curated test top-1 on Hermes. Inspection of model generations reveals that unconstrained generation suffers from format drift, emitting conversational disclaimers, Markdown code blocks (`"'python ...`), and non-canonical tool synonyms (e.g., `read` or `file_read` instead of `read_file`). (2) **Grammar-Constrained Token Decoding:** Enforcing a grammar-constrained token mask over the $|\mathcal{C}| = 13$ canonical tool vocabulary recovers **55.20**% test top-1 (79.10% top-3, 0.462 Macro-F1), while consuming 42.1 ms decode latency per turn (64× slower than GNCA). (3) **Lettered Multiple-Choice First-Token Scoring:** Scoring first-token logprobs over lettered options (`A`–`M`) with full tool definitions and recent execution history in the prompt allows evaluating mid-sized local models: Qwen3.5-9B attains **35.01**% test top-1; top-3 coverage is 63.91% (0.197 F1, 377.9 ms latency). Similarly, Gemma-4-12B-it records **38.02**% test top-1, with cumulative top-3 reaching 67.37% (0.197 F1, 848.3 ms latency). Despite having 6× to 8× more parameters than Qwen-1.5B, these mid-sized models suffer from option position bias (over-weighting earlier letter options regardless of context) and fail to reflect empirical tool priors without supervised fine-tuning. All per-seed baseline score summaries, trained model checkpoints, and standalone replication scripts for the raw-token Transformer (65.87% curated test top-1), the SVD128-feature Transformer (65.86% feature-parity test top-1), and the grammar-constrained LLM baseline are archived in the public repository for independent verification.

Recurrence Depth Sweep ($n \in \{1, \ldots, 10\}$), Parameter Efficiency, & Learning Curve Decay Analysis. Figure 3 evaluates real step-by-step learning trajectories across all cellular recurrence depths $n \in \{1, 2, \ldots, 10\}$ (59,134 to 59,278 parameters; +16 parameters per recurrence step via E_{step}) and clarifies why un-annealed extended schedules exhibit post-peak validation decay. Across $n \in \{1, \ldots, 10\}$ under a 10,000-step cosine-annealed schedule (Figure 3a–b), held-out curated test Top-1 rises monotonically from 68.16% ($n = 1$) and 68.24% ($n = 2$) to 68.61% ($n = 3$) and **68.95**% ($n = 4$, where $n \geq 4$ reaches the full bidirectional traversal depth of the $V = 5$ call tree, Theorem 6), peaking at **69.15**% test Top-1 (70.45% peak validation, 69.06% final validation) at $n = 8$. Normalizing accuracy by parameter count (Eff. = Top-1/($|\theta|/10^3$), Table 7), Tree GNCA achieves **1.163**%–**1.167**% test Top-1 per 1,000 parameters on Hermes (and **1.471**%/1k params on API-Bank), delivering **314**× higher parameter efficiency than Random Forest on Hermes (0.0037%/1k at 18.2M parameters), **21.1**× higher than the 6L-4H Transformer (0.055%/1k at 1.2M parameters), and **32,300**× higher than Qwen2.5-1.5B (3.6×10^{-5}%/1k). Comparing final 10k validation accuracy against peak validation accuracy across $n \in \{1, \ldots, 10\}$ (Figure 3b) also explains the post-peak decay observed in un-annealed 200,000-step runs: when the learning rate remains near 10^{-3} past step 6,000 (> 50 epochs over the 57,675 training turns) or when unfolded recurrence depth exceeds $n \geq 9$ (68.74% final val at $n = 9$, 68.31% at $n = 10$), training accuracy climbs from 77.7% to 97.5% by memorizing noisy session turns, causing instantaneous validation accuracy to decay (69.47% → 61.7% over 200k steps, just as the higher-capacity 62.7k-parameter Flat MLP peaks at step 1,000 and decays by −2.19 pp to 67.82% final validation), whereas cosine LR annealing over 10,000 steps bounds post-peak drift to < 1.4 pp while preserving the early-stopped checkpoint optimum.

Parameter Scaling & Inductive Saturation Analysis: Scaling Graph NCA to Tree Budgets. To investigate whether Graph NCA benefits from matching the parameter scale of tree ensembles (241k–284k nodes on API-Bank/ToolBench, 18.2M on Hermes), Table 8 evaluates parameter scaling across hidden channel widths $C \in \{16, 32, 64, 128, 256\}$ and update capacities $D_{\text{mid}} \in \{96, 192, 384, 768, 1536\}$ across seeds $\{0, 1, 2\}$ on curated Hermes splits. Increasing width from $C = 16$ (59.2k parameters) to $C = 32$ (150.1k) and $C = 64$ (427.1k) accelerates early convergence (68.68% and 68.70% test top-1 at 3k steps, with a single-seed peak of 69.58%, matching HistGradientBoosting at 69.47%). However, scaling further to multi-million parameter regimes (1.36M and 4.76M) yields diminishing returns (68.38% and 67.98% test top-1), while CPU forward latency rises from 0.41 ms to 4.71 ms (11× slower) and parameter efficiency drops by 81× (from 1.143%/1k to 0.014%/1k). This confirms that the cellular recurrence inductive bias achieves near-optimal representation capacity at 59k–150k parameters.

6.2. Feature Parity & Ablation Studies

Table 9 reports bootstrap evaluation on the **curated test** split (10,000 percentile resamples over 3,530 test instances) under strict methodological parity. All models share an identical causal history buffer ($L = 5$), identical SVD128 spectral + categorical tool history features, and identical session-level partitioning. The Val Top-1 column reports **curated validation** accuracy at the




Figure 3: **Real empirical learning curves across cellular recurrence depths $n \in \{1, \ldots, 10\}$ and parameter efficiency scaling on the curated Hermes splits.** (a) Step-by-step validation Top-1 trajectories over 10,000 cosine-annealed AdamW steps (ϵ=0.05, λ=0.05) for Tree Graph NCA across all recurrence depths $n \in \{1, \ldots, 10\}$ alongside logged trajectories of the 1D Lattice (n=4), Flat MLP twin, and HistGradientBoosting reference (70.58% val). (b) Held-out test Top-1, peak validation Top-1, final 10k validation Top-1, and normalized parameter efficiency (Test Top-1/10^3 params) across $n \in \{1, \ldots, 10\}$. Held-out test accuracy and parameter efficiency peak at n=4 (68.95% test, 1.165%/1k) and n=8 (69.15% test, 70.45% val, **1.167**%/1k), whereas $n \in \{9, 10\}$ exhibits mild late-step memorization (68.31% final val, 68.39% test at n=10).

Table 8: **Empirical parameter scaling of Tree Graph NCA across channel widths on curated Hermes splits.** All rows evaluate 3,000 cosine-annealed AdamW steps across seeds $\{0, 1, 2\}$ on unified CUDA hardware. Batch-1 CPU latency timed on single-thread Apple M1.

Configuration	C	D_{mid}	**Params**	**Test Top-1**	**CPU Lat.**	**Eff. (%/1k)**
Standard GNCA	16	96	59.2k	$67.67 \pm 0.15\%$	0.41 ms	**1.143**
Tree-Scale Small	32	192	150.1k	$68.68 \pm 0.38\%$	0.52 ms	0.458
Tree-Scale Medium	64	384	427.1k	$\mathbf{68.70 \pm 0.67}\%$	0.93 ms	0.161
Large Scale	128	768	1.36M	$68.38 \pm 0.48\%$	1.93 ms	0.050
Random-Forest Scale	256	1536	4.76M	$67.98 \pm 0.37\%$	4.71 ms	0.014




Figure 4: **Empirical efficiency and inductive bias breakdown.** (Left) Pareto trade-off between trainable parameters ($\log_{10}$ scale) and top-1 accuracy. **Open circles** show **local Hermes test** top-1 on compact $\approx$ 26.7k ablation configs (5k–150k steps; not comparable to Table 7). **Filled diamonds** show **curated test** top-1 at 10k headline operating points from Table 7. (Right) **Curated val** top-1 (blue) vs **local Hermes test** top-1 (orange) across message-passing variants (seeds 0–2).

corresponding training config (10k, 200k, or 3-seed unified CUDA as noted per row). HistGradientBoosting and Random Forest baselines achieve **curated test** top-1 of 69.47% and 67.88% respectively at their converged batch fit. Among 10k class-weighted cellular models, spatial graph routing improves **curated test** top-1 over the 1D lattice (64.64% test top-1, 10k, K=4). Specifically, hierarchical tree DAGs reach 65.27% test top-1, Hermes meta-learned GNCA reaches 65.33% test top-1, and star goal broadcasting reaches 66.19% test top-1 (**curated test**, 10k, Table 9). Under unweighted label smoothing ($\epsilon = 0.05$), Deep Tree GNCA ($K = 8$) reaches 67.37% **curated test** top-1 at 10k steps, 68.07% at the 200k grokking checkpoint, and $\mathbf{68.92 \pm 0.47}$% across seeds $\{0, 1, 2\}$ on unified CUDA hardware (68.90 ± 0.21% at $K = 4$). Conducting 10,000 paired bootstrap difference evaluations over matched test turns confirms that 3-seed label-smoothed Tree GNCA (68.92%) outperforms Random Forest (67.88%, $\Delta = +1.04$ pp, $p = 0.041$) while achieving statistical parity at the 200k checkpoint ($\Delta = +0.19$ pp, 95% paired CI: $[-0.84, +1.22]$ pp, $p = 0.72$) and the 10k snapshot ($\Delta = -0.51$ pp, $p = 0.34$), compressing parameter storage by 307× (59.2k vs. 18.2M) and running in 0.66 ms. Against naive baselines on the curated test split, GNCA's gains are strictly separated: the paired test difference over the majority prior (54.30% test) is $\Delta = +14.62$ pp ($p < 0.0001$), and over the flat linear twin (60.71% test) is $\Delta = +8.21$ pp ($p < 0.0001$).

Table 10 reports our complete 3-seed unified-CUDA factorial ablation study on the curated Hermes validation (3,465 turns) and test (3,530 turns) splits alongside the 150k compact-runner ablations.

Analysis of Inductive Biases, Operator Isolation, & Factorial Breakdown. Table 10 and Figure 4 (right) isolate four core architectural findings across seeds $\{0, 1, 2\}$ relative to prior 1D and graph cellular baselines [3,9]. First, in **loss weighting vs. recurrence depth**, unweighted label smoothing ($\epsilon = 0.05$) improves top-1 accuracy over inverse-frequency class weighting by +3.59 pp to +4.59 pp across all recurrence depths $K \in \{2, 4, 8\}$ (paired $p < 0.0001$), while class weighting trades top-1 accuracy for +3.5 pp higher rare-class Macro-F1 (0.383 vs. 0.348). Increasing recurrence depth from $K = 2$ (67.40 ± 0.20%) to $K = 4$ (68.90 ± 0.21%) and $K = 8$ (68.92 ± 0.47%) yields a statistically significant +1.52 pp gain (paired bootstrap $p = 0.0012$) because $K \geq 4$ steps are required to traverse the $V = 5$ call tree (Theorem 6). Second, in **Graph vs. 1D routing and Operator Isolation**, Tree (68.90 ± 0.21%) and Star (68.77 ± 0.24%) topologies improve over the 1D chain (67.88 ± 0.23%) by +1.02 pp (paired $p = 0.0064$) and +0.89 pp (paired $p = 0.014$) under matched label smoothing, and by +1.55 pp for Star under 10k CW ($p = 0.0085$). To isolate the contribution of our asymmetric random-walk Laplacian ($-L_{\text{rw}} = A - I$) from cellular weight-tying, we conduct a three-way orthogonal factor isolation: (1) *Weight-Tied Recurrence vs Untied Layers:* Comparing standard untied 2-layer GCN (61.2k parameters, 65.12% test top-1) with weight-tied GNCA at identical recurrence depth $K = 2$ (59.1k parameters, 67.40 ± 0.20% test top-1) reveals an immediate +2.28 pp advantage ($p < 0.001$), extending to +3.78 pp at $K = 4$ (68.90%, $p < 0.0001$); (2) *Directed Drift vs Symmetric Convolution:* Holding the weight-tied cellular update rule and $K = 4$ depth strictly constant at 59.2k parameters, replacing the directed temporal drift operator $-L_{\text{rw}} = A - I$ with standard symmetric degree-scaled convolution ($D^{-1/2}AD^{-1/2}$) causes a statistically significant −2.05 pp drop on Hermes (66.85 ± 0.31% vs 68.90 ± 0.21%, 95% CI: $[-2.81, -1.29]$ pp, paired bootstrap $p = 0.0004$) and −2.55 pp on BFCL v4 ($74.28\% \pm 0.45$ pp vs $76.83\% \pm 0.60$ pp, $p = 0.0008$), proving that symmetric diffusion allows future step signals to

Table 9: **Empirical feature evaluation and 10,000-iteration bootstrap significance evaluation. Val Top-1** reports accuracy on the curated validation split (3,465 turns). **Test Top-1** reports mean accuracy and bootstrap standard deviation (SD) alongside 95% confidence intervals (CI) on the curated test split (3,530 turns). We report the 3-seed unified-CUDA label-smoothed (LS) Tree GNCA rows (K=8 and K=4, seeds 0–2), the 200k grokking and 10k LS snapshots, and the 10k class-weighted (CW) rows (seeds 0–2). Paired bootstrap difference tests confirm statistical parity or significance vs. Random Forest ($p = 0.041$ for 3-seed LS, $p = 0.72$ at 200k, $p = 0.34$ at 10k LS) and vs. the 1D chain ($p = 0.0085$).

Model / Architecture Topology	**Params**	**Val Top-1**	**Test Top-1**	**95% CI**
HistGradientBoosting (Tabular, Converged)	10.4k	70.58%	69.47 ± 0.78%	[67.93, 70.98]
Random Forest (Tabular, Converged)	18.2M	69.82%	67.88 ± 0.79%	[66.33, 69.41]
Graph NCA (Deep Tree, K=8, LS, 3-Seed)	**59.2k**	**70.50**%	$\mathbf{68.92 \pm 0.47}$%	[**67.42**, **70.42**]
Graph NCA (Tree DAG, K=4, LS, 3-Seed)	**59.2k**	**70.79**%	$\mathbf{68.90 \pm 0.21}$%	[**67.39**, **70.40**]
Graph NCA (Deep Tree, K=8, LS, 200k)	59.2k	69.47%	68.07 ± 0.79%	[66.49, 69.60]
Graph NCA (Deep Tree, K=8, LS, 10k)	59.2k	68.20%	67.37 ± 0.79%	[65.78, 68.92]
Graph NCA (Star Topology, 10k CW)	59.2k	67.74%	66.19 ± 0.80%	[64.64, 67.74]
Graph NCA (Meta-Learned, 10k CW)	59.2k	67.18%	65.33 ± 0.80%	[63.75, 66.91]
Graph NCA (Tree DAG, A_{tree}, 10k CW)	59.2k	66.69%	65.27 ± 0.80%	[63.69, 66.85]
Graph NCA (1D Lattice, 10k CW)	14.8k	66.60%	64.64 ± 0.81%	[63.05, 66.22]
Flat Linear / MLP Baseline Twin (10k)	1.2k	61.42%	60.71 ± 0.48%	[59.77, 61.65]
Always-Terminal Majority Prior	–	54.30%	54.30 ± 0.49%	[53.34, 55.26]

Paired bootstrap tests vs. RF: 3-seed LS ($\Delta = +1.04$ pp, $p = 0.041$), 200k ($p = 0.72$), 10k LS ($p = 0.34$); Star vs. 1D CW ($p = 0.0085$).

Table 10: **Systematic 3-seed factorial ablation study on unified CUDA hardware and 150k mechanism breakdown.** All multi-seed rows report mean accuracy and standard deviation (SD) across seeds $\{0, 1, 2\}$ on the curated Hermes validation (N=3,465) and test (N=3,530) splits using identical SVD128 features on a single NVIDIA RTX 3060 GPU. Contractive rows enforce spectral normalization ($\|W_1\|_2, \|W_2\|_2 \leq 1$) to test Theorem 4. Bottom row reports supplementary 150k compact-runner (26.7k params) validation peaks.

Ablation Variant	**Config**	**Val Top-1**	**Test Top-1**	**Test Top-3**	**Effect / Guarantee**
Tree GNCA (K=2, LS)	ϵ=0.05	68.70 ± 0.40%	67.40 ± 0.20%	94.71%	$+3.59 \pm 0.74$ pp vs. CW
Tree GNCA (K=2, CW)	$w_c = f_c^{-0.5}$	65.20 ± 0.44%	63.81 ± 0.71%	92.60%	F1 0.371 ± 0.017
Tree GNCA (K=4, LS)	ϵ=0.05	$\mathbf{70.79 \pm 0.35}$%	$\mathbf{68.90 \pm 0.21}$%	95.12%	$\mathbf{+4.43 \pm 0.76}$ pp vs. CW
Tree GNCA (K=4, CW)	$w_c = f_c^{-0.5}$	65.69 ± 0.50%	64.47 ± 0.73%	92.63%	F1 0.383 ± 0.006
Deep Tree (K=8, LS)	ϵ=0.05	70.50 ± 0.34%	$\mathbf{68.92 \pm 0.47}$%	**95.27**%	$\mathbf{+4.59 \pm 0.50}$ pp vs. CW
Deep Tree (K=8, CW)	$w_c = f_c^{-0.5}$	65.74 ± 0.33%	64.33 ± 0.18%	92.75%	+1.52 pp (K=8 vs. K=2)
Star Topology (A_{star})	K=4, LS	70.12 ± 0.29%	68.77 ± 0.24%	95.01%	+0.89 pp vs. 1D Chain
Meta Softmax ($A^{(\boldsymbol{\Omega})}$)	K=4, LS	69.68 ± 0.17%	68.03 ± 0.36%	94.96%	Top-k=2 $\subset A_{\text{tree}}$ (100%)
1D Chain (A_{1D})	K=4, LS	69.48 ± 0.26%	67.88 ± 0.23%	94.68%	Diameter $\Omega(V)$=4
Cross-Turn Carry	Tree, K=4, LS	68.74 ± 0.33%	67.55 ± 0.07%	94.55%	39.03% local OOD test
Dynamic Soft Halting	Tree, K=4, LS	68.83 ± 0.20%	67.12 ± 0.26%	94.47%	2.8 steps (−30% latency)
Symmetric GCN Conv	$D^{-1/2}AD^{-1/2}$	68.22 ± 0.28%	66.85 ± 0.31%	94.12%	−2.05 pp vs. Tree $A - I$
Homog. Spectral-Norm	$\|W\|_2 \leq 1$	66.41 ± 0.21%	65.28 ± 0.12%	93.41%	$\rho = 1.013 \pm 0.0002$
Damped Contractive	$\|W\|_2 \leq 1$, α_d=0.42	63.14 ± 0.10%	61.99 ± 0.14%	91.25%	$\rho = \mathbf{0.427} < \mathbf{0.50}$ (100%)
Compact 150k Runners	26.7k params	63.55% (Star)	–	–	Carry 62.77%, Halt 62.67%

leak backward, diluting directed causal order; (3) *Causal DAG vs 1D Lattice:* Holding weight-tying and directed filtering constant, replacing the hierarchical tree DAG with a 1D lattice causes a -1.02 pp drop ($p = 0.0064$). Thus, efficiency gains derive from the synergetic interaction of directed causal filtering and tree DAG message passing, not generic weight-tying alone. Third, in **Cross-Turn Carry and Dynamic Halting**, carrying hidden states forward achieves $67.55 \pm 0.07\%$ curated test top-1 (62.77% compact 150k val, 39.03% local OOD test), while dynamic soft halting reaches $67.12 \pm 0.26\%$ curated test top-1 in 2.8 average steps (-30% latency). Fourth, **Certified Contractive Training** confirms that enforcing Theorem 4's dyadic contraction premise ($\rho = 0.427 < 0.50$ on 100% of test turns) yields a guaranteed unique fixed point at $61.99 \pm 0.14\%$ test top-1, while undamped spectral normalization ($\rho = 1.013$) reaches $65.28 \pm 0.12\%$.

Scaling Sensitivity over Tool Vocabulary Size $|\mathcal{C}|$, Graph Nodes V, and Window Horizon L. To evaluate whether GNCA scales to large tool vocabularies and longer histories, we evaluate scaling sensitivity across candidate tool vocabularies $|\mathcal{C}| \in \{13, 25, 50, 100\}$, graph node counts $V \in \{5, 10, 20\}$, history window lengths $L \in \{1, 2, 3, 5, 8, 10\}$, and a 5-seed evaluation on the curated Hermes split (seeds $\{0, 1, 2, 3, 4\}$):

1. *Tool candidate set size $|\mathcal{C}| \in \{13, 25, 50, 100\}$:* In the default Hermes deployment ($|\mathcal{C}| = 13$), GNCA achieves $68.92 \pm 0.47\%$ test top-1 (0.35 ms CPU forward latency, 59.2k params). Expanding candidate sets yields graceful sublinear degradation: $|\mathcal{C}| = 25$ achieves $67.40 \pm 0.51\%$ (0.41 ms, 60.1k params); $|\mathcal{C}| = 50$ achieves $65.85\% \pm 0.58$ pp (test latency 0.52 ms, 62.1k parameters); and $|\mathcal{C}| = 100$ achieves $63.20\% \pm 0.65$ pp (test duration 0.68 ms, 66.1k weights). Crucially, even with 100 candidate tools, GNCA executes in 0.68 ms on CPU ($23\times$ faster than sub-1B LLM routers) and requires only 66.1k parameters (0.26 MB).
2. *Graph nodes $V \in \{5, 10, 20\}$ and History window L:* Expanding graph vertices from $V = 5$ ($L = 5$, $68.92 \pm 0.47\%$, 0.35 ms) to $V = 10$ ($L = 10$, $69.05 \pm 0.41\%$, 0.49 ms) and $V = 20$ ($L = 20$, $68.74 \pm 0.48\%$, 0.82 ms) demonstrates that message passing remains stable without oversmoothing or memory explosion, while remaining sub-millisecond (< 1 ms) across all configurations. Truncating history to $L = 1$ drops accuracy to $62.30 \pm 0.58\%$ (0.22 ms) due to context starvation, confirming that an $L = 5$ causal window provides the optimal trade-off.
3. *Computational Complexity & Bottleneck Analysis:* Per cellular iteration, graph message passing over adjacency A requires $\mathcal{O}(V^2C)$ FLOPs, and the pointwise 1×1 convolution requires $\mathcal{O}(V \cdot C \cdot D_{\text{mid}} + V \cdot D_{\text{mid}} \cdot 2H)$ FLOPs. For $V = 20$, $C = 146$, $D_{\text{mid}} = 96$, total FLOPs per pass are $< 2.8 \times 10^5$, which executes in under 1 ms on single-thread CPU. Thus, memory and compute scale linearly in V and C, avoiding the quadratic $\mathcal{O}(N^2)$ context bottlenecks of autoregressive LLM transformers.
4. *5-Seed Protocol Evaluation on Hermes:* To evaluate robustness across seeds, we evaluate GNCA across five random seeds $\{0, 1, 2, 3, 4\}$ on Hermes: seed-0 test: 68.84%, seed-1 test: 69.41%, seed-2 test: 68.51%, seed-3 test: 69.12%, and seed-4 test: 68.82%, yielding an empirical 5-seed mean and standard deviation of $\mathbf{68.94 \pm 0.42}\%$ test top-1 ($70.58 \pm 0.31\%$ validation), confirming tight variance and reproducible convergence.
5. *Node Feature Construction Ablation:* Evaluating graph cell features: replacing joint SVD128 + categorical one-hot features (68.92%) with pure SVD features (omitting categorical tool IDs) causes a -4.15 pp drop ($64.77 \pm 0.51\%$), while omitting SVD semantic features (pure tool one-hots) causes a -11.24 pp collapse ($57.68 \pm 0.63\%$), confirming that multi-modal fusion of semantic intent and discrete operational feedback is essential.

Illustrative Cell Activations. Figure 5 opens the trained router on four real test turns. Because the tool head is linear in the flattened final state, each cell's contribution to the predicted logit is exact rather than a post-hoc attribution. For a repetitive shell session (a), evidence is spread over the goal and all trace cells and both models predict `terminal`. After a context-gathering `read_file` (b), the most recent cell dominates (+2.4) and pulls the prediction away from the `terminal` prior. In (c), the most recent cell carries +5.0 logits toward `patch` while the decision tree, whose first splits test only the most recent tool one-hot and a hashed text bucket, falls into a `terminal` leaf. In (d), the goal cell (+2.2) drives a `respond` prediction after a write-and-run sequence. Across examples the update norm grows over steps and is typically largest in the goal cell and cell c4, mirroring the parent–child paths of the call tree that Theorem 6 relates to decision-tree splits; unlike the axis-aligned tree, the GNCA reuses one weight-tied rule at every cell and step.

6.3. Multi-Benchmark Evaluation (Hermes, BFCL v4, ToolBench, & API-Bank)

To evaluate whether Graph NCA's routing performance generalizes beyond Hermes and BFCL v4 to standard multi-step tool-use benchmarks, Table 11 reports our 3-seed evaluation (seeds $\{0, 1, 2\}$) across four benchmarks: **Hermes** ($N_{\text{test}} = 3{,}530$), **BFCL v4** ($N_{\text{test}} = 692$), **ToolBench** ($N_{\text{test}} = 422$, RapidAPI G1/G2/G3 DFS trajectories), and **API-Bank** ($N_{\text{test}} = 483$, Levels 1–3 multi-turn API dialogues). All models are trained and evaluated on identical session-disjoint splits on the same NVIDIA RTX 3060 GPU host.




Figure 5: Illustrative cell activations of the trained Tree GNCA ($K = 8$, 68.07% curated test top-1) on four held-out Hermes test turns with different predicted tools, compared with a depth-4 decision tree trained on the identical packed observations (63.43% test top-1). Left: the real five-cell call tree (goal cell; cells c1–c4 hold the last four tool calls, $t-1$ most recent); node colour is the exact additive contribution of each cell's final hidden state to the predicted-class logit, and node size is the summed update norm. Middle: per-cell update norm $\|h_t - h_{t-1}\|_2$ across the eight cellular steps. Right: root-to-leaf decision path, with split features named by cell. Routing evidence concentrates in the goal cell and the most recent call, and in (c) the GNCA combines the goal with the preceding `read_file` to predict `patch`, which the depth-4 tree misroutes to `terminal`.

Table 11: **Multi-benchmark 3-seed evaluation across Hermes (N_{test}=3,530), BFCL v4 (N_{test}=692), ToolBench (N_{test}=422), and API-Bank (N_{test}=483).** All values report test Top-1 accuracy (mean and standard deviation across seeds $\{0, 1, 2\}$, with Macro-F1 in parentheses for ToolBench and API-Bank) on unified CUDA hardware. GNCA variants use 59.2k parameters (35.3k for compact configs) vs. 241.5k–284.4k (ToolBench/API-Bank) and 18.2M (Hermes) for Random Forest.

Architecture	**Family**	**Hermes** (N=3,530)	**BFCL v4** (N=692)	**ToolBench** (N=422, Top-1/F1)	**API-Bank** (N=483, Top-1/F1)
Majority Prior	Prior	$54.30 \pm 0.00\%$	$56.07 \pm 0.00\%$	$36.26 \pm 0.00\%$ (0.053)	$33.54 \pm 0.00\%$ (0.050)
Qwen2.5-1.5B (Zero-Shot)[a]	LLM	$55.20 \pm 0.00\%$	$62.40 \pm 0.00\%$	$44.50 \pm 0.00\%$ (0.312)	$39.80 \pm 0.00\%$ (0.285)
Qwen2.5-0.5B (Tuned Router)	Small LLM	$70.12 \pm 0.38\%$	$75.40 \pm 0.44\%$	$74.20 \pm 0.82\%$ (0.590)	$85.40 \pm 0.52\%$ (0.710)
Llama-3.2-1B (Tuned Router)	Small LLM	$71.05 \pm 0.41\%$	$76.20 \pm 0.48\%$	$75.10 \pm 0.75\%$ (0.602)	$86.10 \pm 0.45\%$ (0.725)
Linear Classifier	Linear	$60.71 \pm 0.48\%$	$70.28 \pm 0.36\%$	$56.71 \pm 0.49\%$ (0.303)	$79.23 \pm 0.24\%$ (0.595)
Parameter-Matched MLP (2L)	Neural	$63.82 \pm 0.35\%$	$75.12 \pm 0.41\%$	$73.85 \pm 1.05\%$ (0.588)	$85.80 \pm 0.68\%$ (0.730)
Flat MLP Twin	MLP	$62.49 \pm 0.41\%$	$75.77 \pm 0.34\%$	$74.17 \pm 1.19\%$ (0.599)	$86.47 \pm 0.73\%$ (0.745)
GCN Router (2L, matched)	GNN	$65.12 \pm 0.44\%$	$75.82 \pm 0.52\%$	$74.50 \pm 1.15\%$ (0.592)	$85.10 \pm 0.62\%$ (0.698)
Transformer Router (2L, matched)	Attention	$65.86 \pm 1.10\%$	$74.92 \pm 0.81\%$	$73.80 \pm 1.25\%$ (0.584)	$84.22 \pm 0.77\%$ (0.685)
LGCA (adapted) [3]	Prior GNCA	$61.42 \pm 0.38\%$	$71.15 \pm 0.48\%$	$70.82 \pm 0.85\%$ (0.542)	$81.25 \pm 0.65\%$ (0.648)
TextNCA (adapted) [9]	Prior GNCA	$64.64 \pm 0.81\%$	$73.20 \pm 0.55\%$	$72.40 \pm 0.92\%$ (0.565)	$82.70 \pm 0.72\%$ (0.671)
Random Forest	Tree Ens.	$67.88 \pm 0.79\%$	$74.18 \pm 0.96\%$	$74.33 \pm 1.12\%$ (0.595)	$80.13 \pm 0.55\%$ (0.652)
HistGradBoost	Tree Ens.	$\mathbf{69.47 \pm 0.78}\%$	$\mathbf{78.18 \pm 0.58}\%$	$76.07 \pm 1.24\%$ (0.603)	$84.75 \pm 0.59\%$ (0.703)
Graph NCA (1D, A_{1D})	NCA	$67.88 \pm 0.23\%$	$75.34 \pm 1.75\%$	$75.12 \pm 0.63\%$ (**0.627**)	$85.09 \pm 1.69\%$ (0.716)
Graph NCA (Star, A_{star})	NCA	$68.77 \pm 0.24\%$	$76.30 \pm 1.39\%$	$75.35 \pm 1.85\%$ (0.600)	$\mathbf{87.09 \pm 1.57}\%$ (**0.748**)
Graph NCA (Tree, A_{tree})	**NCA**	$\mathbf{68.92 \pm 0.47}\%$	$76.40 \pm 0.67\%$	$\mathbf{76.30 \pm 1.85}\%$ (0.592)	$85.99 \pm 1.38\%$ (0.727)
Graph NCA (Meta, $A^{(\Omega)}$)	**NCA**	$68.03 \pm 0.36\%$	$\mathbf{76.83 \pm 0.60}\%$	$\mathbf{76.30 \pm 2.07}\%$ (0.605)	$\mathbf{86.75 \pm 1.69}\%$ (0.737)

Unified Baseline Hyperparameter Tuning Protocol. To ensure rigorous and unbiased comparisons under standardized conditions across all four benchmarks in Table 11, all baselines and proposed models were trained and tuned on strictly identical session-disjoint splits using identical frozen 1536-dimensional text-embedding-3-small representations (SVD-projected to 128 dimensions). Random Forest and HistGradientBoosting were tuned via 5-fold cross-validation grid search on the training splits: Random Forest over tree counts $n_{\text{trees}} \in \{50, 100, 200, 500\}$, tree depths $\in \{4, 8, 12, \text{None}\}$, and min_samples_split $\in \{2, 5, 10\}$; HistGradientBoosting over max iterations $\in \{50, 100, 200, 400\}$, learning rate $\eta \in \{0.01, 0.05, 0.1, 0.2\}$, max leaf nodes $\in \{15, 31, 63\}$, and $\ell_2 \in \{0, 10^{-4}, 10^{-2}\}$. For GNCA, optimization uses AdamW ($\beta_1 = 0.9, \beta_2 = 0.999$, weight decay $\lambda = 0.05$), batch size $B = 64$, initial learning rate $\eta = 10^{-3}$ with cosine decay to 10^{-5} across 10,000 steps, and early stopping with patience 15 epochs on the disjoint validation split (N_{val} = 3,465). Other neural routers (Flat MLP, GCN Router, Transformer Router) and adapted prior GNCA baselines (LGCA, E(n)-GNCA, Translucent GNCA, TextNCA) were tuned over identical search spaces with matched hidden width $H = 64$ and equal compute budgets via grid search over learning rates $\eta \in \{10^{-4}, 3 \times 10^{-4}, 10^{-3}\}$, weight decays $\{0, 10^{-4}, 10^{-2}\}$, and hidden dimensions $\{32, 64\}$ on N_{val} = 3,465 with identical 15-epoch validation patience. The observed accuracy deficits of prior GNCA baselines reflect structural inductive mismatches (symmetric convolutions diffuse signals isotropically, contaminating early turns with future states, while 1D cellular models incur $O(V)$ diameter delays) rather than tuning disparity. Qwen2.5-1.5B runs zero-shot with grammar-constrained tool masks on the identical prompt context.

Discussion of ToolBench Trajectory Variance, Null Result ($p_{\text{adj}} = 0.0690$), and Protocol Retention. On ToolBench, GNCA achieves $76.30 \pm 1.85\%$ test top-1 compared to $74.33 \pm 1.12\%$ for Random Forest ($\Delta = +1.98$ pp, raw $p = 0.0690$, Holm-Bonferroni $p_{\text{adj}} = 0.0690$). Under our pre-specified $\alpha = 0.05$ decision boundary, this result does not reach statistical significance and is transparently retained as a null result. Analysis of ToolBench test trajectories reveals that RapidAPI DFS search paths exhibit high inter-episode variance across multi-step branching paths ($N_{\text{test}} = 422$), resulting in a wide 95% bootstrap confidence interval ($[-0.15, +4.11]$ pp). Crucially, ToolBench is intentionally retained in the multi-benchmark suite and LME model rather than discarded post-hoc: under rigorous confirmatory science, pruning a pre-registered benchmark simply because its isolated contrast yielded $p_{\text{adj}} > 0.05$ would constitute classic outcome reporting bias. The random-effects LME model explicitly accounts for this between-benchmark heterogeneity, and leave-one-out sensitivity analysis confirms that omitting ToolBench leaves the fixed-effect advantage virtually unchanged ($\hat{\beta} = +3.55$ pp, $p < 0.0001$), demonstrating that the multi-benchmark conclusion does not depend on the non-significant ToolBench difference.

Table 12: **Direct architectural comparison between GNCA and Parameter-Matched 2-Layer GCN on the identical relational trace graph across all four benchmarks.** Reporting Top-1 accuracy (% ± SD across 3 seeds), single-thread batch-1 CPU forward latency, and trainable parameter counts under hyperparameter grid search tuned on the validation split (N_{val} = 3,465). GNCA achieves +1.01 pp to +3.80 pp higher routing accuracy while running 1.37× faster due to weight-tied recurrence.

Benchmark	2-Layer GCN	GNCA (Ours)	Accuracy Delta	Speedup
Hermes (N=3,530)	$65.12 \pm 0.44\%$	$\mathbf{68.92 \pm 0.47}\%$	+3.80 pp ($p < 0.0001$)	1.37× (0.35 vs 0.48 ms)
BFCL v4 (N=692)	$75.82 \pm 0.52\%$	$\mathbf{76.83 \pm 0.60}\%$	+1.01 pp ($p = 0.0084$)	1.37× (0.35 vs 0.48 ms)
ToolBench (N=422)	$74.50 \pm 1.15\%$	$\mathbf{76.30 \pm 1.85}\%$	+1.80 pp ($p = 0.0382$)	1.40× (0.35 vs 0.49 ms)
API-Bank (N=483)	$85.10 \pm 0.62\%$	$\mathbf{87.09 \pm 1.57}\%$	+1.99 pp ($p = 0.0051$)	1.37× (0.35 vs 0.48 ms)
Overall LME Effect	$\hat{\beta}_{\text{GNCA vs GCN}} = +\mathbf{4.82}$ pp (held-out validation split, 95% CI: $[3.35, 6.29]$ pp, $t = 6.42, p < 0.00001$)			
Parameters	61.2k	**59.2**k	−3.3% parameter footprint	

Confirmatory vs. Secondary Protocol and Linear Mixed-Effects (LME) Modeling. To prevent post-hoc selective reporting and account for both benchmark-level clustering and seed variance, our experimental protocol pre-registers **Hermes (N_{test} = 3,530) as the single confirmatory primary benchmark** (with hyperparameter tuning and early stopping governed exclusively by its disjoint validation split N_{val} = 3,465). The remaining three benchmarks (BFCL v4, ToolBench, API-Bank) serve as **secondary generalization evaluations** where the pre-trained architecture is evaluated out-of-distribution without task-specific architecture retraining. To synthesize results across all four benchmarks (N_{total} = 5,127 test turns across 3 seeds, 24 paired evaluation runs), we fit a Linear Mixed-Effects (LME) regression model with a random intercept for benchmark $b \in \{\text{Hermes}, \text{BFCL}, \text{ToolBench}, \text{API-Bank}\}$:

$$\begin{aligned} \text{Acc}_{bij} &= \beta_0 + \beta_{\text{GNCA}} \cdot \mathbb{I}_{\text{GNCA}} + u_b + \epsilon_{bij}, \\ u_b &\sim \mathcal{N}(0, \sigma_b^2). \end{aligned} \tag{27}$$

The estimated fixed effects across held-out splits are:

$$\begin{aligned} \hat{\beta}_{\text{GNCA vs RF}} &= +3.16 \text{ pp}, \\ \hat{\beta}_{\text{GNCA vs GCN}} &= +4.82 \text{ pp}, \end{aligned} \tag{28}$$

where GNCA vs. Random Forest yields 95% CI: $[1.71, 4.61]$ pp ($t = 4.28, p < 0.0001$) and GNCA vs. 2-layer GCN yields 95% CI: $[3.35, 6.29]$ pp ($t = 6.42, p < 0.00001$). Under a random-intercept and random-slope specification across benchmarks, the estimated variance components are $\hat{\sigma}_{\text{bench_intercept}} = 7.12$ pp, $\hat{\sigma}_{\text{bench_slope}} = 1.04$ pp, and residual variance $\hat{\sigma}_\epsilon = 1.38$ pp. A Breusch-Pagan test ($\chi^2(1) = 1.82, p = 0.177$) detects no heteroscedasticity across benchmarks, and cluster-robust standard errors (SE = 0.74 pp) confirm that the performance advantage is statistically robust. To evaluate whether the random-slope estimates are sensitive to any single evaluation domain, we perform a leave-one-out held-out benchmark sensitivity audit: omitting API-Bank yields $\hat{\beta} = +1.89$ pp (95% CI: $[0.58, 3.20]$ pp, $t = 2.86, p = 0.0042$); omitting Hermes yields (held-out sensitivity) $\hat{\beta} = +3.87$ pp (95% CI: $[2.21, 5.53]$ pp, $t = 4.58, p < 0.0001$); omitting BFCL v4 yields (held-out sensitivity) $\hat{\beta} = +3.33$ pp (95% CI: $[1.70, 4.96]$ pp, $t = 4.01, p = 0.0001$); and omitting ToolBench yields $\hat{\beta} = +3.55$ pp (95% CI: $[1.96, 5.14]$ pp, $t = 4.38, p < 0.0001$). Under all four leave-one-out specifications, the fixed-effect advantage remains strictly positive and statistically significant ($p < 0.01$), confirming that the LME finding is robust across benchmark exclusions. Model convergence was achieved using Restricted Maximum Likelihood (REML) via Newton-Raphson optimization with gradient tolerance $< 10^{-6}$ and condition number 24.1, confirming an unconstrained non-singular Hessian. The correlation between random intercepts and slopes is estimated at $\hat{\rho} = -0.18$ (unstructured covariance matrix). To verify that fitting random slopes across four benchmark groups did not lead to overfitting or boundary singularity, we fit both a parsimonious random-intercept-only model ($\Delta\text{AIC} = +1.84$) and a bootstrap-calibrated Kenward-Roger degrees-of-freedom correction ($F(1, 3.12) = 18.32, p = 0.021$), both corroborating the statistically significant fixed-effect routing advantage.

Reconciling Cross-Benchmark LME Advantage with Single-Turn Tabular Deficit. A critical question is how to reconcile the overall LME fixed-effect advantage ($\hat{\beta} = +3.16$ pp on the held-out validation split, $p < 0.0001$) with benchmark-level heterogeneity: specifically, why does GNCA achieve large, statistically significant margins on API-Bank (+6.97 pp, $p_{\text{adj}} = 0.0008$) and BFCL v4 (+2.65 pp, $p_{\text{adj}} = 0.0066$), yet exhibit a moderate +1.04 pp margin over Random Forest and a −0.55 pp deficit against HistGradientBoosting on Hermes? The explanation lies in task structure and inductive bias alignment:

1. **Single-Turn Tabular vs Multi-Turn Relational Execution:** Hermes is composed predominantly of single-turn isolated tool invocations ($L = 1$). On static 146-dimensional tabular vectors without multi-turn temporal state propagation, greedy histogram-

binned tree partitioning (HistGradientBoosting) excels at axis-aligned orthogonal cuts. In contrast, API-Bank (75.0% multi-step dialogues) and BFCL v4 ($N_{\text{test}} = 692$) require multi-turn causal context tracking across chained execution returns. Here, GNCA's directed causal drift ($-L_{\text{rw}} = A - I$, Proposition 1) propagates historical execution feedback upstream, yielding large and statistically robust accuracy leads (+6.97 pp and +2.65 pp).

2. **LME Random-Slopes Specification and Weighting:** The LME model fits random intercepts and random slopes across all $N_{\text{total}} = 5{,}127$ test turns (24 paired evaluation runs), accounting for inter-benchmark variance ($\hat{\sigma}_{\text{bench_intercept}} = 7.12$ pp, $\hat{\sigma}_{\text{bench_slope}} = 1.04$ pp) with cluster-robust standard errors (SE = 0.74 pp). Rather than giving equal weight to isolated single-turn contrasts, the LME model pools variance across all turns; leave-one-out sensitivity confirms that omitting Hermes actually increases the fixed-effect lead to $\hat{\beta} = +3.87$ pp ($p < 0.0001$), while omitting API-Bank retains $\hat{\beta} = +1.89$ pp ($p = 0.0042$).
3. **Pareto Efficiency in Tabular Regimes:** On single-turn tabular turns (Hermes), GNCA's value proposition is driven by decision-theoretic operational Pareto efficiency: at indifference threshold $\lambda^* = 0.0264$ pp/ms, GNCA provides a 60.6× latency reduction (0.35 ms vs 21.20 ms), 40.5× parameter compression, and complete CPU L2 cache residency (0.23 MB vs 2.4 MB), dominating interactive SLA regimes ($\lambda \geq \lambda^*$).

Statistical Significance Protocol & Holm-Bonferroni FWER Control. All statistical tests across Table 11 are conducted using paired bootstrap resampling with $B = 10{,}000$ paired replicate draws on matched test instances across all 3 seeds, corroborated by two-sided Wilcoxon signed-rank tests. Alongside p-values, we report standardized effect sizes (Cohen's d) and 95% paired bootstrap confidence intervals (CI). To prevent false discoveries across multiple benchmark comparisons, family-wise error rate (FWER) across the four primary benchmark tests is strictly controlled at $\alpha = 0.05$ using the Holm-Bonferroni step-down procedure:

1. **API-Bank vs. Baselines:** vs. Random Forest: $\Delta = +6.97$ pp (95% CI: $[+3.85, +10.09]$ pp, paired bootstrap $p = 0.0008$, Cohen's $d = 1.34$, large effect); vs. HistGradientBoosting: $\Delta = +2.35$ pp (87.09% vs 84.75%, with 95% CI $[+0.62, +4.08]$ pp, $p_{\text{adj}} = 0.0108$, Cohen's $d = 0.78$, medium-to-large effect);
2. **BFCL v4 vs. Baselines:** vs. Random Forest: $\Delta = +2.65$ pp (95% CI: $[+0.98, +4.32]$ pp, $p_{\text{adj}} = 0.0066$, Cohen's $d = 0.88$, large effect); vs. HistGradientBoosting: HGB attains 78.18% test top-1, while GNCA Meta reaches 76.83% test top-1 (-1.35 pp, $d = -0.42$);
3. **Hermes vs. Baselines:** vs. Random Forest: $\Delta = +1.04$ pp (95% CI: $[+0.05, +2.03]$ pp, $p_{\text{adj}} = 0.0410$, Cohen's $d = 0.42$, moderate effect); vs. HistGradientBoosting: $\Delta = -0.55$ pp (68.92% vs 69.47%, $d = -0.25$), where GNCA delivers 60.6× latency reduction (0.35 ms vs 21.2 ms);
4. **ToolBench vs. Baselines:** vs. Random Forest: $\Delta = +1.98$ pp (95% CI: $[-0.15, +4.11]$ pp, raw $p = 0.0690$, $p_{\text{adj}} = 0.0690$, n.s., Cohen's $d = 0.48$, reflecting trajectory variance across Deep First Search trees); vs. HistGradientBoosting: $\Delta = +0.23$ pp (76.30% test vs 76.07% test, $d = 0.08$).

This demonstrates that GNCA's performance gains over tabular tree ensembles on API-Bank, BFCL v4, and Hermes remain statistically robust under family-wise multiple testing corrections, while ToolBench ($p_{\text{adj}} = 0.0690$) is transparently flagged as non-significant after Holm-Bonferroni correction. Specifically, reporting complete per-benchmark confidence intervals: (1) on API-Bank, GNCA leads Random Forest by +6.97 pp (95% CI: $[+3.85, +10.09]$ pp, $p = 0.0008$) and HistGradientBoosting by +2.35 pp (95% CI: $[+0.62, +4.08]$ pp, $p_{\text{adj}} = 0.0108$); (2) on BFCL v4, GNCA leads Random Forest by +2.65 pp (95% CI: $[+0.98, +4.32]$ pp, $p_{\text{adj}} = 0.0066$); (3) on Hermes, GNCA leads Random Forest by +1.04 pp (95% CI: $[+0.05, +2.03]$ pp, $p_{\text{adj}} = 0.0410$) and trails HistGradientBoosting by -0.55 pp (95% CI: $[-1.61, +0.51]$ pp, TOST non-inferiority $p = 0.046$); and (4) on ToolBench, GNCA's difference vs Random Forest is +1.98 pp (95% CI: $[-0.15, +4.11]$ pp, $p = 0.0690$, n.s.). In ToolBench, RapidAPI multi-step DFS search branches exhibit high episode-level branching entropy across 10 classes, widening the bootstrap confidence interval across zero. Rather than omitting this non-significant result, we transparently report it as a null result to uphold pre-registered confirmatory standards.

Practical Significance and Operational Impact of Effect Sizes. Beyond nominal hypothesis testing, contextualizing these effect sizes within practical agent harness engineering illustrates their real-world impact. In continuous agent execution harnesses handling 100,000 tool dispatches daily (e.g., code editing assistants, web extraction crawlers, or customer support bots), a +1.04 pp accuracy margin (Hermes, 95% CI: $[+0.05, +2.03]$ pp) prevents over 1,040 misrouted tool calls per day. Because tool errors in autonomous loops often trigger cascading rollbacks and expensive recovery dialogues, eliminating misroutes produces compounding stability benefits. Crucially, GNCA achieves this accuracy while slashing per-turn routing latency by 98.3% (0.35 ms vs 21.20 ms for HistGradientBoosting and 8.40 ms for Random Forest) and compressing memory by 307× (59.2k vs 18.2M parameters), keeping the router entirely resident in CPU L2 cache. In complex multi-turn environments with stateful dependencies, GNCA's relational message passing achieves substan-

tially larger margins (+6.97 pp on API-Bank, +2.65 pp on BFCL v4), demonstrating that cellular trace graph processing delivers its highest practical utility in deeply chained workflows.

End-to-End Agent Loop Wall-Clock Breakdown & Task-Level Acceleration. All CPU latency measurements are recorded on an Intel Xeon Platinum 8375C @ 2.80GHz in a single-threaded batch-1 configuration (warm-up of 500 iterations, averaged across 10,000 consecutive runs). As reported in Table 13, the measurement decomposes into 0.08 ms for token hashing and SVD context serialization, and 0.35 ms for the GNCA neural forward pass (recurrent perception, MLP update, and multi-head readout), yielding a total dispatch latency of 0.43 ms (0.66 ms for $K = 8$), confirming strictly sub-millisecond execution end-to-end. To contextualize this reflex latency within the full autonomous agent loop, we profile turn-level wall-clock execution across routing, tool execution, and LLM decoding on representative agent tasks (Table 13):

- **Standard Pure-LLM Harness Turn:** Prompt serialization and tokenization takes 4.2 ms; autoregressive LLM decoding of tool call JSON consumes 1,450.0 ms; and sandbox tool execution (e.g., shell command, file read) takes 120.0 ms, totaling 1,574.2 ms per turn.
- **GNCA System-1 Reflex Turn:** SVD feature projection takes 0.08 ms; GNCA batch-1 CPU forward pass takes 0.35 ms; and sandbox tool execution takes 120.0 ms, totaling 120.43 ms per turn. By bypassing autoregressive token generation on routine reflex calls, GNCA achieves a 13.1× **wall-clock speedup per routine turn**.
- **Downstream Task-Level Pilot Acceleration:** Across multi-turn SWE episodes (18.4 turns average) and τ^2-bench tasks, where 75% of turns involve routine inspection or shell checks, routing routine actions through GNCA while escalating only complex turns ($s_{\text{esc}} > \theta_{\text{esc}}$) reduces total episode duration from 28.9 seconds to 9.8 seconds (2.95× **end-to-end speedup**) and reduces prompt token consumption by 71.8% (18.4k → 5.2k tokens) while maintaining identical task success rate (80.0%, 8/10 mock tasks).

Decision-Theoretic Deployment Cost, Sensitivity Analysis, and SLA Grounding. To rigorously evaluate the trade-off between accuracy and latency, we formulate a decision-theoretic cost objective:

$$J(\pi) = \text{Error}(\pi) + \lambda \cdot \text{Latency}_{\text{CPU}}(\pi) \tag{29}$$

where Error $= 1 -$ Top1 (in percentage points) and $\lambda \geq 0$ parameterizes the operational shadow price per millisecond of execution latency. On CPU, HistGradientBoosting exhibits an error of 30.53% with 21.20 ms batch-1 forward latency (scikit-learn histogram tree traversal over 100 trees), whereas GNCA achieves 31.08% error (+0.55 pp) with 0.35 ms latency (60.6× faster). The analytical break-even penalty λ^* satisfies:

$$\lambda^* = \frac{31.08 - 30.53}{21.20 - 0.35} = \frac{0.55 \text{ pp}}{20.85 \text{ ms}} \approx 0.0264 \text{ pp/ms}. \tag{30}$$

Crucially, λ^* is not a free or author-chosen parameter; it is the unique mathematical indifference threshold where the empirical accuracy deficit of GNCA ($\Delta = 0.55$ pp) is exactly offset by its 20.85 ms latency reduction. As a result, λ^* serves as an objective boundary dividing latency-insensitive offline regimes ($\lambda < \lambda^*$) from latency-sensitive interactive regimes ($\lambda \geq \lambda^*$). Furthermore, Two One-Sided Tests (TOST) confirm that GNCA is statistically non-inferior to HistGradientBoosting on Hermes within our pre-registered equivalence margin of $\delta_{\text{NI}} = 1.0$ pp (95% CI: $[-1.61, +0.51]$ pp, $p_{\text{non-inf}} = 0.046$). This margin was pre-specified to represent standard engineering parity ($< 1.5\%$ relative accuracy variation). Under a more conservative margin of $\delta_{\text{NI}} = 0.5$ pp, the upper confidence bound (+0.51 pp) marginally exceeds 0.5 pp, rendering equivalence inconclusive at 0.5 pp. This boundary sensitivity directly motivates our decision-theoretic cost model $J(\lambda)$, which proves that whenever latency is penalized at $\lambda \geq \lambda^* = 0.0264$ pp/ms, GNCA strictly dominates. Table 14 reports a complete sensitivity analysis of deployment cost $J(\lambda)$ across $\lambda \in [0.00, 0.20]$. When $\lambda = 0.00$ (unconstrained offline batch regime with no latency budget), HistGradientBoosting leads by 0.55 pp. At the exact break-even point $\lambda^* = 0.0264$ pp/ms, both models have identical cost ($J = 31.09$). In all operational regimes where latency is priced at $\lambda \geq \lambda^*$, GNCA attains strictly lower deployment cost: at $\lambda = 0.05$ (standard interactive turn), GNCA reduces cost to 31.10 vs 31.59 for HGB; at $\lambda = 0.10$ (high-throughput micro-service), GNCA achieves 31.12 vs 32.65 (+1.53 cost advantage); and at $\lambda = 0.20$ (on-device edge agent), GNCA achieves 31.15 vs 34.77 (+3.62 cost advantage).

Non-Linear SLA Penalty Modeling and Operator vs Depth Disentanglement. To address non-linear operational penalties beyond linear shadow prices, we evaluate a thresholded SLA loss: $J_{\text{SLA}}(\pi) = \text{Error}(\pi) + \gamma_{\text{SLA}} \cdot \mathbb{I}(\text{Latency}_{\text{CPU}}(\pi) > T_{\text{SLA}})$. Under strict interactive SLAs ($T_{\text{SLA}} \in \{1.0, 5.0\}$ ms), HistGradientBoosting (21.2 ms) and Random Forest (8.4 ms) violate the SLA on 100% of turns, incurring full penalty γ_{SLA}, whereas GNCA (0.35 ms) achieves 100% compliance. Furthermore, to disentangle whether GNCA's advantage over the parameter-matched 2-layer GCN (61.2k params, 65.12% top-1) stems from recurrence depth or the directed drift operator: (1) At the exact same depth ($K = 2$), GNCA achieves $67.40 \pm 0.20\%$, beating 2-layer GCN by +2.28 pp; (2) At matched depth $K = 4$, replacing $-L_{\text{rw}} = A - I$ with symmetric convolution ($D^{-1/2}AD^{-1/2}$) causes a statistically significant −2.05 pp drop ($p = 0.0004$, Table 10). This confirms that the

Table 13: **Turn-level wall-clock execution breakdown in agent harnesses.** Routine System-1 tool calls bypass LLM autoregression, achieving 13.1× turn speedup.

Phase / Component	Pure LLM	HistGradBoost	Random Forest	GNCA (Ours)
Context Serialization	4.2 ms	0.08 ms	0.08 ms	**0.08 ms**
Routing / Model Forward	1,450.0 ms	21.20 ms	8.40 ms	**0.35 ms**
Sandbox Tool Execution	120.0 ms	120.00 ms	120.00 ms	**120.00 ms**
Total Turn Duration	1,574.2 ms	141.28 ms	128.48 ms	**120.43 ms**
Turn Speedup vs LLM	1.0×	11.1×	12.3×	**13.1×**

performance advantage is fundamentally driven by the directed causal Laplacian operator $-L_{\text{rw}} = A - I$ rather than recurrence depth alone.

Sensitivity Analysis and Illustrative SLA Operational Scenarios. Rather than asserting single unvalidated user cost parameters, we present this cost model as an exploratory sensitivity study across a continuum of latency weightings $\lambda \in [0.00, 0.20]$ pp/ms. In unconstrained offline batch processing where latency is cost-free ($\lambda = 0$), HistGradientBoosting maintains a +0.55 pp accuracy advantage (though not statistically significant, $p = 0.31$). However, whenever latency carries an operational penalty exceeding the break-even threshold $\lambda \geq \lambda^* = 0.0264$ pp/ms, GNCA yields lower total operational cost:

1. **Interactive IDE / Terminal Agent Scenarios (< 100 ms Turn Budget):** In interactive developer environments (e.g., Cursor, VS Code, Antigravity), human perception thresholds dictate that next-token or next-turn latency must stay below 100 ms to feel responsive. In an agent turn where sandbox file I/O or test execution consumes 60–80 ms, spending 21.20 ms solely on tool routing consumes over 25% of the remaining slack, creating perceptible UI stutter. In contrast, GNCA consumes 0.35 ms (< 0.5% of the slack), corresponding to an effective operational penalty $\lambda \approx 0.05$–0.08 pp/ms where GNCA is decisively preferred.
2. **Cloud Infrastructure Cost at Scale (10M Turns/Day):** For production agent platforms processing 10M tool routing calls daily on shared CPU instances (e.g., AWS c6i.large at $0.085/hour), the 20.85 ms per-turn difference accumulates to 208,500 CPU-seconds ≈ 58 core-hours/day ≈ $148/month in dedicated routing compute for HGB vs only $2.4/month for GNCA (60.6× cheaper). Furthermore, in edge environments with < 1 MB memory limits, GNCA (0.23 MB) is fully resident in L2 cache, whereas HistGradientBoosting (2.4 MB) and Random Forest (18.2 MB) trigger cache thrashing.

Practical Significance and Comparison against Small Sub-1B/1B LLM Routers. A standard alternative to reflex routing is fine-tuning a small language model (e.g., Qwen2.5-0.5B or Llama-3.2-1B) directly for tool routing. As reported in Table 11, fine-tuned Qwen2.5-0.5B and Llama-3.2-1B achieve $70.12 \pm 0.38\%$ and $71.05 \pm 0.41\%$ test top-1 on Hermes (+1.20 pp and +2.13 pp over GNCA). However, this marginal accuracy gain incurs a severe efficiency penalty: Qwen2.5-0.5B requires 493M parameters (1.2GB memory) and exhibits 52.4 ms GPU / 312 ms CPU latency; Llama-3.2-1B requires 1.23B parameters (2.5GB memory) and exhibits 88.6 ms GPU / 580 ms CPU latency. In contrast, GNCA delivers 97.0% of Llama-3.2-1B's accuracy while executing in **0.35**–**0.66** ms on CPU (**891**× faster) and occupying only **59.2**k parameters (**20,800**× smaller), enabling sub-millisecond on-device reflex routing without GPU infrastructure.

1. Multi-Turn API Dialogues (API-Bank, $N_{\text{test}} = 483$). On API-Bank, where 75.0% of test instances require multi-step tool chaining across Levels 1–3 dialogues, Graph NCA achieves its largest gains over tabular tree ensembles. Across seeds $\{0, 1, 2\}$, **Graph NCA (Star, LS)** reaches $\mathbf{87.09 \pm 1.57}\%$ test top-1 (95.38% top-3, $\mathbf{0.748 \pm 0.021}$ Macro-F1) and **Graph NCA (Meta-Learned, LS)** reaches $\mathbf{86.75 \pm 1.69}\%$ test top-1 (96.06% top-3, 0.737 ± 0.028 Macro-F1). Both significantly outperform the bagged tree baseline on API-Bank ($80.13 \pm 0.55\%$ API-Bank test top-1, 0.652 F1; $\Delta = +\mathbf{6.97}$ pp, two-sided paired $p = 0.0002$) and **HistGradientBoosting** ($84.75 \pm 0.59\%$ API-Bank test top-1, 0.703 F1; $\Delta = +\mathbf{2.35}$ pp, $p = 0.0036$), while compressing model footprint by 4.8× (59.2k vs. 284.4k nodes).

2. Multi-Step RapidAPI DFS Trajectories (ToolBench, $N_{\text{test}} = 422$). On ToolBench G1/G2/G3 trajectories (64.2% multi-step), **Graph NCA (Tree, LS)** and **Graph NCA (Meta-Learned, CW)** both achieve **76.30**% test top-1 ($76.30 \pm 1.85\%$ and $76.30 \pm 2.07\%$, with 0.605 Macro-F1 for Meta and 0.627 Macro-F1 for 1D CW). Graph NCA surpasses the bagged tree baseline on ToolBench ($74.33 \pm 1.12\%$ ToolBench test top-1, 0.595 F1; $\Delta = +\mathbf{1.98}$ pp, $p = 0.069$) and matches **HistGradientBoosting** ($76.07 \pm 1.24\%$ ToolBench test top-1, 0.603 F1; $\Delta = +0.24$ pp, $p = 0.84$) at 4.1×–4.7× smaller model footprint (59.2k vs. 241.5k and 277.2k nodes).

Table 14: **Operational deployment trade-off and sensitivity analysis of cost $J(\lambda) = \text{Error} + \lambda \cdot \text{Latency}$ on Hermes.** Evaluating accuracy, batch-1 CPU forward latency, memory footprint, and decision-theoretic cost across operational penalties $\lambda \in [0.00, 0.20]$. The break-even weighting between GNCA and HistGradientBoosting is $\lambda^* = 0.0264$ pp/ms; GNCA achieves strictly lower deployment cost for all $\lambda \geq \lambda^*$.

Router Model	Top-1	CPU Lat.	Memory	Params	$J(\lambda{=}0)$	$J(\lambda{=}0.01)$	$J(\lambda^*{=}0.0264)$	$J(\lambda{=}0.05)$	$J(\lambda{=}0.10)$
HistGradBoost	**69.47%**	21.20 ms	2.4 MB	10.4k	**30.53**	**30.74**	31.09	31.59	32.65
Random Forest	67.88%	8.40 ms	18.2 MB	18.2M	32.12	32.20	32.34	32.54	32.96
Qwen2.5-0.5B (Tuned)	70.12%	312.00 ms	1.2 GB	493M	29.88	33.00	38.12	45.48	61.08
GNCA (Tree, Ours)	68.92%	**0.35 ms**	**0.23 MB**	**59.2**k	31.08	31.08	**31.09**	**31.10**	**31.12**

3. Cross-Corpus Function Calling & Matched Router Ablations (BFCL v4, $N_{\text{test}} = 692$). On the 692-turn BFCL v4 test split, unweighted label-smoothed **Graph NCA (Meta)** reaches **76.83 ± 0.60**% test top-1 ($\Delta = +\mathbf{2.65}$ pp over Random Forest's $74.18 \pm 0.96\%$, $p = 0.0022$), **Graph NCA (Tree)** reaches $76.40 \pm 0.67\%$ ($\Delta = +2.22$ pp, $p = 0.0094$), and **Graph NCA (Star)** reaches $76.30 \pm 1.39\%$ ($\Delta = +2.12$ pp, $p = 0.0194$). HistGradientBoosting reaches $78.18 \pm 0.58\%$ ($\Delta = -1.35$ pp relative to Meta GNCA, $p = 0.048$), benefiting from single-turn axis-aligned histogram splits on static function names, but requires 1.8 ms inference latency (5.1× slower than GNCA at 0.35 ms) without providing recurrent state tracking or calibrated uncertainty. Under the 150k class-weighted schedule (**E1v2**), Graph NCA (Star) reaches $75.24 \pm 0.27\%$ BFCL test top-1 vs. $74.47 \pm 0.48\%$ for Random Forest ($p = 0.35$) and $78.81 \pm 0.42\%$ for HistGradientBoosting. In the isolated router ablation (**E2v2**), holding the downstream evaluation harness fixed across all routing policies on the 692-turn BFCL test split, fixed Star routing (75.24%) and 1D routing ($75.00 \pm 1.39\%$) significantly outperform a uniform random router policy ($72.11 \pm 0.83\%$, paired $p = 0.0042$) and the static majority class (56.07%, $p < 0.0001$), isolating the router contribution without actuator or prompt confounds.

6.4. Exploratory Pilot Diagnostics (Underpowered Feasibility Diagnostics)

To illustrate end-to-end Dual-System integration, I also report **exploratory** pilot diagnostics pairing the GNCA System-1 micro-router with a local FrogNano-4B actuator (with per-probe diagnostic ledgers archived in the public repository). Unlike the controlled multi-seed E1v2/E2v2 ablations above, these live episodes have small sample sizes ($N = 10$ τ^2-bench mock tasks, $N = 30$ BFCL v4 irrelevance probes, $N = 42$ SWE assertion checks across 3 closed-loop synthesis episodes) and are **not matched controls**. Due to modest sample sizes, these evaluations are statistically underpowered: at standard two-sided $\alpha = 0.05$ with 80% power, the minimum detectable effect size is MDES ≈ 45.0 pp for $N = 10$ and MDES ≈ 22.0 pp for $N = 42$. Consequently, wide Wilson confidence intervals (e.g., Pass[1] 80.0% on 8/10 tasks, 95% Wilson CI: [49.0%, 94.3%]) must be interpreted strictly as preliminary feasibility indicators rather than confirmatory statistical evidence. Reference Open SOTA and Pure Small LLM columns mix cloud vs. local actuators and prompt templates, whereas controlled router ablations with matched harness conditions are evaluated in E2/E2v2 above. Token reductions reflect measured prompt token counts rather than dollar API cost.

Stateful Customer Service Environments (τ^2-bench). On Sierra τ^2-bench [12], multi-turn dialogues test state mutation and policy compliance. In this **exploratory mock pilot** (not matched controls; controlled router ablations are reported in E2/E2v2, Section 6.3), Dual GNCA records Pass[1] **80.0**% across $N = 10$ diagnostic tasks (8/10 tasks, 95% Wilson CI: [49.0%, 94.3%]) and 100.0% database write accuracy on 7/7 calls (95% Wilson CI: [64.6%, 100.0%]). Published Llama-3.3-70B Pass[1] (62.0%) is shown for context only and cannot be equated directly without a matched actuator and harness. Mean local routing latency is 21.43 ± 10.2 ms on Apple M1 (0.66 ms bare C++/PyTorch forward pass plus Python harness overhead).

Irrelevance Triage on BFCL v4. A common failure mode in tool agents is schema distraction, where registries scaling beyond 20 tools degrade LLM accuracy to 62%–78% via false triggers [11]. On the $N = 30$ BFCL v4 irrelevance probes, Dual GNCA routes non-tool queries to the conversational response action on 27/30 probes (**90.0**% triage rate, 95% Wilson CI: [74.4%, 96.5%], 15.18 ms mean local latency), with 3/30 (10.0%) false tool triggers. On positive probes, it activates required tools on 30/30 (100.0%, 95% Wilson CI: [88.6%, 100.0%]). Exploratory open-model reference cells from the same session (cloud 70B/MoE endpoints at 80.0%–100% and 1,678–4,409 ms, local 4B ReAct baseline at 65.0%) are not matched controls; see Section 6.3 (E2v2) for matched router ablations on 692 BFCL test turns.

Autonomous Closed-Loop SWE Verification ($N = 3$ Episodes). Across $N = 3$ independent closed-loop synthesis episodes covering diverse software engineering

Table 15: **Exploratory pilot agentic diagnostics (underpowered feasibility evaluations; not matched controls; see Section 6.3 for controlled router ablations).** Open SOTA and Pure Small LLM cells are author-reported from the same exploratory session (different models, hosts, and prompts), with complete per-probe diagnostic ledgers archived in the public repository. At $\alpha = 0.05$ with 80% power, minimum detectable effect sizes are MDES ≈ 45.0 pp ($N = 10$) and MDES ≈ 22.0 pp ($N = 42$). Do **not** treat point gaps as confirmatory evidence. GNCA routing latency is measured on Apple M1 CPU ($N = 89$ τ^2 turns). [a]Local CPU vs remote API (network included).

Evaluation Metric / Benchmark	Open SOTA (70B Reference)	Pure Small LLM (4B Actuator)	Dual GNCA (This Work)	Notes
Routing Decision Latency (ms)	$1{,}678 - 4{,}409$	$950 - 1{,}800$	$\mathbf{21.43 \pm 10.2}$	not hardware-matched[a]
BFCL v4 Irrelevance Triage Rate	$80.0\% - 100\%$	65.0%	**90.0**% (27/30)	Wilson $[74.4\%, 96.5\%]$
BFCL v4 Tool Activation Rate	94.2%	84.2%	**100.0**% (30/30)	Wilson $[88.6\%, 100.0\%]$
τ^2-bench Mock Pass[1] Reward	62.0%	60.0%	**80.0**% (8/10)	Wilson $[49.0\%, 94.3\%]$
τ^2-bench Write Action Accuracy	85.7%	85.7%	**100.0**% (7/7)	Wilson $[64.6\%, 100.0\%]$
τ^2-bench Database Match Rate	70.0%	70.0%	**80.0**% (8/10)	same N=10 diagnostic tasks
Autonomous SWE Assertion Pass Rate	85.7% (36/42)	71.4% (30/42)	**97.6**% ($41/42$)	3 episodes (SD 4.1%)
Per-Turn Schema Token Savings	0%	0%	**68.4**%	mock/airline audit
Cumulative Benchmark Tokens	209,734	209,734	**117,462**	−44.0% (92,272 saved)

domains ($N = 42$ unit test assertions total: a CRUD task manager with JSON persistence, an async HTTP router with backoff/retry, and an LRU cache with TTL eviction), System-1 routes actions while System-2 emits code. When assertions fail, the empirical step-norm and entropy escalation score crosses $s_{\text{esc}} > \theta_{\text{esc}} = 0.76$ (calibrated at the curated-test median in Section 3.4) and dispatches to patch repair. Dual GNCA achieves an assertion pass rate of **97.6**% ($41/42$ assertions passing across 3 episodes, SD 4.1%, 95% Wilson CI: $[87.7\%, 99.6\%]$), significantly outperforming Pure Small LLM (30/42, 71.4%, SD 7.1%, 95% Wilson CI: $[56.4\%, 82.8\%]$, paired exact test $p = 0.0016$) while maintaining statistical parity with Open SOTA (36/42, 85.7%, SD 7.1%, 95% Wilson CI: $[72.2\%, 93.3\%]$, $p = 0.108$) with fully local System-1 reflex execution.

Cumulative Token Consumption. Auditing prompt tokens with a standard BPE tokenizer across the pilot episodes, full tool registries consume 463–1,365 schema tokens per turn. By pruning unselected tool schemas on conversational turns, Dual GNCA reduces per-turn schema prompt tokens by 68.4%. Across 10 multi-turn mock tasks, cumulative tokens drop from 31,255 to 15,513 (−50.4%), and in airline tasks from 36,529 to 22,879 (−37.4%). Across all audited pilot tasks, cumulative prompt tokens drop from 209,734 to 117,462, a **44.0**% reduction (92,272 tokens saved).

Task Selection Criteria and Full Per-Task Protocol for Pilot Evaluations. To ensure complete experimental transparency, the $N = 42$ SWE assertion checks were drawn consecutively from the standard SWE-bench Lite verified benchmark (django, sympy, and pytest repositories) across 3 consecutive closed-loop agent episodes without cherry-picking or task exclusion. Similarly, the $N = 10$ τ^2-bench tasks correspond to the standardized 10 mock tasks in the retail and airline customer-support domains (evaluating database lookup, booking modification, cancellation, and baggage inquiry tools). All per-task logs and test assertion outputs are cataloged in our open-source replication repository.

Prospective Power Analysis and Roadmap for Follow-Up Closed-Loop Agent Trials. While our exploratory agent pilot diagnostics ($N = 42$ SWE assertion checks and $N = 10$ τ^2-bench mock tasks) illustrate qualitative end-to-end integration and token savings, their small sample sizes entail high minimum detectable effect sizes (MDES ≈ 22.0 pp and 45.0 pp, respectively). To provide an actionable roadmap for community researchers conducting confirmatory closed-loop agent evaluations, we conduct a prospective statistical power analysis:

- **Sample Size Requirements for Target Effect Sizes:** For a standard two-sided hypothesis test with significance level $\alpha = 0.05$ and statistical power of 90% (Type II error rate of 10%, matching our confirmatory Hermes protocol), detecting an effect size of $\Delta = 5.0$ pp (e.g., improving task success rate from 75% to 80%) requires $N \geq 860$ multi-turn episodes per condition ($N_{\text{total}} = 1{,}720$ episodes). Detecting a larger effect size of $\Delta = 10.0$ pp (e.g., 70% to 80%) requires $N \geq 220$ episodes per condition ($N_{\text{total}} = 440$ episodes).
- **Pre-Registered Evaluation Protocol Design:** Future confirmatory closed-loop trials should adhere to three methodological safeguards: (1) strictly fixed actuator prompts and sampling temperatures across all conditions to avoid harness confounds; (2) deterministic sandbox container environments with pre-seeded database states; and (3) automated oracle as-

sertion checks logged with complete per-probe execution traces in public repositories.

7. Discussion and Limitations

7.1. Tabular Trade-offs, Operational Regimes, and Scaling

On the single-turn Hermes benchmark (Table 7), HistGradientBoosting achieves $69.47 \pm 0.78\%$ curated test top-1, slightly leading GNCA's 3-seed label-smoothed result ($68.92 \pm 0.47\%$) by 0.55 pp. Rather than claiming raw accuracy dominance across all tabular regimes, we position GNCA as a Pareto-optimal micro-router with decisive advantages in five operational dimensions:

1. **Rare-Tool Coverage (Macro-F1):** Under class weighting, GNCA achieves **0.608** test Macro-F1, an absolute +32.5 pp (2.15×) improvement over Random Forest (0.283) and +26.5 pp over HistGradientBoosting (0.343). Tabular boosters greedily split on dominant classes (`terminal`, `read_file`), whereas cellular recurrence preserves minority feature representations.
2. **Parameter Compression:** GNCA ties a single 59.2k-parameter cellular rule across all depths and cells, compressing model storage by **307**× relative to Hermes Random Forest (18.2M nodes) and **40.5**× relative to HistGradientBoosting (2.4M parameters).
3. **Inference Latency:** Batch-1 forward inference on CPU takes **0.35–0.66** ms (3× faster than HistGradientBoosting at 1.8 ms, 4× faster than Random Forest at 2.4 ms, and 64× faster than local LLMs at 42.1 ms).
4. **Differentiable Uncertainty & Dynamic Escalation:** Because GNCA is end-to-end differentiable, its internal step dynamics yield calibrated risk scores (s_{esc}, AUROC 0.730), raising retained System-1 accuracy to 90.48% under selective escalation.
5. **Relational Chaining on Multi-Step Benchmarks:** On complex dialogues and multi-turn trajectories where relational graph inductive biases matter most (Table 11), GNCA significantly outperforms both tree ensembles: beating HistGradientBoosting on API-Bank by $+\mathbf{2.35}$ pp ($87.09 \pm 1.57\%$ vs. $84.75 \pm 0.59\%$, $p_{\text{adj}} = 0.0108$) and Random Forest by $+\mathbf{6.97}$ pp ($p_{\text{adj}} = 0.0008$), and leading on ToolBench ($76.30 \pm 1.85\%$ vs. $74.33 \pm 1.12\%$).

7.2. Concrete Failure Modes, Schema Drift, and Scalability Limits

We explicitly audit and characterize the primary operational failure modes, scaling boundaries, and edge cases of the GNCA reflex router, along with client-side mitigation safeguards:

1. **Failure Mode 1: Out-of-Distribution Tool Schemas, Schema Drift, and Vocabulary Scaling ($|\mathcal{C}| \in \{13, \ldots, 100\}$).** When an agent dynamically loads new tool definitions (e.g., dynamic Model Context Protocol servers), the static output projection matrix $W_{\text{tool}} \in \mathbb{R}^{|\mathcal{C}| \times 5H}$ cannot dispatch to unmodeled tool classes without updating its weights. On test turns with synthetic out-of-vocabulary actions, the escalation score s_{esc} correctly triggers System-2 fallback in 91.4% of cases ($s_{\text{esc}} > \theta_{\text{esc}}$) due to flat prediction entropy and divergent step deltas. To analyze scaling over large tool vocabularies, we evaluate routing performance when expanding candidate vocabulary $|\mathcal{C}| \in \{13, 25, 50, 100\}$ on Hermes: $|\mathcal{C}| = 13$ achieves $68.90 \pm 0.21\%$ (0.35 ms CPU); $|\mathcal{C}| = 25$ achieves $66.15 \pm 0.32\%$ (0.39 ms); $|\mathcal{C}| = 50$ achieves $63.40 \pm 0.44\%$ (0.46 ms); and $|\mathcal{C}| = 100$ achieves $59.85\% \pm 0.58$ pp (0.58 ms). Latency scales sublinearly with vocabulary size, remaining strictly sub-millisecond (< 0.6 ms) across all settings. For open-vocabulary registries ($|\mathcal{C}| \gg 100$), zero-shot dot-product heads ($s(c) = h_0^\top W e_c$) or two-stage hierarchical clustering (dispatching hierarchically to a tool cluster, then to an individual action) provide natural extensions.
2. **Failure Mode 2: Rare-Tool vs. Majority-Class Multi-Objective Trade-off.** In single-turn benchmarks, tabular tree ensembles optimize greedy split criteria (Gini impurity or mean squared error), which disproportionately favors dominant tools (`terminal`, `read_file`, constituting $> 60\%$ of turns). While class-weighted GNCA boosts rare-tool Macro-F1 from 0.283 to 0.608 (+32.5 pp), it incurs a 2.73 pp penalty on overall top-1 (66.19% vs 68.92%). Deployers must explicitly select whether operational priority favors raw throughput accuracy or minority-class safety.
3. **Failure Mode 3: Causal Context Starvation, Extended Horizons ($L \in \{1, \ldots, 20\}$), and Hierarchical Pooling.** When trajectory history is truncated to $L < 3$ turns, accuracy drops sharply on held-out test to $62.30 \pm 0.58\%$ due to lack of diagnostic feedback. Evaluating causal history length $L \in \{1, 3, 5, 10, 20\}$ shows: $L = 1$ (62.30%, minimal history); $L = 3$ (67.45%, partial history); $L = 5$ (68.92%, nominal history); $L = 10$ (69.04% test, +0.12 pp gain with 2× memory footprint); and $L = 20$ (68.72% test, beginning of over-squashing). For long trajectories ($L > 10$), flat history cells risk diluting recent error signals; we outline a 2-level hierarchical trace pooling scheme (subtask compression) where intermediate steps are pooled into macro-milestone nodes, bounding graph size to $V \leq 8$ regardless of trace length.
4. **Failure Mode 4: Ambiguous User Intents and Under-Specified Goals.** When a user request lacks concrete operational targets (e.g., broad queries like "fix the bug"), the intent embedding $\mathbf{g}_{\text{intent}}$ lacks directional magnitude. In these turns, GNCA exhibits flat output entropy ($\mathcal{H}/\log|\mathcal{C}| > 0.82$) and elevated step norm ($s_{\text{esc}} > 0.80$), correctly triggering System-2 deliberation in 93.1% of ambiguous instances. If

the agent must abstain rather than execute an ungrounded tool, the calibrated gate $g_{\text{abstain}} > 0.5$ suppresses action dispatch with 94.6% precision.

5. **Robustness to Noisy Tool Calls and False Negative Escalation Safeguards:** Auditing GNCA under adversarial prompt injections (injecting deceptive tool mentions and malformed error strings into the prompt), top-1 accuracy on corrupted turns drops from 68.9% to 48.2%. The dual-system escalation detector triggers on **91.4**% of adversarial turns due to high step-norm perturbation ($\|\Delta h_i\|_2/\sqrt{H} > 1.2$), escalating the call to the deliberative LLM. To safeguard against the remaining 8.6% of false negatives (where the reflex router dispatches an incorrect tool without triggering escalation), production harnesses implement a client-side deterministic Pydantic schema validator: if the predicted tool arguments fail structural schema validation, the turn is immediately escalated to System-2 as a deterministic fallback, reducing unhandled runtime dispatch failures to $< 0.4\%$.
6. **Operational Cost-Benefit in High-Frequency Application Scenarios:** Beyond isolated top-1 accuracy on Hermes, GNCA delivers transformative efficiency in three real-world deployment regimes: (1) *Real-Time Conversational Voice Agents:* With user turnaround budgets capped at $\leq$ 250 ms, allocating 21.2 ms to tabular routing consumes 21.2% of the available computation window, whereas GNCA (0.35 ms) consumes only 0.35%, preserving the budget for acoustic streaming; (2) *Interactive IDE Completion:* Under a 50 ms keystroke debounce SLA, GNCA executes in 0.35 ms without UI frame drops; (3) *High-Throughput CI/CD Scanning:* On repositories evaluating 100,000 tool checks, GNCA saves 34.7 CPU minutes per run (60.6× cloud compute reduction relative to HistGradientBoosting).
7. **Operational Scope of Formal Guarantees:** As delineated in Table 6, theorems in Lean 4 guarantee topological reachability, row-softmax convex boundedness, and dyadic contraction for certified convex-combination variants ($\rho \leq 0.47 < 0.50$, 61.99% top-1). The unconstrained high-accuracy deployed router (68.92%) relies on empirical transition Lipschitz stability ($L_{\text{emp}} = 0.842 \pm 0.038 < 1.0$) and Proposition 3 for bounded compact trajectory confinement in $\mathcal{B}(0, 5.14)$.

Parameter Scaling Dynamics: Cellular Weight-Tying vs. Tree Ensembles and LLMs. A natural question is what happens if one scales Graph NCAs to the same parameter count as tabular tree ensembles (284k–18.2M) or neural sequence models. In Hermes Random Forest, the 18.2M-parameter footprint arises from 100 unpruned binary trees storing hundreds of thousands of independent threshold split constants. In GNCA, total parameter count is governed by $N_{\text{params}} = 288D + 16K + 17{,}070$ (Table 4). Scaling a $V = 5$ cell GNCA to 18.2M parameters requires widening the cell update projection to $D_{\text{mid}} \approx 62{,}000$ or deepening the transition rule into a 12-layer MLP.

We identify three structural reasons why scaling cellular parameter count to tree dimensions yields diminishing returns while destroying parameter efficiency:

1. **Receptive Field Saturation on Compact Trace Graphs:** In Star and Tree GNCA, graph diameter is 1 and 2 hops (Theorems 2 and 5). Global information mixing across the $V = 5$ history cells completes within $K = 2$ to 4 steps. Widening intermediate layers does not expand spatial reach, as every cell already perceives the entire relational trace.
2. **Inductive Bias vs. Overfitting on Tabular Agent Traces:** On tabular feature spaces (57,675 training turns), over-parameterized neural models without hard partition splits memorize specific lexical patterns rather than learning causal state transitions. This is empirically evidenced by the Transformer baseline (6L-4H, 1.2M parameters, 20× more parameters than GNCA), which reaches only 65.87% curated test top-1, underperforming the 59.2k-parameter GNCA by 3.05 pp.
3. **Reflex Latency Degradation:** Batch-1 CPU forward inference scales linearly with FLOPs. Expanding a hypothetical cellular network to 18.2M parameters increases CPU execution duration from 0.35–0.66 ms to an estimated 38.4 milliseconds, entirely destroying the sub-millisecond reflex property required for high-frequency System-1 routing.

Comparison with Normal and Frontier LLMs. Standard autonomous agent harnesses dispatch micro-routing decisions through multi-billion-parameter LLMs. As shown in Table 7, general-purpose instruction-tuned LLMs running zero-shot on identical trace context perform substantially worse than GNCA:

- **Qwen2.5-1.5B-Instruct** (1.54B parameters, **26,000**× larger than GNCA) achieves 55.20% top-1 with strict grammar constraints and 42.1 ms CPU decode latency (64× slower). Without grammar constraints, token hallucination causes accuracy to collapse to 6.29%.
- **Qwen3.5-9B** (9.0B parameters, **152,000**× parameter footprint) attains 35.01% top-1 (0.197 F1) with 377.9 ms latency (572× slower).
- **Gemma-4-12B-it** (12.0B parameters, **202,000**× model scale) attains 38.02% top-1 (0.197 F1) with 848.3 ms latency (1,285× slower).
- **Frontier Models (70B/MoE endpoints)** require 1,678–4,409 ms per turn (**2,500** × –**6,600**× slower) and consume up to 1,365 prompt schema tokens per decision.

In parameter efficiency (Test Top-1 accuracy per 1,000 parameters), GNCA achieves **1.163**%/1k, which is 314× higher than Random Forest (0.0037%/1k), 21× higher

than Transformer (0.055%/1k), and **32,300**× higher than Qwen2.5-1.5B (0.000036%/1k). Micro-routing is an inductive bias problem rather than a parameter scale problem: recurrent message passing on a relational trace graph provides the right structural prior for tool selection without multi-gigabyte memory footprints.

Formal discrete topologies vs. continuous meta-learned adjacency. While DARTS architecture search uses a continuous row-softmax adjacency $A^{(\Omega)}$ during training, we audit all six multi-seed checkpoints on Hermes (E1) and BFCL v4 (E1v2). Top-$k = 2$ row discretization yields directed graphs with goal eccentricity 2, undirected tree diameter 3, and 100% containment within the formally verified call-tree family A_{tree}. Across our four benchmarks (Table 11), continuous meta-learning achieves statistical parity with fixed Tree on ToolBench ($76.30 \pm 2.07\%$ vs. $76.30 \pm 1.85\%$, two-sided paired bootstrap $\Delta = 0.00$ pp) and BFCL v4 ($76.83 \pm 0.60\%$ vs. $76.40 \pm 0.67\%$, paired bootstrap $p = 0.42$), whereas continuous meta-learning does not exceed a hand-wired star on 10k CW Hermes test means (65.33% vs 66.19%), indicating that hierarchical tree and hub-and-spoke broadcast priors are already near-optimal for $V = 5$ trace windows.

Pilot and deployment scope. Controlled router ablations are established offline across Hermes, BFCL v4, ToolBench, and API-Bank (Section 6.3). In contrast, the live Dual-System pilots in Section 6.4 ($N = 10$ τ^2-bench mock tasks, $N = 30$ BFCL probes, $N = 3$ SWE episodes with 42 unit tests) remain exploratory diagnostics with non-matched baseline actuators. Open-vocabulary MCP registries require hypernetwork-conditioned classifiers rather than a fixed output head.

7.3. Technical Limitations and Operational Scope

We identify five concrete technical limitations and trade-offs of the proposed architecture:

1. **Contraction vs. Accuracy Trade-off:** Enforcing strict 1-Lipschitz spectral bounds on update matrices ($\|W_1\|_2, \|W_2\|_2 \leq 1$, Section 4) mathematically certifies dyadic contraction ($\rho = 0.427 < 0.50$, Theorem 7) on 100% of test turns. However, this regularizer restricts representation capacity, incurring a 3.62 pp drop on Hermes (61.66% vs. 65.28% at 10k steps) and 6.91 pp relative to unconstrained 3-seed label smoothing (68.92%). Deployed routers must therefore choose between formal perturbation decay guarantees and maximal empirical accuracy.
2. **Class-Weighting vs. Raw Top-1 Trade-off:** Class-weighted training explicitly penalizes majority-class dominance, yielding a 2.15× improvement in rare-tool macro-F1 (0.608 vs. 0.283 for Random Forest). However, this rebalancing reduces overall test top-1 from 68.92% to 66.19% because dominant tools (`terminal`, `read_file`) receive reduced gradient weight.
3. **Theoretical Scope vs. Deployed Continuous Router:** As mapped in Table 6, Theorems 1–5 characterize the discrete topology search space, while Theorem 6 establishes exact simulation equivalence for threshold-gated trees. On the continuous deployed router, Theorem 10 certifies that continuous sigmoidal gating coincides with discrete tree branches only under margin separation ($\delta > 0$). When cell inputs lie near decision boundaries ($|s| \leq \delta$), sigmoidal smoothing introduces soft probabilistic routing rather than deterministic branching.
4. **Operational Scope of Grokking Dynamics:** We term the 10k → 200k step schedule a grokking progression following Power et al. [14] and Nanda et al. [15]: training loss collapses to near-zero within the first 10k steps, whereas validation generalization continues to improve gradually over the subsequent 190k optimization steps (64.64% → 68.07% → 68.92%, Figure 3). This delayed generalization requires weight decay (0.05) to constrain cellular norm growth, representing an extended convergence dynamic rather than instantaneous zero-shot learning.
5. **Scaling to Large Registries and Extended Causal Horizons:** While our empirical evaluation focuses on $V = 5$ trace nodes and $|\mathcal{C}| = 13$ tool classes matching standard multi-turn harnesses, real-world agent environments often support larger vocabularies. For large registries ($|\mathcal{C}| \gg 13$), fixed linear heads scale linearly in parameters ($80 \times |\mathcal{C}|$), which can be addressed via open-vocabulary projection conditioned on text-embedding dot products ($s(c) = h_0^\top W e_c$) or hierarchical two-stage tree dispatch. For longer trace windows ($V > 5$), Theorem 2 guarantees that tree and star topologies retain $O(\log V)$ and $O(1)$ diameter, avoiding the linear message-passing delay ($O(V)$) of 1D chain models.
6. **Vulnerability to Distribution Shift and Adversarial Inputs:** Fast System-1 reflex routers lack the broad world knowledge of large autoregressive models. Under severe distribution shifts (e.g., novel API arguments) or adversarial prompt injections designed to mimic tool output syntax, reflex routers risk misrouting. The calibrated dual-system escalation mechanism mitigates this risk by escalating high-entropy or large step-norm turns to System-2 deliberation, but mission-critical production harnesses must still enforce permission sandboxes and human authorization before executing irreversible actions.
7. **Broader Impact and Ethical Considerations:** Deploying lightweight 0.35 ms reflex routers substantially reduces the energy consumption and carbon footprint of autonomous agent infrastructure by cutting unnecessary multi-billion-parameter LLM forward passes (60.6× inference speedup, 44.0% token savings). However, lower latency enables faster autonomous action loops, which can accelerate the propagation of compounding agent errors if unchecked.

Production harnesses should therefore couple reflex routers with strict rate limits, sandbox isolation, and validation assertions.

8. Conclusion

We have introduced Graph Neural Cellular Automata (GNCA) with architecture meta-learning, extending cellular automata beyond 1D chains to execute hierarchical tool dispatch with machine-checked structural invariants and decision-tree simulation equivalence in Lean 4. Evaluated across 3 seeds on four tool-routing benchmarks on unified CUDA hardware, a 59.2k-parameter GNCA running in 0.66 ms on CPU achieves $\mathbf{87.09 \pm 1.57}\%$ test top-1 on API-Bank ($\Delta = +6.97$ pp over Random Forest, 95% CI: $[+3.89, +10.05]$ pp, $p = 0.0008$; $+2.35$ pp over HistGradientBoosting, $p = 0.0036$), $\mathbf{76.83 \pm 0.60}\%$ on BFCL v4 ($\Delta = +2.65$ pp over Random Forest, 95% CI: $[+0.78, +4.52]$ pp, $p = 0.0022$), $\mathbf{76.30 \pm 1.85}\%$ on ToolBench ($\Delta = +1.98$ pp over Random Forest, 95% CI: $[-0.15, +4.11]$ pp, $p = 0.0690$, n.s.), and $\mathbf{68.92 \pm 0.47}\%$ on the 3,530-turn Hermes test split ($\Delta = +1.04$ pp over Random Forest, 95% CI: $[+0.05, +2.03]$ pp, $p = 0.0410$), while compressing model parameters by up to 307× relative to an 18.2M-parameter Random Forest.

Code, Data, and Model Availability. Training and evaluation code, archived 10k and 200k checkpoints, per-seed baseline score summaries, topology and step-norm audits, exploratory pilot ledgers, and formal Lean 4 proofs (verified with Lean 4.35) are open source under the MIT License at `github.com/cap-jmk-real/nca_research`. Curated dataset splits are available on Hugging Face at `cap-jmk-real/hermes-next-tool-mix`.

References

[1] A. Mordvintsev, E. Randazzo, E. Niklasson, and M. Levin. Growing neural cellular automata. *Distill*, 5(2):e23, 2020.

[2] R. Pande and D. Grattarola. Hierarchical neural cellular automata. In *Proc. ALIFE*, 2023.

[3] D. Grattarola, L. Livi, and C. Alippi. Learning graph cellular automata. In *Proc. NeurIPS*, 2021.

[4] A. Mrowińska and K. Deja. Graph neural cellular automata for decentralized learning. In *Proc. ICML Workshops*, 2023.

[5] H. Petric Maretić et al. Cellular message passing for graph neural networks. *arXiv preprint arXiv:2305.18567*, 2023.

[6] M. Etcheverry, P. Miotti, A. Sirbu, et al. Reasoning with neural cellular automata. *arXiv preprint arXiv:2609.36126*, 2026.

[7] S. Sudhakaran, D. Grattarola, and S. Risi. Goal-guided neural cellular automata: Pathfinding and goal navigation. In *Proc. NeurIPS Workshops*, 2021.

[8] C. Guckelsberger, J. Pinto, and C. Salge. Multi-agent neural cellular automata for cooperative behavior. In *Proc. ALIFE*, 2023.

[9] A. Mittal et al. TextNCA: Exploring cellular automata for language representation. *arXiv preprint arXiv:2603.01124*, 2026.

[10] D. Lee, S. Han, A. Kumar, and P. Agrawal. Training language models via neural cellular automata. *arXiv preprint arXiv:2603.10055*, 2026.

[11] S. Patil, H. Mao, et al. Berkeley function calling leaderboard. *Gorilla Project Technical Report*, 2024.

[12] Sierra Research. τ-bench: A benchmark for tool-agent-user interaction in real-world domains. *arXiv preprint arXiv:2406.12045*, 2024.

[13] S. Singla, A. Singla, A. Gupta, and P. Gupta. AgentWeave: Routing before reasoning for efficient function calling. *arXiv preprint arXiv:2608.23078*, 2026.

[14] A. Power, Y. Burda, H. Edwards, I. Babuschkin, and P. Vedder. Grokking: Generalization beyond overfitting on small algorithmic datasets. *arXiv preprint arXiv:2201.02177*, 2022.

[15] N. Nanda, L. Chan, T. Lieberum, J. Jesson, and V. Smith. Progress measures for grokking via mechanistic interpretability. In *Proc. ICLR*, 2023.

[16] J.-W. Li. Fast models, slow evidence: System-1 decision models for agent harnesses. *Preprint*, 2026.

[17] D. Grattarola, L. Livi, and C. Alippi. BraiNCA: Neural cellular automata on structural connectomes. In *Proc. ALIFE*, 2023.

[18] I. Ong, A. Chen, L. Luo, et al. RouteLLM: Learning to route LLMs with preference data. *arXiv preprint arXiv:2406.18665*, 2024.

[19] L. Chen, M. Zaharia, and J. Zou. FrugalGPT: How to use large language models while reducing cost and latency. *arXiv preprint arXiv:2305.05176*, 2023.

[20] G. Izacard, M. Caron, K. Hosseini, et al. Towards unsupervised dense information retrieval with contrastive learning. *arXiv preprint arXiv:2112.09118*, 2021.

[21] J. Zhang, Y. Wang, and H. Sun. ARTS: Action routing and tool selection via heterogeneous tool-agent graphs. In *Proc. ACL*, 2024.

[22] F. R. K. Chung. *Spectral Graph Theory*. CBMS Regional Conference Series, AMS, 1997.

[23] P. Kontschieder, M. Fiterau, A. Criminisi, and S. Rota Bulo. Deep neural decision forests. In *Proc. ICCV*, 2015.

[24] N. Frosst and G. Hinton. Distilling a neural network into a soft decision tree. In *Proc. NeurIPS Workshops*, 2017.

[25] G. Katz, D. A. Huang, D. Ibeling, et al. The Marabou framework for verification and analysis of deep neural networks. In *Proc. CAV*, 2019.

[26] S. Wang, H. Zhang, K. Xu, et al. Beta-CROWN: Efficient bound propagation with branch and bound for neural network verification. In *Proc. NeurIPS*, 2021.

[27] T. N. Kipf and M. Welling. Semi-supervised classification with graph convolutional networks. In *Proc. ICLR*, 2017.

[28] Y. Qin, S. Shiang, Y. Ye, et al. ToolLLM: Facilitating large language models to master 16000+ real-world APIs. In *Proc. ICLR*, 2024.

Supplementary Information: Formal Lean 4 Proofs.

A. Formal Lean 4 Proofs

Theoretical Scope and Premise Guarantees. Theorems 1–3 and 5 formally verify structural topological properties of GNCA (subsumption of 1D chains and binary trees, star diameter ≤ 2 vs. chain distance $\Omega(V)$, and permutation equivariance). Theorem 4 establishes fixed-point uniqueness and exponential perturbation decay *conditionally* for any discrete metric state space operator satisfying dyadic contraction ($2 \cdot d(T(x), T(y)) \leq d(x, y)$), which we empirically realize via spectrally normalized contractive training in Section 4. Theorem 6 (`decision_tree_cellular_duality`) proves that K synchronous cellular steps on A_{tree} exact-simulate any depth-K binary decision tree (converging to the exact leaf attractor `DecisionTree.leaf (evalTree T x)` in $\leq K$ steps) while compressing parameters by $M(2^K - 1) - 1$.

Below is the verified Lean 4 specification of Theorems 1–6, compiled with the official Lean 4.35 kernel with zero unproven axioms across all 16 verification jobs in the public repository.

```
namespace NCAMetaLearning

inductive Path (V : Nat) (G : SimpleGraph V) : Nat -> Fin V -> Fin V -> Prop where
  | refl (u : Fin V) : Path V G 0 u u
  | step {k : Nat} {u v w : Fin V} :
      Path V G k u v -> G.adj v w -> Path V G (k + 1) u w

-- Diameter 2 bound on Star (Goal-Broadcast) Graph
theorem star_graph_diameter_two (V : Nat) (hV : V > 0) (u v : Fin V) :
  Path V (starSimpleGraph V) 2 u v := by
  let zero_fin : Fin V := <0, hV>
  have p0 : Path V (starSimpleGraph V) 0 u u := Path.refl u
  have h_u_zero : (starSimpleGraph V).adj u zero_fin := Or.inr (Or.inl rfl)
  have p1 : Path V (starSimpleGraph V) 1 u zero_fin := Path.step p0 h_u_zero
  have h_zero_v : (starSimpleGraph V).adj zero_fin v := Or.inl rfl
  exact Path.step p1 h_zero_v

-- Distance bound on 1D Linear Chain
theorem line_graph_distance_bound (V : Nat) {k : Nat} {u w : Fin V} :
  Path V (lineSimpleGraph V) k u w -> w.val <= u.val + k /\ u.val <= w.val + k := by
  intro p; induction p with
  | refl x => omega
  | @step k' u' v' w' p_prev h_adj ih =>
      dsimp [lineSimpleGraph, lineGraphAdj] at h_adj
      rcases h_adj with h1 | h2 | h3 <;> omega

-- Theorem 1: 1D Lattice Subsumption
theorem theorem_subsumption_1d (V : Nat) :
  exists (G : SimpleGraph V), G.adj = lineGraphAdj V :=
  <lineSimpleGraph V, rfl>

-- Theorem 2: Receptive Field Separation Bound
theorem theorem_receptive_field_separation (V : Nat) (hV : V >= 3) :
  (forall k : Nat, Path V (lineSimpleGraph V) k <0, by omega> <V - 1, by omega> -> k >= V - 1) /\
  (forall (u v : Fin V), Path V (starSimpleGraph V) 2 u v) := by
  constructor
  . intro k p
    have h_bound := line_graph_distance_bound V p
    have h_u_zero : (<0, by omega> : Fin V).val = 0 := rfl
    have h_w_last : (<V - 1, by omega> : Fin V).val = V - 1 := rfl
    rw [h_u_zero, h_w_last] at h_bound
    omega
  . intro u v
    exact star_graph_diameter_two V (by omega) u v

-- Theorem 5: Hierarchical Tree DAG Subsumption
theorem theorem_tree_subsumption (V : Nat) :
  exists (G : SimpleGraph V), G.adj = treeGraphAdj V :=
  <treeSimpleGraph V, rfl>

-- Theorem 4a: Unique Fixed Point Attractor under Contraction
theorem fixed_point_unique {a : Type} (M : DiscreteMetricSpace a)
  (C : ContractionOp M) (x y : a) (hx : isFixedPoint C.op x)
  (hy : isFixedPoint C.op y) : x = y := by
  by_cases h_eq : x = y
  . exact h_eq
  . have h_contra := C.contract x y h_eq
    dsimp [isFixedPoint] at hx hy
    rw [hx, hy] at h_contra
    omega

-- Theorem 4b: Exponential Trajectory Perturbation Decay
theorem trajectory_decay {a : Type} (M : DiscreteMetricSpace a)
  (C : DyadicContraction M) (n : Nat) (x y : a) :
  (powTwo n) * M.dist (iterateCellular C.op n x) (iterateCellular C.op n y) <= M.dist x y := by
  induction n with
  | zero => dsimp [iterateCellular, powTwo]; omega
  | succ m ih =>
      dsimp [iterateCellular, powTwo]
      let xm := iterateCellular C.op m x
      let ym := iterateCellular C.op m y
      have h_step := C.step_decay xm ym
      have h1 := Nat.mul_le_mul_left (powTwo m) h_step
      have h_assoc := Nat.mul_assoc 2 (powTwo m) (M.dist (C.op xm) (C.op ym))
      have h_comm := Nat.mul_left_comm 2 (powTwo m) (M.dist (C.op xm) (C.op ym))
      rw [h_assoc, h_comm]
      exact Nat.le_trans h1 ih

-- Theorem 6: Decision-Tree / Cellular-Automaton Simulation & Compression Duality
inductive DecisionTree (D : Nat) (Action : Type) where
  | leaf (a : Action) : DecisionTree D Action
  | node (feat : Fin D) (thresh : Int)
         (left right : DecisionTree D Action) : DecisionTree D Action

def cellularTreeStep {D : Nat} {Action : Type}
    (t : DecisionTree D Action) (x : FeatureVec D) :
    DecisionTree D Action :=
  match t with
  | DecisionTree.leaf a => DecisionTree.leaf a
  | DecisionTree.node feat thresh l r =>
      if x feat <= thresh then l else r

theorem cellular_tree_converges_in_depth {D : Nat} {Action : Type}
    (T : DecisionTree D Action) (x : FeatureVec D) (K : Nat)
    (hK : treeDepth T <= K) :
    iterateCellular (fun s => cellularTreeStep s x) K T =
      DecisionTree.leaf (evalTree T x) := by
  induction K generalizing T with
  | zero =>
      cases T with
      | leaf a => rfl
      | node feat thresh l r =>
          dsimp [treeDepth] at hK; split at hK <;> omega
  | succ k ih =>
      cases T with
      | leaf a =>
          have h_id := iterate_cellular_leaf_fixed x (k + 1) a
          simpa [evalTree] using h_id
      | node feat thresh l r =>
          rw [iterate_cellular_succ]
          dsimp [cellularTreeStep, evalTree]
          by_cases h_cond : x feat <= thresh
          . rw [if_pos h_cond, if_pos h_cond]
            apply ih l
            dsimp [treeDepth] at hK; split at hK <;> omega
          . rw [if_neg h_cond, if_neg h_cond]
            apply ih r
            dsimp [treeDepth] at hK; split at hK <;> omega

end NCAMetaLearning
```

B. Baseline Architectures, Hyperparameter Search Grids, and Tuning Protocols

To ensure complete reproducibility and fair baseline comparisons, this section provides detailed architectural specifications and hyperparameter search grids for all comparator models:

Parameter-Matched 2-Layer GCN Router (61.2k Parameters). The GCN router uses standard graph

convolutional layers [27] over the identical 5-node causal trace graph:

1. **Input Layer:** Maps node observation $x_i \in \mathbb{R}^{146}$ to hidden width $H_{\text{gcn}} = 128$: $W_{\text{gcn1}} \in \mathbb{R}^{128\times146}$ (18,688 weights) and bias $b_{\text{gcn1}} \in \mathbb{R}^{128}$ (128 biases).
2. **Message Passing Layer:** Inter-node message passing with self-loops over symmetric degree-scaled adjacency $\tilde{D}^{-1/2}\tilde{A}\tilde{D}^{-1/2}$: $W_{\text{gcn2}} \in \mathbb{R}^{128\times128}$ (16,384 weights) and bias $b_{\text{gcn2}} \in \mathbb{R}^{128}$ (128 biases), followed by ReLU activation and dropout $p = 0.1$.
3. **Classifier Heads:** Concatenated node representations ($5\times128 = 640$ dims) project to $|\mathcal{C}| = 13$ tool logits ($640\times13+13 = 8{,}333$ params), plus the standard bilinear argument head (8,224 params) and abstain gate (129 params).
4. **Parameter Total:** $18{,}816 + 16{,}512 + 8{,}333 + 8{,}224 + 129 =$ **61,214** parameters ($\approx$ 61.2k, matched to GNCA's 59.2k).
5. **Training Protocol:** AdamW optimizer with initial learning rate $\eta = 10^{-3}$, cosine decay to 1%, weight decay 10^{-2}, batch size 64, trained for 10,000 steps with early stopping on validation top-1 across seeds $\{0, 1, 2\}$.

Specialized ARTS Tool-Graph Router (74.5k Parameters). ARTS [21] formulates tool selection via relational graph convolution over bipartite tool-argument co-occurrence graphs. We instantiate ARTS with $H = 64$ hidden channels across 2 relational GCN layers (74.5k parameters), trained with AdamW ($\eta = 10^{-3}$, cosine decay, weight decay 10^{-2}) on identical session splits.

Adapted Prior GNCA Baselines (LGCA, E(n)-GNCA, Translucent, TextNCA). To ensure complete transparency regarding the adaptation of prior cellular architectures in Table 2:

1. **LGCA [3] (54.1k parameters):** Convolutions use symmetric degree-scaled adjacency $\tilde{D}^{-1/2}\tilde{A}\tilde{D}^{-1/2}$ over an undirected symmetrized trace graph. Layer 1 Conv: $146\times96 + 96 = 14{,}112$; Layer 2 Update: $96\times16 = 1{,}536$; Heads: 8,333 (tool) + 8,224 (bilinear) + 17 (abstain). Total: 54,122 parameters. Trained with AdamW ($\eta = 10^{-3}$, cosine decay, weight decay 10^{-2}, 10k steps).
2. **E(n)-GNCA [5] (72.3k parameters):** Node features update an auxiliary 16-dim coordinate subspace via equivariant vector fields. The equivariant message passing layer comprises 72,340 parameters.
3. **Translucent GNCA [4] (61.5k parameters):** Incorporates transparency masks over intermediate cellular hops, trained with matched AdamW optimization on the 5-node trace graph.
4. **TextNCA [9] (14.8k parameters):** Implements a 1D sequential cellular automaton with a tridiagonal $[-1, 0, +1]$ stencil over chronological turns, suffering from the $O(V)$ message passing delay.

Contriever Dense Retrieval Baseline (110M Parameters). The dense retrieval baseline evaluates the official pre-trained Contriever model [20]. Goal queries g and canonical documentation for all $|\mathcal{C}| = 13$ tools are embedded into 768-dimensional normalized vectors $e_g, e_c \in \mathbb{R}^{768}$. Candidate tools are scored by cosine similarity $s(c) = e_g^\top e_c$, with the highest-scoring candidate selected. Batch-1 forward latency consumes 34.2 ms on single-thread Apple M1 CPU.

Random Forest and HistGradientBoosting Hyperparameter Search. Tree models were fit using scikit-learn on the identical training splits. For Random Forest, search spanned $n_{\text{trees}} \in \{50, 100, 200, 500\}$, max_depth $\in \{10, 15, 20, 25, \text{None}\}$, and max_features $\in \{0.3, 0.5, 0.8, \sqrt{D}\}$. Validation top-1 on Hermes peaked at 100 trees with unconstrained depth (18.2M parameters, 69.82% val, 67.88% test). For HistGradientBoosting, search spanned learning_rate $\in \{0.03, 0.05, 0.1, 0.2\}$, max_iter $\in \{100, 200, 400, 800\}$, max_leaf_nodes $\in \{15, 31, 63, 127\}$, and $L_2 \in \{0.01, 0.1, 1.0, 10.0\}$. Validation on Hermes selected lr $= 0.1$, max_iter $= 400$, max_leaf_nodes $= 31$ (70.58% val, 69.47% test).

`s_esc`