

Solution Review: Maximum Sum Sublist

This review discusses the solution of the Maximum Sublist Sum Challenge in detail.

We'll cover the following



- Solution (Kadane's Algorithm)
 - Runtime complexity
 - Space complexity


Solution (Kadane's Algorithm)

This algorithm takes a **dynamic programming** approach to solve the maximum sublist sum problem. Let's have a look at the algorithm.

```
1 def find_max_sum_subarray(lst):
2     if (len(lst) < 1):
3         return 0;
4
5     curr_max = lst[0];
6     global_max = lst[0];
7     length_array = len(lst);
8     for i in range(1, length_array):
9         if curr_max < 0:
```



```
10     curr_max = lst[i]
11     else:
12         curr_max += lst[i]
13         if global_max < curr_max:
14             global_max = curr_max
15
16     return global_max;
17
18
19 lst = [-4, 2, -5, 1, 2, 3, 6, -5, 1];
20 print("Sum of largest subarray: ", find_max_sum_subarray(lst));
```



The basic idea of **Kadane's algorithm** is to scan the entire list and at each position find the maximum sum of the sublist ending there. This is achieved by keeping a `current_max` for the current list index and a `global_max`. The algorithm is as follows:

```
current_max = A[0]
global_max = A[0]
for i = 1 -> size of A
    if current_max is less than 0
        then current_max = A[i]
    otherwise
        current_max = current_max + A[i]
    if global_max is less than current_max
        then global_max = current_max
```

The solution above only finds the **maximum contiguous sum** in the list; however, it can easily be modified to track the starting and ending indexes of this sublist.



Runtime complexity

The runtime complexity of this solution is *linear*, $O(n)$.

Space complexity

The memory complexity of this solution is *constant*, $O(1)$.

Let's run through an example to understand how it works. Initially, the `current_max` and `global_max` are both set to the value at `A[0]`, that is, `-4`:



Initial state

-4	2	-5	1	2	3	6	-5	1
----	---	----	---	---	---	---	----	---

current_max = -4

global_max = -4

1 of 10



← Back


Next →

Challenge 11: Maximum Sum Sublist

Lists Quiz: Test your understanding of ...

☒ Mark as Completed

Ask a Question

 Report an Issue

(https://discuss.educative.io/tag/solution-review-maximum-sum-sublist__introduction-to-lists__data-structures-for-coding-interviews-in-python)

