

# Rising Stem Ball Valves

## Design Features


The Rising Stem Ball-Valves use a unique cam system to rotate the ball as the stem raises or lowers. The stem itself does not rotate, and this linear-only travel makes the valve highly suited to frequent cyclic operations while keeping routine maintenance to a minimum.

When closing, the Ball sealing face is only pressed against the seat after the ball has completed its rotation movement, completely removing frictional wear and extending component service.

Operating the valve utilises a single actuator, which can be a manual handwheel (with or without gearbox) or electric, pneumatic or hydraulic.

### Applications and Services

- Stem extension for high temperature service.
- Stem extension and gas column for cryogenic service.
- Slurry and sand service (special design).
- Bellows sealing for dangerous media and zero emissions.
- Molecular sieve / switches valves.
- Gas dehydration and regeneration.
- Hydrogen service.
- Dryer switching.
- Block and bypass.
- Cryogenic Service.
- Emergency shutdown service / Emergency blow down service.
- Hot oil.
- Flow lines.



#### Unique Cam System

Cam arrangement provides friction-free ball/seat mating during opening and closing cycles

#### Top-Entry Design

Allows simple in-line inspection and maintenance



#### Sturdy Design

Minimum heavy-valve wall thickness to API 600/API 6D provides extra corrosion resistance

#### Single Actuator

Linear Stem travel and rotational Ball movement are both driven by the operation of a single actuator

#### Anti-blowout Stem

The inherent anti-blowout stem design ensures safety even for the most challenging applications

#### Backseat Seal

The Backseat Seal design allows stem to be repacked when valve is under pressure and in fully open position

#### Zero Seat Leakage

Seat tightness up to ANSI FCI-70-2 Class VI (with the use of special lapping on the Stellite-6 ball and seat sealing area) ensures zero seat leakage

