

V-Notch (V-Port) Ball Valves

Design Features

These quarter-turn control ball-valves provide superior flow control capability across a range of control applications.

They are more compact, lighter in weight, and much less expensive than comparably-sized globe valves and segmented control valves.

- V-notch ball valves which utilise custom-designed port profiles offer top-level rangeability and repeatability.
- Exceptional interface capabilities are available with PLCs and automated control systems.
- These valves exceed Class VI offering bubble-tight shutoff with zero leakage.
- High flow capacity
- Ability to function with fluids containing solids and fibres.
- Ease of maintenance.
- SchuF high-quality pneumatic and electric control actuators



Below: A range of custom-designed port profiles are available to provide the specific flow-control characteristics required



V-CONTROL BALL VALVE APPLICATIONS

- **TEMPERATURE CONTROL** - With shut-off ability meeting class VI requirements, these valves are ideal for steam / temperature control.
- **FLOW CONTROL** - The high flow capacity and repeatability of the V-control series valves make this the ideal choice for flow control service.
- **STEAM CONTROL** - The V-control series provide tight shutoff. The live-loaded smart-stem design eliminates typical problems of downstream leakage and stem leakage usually associated with globe-style steam-control valves.
- **CAVITATION** - In applications where the possibility of cavitation exists, these valves can be installed with the **V** downstream, helping prevent damage to the valve body