

Introduction to Relational Databases

- Bachelor Computer Science, Lille 1 University
- Lecture 5/12
- Topic: Introduction to SQL as a query language, part 2

© S. Paraboschi (original), C. Kuttler (translation & adaptation)

1

Today's 3 new clauses

```
select ...  
from ...  
[ where ... ]  
[group by ...]  
[having ...]  
[order by ...]
```

Example: contract management

Customer

<u>Cus_ID</u>	CITY	TAX_ID

Contract

<u>Con_ID</u>	Cus_ID	DATE	VALUE

Detail

<u>Con_ID</u>	<u>Prod_ID</u>	Qt

Product

<u>Prod_ID</u>	NAME	PRICE

3

Example of contracts

Contract

Con_ID	Cus_ID	DATE	VALUE
1	3	1-6-12	50.000.000
2	4	3-8-12	8.000.000
3	3	1-9-12	5.500.000
4	1	1-7-12	12.000.000
5	1	1-8-12	1.500.000
6	3	3-9-12	27.000.000

4

Order by clause

- appears at the end of a query, orders the lines of the result

- Syntax:

```
order by OrderAttribute [ asc | desc ]  
        {, OrderAttribute [ asc | desc ] }
```

- The order conditions are applied sequentially :
 - order by first attribute, then by second, etc

```
select *  
from Contract  
where VALUE > 1.000.000  
order by Cus_ID
```

Con_ID	Cus_ID	DATE	VALUE
4	1	1-7-12	12.000.000
5	1	1-8-12	1.500.000
1	3	1-6-12	50.000.000
6	3	3-9-12	5.500.000
3	3	1-9-12	1.500.000
2	4	3-8-12	27.000.000

5

Example

```
select *  
from Contract  
where VALUE > 1.000.000  
order by Date
```

Con_ID	Cus_ID	DATE	VALUE
1	3	1-6-12	50.000.000
4	1	1-7-12	12.000.000
5	1	1-8-12	1.500.000
2	4	3-8-12	8.000.000
3	3	1-9-12	1.500.000
6	3	3-9-12	5.500.000

6

Several order criteria – sequential application

```
select *  
from Contract  
where VALUE > 1.000.00  
order by Cus_ID asc, Date desc
```

Con_ID	Cus_ID	DATE	VALUE
5	1	1-8-12	1.500.000
4	1	1-7-12	12.000.000
6	3	3-9-12	5.500.000
3	3	1-9-12	1.500.000
1	3	1-6-12	50.000.000
2	4	3-8-12	27.000.000

8

Aggregate functions

- Can not be represented in relational algebra
- Aggregate functions evaluate a set of lines
- SQL-2 offers five aggregate functions:
 - count cardinality
 - sum summation
 - max maximum
 - min minimum
 - avg average

9

sum, max, min, avg

Syntax:

- `<sum|max|min|avg> ([distinct|all] AttrExpr)`
- The `distinct` option takes into account each value only once
 - Only useful for `sum` and `avg`
- The option `all` considers all values different from *null*

11

Count Operator

- returns the number of distinct lines or values;
- Syntax:
`Count (< * | [distinct|all] AttributeList >)`
- Extract the number of contracts:
`select count(*) from Contract`
- Extract the number of different values of the attribute `Cus_ID` for all lines of `Contract`:
`select count(distinct Cus_ID) from Contract`
- Extract the number of lines of `Contract` with `Cus_ID` not `NULL`:
`select count(all Cus_ID) from Contract`

10

Maximum query

- **Extract the highest VALUE from all contracts**

```
select max(VALUE) as MaxValue  
from Contract
```

MaxValue
50.000.000

12

Summation query

- What is the total value of customer 1's contracts?

```
select sum(VALUE) as SumAm
from Contract
where Cus_ID = 1
```

SumAm
13.500.000

13

Aggregate function with join

- Extract the maximal VALUE among those contracts that contain the product 'ABC' :

```
select max(VALUE) as MaxValABC
from Contract C join Detail D on
                        C.Con_ID = D.Con_ID
where
    D.Prod_ID = 'ABC'
```

14

Aggregate functions and target list

Want: the date of the contract with maximal value, and its date. Query **with bug**:

```
select Date, max(VALUE)
from Contract C join Detail D on
    C.Con_ID = D.Con_ID
where
    D.Prod_ID = 'ABC'
```

The date of which contract, if there are several with same maximal VALUE?

15

Aggregate functions and target list

Extract the maximal and minimal VALUE of contracts:

```
select max(VALUE) as MaxValue,
       min(VALUE) as MinValue
from Contract
```

MaxValue	MinValue
50.000.000	1.500.000

16

Query with group selection

In queries, we can use aggregation functions as tests on groups of lines by adding another clause :

- **group by** (creation of groups)
- **having** (selection of groups)
-

```
select ...  
from ...  
where ...  
group by ...  
having ...
```

17

Query with grouping

- Extract the sum of values for contracts starting from 10-6-12 for those customers having at least 2 contracts, after that date

```
select Cus_ID, sum(VALUE)  
from Contract  
where Date >= 10-6-12  
group by Cus_ID  
having count(*) >= 2
```

18

Step 1: evaluate where Date >...

Con_ID	Cus_ID	Date	VALUE
2	4	3-8-12	8.000.000
3	3	1-9-12	5.500.000
4	1	1-7-12	12.000.000
5	1	1-8-12	1.500.000
6	3	3-9-12	27.000.000

**Step1 eliminates one tuple with Date
< 10-6-12**

19

Step 2 : grouping

Next, the **group by** clause is evaluated

Con_ID	Cus_ID	Date	VALUE
4	1	1-7-12	12.000.000
5	1	1-8-12	1.500.000
3	3	1-9-12	1.500.000
6	3	3-9-12	5.500.000
2	4	3-8-12	8.000.000

20

Step 3 : computing the aggregates

Now, **sum(VALUE)** and **count(VALUE)** are calculated, separately for each group

Cus_ID	sum (VALUE)	count (VALUE)
1	13.500.000	2
3	7.000.000	2
4	8.000.000	1

21

Step 4 : extracting the groups

Next, we evaluate the predicate

having count(VALUE) >= 2

Cus_ID	sum (VALUE)	count (VALUE)
1	13.500.000	2
3	7.000.000	2
4	8.000.000	1

22

Step 5 : producing the result

Cus_ID	Sum (VALUE)
1	13.500.000
3	7.000.000

23

Avoiding mistakes

- Never write a HAVING without GROUP BY!
- In queries with a group by clause, the select clause (target list) can only contain:
 - grouping attributes
 - aggregate functions
- We *may* add extra grouping attributes for that reason.

24

Target list for queries with group by

- Query with bug:

```
select VALUE
from Contract
  group by Cus_ID
```

- Query with bug:

```
select Cu.Cus_ID, Cu.City, count(*)
from Contract Co join Customer Cu
  on (Co.Cus_ID = Cu.Cus_ID)
  group by Co.Cus_ID
```

- Correct query :

```
select Co.Cus_ID, Cu.City, count(*)
from Contract Co join Customer Cu
  on (Co.Cus_ID = Cu.Cus_ID)
  group by Co.Cus_ID, Cu.City
```

25

<http://docs.postgresql.fr/9.0/sql-select.html#sql-groupby>

Quand GROUP BY est présent, les expressions du SELECT **ne peuvent faire référence qu'à des colonnes groupées**,

sauf à l'intérieur de fonctions d'agrégat,

la valeur de retour d'une colonne non-groupée n'étant pas unique.

where or having?

<http://docs.postgresql.fr/9.1/sql-select.html#sql-groupby>

Quand GROUP BY est présent, les expressions du SELECT ne peuvent faire référence qu'à des colonnes groupées, sauf à l'intérieur de fonctions d'agrégat,

ou bien si la colonne non groupée **dépend fonctionnellement des colonnes groupées.**

En effet, s'il en était autrement, il y aurait plus d'une valeur possible pour la colonne non groupée. Une dépendance fonctionnelle existe si les colonnes groupées (ou un sous-ensemble de ces dernières) sont la clé **primaire** de la table contenant les colonnes non groupées.

- Only predicates that require the evaluation of aggregate functions may appear in the `having` clause!

▪

- Extract the departments where the average incomes of employees working in office 20 exceeds 25:

▪

```
select Depart
from Employee
where Office = '20'
  group by Depart
  having avg(Income) > 25
```

Query with grouping, and ordering

- We can order the result of queries, after grouping

```
select  ...  
from ...  
[ where ...]  
[group by ...]  
[ having ... ]]  
[order by ...]
```

29

Grouping and order

- Extract the sum of the values of contracts after 10-6-12, for clients with at least two such contracts. Display the result in decreasing order in the sum of the VALUE.

```
select  Cus_ID, sum(VALUE)  
from Contract  
where Date > 10-6-12  
group by Cus_ID  
having count(VALUE) >= 2  
order by sum(VALUE) desc
```

30

Result after the order clause

Cus_ID	sum (VALUE)
1	13.500.000
3	7.000.000

31

Grouping by 2 attributes

- Extract per client, per product, how often this client has bought this product, provided the client has bought over 50 of this product.

```
select Cus_ID, Prod_ID, sum(Qt)  
from Contract as C, Detail as D  
where C.Con_ID = D.Con_ID  
group by Cus_ID, Prod_ID  
having sum(Qt) > 50
```

32

Situation after group and joining

Contract		Detail		
Cus_ID	Contract. Con_ID	Detail. Con_ID	Prod_ID	Qt
1	3	3	1	30
1	4	4	1	20
1	3	3	2	30
1	5	5	2	10
2	3	3	1	60
3	1	1	1	40
3	2	2	1	30
3	6	6	1	25

group 1,1

group 1,2

group 2,1

group 3,1

33

Extracting the result

- Now, we evaluate the aggregate function **sum(Qt)** and the predicate **having**, per group.

Cus_ID	Prod_ID	sum(Qt)
1	1	50
1	2	40
2	1	60
3	1	95

34

Set Queries

Set queries

- Built by combining two SQL queries through set operations

- Syntax:

SelectSQL { < **union** | **intersect** | **except** > [**all**]
SelectSQL }

- union** union
- intersect** intersection
- except (minus)** difference
- .

- Duplicates are eliminated, unless the option **all** is used

36

Union

- Extract the identifiers of those contracts whose value is over 500, or in which over 1000 pieces of some product were bought.

```
select Con_ID
from Contract
where VALUE > 500
      union
select Con_ID
from Detail
where VALUE > 1000
```

37

Union all

- Repeat the identifier as often as it appears in the tables Contract and Detail.

```
select Con_ID
from Contract
where VALUE > 500
      union all
select Con_ID
from Detail
where VALUE > 1000
```

38

Difference

- Extract the identifiers of those contracts whose value is over 500, but where no product was bought over 1000 times.

```
select Con_ID
from Contract
where VALUE > 500
      except
select Con_ID
from Detail
where Qt > 1000
```

39

Intersection

- Extract the identifiers of contracts in which the value is over 500 euro, and in which some product has been sold over 1000 times.

```
select Con_ID
from Contract
where VALUE > 500
      intersect
select Con_ID
from Detail
where Qt > 1000
```

41