

Introduction to Relational Databases

- Licence 3 Informatique, Université Lille 1
- Cours 3 /12
- Topic: Introduction to SQL
 - Data Definition Language
 - Data types
 - Table creation
 - Constraints

© S. Paraboschi (original), C. Kuttler (translation)

1

Introduction to SQL: Data Definition Language

2

SQL

- Structured Query Language
- Consists of:
 - definition of domains, relations, indexes, authorizations, views, constraints, procedures, triggers
 - query language, update language, transactional commands
- History:
 - First proposal: SEQUEL (IBM Research, 1974)
 - First commercial implementation in SQL/DS (IBM, 1981)
 - Standardization (1986-2003)


3

Standardization of SQL

- The standardization has been of utmost importance for the success of SQL (mainly within ANSI and ISO)
 - From 1983, it is a standard de facto
 - SQL-1: SQL-86 (basic constructs), SQL-89 (referential integrity constraints)
 - SQL-2: SQL-92 – most adopted version so far
 - SQL-3: SQL:1999 and SQL:2003 – most complete version, with triggers, objects, external functions, extensions for Java and XML, recursion
- In SQL-2 there are three levels:
 - Entry SQL (more or less equivalent to SQL-89)
 - Intermediate SQL
 - Full SQL
- Most systems are compliant to the Intermediate level and offer proprietary extensions for advanced functions

4

Expressiveness of commercial systems versus SQL standard



Data types

- Data types specify the possible values, for each attribute
 - Similar to type definitions in programming languages
- Two categories
 - Built-in (predefined by the SQL standard)
 - SQL-2 distinguishes 6 families
 - user-defined

Notation

- terms use this font
- variables use this font
- square brackets [and] for optional terms, that appear at most once
- curly brackets { and } indicate that the enclosed term may not appear, or may be repeated
- vertical bars indicate that one among several terms separated by the bars must appear
- Curved brackets (and) must be taken as SQL keywords

Built-in data types, 1

- Characters
 - Single characters or strings
 - Strings can have variable lengths
 - Can use character sets that differ from the defaults (e.g., Latin, Greek, Cyrillic, etc.)
 - `character [varying] [(Length)]`
`[character set CharacterFamily]`
 - Can use more compact alternatives as `char` and `varchar`, respectively for `character` and `character varying`
 - Examples:
 - `char(6)`
 - `varchar(50)`

Built-in data types, 2

- Bit
 - Boolean values (true/false), single or in a sequence (the sequence may be of variable length)
 - Syntax:
`bit [varying] [(Length)]`
Examples: `bit(100)`, `varbit(680)`
- Precise numeric types
 - Numeric values: integers or reals
 - 4 alternatives:
`numeric [(Precision [, Scale])]`
`decimal [(Precision [, Scale])]`
`integer` | `smallint`

9

Built-in data types, 3

- Approximate numeric types
 - Approximate real values
 - Based on a floating point representation: integer part + exponent
`float [(Precision)]`
`real`
`double precision`

10

Built-in data types, 4

- Time points
 - With fields:
`date (fields month , day , year)`
`time [(Precision)] [with time zone] : (fields hour , minute , second)`
`timestamp [(Precision)] [with time zone]`
with timezone, one has two additional fields `timezone_hour` and `timezone_minute`
 - Example: `timestamp(4) with time zone` 2-30-2004 3-13-42.0564 5-30
- Time intervals
 - `interval FirstTimeUnit [to LastTimeUnit]`
 - We distinguish 2 groups of time units groups:
 - year, month
 - day, hour, minute, second
 - Examples:
 - `interval year to month`
 - `interval second`

11

Built-in data types, 5

- New built-in types in SQL-3
 - Boolean
 - Bigint
 - BLOB Binary Large Object
 - CLOB Character Large Object
- SQL:1999 also introduces constructors (REF, ARRAY, ROW; they go beyond the relational model and we won't talk about them)

12

User defined data types

- Similar to type definitions in programming languages: for an object, define the values it may take
- A data type is specified by
 - name
 - elementary type
 - default value
 - constraints
- Syntax:
`create domain DomainName as ElementaryDomain
[DefaultValue][Constraints]`
- Example:
`create domain Grade as smallint default null`
- Comparison to programming languages
 - + constraints, default values, richer basic types
 - approved constructors (only renaming of types) 13

"null" values

Null

is a polymorphic value (that is included in all types), and means that a value is unknown

- the value exists in reality, but is unknown to the database (ex.: birthday)
- The value doesn't apply (ex.: driver's license number for children)
- It is unknown if the value is unknown, or used (ex.: driver's license number for adults)

Default values for types

- Fix the value of an attribute, when no value is specified as a tuple is inserted
- Syntax:
`default < GenericValue | user | null >`
- **GenericValue** represents a value compatible with the type, given by a constant or expression
- `user` is the login of the user that executes the command

Definition of application domains

```
create domain DailyPrice
as decimal(3)
default 1,00
not null
```

Definition of schemas

- A **schema** is a collection of objects:
 - domain, tables, indexes, assertions, views, privileges
- Each schema has a name and an owner
- Typical systems do not implement the schema definition of SQL-2 (that however define these at the beginning of a DDL session)

- Syntax:

```
create schema [ SchemaName ]  
[ [ authorization ] Authorization ]  
{ SchemaElementDefinition }
```

17

18

Definition of schemas in SQL

Table creation

- Each SQL table consists of:
 - an ordered set of attributes
 - a set of constraints (may be empty)
- `create table` command
 - Defines the schema of a relation, by creating an empty instance
- Syntax:

```
create table TableName  
(  
  AttributeName Domain [ DefaultValue ] [ Constraints ]  
  {, AttributeName Domain [ DefaultValue ] [ Constraints ] }  
  [ OtherConstraints ]  
)
```

19

create table example (1)

```
create table Student  
( Sid      char(6) primary key,  
  Name     varchar(30) not null,  
  City     varchar(20),  
  Major    char(3) )
```

20

create table examples (2)

```
create table Exam
( Sid char(6),
  Cid char(6),
  Date date not null,
  Grade smallint not null,
  primary key(Sid,Cid) )
```

```
create table Class
( Cid char(6) primary key,
  Title varchar(30) not null,
  Teacher varchar(20) )
```

21

Integrity constraints

- Integrity constraints: conditions that must be satisfied by all instances of the data base
- Constraints on a single relation
 - not null (for one attribute)
 - primary key (implies not null);
 - For a single attribute:
primary key, after the type
 - For several attributes:
primary key(Attribute{, Attribute })
 - unique: key candidates, syntax as for unique
 - check: will be explained later (can represent generic predicates in SQL)

22

Examples of integrity constraints

- Each pair of Name and FirstName uniquely identifies a tuple

```
Name character(20) not null,
FirstName character(20) not null,
unique(Name,FirstName)
```

- Note the difference to the following definition (more restrictive):

```
Name character(20) not null unique,
FirstName character(20) not null unique,
```

23

Referential integrity

24

Example: Student - Exam

Student

Sid	
123	
415	
702	

Exam

Sid	
123	
123	
702	

25

The orphan problems

Student

Sid	
123	
415	
702	

orphans:

Tuples that are without parent,
after deletion of modification in the
parent table

Exam

Sid	
123	
123	
702	

26

How to deal with orphans?

- After modification of the parent table, some operations are performed on the child table
- Violation can be introduced by:
 - (1) updates of the referred attribute
 - (2) deletion of tuples
- Possible reactions:
 - cascade: propagates the modification
 - set null: cancels the referring attribute
 - set default: assigns the default value to the tuple
 - no action: makes the modification impossible
- The reaction can depend on the kind of event ; Syntax:
 on < delete | update >
 < cascade | set null | set default | no²⁷action >

Dealing with orphans: deletion

If a tuple is deleted within **Student**, what happens to his/her exams?

- cascade
the Student's exams are also deleted
- set null
the Sid within Exam is set to null
- set default
the Sid within Exam is set to the default value
- no action
The deletion of tuples within **Student** is forbidden

Dealing with orphans: update

If an Sid is modified within **Student**, what happens to his/her exams?

- **cascade**
the Sid of the students within **Exam** is also modified
- **set null**
the Sid of the students within **Exam** is set to null
- **set default**
the Sid of the students within **Exam** is set to the default value
- **no action**
the modification of the Sid within **Student** is forbidden

Syntax for integrity constraints

- Attributes that are foreign keys inside the child relation must have values present as key values inside the father relation
- `references and foreign key` for referential integrity constraints;
- Syntax:
 - for one attribute
`references after Domain`
 - for one or more attributes
`foreign key (Attribute {, Attribute })
references ...`

Definition: inside the child relation

```
create table Exam
( ....
....
foreign key Sid
references Student
on delete cascade
on update cascade )
```

Definition: inside the child relation

```
create table Exam
( Sid char(6) references Student
on delete cascade
on update cascade ,
.....)
```


It is allowed to have multiple
fathers!

create table Exam

(....

primary key(Sid,Cid)

foreign key Sid

references Student

on delete cascade

on update cascade

foreign key Cid

references Class


on delete no action

on update no action)

33

An incorrect instance

Sid	Name	City	Major
123			
415			
702			



Exam

Sid	Cid	Date	Grade
123	1	7-9-97	30
123	2	8-1-98	28
violates the key constraint	123	2	1-8-97
	702	2	7-9-97
violates the NULL constraint	702	1	NULL
violates the ref. integrity	714	1	7-9-97
			28

34