

Common architecture for portable secure information interchange and unified management (Capsium)

Working Draft Standard

Warning for drafts

This document is not a CalConnect Standard. It is distributed for review and comment, and is subject to change without notice and may not be referred to as a Standard. Recipients of this draft are invited to submit, with their comments, notification of any relevant patent rights of which they are aware and to provide supporting documentation.

Recipients of this draft are invited to submit, with their comments, notification of any relevant patent rights of which they are aware and to provide supporting documentation.

The Calendaring and Scheduling Consortium, Inc. 2024

© 2024 The Calendaring and Scheduling Consortium, Inc.

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from the address below.

The Calendaring and Scheduling Consortium, Inc.

4390 Chaffin Lane
McKinleyville
California 95519
United States of America

copyright@calconnect.org
www.calconnect.org

Contents

Abstract.....	v
Introduction.....	vi
General.....	vi
Features.....	vi
Comparison with existing solutions.....	vi
Benefits.....	vii
Data management impact.....	vii
Summary.....	vii
1. Scope.....	1
2. Normative references.....	1
3. Terms and definitions.....	1
4. Capsium framework.....	8
4.1. General.....	8
4.2. Principles of the framework.....	8
4.3. Key features of the framework.....	9
4.4. Use cases of the framework.....	9
5. Capsium package.....	10
5.1. General.....	10
5.2. Structure.....	10
5.3. Metadata file.....	11
5.4. Manifest file.....	20
5.5. Root file.....	23
5.6. Resource bundling.....	24
5.7. Resource routing.....	28
5.8. Storage.....	36
6. Create new package structure.....	43
7. Update metadata.....	43
8. Validate package.....	43
8.1. Package ID: capsiumPkg2.....	43
9. Create composite package structure.....	44
10. Update metadata.....	44
11. Validate package.....	44
12. Validate composite package.....	45
12.1 Security.....	45
12.2 Encrypted information.....	49
12.3 Validation.....	58
12.4 Testing.....	60
12.5 Complete Example.....	62
12.6 Conformance.....	63
12.7 Composite Packages.....	70
12.8 Capsium Reactor.....	74
12.9 Management of Capsium packages.....	83
12.10 Compliance.....	87
Appendix A Ruby packager.....	90
A.1. Architecture.....	90
A.2. Installation.....	90
A.3. Usage.....	90
A.4. Canonical and legacy schema support.....	91
A.5. security.json generation.....	91
A.6. Programmatic usage.....	92
Appendix B Ruby reactor.....	93
B.1. Starting the reactor.....	93
B.2. Route serving.....	93
B.3. Integrity verification on load.....	93

B.4. Introspection endpoints.....	93
Appendix C Apache httpd reactor.....	95
C.1. Extracting the package to a docroot.....	95
C.2. Integrity pre-verification at deploy time.....	95
C.3. Mapping routes.json to Alias and mod_rewrite.....	95
C.4. Serving manifest-derived MIME types.....	96
C.5. Cache-Control via mod_headers.....	96
C.6. Basic authentication.....	96
C.7. Exposing the introspection API.....	96
Appendix D nginx (OpenResty) reactor.....	98
D.1. Architecture.....	98
D.2. Configuration.....	98
D.3. Extraction and integrity verification.....	100
D.4. Manifest-driven routing.....	100
D.5. Introspection API.....	100
D.6. Docker deployment.....	101

Abstract

Capsium is a modular framework designed to efficiently and securely interchange multi-format information in interoperable portable packages, as well as platform-independent deployment of these packages to serve information consumers.

This document specifies requirements of the Capsium framework and its components:

- Capsium packages: standardized unit of information interchange in the Capsium framework.
- Capsium reactors: server-side or user-side software that allows deployment of a Capsium package.
- Capsium HTTP API: user-facing HTTP API implemented by a Capsium reactor.

Introduction

General

The digital era demands advanced, secure, and efficient methods for deploying and exchanging information. As organizations contend with multi-format data across diverse platforms, the limitations of traditional web packaging solutions become increasingly apparent.

Capsium answers this need with a modular framework designed for the efficient and secure interchange of multi-format information within interoperable and portable packages.

Capsium uniquely supports the packaging and deployment of “non-application websites” or “non-server-side application websites” by delegating those functions to the Capsium reactor, which does not depend on a web server and can be directly implemented by the browser, mimicking the file-serving capabilities of a web server.

Features

Today’s complex digital landscape highlight the necessity for Capsium.

- Portability: There is a critical need for data and applications to be easily transferable across different environments without compromising security or functionality. Capsium ensures that packages can be seamlessly moved between platforms.
- Data immutability: Ensuring that data remains unchanged and secure from tampering is essential for maintaining integrity and trust. Capsium guarantees data immutability through advanced cryptographic techniques, crucial for compliance and auditing.
- Interoperability: Diverse systems and applications must communicate effectively. Capsium supports a wide range of formats and protocols, ensuring seamless integration and data exchange across different platforms.
- Single-page applications (SPAs): Modern web applications demand dynamic, responsive user experiences. Capsium supports the development and deployment of SPAs, reducing server dependency and enhancing performance.
- Capsium Reactors: To meet varied deployment needs, Capsium introduces reactors that can be installed on user machines or servers, managing and deploying Capsium packages with flexibility and scalability, without the need for a traditional web server.

Comparison with existing solutions

Capsium’s unique approach addresses the deficiencies of existing packaging solutions for non-application websites and web applications, which are all unsuitable for the use case.

The following packaging solutions are listed in order of an decreasing level of virtualization.

- Website bundles:
 - Examples: Safari webarchive (extension .webarchive), WARC (extension: .warc), Mozilla Archive Format (MAFF, .maff), Microsoft Compiled HTML Help (CHM, extension .chm) and MHTML/MHT (MIME Encapsulation of Aggregate HTML Documents, extension: .mhtml, .mht) (defined in RFC 2110 and RFC 2557).
 - Purpose: Bundle website resources for offline access and archival.
 - Limitations: Not interoperable and difficult to implement across different browsers. Do not support server-side deployments. Unable to contain single-page applications that require rich HTML API interfaces.
- Client-side web application bundles:
 - Examples: Electron, NW.js.
 - Purpose: Bundle a browser and a web server along with necessary language interpreters.
 - Limitations: Resulting bundles are often very large and cumbersome to distribute, requiring significant memory for simple outputs. Introduce non-platform-independent executable code, complicating data management processes.
- Server-side web application bundles:

- Examples: Webpack, Gulp (JavaScript); Maven (Java); Bundler (Ruby); pip and setuptools (Python).
- Purpose: Automate bundling of static assets and dependencies, improving load times and simplifying development workflows.
- Limitations: Require a large number of dependencies and permissions for port opening and listening. Necessitate running a server, which can be complex and resource-intensive.
- Containers:
 - Examples: Docker, LXC.
 - Purpose: Allow entire applications and their dependencies to be packaged into portable containers, enhancing deployment consistency.
 - Limitations: Require virtualization permissions on the machine, which can be a barrier for some environments. Resource-intensive.
- Virtual machines:
 - Examples: VMWare, Xen.
 - Purpose: Provide complete isolation and can run different operating systems on a single hardware host.
 - Limitations: Require permissions at the hardware level and can be resource-intensive.

Benefits

Capsium addresses the shortcomings of previous solutions and offers unique benefits:

- Interoperability: Supports a variety of formats and protocols, enabling seamless communication between different systems and platforms.
- Portability: Capsium packages are easily transferable, facilitating data migration and deployment without compromising security or functionality.
- Efficiency: Optimizes deployment processes for SPAs and static websites, reducing server dependency and improving performance.
- Security: Utilizing advanced encryption and key management, Capsium ensures secure storage and transfer of information.
- Compliance and auditing: Features for tracking data access and modifications ensure regulatory compliance and robust auditing capabilities.
- Capsium reactors: Provide flexible and scalable package management and deployment solutions, eliminating the need for traditional server infrastructure.

Data management impact

Capsium modernizes and transforms data management practices in several key ways:

- Enhanced Security: Prioritizes data immutability and advanced encryption, helping organizations mitigate data breach risks.
- Improved Interoperability: Facilitates greater integration and communication across different systems, driving innovation and efficiency.
- Portability: Simplifies the transfer of data and applications across different environments, reducing the effort and risk associated with migration.
- Efficiency: Streamlines deployment processes, particularly for SPAs and static websites, leading to faster load times and reduced server loads.
- Compliance and Auditing: Facilitates adherence to regulatory requirements by ensuring data integrity and providing robust tracking of data access and modifications.

Summary

Capsium represents a significant advancement in the realm of data management, addressing critical needs for security, interoperability, portability, efficiency, and compliance. Its innovative approach transforms how organizations handle data, making it a vital tool in the modern digital landscape.

Common architecture for portable secure information interchange and unified management (Capsium)

1. Scope

This document describes Capsium, a modular framework for the secure and efficient interchange of multi-format information within interoperable and portable packages.

This document specifies requirements of the Capsium framework and its components:

- Capsium packages: standardized unit of information interchange in the Capsium framework.
- Capsium reactors: server-side or user-side software that allows deployment of a Capsium package.
- Capsium HTTP API: user-facing HTTP API implemented by a Capsium reactor.

This document also provides:

- Guidelines for the utilization of the Capsium framework.
- Examples for implementing components of the Capsium framework.

2. Normative references

There are no normative references in this document.

3. Terms and definitions

For the purposes of this document, the following terms and definitions apply.

3.1.

Capsium package

A structured bundle of multi-format data and resources that can be securely and efficiently interchanged and deployed across different platforms. Capsium packages are designed to be portable and interoperable, ensuring seamless data transfer and application deployment.

3.2.

Capsium reactor

A component responsible for managing and deploying Capsium packages. The Capsium reactor can be implemented directly by a web browser or installed on user machines or servers. It eliminates the need for a traditional web server by mimicking its file-serving capabilities.

3.3.

Capsium HTTP API

3.4.

Non-application website

A website that does not require server-side logic or dynamic content generation. These websites consist primarily of static resources such as HTML, CSS, and JavaScript files and are deployed using the Capsium framework without the need for a traditional web server.

3.5.

Single-page application (SPA)

A web application that loads a single HTML page and dynamically updates the content as the user interacts with the app. SPAs provide a more fluid and responsive user experience by reducing server dependency. Capsium supports the deployment and optimization of SPAs.

3.6.

Data immutability

The property of data that ensures it remains unchanged and secure from tampering after it has been created. Capsium guarantees data immutability through the use of advanced cryptographic techniques, ensuring the integrity and trustworthiness of the data.

3.7.

Interoperability

The ability of different systems, platforms, and applications to communicate and work together effectively. Capsium supports a wide range of formats and protocols, enabling seamless data exchange and integration across diverse environments.

3.8.

Portability

The capability of a system or application to be easily transferred and used across different environments without compromising security or functionality. Capsium packages are designed to be portable, facilitating easy migration and deployment.

3.9.

Compliance and auditing

The adherence to regulatory requirements and the ability to track and monitor data access and modifications. Capsium includes features that ensure compliance with relevant standards and provide robust auditing capabilities to maintain data integrity and security.

3.10.

Encryption

The process of converting data into a coded format to prevent unauthorized access. Capsium employs advanced encryption techniques to ensure that the data within its packages is securely stored and transferred, protecting sensitive information from breaches.

3.11.

Key management

The administration of cryptographic keys, which includes their generation, exchange, storage, use, and replacement. In the context of Capsium, key management is crucial for maintaining the security of encrypted data and ensuring that only authorized entities can access or modify the data.

3.12.

Static website

A website consisting of fixed content that does not change unless manually updated. Static websites are composed of HTML, CSS, and JavaScript files and do not require server-side processing. Capsium aids in the deployment of static websites by packaging all necessary resources into a single, portable bundle.

3.13.

Virtualization

The creation of a virtual version of something, such as an operating system, a server, a storage device, or network resources. Capsium packages reduce the need for virtualization by allowing applications to run directly in the browser or on the client machine, simplifying deployment and reducing resource requirements.

3.14.

Package management

The process of handling software packages, including their installation, upgrade, configuration, and removal. Capsium's package management capabilities ensure that Capsium packages can be efficiently deployed and maintained, streamlining the application lifecycle.

3.15.**Browser-implemented reactor**

A Capsium reactor that is directly implemented by the web browser, enabling it to serve Capsium packages without the need for additional server infrastructure. This approach leverages the browser's native capabilities to handle package deployment and management.

3.16.**Serverless architecture**

A design pattern where the server management and infrastructure concerns are abstracted away from the developer. Capsium supports serverless architectures by allowing applications to be deployed and run without a traditional server, relying instead on the Capsium reactor.

3.17.**Cryptographic techniques**

Methods used to secure information and communications through the use of codes, ensuring that only those for whom the information is intended can read and process it. Capsium utilizes cryptographic techniques to maintain data security and integrity within its packages.

3.18.**Interchange format**

A standardized format used for exchanging data between different systems or platforms. Capsium defines a specific interchange format to ensure that its packages can be seamlessly transferred and utilized across various environments.

3.19.**Multi-format information**

Data that exists in various formats, such as text, images, video, and structured data. Capsium packages are designed to handle multi-format information, ensuring that diverse types of data can be securely and efficiently bundled together and deployed.

3.20.**Deployment**

The process of distributing and installing software or data packages in a specific environment. Capsium streamlines deployment by allowing packages to be easily transferred and installed without the need for extensive configuration or server infrastructure.

3.21.**Regulatory compliance**

Adhering to laws, regulations, and guidelines relevant to the handling and protection of data. Capsium helps organizations maintain regulatory compliance by providing tools and features that ensure data security, integrity, and traceability.

3.22.**File-serving capabilities**

The ability of a server or system to deliver files to clients upon request. In the context of Capsium, the reactor mimics traditional file-serving capabilities, allowing it to serve packaged resources directly to the browser or client machine.

3.23.**Resource bundling**

The process of combining multiple files and resources into a single package. Capsium facilitates resource bundling, enabling efficient transfer and deployment of all necessary components of a web application or website.

3.24.

Package integrity

The assurance that a package has not been altered or tampered with since its creation. Capsium ensures package integrity through cryptographic signatures and other security measures, guaranteeing that the contents of a package remain unchanged during transfer and deployment.

3.25.

Transferability

The ease with which data or applications can be moved from one environment to another. Capsium enhances transferability by providing a standardized package format that can be easily migrated across different platforms and systems.

3.26.

Static content

Web content that does not change and is delivered to the user exactly as stored. Capsium supports the deployment of static content by packaging it into a portable format that can be served without the need for dynamic processing.

3.27.

Advanced cryptography

The use of sophisticated encryption algorithms and techniques to protect data. Capsium employs advanced cryptography to ensure that the data within its packages is secure from unauthorized access and tampering.

3.28.

Data migration

The process of moving data from one system or environment to another. Capsium simplifies data migration by providing a portable package format that facilitates the transfer of data and resources across different platforms.

3.29.

Scalable deployment

The ability to efficiently deploy applications and data across a varying number of environments and users. Capsium supports scalable deployment by providing a flexible package format and reactor that can handle deployments of any size.

3.30.

Platform independence

The ability of software or data to operate on various hardware and operating systems without requiring modification. Capsium ensures platform independence by using standardized formats and protocols, allowing its packages to be used across different environments seamlessly.

3.31.

Dependency management

The process of handling and resolving the dependencies required by software applications or packages. Capsium includes mechanisms for managing dependencies within its packages, ensuring that all necessary components are available and properly configured during deployment.

3.32.

Immutable data

Data that cannot be altered once it has been created. Capsium guarantees immutability through cryptographic methods, making sure that data within a package remains unchanged and secure from tampering.

3.33.**Data integrity**

The accuracy and consistency of data over its lifecycle. Capsium ensures data integrity by using cryptographic techniques to protect data from unauthorized alterations, ensuring reliable and trustworthy information.

3.34.**Secure interchange**

The safe and protected exchange of data between different systems or platforms. Capsium facilitates secure interchange by using advanced encryption and ensuring that packages are transferred without compromising their integrity or confidentiality.

3.35.**Application lifecycle**

The entire process of developing, deploying, maintaining, and eventually decommissioning an application. Capsium supports the application lifecycle by providing tools and features that streamline deployment, maintenance, and updates of packaged applications.

3.36.**Server dependency**

The reliance on a server to provide resources, process requests, and manage data. Capsium reduces server dependency by enabling applications and websites to be deployed and run using the Capsium reactor, which can function without a traditional server.

3.37.**Resource optimization**

The process of improving the efficiency and performance of resources used by an application or system. Capsium supports resource optimization by packaging resources in a way that reduces load times and minimizes server demands.

3.38.**Data traceability**

The ability to track the history, usage, and location of data over its lifecycle. Capsium includes features that enhance data traceability, ensuring that data access and modifications can be monitored and audited for compliance and security purposes.

3.39.**Data security**

The protection of data from unauthorized access, corruption, or theft. Capsium ensures data security through encryption, key management, and other protective measures, maintaining the confidentiality and integrity of packaged data.

3.40.**Audit trail**

A record of all actions and changes made to data, providing transparency and accountability. Capsium supports the creation of audit trails, helping organizations monitor data access and modifications for compliance and security.

3.41.**Browser-native deployment**

The ability to deploy applications and resources directly within a web browser without requiring additional plugins or software. Capsium supports browser-native deployment, leveraging the browser's capabilities to handle and serve packaged data and applications.

3.42.

Dynamic content

Web content that changes based on user interactions or other conditions. While Capsium primarily targets static and SPA content, it can support dynamic content through appropriate integration with client-side scripting.

3.43.

Lightweight deployment

A deployment method that minimizes resource usage and overhead, making it suitable for environments with limited resources. Capsium supports lightweight deployment by packaging applications and data in an efficient, compact format.

3.44.

Multi-platform support

The ability to operate across various operating systems, devices, and environments. Capsium ensures multi-platform support by adhering to standardized formats and protocols, allowing its packages to function seamlessly across different systems.

3.45.

Portable package

A self-contained bundle that includes all necessary resources and data, designed to be easily transferred and deployed across different environments. Capsium packages are inherently portable, facilitating straightforward migration and deployment.

3.46.

Client-side processing

The execution of operations on the user's device rather than on a server. Capsium supports client-side processing by enabling web applications to run directly in the browser, reducing the need for server interactions.

3.47.

Cross-platform compatibility

The ability of software or data to work on various operating systems and devices without requiring modifications. Capsium ensures cross-platform compatibility by using standardized formats and protocols, making its packages usable across different platforms.

3.48.

Version control

A system for managing changes to documents, programs, and other information stored as computer files. Capsium integrates version control mechanisms to help track changes, manage different versions, and ensure consistency of packaged data.

3.49.

Secure deployment

The practice of deploying applications and data in a manner that ensures their security throughout the process. Capsium supports secure deployment by using encryption and other security measures to protect packages from tampering and unauthorized access.

3.50.

Configuration management

The process of handling changes in software, hardware, documentation, and other components. Capsium includes features for configuration management, ensuring that packages are correctly configured and maintained throughout their lifecycle.

3.51.**Integrity check**

A method to verify that data has not been altered or tampered with. Capsium performs integrity checks using cryptographic signatures, ensuring the authenticity and consistency of the data within its packages.

3.52.**Modular framework**

A design approach that divides a system into smaller parts, or modules, that can be independently created and then used in different systems. Capsium is a modular framework, allowing components to be added, removed, or updated without affecting the whole system.

3.53.**User authentication**

The process of verifying the identity of a user. Capsium supports user authentication to ensure that only authorized individuals can access and interact with the contents of a package.

3.54.**Data encapsulation**

The bundling of data with the methods that operate on that data, restricting direct access to some of the object's components. Capsium utilizes data encapsulation to protect the integrity and security of the packaged data.

3.55.**Environment abstraction**

The separation of application logic from the underlying hardware and software environment. Capsium provides environment abstraction by allowing packages to operate independently of the specific details of the deployment environment.

3.56.**Resilience**

The ability of a system or application to recover quickly from failures and continue to function. Capsium enhances resilience by packaging applications in a way that minimizes dependencies and facilitates recovery and redeployment.

3.57.**Scalability**

The capacity to handle increasing amounts of work or to be readily enlarged. Capsium supports scalability by ensuring that its packages can be deployed and managed efficiently, regardless of the scale of the deployment.

3.58.**Trusted execution**

The assurance that code and data are executed in a secure environment, protected from unauthorized access and tampering. Capsium supports trusted execution through the use of secure packaging and deployment mechanisms.

3.59.**Content delivery**

The process of distributing digital content to users. Capsium optimizes content delivery by bundling resources into efficient packages that can be served directly by the browser or client machine.

3.60.**Content encapsulation**

The practice of bundling content with the necessary metadata and resources to ensure it can be used independently of its original environment. Capsium uses content encapsulation to create portable packages that can be deployed and used across different systems.

3.61.**Application sandboxing**

The technique of running applications in a restricted environment to limit their access to system resources and data. Capsium can support application sandboxing by enabling packages to run in isolated environments, enhancing security and control.

3.62.**Metadata management**

The process of handling metadata, which is data that describes other data. Capsium includes features for metadata management, ensuring that the necessary information about packaged data and resources is available and properly maintained.

3.63.**Data lifecycle management**

The process of managing data from its creation to its eventual disposal. Capsium includes features for data lifecycle management, ensuring that data within its packages is properly handled, maintained, and disposed of according to best practices and regulatory requirements.

4. Capsium framework

The Capsium framework provides a comprehensive set of principles, features, and use cases that define its architecture and functionality. This clause outlines the essential components and concepts that make up the framework, ensuring a clear understanding of its capabilities and applications.

4.1. General

Capsium (Common architecture for portable secure information interchange and unified management) is an innovative technology framework designed to facilitate the interoperable and portable deployment of lightweight, web-compatible, interactive data packages. The framework supports the packaging and deployment of static websites, which can be hosted by any cloud file hosting service with minimal web serving functionality, such as AWS S3 or GitHub Pages.

The core concept of Capsium is to enable the packaging of static websites into deployable objects, called Capsium packages. These packages are self-contained, size-efficient, and secure, providing all necessary resources and metadata to be served by a simple web server.

4.2. Principles of the framework

The Capsium framework is based on several key principles that ensure its effectiveness and reliability:

Ease of use	The deployable object can be easily built, inspected, extracted, and deployed.
Cross-platform deployment	The deployable object can be deployed across multiple platforms without modification.
Static nature	The deployable object is static, meaning it does not require server-side processing to function.

Size efficiency	The deployable object is designed to be as small and efficient as possible.
Integrity	The deployable object cannot be corrupted, ensuring data integrity.
Self-containment	The deployable object is self-contained, including all necessary routes and redirects for the static site.
Versioning	The deployable object can be versioned, allowing for efficient updates and rollbacks.
Dependencies	The deployable object can require other deployable objects, enabling modularity and extensibility.
File system support	The deployable object has a file system that supports all types of files and provides immutable, layered versioning.
Deployment API compatibility	The deployment API can be easily implemented by common web servers such as Apache and nginx.
Compliance	The deployment API complies with common expectations and supports fetching of metadata and other introspection features.

4.3. Key features of the framework

The Capsium framework includes several key features that enhance its functionality and usability:

Capsium package	A deployable object that is a compressed, single-file package containing all files necessary for a static site.
Capsium filesystem	A file system within the Capsium package, representing the file/folder hierarchy as it will be served by the package's external API.
Capsium reactor	A Capsium-enabled web server that activates and deploys the Capsium package.
Activation	The process by which a reactor loads the content of a Capsium package and serves its routes to a web address.

These features enable the efficient creation, deployment, and management of web-compatible, interactive data packages.

4.4. Use cases of the framework

The Capsium framework supports a variety of use cases, demonstrating its versatility and practicality:

Static website deployment	Capsium packages can be used to deploy static websites, including HTML, CSS, JS, and media files, on cloud file hosting services.
Microservices integration	Capsium packages can mount routes from other deployable objects, facilitating the integration of microservices.
Data migration	Capsium packages can be used to securely and efficiently migrate data across different platforms and environments.

Secure interchange	Capsium packages provide a secure method for exchanging data between systems, with support for encryption and digital signatures.
Version control and updates	Capsium packages support versioning, enabling efficient updates and rollbacks of deployed static websites.

These use cases highlight the practical applications of the Capsium framework in various scenarios, emphasizing its ability to enhance the deployment and management of web-compatible data packages.

5. Capsium package

The Capsium package is the fundamental unit of deployment within the Capsium framework. This clause details the structure, contents, and specifications of a Capsium package, ensuring a comprehensive understanding of its components and functionality.

5.1. General

A Capsium package is a compressed, single-file deployable object that contains all the necessary files for a static site. It is designed to be easily built, inspected, extracted, and deployed across various platforms. The package ensures that all resources, metadata, and configurations required for site deployment are self-contained within it.

Description	A Capsium package encapsulates a static website, including HTML, CSS, JS, media files, and potentially a data store.
MIME type	The MIME type for a Capsium package is <code>application/vnd.capsium.package</code> .
File extension	The standard file extension for a Capsium package is <code>.cap</code> .

5.2. Structure

5.2.1. General

The structure of a Capsium package includes several key elements that organize and define the contents and functionality of the package:

Folder hierarchy	The internal file/folder hierarchy represents how files will be served by the package's external API.
Metadata, versions, package dependencies	Metadata provides information about the package, including versioning details and dependencies on other Capsium packages.
License and copyright file and declaration	The package includes a license and copyright file, typically in SPDX format, to specify the legal terms of use.

5.2.2. Folder hierarchy

The folder hierarchy is:

```
example-capsium-package/
├── index.html
└── styles.css
```

```

├─ app.js
├─ manifest.json
├─ routes.json
├─ http-api.json
├─ storage.json
├─ security.json
├─ authentication.json
├─ logging-monitoring.json
├─ validation.json
├─ LICENSE.spdx
└─ README.md

```

Figure 1

5.3. Metadata file

5.3.1. General

```

{
  "name": "example-capsium-package",
  "version": "1.0.0",
  "description": "A sample Capsium package that demonstrates resource bundling.",
  "guid": "example.com/example-capsium-package",
  "uuid": "123e4567-e89b-12d3-a456-426614174000",
  "author": "Your Name",
  "repository": {
    "type": "git",
    "url": "https://github.com/yourusername/example-capsium-package.git"
  },
  "dependencies": {
    "other-package.capsium": ">=1.0.0"
  },
  "license": "path/to/LICENSE.spdx",
  "readOnly": true
}

```

Figure 2

- 1) **name**

Description	The name of the package.
Requirements	— Should be a string. — Must be unique within the ecosystem. — Typically uses kebab-case (lowercase letters with hyphens).
- 2) **version**

Description	The version of the package.
Requirements	— Should follow [Semantic Versioning](https://semver.org/) (e.g., 1.0.0). — Consists of three digits separated by dots, representing major, minor, and patch versions.
- 3) **description**

Description	A brief description of the package.
Requirements	— Should be a string. — Provides a concise overview of what the package does.
- 4) **guid**

Description	A globally unique identifier for the package.
Requirements	— Should be a URI. — URI format
- 5) **uuid**

Description	A universally unique identifier for the package.
Requirements	— Should be a string.

- Must be a valid UUID (e.g., 123e4567-e89b-12d3-a456-426614174000).
- 6) **author**
 - Description The name of the author or maintainer of the package.
 - Requirements
 - Should be a string.
 - Can include the author's name or organization.
- 7) **license**
 - Description The license under which the package is distributed.
 - Requirements
 - Should be a string.
 - Can be a standard license identifier (e.g., MIT) or a path to a license file (e.g., path/to/LICENSE.spdx).
- 8) **repository**
 - Description Information about the repository where the package source code is hosted.
 - Sub-attributes
 - type The type of version control system (e.g., git).
 - Requirements: Should be a string.
 - url The URL of the repository.
 - Requirements: Should be a string and a valid URL.
- 9) **dependencies**
 - Description A list of other packages that this package depends on.
 - Requirements
 - Should be an object where keys are package names and values are version requirements.
 - Version requirements can use semantic versioning ranges (e.g., >=1.0.0).
- 10) **readOnly:**
 - Type boolean
 - Description Specifies if the package is immutable.
 - Value Must be set to true to activate immutability.
 - Requirements
 - Example NOTE: The name, version, guid, and uuid attributes are critical for the unique identification of the package.

NOTE The repository and dependencies attributes help in maintaining and managing the package's source code and its dependencies, respectively.

5.3.2. Identifier

The GUID (Globally Unique Identifier) for a Capsium package is used for uniquely identifying the package within the ecosystem. It follows a URI (Uniform Resource Identifier) format to ensure global uniqueness and to provide a standardized way of referencing the package.

It ensures global uniqueness, readability, and consistent identification of packages.

The GUID is essential for dependency tracking, providing a reliable reference to specific packages within the ecosystem.

5.3.2.1. Requirements for GUID in URI Format

- 1) Structure:
 - The GUID should be structured in a URI format.
 - Typically, it follows a reverse domain name notation to ensure uniqueness.
- 2) Components:
 - Scheme The scheme part of the URI, which could be http, https, or a custom scheme like capsium.
 - Authority This usually includes the domain name, ensuring the identifier is unique to an organization or individual.
 - Path A path that typically reflects the package name and possibly the version.
- 3) Uniqueness:

- The GUID must be unique across all packages to avoid conflicts.
 - Using the domain name owned by the package maintainer helps ensure uniqueness.
- 4) Readability:
- The GUID should be easy to read and understand, reflecting the package's origin and name.
- 5) Examples:
- The GUID should ideally be in lowercase to maintain consistency and avoid case-sensitivity issues.

5.3.2.2. Examples of GUIDs in URI Format

Here are a few examples of GUIDs that comply with the URI format requirements:

1) Example 1:

```
"guid": "capsium://example.com/package-name"
```

Figure 3

Scheme	capsium
Authority	example.com
Path	/package-name

1) Example 2:

```
"guid": "https://example.com/packages/sample-package"
```

Figure 4

Scheme	https
Authority	example.com
Path	/packages/sample-package

1) Example 3:

```
"guid": "http://myorganization.org/capsium/my-package"
```

Figure 5

Scheme	http
Authority	myorganization.org
Path	/capsium/my-package

1) Example 4:

```
"guid": "capsium://opensource.org/libs/lib-capsium"
```

Figure 6

Scheme	capsium
Authority	opensource.org
Path	/libs/lib-capsium

5.3.2.3. Dependency tracking

The GUID is crucial for dependency tracking as it provides a unique and consistent identifier for each package. When defining dependencies in the `metadata.json` file, the GUID ensures that the correct package is referenced, avoiding confusion with similarly named packages.

In the `metadata.json` file, dependencies can be listed using the GUID:

```
{
  "dependencies": {
    "capsium://example.com/package-name": ">=1.0.0",
    "https://example.com/packages/another-package": "^2.1.0"
  }
}
```

Figure 7

`capsium://example.com/package-name` This GUID uniquely identifies the package-name from `example.com` and specifies that any version `>=1.0.0` is acceptable.

`https://example.com/packages/another-package` This GUID uniquely identifies the another-package from `example.com` and specifies that any version compatible with `2.1.0` (using semantic versioning) is acceptable.

5.3.3. Versions

5.3.3.1. General

Versions in the metadata file use [Semantic Versioning](<https://semver.org/>), which follows the MAJOR.MINOR.PATCH format.

Here is an example:

```
{
  "version": "1.0.0"
}
```

Figure 8

The version of a Capsium package is a critical attribute that indicates the state and compatibility of the package over time. It follows the Semantic Versioning (SemVer) convention to ensure clarity and consistency across package versions.

5.3.3.2. Requirements for Version

- 1) Format:
 - The version should follow the Semantic Versioning format: MAJOR.MINOR.PATCH.
 - Each component (MAJOR, MINOR, PATCH) should be a non-negative integer without leading zeros.
- 2) Components:

MAJOR	Incremented for incompatible API changes. When you make changes that break backward compatibility, you increase the major version.
MINOR	Incremented for adding functionality in a backward-compatible manner. When you add new features that do not break existing functionality, you increase the minor version.
PATCH	Incremented for backward-compatible bug fixes. When you make minor changes or fixes that do not affect the API, you increase the patch version.

1) **Pre-release and Build Metadata** (Optional):

Pre-release version Indicated by appending a hyphen and a series of dot-separated identifiers (e.g., 1.0.0-alpha, 1.0.0-beta.1).
Build metadata Indicated by appending a plus sign and a series of dot-separated identifiers (e.g., 1.0.0+20130313144700, 1.0.0-beta+exp.sha.5114f85).

3) Incrementing Versions:

- Always increment the appropriate part of the version number based on the nature of the changes.
- Reset the lower components to zero when incrementing a higher component (e.g., 1.2.3 to 2.0.0).

4) Uniqueness:

- Each release of a package should have a unique version number to distinguish it from other releases.

5.3.3.3. Examples of Version Numbers

1) Stable Versions:

- 1.0.0: Initial stable release.
- 2.1.0: Minor update with new features that are backward-compatible.
- 3.0.2: Patch update with bug fixes for the third major version.

2) Pre-release Versions:

- 1.0.0-alpha: An alpha version, which is an early release not intended for production use.
- 1.0.0-beta.1: The first beta release, which is more stable than alpha but still not production-ready.
- 1.0.0-rc.1: The first release candidate, which is a final stage before a stable release.

3) Versions with Build Metadata:

- 1.0.0+20130313144700: A stable release with build metadata indicating the build timestamp.
- 2.0.0-beta+exp.sha.5114f85: A beta release with experimental build metadata.

5.3.4. Dependencies

5.3.4.1. General

Dependencies are specified in the `dependencies` section of the metadata JSON file. Each dependency is listed with a name and a version requirement.

The `dependencies` section in the `metadata.json` file specifies other packages that the Capsium package depends on. This section ensures that all necessary packages are available for the package to function correctly.

Here is an example:

```
{
  "dependencies": {
    "other-package.capsium": ">=1.0.0",
    "another-package.capsium": "^2.3.4"
  }
}
```

Figure 9

5.3.4.2. Requirements for Dependencies

1) Structure:

- The `dependencies` section should be an object where each key is the GUID of a dependency package and the corresponding value is the version requirement.

2) GUID:

- The key should be the GUID of the dependency package in URI format, ensuring global uniqueness and proper identification.
- 3) Version Requirement:
 - The value should be a string that specifies the version requirement of the dependency.
 - Version requirements can use semantic versioning ranges, such as:
 - Exact version: 1.2.3
 - Greater than or equal to a version: `>=1.0.0`
 - Compatible with a version: `^2.1.0`
 - Ranges: `>=1.0.0 <2.0.0`
- 4) Multiple Dependencies:
 - The dependencies section can list multiple dependencies, each with its GUID and version requirement.

5.3.4.3. Examples of Dependencies

1) Single Dependency:

```
"dependencies": {
  "capsium://example.com/package-name": ">=1.0.0"
}
```

Figure 10

- This specifies that the package depends on package-name from example.com with any version `>=1.0.0`.

1) Multiple Dependencies:

```
"dependencies": {
  "https://example.com/packages/first-package": "^2.1.0",
  "capsium://another.com/second-package": "1.2.3"
}
```

Figure 11

- This specifies that the package depends on:
 - first-package from example.com with any version compatible with 2.1.0.
 - second-package from another.com with the exact version 1.2.3.

1) Range Version Dependency:

```
"dependencies": {
  "capsium://example.org/dependency-package": ">=1.0.0 <2.0.0"
}
```

Figure 12

- This specifies that the package depends on dependency-package from example.org with any version between 1.0.0 (inclusive) and 2.0.0 (exclusive).

1) Pre-release Version Dependency:

```
"dependencies": {
  "capsium://example.net/experimental-package": "1.0.0-beta.1"
}
```

Figure 13

- This specifies that the package depends on experimental-package from example.net with the specific pre-release version 1.0.0-beta.1.

1) Dependency with Build Metadata:

```
"dependencies": {
  "https://example.com/special-package": "1.0.0+20130313144700"
}
```

Figure 14

- This specifies that the package depends on `special-package` from `example.com` with the exact version `1.0.0` including build metadata `20130313144700`.

1) Multiple Version Ranges:

```
"dependencies": {
  "capsium://example.org/multi-range-package": ">=1.0.0 <1.5.0 || >=2.0.0 <3.0.0"
}
```

Figure 15

- This specifies that the package depends on `multi-range-package` from `example.org` with versions either between `1.0.0` (inclusive) and `1.5.0` (exclusive) or between `2.0.0` (inclusive) and `3.0.0` (exclusive).

1) Wildcard Version Dependency:

```
"dependencies": {
  "capsium://example.com/wildcard-package": "*"
}
```

Figure 16

- This specifies that the package depends on `wildcard-package` from `example.com` with any available version.

1) Caret (^) and Tilde (~) Ranges:

```
"dependencies": {
  "capsium://example.com/caret-package": "^1.2.3",
  "capsium://example.com/tilde-package": "~1.2.3"
}
```

Figure 17

- This specifies that the package depends on:
 - `caret-package` from `example.com` with any version compatible with `1.2.3` (meaning `>=1.2.3 <2.0.0`).
 - `tilde-package` from `example.com` with any version compatible with `1.2.3` (meaning `>=1.2.3 <1.3.0`).

Each dependency in the `dependencies` section ensures that the package has access to the required versions of other packages necessary for its proper functionality.

5.3.5. License

5.3.5.1. General

The `license` key in the `metadata.json` file specifies the licenses under which the Capsium package is distributed. This key ensures compliance with legal requirements and informs users of their rights and obligations regarding the package.

The license file should be in the SPDX format and referenced from the metadata file.

5.3.5.2. Requirements for License

- 1) Format:
 - The `license` key should be a string or an array of objects.
 - Each string should be a valid SPDX (Software Package Data Exchange) license identifier or a path to an SPDX file included in the package.
- 2) Single License:
 - When the package is distributed under a single license, the `license` key should be a string.
- 3) Multiple Licenses:
 - When the package is distributed under multiple licenses, the `license` key should be an array of objects.
 - Each object in the array should specify a type and an optional `file` field if pointing to an SPDX file.
 - Each object should also include a `condition` field that describes when the license applies.
- 4) SPDX Identifier or File:
 - An SPDX identifier should be a valid SPDX license identifier.
 - An SPDX file should be a path to a file included in the package that contains the SPDX license text.

5.3.5.3. Examples of License

- 1) Single SPDX License:

```
"license": "MIT"
```

Figure 18

- This specifies that the package is distributed under the MIT License.

- 1) Single SPDX File License:

```
"license": "LICENSE.spdx"
```

Figure 19

- This specifies that the package is distributed under the license detailed in the `LICENSE.spdx` file.

- 1) Multiple Licenses with Conditions:

```
"license": [
  {
    "type": "MIT",
    "condition": "Default license"
  },
  {
    "type": "Apache-2.0",
    "condition": "For use in commercial environments"
  }
]
```

]

Figure 20

- This specifies that the package is distributed under the MIT License by default, but under the Apache License 2.0 when used in commercial environments.

1) Combination of SPDX Identifier and File with Conditions:

```
"license": [
  {
    "type": "MIT",
    "condition": "Default license"
  },
  {
    "type": "Custom-License",
    "file": "custom-license.spdx",
    "condition": "For internal use only"
  }
]
```

Figure 21

- This specifies that the package is distributed under the MIT License by default, but under a custom license detailed in the custom-license.spdx file for internal use only.

1) Complex License Conditions:

```
"license": [
  {
    "type": "GPL-3.0-only",
    "condition": "When redistributed"
  },
  {
    "type": "LGPL-3.0-only",
    "condition": "When used as a library"
  }
]
```

Figure 22

- This specifies that the package is distributed under the GPL-3.0-only License when redistributed and under the LGPL-3.0-only License when used as a library.

By following these requirements and examples, the license key in the Capsium package's metadata.json file provides clear information about the applicable licenses and the conditions under which they apply.

Below is an example of a simple SPDX license file (LICENSE.spdx):

```
SPDXVersion: SPDX-2.1
DataLicense: CC0-1.0
SPDXID: SPDXRef-DOCUMENT
DocumentName: example-capsium-package
DocumentNamespace: http://spdx.org/spdxdocs/example-capsium-package-abc123
Creator: Person: John Doe
Creator: Organization: Example Organization
Creator: Tool: SPDX-Tools-Version-2.1.0
Created: 2024-05-28T12:00:00Z
LicenseID: MIT
LicenseName: MIT License
```

LicenseText: |
MIT License

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

Figure 23

Ensure this SPDX license file is referenced in the `manifest.json`:

```
{
  "license": "path/to/LICENSE.spdx"
}
```

Figure 24

5.3.6. Read-only

Capsium packages can be configured as immutable, ensuring that their content cannot be modified after creation.

This section details the requirements, specifications, and use cases for configuring a package as read-only, including value requirements and enumerations for attributes. The read-only attribute is package-wide and set inside `metadata.json`.

5.4. Manifest file

5.4.1. General

The manifest file describes how to handle multi-format content within the package.

It includes mappings and configurations for handling different types of files and resources.

When the `manifest.json` file does not exist, it should be built automatically from the contents of the `contents/` directory.

Specification	File name	<code>manifest.json</code>
	Location	Root directory of the package
	Content	JSON format, specifying the resources, their versions, and configurations.

Example:

```
{
  "resources": {
    "index.html": {
      "type": "text/html",
      "version": "1.0.0"
    },
    "styles.css": {
      "type": "text/css",
      "version": "1.0.0"
    },
    "app.js": {
      "type": "application/javascript",
      "version": "1.0.0"
    },
    "dynamic-content.js": {
      "type": "application/javascript",
      "version": "1.0.0"
    },
    "mobile.css": {
      "type": "text/css",
      "version": "1.0.0"
    },
    "desktop.css": {
      "type": "text/css",
      "version": "1.0.0"
    },
    "images/small.jpg": {
      "type": "image/jpeg",
      "version": "1.0.0"
    },
    "images/medium.jpg": {
      "type": "image/jpeg",
      "version": "1.0.0"
    },
    "images/large.jpg": {
      "type": "image/jpeg",
      "version": "1.0.0"
    },
    "content/en/index.html": {
      "type": "text/html",
      "version": "1.0.0"
    },
    "content/en/about.html": {
      "type": "text/html",
      "version": "1.0.0"
    },
    "content/es/index.html": {
      "type": "text/html",
      "version": "1.0.0"
    },
    "content/es/about.html": {
      "type": "text/html",
      "version": "1.0.0"
    }
  }
}
```

}

Figure 25**5.4.2. Content visibility**

Content visibility in the Capsium package is managed through the `manifest.json` file, where resources can be designated as either exported or private. This designation determines whether the resource can be re-used by other packages or is restricted to the current package.

- | | |
|---------------------------------|---|
| Requirements and Specifications | <ol style="list-style-type: none"> 1) Resource Declaration: <ul style="list-style-type: none"> — Resources must be declared in the <code>manifest.json</code> file. — Each resource entry should include the path to the resource and its visibility status. 2) Visibility Options: <ul style="list-style-type: none"> Exported Resources marked as <code>exported</code> are available for re-use by other packages that depend on the current package. Private Resources marked as <code>private</code> are restricted to the current package and cannot be accessed by other packages. 3) Example Configuration: <ul style="list-style-type: none"> — An example <code>manifest.json</code> file demonstrating resource visibility: |
|---------------------------------|---|

```

{
  "resources": [
    {
      "path": "scripts/main.js",
      "visibility": "exported"
    },
    {
      "path": "styles/theme.css",
      "visibility": "private"
    },
    {
      "path": "images/logo.png",
      "visibility": "exported"
    }
  ]
}

```

Figure 26

- 1) Usage in Dependent Packages:
 - Packages that depend on another package can access resources marked as exported by including the appropriate references in their own configuration files.
 - Example usage in a dependent package:

```

{
  "dependencies": {
    "capsium-core": "1.0.0"
  },
  "resources": [
    {
      "path": "node_modules/capsium-core/scripts/main.js",
      "visibility": "exported"
    }
  ]
}

```

}

Figure 27

- 1) Enforcement:
 - The Capsium system should enforce visibility rules, ensuring that private resources are not accessible to other packages.
 - Attempts to access private resources from other packages should result in an error, maintaining the integrity of resource boundaries.

By clearly defining and adhering to these visibility rules, the Capsium package ensures that resource bundling is both flexible and secure, allowing for effective re-use of assets while protecting private resources.

5.5. Root file

The root file of a Capsium package serves as the main entry point and must be an HTML file. This file is crucial as it defines the primary structure and content that the system should load or render.

5.5.1. Requirements for Root File

- 1) File Type:
 - The root file must be an HTML file. It should have an `.html` extension.
- 2) File Location:
 - The root file should be located within the package directory.
 - The path to the root file should be specified relative to the root directory of the package.
- 3) File Naming:
 - The root file should have a clear and descriptive name, commonly named `index.html` or `main.html`.
- 4) Entry Point Specification:
 - The path to the root HTML file should be accurately specified in the `index` key of the `routes.json` file.
 - Ensure the path does not contain typos or incorrect directory names.
- 5) Content Requirements:
 - The HTML file should include the necessary structure (`<html>`, `<head>`, and `<body>` tags).
 - It must be well-formed and valid HTML to ensure proper rendering and functionality.

5.5.2. Examples of Root File

- 1) Basic HTML Entry Point:

```
{
  "index": "public/index.html"
}
```

Figure 28

- This specifies that the root file for the package is `index.html` located in the `public` directory.
- 1) HTML Entry Point in Documentation Directory:

```
{
  "index": "docs/main.html"
}
```

Figure 29

- This specifies that the root file for the package is `main.html` located in the `docs` directory.

1) HTML Entry Point in Web Directory:

```
{
  "index": "web/index.html"
}
```

Figure 30

— This specifies that the root file for the package is `index.html` located in the web directory.

1) HTML Entry Point in Dist Directory:

```
{
  "index": "dist/index.html"
}
```

Figure 31

— This specifies that the root file for the package is `index.html` located in the dist directory.

1) HTML Entry Point in Root Directory:

```
{
  "index": "index.html"
}
```

Figure 32

— This specifies that the root file for the package is `index.html` located in the root directory of the package.

Example:

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <meta name="viewport" content="width=device-width, initial-scale=1.0">
  <title>Capsium Package</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <h1>Welcome to the Capsium Package</h1>
  <script src="app.js"></script>
</body>
</html>
```

Figure 33

5.6. Resource bundling

5.6.1. General

Resource bundling involves packaging all necessary static and dynamic content within the Capsium package to ensure that the package is self-contained and can be served efficiently.

The content include:

Static content	Includes HTML, CSS, JS, images, and other media files.
----------------	--

Dynamic content	Although primarily static, the package can include references to dynamic content handled by client-side scripts.
Conditional alternative content	The package can include alternative content that is conditionally loaded based on specific criteria, such as files with alternative image resolutions.

Example directory structure:

```
example-capsium-package/
├── index.html
├── styles.css
├── app.js
├── dynamic-content.js
├── mobile.css
├── desktop.css
├── images/
│   ├── small.jpg
│   ├── medium.jpg
│   └── large.jpg
├── content/
│   ├── en/
│   │   ├── index.html
│   │   └── about.html
│   └── es/
│       ├── index.html
│       └── about.html
├── metadata.json
├── manifest.json
├── routes.json
├── LICENSE.spdx
└── README.md
```

Figure 34

5.6.2. Static Content

Static content includes files that do not change once the package is created and can be directly served to the client. These files are essential for the visual and functional aspects of the web application.

HTML Files	These files define the structure and layout of web pages. They typically include elements like headers, paragraphs, links, and embedded resources such as images and scripts.
------------	---

Example:

Figure 35

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <title>Example Page</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <h1>Welcome to Example Page</h1>
  <script src="app.js"></script>
</body>
```

```
</html>
```

Figure 36

CSS Files These files define the styles for HTML elements, specifying colors, fonts, layouts, and other visual aspects.

Example (pass:c,q,a,m,p[`styles.css`]):

Figure 37

```
body {
  font-family: Arial, sans-serif;
  background-color: #f0f0f0;
}
h1 {
  color: #333;
}
```

Figure 38

JavaScript Files These files contain client-side scripts that add interactivity and dynamic behavior to the web pages.

Example (pass:c,q,a,m,p[`app.js`]):

Figure 39

```
document.addEventListener('DOMContentLoaded', () => {
  console.log('Page loaded');
});
```

Figure 40

Images and Media Files These include JPEG, PNG, GIF images, SVG graphics, and other media files like videos and audio clips that are used within the web pages.

Example:

Figure 41

```
example-capsium-package/
├── images/
│   ├── logo.png
│   └── banner.jpg
```

Figure 42

5.6.3. Dynamic Content

Dynamic content refers to content that can change or be generated on the fly, typically handled by client-side scripts. While the package itself is primarily static, it can include references to dynamic content.

Client-side Scripts JavaScript files that fetch and display dynamic content from APIs or other sources at runtime.

Example (pass:c,q,a,m,p[`dynamic-content.js`]):

Figure 43

```
fetch('https://api.example.com/data')
  .then(response => response.json())
  .then(data => {
    document.getElementById('dynamic-
content').innerText = data.message;
  });
```

Figure 44

Dynamic References Links and scripts that point to external resources or APIs that provide dynamic data.

Example (pass:c,q,a,m,p[`index.html`]):

Figure 45

```
<div id="dynamic-content"></div>
<script src="dynamic-content.js"></script>
```

Figure 46

5.6.4. Conditional Alternative Content

Conditional alternative content allows the package to include multiple versions of a resource, with the appropriate version being loaded based on specific criteria. This can enhance performance and provide a better user experience.

Alternative Image Resolutions Including images in multiple resolutions and loading the appropriate one based on the device's screen resolution.

Example (pass:c,q,a,m,p[`index.html`]):

Figure 47

```


```

Figure 48

Content for Different Languages Providing content in multiple languages and loading the appropriate version based on the user's language preferences.

Example:

Figure 49



```
| | └─ about.html
```

Figure 50

JavaScript to load language-specific content (pass: `c,q,a,m,p[`language-loader.js`]`):

Figure 51

```
const userLang = navigator.language ||
navigator.userLanguage;
const contentPath = userLang.startsWith('es') ?
'content/es/' : 'content/en/';
fetch(contentPath + 'index.html')
  .then(response => response.text())
  .then(html => {
    document.body.innerHTML = html;
  });
```

Figure 52

Device-Specific
Content

Serving different versions of content based on the type of device (e.g., mobile vs. desktop).

Example:

Figure 53

```
<link rel="stylesheet" media="screen and (max-width:
600px)" href="mobile.css">
<link rel="stylesheet" media="screen and (min-width:
601px)" href="desktop.css">
```

Figure 54

5.7. Resource routing

5.7.1. General

Resource routing defines how requests to the Capsium package are handled and routed.

The `routes.json` file is the central configuration for routing within your package. It maps URL paths to resources or handlers, including both static data and dynamic HTTP API routes.

The routing file `routes.json` is the single source of truth for routing in the package, simplifying management and ensuring consistency. This setup covers static resource routing, dynamic API endpoints, and the essential configurations for headers and HTTP methods.

When the `routes.json` file doesn't exist, automatically generate it based on the contents in the manifest. When it is an HTML file, create 2 routes, one with the file's base name, one with the full file name. When a file of another type, generate the route relative from the `content/` path.

Example `routes.json`

```
{
  "index": "index.html",
  "routes": [
    // Static resource routes
    {
      "path": "/",
```

```

    "resource": "index.html"
  },
  {
    "path": "/styles.css",
    "resource": "styles.css"
  },
  {
    "path": "/app.js",
    "resource": "app.js"
  },
  {
    "path": "/images/small.jpg",
    "resource": "images/small.jpg"
  },
  {
    "path": "/data/users",
    "resource": "data/users.json"
  },
  {
    "path": "/data/products",
    "resource": "data/products.json"
  },
  // HTTP API routes
  {
    "path": "/api/v1/users",
    "method": "GET",
    "handler": "api/v1/users/getUsers.js"
  },
  {
    "path": "/api/v1/users",
    "method": "POST",
    "handler": "api/v1/users/createUser.js"
  },
  {
    "path": "/api/v1/users/:id",
    "method": "PUT",
    "handler": "api/v1/users/updateUser.js"
  },
  {
    "path": "/api/v1/users/:id",
    "method": "DELETE",
    "handler": "api/v1/users/deleteUser.js"
  }
]
}

```

Figure 55

In this example, the `routes.json` file includes routes for both static resources (like HTML, CSS, images, and data files) and dynamic HTTP API endpoints.

5.7.2. Index route

The `index` key in the `routes.json` file designates the entry point or root file of the Capsium package. This key is crucial for defining the primary file that the system should load or execute.

5.7.2.1. Requirements for index Key

- 1) File Path:

- The index key should be a string representing the relative path to the root file from the root directory of the package.
 - The path should be valid and point to an existing file within the package.
- 2) File Type:
 - The root file can be of various types depending on the nature of the package (e.g., JavaScript, HTML, JSON). Ensure the file type is appropriate for the package's purpose.
 - 3) Uniqueness:
 - There should be only one index key in the `routes.json` file, specifying a single root file.
 - 4) Consistency:
 - The path specified by the index key should be consistent with the project's structure and should not include typos or incorrect directory names.

5.7.2.2. Examples of index Key

HTML Entry Point

```
{
  "index": "public/index.html"
}
```

Figure 56

- This specifies that the root file for the package is `index.html` located in the `public` directory.

By adhering to these requirements and examples, the `index` key in the `routes.json` file ensures that the Capsium package has a clearly defined entry point, facilitating proper loading and execution of the package.

5.7.3. Dataset routes

Mounting routes to data sets involves configuring specific endpoints that provide access to various data sets within the package. This allows for organized and efficient data retrieval, enabling users to access the data they need through well-defined routes. All data route mounts will use the HTTP path mount point `/api/v1/data/` as the root.

Route definition	Specifies the URL path that will be used to access the data set, using <code>/api/v1/data/</code> as the root.
Data source	Defines the source of the data, such as a file path, database query, or external API.
Access control	Configurations to manage who can access the data and under what conditions.
Response format	Specifies the format in which the data will be returned, such as JSON, XML, or CSV.

Dataset routes should be mounted as specified in `routes.json`, with each route pointing to a key dataset that is provided in `storage.json`.

Example of `storage.json`:

```
{
  "storage": {
    "dataSets": {
      "users": {
        "source": "db/users",
      },
      "products": {
        "source": "files/products.json",
      },
    },
  },
}
```

```

        "sales": {
            "source": "api/external/sales",
        }
    }
}

```

Figure 57

Example of routes.json:

```

{
  "routes": [
    {
      "route": "/api/v1/data/users",
      "dataset": "users",
      "accessControl": {
        "roles": ["admin", "user"],
        "authenticationRequired": true
      }
    },
    {
      "route": "/api/v1/data/products",
      "dataset": "products",
      "accessControl": {
        "roles": ["admin"],
        "authenticationRequired": true
      }
    },
    {
      "route": "/api/v1/data/sales",
      "dataset": "sales",
      "accessControl": {
        "roles": ["admin"],
        "authenticationRequired": true
      }
    }
  ]
}

```

Figure 58

In this example, routes.json defines three routes, each pointing to a data set specified in storage.json:

- | | |
|-------------------|---|
| Users data set | <ul style="list-style-type: none"> — Route: /api/v1/data/users — Dataset: users (refers to the users key in storage.json) — Access control: Only accessible by users with admin or user roles, and authentication is required. |
| Products data set | <ul style="list-style-type: none"> — Route: /api/v1/data/products — Dataset: products (refers to the products key in storage.json) — Access control: Only accessible by users with the admin role, and authentication is required. |
| Sales data set | <ul style="list-style-type: none"> — Route: /api/v1/data/sales — Dataset: sales (refers to the sales key in storage.json) — Access control: Only accessible by users with the admin role, and authentication is required. |

5.7.4. Attributes summary

Table 1 — Table 1: Storage Attributes

Attribute	Description
Storage	The root object for storage configuration.

Table 2 — Table 2: DataSets Attributes (in storage.json)

Attribute	Description
Source	The source of the data (e.g., database path, file path, external API URL).
Response format	The format in which the data will be returned (e.g., json, xml, csv).

Table 3 — Table 3: Routes Attributes (in routes.json)

Attribute	Description
Route	The URL path for accessing the data set, starting with /api/v1/data/.
Dataset	The key in storage.json that this route points to.
Access control	Object containing access control settings.

Table 4 — Table 4: Access Control Attributes

Attribute	Description
Roles	Specifies the roles that are allowed to access the data set.
Authentication required	Specifies whether authentication is required to access the data set.

By configuring these attributes, Capsium packages can effectively manage data storage and provide structured access to data sets through defined routes. This ensures data can be securely and efficiently retrieved by authorized users.

5.7.5. Header responses

5.7.5.1. General

In the Capsium package, resource routing allows you to map URLs to specific resources and define how they should be handled. One crucial aspect of resource routing is defining header responses, which can be done directly in the routes.json file or via external files.

5.7.5.2. Inline declarations

You can specify header responses directly within the routes.json file. This approach embeds the header definitions within the routing configuration, making it straightforward to manage.

Example:

```
{
  "routes": {
    "/api/resource": {
      "GET": {
        "file": "handlers/getResource.js",
        "headers": {
          "Content-Type": "application/json",
          "Cache-Control": "no-cache",
          "Access-Control-Allow-Origin": "*"
        }
      },
      "POST": {
        "file": "handlers/postResource.js",
        "headers": {
          "Content-Type": "application/json",
          "Access-Control-Allow-Origin": "*"
        }
      }
    }
  }
}
```



```

    }
  }
}

```

Figure 59

In this example: - The GET method for /api/resource has headers defined directly in the routes . json file. - The POST method for /api/resource also defines its headers directly.

5.7.5.3. Declaring through external files

Alternatively, you can manage header definitions in external files, which can be useful for maintaining cleaner and more modular configurations.

Example:

```

{
  "routes": {
    "/api/resource": {
      "GET": {
        "file": "handlers/getResource.js",
        "headersFile": "headers/getResourceHeaders.json"
      },
      "POST": {
        "file": "handlers/postResource.js",
        "headersFile": "headers/postResourceHeaders.json"
      }
    }
  }
}

```

Figure 60

In this example: - The GET method for /api/resource references an external file headers / getResourceHeaders . json for headers. - The POST method for /api/resource references an external file headers / postResourceHeaders . json for headers.

The content of headers / getResourceHeaders . json might look like this:

```

{
  "Content-Type": "application/json",
  "Cache-Control": "no-cache",
  "Access-Control-Allow-Origin": "*"
}

```

Figure 61

And headers / postResourceHeaders . json might look like this:

```

{
  "Content-Type": "application/json",
  "Access-Control-Allow-Origin": "*"
}

```

Figure 62

By using these mechanisms, you can effectively manage and define header responses in the Capsium package, either directly within the routes . json file or through external files for better modularity and maintainability.

5.7.6. Route visibility

Route visibility in the Capsium package is managed through the `routes.json` file, where routes can be designated as either exported or private. This designation determines whether the route can be re-used by other packages or is restricted to the current package.

- | | |
|---------------------------------|---|
| Requirements and Specifications | <ol style="list-style-type: none"> 1) Route Declaration: <ul style="list-style-type: none"> — Routes must be declared in the <code>routes.json</code> file. — Each route entry should include the path to the resource and its visibility status. 2) Visibility Options: <ul style="list-style-type: none"> Exported Routes marked as exported are available for re-use by other packages that depend on the current package. Private Routes marked as private are restricted to the current package and cannot be accessed by other packages. 3) Example Configuration: <ul style="list-style-type: none"> — An example <code>routes.json</code> file demonstrating route visibility: |
|---------------------------------|---|

```
{
  "routes": [
    {
      "path": "/api/public",
      "handler": "publicHandler",
      "visibility": "exported"
    },
    {
      "path": "/api/private",
      "handler": "privateHandler",
      "visibility": "private"
    }
  ]
}
```

Figure 63

5.7.7. Route Inheritance and Processing

The Capsium package supports inheriting routes from dependency packages, allowing for remapping, rewriting responses, enhancing response headers, or supplanting request headers. This flexibility enables packages to extend and modify the behavior of routes defined in their dependencies.

- | | |
|---------------------------------|--|
| Requirements and Specifications | <ol style="list-style-type: none"> 1) Inheriting Routes: <ul style="list-style-type: none"> — Inherited routes must be declared in the <code>routes.json</code> file of the dependent package. — An inherited route should specify the package and the original route path. 2) Remapping Routes: <ul style="list-style-type: none"> — Inherited routes can be remapped to a new path in the dependent package. 3) Rewriting Responses: <ul style="list-style-type: none"> — The system should allow for rewriting the response of an inherited route, either by modifying the content or altering the headers. 4) Enhancing Response Headers: |
|---------------------------------|--|

- Additional headers can be added to the response of an inherited route to enhance security, performance, or other attributes.
- 5) Supplanting Request Headers:
 - Request headers can be modified or added before forwarding the request to the inherited route.
- 6) Example Configuration:
 - An example routes.json file demonstrating route inheritance and processing:

```
{
  "dependencies": {
    "capsium-core": "1.0.0"
  },
  "routes": [
    {
      "path": "/api/exported",
      "handler": "node_modules/capsium-core/handlers/publicHandler",
      "visibility": "exported"
    },
    {
      "path": "/api/remapped",
      "handler": "node_modules/capsium-core/handlers/publicHandler",
      "visibility": "private",
      "remap": "/api/newpath"
    },
    {
      "path": "/api/rewritten",
      "handler": "node_modules/capsium-core/handlers/publicHandler",
      "visibility": "private",
      "responseRewrite": {
        "body": "Modified response content",
        "headers": {
          "X-Custom-Header": "CustomValue"
        }
      }
    },
    {
      "path": "/api/enhanced",
      "handler": "node_modules/capsium-core/handlers/publicHandler",
      "visibility": "exported",
      "responseHeaders": {
        "Cache-Control": "no-cache",
        "X-Enhanced-Header": "EnhancedValue"
      }
    },
    {
      "path": "/api/supplanted",
      "handler": "node_modules/capsium-core/handlers/publicHandler",
      "visibility": "private",
      "requestHeaders": {
        "Authorization": "Bearer new-token",
        "X-Forwarded-For": "client-ip"
      }
    }
  ]
}
```

Figure 64

By clearly defining and adhering to these visibility, inheritance, and processing rules, the Capsium package ensures that resource routing is both flexible and secure, enabling effective re-use of routes while protecting private routes and allowing for extensive customization.

5.8. Storage

The Capsium package includes a comprehensive storage system that supports layered storage with a unified merged filesystem view, static data files, and databases. This section outlines the requirements and specifications for each storage type.

A Capsium package can contain datasets. Each dataset is composed of data items. A dataset can be one of:

Layered storage	Utilizes a unified merged filesystem view, similar to overlay FS, to manage different layers of content.
Static File with Structured Data	Formats such as CSV, JSON, YAML.
Backed by Schemas	Formats that use JSON Schema or YAML Schema for validation.
Static data files	Contains immutable data files that are part of the package.
Databases	Includes support for embedded databases such as SQLite to store structured data (if supported by the Capsium reactor).

5.8.1. Defining datasets

Datasets are explicitly defined, and are referred by other components, such as [Clause 5.7.3](#).

source Defines the source of the data, such as a file path, database query, or external API.

Example:

```
{
  "storage": {
    "dataSets": {
      "users": {
        "source": "db/users",
      },
      "products": {
        "source": "files/products.json",
      },
      "sales": {
        "source": "api/external/sales",
      }
    }
  }
}
```

Figure 65

5.8.2. Layered storage

Layered storage in the Capsium package allows for multiple storage layers to be combined into a single, unified filesystem view, similar to the functionality of “overlay FS.” This approach ensures that changes can be made in a non-destructive manner while preserving the original data.

Requirements and Specifications

- 1) Layer Structure:
 - The storage system must support multiple layers, where each layer can be read-only or writable.
 - Layers should be stacked in a specified order, with the topmost layer being the most recent.
- 2) Unified View:
 - The system must present a single filesystem view that merges all layers.
 - File access should respect the layer order, with the topmost layer taking precedence in case of conflicts.
- 3) Non-destructive Changes:
 - Changes should be written to the topmost writable layer, preserving lower layers intact.
 - Deletions in higher layers should not physically remove the files from lower layers but should mark them as deleted in the unified view.
- 4) Configuration:
 - The configuration for layered storage should be specified in a `manifest.json` file.
 - Example:

```
{
  "layers": [
    {
      "path": "base",
      "writable": false,
      "visibility": "exported"
    },
    {
      "path": "updates",
      "writable": true,
      "visibility": "private"
    }
  ]
}
```

Figure 66

- The `visibility` field determines if the layer is exposed as an inheritable interface (`exported`) or kept private (`private`).

5.8.3. Static data files

Static data files are immutable files that are served directly by the Capsium package. These files typically include assets such as images, stylesheets, and JavaScript files.

Requirements and Specifications

- 1) Storage Location:
 - Static data files must be stored in a designated directory, such as `static` or `public`.
- 2) Access Path:
 - Static files should be accessible via predictable URL paths, typically mirroring their directory structure.
 - Example: `/static/images/logo.png` should map to `static/images/logo.png` in the filesystem.
- 3) Caching:
 - Static files should be served with appropriate caching headers to improve performance.
 - Example:

Cache-Control: public, max-age=31536000

Figure 67

1) Configuration:

- The location of static files should be defined in the `routes.json` file.
- Example:

```
{
  "static": {
    "path": "static",
    "url": "/static"
  }
}
```

Figure 68

5.8.4. Datasets

Datasets in the Capsium package provide structured storage for dynamic data that requires querying and transactional operations.

JSON schema or YAML schema for datasets using static files like JSON or YAML in the `storage.json` configuration file.

5.8.4.1. Schema-backed file datasets

When working with datasets in static file formats such as JSON or YAML, it's important to validate the data against a predefined schema. This ensures the data adheres to the expected structure and types. The `storage.json` configuration file can include references to these schemas.

The `storage.json` file should be structured to include the following attributes for each dataset:

<code>datasetId</code>	Identifier for the dataset.
<code>dataFile</code>	Path to the static data file (JSON or YAML).
<code>schemaFile</code>	Path to the schema file (JSON Schema or YAML Schema).
<code>schemaType</code>	Type of the schema (e.g., "json-schema" or "yaml-schema").

Example structure: ``json { "datasets": [ { "datasetId": "dataset1", "dataFile": "/path/to/datafile.json", "schemaFile": "/path/to/schemafile.json", "schemaType": "json-schema" }, { "datasetId": "dataset2", "dataFile": "/path/to/datafile.yaml", "schemaFile": "/path/to/schemafile.yaml", "schemaType": "yaml-schema" } ] }``

Here's an example of a JSON schema for validating a dataset of user information: ``json { "$schema": "http://json-schema.org/draft-07/schema#", "type": "object", "properties": { "users": { "type": "array", "items": { "type": "object", "properties": { "id": { "type": "string" }, "name": { "type": "string" }, "email": { "type": "string", "format": "email" } }, "required": ["id", "name", "email"] } }, "required": ["users"] }``

Here's an example of a YAML schema for validating a dataset of user information: ``yaml %YAML 1.2 --- $schema: "http://json-schema.org/draft-07/schema#" type: "object" properties: users: type: "array" items: type: "object" properties: id: type: "string" name: type: "string" email: type: "string" format: "email" required: — id — name — email required: — users``

5.8.4.2. SQLite database

In addition to static file formats like JSON and YAML, datasets can also be stored in SQLite databases. This section explains how to configure SQLite datasets in the `storage.json` file.

The `storage.json` file should include the following attributes for each SQLite dataset:

<code>datasetId</code>	Identifier for the dataset.
<code>databaseFile</code>	Path to the SQLite database file.
<code>schemaFile</code>	Path to the schema file (SQL schema or JSON schema for defining table structures).
<code>schemaType</code>	Type of the schema (e.g., "sql-schema" or "json-schema").
<code>table</code>	Name of the table in the SQLite database that the dataset corresponds to.

Example structure: ``json { "datasets": [{ "datasetId": "dataset1", "databaseFile": "/path/to/database.sqlite", "schemaFile": "/path/to/schemafile.sql", "schemaType": "sql-schema", "table": "users" }, { "datasetId": "dataset2", "databaseFile": "/path/to/another_database.sqlite", "schemaFile": "/path/to/schemafile.json", "schemaType": "json-schema", "table": "products" }] } ``

Here's an example of an SQL schema for a table of user information: ``sql CREATE TABLE users ( id TEXT PRIMARY KEY, name TEXT NOT NULL, email TEXT NOT NULL UNIQUE ); ``

Here's an example of a JSON schema for validating the structure of a table of user information: ``json { "$schema": "http://json-schema.org/draft-07/schema#", "type": "object", "properties": { "id": { "type": "string" }, "name": { "type": "string" }, "email": { "type": "string", "format": "email" } }, "required": ["id", "name", "email"] } ``

5.8.4.3. Validation

To validate the datasets in a YAML, JSON dataset or a SQLite database against their respective schemas, you can use various tools and libraries depending on the programming language.

5.8.5. REST API for data access and modification

This is the HTTP REST API that the Capsium reactor offers for an activated Capsium package to the HTTP user. The following endpoints are supported for all datasets, as defined in `storage.json`.

5.8.5.1. GET (Fetch Data)

Endpoint	<code>/dataset/{datasetId}/data</code>
Method	GET
Description	Fetches all data items from the specified dataset.
datasetId	Request Attributes
	The identifier of the dataset. Must be a string.
status	Response
	200 OK on success.
body	An array of data items.

Example: ``json { "datasetId": "dataset1" } ``

5.8.5.2. GET (Fetch Single Data Item)

Endpoint	/dataset/{datasetId}/data/{dataId}
Method	GET
Description	Fetches a single data item from the specified dataset.
Request Attributes	
datasetId	The identifier of the dataset. Must be a string.
dataId	The identifier of the data item to be fetched. Must be a string.
Response	
status	200 OK on success.
body	The requested data item.

Example: ``json { "datasetId": "dataset1", "dataId": "dataItem42" } ``

5.8.5.3. POST (Create Data Item)

Endpoint	/dataset/{datasetId}/data
Method	POST
Description	Adds a new data item to the specified dataset.
Request Attributes	
datasetId	The identifier of the dataset. Must be a string.
data	The data item to be added. Must conform to the dataset's schema.
Response	
status	201 Created on success.
body	The created data item with its new identifier.

Example: ``json { "datasetId": "dataset1", "data": { "key1": "value1", "key2": 123 } } ``

5.8.5.4. PUT (Update Data Item)

Endpoint	/dataset/{datasetId}/data/{dataId}
Method	PUT
Description	Updates an existing data item in the specified dataset.
Request Attributes	
datasetId	The identifier of the dataset. Must be a string.
dataId	The identifier of the data item to be updated. Must be a string.
data	The updated data item. Must conform to the dataset's schema.
Response	

status	200 OK on success.
body	The updated data item.

Example: ``json { "datasetId": "dataset1", "dataId": "dataItem42", "data": { "key1": "newValue", "key2": 456 } }``

5.8.5.5. DELETE (Delete Data Item)

Endpoint	/dataset/{datasetId}/data/{dataId}
Method	DELETE
Description	Deletes a data item from the specified dataset.
Request Attributes	
datasetId	The identifier of the dataset. Must be a string.
dataId	The identifier of the data item to be deleted. Must be a string.
Response	
status	204 No Content on success.

Example: ``json { "datasetId": "dataset1", "dataId": "dataItem42" }``

5.8.6. Data Persistence

5.8.6.1. General

A Capsium package containing data may allow modification of data inside the included datasets. Configuration needs to be specified in the package on which data files can be modified or updated.

Since a Capsium package at its core is immutable, the mechanism for handling modifications is by storing action patches in an "action history" folder. This folder can be external to the Capsium package or inside a composite Capsium package. Each data change is stored as a separate patch file.

When a Capsium reactor loads a Capsium package with an action history folder, it will replay those actions on top of the dataset so that the changes persist for users who access the activated Capsium package.

5.8.6.2. Action patch

An action patch represents a single change to a dataset. The following attributes are required:

timestamp	The time when the change was made. Must be in ISO 8601 format (e.g., 2024-05-28T12:34:56Z).
user	The identifier of the user who made the change. Should be a string.
action	The type of action performed. Enumerated values: add, update, delete.
datasetId	The identifier of the dataset affected by the action. Should be a string.
dataId	The identifier of the data item affected by the action. Should be a string.
changes	A JSON object detailing the changes made. The format depends on the type of action.

Example: ``json { "timestamp": "2024-05-28T12:34:56Z", "user": "user123", "action": "update", "datasetId": "dataset1", "dataId": "dataItem42", "changes": { "key1": "newValue" } } ``

5.8.6.3. Action history folder

The action history folder stores all action patches. The folder must have the following structure and attributes:

Location	Can be external to the Capsium package or inside a composite Capsium package.
Structure	Each action patch is stored as a separate file within the folder.
Filename Convention	Each file name should be unique and can be based on the timestamp and user ID (e.g., 20240528T123456Z_user123_update_dataItem42.json).
File Content	Each file must contain a valid action patch JSON object as specified above.

Example: `` action-history/ |—— 20240528T123456Z_user123_update_dataItem42.json |—— 20240529T101112Z_user456_add_dataItem43.json |—— ... ``

Additional requirements for the action history folder:

Access Control	The folder must be secured to prevent unauthorized access. Only designated users or systems should have read/write access.
Backup	Regular backups of the action history folder should be maintained to prevent data loss.
Versioning	Each action patch should include a version attribute to manage changes to the action patch schema.

Example of an action patch with versioning: ``json { "version": "1.0", "timestamp": "2024-05-28T12:34:56Z", "user": "user123", "action": "update", "datasetId": "dataset1", "dataId": "dataItem42", "changes": { "key1": "newValue" } } ``

5.8.6.4. Saving Data Changes in Datasets to a New External Capsium Package

To save data changes in datasets to a new external Capsium package, the following configuration is required:

Configuration File	save-external.json	
Attributes	originalPackageId	The identifier of the original Capsium package. Must be a string.
	newPackageId	The identifier for the new external Capsium package. Must be a string.
	actionHistoryLocation	The location of the action history folder. Must be a valid path.

Example: ``json { "originalPackageId": "capsiumPkg1", "newPackageId": "capsiumPkg2", "actionHistoryLocation": "/path/to/action-history" } ``

The process for saving data changes includes the following steps:

- 1) Identify Changes: Collect all action patches related to the dataset modifications.
- 2) Create New Package: Generate a new Capsium package structure.
- 3) Include Action Patches: Copy the action patches to the new package's action history folder.
- 4) Update Metadata: Modify the `storage.json` and other relevant configuration files to reflect the new package and its contents.
- 5) Validate Package: Ensure that the new package meets all Capsium package requirements and is properly versioned.

Example process: ``shell # Collect action patches cp /path/to/action-history/* /new-package/action-history/``

6. Create new package structure

```
mkdir /new-package cp -r /original-package/* /new-package/
```

7. Update metadata

```
jq '.packages += [{ "id": "capsiumPkg2", "actionHistoryLocation": "/new-package/action-history" }]' /new-package/storage.json > /new-package/storage_tmp.json mv /new-package/storage_tmp.json /new-package/storage.json
```

8. Validate package

```
capsium-validate /new-package `
```

Additional considerations for creating a new external Capsium package:

Integrity Checks	Perform integrity checks to ensure that all data items and action patches are correctly included and no data corruption has occurred.
Documentation	Update the package documentation to reflect the changes and new version information.
Notification	Notify users or systems that depend on the package about the update to the new package.

Example of integrity check: ``shell capsium-check-integrity /new-package ``

Example of updating documentation: ``markdown # Capsium Package Documentation``

8.1. Package ID: capsiumPkg2

Description	This package includes updated datasets from capsiumPkg1 with action patches applied.
Version	2.0
Action History Location	<code>/new-package/action-history `</code>

8.1.1. Saving Data Changes in Datasets in a Composite Capsium Package That Contains the Current Package

To save data changes in datasets in a composite Capsium package, the following configuration is required:

Configuration File	save-composite.json	
Attributes	originalPackageId	The identifier of the original Capsium package. Must be a string.
	compositePackageId	The identifier for the composite Capsium package. Must be a string.
	internalActionHistoryPath	The path to the action history folder within the composite Capsium package. Must be a valid internal path.

Example: ``json { "originalPackageId": "capsiumPkg1", "compositePackageId": "compositeCapsiumPkg1", "internalActionHistoryPath": "internal/action-history" } ``

The process for saving data changes in a composite Capsium package includes the following steps:

- 1) Identify Changes: Collect all action patches related to the dataset modifications.
- 2) Create Composite Package Structure: Ensure that the composite package contains the current package and an action history folder.
- 3) Include Action Patches: Copy the action patches to the action history folder within the composite package.
- 4) Update Metadata: Modify the `storage.json` and other relevant configuration files to reflect the composite package and its contents.
- 5) Validate Package: Ensure that the composite package meets all Capsium package requirements and is properly versioned.

Example process: ``shell # Collect action patches cp /path/to/action-history/* /composite-package/internal/action-history/``

9. Create composite package structure

```
mkdir /composite-package/internal cp -r /original-package/* /composite-package/internal/
```

10. Update metadata

```
jq '.packages += [{"id": "compositeCapsiumPkg1", "internalActionHistoryPath": "internal/action-history"}]' /composite-package/storage.json > /composite-package/storage_tmp.json mv /composite-package/storage_tmp.json /composite-package/storage.json
```

11. Validate package

```
capsium-validate /composite-package `
```

Additional considerations for creating a composite Capsium package:

Dependency Management	Ensure that the composite package correctly references the current package and any other dependencies.
Namespace Handling	Manage namespaces to avoid conflicts between datasets from different packages.
Testing	Thoroughly test the composite package to ensure that the data changes are correctly applied and all functionalities work as expected.

Example of dependency management: ``json { "compositePackageId": "compositeCapsiumPkg1", "dependencies": [ { "packageId": "capsiumPkg1", "version": "1.0" } ], "internalActionHistoryPath": "internal/action-history" } ``

```
Example of namespace handling: `json { "datasetNamespaces": { "capsiumPkg1": "namespace1",  
"compositeCapsiumPkg1": "namespace2" } } `
```

Example of testing script: ``shell # Test script for composite package capsium-test /composite-package``

12. Validate composite package

capsium-validate /composite-package `

12.1. Security

12.1.1. General

Security is a critical aspect of the Capsium package, ensuring data integrity and protection. This section describes the requirements and specifications for implementing security features, with detailed use cases illustrating practical applications.

Digital signatures	The package can be signed digitally to verify its authenticity and integrity.
Integrity checks	Mechanisms to ensure that the package's content has not been tampered with.
Sandboxing packaged application	Isolates the execution of the package's content to prevent security breaches.

Example:

[illegible]

}

Figure 69

12.1.2. Digital Signatures

Requirements and Specifications	1) Digital Signature Implementation: <table border="0"> <tr> <td>publicKey</td> <td>Path to the public key file used for verifying the digital signature.</td> </tr> <tr> <td>Type</td> <td>string</td> </tr> <tr> <td>Example</td> <td>"path/to/public.key"</td> </tr> <tr> <td>signatureFilePath</td> <td>Path to the signature file that contains the digital signature.</td> </tr> <tr> <td>Type</td> <td>string</td> </tr> <tr> <td>Example</td> <td>"package.sig"</td> </tr> </table> 2) Verification Process: — The system must use the public key to verify the digital signature. — The verification process should ensure that the package has not been altered since it was signed.	publicKey	Path to the public key file used for verifying the digital signature.	Type	string	Example	"path/to/public.key"	signatureFilePath	Path to the signature file that contains the digital signature.	Type	string	Example	"package.sig"
publicKey	Path to the public key file used for verifying the digital signature.												
Type	string												
Example	"path/to/public.key"												
signatureFilePath	Path to the signature file that contains the digital signature.												
Type	string												
Example	"package.sig"												
Use Case	<table border="0"> <tr> <td>Package Distribution</td> <td>When distributing the Capsium package, the publisher signs the package with their private key. The recipient can then verify the package using the included public key to ensure it has not been tampered with.</td> </tr> </table>	Package Distribution	When distributing the Capsium package, the publisher signs the package with their private key. The recipient can then verify the package using the included public key to ensure it has not been tampered with.										
Package Distribution	When distributing the Capsium package, the publisher signs the package with their private key. The recipient can then verify the package using the included public key to ensure it has not been tampered with.												

Example Configuration

```
{
  "security": {
    "digitalSignatures": {
      "publicKey": "path/to/public.key",
      "signatureFile": "package.sig"
    }
  }
}
```

Figure 70

12.1.3. Integrity Checks

[illegible]

[illegible]

Figure 71

1) Integrity Verification:

- The system must verify the integrity of the package's content by comparing the calculated checksums with those in the manifest file.
- Any discrepancies must trigger an alert or rejection of the package.

Use Case	Content Integrity	After downloading the Capsium package, the system calculates checksums for all files and compares them to the provided checksums to ensure no files were altered during transit.
----------	-------------------	--

Example Configuration

[illegible]

Figure 72

Procedure to Calculate the Integrity Hash of a Capsium Package

- 1) Select the Checksum Algorithm:
 - Choose an algorithm from the supported options (e.g., SHA-256).
 - Example: `checksumAlgorithm: "SHA-256"`
- 2) Calculate Checksums:
 - For each file in the package, calculate the checksum using the selected algorithm.
 - Use a reliable tool or library to perform the checksum calculation.
 - Example command using `sha256sum`:

```
sha256sum index.html > checksums.txt
sha256sum styles.css >> checksums.txt
```

Figure 73

1) Create a Checksums Manifest:

- Compile the calculated checksums into a JSON object.
- Ensure the file paths are correctly mapped to their respective checksums.
- Example:

[illegible]

}

Figure 74

- 1) Store the Checksum Manifest:
 - Save the checksum manifest file (e.g., `checksums.json`) within the package.
 - Ensure this file is included when distributing the package.
- 2) Verify the Integrity:
 - Upon receiving the package, recalculate the checksums for each file using the same algorithm.
 - Compare the newly calculated checksums with those in the `checksums.json` manifest.
 - If all checksums match, the package integrity is verified. If any checksum does not match, reject the package as it may have been tampered with.

12.1.4. Sandboxing Packaged Applications

Requirements and Specifications	1) Sandboxing Environment:	
	enabled	Indicates whether sandboxing is enabled.
	Type	boolean
	Values	true, false
	Example	true
	parameters	An object specifying resource limits for the sandbox.
	Type	object
	Attributes	memoryLimit: The maximum amount of memory allocated to the sandbox.
		Type: number
		Example: 512
Use Case		
	Running Untrusted Code	When deploying a Capsium package that contains untrusted or third-party code, the sandbox ensures that the code runs in isolation, preventing it from affecting the host system.
Example Configuration		

```

{
  "security": {
    "sandboxing": {
      "enabled": true,

```



```
        "parameters": {
            "memoryLimit": "512MB",
            "cpuLimit": 2
        }
    }
}
```

Figure 75

By implementing these security features, including a detailed procedure for calculating and verifying integrity hashes, the Capsium package ensures high standards of data integrity and protection, safeguarding both the package content and the systems it interacts with.

12.2. Encrypted information

12.2.1. General

The Capsium package can contain both encrypted and cleartext content. Encryption uses public/private keys and data encryption keys (DEK) with the OCB algorithm or OpenPGP to ensure security.

This section details the requirements and specifications for each aspect of encryption, along with relevant use cases and how encrypted files interact with routes.json and manifest.json.

Example:

```
{
  "encryption": {
    "publicKeyFile": "path/to/public.key",
    "encryptedFiles": [
      {
        "file": "secret.dat",
        "encryptedWith": "DEK",
        "algorithm": "OCB"
      }
    ]
  }
}
```

Figure 76

12.2.2. Public Key File

Requirements and Specifications	1) publicKeyFile:	
	Description	Path to the public key file used for encrypting the Data Encryption Key (DEK) or directly encrypting files using OpenPGP.
	Type	string
	Value	— Must be a valid file path.
	Requirements	— The file should exist and be accessible.
		— Example: "path/to/public.key"
Use Case	Encrypting DEK	When encrypting sensitive files, the DEK is encrypted using the recipient's public key to ensure that only the recipient, who possesses the corresponding private key, can decrypt the DEK and subsequently the files.

OpenPGP Encryption Files can be directly encrypted using OpenPGP with the recipient's public key, ensuring secure transmission and storage.

Example Configuration

```
{
  "encryption": {
    "publicKeyFile": "path/to/public.key"
  }
}
```

Figure 77

12.2.3. Encrypted Files

Requirements and Specifications

1) encryptedFiles:	Description	List of files within the package that are encrypted.
Type	array	
Items	file	
encryptedWith	Description	Indicates the method used for encryption.
Type	string	
Enumeration:	Definition:	
	"OpenPGP"	
Value	Must	
Requirements:		
	"DEK"	
	or	
	"OpenPGP".	
	— "DEK"	specifies the use of Data

			Encryption Key.	
			— "OpenPGP" specifies the use of OpenPGP encryption.	
algorithm			Description: The encryption algorithm used.	
			Type: Encryption	
			Value: "OCB"	
			Requirements: Must be "OCB" when encryptedWith is "DEK".	
			— Must be "OpenPGP" when encryptedWith is "OpenPGP".	

Use Case	Sensitive File Encryption with DEK	To protect sensitive data within a package, files like secret.dat are encrypted using a DEK. The DEK is then encrypted with the recipient's public key to ensure secure transmission.
	Sensitive File Encryption with OpenPGP	Files can be directly encrypted using OpenPGP with the recipient's public key, providing an alternative method for secure file encryption.

Example Configuration

```
{
  "encryption": {
    "encryptedFiles": [
      {
        "file": "secret.dat",
        "encryptedWith": "DEK",
        "algorithm": "OCB"
      },
      {
        "file": "confidential.txt",
        "encryptedWith": "OpenPGP",
        "algorithm": "OpenPGP"
      }
    ]
  }
}
```

}

Figure 78**12.2.4. Interaction with routes.json and manifest.json**

Requirements and Specifications	1) routes.json:	
	Description	This file defines the routing of various endpoints within the package.
	Handling Encrypted Files	Routes that serve encrypted files should indicate that the files are encrypted and specify the decryption method required.
	Example Configuration	

```
{
  "routes": [
    {
      "path": "/download/secret",
      "file": "secret.dat",
      "encrypted": true,
      "decryptionMethod": "DEK"
    },
    {
      "path": "/download/confidential",
      "file": "confidential.txt",
      "encrypted": true,
      "decryptionMethod": "OpenPGP"
    }
  ]
}
```

Figure 79

1) manifest.json:	
Description	This file contains metadata about the package, including information about the encrypted files.
Handling Encrypted Files	The manifest should list encrypted files and provide details about their encryption methods.
Example Configuration	

```
{
  "manifestVersion": "1.0",
  "description": "Capsium package containing both encrypted and cleartext content.",
  "files": [
    {
      "path": "secret.dat",
      "encrypted": true,
      "encryptionDetails": {
        "encryptedWith": "DEK",
        "algorithm": "OCB"
      }
    },
    {
      "path": "confidential.txt",
      "encrypted": true,
      "encryptionDetails": {
        "encryptedWith": "OpenPGP",

```

```

        "algorithm": "OpenPGP"
      },
    ],
    {
      "path": "readme.txt",
      "encrypted": false
    }
  ]
}

```

Figure 80

12.2.5. Detailed Use Cases and Examples

12.2.5.1. Use Case: Serving Encrypted Files via `routes.json`

When a client requests a file that is listed in `routes.json`, the server identifies if the file is encrypted based on the `encrypted` attribute. It then uses the specified `decryptionMethod` to decrypt the file before serving it to the client.

Example Entry in `routes.json`

```

{
  "routes": [
    {
      "path": "/download/secret",
      "file": "secret.dat",
      "encrypted": true,
      "decryptionMethod": "DEK"
    },
    {
      "path": "/download/confidential",
      "file": "confidential.txt",
      "encrypted": true,
      "decryptionMethod": "OpenPGP"
    }
  ]
}

```

Figure 81

- Explanation — The route `/download/secret` serves the `secret.dat` file, which is encrypted using a DEK and needs to be decrypted using the DEK method.
- The route `/download/confidential` serves the `confidential.txt` file, which is encrypted using OpenPGP and must be decrypted using the OpenPGP method.

12.2.5.2. Use Case: Metadata Management in `manifest.json`

The `manifest.json` provides a comprehensive overview of the files in the package, indicating which files are encrypted and detailing the encryption methods used. This helps clients understand how to handle and decrypt the files correctly.

Example Entry in `manifest.json`

```

{
  "manifestVersion": "1.0",
  "description": "Capsium package containing both encrypted and cleartext content.",
  "files": [

```

```

{
  "path": "secret.dat",
  "encrypted": true,
  "encryptionDetails": {
    "encryptedWith": "DEK",
    "algorithm": "OCB"
  }
},
{
  "path": "confidential.txt",
  "encrypted": true,
  "encryptionDetails": {
    "encryptedWith": "OpenPGP",
    "algorithm": "OpenPGP"
  }
},
{
  "path": "readme.txt",
  "encrypted": false
}
]

```

Figure 82

- Explanation — The secret.dat file is marked as encrypted with details specifying it uses a DEK and the OCB algorithm.
- The confidential.txt file is marked as encrypted with details specifying it uses OpenPGP.
- The readme.txt file is not encrypted.

12.2.6. Value Requirements and Enumerations for Attributes

- 1) publicKeyFile:

Type	string
Value Requirements	Valid file path, accessible.
- 2) encryptedFiles:

Type	array						
Items	file						
encryptedWith	<table border="0" style="margin-left: 20px;"> <tr> <td>Type</td> <td>string</td> </tr> <tr> <td>Value Requirements</td> <td>Valid file path, part of the package.</td> </tr> </table>	Type	string	Value Requirements	Valid file path, part of the package.		
Type	string						
Value Requirements	Valid file path, part of the package.						
algorithm	<table border="0" style="margin-left: 20px;"> <tr> <td>Type</td> <td>string</td> </tr> <tr> <td>Enumeration</td> <td>"DEK", "OpenPGP"</td> </tr> <tr> <td>Value Requirements</td> <td>Value Must be either "DEK" or "OpenPGP".</td> </tr> </table>	Type	string	Enumeration	"DEK", "OpenPGP"	Value Requirements	Value Must be either "DEK" or "OpenPGP".
Type	string						
Enumeration	"DEK", "OpenPGP"						
Value Requirements	Value Must be either "DEK" or "OpenPGP".						
- 3) routes.json:

Attributes	— path: string (Valid route path) — file: string (Valid file path) — encrypted: boolean — decryptionMethod: string (Enumeration: "DEK", "OpenPGP")
------------	---
- 4) manifest.json:

Attributes	—	manifestVersion: string
	—	description: string
	—	files: array
	Items:	— path: string (Valid file path)
		— encrypted: boolean
		— `encryptionDetails

12.2.6.1. Attributes in manifest.json

- 1) manifestVersion:

Type	string
Description	Version of the manifest schema.
Example	"1.0"
- 2) description:

Type	string
Description	A description of the Capsium package.
Example	"Capsium package containing both encrypted and cleartext content."
- 3) files:

Type	array																																											
Description	List of files included in the package.																																											
Items	<table> <tr> <td>path</td> <td>Type string</td> <td>Description</td> <td>Path to the file within the package.</td> <td>Example</td> <td>secret.dat</td> </tr> <tr> <td>encrypted</td> <td>Type boolean</td> <td>Description</td> <td>Indicates whether the file is encrypted.</td> <td>Example</td> <td>if the file is encrypted, false otherwise.</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td>—</td> <td>encryptionDetails (Required if encrypted is true): Type object Description: Details about the encryption method used. Properties: <table> <tr> <td>encryptedWith:</td> <td>Type string</td> <td>Description: The algorithm used for encryption.</td> <td>Example:</td> <td>"Diffie-Hellman"</td> </tr> <tr> <td>or ::</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>OpenPGP</td> <td>Type string</td> <td>Description: The algorithm used for encryption.</td> <td>Example:</td> <td>"OpenPGP"</td> </tr> <tr> <td>or ::</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>OpenPGP</td> <td>Type string</td> <td>Description: The algorithm used for encryption.</td> <td>Example:</td> <td>"OpenPGP"</td> </tr> </table> </td> </tr> </table>	path	Type string	Description	Path to the file within the package.	Example	secret.dat	encrypted	Type boolean	Description	Indicates whether the file is encrypted.	Example	if the file is encrypted, false otherwise.					—	encryptionDetails (Required if encrypted is true): Type object Description: Details about the encryption method used. Properties: <table> <tr> <td>encryptedWith:</td> <td>Type string</td> <td>Description: The algorithm used for encryption.</td> <td>Example:</td> <td>"Diffie-Hellman"</td> </tr> <tr> <td>or ::</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>OpenPGP</td> <td>Type string</td> <td>Description: The algorithm used for encryption.</td> <td>Example:</td> <td>"OpenPGP"</td> </tr> <tr> <td>or ::</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>OpenPGP</td> <td>Type string</td> <td>Description: The algorithm used for encryption.</td> <td>Example:</td> <td>"OpenPGP"</td> </tr> </table>	encryptedWith:	Type string	Description: The algorithm used for encryption.	Example:	"Diffie-Hellman"	or ::					OpenPGP	Type string	Description: The algorithm used for encryption.	Example:	"OpenPGP"	or ::					OpenPGP	Type string	Description: The algorithm used for encryption.	Example:	"OpenPGP"
path	Type string	Description	Path to the file within the package.	Example	secret.dat																																							
encrypted	Type boolean	Description	Indicates whether the file is encrypted.	Example	if the file is encrypted, false otherwise.																																							
				—	encryptionDetails (Required if encrypted is true): Type object Description: Details about the encryption method used. Properties: <table> <tr> <td>encryptedWith:</td> <td>Type string</td> <td>Description: The algorithm used for encryption.</td> <td>Example:</td> <td>"Diffie-Hellman"</td> </tr> <tr> <td>or ::</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>OpenPGP</td> <td>Type string</td> <td>Description: The algorithm used for encryption.</td> <td>Example:</td> <td>"OpenPGP"</td> </tr> <tr> <td>or ::</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>OpenPGP</td> <td>Type string</td> <td>Description: The algorithm used for encryption.</td> <td>Example:</td> <td>"OpenPGP"</td> </tr> </table>	encryptedWith:	Type string	Description: The algorithm used for encryption.	Example:	"Diffie-Hellman"	or ::					OpenPGP	Type string	Description: The algorithm used for encryption.	Example:	"OpenPGP"	or ::					OpenPGP	Type string	Description: The algorithm used for encryption.	Example:	"OpenPGP"														
encryptedWith:	Type string	Description: The algorithm used for encryption.	Example:	"Diffie-Hellman"																																								
or ::																																												
OpenPGP	Type string	Description: The algorithm used for encryption.	Example:	"OpenPGP"																																								
or ::																																												
OpenPGP	Type string	Description: The algorithm used for encryption.	Example:	"OpenPGP"																																								

The Description:
encryption
algorithm
used.
Example:
or ::
"OpenPGP"
Example
Configuration
in
manifest.
json

```
{
  "manifestVersion": "1.0",
  "description": "Capsium package containing both encrypted and cleartext
content.",
  "files": [
    {
      "path": "secret.dat",
      "encrypted": true,
      "encryptionDetails": {
        "encryptedWith": "DEK",
        "algorithm": "OCB"
      }
    },
    {
      "path": "confidential.txt",
      "encrypted": true,
      "encryptionDetails": {
        "encryptedWith": "OpenPGP",
        "algorithm": "OpenPGP"
      }
    },
    {
      "path": "readme.txt",
      "encrypted": false
    }
  ]
}
```

Figure 83

12.2.7. Detailed Example

12.2.7.1. Combined Example Configuration

Here is a comprehensive example showing how the encryption, routes.json, and manifest.json files work together in a Capsium package.

Encryption Configuration (encryption section)

```
{
  "encryption": {
    "publicKeyFile": "path/to/public.key",
    "encryptedFiles": [
      {
        "file": "secret.dat",
        "encryptedWith": "DEK",
        "algorithm": "OCB"
      },
    ],
  },
}
```



```

    {
      "file": "confidential.txt",
      "encryptedWith": "OpenPGP",
      "algorithm": "OpenPGP"
    }
  ]
}

```

Figure 84

Routes Configuration (routes.json)

```

{
  "routes": [
    {
      "path": "/download/secret",
      "file": "secret.dat",
      "encrypted": true,
      "decryptionMethod": "DEK"
    },
    {
      "path": "/download/confidential",
      "file": "confidential.txt",
      "encrypted": true,
      "decryptionMethod": "OpenPGP"
    },
    {
      "path": "/download/readme",
      "file": "readme.txt",
      "encrypted": false
    }
  ]
}

```

Figure 85

Manifest Configuration (manifest.json)

```

{
  "manifestVersion": "1.0",
  "description": "Capsium package containing both encrypted and cleartext content.",
  "files": [
    {
      "path": "secret.dat",
      "encrypted": true,
      "encryptionDetails": {
        "encryptedWith": "DEK",
        "algorithm": "OCB"
      }
    },
    {
      "path": "confidential.txt",
      "encrypted": true,
      "encryptionDetails": {
        "encryptedWith": "OpenPGP",
        "algorithm": "OpenPGP"
      }
    },
    {
      "path": "readme.txt",
      "encrypted": false
    }
  ]
}

```

```
    }  
  ]  
}
```

Figure 86

12.3. Validation

12.3.1. General

Validation ensures the quality and correctness of the Capsium package. This section describes the various quality and correctness checks that can be performed on a Capsium package, along with their attributes and features.

12.3.2. Data validation

Data sets included should be validated against respective schemas to be correct otherwise operational deployment of the Capsium package will fail.

12.3.3. Quality Checks

Quality checks are processes designed to verify the quality of the package’s content. These checks ensure that the package adheres to best practices and standards for code quality and content integrity.

HTML Validation	Ensures that all HTML files in the package are well-formed and comply with HTML standards.
CSS Validation	Checks that all CSS files are syntactically correct and conform to CSS specifications.
JavaScript Linting	Uses a linter tool to analyze JavaScript code for potential errors and adherence to coding standards.

Example:

```
{  
  "validation": {  
    "qualityChecks": {  
      "htmlValidation": true,  
      "cssValidation": true,  
      "jsLinting": true  
    }  
  }  
}
```

Figure 87

In this example, all three quality checks (htmlValidation, cssValidation, and jsLinting) are enabled, indicating that HTML, CSS, and JavaScript files will be validated.

12.3.4. Correctness Checks

Correctness checks ensure that the package meets all specifications and requirements. These checks validate the structural and functional integrity of the package.

Schema Validation	Ensures that data files within the package conform to predefined schemas. This is critical for maintaining consistency and correctness in data formats.
-------------------	---

Dependency Validation	Checks that all dependencies required by the package are correctly specified and available. This ensures that the package can be built and run without missing dependencies.
-----------------------	--

Example:

```
{
  "validation": {
    "correctnessChecks": {
      "schemaValidation": true,
      "dependencyValidation": true
    }
  }
}
```

Figure 88

In this example, both schemaValidation and dependencyValidation are enabled, indicating that the package’s data files will be validated against their schemas, and all dependencies will be checked for correctness.

12.3.5. Combined Example

A comprehensive validation configuration that includes both quality and correctness checks might look like this:

```
{
  "validation": {
    "qualityChecks": {
      "htmlValidation": true,
      "cssValidation": true,
      "jsLinting": true
    },
    "correctnessChecks": {
      "schemaValidation": true,
      "dependencyValidation": true
    }
  }
}
```

Figure 89

In this expanded example, the validation object contains both quality checks and correctness checks, providing a holistic validation approach to ensure the package is both high-quality and correct.

12.3.6. Attributes Summary

validation	The root object for validation configuration.
qualityChecks	Object containing quality check configurations.
htmlValidation (boolean)	Enable or disable HTML validation.
cssValidation (boolean)	Enable or disable CSS validation.

jsLinting (boolean): Enable or disable JavaScript linting.

correctnessChecks Object containing correctness check configurations.

schemaValidation (boolean): Enable or disable schema validation.

dependencyValidation (boolean): Enable or disable dependency validation.

By configuring these attributes, Capsium packages can be thoroughly validated to ensure they meet both quality and correctness standards. This structured approach helps maintain high standards and reliability for Capsium packages.

12.4. Testing

12.4.1. General

This clause specifies the structure and options for the Capsium package testing YAML format. This format is used to define tests for various aspects of Capsium packages, including HTTP routes, file existence, data validation, and configuration testing.

A YAML-based domain-specific language (DSL) for describing tests to be executed against Capsium packages is specified below. The DSL is designed to be programming language-independent, allowing for implementations in various languages.

The Capsium testing YAML structure consists of a list of tests, each defined with specific attributes depending on the type of test. The top-level structure is as follows:

```
tests:
  - name: <Test Name>
    type: <Test Type>
    ...
```

Figure 90

12.4.2. Test Types and Options

12.4.3. Route Testing

Route testing is used to verify the behavior of HTTP endpoints. Each route test includes the following attributes:

```
- name: <Test Name>
  type: route
  url: <URL>
  expected_status: <HTTP Status Code>
  response_contains: <Optional String to Check in Response>
```

Figure 91

- name: A descriptive name for the test.
- type: Must be route for route testing.
- url: The URL of the HTTP endpoint to be tested.
- expected_status: The expected HTTP status code (e.g., 200).
- response_contains: (Optional) A string that should be present in the response body.

Example:

```
- name: Home Route Test
  type: route
  url: "http://localhost:8000/home"
  expected_status: 200
  response_contains: "Welcome"
```

Figure 92

12.4.4. File Testing

File testing checks for the existence of required files. Each file test includes the following attributes:

```
- name: <Test Name>
  type: file
  path: <File Path>
```

Figure 93

- name: A descriptive name for the test.
- type: Must be file for file existence testing.
- path: The file path to be checked.

Example:

```
- name: Config File Exists
  type: file
  path: "/path/to/config.json"
```

Figure 94

12.4.5. Data Validation

Data validation tests validate datasets against predefined schemas. Each data validation test includes the following attributes:

```
- name: <Test Name>
  type: data_validation
  format: <Data Format>
  data_file: <Data File Path>
  schema_file: <Schema File Path>
```

Figure 95

- name: A descriptive name for the test.
- type: Must be data_validation for data validation tests.
- format: The format of the data file (e.g., json, yaml).
- data_file: The path to the data file to be validated.
- schema_file: The path to the schema file to validate against.

Example:

```
- name: JSON Data Validation
  type: data_validation
  format: json
  data_file: "/path/to/datafile.json"
  schema_file: "/path/to/schemafile.json"
```

Figure 96

12.4.6. Configuration Testing

Configuration testing ensures that configuration files are correctly structured and valid. Each configuration test includes the following attributes:

- name: <Test Name>
- type: config
- format: <Config Format>
- config_file: <Config File Path>

Figure 97

- name: A descriptive name for the test.
- type: Must be config for configuration file validation.
- format: The format of the configuration file (e.g., json, yaml).
- config_file: The path to the configuration file to be validated.

Example:

- name: JSON Config Validation
- type: config
- format: json
- config_file: "/path/to/config.json"

Figure 98

12.5. Complete Example

Below is a complete example of a Capsium package testing YAML file, demonstrating various test types and their options:

```
tests:
  - name: Home Route Test
    type: route
    url: "http://localhost:8000/home"
    expected_status: 200
    response_contains: "Welcome"

  - name: API Route Test
    type: route
    url: "http://localhost:8000/api/data"
    expected_status: 200
    response_contains: "data"

  - name: Config File Exists
    type: file
    path: "/path/to/config.json"

  - name: Data File Exists
    type: file
    path: "/path/to/datafile.json"

  - name: JSON Data Validation
    type: data_validation
    format: json
    data_file: "/path/to/datafile.json"
    schema_file: "/path/to/schemafile.json"

  - name: YAML Data Validation
```

```

type: data_validation
format: yaml
data_file: "/path/to/datafile.yaml"
schema_file: "/path/to/schemafile.yaml"

- name: JSON Config Validation
  type: config
  format: json
  config_file: "/path/to/config.json"

```

Figure 99

12.6. Conformance

To conform to this standard, an implementation must correctly interpret and execute the tests defined in the Capsium package testing YAML format as described in this document. Implementations may be developed in any programming language, provided they adhere to the specified structure and options.

12.6.1. Packaging options

12.6.1.1. General

Encapsulation in the context of Capsium packages involves ensuring data integrity, security, and efficiency through compression, digital signatures, and encryption. These operations are configured and managed through a `packaging.json` file.

The `packaging.json` file serves as a centralized configuration for managing the compression, digital signature, and encryption aspects of the Capsium package encapsulation process. It ensures that all necessary parameters and standards are clearly defined and easily accessible for implementation.

Compression is always applied. Signing occurs on the entire package, and will be stored in a file called `signature.sig` inside the package. Encryption happens before signing. The file `metadata.json` and `signature.json` itself are unencrypted.

When an encrypted and signed Capsium package is uncompressed, it looks like this:

- `package/metadata.json`
- `package/signature.json`
- `package/package.enc`

The digital signature is calculated on the combined data of:

- `package/metadata.json`
- `package/signature.json` (where the “signature” key is set to an empty string)
- `package/package.enc`

When `package.enc` is decrypted, the package looks like this, depending on what the package contains:

- `package/metadata.json`
- `package/signature.json`
- `package/routes.json`
- `package/manifest.json`
- `package/storage.json`
- `package/contents/index.html`
- `package/data/my_yaml.yaml`

```

{
  "compression": {
    "algorithm": "zip",
    "level": "best",
    "fileExtension": ".zip"
  },
  "digitalSignature": {
    "algorithm": "RSA-SHA256",
    "keyLength": 2048,
    "certificateType": "X.509",
    "signatureFile": "signature.sig"
  },
  "encryption": {
    "algorithm": "AES-256",
    "mode": "GCM",
    "keyManagement": "secure",
    "fileExtension": ".enc"
  }
}

```

Figure 100

12.6.1.2. Compression

Compression reduces the size of the package, allowing for more efficient storage and transmission. The Zip algorithm, as defined by the ISO document compression standard, is used.

12.6.1.2.1. Requirements and Specifications

Algorithm	Zip
ISO Standard Compliance	The compression must adhere to the ISO/IEC 21320-1:2015 standard for document compression.
Compression Level	Configurable levels of compression (e.g., no compression, fastest, best compression).
File Extensions	Compressed files should use the .zip extension.

12.6.1.2.2. Configuration Details in packaging.json

```

{
  "compression": {
    "algorithm": "Zip",
    "standard": "ISO/IEC 21320-1:2015",
    "level": "best",
    "fileExtension": ".zip"
  }
}

```

Figure 101

12.6.1.3. Digital Signature Using X.509 or OpenPGP

Digital signatures ensure the authenticity and integrity of the package, verifying that it has not been tampered with and confirming the identity of the sender. Capsium packages can use either X.509 certificates or OpenPGP keys for digital signatures.

12.6.1.3.1. Requirements and Specifications

Signature Algorithm	RSA with SHA-256	
Key Length	Minimum 2048 bits	
Digital Certificate	X.509	Must follow the X.509 standard for public key infrastructure.
	OpenPGP	Must follow the OpenPGP standard for encryption and signatures.
Signature File	A separate file (e.g., signature.sig) containing the digital signature.	

12.6.1.3.2. Configuration Details in packaging.json

```
{
  "digitalSignature": {
    "algorithm": "RSA-SHA256",
    "keyLength": 2048,
    "certificateType": "X.509",
    "signatureFile": "signature.sig"
  }
}
```

Figure 102

For OpenPGP:

```
{
  "digitalSignature": {
    "algorithm": "RSA-SHA256",
    "keyLength": 2048,
    "certificateType": "OpenPGP",
    "signatureFile": "signature.sig"
  }
}
```

Figure 103

12.6.1.4. Encryption

Encryption protects the package’s contents from unauthorized access, ensuring that only intended recipients can decrypt and access the data.

12.6.1.4.1. Requirements and Specifications

Encryption Algorithm	AES-256	
Mode of Operation	GCM (Galois/Counter Mode) for authenticated encryption	
Key Management	Secure distribution and storage of encryption keys	
Encrypted File	The encrypted package should have a .enc extension.	

12.6.1.4.2. Configuration Details in packaging.json

```
{
  "encryption": {
    "algorithm": "AES-256",
    "mode": "GCM",
    "keyManagement": "secure",
    "fileExtension": ".enc"
  }
}
```

Figure 104

12.6.1.5. Optimization

Optimization ensures that the Capsium package is delivered efficiently and performs optimally in various environments. This section describes the methods and attributes involved in optimizing content delivery for Capsium packages.

12.6.1.5.1. Content Delivery Optimization

Content Delivery Optimization focuses on improving the speed and efficiency with which package content is delivered to end-users. This includes techniques for minimizing load times, reducing bandwidth usage, and enhancing overall user experience.

Minification	The process of removing unnecessary characters from code (such as whitespace, comments, and redundant formatting) to reduce file size without affecting functionality. This is commonly applied to HTML, CSS, and JavaScript files.
Compression	The use of algorithms to reduce the size of files for transmission over the network. Common methods include gzip and Brotli compression.
Caching	Storing copies of files in strategic locations (such as on a user's device or at various points in a content delivery network) to reduce load times and server requests.
Image Optimization	Techniques for reducing the file size of images without significantly compromising quality. This can include methods like resizing, format conversion, and compression.
Lazy Loading	A strategy for loading images and other resources only when they are needed, rather than all at once. This can significantly improve initial load times and overall performance.

Example:

```
{
  "optimization": {
    "minification": {
      "html": true,
      "css": true,
      "js": true
    },
    "compression": {
      "enabled": true,
      "method": "gzip"
    },
    "caching": {
```

```
        "enabled": true,
        "strategy": "aggressive"
    },
    "imageOptimization": {
        "enabled": true,
        "methods": ["resize", "compress"]
    },
    "lazyLoading": {
        "enabled": true,
        "elements": ["images", "videos"]
    }
}
}
```

Figure 105

In this example, various optimization techniques are enabled and configured:

Minification	HTML, CSS, and JavaScript files will be minified.
Compression	Gzip compression is enabled for reducing file sizes during transmission.
Caching	An aggressive caching strategy is employed to store and serve content efficiently.
Image Optimization	Images will be resized and compressed to reduce their file sizes.
Lazy Loading	Images and videos will be loaded only when they come into view, reducing initial load times.

12.6.1.5.2. Attributes Summary

optimization The root object for optimization configuration.

minification	Object containing minification settings. html (boolean): Enable or disable HTML minification. css (boolean): Enable or disable CSS minification. js (boolean): Enable or disable JavaScript minification.
compression	Object containing compression settings. enabled (boolean): Enable or disable compression. method (string): Specifies the compression method (e.g., gzip, brotli).
caching	Object containing caching settings. enabled (boolean): Enable or disable caching.

<code>strategy</code>	(string): Specifies the caching strategy (e.g., aggressive, conservative).
<code>imageOptimization</code>	Object containing image optimization settings.
<code>enabled</code>	(boolean): Enable or disable image optimization.
<code>methods</code>	(array of string): Specifies the methods used for image optimization (e.g., resize, compress).
<code>lazyLoading</code>	Object containing lazy loading settings.
<code>enabled</code>	(boolean): Enable or disable lazy loading.
<code>elements</code>	(array of string): Specifies the elements to apply lazy loading to (e.g., images, videos).

By implementing these optimization techniques, Capsium packages can deliver content more efficiently, providing a faster and smoother user experience. This structured approach ensures that content is not only high-quality and correct but also optimized for performance and delivery.

12.6.2. User authentication

12.6.2.1. General

General user authentication requirements apply to all methods and provide a foundation for secure access control.

Example:

```
{
  "authentication": {
    "basicAuth": {
      "enabled": true,
      "passwdFile": "path/to/.htpasswd"
    },
    "oauth": {
      "enabled": true,
      "provider": "Google",
      "clientId": "your-client-id",
      "clientSecret": "your-client-secret",
      "redirectUri": "your-redirect-uri"
    }
  }
}
```

Figure 106

12.6.2.2. Requirements and Specifications

User ID and Password	Each user must have a unique User ID and a strong password.
Password Policy	Enforce strong password policies, including:

	— Minimum length: 8 characters — At least one uppercase letter, one lowercase letter, one digit, and one special character
Account Lockout	Implement account lockout after a specified number of failed login attempts (e.g., 5 attempts).
Session Management	Secure session management with timeout and automatic logout after a period of inactivity.
Encryption	All authentication data should be encrypted during transmission and storage.

12.6.2.3. Apache Authentication (passwd)

Apache authentication using passwd involves basic HTTP authentication with user credentials stored in a .htpasswd file.

12.6.2.3.1. Requirements and Specifications

File Location	The .htpasswd file must be securely stored and accessible only to the web server.
Encryption	Passwords in the .htpasswd file should be hashed using a secure algorithm (e.g., bcrypt).
Configuration	Apache configuration to support basic authentication using the .htpasswd file.

12.6.2.3.2. Configuration Details

htpasswd File::

- Use the htpasswd utility to create and manage the file.
- Example entry: `username:$apr1$eWvS2f3d$Ee9uU7/r8C3W1J9QkE45H0`
- **Apache Configuration** (.htaccess or httpd.conf): `` AuthType Basic AuthName "Restricted Access" AuthUserFile /path/to/.htpasswd Require valid-user ``

12.6.2.4. External Authentication via OAuth

External authentication via OAuth involves delegating the authentication process to an external OAuth provider (e.g., Google, Facebook).

12.6.2.4.1. Requirements and Specifications

OAuth Provider	Select a trusted OAuth provider (e.g., Google, Facebook, GitHub).
Client ID and Secret	Obtain a Client ID and Secret from the OAuth provider.
Redirect URI	Configure a redirect URI on the OAuth provider's dashboard that points to your application's OAuth callback endpoint.
Scope	Define the scope of access (e.g., email, profile).
State Parameter	Use the state parameter to prevent CSRF attacks.

Token Management	Securely manage and store OAuth tokens.
Secret Protection	The OAuth secret must be kept protected from users who can extract the package. This includes storing the secret in a secure environment variable or a secure server-side configuration file, not within the package itself.

12.6.2.4.2. Configuration Details in `oauth_config.json`

```
`json { "oauth": { "provider": "Google", "clientId": "YOUR_CLIENT_ID", "clientSecret":
"${OAUTH_CLIENT_SECRET}", "redirectUri": "https://yourapp.com/oauth/callback", "scope": ["email",
"profile"], "stateSecret": "YOUR_STATE_SECRET" } } `
```

12.6.2.4.3. Secret Protection

To protect the OAuth secret from users who can extract the package: - Store the `clientSecret` in a secure environment variable (`OAUTH_CLIENT_SECRET`) instead of hardcoding it in the configuration file. - Ensure that the `oauth_config.json` file references the environment variable for the `clientSecret`. - On the server side, configure the environment variable securely and load it during application startup.

12.6.2.5. Combined Configuration Example

Here is a combined configuration example that includes general requirements, Apache authentication, and OAuth configuration.

`authentication.json`

```
`json { "authentication": { "general": { "passwordPolicy": { "minLength": 8, "requireUppercase": true,
"requireLowercase": true, "requireDigit": true, "requireSpecialCharacter": true }, "accountLockout":
{ "threshold": 5, "duration": 30 }, "sessionManagement": { "timeout": 30, "autoLogout": true },
"encryption": "AES-256" }, "apache": { "htpasswdFile": "/path/to/.htpasswd", "encryptionAlgorithm":
"bcrypt" }, "oauth": { "provider": "Google", "clientId": "YOUR_CLIENT_ID", "clientSecret":
"${OAUTH_CLIENT_SECRET}", "redirectUri": "https://yourapp.com/oauth/callback", "scope": ["email",
"profile"], "stateSecret": "YOUR_STATE_SECRET" } } } `
```

`general` Specifies general authentication requirements,

`general` Specifies general authentication requirements, including password policy, account lockout, session management, and encryption.

`apache` Details Apache authentication configuration, including the path to the `.htpasswd` file and the encryption algorithm used for passwords.

`oauth` Configures external authentication via OAuth, including the OAuth provider, client ID, client secret (referenced from an environment variable), redirect URI, scope, and state secret.

This comprehensive configuration ensures that user authentication is secure, flexible, and compliant with best practices, while also protecting sensitive information such as the OAuth secret from being exposed.

12.7. Composite Packages

Composite packages in Capsium allow for the bundling of multiple Capsium packages into a single, cohesive unit. This provides an organized and efficient way to manage dependencies, resources, and configurations.

12.7.1. Structure (Composite Package of Multiple Capsium Packages)

A composite package is a structured collection of multiple Capsium packages, each contributing its own functionality and resources. The structure typically includes:

- * A manifest file (`manifest.json`) that outlines the composite package's metadata and dependencies.
- * A `packages` directory containing the individual Capsium packages.
- * Configuration files for resource routing and storage management.

Example `manifest.json`:

```
{
  "name": "composite-package-example",
  "version": "1.0.0",
  "description": "A composite package consisting of multiple Capsium packages.",
  "packages": [
    "package1",
    "package2",
    "package3"
  ]
}
```

Figure 107

Directory structure: `composite-package/` | `manifest.json` | `packages/` | `package1/` | `package2/` | `package3/` | `routes.json` | `storage.json`

12.7.2. Specifying Dependencies in Metadata

Dependencies between Capsium packages within a composite package are specified in the `manifest.json` file. This includes defining which packages are required and any specific versions or constraints.

Example `manifest.json` with dependencies:

```
{
  "name": "composite-package-example",
  "version": "1.0.0",
  "description": "A composite package consisting of multiple Capsium packages.",
  "packages": [
    "package1",
    "package2",
    "package3"
  ],
  "dependencies": {
    "package1": ">=1.0.0",
    "package2": "^2.0.0",
    "package3": "3.x"
  }
}
```

Figure 108

12.7.3. Resource Routing

Resource routing in a composite package involves defining how HTTP routes and data routes are managed and potentially remapped to avoid conflicts and ensure proper integration.

12.7.3.1. Remapping Included HTTP Routes

When combining multiple packages, HTTP routes may need to be remapped to avoid conflicts or to better organize the API endpoints. This is done in the `routes.json` file.

Example `routes.json` with remapping:

```
{
  "routes": [
    {
      "originalRoute": "/api/v1/package1/",
      "remappedRoute": "/api/v1/composite/package1/"
    },
    {
      "originalRoute": "/api/v1/package2/",
      "remappedRoute": "/api/v1/composite/package2/"
    }
  ]
}
```

Figure 109

12.7.3.2. Remapping Included Data Routes

Similar to HTTP routes, data routes may also need to be remapped to ensure data sources are correctly referenced and do not conflict.

Example `routes.json` with data route remapping:

```
{
  "dataRoutes": [
    {
      "originalRoute": "/api/v1/data/package1/",
      "remappedRoute": "/api/v1/data/composite/package1/"
    },
    {
      "originalRoute": "/api/v1/data/package2/",
      "remappedRoute": "/api/v1/data/composite/package2/"
    }
  ]
}
```

Figure 110

12.7.4. Storage

Storage configurations in a composite package involve managing and potentially customizing which layers from included packages are activated or deactivated.

12.7.4.1. Selecting Inherited Layers to Activate / Deactivate

Inherited layers from individual packages can be selectively activated or deactivated based on the needs of the composite package. This is specified in the `storage.json` file.

Example `storage.json`:

```
{
  "storage": {
    "activeLayers": [
```



```

    "package1.layer1",
    "package2.layer2"
  ],
  "inactiveLayers": [
    "package3.layer3"
  ]
}
}

```

Figure 111

12.7.5. Security, Digital Signatures, and Integrity Checks

Ensuring the security and integrity of a composite package involves the use of digital signatures and integrity checks. Each package within the composite package should have its own digital signature, and the composite package itself should also be signed.

Digital Signatures	Each package and the composite package should be signed using a cryptographic key to ensure authenticity.
Integrity Checks	Hashes (e.g., SHA-256) should be used to verify that the package contents have not been tampered with.

Example manifest.json with signatures and hashes:

```

{
  "name": "composite-package-example",
  "version": "1.0.0",
  "description": "A composite package consisting of multiple Capsium packages.",
  "packages": [
    {
      "name": "package1",
      "version": "1.0.0",
      "hash": "sha256-abcdef1234567890...",
      "signature": "MIIBIjANBgkqhkiG9w0BAQEFAAOCAQ8AMIIBCgKCAQEA..."
    },
    {
      "name": "package2",
      "version": "2.1.0",
      "hash": "sha256-12345abcdef67890...",
      "signature": "MIIBIjANBgkqhkiG9w0BAQEFAAOCAQ8AMIIBCgKCAQEA..."
    }
  ],
  "compositeSignature": "MIIBIjANBgkqhkiG9w0BAQEFAAOCAQ8AMIIBCgKCAQEA..."
}

```

Figure 112

12.7.6. User Authentication

User authentication in a composite package ensures that only authorized users can access the resources and data provided by the included packages. This is typically managed via an authentication service that supports various authentication methods such as OAuth, JWT, or API keys.

OAuth	Use OAuth 2.0 for user authentication, allowing users to log in using their existing credentials from an OAuth provider (e.g., Google, Facebook).
-------	---

JWT	Implement JSON Web Tokens (JWT) for stateless authentication. Tokens are issued upon successful login and are included in subsequent requests to verify user identity.
API Keys	Use API keys for application-level access control. API keys are issued to applications and are included in API requests for authentication.

Example auth.json configuration:

```
{
  "authentication": {
    "methods": ["OAuth", "JWT", "APIKey"],
    "OAuth": {
      "provider": "https://oauth.example.com",
      "clientId": "your-client-id",
      "clientSecret": "your-client-secret"
    },
    "JWT": {
      "secret": "your-jwt-secret",
      "issuer": "your-issuer",
      "audience": "your-audience"
    },
    "APIKey": {
      "headerName": "X-API-Key",
      "validKeys": ["key1", "key2", "key3"]
    }
  }
}
```

Figure 113

By configuring these options, a composite package can ensure robust security and proper access control across all included packages. This structured approach helps maintain the integrity of the composite package while providing a seamless experience for end-users.

12.8. Capsium Reactor

The Capsium reactor is the execution environment responsible for running Capsium packages. It supports various deployment environments, provides APIs for introspection, manages user authentication and data security, and ensures reliable and trusted execution of packages.

12.8.1. Structure

The structure of a Capsium reactor typically includes:

Core Engine	The core runtime that executes Capsium packages.
Configuration Files	Settings and configurations for the reactor's operation.
Plugins	Optional plugins for additional functionality (e.g., authentication, logging).
APIs	Interfaces for introspection, monitoring, and management.

Directory structure example: `capsium-reactor/`

```
├── core/ | ├── engine.js | ├── config/
│   ├── settings.json |   ├── plugins.json |   ├── plugins/ |   ├── auth-plugin.js |
├── logging-plugin.js | ├── apis/ |   ├── introspection-api.js |   ├── monitoring-api.js |
├── package-api.js | ├── logs/ |   └── data/`
```

12.8.2. Operation Environments

The Capsium reactor is designed to operate in various environments to provide flexibility and scalability.

12.8.2.1. Reactor in the Browser Natively or as a Plugin

- | | |
|-------------|---|
| Natively | <p>The reactor can run directly in the browser using WebAssembly or JavaScript, allowing for client-side execution of Capsium packages.</p> <ul style="list-style-type: none"> — Requirements: Modern web browser with WebAssembly and JavaScript support. — Use Cases: Client-side applications, browser extensions. |
| As a Plugin | <p>The reactor can be embedded as a browser plugin, providing additional capabilities and tighter integration with browser features.</p> <ul style="list-style-type: none"> — Requirements: Plugin installation, browser compatibility. — Use Cases: Enhanced browser extensions, specific web application functionalities. |

12.8.2.2. Reactor in the Web Server as a Plugin

- | | |
|-------------------|--|
| Web Server Plugin | <p>The reactor can be deployed as a plugin in web servers such as Apache, Nginx, or Node.js.</p> <ul style="list-style-type: none"> — Requirements: Compatible web server, plugin installation. — Use Cases: Server-side applications, API backends. |
|-------------------|--|

Example configuration for Node.js: ``javascript const capsiumReactor = require('capsium-reactor'); const express = require('express'); const app = express();`

`app.use('/capsium', capsiumReactor());`

`app.listen(3000, () => { console.log('Capsium reactor running on port 3000'); });``

12.8.2.3. Reactor on Cloud Services (AWS S3 or GitHub Pages)

- | | |
|--------------|--|
| AWS S3 | <ul style="list-style-type: none"> — Deployments can be hosted on AWS S3 as static websites. — Requirements: AWS S3 bucket, configuration for static website hosting. — Use Cases: Hosting static applications, deploying packages with minimal backend requirements. |
| GitHub Pages | <ul style="list-style-type: none"> — Deployments can be hosted on GitHub Pages for easy access and version control. — Requirements: GitHub repository, Pages configuration. — Use Cases: Open-source projects, documentation sites. |

Example GitHub Pages setup: `` 1. Create a GitHub repository. 2. Push your Capsium package to the repository. 3. Enable GitHub Pages in the repository settings. 4. Access your package at https://<username>.github.io/<repository>/.``

12.8.3. HTTP API for Introspection of Reactor

The reactor provides an HTTP API for introspection, allowing users to query the reactor's status, configuration, and operational metrics.

- Endpoints — /introspect/status: Returns the current status of the reactor.
 — /introspect/config: Returns the reactor's configuration details.
 — /introspect/metrics: Returns operational metrics (e.g., uptime, resource usage).

Example API response for /introspect/status:

```
{
  "status": "running",
  "uptime": 3600,
  "packagesLoaded": 5
}
```

Figure 114

12.8.4. HTTP API for Introspection of Package

The reactor also provides an HTTP API to introspect individual Capsium packages, enabling users to retrieve package-specific information.

- Endpoints — /package/:packageId/status: Returns the status of the specified package.
 — /package/:packageId/metadata: Returns the metadata of the specified package.
 — /package/:packageId/logs: Returns the logs related to the specified package.

Example API response for /package/:packageId/metadata:

```
{
  "name": "example-package",
  "version": "1.0.0",
  "description": "An example Capsium package",
  "author": "Author Name"
}
```

Figure 115

12.8.5. Access to Activated Capsium Package Information, Metadata

The reactor maintains detailed information and metadata for each activated Capsium package. This information includes version details, dependencies, and configuration settings.

- Access — Via HTTP API: Endpoints such as /package/:packageId/metadata
 Methods — provide access to package metadata.
 — Via Configuration Files: Metadata can be stored and accessed through configuration files within the reactor's directory structure.

Example metadata structure:

```
{
  "packages": {
    "example-package": {
      "name": "example-package",

```

```

    "version": "1.0.0",
    "description": "An example Capsium package",
    "author": "Author Name",
    "dependencies": ["dependency1", "dependency2"],
    "config": {
      "option1": "value1",
      "option2": "value2"
    }
  }
}
}
}

```

Figure 116

12.8.6. Monitoring and Logging

The Capsium reactor includes robust monitoring and logging capabilities to ensure smooth operation and facilitate troubleshooting.

- | | |
|------------|---|
| Monitoring | <ul style="list-style-type: none"> — Health Checks: Periodic checks to ensure the reactor and its packages are running correctly. — Metrics Collection: Collection of performance metrics such as CPU and memory usage, request counts, and error rates. |
| Logging | <ul style="list-style-type: none"> — Access Logs: Logs of all incoming requests and their responses. — Error Logs: Detailed logs of errors encountered during operation. — Custom Logs: Logs generated by individual packages for specific events. |

Example logging configuration in `plugins/logging-plugin.js`: ``javascript const fs = require('fs'); const path = require('path');`

```

module.exports = function loggingPlugin(req, res, next) { const logEntry = ${new Date()}.
toISOString()} - ${req.method} ${req.url}\n; fs.appendFileSync(path.join(__dirname, '../
logs/access.log'), logEntry); next(); }; `

```

12.8.7. Handling User Authentication (Apache passwd, External OAuth Authentication Defined by Packages)

The reactor supports various user authentication methods to secure access to its resources:

- | | |
|-------------------|--|
| Apache
passwd | <p>Uses <code>.htpasswd</code> files for basic HTTP authentication.</p> <ul style="list-style-type: none"> — Requirements: <code>.htpasswd</code> file containing user credentials. — Use Cases: Simple authentication for small deployments. |
| External
OAuth | <p>Supports OAuth authentication as defined by individual packages.</p> <ul style="list-style-type: none"> — Configuration: OAuth provider details need to be configured. — Use Cases: Integration with third-party authentication providers like Google, Facebook, or custom OAuth servers. |

Example configuration for OAuth in `auth-plugin.js`: ``javascript const passport = require('passport'); const OAuth2Strategy = require('passport-oauth2').Strategy;`

```

passport.use(new OAuth2Strategy({ authorizationURL: 'https://example.com/oauth/authorize',
tokenURL: 'https://example.com/oauth/token', clientID: 'your-client-id', clientSecret: 'your-client-
secret', callbackURL: 'https://your-app.com/callback' }, (accessToken, refreshToken, profile, cb) =>
{ // Verify and handle user profile cb(null, profile); }));

```

```
app.use(passport.initialize()); app.get('/auth/example', passport.authenticate('oauth2'));
app.get('/callback', passport.authenticate('oauth2', { failureRedirect: '/' } ), (req, res) =>
{ res.redirect('/'); });`
```

12.8.8. Decrypting User Data

The reactor includes mechanisms for securely decrypting user data, ensuring it remains protected while in transit and at rest.

Encryption Algorithms	Supports standard encryption algorithms such as AES-256.
Key Management	Secure storage and management of encryption keys.
API for Decryption	Provides an API for decrypting user data when needed.

Example decryption function in `data-handler.js`: ``javascript const crypto = require('crypto');`

```
function decryptData(encryptedData, key) { const decipher = crypto.createDecipher('aes-256-cbc',
key); let decrypted = decipher.update(encryptedData, 'hex', 'utf8'); decrypted += decipher.final('utf8');
return decrypted; }`
```

12.8.9. Updating Modifiable Capsium Packages

The reactor allows for the dynamic updating of modifiable Capsium packages, ensuring that packages can be kept up-to-date without downtime.

Update Mechanism	Supports hot-swapping of packages with minimal disruption.
Version Control	Keeps track of package versions and allows rollback if necessary.
API for Updates	Provides an API for updating packages.

Example update API endpoint in `update-api.js`: ``javascript
app.post('/update-package/:packageId', (req, res) => { const packageId = req.params.packageId;
const newPackageData = req.body; // Assume package data is sent in the request body try { //
Logic to update the package res.status(200).send({ message: 'Package updated successfully' }); }
catch (error) { res.status(500).send({ message: 'Failed to update package', error }); } });``

12.8.10. Trusted Execution

The reactor ensures trusted execution of Capsium packages by enforcing security measures and maintaining integrity throughout the runtime.

Sandboxing	Each package runs in an isolated environment to prevent interference and enhance security. — Requirements: Use of technologies like Docker containers or virtual machines. — Use Cases: Running untrusted code, ensuring package isolation.
Code Signing	All packages must be signed by a trusted authority to verify their integrity and authenticity. — Requirements: Digital certificates and a trusted certificate authority (CA). — Use Cases: Preventing tampering and ensuring only authorized packages are executed.

Integrity Checks	Regular integrity checks are performed to ensure that packages have not been altered. — Methods: Hash verification, signature validation. — Use Cases: Detecting unauthorized changes, maintaining trust.
Audit Logs	Detailed logs of all operations and accesses are maintained to provide an audit trail. — Requirements: Comprehensive logging infrastructure. — Use Cases: Security audits, forensic analysis.

Example sandboxing setup using Docker: ``dockerfile # Dockerfile for a Capsium package FROM node:14`

`WORKDIR /app`

`COPY . .`

`RUN npm install`

`CMD ["node", "index.js"]``

Example code signing process: . Generate a key pair: ``bash openssl genrsa -out private.key 2048``
`openssl rsa -in private.key -pubout -out public.key``

- 1) Sign the package: ``bash openssl dgst -sha256 -sign private.key -out package.sig package.zip``
- 2) Verify the signature: ``bash openssl dgst -sha256 -verify public.key -signature package.sig package.zip``

With these detailed requirements and specifications, the Capsium reactor ensures a secure, flexible, and robust environment for executing Capsium packages across various deployment scenarios.

12.8.11. Monitoring HTTP API

The Capsium reactor provides a comprehensive Monitoring HTTP API designed to expose various details about the reactor and its packages. This API is particularly useful for browser users who need to access metadata, routes, content hashes, and validity information directly from the browser. All endpoints are namespaced under `/api/v1/introspect`.

12.8.11.1. Exposing metadata.json

The `metadata.json` file contains essential information about the Capsium packages, including their names, versions, authors, and descriptions. The Monitoring HTTP API provides an endpoint to retrieve this information.

Endpoint	<code>/api/v1/introspect/metadata</code>
Method	GET
Response	JSON containing the metadata of all active packages.

Example response:

```
{
  "packages": [
    {
      "name": "example-package",
```

```

    "version": "1.0.0",
    "author": "Author Name",
    "description": "An example Capsium package"
  },
  {
    "name": "another-package",
    "version": "2.0.0",
    "author": "Another Author",
    "description": "Another example Capsium package"
  }
]
}

```

Figure 117

12.8.11.2. Exposing routes.json

The `routes.json` file lists all the available routes provided by the Capsium packages. This is critical for understanding the API surface and available endpoints.

Endpoint	/api/v1/introspect/routes
Method	GET
Response	JSON containing the routes of all active packages.

Example response:

```

{
  "routes": [
    {
      "package": "example-package",
      "routes": [
        {
          "method": "GET",
          "path": "/example"
        }
      ]
    },
    {
      "package": "another-package",
      "routes": [
        {
          "method": "POST",
          "path": "/another"
        }
      ]
    }
  ]
}

```

Figure 118

12.8.11.3. Exposing packaged content hashes

To ensure content integrity, the reactor can expose the hashes of the packaged content. This allows users to verify that the content has not been tampered with.

Endpoint	/api/v1/introspect/content-hashes
----------	-----------------------------------

Method	GET
Response	JSON containing the hashes of all packaged content.

Example response:

```
{
  "contentHashes": [
    {
      "package": "example-package",
      "hash": "abcd1234efgh5678ijkl9012mnop3456qrst6789uvwx0123yzab4567cdef8901"
    },
    {
      "package": "another-package",
      "hash": "1234abcd5678efgh9012ijkl3456mnop6789qrst0123uvwx4567yzab8901cdef"
    }
  ]
}
```

Figure 119

12.8.11.4. Exposing content validity information

The reactor can also expose information regarding the validity of the packaged content. This includes checks on whether the content has passed integrity checks and is trusted for execution.

Endpoint	/api/v1/introspect/content-validity
Method	GET
Response	JSON containing the validity status of all packaged content.

Example response:

```
{
  "contentValidity": [
    {
      "package": "example-package",
      "valid": true,
      "lastChecked": "2024-05-28T12:34:56Z"
    },
    {
      "package": "another-package",
      "valid": false,
      "lastChecked": "2024-05-28T12:34:56Z",
      "reason": "Signature mismatch"
    }
  ]
}
```

Figure 120

12.8.12. Deploy configuration

When deploying a Capsium package to a Capsium reactor, an optional configuration file named `deploy.json` can be provided to control the behavior of the package in the deployed environment. This file allows fine-tuning of various aspects, including logging and monitoring options, data storage, deployment performance requirements, and server-side secrets.

12.8.12.1. Structure of `deploy.json`

The `deploy.json` file should be a JSON-formatted file with the following sections:

logging	Options for controlling logging behavior.
monitoring	Configuration for monitoring the package.
dataStorage	Settings for data storage.
performance	Deployment performance requirements.
secrets	Server-side secrets, such as OAuth secrets.

12.8.12.2. Example `deploy.json` File

```
{
  "logging": {
    "level": "DEBUG",
    "file": "/var/log/capsium/example-package.log",
    "format": "json"
  },
  "monitoring": {
    "enabled": true,
    "endpoint": "http://monitoring.example.com/api/v1/metrics",
    "interval": "60s"
  },
  "dataStorage": {
    "type": "filesystem",
    "path": "/var/data/capsium/example-package"
  },
  "performance": {
    "maxMemory": "512MB",
    "maxCPU": "2"
  },
  "secrets": {
    "oauthSecret": "supersecretkey"
  }
}
```

Figure 121

12.8.12.3. Detailed Specifications

12.8.12.3.1. Logging and Monitoring Options

The logging and monitoring sections control how the package logs information and integrates with monitoring systems.

logging.level	Defines the logging level (e.g., DEBUG, INFO, WARN, ERROR).
logging.file	Specifies the file path where logs should be written.
logging.format	Determines the format of the logs (e.g., plain text, JSON).
monitoring.enabled	A boolean to enable or disable monitoring.

<code>monitoring.endpoint</code>	The URL of the monitoring system's API endpoint.
<code>monitoring.interval</code>	The interval at which monitoring data should be sent.

12.8.12.3.2. Data Storage

The `dataStorage` section specifies configurations for data storage.

<code>dataStorage.type</code>	The type of data storage (e.g., <code>filesystem</code>).
<code>dataStorage.path</code>	The file system path where data should be stored.

12.8.12.3.3. Deployment Performance Requirements

The `performance` section defines the performance requirements for the deployed package.

<code>performance.maxMemory</code>	The maximum amount of memory the package is allowed to use (e.g., <code>"512MB"</code>).
<code>performance.maxCPU</code>	The maximum number of CPU cores the package can utilize (e.g., <code>"2"</code>).

12.8.12.3.4. Server-Side Secrets

The `secrets` section is used to provide sensitive information such as OAuth secrets.

<code>secrets.oauthSecret</code>	The secret key used for OAuth authentication.
----------------------------------	---

12.8.12.4. Usage

To deploy a Capsium package with the additional configuration provided in `deploy.json`, include the file during the deployment process.

Example deployment command: ``bash capsium deploy example-package@1.0.0 --config deploy.json``

The Capsium reactor will read the `deploy.json` file and apply the specified configurations, ensuring that the package operates according to the defined settings.

12.9. Management of Capsium packages

A Capsium package passes through a well-defined lifecycle: it is built from a package directory, inspected, validated, deployed and activated on a Capsium reactor, monitored while serving, and eventually updated or rolled back. This clause specifies the management operations that apply at each stage of that lifecycle and the behavior expected of the tools that perform them.

12.9.1. General

The lifecycle of a Capsium package consists of the following operations:

Building	A package directory conforming to Clause 5 is packed into a single <code>.cap</code> file.
----------	--

Inspecting	The metadata, manifest, routes, and storage configuration of a package are examined without activating the package.
Validation	The package is checked against the requirements of Clause 5 before or after distribution.
Deployment and activation	The package is loaded by a Capsium reactor, which verifies its integrity and serves its routes at a web address.
Monitoring	The reactor exposes the state of the activated package through the Monitoring HTTP API (Clause 7).
Updating and rollback	A new version of the package replaces a deployed one, or a previously deployed version is reinstated.
Dependency resolution	The packages required by a package, as declared in its metadata, are identified and made available.

Management operations are performed by packagers and reactors; the command examples in this clause use the capsium command-line interface (Annex A) and the reactor introspection endpoints (Clause 7) to illustrate them.

12.9.2. Building a package

Building assembles a package directory and produces the distributable `.cap` file. The build process shall:

- 1) Start from a package directory whose structure conforms to Clause 5, containing at minimum a hand-authored `metadata.json`.
- 2) Generate `manifest.json` from the package content when it is absent, and generate `routes.json` from the manifest when it is absent, applying the generation rules of Clause 5.
- 3) Generate `security.json` containing a SHA-256 checksum for every file in the package except `security.json` itself (Clause 5, Security).
- 4) Compress the directory into a single file conforming to the packaging rules of Clause 5, named `{name}-{version}.cap` where `name` and `version` are taken from `metadata.json`.

Example using the capsium CLI:

```
capsium package pack -f path-to-package
# => Package created: example-package-1.0.0.cap
```

Figure 122

A built `.cap` file can be unpacked again for inspection or modification:

```
capsium package unpack example-package-1.0.0.cap -o example-package
```

Figure 123

Extraction shall reject archive entries whose paths would be written outside the destination directory (absolute paths, drive letters, `..` segments), so that unpacking an untrusted package cannot overwrite unrelated files.

12.9.3. Inspecting a package

Inspection exposes the configuration of a package without deploying it. Management tooling shall be able to report, for a package directory or a `.cap` file:

- the metadata (`metadata.json`), including name, version, identifiers, and dependencies;
- the manifest (`manifest.json`), generated when absent;

- the routes (`routes.json`), generated when absent;
- the storage configuration (`storage.json`) and its datasets.

Example using the capsium CLI:

```
capsium package info      example-package-1.0.0.cap
capsium package metadata example-package-1.0.0.cap
capsium package manifest example-package-1.0.0.cap
capsium package routes   example-package-1.0.0.cap
capsium package storage  example-package-1.0.0.cap
```

Figure 124

12.9.4. Validation

Validation determines whether a package satisfies the requirements of Clause 5. Validation should be performed after building and before distribution, and may be repeated by any recipient of the package.

A validation procedure shall check, and report per check, at least:

metadata	required fields are present and well-formed (kebab-case name, semantic version, URI guid, valid uuid);
manifest	every declared resource exists in the package;
routes	route targets exist, dataset routes are mounted under <code>/api/v1/data/</code> , and the index resolves to an existing HTML file;
storage	dataset sources and schemas exist, and dataset data validates against its declared schema;
security	when <code>security.json</code> is present, all checksums match;
content	packaged content does not reference external resources that would break self-containment.

Validation shall produce a per-check report and shall signal failure (for example, through a non-zero process exit status) when any check fails.

Example using the capsium CLI:

```
capsium package validate example-package-1.0.0.cap
# => PASS metadata
# => PASS manifest
# => PASS routes
# => PASS storage
# => PASS security
# => PASS content
```

Figure 125

12.9.5. Deployment and activation on a reactor

Deployment delivers a `.cap` file to a Capsium reactor; activation is the process by which the reactor loads the package and serves its routes at a web address (Clause 4).

On activation the reactor shall:

- 1) Accept a package from a local `.cap` file or package directory.

- 2) Verify the integrity of the package against `security.json` when present, and reject a package that fails verification (Clause 5, Security).
- 3) Load the package configuration, generating `manifest.json` and `routes.json` when absent, and mount every route defined by the package.
- 4) Serve the package routes as specified in Clause 7, and expose the Monitoring HTTP API for the activated package.

An optional deployment configuration file (`deploy.json`, Clause 7) may be provided to tune logging, monitoring, data storage, performance, and server-side secrets for the deployed environment.

Example using the capsium CLI:

```
capsium reactor serve example-package-1.0.0.cap --port 8864
# => Starting server on http://localhost:8864
```

Figure 126

12.9.6. Monitoring an activated package

While a package is activated, the reactor answers the Monitoring HTTP API (Clause 7) under `/api/v1/introspect`. Management tooling should use these endpoints to confirm the state of a deployment:

- GET `/api/v1/introspect/metadata` — the metadata of the activated package(s), confirming which name and version are serving;
- GET `/api/v1/introspect/routes` — the routes served per package;
- GET `/api/v1/introspect/content-hashes` — the content hash per package, for comparison against a known-good value;
- GET `/api/v1/introspect/content-validity` — the result of re-verifying the package against `security.json`, including the time of the check and the reason when invalid.

12.9.7. Updating and rollback

Capsium packages are versioned with Semantic Versioning in `metadata.json` (Clause 5), and the built artifact carries the version in its file name (`{name}-{version}.cap`). Versioning enables efficient updates and rollbacks (Clause 4).

Updating An update is built as a new `.cap` file whose version is incremented according to the nature of the change (Clause 5, Versions). Deploying the new artifact to the reactor replaces the previously activated version.

Rollback Because each built `.cap` is immutable and self-contained, rollback is performed by re-deploying the artifact of an earlier version. Management tooling should retain previously deployed artifacts to make rollback possible without rebuilding.

12.9.8. Integrity verification

Integrity verification protects every stage of the lifecycle after building:

- At build time, `security.json` records a SHA-256 checksum for every package file except itself (Clause 5, Security).
- At activation time, the reactor shall re-calculate the checksums and reject the package on any mismatch.
- While serving, verification can be repeated on demand through the `/api/v1/introspect/content-validity` endpoint (Clause 7), which reports the outcome together with a check timestamp.

A package whose content does not match `security.json` shall be rejected; it shall not be served.

12.9.9. Dependency resolution

A package declares its dependencies in `metadata.json` as an object mapping the GUID of each required package to a semantic version range (Clause 5, Dependencies). Dependency resolution is the process of identifying the required packages and versions and making them available so that the dependent package functions correctly.

Resolution shall:

- 1) Read the `dependencies` object from the package metadata.
- 2) Select, for each dependency, an available package whose GUID matches and whose version satisfies the declared range.
- 3) Make the selected packages available to the deployment, either as individually activated packages or composed into a composite package (Clause 6).

Management tooling should detect unresolvable dependencies — a missing GUID or a version range no available artifact satisfies — and report them before activation rather than serving a partially functional package.

12.10. Compliance

This clause defines the conformance classes of the Capsium framework and the requirements that an artifact or implementation shall satisfy to claim conformance to each class. Requirements are expressed as numbered, testable statements and reference the clauses in which the underlying specifications are given.

12.10.1. General

Three conformance classes are defined:

Conformant Capsium Package	A <code>.cap</code> artifact that satisfies the package requirements of Clause 5.
Conformant Packager	Software that produces Conformant Capsium Packages.
Conformant Reactor	Software that activates and serves Conformant Capsium Packages as specified in Clause 7.

Informative examples of implementations of these classes are given in Annexes A to D.

12.10.2. Conformant Capsium Package

A Capsium package conforms to this document when all of the following statements are true:

- 1) The package is distributed as a single compressed file with the `.cap` extension and the MIME type `application/vnd.capsium.package` (Clause 5, General; Packaging options).
- 2) The package directory structure conforms to the folder hierarchy of Clause 5 (Structure): configuration files reside at the package root, served content under the content directory, and paths inside configuration files are package-relative.
- 3) The package contains a `metadata.json` file (Clause 5, Metadata file) in which the name, version, description, guid, and uuid attributes are present, and in which:
 - a) name is a kebab-case string;
 - b) version follows Semantic Versioning;
 - c) guid is a URI;
 - d) uuid is a valid UUID.
- 4) Dependencies, when declared, are expressed in `metadata.json` as an object mapping the GUID of each required package to a semantic version range (Clause 5, Dependencies).

- 5) The package contains a `manifest.json` file, either provided or generated from the package content according to the generation rules of Clause 5 (Manifest file), and every resource declared in the manifest exists in the package.
- 6) The package contains a `routes.json` file, either provided or generated from the manifest according to the generation rules of Clause 5 (Resource routing): HTML content is reachable through both its base name and its full file name, and other resources are routed relative to the content path.
- 7) Every target referenced by `routes.json` exists in the package, and dataset routes are mounted under `/api/v1/data/` (Clause 5, Dataset routes).
- 8) When the package contains datasets, `storage.json` declares each dataset referenced by a dataset route, and dataset data validates against its declared schema (Clause 5, Storage; Validation).
- 9) When `security.json` is present, it declares SHA-256 as the checksum algorithm and lists a SHA-256 checksum for every file in the package except `security.json` itself, and every listed checksum matches the corresponding file (Clause 5, Security).
- 10) The package is self-contained: served content does not depend on external resources to function (Clause 4, Principles; Clause 5, Validation).

12.10.3. Conformant Packager

A packager conforms to this document when all of the following statements are true:

- 1) The packager produces packages that satisfy every statement of the Conformant Capsium Package class.
- 2) When `manifest.json` is absent from the package directory, the packager generates it from the package content according to Clause 5 (Manifest file).
- 3) When `routes.json` is absent from the package directory, the packager generates it from the manifest according to Clause 5 (Resource routing).
- 4) The packager writes `security.json` at packaging time, containing a SHA-256 checksum for every file in the package except `security.json` itself (Clause 5, Security).
- 5) The packager names the built artifact `{name}-{version}.cap`, taking name and version from `metadata.json` (Clause 8, Building a package).
- 6) When extracting a `.cap` file, the packager rejects archive entries whose paths would escape the destination directory (Clause 8, Building a package).
- 7) The packager should offer validation of a package directory or `.cap` file against the Conformant Capsium Package statements, reporting per check and signalling failure when any check fails (Clause 8, Validation).

12.10.4. Conformant Reactor

A reactor conforms to this document when all of the following statements are true:

- 1) The reactor activates a package from a `.cap` file or package directory and serves every route defined by the package's `routes.json` as specified in Clause 7, including dataset routes under `/api/v1/data/` and the package index route.
- 2) Static resources are served with the MIME types recorded in `manifest.json`.
- 3) When `security.json` is present in a package, the reactor verifies the package content against the listed SHA-256 checksums on activation (Clause 5, Security; Clause 8, Deployment and activation).
- 4) The reactor rejects a package that fails integrity verification and does not serve its content (Clause 5, Security).
- 5) The reactor exposes the Monitoring HTTP API of Clause 7, answering GET requests under `/api/v1/introspect` for each activated package:
 - a) `/api/v1/introspect/metadata` returning package metadata;
 - b) `/api/v1/introspect/routes` returning served routes;
 - c) `/api/v1/introspect/content-hashes` returning content hashes;
 - d) `/api/v1/introspect/content-validity` returning the integrity verification outcome.

- 6) Requests to routes or endpoints with an unsupported HTTP method are answered with an appropriate HTTP error status.

A Conformant Reactor may additionally implement the following optional capabilities; their absence does not affect conformance:

- layered storage (Clause 5, Storage);
- user authentication, including Apache passwd (.htpasswd) and external OAuth as defined by packages (Clause 5, User authentication; Clause 7);
- decryption of encrypted package content (Clause 5, Encrypted information; Clause 7);
- activation of composite packages (Clause 6);
- serving routes that invoke dynamic handlers, answering 501 Not Implemented for handler routes it does not execute.

Appendix A (informative) Ruby packager

The capsium Ruby gem (version 0.2.0, MIT licensed, copyright Ribose) is the reference packager and reactor for Capsium packages. It packages a directory into a .cap file, unpacks, inspects and validates packages, and includes the WEBrick-based reactor described in Annex B. This annex describes the packager side of the gem; it requires Ruby 3.2 or later.

A.1. Architecture

The gem is organized under `lib/capsium` with autoload-only loading: the top level Capsium module declares autoload for every component (Package, Packager, Reactor, Cli, Converters, ThorExt, VERSION), so no implementation file is loaded until the corresponding constant is first referenced.

Package domain objects are modelled with `lutaml-model` (`Lutaml::Model::Serializable`). Each configuration file of Clause 5 has a dedicated model with explicit JSON mappings:

- `metadata.json` — `Capsium::Package::MetadataData` (with a nested Repository model);
- `manifest.json` — the manifest model, keyed by package-relative resource path;
- `routes.json` — the routes model (index plus a routes array);
- `storage.json` — the storage model (`storage.dataSets`);
- `security.json` — the security model (`security.integrityChecks`).

The metadata model carries the field-level format rules of Clause 5 (kebab-case name, semantic version, URI guid, UUID uuid) and reports human-readable format errors; these rules drive the `validate` command.

The command-line interface is built on Thor. `Capsium::Cli` exposes three subcommands — `package`, `reactor`, and `convert` — implemented as Thor subcommand classes under `lib/capsium/cli`.

Notable dependencies: `lutaml-model` (domain models), `thor` (CLI), `rubyzip` (.cap compression and extraction), `marcel` (MIME type detection when generating manifests), `json-schema` (dataset schema validation), `sqlite3` (SQLite datasets), `listen` and `webrick` (reactor, Annex B).

A.2. Installation

```
gem install capsium
```

Figure A.1

A.3. Usage

A.3.1. Packing a package

```
capsium package pack [--force/-f] path-to-package
```

Figure A.2

`pack` generates `manifest.json` and `routes.json` when absent, writes `security.json` with a SHA-256 checksum of every package file except `security.json` itself, and compresses the directory into `{name}-{version}.cap`, with name and version taken from `metadata.json`. Without `--force`, an existing target file aborts the build with `Capsium::Packager::FileAlreadyExistsError`.

EXAMPLE — Sample pack session

```
$ capsium package pack -f spec/fixtures/bare-package
Package created: bare-package-0.1.0.cap
```

A.3.2. Unpacking a package

```
capsium package unpack bare-package-0.1.0.cap [-o/--output my_bare_package]
```

Figure A.3

When `-o` is omitted, the package is unpacked into a directory named after the `.cap` file. Extraction is zip-slip safe: entries whose names would escape the destination (absolute paths, drive letters, `..` segments) are rejected with `Capsium::Packager::UnsafeEntryError`.

A.3.3. Validating a package

```
capsium package validate path-to-package-or-cap
```

Figure A.4

Validation runs a per-check report and exits with status 1 on any failure:

- metadata: required fields present and well-formed (kebab-case name, semver version, URI guid, UUID);
- manifest: every resource exists on disk;
- routes: route targets exist; dataset routes live under `/api/v1/data/`; the index resolves to an existing HTML file;
- storage: dataset sources (and schemas) exist; dataset data passes JSON-schema validation;
- security: checksums match when `security.json` is present;
- content: no external `http(s)` references in packaged content files.

A.3.4. Inspecting a package

```
capsium package info      path-to-package
capsium package metadata  path-to-package
capsium package manifest  path-to-package
capsium package routes    path-to-package
capsium package storage   path-to-package
```

Figure A.5

`info` prints the package path, routes, and manifest; the other commands pretty-print the corresponding configuration as JSON.

A.4. Canonical and legacy schema support

The gem reads both the canonical configuration forms of Clause 5 and the legacy (pre-0.2) gem forms, normalizing the legacy forms on read; writers emit only the canonical forms. For example, a legacy dependencies array of `{name, version}` objects in `metadata.json` is accepted and normalized to the canonical object form mapping each dependency GUID to its version range.

A.5. security.json generation

At pack time the gem generates `security.json` (Clause 5, Security) with `checksumAlgorithm` `SHA-256` and a `checksums` object holding the SHA-256 hex digest of every file in the package except `security.json` itself:

```
{
  "security": {
```

[illegible]

Figure A.6

When `security.json` is present, loading a package verifies it and raises `Capsium::Package::Security::IntegrityError` on mismatch.

A.6. Programmatic usage

```
require 'capsium'

package = Capsium::Package.new('example-package-1.0.0.cap')
puts package.metadata.name
errors = package.verify_integrity # typed errors, empty when valid

packager = Capsium::Packager.new
cap_file = packager.pack(package, force: true)
packager.unpack(cap_file, 'output-directory')
```

Figure A.7

The public API ships with RBS signatures in `sig/`.

Appendix B (informative) Ruby reactor

The capsium Ruby gem (Annex A) ships a built-in reactor, `Capsium::Reactor`, implemented on WEBrick. It activates a single package from a local `.cap` file or package directory and serves its routes over HTTP, together with the Monitoring HTTP API of Clause 7. Serving directly from a URL is not supported.

B.1. Starting the reactor

```
capsium reactor serve my_package.cap [--port 8864] [--do_not_listen]
```

Figure B.1

The default port is 8864. While serving, the reactor watches the package directory with the `listen` gem and restarts the server when files change, so edits to a package directory are picked up without manual restarts.

B.2. Route serving

On startup the reactor mounts every route declared by the package's `routes.json`, plus the introspection paths, as WEBrick mount procs, and resolves each incoming request path against the package routes:

- an unknown path is answered 404 Not Found;
- a resource route serves the referenced file with the MIME type recorded in `manifest.json` (falling back to `application/octet-stream`), and a 404 when the file is missing on disk;
- a dataset route (`{path, dataset}`) serves the dataset from `storage.json` as `application/json` under its `/api/v1/data/<id>` mount, and a 404 when the dataset is unknown;
- any other route kind, including dynamic handler routes, is answered 501 Not Implemented.

Unless a route declares its own headers, resource responses carry `Cache-Control: public, max-age=31536000` (one year), the reactor's configurable default.

B.3. Integrity verification on load

Loading a package that contains `security.json` verifies every listed SHA-256 checksum before anything is served; a mismatch raises `Capsium::Package::Security::IntegrityError` and the package is rejected (Clause 5, Security).

B.4. Introspection endpoints

While serving, the reactor answers the Monitoring HTTP API (Clause 7) as `application/json`. The endpoints are GET-only; other methods are answered 405 Method Not Allowed.

```
GET /api/v1/introspect/metadata      # => {"packages": [{"name", "version",
"author", "description"}]}
GET /api/v1/introspect/routes      # => {"routes": [{"package", "routes":
[{"method", "path"}]}}
GET /api/v1/introspect/content-hashes # => {"contentHashes": [{"package",
"hash"}]}
GET /api/v1/introspect/content-validity # => {"contentValidity": [{"package",
"valid", "lastChecked", "reason"?}]}
```

Figure B.2

metadata	wraps the served package's name, version, author, and description in the packages list shape of Clause 7.
routes	lists every served route with its HTTP method (defaulting to GET) and path.
content-hashes	reports the SHA-256 of the .cap blob when the package was served from one. For a directory source there is no blob, so the hash covers the canonical (sorted-key) JSON serialization of the package content checksums — the same data security .json integrity checks carry.
content-validity	re-verifies the package against security.json on every request and reports the outcome with a UTC lastChecked timestamp; reason lists the integrity errors when valid is false.

Example content-validity response for a healthy package:

```
{
  "contentValidity": [
    {
      "package": "example-package",
      "valid": true,
      "lastChecked": "2024-05-28T12:34:56Z"
    }
  ]
}
```

Figure B.3

Appendix C (informative) Apache httpd reactor

No Apache httpd implementation of a Capsium reactor exists at the time of writing. This annex provides guidance for realizing one, mapping the reactor responsibilities of Clause 7 onto standard Apache httpd modules. Because a Capsium package is static by design (Clause 4), most of the serving behavior can be expressed in declarative httpd configuration; only integrity verification and the Monitoring HTTP API require external tooling or a dynamic backend.

C.1. Extracting the package to a docroot

A .cap file is a ZIP archive (Clause 5, Packaging options). Deployment starts by extracting it into a directory that becomes (part of) the Apache document root:

```
mkdir -p /var/www/capsium/example-package-1.0.0
cd /var/www/capsium/example-package-1.0.0
unzip /srv/capsium/packages/example-package-1.0.0.cap
```

Figure C.1

Extraction should reject archive entries whose paths would escape the destination directory (absolute paths, .. segments), as required of packagers in Clause 8. After extraction, the served content tree is available at the docroot and the configuration files (metadata.json, manifest.json, routes.json, security.json) are available for deriving the site configuration.

C.2. Integrity pre-verification at deploy time

Apache httpd itself does not verify security.json. Integrity verification (Clause 5, Security) should therefore be performed at deploy time by external tooling, before the extracted directory is published: recalculate the SHA-256 of every extracted file and compare it against security.integrityChecks.checksums; refuse to publish the docroot on any mismatch. The capsium package validate command (Annex A) performs exactly this check, as does a short script in any language with a SHA-256 library.

C.3. Mapping routes.json to Alias and mod_rewrite

Each resource route in routes.json maps a URL path to a package-relative file. Static mappings translate directly into Alias directives or, for rule shapes such as the dual HTML routes of Clause 5 (base name and full file name), into mod_rewrite rules:

```
Alias "/styles.css" "/var/www/capsium/example-package-1.0.0/content/styles.css"

RewriteEngine On
# Dual HTML routes: /page serves content/page.html
RewriteCond "%{DOCUMENT_ROOT}/content/$1.html" -f
RewriteRule "^/([^\s/]+)$" "/content/$1.html" [PT]
```

Figure C.2

The index route of routes.json maps to DirectoryIndex. Dataset routes under /api/v1/data/ (Clause 5, Dataset routes) map to the JSON rendering of the dataset: for file-backed datasets this can again be an Alias to a pre-generated JSON file; database-backed datasets require a small dynamic backend (see the introspection paragraph below).

C.4. Serving manifest-derived MIME types

`manifest.json` records the MIME type of every resource (Clause 5, Manifest file). `httpd`'s own `mime.types` covers the common types; package-specific or unusual types recorded in the manifest can be added with `mod_mime`:

```
AddType application/vnd.capsium.package .cap
AddType text/javascript .js
```

Figure C.3

C.5. Cache-Control via `mod_headers`

Clause 7-compliant reactors serve static resources with a long-lived `Cache-Control` policy by default. With `mod_headers`:

```
<Directory "/var/www/capsium/example-package-1.0.0/content">
  Header set Cache-Control "public, max-age=31536000"
</Directory>
```

Figure C.4

Per-route header declarations in `routes.json` (Clause 5, Header responses) translate into more specific Header directives scoped by `<Location>`.

C.6. Basic authentication

The Apache `passwd` authentication defined for packages (Clause 5, User authentication) is native `httpd` functionality. A package that declares `.htpasswd` basic authentication maps to:

```
<Directory "/var/www/capsium/example-package-1.0.0/content">
  AuthType Basic
  AuthName "Restricted Access"
  AuthUserFile /etc/httpd/capsium/example-package.htpasswd
  Require valid-user
</Directory>
```

Figure C.5

The `.htpasswd` file is managed with the `htpasswd` utility, must be stored outside the served docroot, and passwords should be hashed with `bcrypt` (Clause 5, User authentication). OAuth authentication defined by a package requires a dynamic backend or a module such as `mod_auth_openidc`, with the client secret kept outside the package as specified in Clause 5.

C.7. Exposing the introspection API

The Monitoring HTTP API (Clause 7) is dynamic and cannot be served from static files alone, because content-validity re-verifies the package at request time. Options for exposing it behind `httpd` include:

- a CGI or FastCGI script that reads the extracted package's configuration files and recomputes the verification on demand;
- a small application server (for example the Ruby reactor of Annex B running alongside `httpd`) reverse-proxied with `mod_proxy`:

```
ProxyPass "/api/v1/introspect" "http://127.0.0.1:8864/api/v1/introspect"
```



```
ProxyPassReverse "/api/v1/introspect" "http://127.0.0.1:8864/api/v1/introspect"
```

Figure C.6

Whichever backend is chosen, the four endpoints of Clause 7 — `/api/v1/introspect/metadata`, `/routes`, `/content-hashes`, and `/content-validity` — should answer GET requests with the JSON shapes defined there, and reject other methods with 405.

Appendix D (informative) nginx (OpenResty) reactor

The capsium-lua project (version 0.2.0, MIT licensed) is a Capsium reactor built on OpenResty, the Lua-enabled nginx distribution. It serves Capsium packages (.cap files) directly through nginx with Lua: a .cap file dropped into the packages directory is extracted on demand, verified against security.json, and routed, with optional per-mount configuration for paths, domains, headers, caching, and CORS.

D.1. Architecture

The implementation keeps a single framework-agnostic core and a thin nginx glue layer, with no duplicated logic:

lib/capsium/	Framework-agnostic core (the rock)
├─ utils.lua	Pure helpers (tables, JSON files, paths)
├─ mime.lua	MIME type detection (text/javascript per RFC 9239)
├─ csv.lua	Minimal CSV parser (dataset support)
├─ reactor.lua	Reactor core: package management + introspection
├─ package/	
│ ├─ package.lua	Package model (OOP): load/normalize/resolve
│ ├─ extractor.lua	Atomic .cap extraction (tmp dir + rename)
│ ├─ router.lua	Schema normalization + route auto-generation
│ └─ security.lua	security.json parsing + SHA-256 verification
├─ adapters/	
│ ├─ nginx.lua	fs/zip adapters (LuaFileSystem + lua-zip)
│ └─ hash.lua	SHA-256 (resty.sha256 in OpenResty, pure-Lua fallback elsewhere)
lua/capsium/	nginx glue (only code that touches ngx)
├─ init.lua	Entry point: wires adapters into the core, request handling, introspection API
└─ config.lua	config.json loading + mount resolution

Figure D.1

The core never references ngx; the glue never implements domain logic. Other platforms can plug in their own filesystem, zip, and hash adapters.

D.2. Configuration

Configuration is read from \$CAPSIUM_CONFIG_PATH, else the first existing of /etc/capsium/config.json, /etc/capsium/nginx/config.json, /var/lib/capsium/config.json, ./config.json. Top-level keys:

package_dir	Directory containing .cap files (default /var/lib/capsium/packages).
extract_dir	Extraction target (default /var/lib/capsium/extracted).
cache_enabled	Use the capsium_cache shared dict to cache introspection responses (default true).
cache_ttl	TTL in seconds for the shared-dict cache (default 3600).

packages_ config_dir	Optional directory with per-package <name>.json mount configs, merged with mounts at startup.
mounts	Array of mount entries (below).

Example mount entries:

```
{
  "package_dir": "/var/lib/capsium/packages",
  "extract_dir": "/var/lib/capsium/extracted",
  "cache_enabled": true,
  "cache_ttl": 3600,
  "mounts": [
    {
      "package": "mn-samples-iso-0.1.0.cap",
      "path": "/app",
      "domain": "example.com",
      "options": {
        "cache_ttl": 7200,
        "headers": {
          "X-Frame-Options": "SAMEORIGIN",
          "X-Content-Type-Options": "nosniff"
        }
      }
    },
    {
      "package": "api-1.0.0.cap",
      "path": "/api",
      "options": {
        "cors": {
          "allowed_origins": ["https://example.com"],
          "allowed_methods": ["GET"],
          "allowed_headers": ["Content-Type"],
          "max_age": 600
        }
      }
    }
  ]
}
```

Figure D.2

Mount entry keys:

package	Package filename (.cap extension optional).
path	Mount path prefix (default /capsium/<package-name>).
domain	Virtual host. Advisory: the mount answers on all hosts, and is preferred for the named host when mounts overlap.
options. cache_ttl	Static Cache-Control max-age override for this mount (default 31536000, giving public, max-age=31536000).
options. headers	Extra response headers applied to every response from this mount; an explicit Cache-Control here wins over cache_ttl.

`options.cors` CORS policy: `allowed_origins` (array, * supported), `allowed_methods`, `allowed_headers`, `expose_headers`, `max_age`. Preflight `OPTIONS` requests are answered with 204 when CORS is configured.

Every package in `package_dir` is always also available at `/capsium/<package-name>` without configuration; `/api/v1/introspect` is reserved.

D.3. Extraction and integrity verification

Packages are extracted lazily, on first request. Extraction is atomic: the archive unpacks into a temporary directory that is renamed into place only after `metadata.json` parses and, when `security.json` is present, every listed file's SHA-256 verifies (Clause 5, Security). A package that fails verification is rejected with a 5xx response carrying the reason, and nothing is left at the final extraction path. Archive entries containing `..` path segments are refused (zip-slip protection). Re-extraction happens automatically when the `.cap` file is newer than the extracted tree.

D.4. Manifest-driven routing

Both the canonical configuration forms of Clause 5 and the legacy gem forms are accepted and normalized on read. When `routes.json` is absent, routes are auto-generated from `manifest.json` per the routing rules of Clause 5:

- `index` defaults to `content/index.html`, also routed at `/`;
- every manifest resource under `content/` is routed relative to `content/`;
- HTML files get dual routes, `/page` and `/page.html`;
- every dataset gets `/api/v1/data/<id>`.

Package routes are GET-only: other methods receive 405 with `Allow: GET, HEAD`; HEAD is served like GET without a body. Dynamic handler routes are accepted by the parser but answered with 501 Not Implemented. Dataset sources are served as JSON — `.json` served as-is, `.csv` converted to JSON objects; YAML and SQLite datasets are not supported by this reactor.

D.5. Introspection API

The reactor answers the Monitoring HTTP API (Clause 7), GET only:

```

/api/v1/introspect/metadata    {packages: [{name, version, author,
                                description}]}

/api/v1/introspect/routes     {routes: [{package, routes: [{method,
                                path}]}]}

/api/v1/introspect/content-hashes {contentHashes: [{package, hash}]} —
                                SHA-256 of the .cap blob.

/api/v1/introspect/content-validity {contentValidity: [{package, valid,
                                lastChecked, reason?}]} — the actual
                                integrity verification result.
```

All introspection endpoints lazily extract and load packages on demand, so a freshly started reactor reports every `.cap` in `package_dir` (cold-start introspection). Responses are cached in the `capsium_cache` shared dict with the configured `cache_ttl`.

D.6. Docker deployment

The project ships a Dockerfile whose base image is pinned: `openresty/openresty:1.27.1.2-12-alpine-fat` (the `BASE_IMAGE` build arg). A typical deployment mounts the packages and configuration directories into the container:

```
docker build -t capsium-nginx .
docker run -d -p 8080:80 \
  -v $PWD/packages:/var/lib/capsium/packages \
  -v $PWD/config:/etc/capsium \
  capsium-nginx
```

Figure D.3