QDIP Input — CorrectionScreen + ActionsScreen + EditActionScreen

Förutsättningar (från tidigare steg)

- HomeScreen ✅ klar (har btnCorrection och btnActions)
- DailyScreen ✅ klar
- SharePoint-listor anslutna: QDIP_EHS_Daily, QDIP_Quality_Daily, QDIP_Delivery_Daily, QDIP_Actions
- QDIP_Actions: `QDIP_Section`, `Status`, `PersonResponsible` är alla **Single line of text**
- Canvas: **1366 × 768** Fixed 16:9 Default

DEL 1 — CorrectionScreen

1.1 Översikt — så ska det se ut

```
┌──────────────────────────────────────────────────────────────────────┐
│ [◀] Correction / Edit Mode                                (blå header)  │
├──────────────────────────────────────────────────────────────────────┤
│ ⚠ Correction Mode — use only to fix past data. Daily input should use…  │
├──────────────────────────────────────────────────────────────────────┤
│ Category: [EHS ▾]   Date: [2026-04-14]   [ Load Row ]                  │
│                                                                        │
│ Status: Existing EHS row loaded for 2026-04-14 — Save will update it.  │
├──────────────────────────────────────────────────────────────────────┤
│                                                                        │
│  (Formulär visas beroende på vald kategori — EHS / Quality / Delivery)  │
│                                                                        │
│                                                                        │
│                                                                        │
│                                                                        │
│                                                                        │
│                                                                        │
│  [ Save Correction ]                                                   │
└──────────────────────────────────────────────────────────────────────┘
```

1.2 Skapa skärmen

1. Power Apps Studio → vänster panel → **+ New screen** → **Blank**

2. Rename: `CorrectionScreen`
3. Properties → **Fill:** `RGBA(245, 246, 250, 1)`

1.3 Lägg in OnVisible-koden

Klicka på `CorrectionScreen` → properties-dropdown → **OnVisible**:

```
Set(varCorrectionStatus, "No row loaded. Select category + date, then click Load Row.");
Set(varCorrection_EHS, Blank());
Set(varCorrection_Q, Blank());
Set(varCorrection_D, Blank())
```

1.4 Bygg header (3 kontroller)

Rectangle1_Corr (blå balk)

1. Insert → Shapes → **Rectangle**
2. Rename: `Rectangle1_Corr`
3. Properties:
   - **X:** `0`
   - **Y:** `0`
   - **Width:** `Parent.Width`
   - **Height:** `80`
   - **Fill:** `RGBA(56, 96, 178, 1)`

IconCorr_Back

1. Insert → Icons → **Back arrow**
2. Rename: `IconCorr_Back`
3. Properties:
   - **X:** `20` , **Y:** `20`
   - **Width:** `40` , **Height:** `40`
   - **Color:** `RGBA(255, 255, 255, 1)`
   - **OnSelect:** `Navigate(HomeScreen, ScreenTransition.UnCover)`

lblCorr_Title

1. Insert → Label

2. Rename: `lblCorr_Title`
3. Properties:
   - **X:** `80` , **Y:** `20` , **Width:** `600` , **Height:** `30`
   - **Text:** `"Correction / Edit Mode"`
   - **Color:** `RGBA(255, 255, 255, 1)`
   - **Size:** `20` , **FontWeight:** `FontWeight.Bold`

1.5 Varningstext

1. Insert → Label → rename: `lblCorr_Warning`
2. Properties:
   - **X:** `30` , **Y:** `95` , **Width:** `1300` , **Height:** `25`
   - **Text:** `"⚠ Correction Mode — use only to fix past data. Daily input should use Daily Mode."`
   - **Color:** `RGBA(224, 0, 0, 1)`
   - **Size:** `13`
   - **Italic:** `true`

1.6 Kategori-val (Dropdown)

1. Insert → Input → **Dropdown**
2. Rename: `ddCategory`
3. Properties:
   - **X:** `30` , **Y:** `135` , **Width:** `200` , **Height:** `40`
   - **Items:** `["EHS", "Quality", "Delivery"]`

1.7 Datum-väljare

1. Insert → Input → **Date picker**
2. Rename: `dpCorrectionDate`
3. Properties:
   - **X:** `250` , **Y:** `135` , **Width:** `200` , **Height:** `40`
   - **DefaultDate:** `Today()`

1.8 Load Row-knapp

1. Insert → Button → rename: `btnCorrectionLoad`
2. Properties:
   - **X:** `470` , **Y:** `135` , **Width:** `130` , **Height:** `40`
   - **Text:** `"Load Row"`
   - **Fill:** `RGBA(56, 96, 178, 1)`
   - **Color:** `RGBA(255, 255, 255, 1)`

OnSelect — klistra in exakt:

```
If(
    IsBlank(ddCategory.Selected) || IsBlank(dpCorrectionDate.SelectedDate),
    Set(varCorrectionStatus, "⚠ Please select both category and date first."),

    Switch(
        ddCategory.Selected.Value,

        "EHS",
        Set(varCorrection_EHS, LookUp(QDIP_EHS_Daily, InputDate = dpCorrectionDate.SelectedD
        Set(varCorrection_Q, Blank());
        Set(varCorrection_D, Blank());
        Set(varCorrectionStatus,
            If(IsBlank(varCorrection_EHS),
                "No EHS row found for " & Text(dpCorrectionDate.SelectedDate, "yyyy-mm-dd")
                "Existing EHS row loaded for " & Text(dpCorrectionDate.SelectedDate, "yyyy-m
            )
        ),

        "Quality",
        Set(varCorrection_Q, LookUp(QDIP_Quality_Daily, InputDate = dpCorrectionDate.Selecte
        Set(varCorrection_EHS, Blank());
        Set(varCorrection_D, Blank());
        Set(varCorrectionStatus,
            If(IsBlank(varCorrection_Q),
                "No Quality row found for " & Text(dpCorrectionDate.SelectedDate, "yyyy-mm-d
                "Existing Quality row loaded for " & Text(dpCorrectionDate.SelectedDate, "yy
            )
        ),

        "Delivery",
        Set(varCorrection_D, LookUp(QDIP_Delivery_Daily, InputDate = dpCorrectionDate.Select
        Set(varCorrection_EHS, Blank());
        Set(varCorrection_Q, Blank());
        Set(varCorrectionStatus,
            If(IsBlank(varCorrection_D),
                "No Delivery row found for " & Text(dpCorrectionDate.SelectedDate, "yyyy-mm-
                "Existing Delivery row loaded for " & Text(dpCorrectionDate.SelectedDate, "y
```

```
            )
        )
    )
)
```

1.9 Status-label

1. Insert → Label → rename: `lblCorrectionStatus`
2. Properties:
   - **X:** `30` , **Y:** `185` , **Width:** `1300` , **Height:** `25`
   - **Text:** `varCorrectionStatus`
   - **Size:** `13`
   - **FontWeight:** `FontWeight.Semibold`
   - **Color:**

```
If(StartsWith(varCorrectionStatus, "⚠"), RGBA(224, 0, 0, 1),
    If(StartsWith(varCorrectionStatus, "Existing"), RGBA(245, 158, 11, 1),
        If(StartsWith(varCorrectionStatus, "No "), RGBA(0, 176, 80, 1),
            RGBA(80, 80, 80, 1)
        )
    )
)
```

1.10 Container för EHS-formulär

1. Insert → Layout → **Container** (Variant: ManualLayout)
2. Rename: `cntCorr_EHS`
3. Properties:
   - **X:** `20` , **Y:** `225` , **Width:** `1326` , **Height:** `470`
   - **Visible:** `ddCategory.Selected.Value = "EHS"`
   - **Fill:** `RGBA(255, 255, 255, 1)`
   - **BorderColor:** `RGBA(220, 220, 220, 1)`
   - **BorderThickness:** `1`

Inuti cntCorr_EHS

Markera `cntCorr_EHS` i Tree view innan du sätter in varje nedanstående kontroll — då hamnar de inuti containern.

EHS Score (obligatorisk):

- Label `lblCorr_EHSScoreLabel` : X=20, Y=15, W=250, H=18, Text="EHS Checklist Score *", Size=11
- TextInput `txtCorr_EHSScore` : X=20, Y=35, W=180, H=36, Format=Number
  - **Default:** `If(IsBlank(varCorrection_EHS), "", Text(varCorrection_EHS.EHS_Checklist_Score))`

Amplicon + Incident:

- Label `lblCorr_EHSAmpliconLabel` : X=220, Y=15, W=180, H=18, Text="Amplicon Points", Size=11
- TextInput `txtCorr_EHSAmplicon` : X=220, Y=35, W=180, H=36, Format=Number
  - **Default:** `If(IsBlank(varCorrection_EHS), "", Text(varCorrection_EHS.Amplicon_Positive_Points))`
- Label `lblCorr_EHSIncidentLabel` : X=420, Y=15, W=180, H=18, Text="Incident Count", Size=11
- TextInput `txtCorr_EHSIncident` : X=420, Y=35, W=180, H=36, Format=Number
  - **Default:** `If(IsBlank(varCorrection_EHS), "", Text(varCorrection_EHS.Incident_Count))`

EHS Causes rubrik:

- Label `lblCorr_EHSCausesHeader` : X=20, Y=90, W=400, H=20, Text="EHS Causes (optional)", Size=11, FontWeight=Semibold

EHS Causes-fält (5 st):

Rad layout: Label Y=115, Input Y=135, Height input=34, Width=140

Kontroll	X	Text (för label)	Default (för input)
lblCorr_EHSCause_PPE + txtCorr_EHSPPE	20	"Incorrect PPE"	`If(IsBlank(varCorrection_EHS), "", Text(varCorrection_EHS.Cause_IncorrectPPE))`
lblCorr_EHSCause_CM + txtCorr_EHSCM	170	"Open CM Boxes"	`If(IsBlank(varCorrection_EHS), "", Text(varCorrection_EHS.Cause_OpenCMBoxes))`
lblCorr_EHSCause_Shoes + txtCorr_EHSShoes	320	"Shoes Not On Shelf"	`If(IsBlank(varCorrection_EHS), "", Text(varCorrection_EHS.Cause_ShoesNotOnShelf))`
lblCorr_EHSCause_Checklist + txtCorr_EHSChecklist	470	"Checklist Not Signed"	`If(IsBlank(varCorrection_EHS), "", Text(varCorrection_EHS.Cause_ChecklistNotSigned))`
lblCorr_EHSCause_Other + txtCorr_EHSOther	620	"Other"	`If(IsBlank(varCorrection_EHS), "", Text(varCorrection_EHS.Cause_Other))`

Varje label: W=140, H=18, Size=10 Varje input: W=140, H=34, Format=Number

EHS Notes:

- Label `lblCorr_EHSNotesLabel` : X=20, Y=195, W=150, H=18, Text="EHS Notes", Size=11
- TextInput `txtCorr_EHSNotes` : X=20, Y=215, W=1000, H=40, **Mode=TextMode.MultiLine**, ingen Format-property
  - **Default:** `If(IsBlank(varCorrection_EHS), "", varCorrection_EHS.Notes)`

1.11 Container för Quality-formulär

1. Insert → Layout → Container → rename: `cntCorr_Quality`
2. Properties:
   - **X:** `20` , **Y:** `225` , **Width:** `1326` , **Height:** `470`
   - **Visible:** `ddCategory.Selected.Value = "Quality"`
   - **Fill:** `RGBA(255, 255, 255, 1)`
   - **BorderColor:** `RGBA(220, 220, 220, 1)`
   - **BorderThickness:** `1`

Inuti cntCorr_Quality

NRFT + LFI counts (obligatoriska):

- Label `lblCorr_NRFTLabel` : X=20, Y=15, W=180, H=18, Text="NRFT Count *", Size=11
- TextInput `txtCorr_NRFT` : X=20, Y=35, W=180, H=36, Format=Number
  - **Default:** `If(IsBlank(varCorrection_Q), "", Text(varCorrection_Q.NRFT_Count))`
- Label `lblCorr_LFILabel` : X=220, Y=15, W=180, H=18, Text="LFI Count *", Size=11
- TextInput `txtCorr_LFI` : X=220, Y=35, W=180, H=36, Format=Number
  - **Default:** `If(IsBlank(varCorrection_Q), "", Text(varCorrection_Q.LFI_Count))`

Expand-knappar (samma mönster som DailyScreen-panelen):

- Button `btnCorr_ShowNRFT` : X=420, Y=35, W=180, H=36
  - **Text:** `If(varCorrShowNRFT, "Hide NRFT causes", "Show NRFT causes")`
  - **Fill:** `RGBA(56, 96, 178, 1)` , **Color:** vit
  - **OnSelect:**

```
Set(varCorrShowNRFT, !varCorrShowNRFT);
Set(varCorrShowLFI, false)
```

- Button `btnCorr_ShowLFI` : X=610, Y=35, W=180, H=36
  - **Text:** `If(varCorrShowLFI, "Hide LFI causes", "Show LFI causes")`
  - **Fill:** `RGBA(56, 96, 178, 1)` , **Color:** vit
  - **OnSelect:**

```
Set(varCorrShowLFI, !varCorrShowLFI);
Set(varCorrShowNRFT, false)
```

Sub-container för NRFT-causes (11 fält):

1. Markera `cntCorr_Quality` → Insert → Layout → Container → rename: `cntCorr_NRFTCauses`
2. Properties:
   - **X:** `20` , **Y:** `90` , **Width:** `1280` , **Height:** `200`
   - **Visible:** `varCorrShowNRFT`
   - **Fill:** `RGBA(250, 250, 250, 1)` , **BorderColor:** `RGBA(230, 230, 230, 1)`

Inuti cntCorr_NRFTCauses — 11 labels + 11 textfält, 4 per rad:

Rader: Y label = 10/75/140, Y input = 30/95/160 Kolumn-X: 10, 275, 540, 805 (4 per rad i rad 1 och 2, 3 i rad 3)

Namn-mönster: `lblCorr_NRFT_XXX` + `txtCorr_NRFT_XXX` där XXX är kolumnnamnet utan prefix.

Alla kolumner att skapa (se "Text" och "Default"):

#	Suffix	Text	SharePoint-kolumn (för Default)
1	WrongInfoChecklist	"Wrong info checklist"	Cause_NRFT_WrongInfoChecklist
2	MissingInfoChecklist	"Missing info checklist"	Cause_NRFT_MissingInfoChecklist
3	MissingSigWorksheet	"Missing sign worksheet"	Cause_NRFT_MissingSigWorksheet
4	WrongRevWorksheet	"Wrong rev worksheet"	Cause_NRFT_WrongRevWorksheet
5	MissingPDRChecklist	"Missing PDR checklist"	Cause_NRFT_MissingPDRChecklist
6	MissingPDRWorksheet	"Missing PDR worksheet"	Cause_NRFT_MissingPDRWorksheet
7	WrongOBRChecklist	"Wrong OBR checklist"	Cause_NRFT_WrongOBRChecklist
8	CarrierMoveNC	"Carrier move NC"	Cause_NRFT_CarrierMoveNC
9	LotMovedNCFlow	"Lot moved NC flow"	Cause_NRFT_LotMovedNCFlow
10	Other	"Other"	Cause_NRFT_Other

11	ChecklistNotExecuted	“Checklist not executed”	Cause_NRFT_ChecklistNotExecuted

Varje label: W=250, H=18, Size=10 Varje input: W=250, H=34, Format=Number

Default-formel för varje input:

```
If(IsBlank(varCorrection_Q), "", Text(Coalesce(varCorrection_Q.Cause_NRFT_XXX, 0)))
```

(byt ut XXX till rätt kolumnnamn)

Rad-positioner:

Rad	Y label	Y input	Fält
1	10	30	1, 2, 3, 4 (på X=10, 275, 540, 805)
2	75	95	5, 6, 7, 8
3	140	160	9, 10, 11

Snabbare: Om du redan byggt panelens cntNRFTCauses i DailyScreen, kopiera den helt enkelt (Tree view → högerklicka cntNRFTCauses → Copy → klistra in inuti cntCorr_Quality → rename till cntCorr_NRFTCauses → byt Visible-regel + alla Default-formler till `varCorrection_Q` istället för `varQ_LagCurrent`).

Sub-container för LFI-causes (9 fält):

1. Markera `cntCorr_Quality` → Insert → Layout → Container → rename: `cntCorr_LFICauses`
2. Properties:
   - **X:** `20` , **Y:** `90` , **Width:** `1280` , **Height:** `200`
   - **Visible:** `varCorrShowLFI`
   - Samma Fill/Border som NRFT

Innehåll (9 LFI-fält, 3 per rad):

#	Suffix	Text	SP-kolumn
1	Dilution	“Dilution”	Cause_LFI_Dilution
2	Vortexing	“Vortexing”	Cause_LFI_Vortexing
3	VortexingPippeting	“Vortexing / Pippeting”	Cause_LFI_VortexingPippeting
4	SampleAddition	“Sample addition”	Cause_LFI_SampleAddition
5	Contamination	“Contamination”	Cause_LFI_Contamination
6	NCAfterInitiated	“NC after initiated”	Cause_LFI_NCAfterInitiated

7	NCControlMaterial	“NC control material”	Cause_LFI_NCControlMaterial
8	VoidedLFI	“Voided LFI”	Cause_LFI_VoidedLFI
9	Other	“Other”	Cause_LFI_Other

Namn-mönster: `lblCorr_LFI_XXX` + `txtCorr_LFI_XXX`

Positioner: 3 rader × 3 kolumner. X: 10, 360, 710. Y label: 10/75/140, Y input: 30/95/160. W=300, H=34.

Default:

```
If(IsBlank(varCorrection_Q), "", Text(Coalesce(varCorrection_Q.Cause_LFI_XXX, 0)))
```

Quality Notes:

- Label `lblCorr_QNotesLabel` : X=20, Y=305, W=150, H=18, Text=“Quality Notes”, Size=11
- TextInput `txtCorr_QNotes` : X=20, Y=325, W=1000, H=40, **Mode=TextMode.MultiLine**
  - **Default:** `If(IsBlank(varCorrection_Q), "", varCorrection_Q.Notes)`

1.12 Container för Delivery-formulär

1. Insert → Layout → Container → rename: `cntCorr_Delivery`
2. Properties:
   - **X:** `20` , **Y:** `225` , **Width:** `1326` , **Height:** `470`
   - **Visible:** `ddCategory.Selected.Value = "Delivery"`

Inuti cntCorr_Delivery

D_Leading_LotsWIP_10hPlus (obligatorisk):

- Label `lblCorr_DWIPLabel` : X=20, Y=15, W=250, H=18, Text=“Lots WIP >= 10h *”, Size=11
- TextInput `txtCorr_DWIP` : X=20, Y=35, W=180, H=36, Format=Number
  - **Default:** `If(IsBlank(varCorrection_D), "", Text(varCorrection_D.D_Leading_LotsWIP_10hPlus))`

Expand-knapp för Delivery Causes:

- Button `btnCorr_ShowDCauses` : X=220, Y=35, W=220, H=36
  - **Text:** `If(varCorrShowDCauses, "Hide Delivery causes", "Show Delivery causes")`
  - **Fill:** `RGBA(56, 96, 178, 1)` , **Color:** vit
  - **OnSelect:** `Set(varCorrShowDCauses, !varCorrShowDCauses)`

Sub-container för Delivery Causes (13 fält):

1. Markera `cntCorr_Delivery` → Insert → Container → rename: `cntCorr_DeliveryCauses`
2. Properties:
   - **X:** `20` , **Y:** `90` , **Width:** `1280` , **Height:** `240`
   - **Visible:** `varCorrShowDCauses`

Innehåll (13 Delivery-fält, 4 per rad + 1):

#	Suffix	Text	SP-kolumn
1	MissingReplicates	"Missing replicates"	Cause_MissingReplicates
2	SmallLots	"Small lots"	Cause_SmallLots
3	StaffingIssues	"Staffing issues"	Cause_StaffingIssues
4	AbortedLots	"Aborted lots"	Cause_AbortedLots
5	NC	"NC"	Cause_NC
6	Resample	"Resample"	Cause_Resample
7	SPInputError	"SP input error"	Cause_SPInputError
8	SRRetest	"SR retest"	Cause_SRRetest
9	QAFinding	"QA finding"	Cause_QAFinding
10	MissFromROBAL	"Miss from ROBAL"	Cause_MissFromROBAL
11	ITMESIssues	"IT/MES issues"	Cause_ITMESIssues
12	UnknownReason	"Unknown reason"	Cause_UnknownReason
13	FoundOverdueLotsPowerBI	"Found overdue lots PBI"	Cause_FoundOverdueLotsPowerBI

Namn-mönster: `lblCorr_D_XXX` + `txtCorr_D_XXX`

Positioner: 4 rader × 4 kolumner (sista raden 1 fält). X: 10, 325, 640, 955. Y label: 10/80/150/220, Y input: 30/100/170/240. W=300, H=34.

Default:

```
If(IsBlank(varCorrection_D), "", Text(Coalesce(varCorrection_D.Cause_XXX, 0)))
```

Delivery Notes:

- Label `lblCorr_DNotesLabel` : X=20, Y=345, W=150, H=18, Text="Delivery Notes", Size=11

- TextInput `txtCorr_DNotes` : X=20, Y=365, W=1000, H=40, **Mode=TextMode.MultiLine**
  - **Default:** `If(IsBlank(varCorrection_D), "", varCorrection_D.Notes)`

1.13 Save-knapp

1. Insert → Button → rename: `btnCorrectionSave`
2. Properties:
   - **X:** `30` , **Y:** `710` , **Width:** `300` , **Height:** `45`
   - **Text:** `"Save Correction"`
   - **Fill:** `RGBA(0, 176, 80, 1)` , **Color:** vit
   - **FontWeight:** `FontWeight.Bold`

OnSelect — klistra in exakt:

```
If(
    IsBlank(ddCategory.Selected) || IsBlank(dpCorrectionDate.SelectedDate),
    Notify("Please select category and date first", NotificationType.Error),

    Switch(
        ddCategory.Selected.Value,

        "EHS",
        If(IsBlank(txtCorr_EHSScore.Text),
            Notify("EHS Checklist Score is required", NotificationType.Error),
            Patch(
                QDIP_EHS_Daily,
                If(IsBlank(varCorrection_EHS), Defaults(QDIP_EHS_Daily), varCorrection_EHS),
                {
                    Title: "EHS " & Text(dpCorrectionDate.SelectedDate, "yyyy-mm-dd"),
                    InputDate: dpCorrectionDate.SelectedDate,
                    EHS_Checklist_Score: Value(txtCorr_EHSScore.Text),
                    Amplicon_Positive_Points: If(IsBlank(txtCorr_EHSAmplicon.Text), 0, Value
                    Incident_Count: If(IsBlank(txtCorr_EHSIncident.Text), 0, Value(txtCorr_E
                    Cause_IncorrectPPE: If(IsBlank(txtCorr_EHSPPE.Text), 0, Value(txtCorr_EH
                    Cause_OpenCMBoxes: If(IsBlank(txtCorr_EHSCM.Text), 0, Value(txtCorr_EHSC
                    Cause_ShoesNotOnShelf: If(IsBlank(txtCorr_EHSShoes.Text), 0, Value(txtCo
                    Cause_ChecklistNotSigned: If(IsBlank(txtCorr_EHSChecklist.Text), 0, Valu
                    Cause_Other: If(IsBlank(txtCorr_EHSOther.Text), 0, Value(txtCorr_EHSOthe
                    Notes: txtCorr_EHSNotes.Text
                }
            );
            Set(varCorrection_EHS, LookUp(QDIP_EHS_Daily, InputDate = dpCorrectionDate.Selec
            Set(varCorrectionStatus, "Saved EHS for " & Text(dpCorrectionDate.SelectedDate,
            Notify("EHS correction saved", NotificationType.Success)
        ),

        "Quality",
```

```
If(IsBlank(txtCorr_NRFT.Text) || IsBlank(txtCorr_LFI.Text),
    Notify("NRFT and LFI counts are required", NotificationType.Error),
    Patch(
        QDIP_Quality_Daily,
        If(IsBlank(varCorrection_Q), Defaults(QDIP_Quality_Daily), varCorrection_Q),
        {
            Title: "Q " & Text(dpCorrectionDate.SelectedDate, "yyyy-mm-dd"),
            InputDate: dpCorrectionDate.SelectedDate,
            NRFT_Count: Value(txtCorr_NRFT.Text),
            LFI_Count: Value(txtCorr_LFI.Text),
            Cause_NRFT_WrongInfoChecklist: If(IsBlank(txtCorr_NRFT_WrongInfoChecklis
            Cause_NRFT_MissingInfoChecklist: If(IsBlank(txtCorr_NRFT_MissingInfoChec
            Cause_NRFT_MissingSigWorksheet: If(IsBlank(txtCorr_NRFT_MissingSigWorksh
            Cause_NRFT_WrongRevWorksheet: If(IsBlank(txtCorr_NRFT_WrongRevWorksheet.
            Cause_NRFT_MissingPDRChecklist: If(IsBlank(txtCorr_NRFT_MissingPDRCheckl
            Cause_NRFT_MissingPDRWorksheet: If(IsBlank(txtCorr_NRFT_MissingPDRWorksh
            Cause_NRFT_WrongOBRChecklist: If(IsBlank(txtCorr_NRFT_WrongOBRChecklist.
            Cause_NRFT_CarrierMoveNC: If(IsBlank(txtCorr_NRFT_CarrierMoveNC.Text), 0
            Cause_NRFT_LotMovedNCFlow: If(IsBlank(txtCorr_NRFT_LotMovedNCFlow.Text),
            Cause_NRFT_Other: If(IsBlank(txtCorr_NRFT_Other.Text), 0, Value(txtCorr_
            Cause_NRFT_ChecklistNotExecuted: If(IsBlank(txtCorr_NRFT_ChecklistNotExe
            Cause_LFI_Dilution: If(IsBlank(txtCorr_LFI_Dilution.Text), 0, Value(txtC
            Cause_LFI_Vortexing: If(IsBlank(txtCorr_LFI_Vortexing.Text), 0, Value(tx
            Cause_LFI_VortexingPippeting: If(IsBlank(txtCorr_LFI_VortexingPippeting.
            Cause_LFI_SampleAddition: If(IsBlank(txtCorr_LFI_SampleAddition.Text), 0
            Cause_LFI_Contamination: If(IsBlank(txtCorr_LFI_Contamination.Text), 0, 
            Cause_LFI_NCAfterInitiated: If(IsBlank(txtCorr_LFI_NCAfterInitiated.Text
            Cause_LFI_NCControlMaterial: If(IsBlank(txtCorr_LFI_NCControlMaterial.Te
            Cause_LFI_VoidedLFI: If(IsBlank(txtCorr_LFI_VoidedLFI.Text), 0, Value(tx
            Cause_LFI_Other: If(IsBlank(txtCorr_LFI_Other.Text), 0, Value(txtCorr_LF
            Notes: txtCorr_QNotes.Text
        }
    );
    Set(varCorrection_Q, LookUp(QDIP_Quality_Daily, InputDate = dpCorrectionDate.Sel
    Set(varCorrectionStatus, "Saved Quality for " & Text(dpCorrectionDate.SelectedDa
    Notify("Quality correction saved", NotificationType.Success)
),

"Delivery",
If(IsBlank(txtCorr_DWIP.Text),
    Notify("D_Leading_LotsWIP_10hPlus is required", NotificationType.Error),
    Patch(
        QDIP_Delivery_Daily,
        If(IsBlank(varCorrection_D), Defaults(QDIP_Delivery_Daily), varCorrection_D)
        {
            Title: "D " & Text(dpCorrectionDate.SelectedDate, "yyyy-mm-dd"),
            InputDate: dpCorrectionDate.SelectedDate,
            D_Leading_LotsWIP_10hPlus: Value(txtCorr_DWIP.Text),
            Cause_MissingReplicates: If(IsBlank(txtCorr_D_MissingReplicates.Text), 0
            Cause_SmallLots: If(IsBlank(txtCorr_D_SmallLots.Text), 0, Value(txtCorr_
            Cause_StaffingIssues: If(IsBlank(txtCorr_D_StaffingIssues.Text), 0, Valu
            Cause_AbortedLots: If(IsBlank(txtCorr_D_AbortedLots.Text), 0, Value(txtC
            Cause_NC: If(IsBlank(txtCorr_D_NC.Text), 0, Value(txtCorr_D_NC.Text)),
```

```
                    Cause_Resample: If(IsBlank(txtCorr_D_Resample.Text), 0, Value(txtCorr_D_
                    Cause_SPInputError: If(IsBlank(txtCorr_D_SPInputError.Text), 0, Value(tx
                    Cause_SRRetest: If(IsBlank(txtCorr_D_SRRetest.Text), 0, Value(txtCorr_D_
                    Cause_QAFinding: If(IsBlank(txtCorr_D_QAFinding.Text), 0, Value(txtCorr_
                    Cause_MissFromROBAL: If(IsBlank(txtCorr_D_MissFromROBAL.Text), 0, Value(
                    Cause_ITMESIssues: If(IsBlank(txtCorr_D_ITMESIssues.Text), 0, Value(txtC
                    Cause_UnknownReason: If(IsBlank(txtCorr_D_UnknownReason.Text), 0, Value(
                    Cause_FoundOverdueLotsPowerBI: If(IsBlank(txtCorr_D_FoundOverdueLotsPowe
                    Notes: txtCorr_DNotes.Text
                }
            );
            Set(varCorrection_D, LookUp(QDIP_Delivery_Daily, InputDate = dpCorrectionDate.Se
            Set(varCorrectionStatus, "Saved Delivery for " & Text(dpCorrectionDate.SelectedD
            Notify("Delivery correction saved", NotificationType.Success)
        )
    )
)
```

DEL 2 — ActionsScreen

2.1 Översikt

```
┌──────────────────────────────────────────────────────────────────────┐
│ [◀] QDIP Actions                                        (blå header)  │
├──────────────────────────────────────────────────────────────────────┤
│ [+ New Action]           Filter: [Open ▾]   Search: [________]       │
├──────────────────────────────────────────────────────────────────────┤
│ Section │ Date       │ Issue Description      │ Person    │ Due    │St. │
│ EHS     │ 2026-04-14 │ Shoes not on shelf...  │ Marcus    │ 04-21  │Open│
│ Q       │ 2026-04-12 │ Missing OBR on chk     │ Anna      │ 04-20  │ IP │
│ D       │ 2026-04-10 │ Resample backlog       │ Erik      │ 04-17  │Open│
│                                                                      │
└──────────────────────────────────────────────────────────────────────┘
```

2.2 Skapa skärmen

1. - New screen → Blank → rename: `ActionsScreen`
2. **Fill:** `RGBA(245, 246, 250, 1)`

2.3 Header (3 kontroller)

Rectangle1_Act

- Insert → Rectangle → rename: `Rectangle1_Act`

- **X:**0, **Y:**0, **Width:**Parent.Width, **Height:**80
- **Fill:** `RGBA(56, 96, 178, 1)`

IconAct_Back

- Insert → Icon → Back arrow → rename: `IconAct_Back`
- **X:**20, **Y:**20, **Width:**40, **Height:**40, **Color:** vit
- **OnSelect:** `Navigate(HomeScreen, ScreenTransition.UnCover)`

lblAct_Title

- Insert → Label → rename: `lblAct_Title`
- **X:**80, **Y:**20, **Width:**600, **Height:**30
- **Text:** `"QDIP Actions"` , **Color:** vit, **Size:**20, **FontWeight:** Bold

2.4 Toolbar (under headern)

btnNewAction

- Insert → Button → rename: `btnNewAction`
- **X:**30, **Y:**100, **Width:**180, **Height:**45
- **Text:** `"+ New Action"`
- **Fill:** `RGBA(0, 176, 80, 1)` , **Color:** vit
- **FontWeight:** Bold
- **OnSelect:**

```
Set(varEditAction, Blank());
Navigate(EditActionScreen, ScreenTransition.Cover)
```

lblFilterLabel

- Insert → Label → rename: `lblFilterLabel`
- **X:**240, **Y:**115, **Width:**60, **Height:**18
- **Text:** `"Filter:"` , **Size:** 11

ddActionFilter

- Insert → Input → Dropdown → rename: `ddActionFilter`
- **X:**300, **Y:**105, **Width:**180, **Height:**40

- **Items:** `["All", "Open", "In Progress", "Closed"]`
- **Default:** `"Open"`

lblSearchLabel

- Insert → Label → rename: `lblSearchLabel`
- **X:**510, **Y:**115, **Width:**70, **Height:**18
- **Text:** `"Search:"` , **Size:** 11

txtSearch

- Insert → Text input → rename: `txtSearch`
- **X:**580, **Y:**105, **Width:**300, **Height:**40
- **HintText:** `"Search in issue or location..."`
- **Default:** `""`

2.5 Gallery-rubrikrad

Vi lägger till en fast rubrikrad ovanför galleriet:

rectHeaderRow

- Insert → Rectangle → rename: `rectHeaderRow`
- **X:**20, **Y:**165, **Width:**1326, **Height:**36
- **Fill:** `RGBA(56, 96, 178, 1)`

Rubrik-labels (7 st)

Alla på Y=170, Height=26, Color=vit, Size=11, FontWeight=Bold

Kontroll	X	Width	Text
lblHeader_Section	30	80	“Section”
lblHeader_Date	115	120	“Date identified”
lblHeader_Issue	240	400	“Issue”
lblHeader_Corrective	645	380	“Corrective action”
lblHeader_Person	1030	140	“Owner”
lblHeader_Due	1175	110	“Due”
lblHeader_Status	1290	60	“Status”

2.6 Gallery

1. Insert → Gallery → **Blank vertical** → rename: `galActions`
2. **X:**20, **Y:**205, **Width:**1326, **Height:**540
3. **TemplateSize:** `48`
4. **TemplatePadding:** `0`

Items:

```
SortByColumns(
    Filter(QDIP_Actions,
        (ddActionFilter.Selected.Value = "All" || Status = ddActionFilter.Selected.Value)
        && (
            IsBlank(txtSearch.Text) ||
            StartsWith(IssueDescription, txtSearch.Text) ||
            StartsWith(Location, txtSearch.Text)
        )
    ),
    "DateIdentified",
    SortOrder.Descending
)
```

Gallery template (rad-innehåll)

Markera `galActions` i Tree view → klicka på första raden (TemplateLayout) → lägg till följande kontroller:

Bakgrundsrektangel (för varvade rader):

- Insert → Rectangle → rename: `rectRowBg`
- **X:**0, **Y:**0, **Width:**Parent.TemplateWidth, **Height:**48
- **Fill:** `If(Mod(ThisItem.ID, 2) = 0, RGBA(255, 255, 255, 1), RGBA(248, 249, 251, 1))`
- **BorderColor:** `RGBA(230, 230, 230, 1)`
- **BorderThickness:** `0.5`

Labels i raden (alla Y=12, H=24, Size=11):

Kontroll	X	Width	Text
lblRow_Section	10	80	`ThisItem.QDIP_Section`
lblRow_Date	95	120	`Text(ThisItem.DateIdentified, "yyyy-mm-dd")`
lblRow_Issue	220	400	`ThisItem.IssueDescription`
lblRow_Corrective	625	380	`ThisItem.CorrectiveActions`

lblRow_Person	1010	140	`ThisItem.PersonResponsible`
lblRow_Due	1155	110	`Text(ThisItem.ExpectedDueDate, "yyyy-mm-dd")`
lblRow_Status	1270	60	`ThisItem.Status`

Status-färgning: Klicka på `lblRow_Status` → Color-property:

```
Switch(ThisItem.Status,
    "Open", RGBA(224, 0, 0, 1),
    "In Progress", RGBA(245, 158, 11, 1),
    "Closed", RGBA(0, 176, 80, 1),
    RGBA(80, 80, 80, 1)
)
```

Sätt också **FontWeight:** `FontWeight.Semibold` på status-labeln.

Gallery OnSelect: Klicka på galleriets yttre kant (själva `galActions`) → OnSelect:

```
Set(varEditAction, ThisItem);
Navigate(EditActionScreen, ScreenTransition.Cover)
```

2.7 “Inga rader”-placeholder

Om filtret inte ger några träffar ska det stå något:

- Insert → Label → rename: `lblNoActions`
- **X:**20, **Y:**360, **Width:**1326, **Height:**30
- **Text:** `"No actions matching current filter."`
- **Align:** Center
- **Color:** `RGBA(120, 120, 120, 1)`
- **Italic:** true
- **Visible:** `CountRows(galActions.AllItems) = 0`

DEL 3 — EditActionScreen

3.1 Översikt

```
┌──────────────────────────────────────────────────────────────────────────┐
│ [◀] New Action   (eller Edit Action)                        (blå header)  │
├──────────────────────────────────────────────────────────────────────────┤
```

```
│                                                                          │
│ Section *          Date identified *       Status *                      │
│ [EHS ▾]            [2026-04-17]            [Open ▾]                      │
│                                                                          │
│ Location                   Owner                                         │
│ [_________________]        [_________________]                           │
│                                                                          │
│ Issue description *                                                      │
│ [____________________________________________________]                   │
│ [____________________________________________________]                   │
│                                                                          │
│ Corrective action(s)                                                     │
│ [____________________________________________________]                   │
│ [____________________________________________________]                   │
│                                                                          │
│ Required due date          Expected due date                             │
│ [2026-04-24]               [2026-04-24]                                  │
│                                                                          │
│ [ Save ]      [ Delete ]  (Delete only visible for existing)             │
│                                                                          │
└──────────────────────────────────────────────────────────────────────────┘
```

3.2 Skapa skärmen

1. - New screen → rename: `EditActionScreen`
2. **Fill:** `RGBA(245, 246, 250, 1)`

3.3 Header

Rectangle1_Edit

- Rectangle: X:0, Y:0, Width:Parent.Width, Height:80, Fill: `RGBA(56, 96, 178, 1)`

IconEdit_Back

- Icon Back: X:20, Y:20, W:40, H:40, Color: vit
- **OnSelect:** `Navigate(ActionsScreen, ScreenTransition.UnCover)`

lblEdit_Title

- Label: X:80, Y:20, W:600, H:30, Color vit, Size 20, Bold
- **Text:** `If(IsBlank(varEditAction), "New Action", "Edit Action")`

3.4 QDIP_Section (Text — statisk dropdown)

Eftersom kolumnen är Single line of text gör vi en **statisk dropdown** som sparar text.

lblEdit_SectionLabel

- Label: X:30, Y:105, W:200, H:18, Text: `"Section *"` , Size:11

ddEditSection

- Insert → Dropdown → rename: `ddEditSection`
- **X:**30, **Y:**125, **Width:**200, **Height:**40
- **Items:** `["EHS", "Quality", "Delivery"]`
- **Default:** `If(IsBlank(varEditAction), Blank(), {Value: varEditAction.QDIP_Section})`

OBS om Default: Eftersom Items är en lista av strängar, vill Dropdown ha antingen en sträng eller ett record med Value. Ovanstående funkar.

3.5 DateIdentified

lblEdit_DateIdLabel

- Label: X:260, Y:105, W:200, H:18, Text: `"Date identified *"` , Size:11

dpEditDateIdentified

- Insert → Date picker → rename: `dpEditDateIdentified`
- **X:**260, **Y:**125, **Width:**200, **Height:**40
- **DefaultDate:** `If(IsBlank(varEditAction), Today(), varEditAction.DateIdentified)`

3.6 Status (Text — statisk dropdown)

lblEdit_StatusLabel

- Label: X:490, Y:105, W:200, H:18, Text: `"Status *"` , Size:11

ddEditStatus

- Insert → Dropdown → rename: `ddEditStatus`
- **X:**490, **Y:**125, **Width:**200, **Height:**40
- **Items:** `["Open", "In Progress", "Closed"]`
- **Default:** `If(IsBlank(varEditAction), {Value: "Open"}, {Value: varEditAction.Status})`

3.7 Location

lblEdit_LocationLabel

- Label: X:30, Y:185, W:200, H:18, Text: `"Location"` , Size:11

txtEditLocation

- Text input: X:30, Y:205, W:430, H:40
- **Default:** `If(IsBlank(varEditAction), "", varEditAction.Location)`
- **HintText:** `"Work center, room..."`

3.8 PersonResponsible (Text)

lblEdit_PersonLabel

- Label: X:490, Y:185, W:200, H:18, Text: `"Owner"` , Size:11

txtEditPerson

- Text input: X:490, Y:205, W:430, H:40
- **Default:** `If(IsBlank(varEditAction), "", varEditAction.PersonResponsible)`
- **HintText:** `"Name or initials"`

3.9 IssueDescription (obligatorisk, multiline)

lblEdit_IssueLabel

- Label: X:30, Y:265, W:400, H:18, Text: `"Issue description *"` , Size:11

txtEditIssue

- Text input: X:30, Y:285, W:1290, H:70
- **Mode:** `TextMode.MultiLine`
- **Default:** `If(IsBlank(varEditAction), "", varEditAction.IssueDescription)`

3.10 CorrectiveActions (multiline)

lblEdit_CorrectiveLabel

- Label: X:30, Y:375, W:400, H:18, Text: `"Corrective action(s)"` , Size:11

txtEditCorrective

- Text input: X:30, Y:395, W:1290, H:70
- **Mode:** `TextMode.MultiLine`
- **Default:** `If(IsBlank(varEditAction), "", varEditAction.CorrectiveActions)`

3.11 RequiredDueDate

lblEdit_RequiredDueLabel

- Label: X:30, Y:485, W:200, H:18, Text: `"Required due date"` , Size:11

dpEditRequiredDue

- Date picker: X:30, Y:505, W:200, H:40
- **DefaultDate:** `If(IsBlank(varEditAction), DateAdd(Today(), 7, Days), varEditAction.RequiredDueDate)`

3.12 ExpectedDueDate

lblEdit_ExpectedDueLabel

- Label: X:260, Y:485, W:200, H:18, Text: `"Expected due date"` , Size:11

dpEditExpectedDue

- Date picker: X:260, Y:505, W:200, H:40
- **DefaultDate:** `If(IsBlank(varEditAction), DateAdd(Today(), 7, Days), varEditAction.ExpectedDueDate)`

3.13 Save-knapp

btnSaveAction

- Button: X:30, Y:575, W:200, H:45
- **Text:** `"Save"`
- **Fill:** `RGBA(0, 176, 80, 1)` , **Color:** vit, **Bold**

OnSelect:

```
If(
    IsBlank(ddEditSection.Selected) || IsBlank(txtEditIssue.Text) || IsBlank(ddEditStatus.Se
    Notify("Section, Issue description and Status are required", NotificationType.Error),

    Patch(
        QDIP_Actions,
        If(IsBlank(varEditAction), Defaults(QDIP_Actions), varEditAction),
        {
            Title: ddEditSection.Selected.Value & " - " & Text(dpEditDateIdentified.Selected
            QDIP_Section: ddEditSection.Selected.Value,
            DateIdentified: dpEditDateIdentified.SelectedDate,
            Location: txtEditLocation.Text,
```

```
            IssueDescription: txtEditIssue.Text,
            CorrectiveActions: txtEditCorrective.Text,
            PersonResponsible: txtEditPerson.Text,
            RequiredDueDate: dpEditRequiredDue.SelectedDate,
            ExpectedDueDate: dpEditExpectedDue.SelectedDate,
            Status: ddEditStatus.Selected.Value
        }
    );
    Notify("Action saved", NotificationType.Success);
    Navigate(ActionsScreen, ScreenTransition.UnCover)
)
```

3.14 Delete-knapp (bara för existerande actions)

btnDeleteAction

- Button: X:250, Y:575, W:200, H:45
- **Text:** `"Delete"`
- **Fill:** `RGBA(224, 0, 0, 1)` , **Color:** vit
- **Visible:** `!IsBlank(varEditAction)`

OnSelect:

```
Remove(QDIP_Actions, varEditAction);
Notify("Action deleted", NotificationType.Success);
Navigate(ActionsScreen, ScreenTransition.UnCover)
```

3.15 Cancel-knapp (valfri men rekommenderad)

btnCancelAction

- Button: X:470, Y:575, W:200, H:45
- **Text:** `"Cancel"`
- **Fill:** `RGBA(120, 120, 120, 1)` , **Color:** vit
- **OnSelect:** `Navigate(ActionsScreen, ScreenTransition.UnCover)`

DEL 4 — Testa hela flödet

Test 1: Correction Mode

1. HomeScreen → klicka **Correction / Edit**

2. Välj **EHS** i dropdown, välj ett datum där du vet att data finns (t.ex. 2026-04-14)
3. Klicka **Load Row** → status-label ska säga "Existing EHS row loaded..."
4. Ändra ett värde → klicka **Save Correction**
5. Verifiera i SharePoint att raden uppdaterats

Test 2: Skapa ny Action

1. HomeScreen → klicka **Actions**
2. Klicka **+ New Action**
3. Välj Section=EHS, skriv Issue="Test action", sätt Status=Open
4. Klicka **Save** → navigerar tillbaka till Gallery
5. Din nya rad ska synas överst (sorterad på datum descending)

Test 3: Redigera befintlig Action

1. Actions → klicka på en rad i Gallery
2. EditActionScreen öppnas med fälten förifyllda
3. Ändra Status till "In Progress" → **Save**
4. Gallery uppdateras → statusfärgen byter från röd till orange

Test 4: Radera Action

1. Actions → klicka på en rad → EditActionScreen
2. Klicka **Delete**
3. Rad försvinner från Gallery + från SharePoint

Test 5: Filter + Sök

1. Actions → Filter dropdown → välj "Closed"
2. Endast stängda actions syns
3. Skriv något i Search → listan filtreras på issue/location

DEL 5 — Publicera

När allt fungerar:

1. **File → Save** → Save to the cloud
2. **File → Publish** → Publish this version
3. **File → Share** → lägg till användare/grupper
4. I **Power BI Desktop** → page 10 → Insert → Power Apps visual → välj din app

---

DEL 6 — Byggordning och tidsuppskattning

Del	Tid
CorrectionScreen — header + toolbar + status	15 min
CorrectionScreen — cntCorr_EHS (6 huvudfält + 5 causes + notes)	30 min
CorrectionScreen — cntCorr_Quality (2 counts + 2 sub-containers + notes)	60 min
CorrectionScreen — cntCorr_Delivery (1 count + 1 sub-container + notes)	30 min
CorrectionScreen — Save-knapp med full kod	10 min
Subtotal CorrectionScreen	**~2h 15m**
ActionsScreen — header + toolbar + header-row	20 min
ActionsScreen — Gallery template	30 min
EditActionScreen — alla fält	45 min
EditActionScreen — Save, Delete, Cancel	15 min
Subtotal Actions	**~1h 50m**
Testa alla flöden	30 min
Totalt	**~4h 35m**

VIKTIGA OBSERVATIONER

1. **Gallery OnSelect vs ThisItem:** Om OnSelect inte triggar när man klickar på en rad, se till att det är på själva `galActions` (inte på en label inuti). Du kan också lägga till `OnSelect: Select(Parent)` på labels inuti raden så att klick propagerar.
2. **Dropdown Default med statisk lista:** När Items är `["EHS", "Quality", "Delivery"]` räknar Power Apps det som en tabell med kolumnen `Value`. Default måste vara `{Value: "EHS"}` — inte bara `"EHS"`. I spar-koden hämtar vi värdet med `.Value`.

3. **MultiLine-fält och Format:** Om du får fel att texten inte syns, kontrollera att Format-propertyn är borta från Notes/Issue/Corrective-fälten.
4. **Single line of text för datum?** QDIP_Actions verkar ha Date and Time-kolumner för DateIdentified/RequiredDueDate/ExpectedDueDate. Om någon av dem är Single line of text måste vi justera — säg till om du får fel.

När du byggt klart — skicka en skärmdump av:

1. CorrectionScreen (med en laddad rad)
2. ActionsScreen (med minst 2 testrader)
3. EditActionScreen (med en öppen action)

Då verifierar jag att allt sitter rätt.