

Name: Dherick D. Salavacion
Course, Year & Section: BSIT 4-1

Student Number: 202304527
Date: 09/19/2026

ONLINE ACTIVITY #2
Personalized Linux, and Git Cheat Sheet

Using any available resources (official Git documentation, online tutorials, or the built-in git --help command), research the following topics and create a personalized 1-page (A4) cheat sheet:

1. Basic Linux commands (command, sample usage) (at least 10)
2. Basic Git commands (command, sample usage, description (use your own wordings), common options/flags

git init	git restore
git status	git branch
git add	git checkout / git switch
git commit	git merge
git log	git tag
git diff	git clone

3. the three-tree architecture of Git

You are free to use any design or color scheme, just make sure it is readable.

Submission:

1. Use PDF as the file format for your cheat sheet.
2. Upload it to your GitHub repository
3. Submit the link here: <https://drive.google.com/drive/folders/1-Y6e6E6PoLyGgB0WZ8prRCNfolpV3cj0?usp=sharing>

Reminders:

Please put a "Reference" section in the cheat sheet for the materials you cited.

I DO NOT PROHIBIT the use of AI for this activity, but please declare the extent of the use.

Sample:

"The author used [Tool Name, Version] to [specific task] during assignment preparation. The author reviewed and edited the content as needed and takes full responsibility for the final content of the work."

Or

"I have not used any AI or AI-assisted technologies to prepare this work."

References:

<https://www.geeksforgeeks.org/linux-unix/basic-linux-commands/>

<https://git-scm.com/cheat-sheet>

<https://www.darwinbiler.com/understanding-the-3-tree-architecture-of-git/>

BASIC LINUX COMMANDS

COMMANDS	SYNTAX	USES
1. ls	ls [options] [directory]	The ls command lists all the directories and files.
2. pwd	pwd	The pwd command prints the absolute path of the current working directory.
3. mkdir	mkdir directory_name mkdir salvacion_act2	The <u>mkdir</u> command in Linux is used to create new directories or folders.
4. cd	cd directory_name	The <u>cd</u> command in Linux is used to change the current working directory.
5. rmdir	rmdir directory_name	The <u>rmdir</u> command in Linux is used to delete empty directories.
6. cat	cat file_name	The <u>cat</u> command in Linux is used to display file contents and combine multiple files.
7. cp	cp source destination Example: cp file1.txt file2.txt	The <u>cp</u> command in Linux is used to copy files or directories.
8. mv	mv old_name new_name Example: mv old.txt new.txt	The <u>mv</u> command in Linux is used to move or rename files and directories.
9. rm	rm file_name Example: rm demo.txt	The <u>rm</u> command in Linux is used to delete files permanently.
10. uname	uname [OPTIONS] Example: uname	The <u>uname</u> command in Linux is used to display system information.
11. locate	locate file_name Example: locate demo.txt	The locate command shows the path of the searched file.

12. touch	touch file_name Example: touch test.txt	The <u>touch</u> command in Linux is used to create empty files and updates file timestamps.
13. ln	ln -s source link_name Example: ln -s file1.txt link1.txt	The <u>ln</u> command in Linux is used to create links between files.
14. clear	clear	The <u>clear</u> command in Linux is used to clear the terminal screen.
15. ps	ps	The <u>ps</u> command in Linux is used to display running processes.
16. man	man command_name Example: man ls	The <u>man</u> command in Linux is used to display command manuals.
17. grep	grep "text" file_name Example: grep "Python" notes.txt	The <u>grep</u> command in Linux is used to search text patterns.
18. echo	echo "text" Example: echo "Hello Linux"	The <u>echo</u> command in Linux is used to display text in the terminal.
19. sort	sort file_name Example: sort test.txt	The <u>sort</u> command in Linux is used to sort file contents.

BASIC GIT COMMANDS

COMMANDS	USES
git init	Start a new repo
git clone <url>	Clone an existing repo
git add <file>	Add untracked file or unstaged changes
git commit -m 'message'	Make a commit
git add .	Add all untracked files and unstaged changes
git add -p	Choose which parts of a file to stage
git mv <old> <new>	Move file
git rm <file>	Delete file
git status	Check what you added
git switch <name>	Switch branches
git checkout -b <name>	Create a branch
git branch	List branches
git branch -d <name>	Delete a branch
git branch -D <name>	Force delete a branch
git checkout <file>	Delete unstaged changes to one file
git push origin main	Push the main branch to the remote origin
git push -u origin <name>	Push a branch that you've never pushed before
git pull origin main	Fetch changes and then merge them into your current branch

