


Intro to Aggregation: From Query Components to Aggregation Stages

INTRODUCTION TO MONGODB IN PYTHON

Donny Winston
Instructor



Queries have implicit stages

```
cursor = db.laureates.find(  
    filter={"bornCountry": "USA"},  
    projection={"prizes.year": 1},  
    limit=3  
)  
for doc in cursor:  
    print(doc["prizes"])
```

```
[{'year': '1923'}]  
[{'year': '1927'}]  
[{'year': '1936'}]
```

```
cursor = db.laureates.aggregate([  
    {"$match": {"bornCountry": "USA"}},  
    {"$project": {"prizes.year": 1}},  
    {"$limit": 3}  
)  
for doc in cursor:  
    print(doc["prizes"])
```

```
[{'year': '1923'}]  
[{'year': '1927'}]  
[{'year': '1936'}]
```

```
cursor = db.laureates.aggregate([  
    stage_1,  
    stage_2,  
    ...  
)
```

Adding sort and skip stages

```
from collections import OrderedDict

list(db.laureates.aggregate([
    {"$match": {"bornCountry": "USA"}},
    {"$project": {"prizes.year": 1, "_id": 0}},
    {"$sort": OrderedDict([("prizes.year", 1)])},
    {"$skip": 1},
    {"$limit": 3}
]))
```

```
[{'prizes': [{'year': '1912'}]},
 {'prizes': [{'year': '1914'}]},
 {'prizes': [{'year': '1919'}]}]
```

But can I count?

```
list(db.laureates.aggregate([
    {"$match": {"bornCountry": "USA"}},
    {"$count": "n_USA-born-laureates"}
]))
```

```
[{'n_USA-born-laureates': 269}]
```

```
db.laureates.count_documents({"bornCountry": "USA"})
```

```
269
```

What about `db.laureates.distinct("bornCountry")` ?

Let's practice!

INTRODUCTION TO MONGODB IN PYTHON

Back to Counting:

INTRODUCTION TO MONGODB IN PYTHON



Donny Winston
Instructor

Field paths

- *expression object?*

```
{field1: <expression1>, ...}
```

```
db.laureates.aggregate([
    {"$project": {"prizes.share": 1}}
]).next()
```

```
{'_id': ObjectId('5bd3a610053b1704219e19d4'),
  'prizes': [{'share': '1'}]}
```

- expression: 1

```
db.laureates.aggregate([
    {"$project": {"n_prizes": {"$size": "$prizes"}}}
]).next()
```

```
{'_id': ObjectId('5bd3a610053b1704219e19d4'),
  'n_prizes': 1}
```

- expression: {"\$size": "\$prizes"}
- field path: \$prizes

Operator expressions

```
db.laureates.aggregate([
    {"$project": {"n_prizes": {"$size": "$prizes"}}}]
).next()
```

```
{'_id': ObjectId('5bd3a610053b1704219e19d4'), 'n_prizes': 1}
```

- *operator expression*: {"\$size": "\$prizes"}
- *field path*: \$prizes

```
db.laureates.aggregate([
    {"$project": {"n_prizes": {"$size": ["$prizes"]}}}
]).next()
```

```
{'_id': ObjectId('5bd3a610053b1704219e19d4'), 'n_prizes': 1}
```


One more example: a multi-parameter operator

```
db.laureates.aggregate([
    {"$project": {"solo_winner": {"$in": ["1", "$prizes.share"]}}}
]).next()
```

```
{'_id': ObjectId('5bd3a610053b1704219e19d4'), 'solo_winner': True}
```

Implementing .distinct()

```
list_1 = db.laureates.distinct("bornCountry")
```

```
list_2 = [doc["_id"] for doc in db.laureates.aggregate([
    {"$group": {"_id": "$bornCountry"}}
])]
set(list_2) - {None} == set(list_1)
```

```
True
```

- `$group` must map `_id`, which must be unique (like any Mongo document)
- No `$match` before `$group`
 - All distinct "bornCountry" values captured
 - including "no value" (`None`)

How many prizes have been awarded in total?

```
list(db.laureates.aggregate([
    {"$project": {"n_prizes": {"$size": "$prizes"}}},
    {"$group": {"_id": None, "n_prizes_total": {"$sum": "$n_prizes"}}}
]))
```

```
[{'_id': None, 'n_prizes_total': 941}]
```

- {"_id": None} ? one document out.
- \$sum operator acts as *accumulator* in \$group stage

Let's practice!

INTRODUCTION TO MONGODB IN PYTHON

Zoom into Array Fields with \$unwind

INTRODUCTION TO MONGODB IN PYTHON



Donny Winston
Instructor

Sizing and summing

```
list(db.prizes.aggregate([
    {"$project": {"n_laureates": {"$size": "$laureates"},
                  "year": 1, "category": 1, "_id": 0}}
]))
```

```
[{'year': '2018', 'category': 'physics', 'n_laureates': 3},
 {'year': '2018', 'category': 'chemistry', 'n_laureates': 3},
 {'year': '2018', 'category': 'medicine', 'n_laureates': 2},
 ...]
```

```
list(db.prizes.aggregate([
    {"$project": {"n_laureates": {"$size": "$laureates"},
                  "category": 1}},
    {"$group": {"_id": "$category", "n_laureates":
                {"$sum": "$n_laureates"}}},
    {"$sort": {"n_laureates": -1}},
]))
```

```
[{'_id': 'medicine', 'n_laureates': 216},
 {'_id': 'physics', 'n_laureates': 210},
 {'_id': 'chemistry', 'n_laureates': 181},
 {'_id': 'peace', 'n_laureates': 133},
 {'_id': 'literature', 'n_laureates': 114},
 {'_id': 'economics', 'n_laureates': 81}]
```

How to \$unwind

```
list(db.prizes.aggregate([
    {"$unwind": "$laureates"},
    {"$project": {
        "_id": 0, "year": 1, "category": 1,
        "laureates.surname": 1, "laureates.share": 1}},
    {"$limit": 3}
]))
```

```
[{'year': '2018',
  'category': 'physics',
  'laureates': {'surname': 'Ashkin', 'share': '2'}},
{'year': '2018',
  'category': 'physics',
  'laureates': {'surname': 'Mourou', 'share': '4'}},
{'year': '2018',
  'category': 'physics',
  'laureates': {'surname': 'Strickland', 'share': '4'}}]
```

Renormalization, anyone?

```
list(db.prizes.aggregate([
    {"$unwind": "$laureates"},
    {"$project": {"year": 1, "category": 1, "laureates.id": 1}},
    {"$group": {"_id": {"$concat": ["$category", ":", "$year"]},
                "laureate_ids": {"$addToSet": "$laureates.id"}}},
    {"$limit": 5}
]))
```

```
[{'_id': 'medicine:1901', 'laureate_ids': ['293']},
 {'_id': 'peace:1902', 'laureate_ids': ['465', '464']},
 {'_id': 'physics:1902', 'laureate_ids': ['3', '2']},
 {'_id': 'peace:1903', 'laureate_ids': ['466']},
 {'_id': 'medicine:1903', 'laureate_ids': ['295']}
```


\$unwind and count 'em, one by one

```
list(db.prizes.aggregate([
    {"$project": {"n_laureates": {"$size": "$laureates"}, "category": 1}},
    {"$group": {"_id": "$category", "n_laureates": {"$sum": "$n_laureates"}}},
    {"$sort": {"n_laureates": -1}},
]))
```

```
list(db.prizes.aggregate([
    {"$unwind": "$laureates"},
    {"$group": {"_id": "$category", "n_laureates": {"$sum": 1}}},
    {"$sort": {"n_laureates": -1}},
]))
```

```
[{'_id': 'medicine', 'n_laureates': 216},
 {'_id': 'physics', 'n_laureates': 210},
 {'_id': 'chemistry', 'n_laureates': 181},
 {'_id': 'peace', 'n_laureates': 133},
 {'_id': 'literature', 'n_laureates': 114},
 {'_id': 'economics', 'n_laureates': 81}]
```

\$lookup

```
list(db.prizes.aggregate([
    {"$match": {"category": "economics"}},
    {"$unwind": "$laureates"},
    {"$lookup": {"from": "laureates", "foreignField": "id",
                 "localField": "laureates.id", "as": "laureate_bios"}}
```

```
    {"$unwind": "$laureate_bios"},
    {"$group": {"_id": None,
                "bornCountries":
                    {"$addToSet": "$laureate_bios.bornCountry"}
    }},
]))
```

```
[{'_id': None,
  'bornCountries': [
    'the Netherlands', 'British West Indies (now Saint Lucia)', 'Ita
    'Germany (now Poland)', 'Hungary', 'Austria', 'India', 'USA',
    'Canada', 'British Mandate of Palestine (now Israel)', 'Norway',
    'Russian Empire (now Russia)', 'Russia', 'Finland', 'Scotland',
    'France', 'Sweden', 'Germany', 'Russian Empire (now Belarus)',
    'United Kingdom', 'Cyprus'
  ]
}]
```


```
bornCountries = db.laureates.distinct(
    "bornCountry", {"prizes.category": "economics"})
assert set(bornCountries) == set(agg[0]['bornCountries'])
```

**Time to unwind...
with exercises!**

INTRODUCTION TO MONGODB IN PYTHON

Something Extra: \$addFields to Aid Analysis

INTRODUCTION TO MONGODB IN PYTHON



Donny Winston
Instructor

A somber \$project

```
docs = list(db.laureates.aggregate([
    {"$project": {"died": {"$dateFromString": {"dateString": "$died"}},
                  "born": {"$dateFromString": {"dateString": "$born"}}}}
]))
```

```
OperationFailure: Error parsing date string '0000-00-00';
                  11: The parsed date was invalid ''
```

```
docs = list(db.laureates.aggregate([
    {"$match": {"died": {"$gt": "1700"}, "born": {"$gt": "1700"}}},
    {"$project": {"died": {"$dateFromString": {"dateString": "$died"}},
                  "born": {"$dateFromString": {"dateString": "$born"}}}}
]))
```

```
OperationFailure: Error parsing date string '1898-00-00';
                  11: The parsed date was invalid ''
```

split and conditionally correct (with \$concat)

```
docs = list(db.laureates.aggregate([
```

```
    {"$match": {"died": {"$gt": "1700"}, "born": {"$gt": "1700"}}},  
    {"$addFields": {"bornArray": {"$split": ["$born", "-"]},  
                     "diedArray": {"$split": ["$died", "-"]}}},
```

```
    {"$addFields": {"born": {"$cond": [  
        {"$in": ["00", "$bornArray"]},  
        {"$concat": [{"$arrayElemAt": ["$bornArray", 0]}, "-01-01"]},  
        "$born"  
    ]}}},  
    ]}}
```

```
    {"$project": {"died": {"$dateFromString": {"dateString": "$died"}},  
                 "born": {"$dateFromString": {"dateString": "$born"}},  
                 "_id": 0}}
```

```
    ]})
```

A \$bucket list

```
docs = list(db.laureates.aggregate([
    ...,
    {"$project": {"died": {"$dateFromString": {"dateString": "$died"}},
                  "born": {"$dateFromString": {"dateString": "$born"}}}},
```

```
    {"$project": {"years": {"$floor": {"$divide": [
        {"$subtract": ["$died", "$born"]},
        31557600000 # 1000 * 60 * 60 * 24 * 365.25
    ]}}}},
```

```
    {"$bucket": {"groupBy": "$years",
                 "boundaries": list(range(30, 120, 10))}}
]))
```

```
for doc in docs: print(doc)
```

```
{'_id': 30, 'count': 1}
{'_id': 40, 'count': 6}
```

Practice \$addFields

INTRODUCTION TO MONGODB IN PYTHON

Wrap-Up

INTRODUCTION TO MONGODB IN PYTHON



Donny Winston
Instructor

You know know how to...

- Create and compose query filters and use operators
 - Use dot notation
 - Fetch values, arrays, use regex
 - Project, sort, index
 - Aggregate
-
- [MongoDB documentation](#)
 - [PyMongo documentation](#)

Thanks!

INTRODUCTION TO MONGODB IN PYTHON