

Introduction to 8086 Assembly

Lecture 9

Introduction to Subprograms

Indirect addressing



K. N. Toosi
University of Technology

indirect.asm

```
segment .data
l1:  dd 111
segment .text
:
mov eax, l1
call print_int
call print_nl

mov eax, [l1]
call print_int
call print_nl
```

Indirect addressing



indirect.asm

```
segment .data
l1:  dd 111
segment .text
:
mov eax, l1
call print_int
call print_nl

mov eax, [l1]
call print_int
call print_nl

mov ecx, l1
mov eax, [ecx]
call print_int
call print_nl
```

Indirect addressing



indirect.asm

```
segment .data
l1:  dd 111
segment .text
:
mov eax, l1
call print_int
call print_nl

mov eax, [l1]
call print_int
call print_nl

mov ecx, l1
mov eax, [ecx]
call print_int
call print_nl
```

Indirect addressing



```
segment .data
```

```
indirect2.asm
```

```
l1:  dd 111  
     dd 222  
     dd 444
```

```
segment .text
```

```
:
```

```
mov ecx, l1
```

```
mov eax, [ecx]  
call print_int  
call print_nl
```

```
indirect2.asm (cont.)
```

```
mov eax, [ecx+1]  
call print_int  
call print_nl
```

```
mov eax, [ecx+4]  
call print_int  
call print_nl
```

```
mov eax, [ecx+8]  
call print_int  
call print_nl
```

Indirect addressing



K. N. Toosi
University of Technology

segment .data

indirect2.asm

```
l1: dd 111  
    dd 222  
    dd 444
```

segment .text

:

```
mov ecx, l1
```

```
mov eax, [ecx]  
call print_int  
call print_nl
```

indirect2.asm (cont.)

```
mov eax, [ecx+1]  
call print_int  
call print_nl
```

```
mov eax, [ecx+4]  
call print_int  
call print_nl
```

```
mov eax, [ecx+8]  
call print_int  
call print_nl
```

How does the assembler do this?

Indirect addressing



K. N. Toosi
University of Technology

```
mov eax, [ecx]
```

```
mov ax, [ecx]
```

```
mov al, [ecx]
```



How to implement subprograms?

- Subprogram
- function
- subroutine
- procedure
- routine
- method
- callable

```
void print_salam(void);

int main() {

    print_salam();

}

void print_salam() {
    printf("Salaaaaam!\n");
}
```


How to implement subprograms?



K. N. Toosi
University of Technology

```
void print_salam(void);
```

```
int main() {
```

```
    print_salam();
```

```
}
```

```
void print_salam() {  
    printf("Salaaaaam!\n");
```

```
}
```

```
segment .data
```

```
msg:    db "Salaaaaam!", 10, 0
```

```
segment .text
```

```
    :
```

```
    :
```

```
print_salam:
```

```
    mov eax, msg
```

```
    call print_string
```

How to implement subprograms?



K. N. Toosi
University of Technology

```
void print_salam(void);
```

```
int main() {
```

```
    print_salam();
```

```
}
```

```
void print_salam() {  
    printf("Salaaaaam!\n");
```

```
}
```

```
segment .data
```

```
msg:  db "Salaaaaam!", 10, 0
```

```
segment .text
```

```
    :
```

```
    jmp print_salam
```

```
    :
```

```
print_salam:
```

```
    mov eax, msg
```

```
    call print_string
```

How to implement subprograms?



K. N. Toosi
University of Technology

```
void print_salam(void);
```

```
int main() {
```

```
    print_salam();
```

```
}
```

```
void print_salam() {
```

```
    printf("Salaaaaam!\n");
```

```
}
```

```
segment .data
```

```
msg:  db "Salaaaaam!", 10, 0
```

```
segment .text
```

```
    :
```

```
    jmp print_salam
```

```
l1:
```

```
    :
```

```
print_salam:
```

```
    mov eax, msg
```

```
    call print_string
```

How to implement subprograms?



K. N. Toosi
University of Technology

```
void print_salam(void);
```

```
int main() {
```

```
    print_salam();
```

```
}
```

```
void print_salam() {
```

```
    printf("Salaaaaam!\n");
```

```
}
```

```
segment .data
```

```
msg:  db "Salaaaaam!", 10, 0
```

```
segment .text
```

```
    :
```

```
    jmp print_salam
```

```
l1:  _____→ return address
```

```
    :
```

```
print_salam:
```

```
    mov eax, msg
```

```
    call print_string
```

How to implement subprograms?



K. N. Toosi
University of Technology

```
void print_salam(void);
```

```
int main() {
```

```
    print_salam();
```

```
}
```

```
void print_salam() {  
    printf("Salaaaaam!\n");  
}
```

```
segment .data
```

```
msg:  db "Salaaaaam!", 10, 0
```

```
segment .text
```

```
    :
```

```
    jmp print_salam
```

```
l1:  _____→ return address  
    :
```

```
print_salam:
```

```
    mov eax, msg
```

```
    call print_string
```

```
    jmp l1
```

simplefunc1.asm

How to implement subprograms?



K. N. Toosi
University of Technology

```
void print_salam(void);
```

```
int main() {
```

```
    print_salam();
```

```
}
```

```
void print_salam() {  
    printf("Salaaaaam!\n");  
}
```

What's wrong?

```
segment .data
```

```
msg:  db "Salaaaaam!", 10, 0
```

```
segment .text
```

```
    :
```

```
    jmp print_salam
```

```
l1:  _____→ return address  
    :
```

```
print_salam:
```

```
    mov eax, msg
```

```
    call print_string
```

```
    jmp l1
```

How to implement subprograms?



```
void print_salam(void);
```

```
int main() {
```

```
    print_salam();
```

```
}
```

```
void print_salam() {  
    printf("Salaaaaam!\n");  
}
```

```
segment .data
```

```
msg:  db "Salaaaaam!", 10, 0
```

```
segment .text
```

```
    :
```

```
    jmp print_salam
```

```
l1:  _____→ return address
```

```
    :
```

```
    jmp print_salam
```

```
l2:  _____→
```

```
    :
```

```
print_salam:
```

```
    mov eax, msg
```

```
    call print_string
```

```
    jmp ?
```

Looking closer at the jmp command



K. N. Toosi
University of Technology

```
mov eax, 1  
add eax, eax  
jmp label1  
  
xor eax, eax  
  
label1:  
  
sub eax, 303
```


memory	
1001	mov eax, 1
1006	add eax, eax
1008	jmp 1012
1010	xor eax, eax
1012	sub eax, 303

Remember: Jump and The Instruction Pointer



K. N. Toosi
University of Technology

The **Instruction Pointer**
(program counter) IP, EIP, RIP





Remember: Jump and The Instruction Pointer



K. N. Toosi
University of Technology

Executing: `mov eax, 1`





Remember: Jump and The Instruction Pointer



K. N. Toosi
University of Technology

Executing: `add eax, eax`





Remember: Jump and The Instruction Pointer



K. N. Toosi
University of Technology

Executing: `jmp 1012`




Remember: Jump and The Instruction Pointer



K. N. Toosi
University of Technology

Executing: `jmp 1012`



label1 = 1012

memory


1001	<code>mov eax, 1</code>
1006	<code>add eax, eax</code>
1008	<code>jmp 1012</code>
1010	<code>xor eax, eax</code>
	<code>sub eax, 303</code>

Remember: Jump and The Instruction Pointer



K. N. Toosi
University of Technology

Executing: `jmp 1012`




Remember: Jump and The Instruction Pointer



K. N. Toosi
University of Technology

`jmp label1`

How are `mov` and `jmp` similar?




Remember: Jump and The Instruction Pointer



K. N. Toosi
University of Technology

```
jmp label1  
(mov EIP, label1)
```





label1 = 1012

Remember: Jump and The Instruction Pointer



K. N. Toosi
University of Technology

```
jmp label1  
(mov EIP, label1)
```




Remember: Jump and The Instruction Pointer



K. N. Toosi
University of Technology

```
jmp label1  
(mov EIP, label1)
```




label1 = 1012

Remember: Jump and The Instruction Pointer



K. N. Toosi
University of Technology

```
mov EAX, label1  
(mov EIP, EAX)
```




label1 = 1012

Remember: Jump and The Instruction Pointer



K. N. Toosi
University of Technology

```
mov EAX, label1  
jmp EAX      (mov EIP, EAX)
```




label1 = 1012

Remember: Jump and The Instruction Pointer



K. N. Toosi
University of Technology

```
(mov EIP, [11])  
jmp [11]
```




label1 = 1012

Remember: Jump and The Instruction Pointer



K. N. Toosi
University of Technology

```
mov EAX, label1  
jmp EAX      (mov EIP, EAX)
```



label1 = 1012

Indirect jump



K. N. Toosi
University of Technology

Direct Jump: `jmp l1`

Indirect Jump: `mov eax, l1`
 `jmp eax`

How to implement subprograms?



```
void print_salam(void);
```

```
int main() {
```

```
    print_salam();
```

```
}
```

```
void print_salam() {  
    printf("Salaaaaam!\n");  
}
```

```
segment .data
```

```
msg:  db "Salaaaaam!", 10, 0
```

```
segment .text
```

```
    :
```

```
        jmp print_salam
```

I1:  **return address**

```
        jmp print_salam
```

I2: 

```
    :
```

```
print_salam:
```

```
    mov eax, msg
```

```
    call print_string
```

```
    jmp ?
```

simplefunc3.asm

How to implement subprograms?



```
void print_salam(void);
```

```
int main() {
```

```
    print_salam();
```

```
}
```

```
void print_salam() {  
    printf("Salaaaaam!\n");  
}
```

```
segment .data
```

```
msg:  db "Salaaaaam!", 10, 0
```

```
segment .text
```

```
    :
```

```
        jmp print_salam
```

I1:  **return address**

```
        jmp print_salam
```

I2: 

```
    :
```

```
print_salam:
```

```
    mov eax, msg
```

```
    call print_string
```

```
    jmp edx
```

How to implement subprograms?



```
void print_salam(void);
```

```
int main() {
```

```
    print_salam();
```

```
}
```

```
void print_salam() {  
    printf("Salaaaaam!\n");  
}
```

```
segment .data
```

```
msg:  db "Salaaaaam!", 10, 0
```

```
segment .text
```

```
    :
```

```
    mov edx, l1
```

```
    jmp print_salam
```

```
l1:
```

```
    mov edx, l2
```

```
    jmp print_salam
```

```
l2:
```

```
    :
```

```
print_salam:
```

```
    mov eax, msg
```

```
    call print_string
```

```
    jmp edx
```

simplefunc3.asm

return address

How to implement subprograms?



K. N. Toosi
University of Technology

```
void print_salam(void);
```

```
int main() {
```

```
    print_salam();
```

```
}
```

```
void print_salam() {  
    printf("Salaaaaam!\n");
```

```
}
```

Limitations?

```
segment .data
```

```
msg:  db "Salaaaaam!", 10, 0
```

```
segment .text
```

```
    :
```

```
    mov edx, l1
```

```
    jmp print_salam
```

l1: → return address

```
    mov edx, l2
```

```
    jmp print_salam
```

l2: →

```
    :
```

```
print_salam:
```

```
    mov eax, msg
```

```
    call print_string
```

```
    jmp edx
```

The stack




K. N. Toosi
University of Technology



<http://freepngimg.com/png/25783-coin-stack-transparent-image>



<https://pixabay.com/en/plate-stack-tableware-plate-stack-629970/>



<http://carbon.materialwitness.co/book-stack/>

The stack




K. N. Toosi
University of Technology

Memory



Memory



Implementing the stack




K. N. Toosi
University of Technology

Stack Segment



Stack Segment



Implementing the stack




K. N. Toosi
University of Technology

Stack Segment



Stack Segment



x86

Implementing the stack




K. N. Toosi
University of Technology

Stack Segment



Stack Segment



x86
(why?)

Implementing the stack



K. N. Toosi
University of Technology


stack segment

2088

2092

2096


2100



Stack Pointer (SP, ESP, RSP)




K. N. Toosi
University of Technology



Pushing on the stack




K. N. Toosi
University of Technology



Push EAX on the stack




K. N. Toosi
University of Technology



Push EAX on the stack




K. N. Toosi
University of Technology



Push EAX on the stack




K. N. Toosi
University of Technology



Push EAX on the stack




K. N. Toosi
University of Technology



Push EAX on the stack




K. N. Toosi
University of Technology



Push EAX on the stack




K. N. Toosi
University of Technology



Pop into EBX



K. N. Toosi
University of Technology



Pop into EBX



K. N. Toosi
University of Technology

```
mov ebx, [esp]
```

CPU

ESP

2084

EAX

44200

EBX

44200

stack segment


44200

2088

2092

2096

2100



Pop into EBX



K. N. Toosi
University of Technology

```
mov ebx, [esp]  
add esp, 4
```

CPU

ESP

2088

EAX

44200

EBX

44200

stack segment


44200

2088

2092

2096

2100



Pop into EBX



K. N. Toosi
University of Technology

CPU

ESP

2088

EAX

44200

EBX

44200

```
mov ebx, [esp]
add esp, 4
```



```
pop ebx
```

stack segment

44200

2088

2092

2096

2100



just pop 4 bytes (store nowhere)



K. N. Toosi
University of Technology

CPU

ESP

2088

EAX

44200

EBX

stack segment


2088

2092

2096

2100

pop ebx



just pop 4 bytes (store nowhere)



K. N. Toosi
University of Technology

CPU

ESP

2088

EAX

44200

EBX

stack segment

2088

2092

2096

2100

pop ebx

OR?

add esp, 4

just pop 4 bytes (store nowhere)



K. N. Toosi
University of Technology

CPU

ESP

2088

EAX

44200

EBX

stack segment

2088

2092

2096

2100

pop ebx

OR?

add esp, 4

add esp, 20

reserve memory on stack



K. N. Toosi
University of Technology

CPU

ESP

2088

EAX

44200

EBX

stack segment


2088

2092

2096

2100

push edx



reserve memory on stack



K. N. Toosi
University of Technology

CPU

ESP

2088

EAX

44200

EBX

stack segment

2088

2092


2096

2100

push edx

OR?


sub esp, 4



reserve memory on stack



K. N. Toosi
University of Technology



Push and Pop



K. N. Toosi
University of Technology

Push reg/mem/immed

Pop reg/mem

Practice



K. N. Toosi
University of Technology

```
push eax
```

```
push ebx
```

```
pop  eax
```

```
pop  ebx
```

pusha and popa



K. N. Toosi
University of Technology

- 8086:
 - pusha: Push AX, CX, DX, BX, SP, BP, SI, DI
 - popa: Pop DI, SI, BP, BX, DX, CX, AX.
- 80386: netwide assembler (what we use)
 - pusha, pushad: Push EAX, ECX, EDX, EBX, ESP, EBP, ESI, EDI
 - popa, popad: Pop EDI, ESI, EBP, EBX, EDX, ECX, EAX.
- 80386: some other assemblers
 - pusha: Push AX, CX, DX, BX, SP, BP, SI, DI
 - pushad: Push EAX, ECX, EDX, EBX, ESP, EBP, ESI, EDI
 - popa: Pop DI, SI, BP, BX, DX, CX, AX.
 - popad: Pop EDI, ESI, EBP, EBX, EDX, ECX, EAX
- 64 bit
 - no pusha/popa in 64-bit mode

pushf and popf



K. N. Toosi
University of Technology

- push and pop FLAGS/EFLAGS register
- some assemblers use (pushf/pushfd/pushfq, etc.)

Back to subroutines



K. N. Toosi
University of Technology

```
segment .data
```

```
simplefunc3.asm
```

```
msg:  db "Salaaaaam!", 10, 0
```

```
segment .text
```

```
⋮
```

```
mov edx, I1
```

```
jmp print_salam
```

```
I1:
```

```
mov edx, I2
```

```
jmp print_salam
```

```
I2:
```

```
⋮
```

```
print_salam:
```

```
mov eax, msg
```

```
call print_string
```

```
jmp edx
```


Back to subroutines



K. N. Toosi
University of Technology

segment .data simplefunc3.asm

msg: db "Salaaaaam!", 10, 0

segment .text

⋮

mov **edx**, l1

jmp print_salam

l1:

mov **edx**, l2

jmp print_salam

l2:

⋮

print_salam:

mov **eax**, msg

call print_string

jmp **edx**

segment .data simplefunc4.asm

msg: db "Salaaaaam!", 10, 0

segment .text

⋮

push l1

jmp print_salam

l1:

push l2

jmp print_salam

l2:

⋮

print_salam:

mov **eax**, msg

call print_string

??

Back to subroutines



K. N. Toosi
University of Technology

segment .data simplefunc3.asm

msg: db "Salaaaaam!", 10, 0

segment .text

⋮

mov edx, I1

jmp print_salam

I1:

mov edx, I2

jmp print_salam

I2:

⋮

print_salam:

mov eax, msg

call print_string

jmp edx

segment .data simplefunc4.asm

msg: db "Salaaaaam!", 10, 0

segment .text

⋮

push I1

jmp print_salam

I1:

push I2

jmp print_salam

I2:

⋮

print_salam:

mov eax, msg

call print_string

pop edx

jmp edx

the CALL instruction



segment .data simplefunc3.asm

msg: db "Salaaaaam!", 10, 0

segment .text

⋮

mov edx, I1

jmp print_salam

I1:

mov edx, I2

jmp print_salam

I2:

⋮

print_salam:

mov eax, msg

call print_string

jmp edx

segment .data simplefunc4.asm

msg: db "Salaaaaam!", 10, 0

segment .text

⋮

push I1

jmp print_salam

I1:

push I2

jmp print_salam

I2:

⋮

print_salam:

mov eax, msg

call print_string

pop edx

jmp edx

segment .data simplefunc5.asm

msg: db "Salaaaaam!", 10, 0

segment .text

⋮

call print_salam

I1:

call print_salam

I2:

⋮

print_salam:

mov eax, msg

call print_string

pop edx

jmp edx

the CALL instruction



segment .data simplefunc3.asm

msg: db "Salaaaaam!", 10, 0

segment .text

⋮

mov edx, I1

jmp print_salam

I1:

mov edx, I2

jmp print_salam

I2:

⋮

print_salam:

mov eax, msg

call print_string

jmp edx

segment .data simplefunc4.asm

msg: db "Salaaaaam!", 10, 0

segment .text

⋮

push I1

jmp print_salam

I1:

push I2

jmp print_salam

I2:

⋮

print_salam:

mov eax, msg

call print_string

pop edx

jmp edx

segment .data simplefunc5.asm

msg: db "Salaaaaam!", 10, 0

segment .text

⋮

call print_salam

call print_salam

⋮

print_salam:

mov eax, msg

call print_string

pop edx

jmp edx

the *CALL* instruction

CALL is merely a form of jump!



K. N. Toosi
University of Technology

the CALL instruction



K. N. Toosi
University of Technology

CALL is merely a form of jump!

```
call label1
```

- Push return address (EIP) on stack
- jump to label1



`call print_salam`

CPU

EIP 1008

ESP 2088

`print_salam = 1024`

1008

2088

2092

`call print_salam`

`popa`

`:`

`mov eax, msg`

`segment .data`

`msg: db "Salaaaaam!", 10, 0`

`segment .text`

`:`

`→ call print_salam`

`popa`

`:`

`print_salam:`

`mov eax, msg`

`call print_string`

`pop edx`

`jmp edx`



`call print_salam`

CPU

EIP 1008

ESP 2084

`print_salam = 1024`

1008

`call print_salam`

`popa`

`:`

`mov eax, msg`

1008

2088

2092

`segment .data`

`msg: db "Salaaaaam!", 10, 0`

`segment .text`

`:`

`→ call print_salam`

`popa`

`:`

`print_salam:`

`mov eax, msg`

`call print_string`

`pop edx`

`jmp edx`



`call print_salam`

1008

`call print_salam`

`popa`

`:`

`mov eax, msg`

`print_salam = 1024`

CPU

EIP

1024

ESP

2084

1008

2088

2092

`segment .data`

`msg: db "Salaaaaam!", 10, 0`

`segment .text`

`:`

`→ call print_salam`

`popa`

`:`

`print_salam:`

`mov eax, msg`

`call print_string`

`pop edx`

`jmp edx`

returning from a subroutine



K. N. Toosi
University of Technology

```
segment .data      simplefunc5.asm
msg:  db "Salaaaaam!", 10, 0
segment .text
:

    call print_salam

    call print_salam

:
print_salam:
    mov eax, msg
    call print_string
    pop edx
    jmp edx
```

the RET instruction



K. N. Toosi
University of Technology

```
segment .data simplefunc5.asm
msg: db "Salaaaaam!", 10, 0
segment .text
:

call print_salam

call print_salam

:
print_salam:
    mov eax, msg
    call print_string
    pop edx
    jmp edx
```

```
segment .data simplefunc6.asm
msg: db "Salaaaaam!", 10, 0
segment .text
:

call print_salam

call print_salam

:
print_salam:
    mov eax, msg
    call print_string
    ret
```

the RET instruction



K. N. Toosi
University of Technology

```
segment .data      simplefunc5.asm
msg:  db "Salaaaaam!", 10, 0
segment .text
:

call print_salam

call print_salam

:
print_salam:
    mov eax, msg
    call print_string
    pop edx
    jmp edx
```

```
segment .data      simplefunc6.asm
msg:  db "Salaaaaam!", 10, 0
segment .text
:

call print_salam

call print_salam

:
print_salam:
    mov eax, msg
    call print_string
    ret

ret (pop EIP)
```

the RET instruction



K. N. Toosi
University of Technology

```
segment .data      simplefunc5.asm
msg:  db "Salaaaaam!", 10, 0
segment .text
:

call print_salam

call print_salam

:
print_salam:
    mov eax, msg
    call print_string
    pop edx
    jmp edx
```

```
segment .data      simplefunc6.asm
msg:  db "Salaaaaam!", 10, 0
segment .text
:

call print_salam

call print_salam

:
print_salam:
    mov eax, msg
    call print_string
    ret
```

the RET instruction

RET is merely a form of jump!



K. N. Toosi
University of Technology

the RET instruction



K. N. Toosi
University of Technology

RET is merely a form of jump!

`ret`

- jump to the address stored on top of stack
- pop stack



ret

1008

call print_salam

popa

:

ret

print_salam = 1024

CPU

EIP

1032

ESP

2084

2088

2092

1008

segment .data

msg: db "Salaaaaam!", 10, 0

segment .text

:

call print_salam

popa

:

print_salam:

mov eax, msg

call print_string

ret



ret

CPU

EIP 1008

ESP 2088

print_salam = 1024

1008

call print_salam

popa

:

ret

1008

2088

2092

segment .data

msg: db "Salaaaaam!", 10, 0

segment .text

:

call print_salam

popa

:

print_salam:

mov eax, msg

call print_string

ret

What else?

- parameters (arguments)
- local variables
- return values



K. N. Toosi
University of Technology