

# Using L<sup>A</sup>T<sub>E</sub>X for High Quality Project Report Generation

A PROJECT REPORT

*Submitted in partial fulfilment for the award of the degree of*

MS

in

Software Engineering

By

Santhos Baala RS, 09MSE038

Under the Guidance of

Dr. Krishna Chandramouli

Associate Professor

SCHOOL OF INFORMATION TECHNOLOGY AND ENGINEERING

VIT UNIVERSITY



**VIT**  
UNIVERSITY  
(Estd. u/s 3 of UGC Act 1956)  
Vellore - 632 014, Tamil Nadu, India

## **DECLARATION BY THE CANDIDATE**

I here by declare that the project report titled, **“Using L<sup>A</sup>T<sub>E</sub>X for High Quality Project Report Generation”** submitted by me to VIT University, Vellore in partial fulfilment of the requirement for the award of the degree of **M.S. (Software Engineering)** is a record of bonafide project work carried out by me under the guidance of **Dr. Krishna Chandramouli (Associate Professor)**. I further declare that the work reported in this project has not been submitted and will not be submitted, either in part or in full, for the award of any other degree or diploma in this institute or any other institute or university.

Place: Vellore

Signature of the Candidate

Date:

Santhos Baala RS (09MSE038)



**VIT**  
**UNIVERSITY**  
(Estd. u/s 3 of UGC Act 1956)  
Vellore - 632 014, Tamil Nadu, India

**SCHOOL OF INFORMATION TECHNOLOGY AND ENGINEERING [SITE]**  
**SOFTWARE ENGINEERING DIVISION**  
**BONAFIDE CERTIFICATE**

This is to certify that the project report titled, “**Using L<sup>A</sup>T<sub>E</sub>X for High Quality Project Report Generation**”, submitted by **Santhos Baala RS (09MSE038)** to VIT University, Vellore in partial fulfillment of the requirement for the award of the degree of M.S. (Software Engineering) is a record of bonafide work carried out by him/her under my guidance. The project fulfills the requirements as per the regulations of this institute and in my opinion meets the necessary standards for submission. The contents of this report have not been submitted and will not be submitted either in part or in full, for the award of any other degree or diploma in this institute or any other institute or university.

**Dr. Krishna Chandramouli**

**Internal Guide**

Associate Professor,

School Of Information Technology & Engineering

---

**Internal Examiner**

**External Examiner**

## Acknowledgements

I take immense pleasure in thanking **Dr. G. Viswanathan**, my beloved chancellor, VIT University, **Dr. Sankaran**, dean, School Of Information Technology and Engineering, **Prof. Jayaram Reddy A**, Program Manager, M.S. Software Engineering and **Dr. Krishna Chandramouli**, project coordinator, M.S. Software Engineering for having permitted me to carry out the project.

I express gratitude to my guide, **Dr. Krishna Chandramouli**, for guidance and suggestions that helped me to complete the project on time. Words are inadequate to express my gratitude to the faculty and staff members who encouraged and supported me during the project. Finally, I would like to thank my ever-loving parents for their blessings and my friends for their timely help and support.

## **Executive Summary**

This document describes how to use the `vitmsprojectreport` class with  $\text{\LaTeX}$  to produce high quality typeset project report that is suitable for submission to the School of Information Technology and Engineering (SITE). The class can further be extended to various courses and department by modifying the title page and department information.

## Table of Contents

<b>1</b>	<b>Introduction</b>	<b>1</b>
1.1	About the Template . . . . .	1
1.2	Generic L <sup>A</sup> T <sub>E</sub> X Commands . . . . .	1
1.3	Generating the Final Document . . . . .	2
1.4	Asking Questions . . . . .	2
1.5	Contributing . . . . .	2
<b>2</b>	<b>Auto-Generated Pages</b>	<b>3</b>
2.1	The Title Page . . . . .	3
2.1.1	Project Title . . . . .	3
2.1.2	Regno . . . . .	4
2.1.3	Guide Name . . . . .	4
2.1.4	Guide Title . . . . .	4
2.2	Declartion Page . . . . .	4
2.3	Bonafide Page . . . . .	4
2.4	Acknowledgement Page . . . . .	4
2.5	Executive Summary Page . . . . .	5
2.6	Single Command to Generate All the Starting Pages . . . . .	5
<b>3</b>	<b>Text Elements</b>	<b>6</b>
3.1	Chapters, Sections and Sub-Sections . . . . .	6
3.2	Lists . . . . .	6
3.2.1	Unordered . . . . .	7
3.2.2	Ordered . . . . .	7
3.2.3	Description List . . . . .	7
3.3	Footnotes . . . . .	8
3.4	Cross-References . . . . .	8
3.5	External References . . . . .	9
<b>4</b>	<b>Figures and Algorithms</b>	<b>10</b>
4.1	Figures . . . . .	10
4.1.1	Sub-Figures . . . . .	10
4.2	Algorithms . . . . .	10

<b>5</b>	<b>Tables</b>	<b>16</b>
5.1	A Simple Table . . . . .	16
5.2	A Somewhat Big Table . . . . .	16
5.3	A Ver Big Table . . . . .	17
5.4	Rotated Table . . . . .	17
<b>6</b>	<b>Equations</b>	<b>19</b>
6.1	Inline . . . . .	19
6.2	More examples . . . . .	19
6.2.1	Greek Characters . . . . .	19
6.2.2	Operator . . . . .	19
6.3	Subscript/Superscript . . . . .	19
6.4	Fractions and Binomials . . . . .	19
6.5	Equation Environment . . . . .	20
6.6	Fractions . . . . .	20
6.6.1	Inline . . . . .	20
6.6.2	Continued Fractions . . . . .	20
6.6.3	Multiplication of two numbers . . . . .	20
6.7	Fermat numbers . . . . .	20
6.8	Roots . . . . .	21
6.9	Mathematical Symbols . . . . .	21
6.10	Sample Vectors . . . . .	21
6.11	More Mathematics . . . . .	21
6.11.1	Multiline Equations . . . . .	22
6.11.2	Cases . . . . .	23
6.11.3	Matrices . . . . .	23
6.11.4	Symbols with alignment . . . . .	24
6.11.5	Summations . . . . .	24
6.11.6	Limits and Integrals . . . . .	24
<b>7</b>	<b>References</b>	<b>25</b>

## **List of Figures**

2.1	The syntax of <code>\maketitlepage</code> command . . . . .	3
2.2	The syntax of <code>\makeackpage</code> command. . . . .	5
2.3	Example usage of the <code>\makeexecsummarypage</code> command. . . . .	5
2.4	Single command to render all the starting pages. . . . .	5
3.1	Commands to create text structures. . . . .	6
3.2	Unordered list example. . . . .	7
3.3	Ordered list example. . . . .	7
3.4	Description list example. . . . .	8
3.5	An example footnote. . . . .	8
4.1	Using 50% of the textbox to place the image. . . . .	10
4.2	The big cat . . . . .	11
4.3	Subfigure example. . . . .	12
4.4	The steps of mitosis. . . . .	13
4.5	Euclid's algorithm, written in algorithmic. . . . .	14
4.6	Euclid's Algorithm . . . . .	14
4.7	Listing to generate an enumerated list of steps. . . . .	14
4.8	Steps to perform Brownian motion. . . . .	15



## **List of Tables**

5.1	Number of images in 18 concepts according to ground truth. . . . .	16
5.2	Concept detection accuracy . . . . .	16
5.3	Retrieval Precision for each Concept from Corel Database . . . . .	17
5.4	Concept detection accuracy with 15 concepts. . . . .	18

# 1. Introduction

## 1.1 About the Template

With a basic understanding of the  $\text{\LaTeX}$  language and say 10 to 20 commands, an author can produce beautiful typeset project report quickly, with minimal effort. The purpose of this document is to serve as a user guide for the project report template and document its special behaviours. Examples have also been provided for common tasks such as insertion of images, table, equation, etc., that can be copied as is by the users. It is assumed that the user has a basic knowledge on working of the  $\text{\LaTeX}$  system. Those lacking are strongly urged to lookup some excellent literature through [2].

Sufficient examples have been given in the document and as users request solutions for specific problems that they encounter, more will be added. However, an understanding of the  $\text{\LaTeX}$  system will help the user in unexplainable ways<sup>1</sup>. The main advantage of using the custom class is that, the user need not worry about the final layout. The class may be changed during the development of the project report, the user needs to just place the latest version of the class file, without touching the content<sup>2</sup>.  $\text{\LaTeX}$ , along with the custom class file gives an incredible expressive power its users so that they can focus on the semantics of the document.

## 1.2 Generic $\text{\LaTeX}$ Commands

$\text{\LaTeX}$  contains many commands and with it comes numerous built-in packages that add many features and provide options to customise the output. However, the user is advised to stick to the basic commands, illustrated in this document so that unexpected or incorrect output can be avoided. If, however a specific feature is requested it shall be considered and incorporated into the template. The class file for project report has been extended from the standard *report* class, supplied by  $\text{\LaTeX}$ . Therefore, whatever applied for report also applies for the custom class file.

---

<sup>1</sup>The  $\text{\LaTeX}$  system is a vast ocean. That said, you can mostly get away with copy-paste skills. You have to observe the source code of the examples and learn

<sup>2</sup>It is always recommended to get the latest class file from the repository and compile before project report submission.

### **1.3 Generating the Final Document**

The template development is an ongoing process. It is mature at this point from the point of view of semantics. Layout or default contents (e.g bonafide, acknowledgement, etc.,) may change at a later point in time. Therefore, before generating the final document, please make sure to check out a frozen version of the class file from the repository before compiling the class file.

### **1.4 Asking Questions**

You can post your questions in the forum or if you encounter any problem related to unexpected/incorrect output due to the template send an e-mail to the contributors at the [github](#) page.

### **1.5 Contributing**

The project is hosted on GitHub [3] and uses the GIT repository management system. Contributors can fork the project and send pull requests to the repository for the changes to be merged. The patch will be evaluated and if found to be good, merged into the master branch of the repository. If however, a separate template is required for other departments and courses, the project can be forked and maintained separately. Issues, pertaining to the template, such as rendering faults, can be posted in the issues section of the repo. The contributors shall also put up a list of items that need improvement or new features in progress that people can contribute to.

## 2. Auto-Generated Pages

The parts of the document, unique to the project report are generated by a predefined template, using simple commands. The order in which the commands are issued determine the corresponding order of these individual pages. The arguments that need to be passed to these commands are explained in the following sections. The sequence of commands to generate such pages have already been placed in the example document and it is recommended not to touch those, expect when inserting your project specific information.

### 2.1 The Title Page

The user can generate the title page using the `\maketitlepage` command. The detailed syntax is given in Figure 2.1.

---

```
\maketitlepage
{Project Title}
{Name}
{RegNo}
{Guide Name}
{Guide Title}
```

---

Figure 2.1: The syntax of `\maketitlepage` command

Note that you should always set the title page to be the first page of the document, so issue this command right after the document begins. The template also collects information like your name and regno when you declare the title page so that it can be auto-inserted into other pages like declaration and bonafide. The following subsections d

#### 2.1.1 Project Title

Your project title should be placed here. If your title is long and you are not satisfied with the way the lines break, use `\\` to insert line breaks at suitable locations. Note the inclusion of blank space after the backslashes.

E.g. `{A very very\\ long long title}`.

### 2.1.2 Regno

Supply your register number here. A long name will automatically push the register number to the next line. However, to be safe, prepend your RegNo with `\`.

E.g. `{\\09MSE038}`.

### 2.1.3 Guide Name

Your guide's name goes here. Make sure to add your guide's title too, Prof., Dr., etc. Also, be sure to add a non-breaking space “~” after the title so that unintended line breaks are prevented. Follow the regular convention of first name, last name.

E.g. `{Prof.~Robert}` or `{Dr.~John}`.

### 2.1.4 Guide Title

Your Guide's title(designation) goes here. Do not abbreviate anything.

E.g `{Assistant Professor (Senior)}`.

## 2.2 Declartion Page

Use `\makedeclarationpage` command, rest is automatically generated!

## 2.3 Bonafide Page

Use `\makebonafidepage` command, rest is automatically generated!

## 2.4 Acknowledgement Page

Use `\makeackpage` command to generate the page. The generated text is more than sufficient for acknowledgement. However, if there is a request for custom writeup for the acknowledgement page, we'll consider that<sup>1</sup>. There are three arguments to this page as given in Figure 2.2. Make sure to prepend the names with appropriate titles, Mr, Dr, etc., and remember to give a non-breaking space character just after the title as you did for your guide's name in 2.1.3

---

<sup>1</sup>We don't want to kill creativity!

---

```
\makeackpage  
{Dean Name}  
{Program Manager Name}  
{Year Co-Ordinator Name}
```

---

Figure 2.2: The syntax of `\makeackpage` command.

## 2.5 Executive Summary Page

The command `\makeexecsummarypage` creates the executive summary page. The only argument to this function is your executive summary. Keep it down to 1-2 paragraphs. An example is given in Figure 2.3.

---

```
\makeexecsummarypage{  
This document describes how to use the vitmsprojectreport  
class with \LaTeX\ to produce high quality typeset project  
report that is suitable for submission to the School of  
Information Technology and Engineering (SITE). The class  
can further be extended to various courses and department  
by modifying the title page and department information.  
}
```

---

Figure 2.3: Example usage of the `\makeexecsummarypage` command.

## 2.6 Single Command to Generate All the Starting Pages

The shortcut `\makestartingpages`, renders all the starting pages. The format of the parameters that applied to individual commands mentioned previously apply here to.

---

```
\makestartingpages  
{Project Title}  
{Name}{Regno}  
{Guide Name}{Guide Title}  
{Dean Name}  
{Program Manager Name}  
{Year Co-Ordinator Name}  
{Executive Summary Contents}
```

---

Figure 2.4: Single command to render all the starting pages.

### 3. Text Elements

The chapters, sections and subsections in the document are created with the standard commands `\chapter`, `\section` and `\subsection` respectively. The text sections are automatically numbered using arabic numerals and also added to the table of contents. You can create a deeper level using `\subsubsection`. It is recommended to keep the depth restricted to the subsection level. The template doesn't guarantee proper output for beyond that. The following sections illustrate on creating various text structures in the document and cross-references.

#### 3.1 Chapters, Sections and Sub-Sections

Chapters are created with the `\chapter` command. The chapter title is passed as an argument. Each chapter is automatically placed in a separate page. Sections and Sub-Sections under a chapter are created with the `\section` and `\subsection` respectively. The syntax of all the commands are given in Figure 3.1.

---

```
\chapter{The Chapter Title}
\section{The Section Title}
\subsection{The Sub-Section Title}
```

---

Figure 3.1: Commands to create text structures.

If you want to place a section inside a chapter, place it under that chapter. Similarly, a sub-section meant to be placed inside a section is placed under the corresponding section. That's how levels are created. The sequence of commands in Figure 3.1 will create a sub-section, under a section, which in turn is under a chapter.

#### 3.2 Lists

List is inherited directly from vanilla  $\text{\LaTeX}$  list. You can look them up from any tutorial for  $\text{\LaTeX}$  lists, preferably from [2]. We give a short example of an unordered list and an ordered list over here. Changing the list style, bullet shape, etc., is your choice. *Note that an empty list(list with no items) will throw an error during compilation.* More information on the list structure is available at [http://en.wikibooks.org/wiki/LaTeX/List\\_Structures#Enumerate](http://en.wikibooks.org/wiki/LaTeX/List_Structures#Enumerate).

### 3.2.1 Unordered

An unordered list is generated by the `\begin{itemize}...\end{itemize}` environment with `\item` commands inside. The listing in Figure 3.2 generates an unordered list, placed to the right of the same figure.

---

<code>\begin{itemize}</code>	• C
<code>\item C</code>	
<code>\item C++</code>	• C++
<code>\item Java</code>	• Java
<code>\end{itemize}</code>	

---

Figure 3.2: Unordered list example.

### 3.2.2 Ordered

Ordered lists can be generated by the `\begin{enumerate}...\end{enumerate}` environment with `\item` commands inside. The listing in Figure 3.3 generates an ordered list, placed to the right of the same figure.

---

<code>\begin{enumerate}</code>	1. C
<code>\item C</code>	
<code>\item C++</code>	2. C++
<code>\item Java</code>	3. Java
<code>\end{enumerate}</code>	

---

Figure 3.3: Ordered list example.

The default numbering scheme of the template is arabic and it is recommended not to change that. The numbering scheme for nested ordered lists is automatically managed.

### 3.2.3 Description List

Sometimes, it is required to render something like a definition list. Although semantically it isn't a list, it follows the same syntax structure. Such special type of lists can be created with the `\begin{description}...\end{description}` environment and the `\item[...]` command. The usage of one such special list is illustrated in Figure 3.4 along with the output.



---

```
\begin{description}
\item[C] The first item's description
\item[C++] The second item's description
\item[Java] The third item's description
\end{description}
```

**C** The first item's description

**C++** The second item's description

**Java** The third item's description

---

Figure 3.4: Description list example.

### 3.3 Footnotes

A footnote is an ancillary piece of information, something that is additional but less important. They are placed at the bottom of the page<sup>1</sup>. The template automatically adds a horizontal rule to separate it from the main flow of the document. Each footnote is numbered, specific to the chapter in which it resides. A footnote is added through the `\footnote` command, with the actual contents of the footnote as the argument. Footnotes are meant to be added along the regular flow of the document. It is illustrated by Figure 3.5.

---

```
This is the regular flow of document\footnote{This piece of
text is treated as a footnote}.
```

---

Figure 3.5: An example footnote.

There may be multiple pages in the same page. The placement of the footnote, flow into the next page, numbering, etc., are all automatically managed.

### 3.4 Cross-References

Other elements in the document can be referenced via the `\ref` command at the location where a reference is to be inserted and the target identifies itself with a `\label` command.

---

<sup>1</sup>This is a sample footnote

### **3.5 External References**

TODO

## 4. Figures and Algorithms

Elements that are treated as figures the document are discussed here. In the following sections, examples have been provided on how to include figures and algorithms in the document.

### 4.1 Figures

Figures are handled in the standard  $\text{\LaTeX}$  manner. An minimalistic example is given in Figure 4.1. The figure is placed inside the `\begin{figure}...\end{figure}` environment. The options passed to the environment is the figure placement priority preference, h - at the current location, t - top and b - bottom. `\centering` indicates that the figure and caption should be placed at the centre. `\includegraphics` is self explanatory, with the width option and the source file. The source file extension is optional, left blank,  $\text{\LaTeX}$  chooses the best available format automatically. The rest of the section contains image inclusion and subfigure examples. The output generated is Figure 4.2.

---

```
\begin{figure}[htb]
\centering
\includegraphics[width=0.5\textwidth]{images/105003.jpg}
\caption{The big cat}
\label{fig:big_cat}
\end{figure}
```

---

Figure 4.1: Using 50% of the textbox to place the image.

#### 4.1.1 Sub-Figures

Figures inside figures. The subfigures are suitable when you want to explain a progressive concept through images. For example, a solar eclipse, amoeba fission, etc. Figure 4.3 partially lists the code for rendering subfigures<sup>1</sup>, Figure 4.4 is the output.

## 4.2 Algorithms

In this template, algorithms are treated as figures for the sake of simplicity. They too get listed in the list of figures. Similar to a figure, algorithms need to be placed in the

---

<sup>1</sup>Refer the source code of this document for more



Figure 4.2: The big cat

`{algorithm}` environment. The actual algorithm is represented by the statements inside the `{algorithmic}` environment. It defines its own set of commands. We strongly recommend the algorithmic environment compared to other packages offering similar functionality since it has been tested on the template and has a compact vocabulary. Figure 4.5 lists the algorithmic code for generating the output in Figure 4.6. Learn more about the algorithmic commands from [1].

Another informal way of defining algorithms is to use an enumeration list, suppose you are not concerned with the specifics of your algorithm or it simply needs to be descriptive. Figure 4.8 is one such listing, generated by the sample source in Figure 4.7<sup>2</sup>.

---

<sup>2</sup>Refer to the complete listing in this document's source code

---

```

\begin{figure} [htb]
\centering
\begin{subfigure} [b] {0.4\textwidth}
\includegraphics[width=\textwidth]{images/interphase.png}
\caption{Interphase}
\label{fig:mitosis_interphase}
\end{subfigure}
% Spacing %
\hspace{0.1\textwidth}
% Spacing %
\begin{subfigure} [b] {0.4\textwidth}
\includegraphics[width=\textwidth]{images/prometaphase.png}
\caption{Prometaphase}
\label{fig:mitosis_prometaphase}
\end{subfigure}
% Spacing %
\linebreak\linebreak
% Spacing %
\begin{subfigure} [b] {0.4\textwidth}
\includegraphics[width=\textwidth]{images/prometaphase.png}
\caption{Prometaphase}
\label{fig:mitosis_prometaphase}
\end{subfigure}
% Spacing %
\hspace{0.1\textwidth}
% Spacing %
...
...
...
% End of subfigures
\caption{The steps of mitosis.}
\label{fig:mitosis}
\end{figure}

```

---

Figure 4.3: Subfigure example.




Figure 4.4: The steps of mitosis.

---

```

\begin{algorithm}
\begin{algorithmic}[1]
\Procedure{Euclid}{$a,b$}\Comment{The g.c.d. of a and b}
\State $r \leftarrow a \bmod b$
\State $a \leftarrow b$
\State $b \leftarrow r$
\State $r \leftarrow a \bmod b$
\State \textbf{return} $b$ \Comment{The gcd is b}
\EndProcedure
\end{algorithmic}
\caption{Euclid's Algorithm}
\label{algo:euclid_algorithm}
\end{algorithm}

```

---

Figure 4.5: Euclid's algorithm, written in algorithmic.

---

1: <b>procedure</b> EUCLID( $a, b$ )	▷ The g.c.d. of $a$ and $b$
2: $r \leftarrow a \bmod b$	
3: $a \leftarrow b$	
4: $b \leftarrow r$	
5: $r \leftarrow a \bmod b$	
6: <b>return</b> $b$	▷ The gcd is $b$
7: <b>end procedure</b>	

---

Figure 4.6: Euclid's Algorithm

---

```

\begin{algorithm}
\begin{enumerate}
\item Initialize a population array of particles with
random positions and velocities on  $d$  dimensions,
in the problem space.
...
...
...
\item Loop to 2, until the stoping criterion is satisfied.
\end{enumerate}
\caption{Steps to perform Brownian motion.}
\label{algo:brownian_motion_steps}
\end{algorithm}

```

---

Figure 4.7: Listing to generate an enumerated list of steps.

- 
1. Initialize a population array of particles with random positions and velocities on  $d$  dimensions, in the problem space.
  2. For each particle, evaluate the desired optimization fitness function in  $d$  variables.
  3. Compare particles fitness evaluation with particles  $pbest$ . Then set  $pbest$  value (to make it ) equal to the current value, and the  $pbest$  location equal to the current location in  $d$ -dimensional space.
  4. Compare fitness evaluation with the populations overall previous best. If current value reduces the error to achieve global minima than previous  $gbest$ , then update  $gbest$  value.
  5. Update the velocity and position of the particle according to equation 1 and 2.
  6. Loop to 2, until the stoping criterion is satisfied.
- 

Figure 4.8: Steps to perform Brownian motion.



## 5. Tables

Tables are created with the tabular environment. The following sections illustrate the various types of tables.

### 5.1 A Simple Table

Tables that just present key-values are best suited for the plain layout.

Concepts	Ground truth [no img.]
lion	102
water	1081
grass	1064
building	1271
car	182
cloud	708
rock	922
tiger	102
elephant	109
flower	730
boat	234
flower fields	32
modern city view	168
rural garden	182
mountain view	598
waterfalls	15
wild life	322
city street	191

Table 5.1: Number of images in 18 concepts according to ground truth.

### 5.2 A Somewhat Big Table

Table 5.2: Concept detection accuracy

Training set proportion(%)	5 supported concepts				10 supported concepts			
10	52.06%	51.28%	33.73%	<b>57.77%</b>	45.18%	29.10%	21.98%	<b>49.26%</b>
30	<b>64.60%</b>	63.77%	27.21%	62.99%	56.49%	<b>56.99%</b>	21.15%	52.53%
50	<b>70.67%</b>	69.58%	25.45%	63.72%	61.88%	<b>62.37%</b>	19.76%	50.25%
Method	SVM	GA	SOM	PSO	SVM	GA	SOM	PSO

### 5.3 A Ver Big Table

Table 5.3: Retrieval Precision for each Concept from Corel Database

Concepts	Methods	Retrieval Precision				
Building	SOM	42%	34%	41%	42%	44%
	SVM	46%	<b>75%</b>	53%	50%	47%
	PSO	<b>52%</b>	68%	<b>73%</b>	<b>75%</b>	<b>76%</b>
Car	SOM	31%	33%	27%	28%	31%
	SVM	<b>58%</b>	<b>74%</b>	<b>67%</b>	<b>68%</b>	56%
	PSO	44%	54%	63%	64%	<b>66%</b>
Cloud	SOM	39%	40%	41%	42%	44%
	SVM	<b>80%</b>	<b>92%</b>	73%	70%	69%
	PSO	53%	68%	<b>75%</b>	<b>75%</b>	<b>77%</b>
Grass	SOM	<b>41%</b>	26%	34%	26%	37%
	SVM	27%	42%	28%	24%	27%
	PSO	40%	<b>57%</b>	<b>62%</b>	<b>65%</b>	<b>68%</b>
Elephant	SOM	31%	38%	36%	34%	40%
	SVM	<b>74%</b>	<b>96%</b>	<b>91%</b>	<b>83%</b>	<b>96%</b>
	PSO	50%	70%	78%	81%	83%
Lion	SOM	21%	25%	22%	23%	25%
	SVM	48%	59%	49%	48%	42%
	PSO	<b>53%</b>	<b>63%</b>	<b>68%</b>	<b>71%</b>	<b>76%</b>
Tiger	SOM	36%	29%	40%	32%	46%
	SVM	28%	60%	62%	58%	52%
	PSO	<b>58%</b>	<b>73%</b>	<b>78%</b>	<b>77%</b>	<b>76%</b>
Average	SOM	34%	32%	34%	32%	38%
	SVM	<b>51%</b>	<b>71%</b>	60%	57%	55%
	PSO	50%	64%	<b>71%</b>	<b>72%</b>	<b>74%</b>
User Iteration		1	2	3	4	5

### 5.4 Rotated Table

When you want a horizontally big table to be placed, you have to rotate it<sup>1</sup>. Placing a table inside of the `\begin{sidewaystable}...\end{sidewaystable}` environment, instead of the `\table` environment renders it 90° counter-clockwise rotated. Note that the caption is also rotated.

---

<sup>1</sup>It is recommended not to span tables across multiple pages, especially when it is being rotated. In case a big data sheet is to be placed, print it separately and attach it to an appendix at the end of your report

Table 5.4: Concept detection accuracy with 15 concepts.

Training set proportion(%)	5 supported concepts					10 supported concepts					15 supported concepts				
	SVM	GA	SOM	PSO	SVM	GA	SOM	PSO	SVM	GA	SOM	PSO	SVM	GA	SOM
10	52.06%	51.28%	33.73%	<b>57.77%</b>	45.18%	29.10%	21.98%	<b>49.26%</b>	41.87%	37.88%	9.87%	<b>43.80%</b>			
30	<b>64.60%</b>	63.77%	27.21%	62.99%	56.49%	<b>56.99%</b>	21.15%	52.53%	53.76%	<b>53.85%</b>	20.69%	47.85%			
50	<b>70.67%</b>	69.58%	25.45%	63.72%	61.88%	<b>62.37%</b>	19.76%	50.25%	59.05%	<b>59.91%</b>	20.87%	47.03%			
Method	SVM	GA	SOM	PSO	SVM	GA	SOM	PSO	SVM	GA	SOM	PSO	SVM	GA	PSO

## 6. Equations

Example of equations have been listed below. Refer to the document source code for more.

### 6.1 Inline

$\Sigma$  - Inline equation symbols can be inserted with the help of `$ . . . $`

### 6.2 More examples

$$\forall x \in X, \quad \exists y \leq \epsilon$$

#### 6.2.1 Greek Characters

$$\alpha, \beta, \gamma, \pi, \Pi, \phi, \varphi, \Phi$$

#### 6.2.2 Operator

$$\cos(2\theta) = \cos^2 \theta - \sin^2 \theta$$

### 6.3 Subscript/Superscript

$$\lim_{x \rightarrow \infty} \exp(-x) = 0$$

$$k_{n+1} = n^2 + k_n^2 - k_{n-1}$$

### 6.4 Fractions and Binomials

$$\frac{n!}{k!(n-k)!} = \binom{n}{k}$$

$$\frac{n!}{k!(n-k)!} = \binom{n}{k}$$

## 6.5 Equation Environment

Things put into the `\begin{equation}...\end{equation}` environment will automatically be numbered and can be referred like 6.1.

$$\frac{\frac{1}{x} + \frac{1}{y}}{y - z} \quad (6.1)$$

## 6.6 Fractions

### 6.6.1 Inline

Fractions can be inline like:

Take  $\frac{1}{2}$  cup of sugar, ...  $3 \times \frac{1}{2} = 1\frac{1}{2}$

Take  $\frac{1}{2}$  cup of sugar, ...  $3 \times \frac{1}{2} = 1\frac{1}{2}$

### 6.6.2 Continued Fractions

$$x = a_0 + \frac{1}{a_1 + \frac{1}{a_2 + \frac{1}{a_3 + a_4}}} \quad (6.2)$$

### 6.6.3 Multiplication of two numbers

To make multiplication visually similar to a fraction, a nested array can be used, for example multiplication of numbers written one below the other.

$$\frac{\begin{array}{c} (x_1 x_2) \\ \times (x'_1 x'_2) \end{array}}{(y_1 y_2 y_3 y_4)} \quad (6.3)$$

## 6.7 Fermat numbers

Numbers of the form  $2^{2^n} + 1$ , where  $n$  is a natural number, are called Fermat numbers

## 6.8 Roots

$$2\sqrt{2}, \quad 2^2\sqrt{2-\sqrt{2}}, \quad 2^3\sqrt{2-\sqrt{2+\sqrt{2}}},$$

$$2^4\sqrt{2-\sqrt{2+\sqrt{2+\sqrt{2+\sqrt{2}}}\dots}}$$

## 6.9 Mathematical Symbols

circ symbol:  $x \circ y = x + y - xy$

box symbol:  $x \boxplus y = x^2 + y^2$

## 6.10 Sample Vectors

`\vect` can be used to generate sample vectors  $(x_1, x_2, \dots, x_n)$

Variable name as a parameter `\expres{a}` generates  $(a_1, a_2, \dots, a_n)$

`\vecto{a}{p}`, generates  $(a_1, a_2, \dots, a_p)$

## 6.11 More Mathematics

Remove equation numbers with `\begin{equation*}\dots\end{equation*}`.

$$ax + by + c = 0$$

$$x \leq |x| \quad \text{and} \quad x \geq |x|$$

and so

$$x \leq |x| \quad \text{for all } x \text{ in } R.$$

Use `\begin{multiline}\dots\end{multiline}` if your equation has to span multiple lines 6.4. Similar to the equation environment, equation numbers can be removed in multiline with `\begin{multiline*}\dots\end{multiline*}`. Including `\split` inside the multiline gives you a better alignment by splitting the equation into LHS and RHS<sup>1</sup> The various type of equations and techniques to arrange/align them are given the following sections.

---

<sup>1</sup>A few more examples have been commented out in the source code so that it doesn't look overwhelming to you! Check out the source code, you may find what you need.

### 6.11.1 Multiline Equations

$$\begin{aligned}(a + b + c + d + e)^2 &= a^2 + b^2 + c^2 + d^2 + e^2 \\ &\quad + 2ab + 2ac + 2ad + 2ae + 2bc + 2bd \\ &\quad + 2be + 2cd + 2ce + 2de\end{aligned}\tag{6.4}$$

$$\begin{aligned}(a + b + c + d + e + f)^2 &= a^2 + b^2 + c^2 + d^2 + e^2 + f^2 \\ &\quad + 2ab + 2ac + 2ad + 2ae + 2af \\ &\quad + 2bc + 2bd + 2be + 2bf \\ &\quad + 2cd + 2ce + 2cf \\ &\quad + 2de + 2df \\ &\quad + 2ef\end{aligned}$$

$$\begin{aligned}(a + b + c + d + e + f)^2 &= a^2 + b^2 + c^2 + d^2 + e^2 + f^2 \\ &\quad + 2ab + 2ac + 2ad + 2ae + 2af \\ &\quad + 2bc + 2bd + 2be + 2bf \\ &\quad + 2cd + 2ce + 2cf \\ &\quad + 2de + 2df \\ &\quad + 2ef\end{aligned}$$

$$\begin{aligned}(a + b)^2 &= (a + b)(a + b) \\ &= a^2 + ab + ba + b^2 \\ &= a^2 + 2ab + b^2\end{aligned}$$

### 6.11.2 Cases

$$|x| = \begin{cases} x & \text{if } x \geq 0 \\ -x & \text{if } x \leq 0 \end{cases}$$

### 6.11.3 Matrices

The system of equations

$$x + y - z = 1$$

$$x - y + z = 1$$

$$x + y + z = 1$$

can be written in matrix terms as

$$\begin{pmatrix} 1 & 1 & -1 \\ 1 & -1 & 1 \\ 1 & 1 & 1 \end{pmatrix} \begin{pmatrix} x \\ y \\ z \end{pmatrix} = \begin{pmatrix} 1 \\ 1 \\ 1 \end{pmatrix}.$$

Here, the matrix  $\begin{pmatrix} 1 & 1 & -1 \\ 1 & -1 & 1 \\ 1 & 1 & 1 \end{pmatrix}$  is invertible.

A Bracket Matrix:  $\begin{bmatrix} a & b \\ c & d \end{bmatrix}$

$$\begin{vmatrix} a & b \\ c & d \end{vmatrix} = ad - bc$$

$$\begin{pmatrix} a_{11} & a_{12} & \dots & a_{1n} \\ a_{21} & a_{22} & \dots & a_{2n} \\ \dots & \dots & \dots & \dots \\ a_{m1} & a_{m2} & \dots & a_{mn} \end{pmatrix}$$

$\begin{vmatrix} a & h & g \\ h & b & f \\ g & f & c \end{vmatrix} = 0$ , the matrix  $\begin{pmatrix} a & h & g \\ h & b & f \\ g & f & c \end{pmatrix}$  is not invertible.



#### 6.11.4 Symbols with alignment

$$\left. \begin{array}{l} u_x = v_y \\ u_y = -v_x \end{array} \right\} \text{Cauchy-Riemann Equations}$$

#### 6.11.5 Summations

$$\left( \sum_{k=1}^n |x_k y_k| \right)^2 \leq \left( \sum_{k=1}^n |x_k| \right) \left( \sum_{k=1}^n |y_k| \right)$$

#### 6.11.6 Limits and Integrals

$\lim_{x \rightarrow \infty} \int_0^x \frac{\sin x}{x} dx = \frac{\pi}{2}$  and so by definition,

$$\int_0^\infty \frac{\sin x}{x} dx = \frac{\pi}{2}$$

## 7. References

- [1] Szasz Janos. *The algorithmicx package*. Indiana State University, USA, 2005.  
<http://cs.indstate.edu/CS695/algorithmicx.pdf>.
- [2] Stefan Kottwitz. *LaTeX beginner's guide*. Packt, Birmingham, UK, 2011.
- [3] RS Santhos Baala. Vit ms project report class, 2014.  
<https://github.com/santhosbaala/vitmsprojectreport>.