

## Recurrence for merge sort

$$T(n) = \begin{cases} \Theta(1) & \text{if } n = 1; \\ 2T(n/2) + \Theta(n) & \text{if } n > 1. \end{cases}$$

- We shall usually omit stating the base case when  $T(n) = \Theta(1)$  for sufficiently small  $n$ , but only when it has no effect on the asymptotic solution to the recurrence.

L2.1

L2.2

## Recursion tree


Solve  $T(n) = 2T(n/2) + cn$ , where  $c > 0$  is constant.

$T(n)$

L2.3

## Recursion tree


Solve  $T(n) = 2T(n/2) + cn$ , where  $c > 0$  is constant.



L2.4

## Recursion tree


Solve  $T(n) = 2T(n/2) + cn$ , where  $c > 0$  is constant.



L2.5

## Recursion tree


Solve  $T(n) = 2T(n/2) + cn$ , where  $c > 0$  is constant.



L2.6

## Recursion tree


Solve  $T(n) = 2T(n/2) + cn$ , where  $c > 0$  is constant.



L2.7

## Recursion tree


Solve  $T(n) = 2T(n/2) + cn$ , where  $c > 0$  is constant.



L2.8

## Recursion tree


Solve  $T(n) = 2T(n/2) + cn$ , where  $c > 0$  is constant.



L2.9

## Recursion tree


Solve  $T(n) = 2T(n/2) + cn$ , where  $c > 0$  is constant.



L2.10

## Recursion tree


Solve  $T(n) = 2T(n/2) + cn$ , where  $c > 0$  is constant.



L2.11

## Recursion tree

Solve  $T(n) = 2T(n/2) + cn$ , where  $c > 0$  is constant.



L2.12

## Conclusions

- $\Theta(n \lg n)$  grows more slowly than  $\Theta(n^2)$ .
- Therefore, merge sort asymptotically beats insertion sort in the worst case.
- In practice, merge sort beats insertion sort for  $n > 30$  or so.
- Go test it out for yourself! Try it out with random, ascending, and descending inputs
- <https://www.cs.usfca.edu/~galles/visualization/ComparisonSort.html>
- <https://www.toptal.com/developers/sorting-algorithms>

L2.13