

Programming Challenges (GB21802)

Week 9 - Computational Geometry

Claus Aranha

caranha@cs.tsukuba.ac.jp

University of Tsukuba, Department of Computer Sciences

(last updated: June 12, 2021)

Version 2021.1


Part I: Introduction

What is Computational Geometry?

In programming challenges, Computational Geometry problems involve answering questions about **lines, points and angles**.

Example 1

Given a set of N points $(s_1, s_2, s_3, \dots, s_N)$, what is the area of the smallest polygon that covers all points in the set?




What is Computational Geometry?

In programming challenges, Computational Geometry problems involve answering questions about **lines, points and angles**.

Example 2

Given N rectangles, $\{x_1, y_1, w_1, h_1\}; \dots; \{x_N, y_N, w_N, h_N\}$, what is the smallest length of line segments needed to connect them?




What is Computational Geometry?

In programming challenges, Computational Geometry problems involve answering questions about **lines, points and angles**.

Example 3

Given a polygon and a set of N points, find a line that divides the polygon in equal areas, with the same number of points in each area?



Computational Geometry: The good and the bad

Positive Points

- Geometry problems are fun, and you draw pretty pictures when thinking about them;
- A large part of geometry problems can be solved with algorithms and techniques that you learned in high school;
- The code for techniques is highly re-usable;

Negative Points

- You have to write a lot of code (but a lot of it is reusable!);
- Easy to get WE for small mistakes;
- Many special cases in the input data;

Common Mistakes in Geometry Problems

Errors because of special cases in input data

- Multiple points in the same position;
- Collinear points (three points in the same line);
- Vertical lines (bad tangent value, division by 0);
- Parallel Lines (bad intersection value);
- Intersection at end of a segment;
- etc;

Floating Number Precision Errors

- Wrong Answer because of poor rounding of final result;
- Error Propagation inside functions (multiplication, division);

Common Mistakes in Geometry Problems

How to avoid these mistakes in Geometry Problems?

- **Special Cases:**

- Make sure to think which special cases affect your technique, and add checks for these cases;
- When testing your problem, include input with the special case;

- **Precision Errors:**

- If possible, convert values to integers before calculation;
- When testing equality of two values, use an **Epsilon Constant**:

```
if (float.1 == float.2) then                // NO  
if (fabs(float.1 - float.2) < EPS) then // YES!
```


Class Outline

In this lecture, we will focus on:


- Discussion of implementation of geometric operations;
- Discussion of problem examples;

Specific topics will be:

- Intersection and Rotation of points and lines;
- Circle representation and components;
- Triangles (area, angles, triangles and circles);
- Polygon representation and Convex Hull;


Problem Example: Intersection

- **Input:** A rectangle and a line segment:
 - Rectangle: $x_s y_s x_e y_e$
 - Line: x_0, y_0, x_1, y_1
- **Output**
True if the line segment intersects the rectangle, **False** if not



How do you solve it?

Problem Example: Intersection



- Test if p_1 or p_2 are inside the rectangle;
- For each segment \overline{AB} , test if $\overline{p_1, p_2}$ intersects \overline{AB} .

```
int segmentIntersect(ax, ay, bx, by,
                    cx, cy, dx, dy)
{
    ta = (cx - dx) * (ay - cy) + (cy - dy) * (cx - ax);
    tb = (cx - dx) * (by - cy) + (cy - dy) * (cx - bx);
    tc = (ax - bx) * (cy - ay) + (ay - by) * (ax - cx);
    td = (ax - bx) * (dy - ay) + (ay - by) * (ax - dx);

    return tc*td <= 0 && ta*tb <= 0;
};
```


Problem Example: Waterfalls

- **Input**


- List of line segments that block water;
- List of water sources;

- **Output**

- For every waterfall w , the end position X_w where $Y_w = 0$



Problem Example: Waterfalls




Full Search:

- For each water source S_i :
 - Calculate which segment intersects $\overline{S_i 0}$ first.
 - Adjust the position X_i and repeat until $Y_i = 0$.
- This is a bit slow if there are many sources and segments.
- Can you pre-calculate something?
- Remember that all inputs are integers!

Part II – Points and Lines

Representing a point as a structure



```
struct point_i { int x, y; // integer coordinates
  point_i() { x = y = 0; }
  point_i(int _x, int _y) : x(_x), y(_y) {} };

struct point { double x, y; // double coordinates
  point() { x = y = 0.0; }
  point(double _x, double _y) : x(_x), y(_y) {} };
```

Overloading Point Operators

```
struct point { double x, y;
    point() { x = y = 0.0; }
    point(double _x, double _y) : x(_x), y(_y) {}

    bool operator < (point other) const {           // Overloading "<"
        if (fabs(x - other.x) > EPS)
            return x < other.x;
        return y < other.y; }

    bool operator == (point other) const {          // Overloading "=="
        return (fabs(x - other.x) < EPS &&
            (fabs(y - other.y) < EPS)); }
}


point a = point(1,2); point b = point(3,4);

if (!(a == b)) printf("Different\n");
```


Point Distance

```
// Euclidean Distance: "normal" distance
#define hypot(dx,dy) sqrt(dx*dx + dy*dy)
double dist(point p1, point p2) { return hypot(p1.x - p2.x, p1.y - p2.y); }


// Taxicab Distance / Manhattan Distance : Distance on a grid
double taxicab(point p1, point p2) { return fabs(p1.x-p2.x) + fabs(p1.y-p2.y); }
```



Point Rotation

```
#define PI          3.14159265358979323846 // Pi constant
double PI = 2 * acos(0.0)                // Better Pi
#define DEG_to_RAD(X) (X*PI)/180.0        // Don't confuse DEG and RAD

// suppose angle t is in degrees (0--360)
point rotate(point p, double t) {
    double rad = DEG_to_RAD(t);
    return point(p.x * cos(rad) - p.y * sin(rad),
                p.x * sin(rad) + p.y * cos(rad));}
```



$$\begin{bmatrix} x' \\ y' \end{bmatrix} = \begin{bmatrix} \cos(\theta) & -\sin(\theta) \\ \sin(\theta) & \cos(\theta) \end{bmatrix} \times \begin{bmatrix} x \\ y \end{bmatrix}$$

Data Structure for a Line

- $ax + by + c = 0$

(a,b,c) – useful for most cases

- $y = mx + c$

(m,c) – useful for angle manipulation

- x_0, y_0, x_1, y_1

(p_1, p_2) – harder to use, but common input


How to convert from two points to a line

```
struct line { double a,b,c; };
```

```
void pointsToLine(point p1, point p2, line &l) {  
    if (fabs(p1.x - p2.x) < EPS {  
        l.a = 1.0; l.b = 0.0; l.c = -p1.x; }  
    else {  
        l.a = -(double) (p1.y - p2.y) / (p1.x - p2.x);  
        l.b = 1.0; l.c = -(double) (l.a*p1.x) - p1.y;}  
}
```

Line Equality

- We define a line as $a, b, c \rightarrow (ax + by = c)$
- Two lines are parallel if their coefficients (a, b) are the same;
- Two lines are identical if all coefficients (a, b, c) are the same;



```
bool areParallel(line l1, line l2) {  
    return (fabs(l1.a-l2.a) < EPS) && (fabs(l1.b-l2.b) < EPS); }
```

```
bool areSame(line l1, line l2) {  
    return areParallel(l1,l2) && (fabs(l1.c - l2.c) < EPS); }
```

Line Intersection

The intersection point x_I, y_I can be found by solving:

$$a_1 x_I + b_1 y_I + c_1 = 0$$

$$a_2 x_I + b_2 y_I + c_2 = 0$$

Remember that when we create a line i , we set $b_i = 0$ or $b_i = 1$


```
bool areIntersect(line l1, line l2, point &p) {
    if (areParallel(l1,l2)) return False;

    p.x = (l2.b * l1.c - l1.b * l2.c) /
          (l2.a * l1.b - l1.a * l2.b);

    // Test for vertical case:
    if (fabs(l1.b) > EPS)    p.y = -(l1.a * p.x + l1.c);
    else                    p.y = -(l2.a * p.x + l2.c);
    return True;
}
```

Segments and Vectors

- A **line segment** is a line with two endpoints (p_1, p_2);
- A **Vector** is a line segment with a direction;
 - Usually represented as "direction" and "magnitude";
 - Direction is a point with distance 1 from (0, 0)
 - Magnitude is a multiplier to the size of the vector;
 - Represent movement, translation, speed, etc;



```
struct vec { double x, y;
    vec(double _x, double _y) : x(_x), y(_y) {} };

vec toVec(point a, point b) {
    return vec(b.x - a.x, b.y - a.y); }

vec scale(vec v, double s) {
    return vec(v.x * s, v.y * s); }

point translate(point p, vec v) {
    return point(p.x + v.x , p.y + v.y); }
```

Distance between point and line, point and segment



For a point p and a line l (represented by \overline{ab}), the distance between both is given by the segment pc , where c is the projection of p in l .

Calculating c :

- calculate scalar proj. u of \vec{ap} in l .
- change magnitude of \vec{ab} to u to obtain \vec{ac} .
- calculate distance between p and c .

Distance between p and \overline{ab} :

- calculate scalar proj. u of \vec{ap} in l .
- if $u < 0$ or $u > |\vec{ab}|$, then the distance is $\min(d(a, p), d(b, p))$.
- else, calculate \vec{ac} and calculate distance $d(p, c)$.



CODE: Distance between point and line

```
double dot(vec a, vec b) { return (a.x * b.x + a.y * b.y); } // dot product
double norm_sq(vec v) { return v.x * v.x + v.y * v.y; } // norm squared

// Given points a,b,p, calculate distance from p to line ab.
double distToLine(point p, point a, point b, point &c) {
    // point c: c = a + u * |ab|
    vec ap = toVec(a, p), ab = toVec(a, b);

    // dot product calculates size of ap in ab
    // norm square will calculate the scale to ab
    double u = dot(ap, ab) / norm_sq(ab);

    // translate a by u to find point c.
    c = translate(a, scale(ab, u));
    return dist(p, c);
}
```


CODE: Distance between point and segment

Same as before, but first we test if c is inside \overline{ab} .

```
double distToSegment(point p, point a, point b, point &c) {  
    // next two lines is exact same as last slide  
    vec ap = toVec(a, p), ab = toVec(a, b);  
    double u = dot(ap, ab) / norm_sq(ab);  
  
    // test if the magnitude $u$ is bigger or smaller than ab.  
    if (u < 0.0) { c = point(a.x, a.y); // closer to a  
        return dist(p, a); }  
    if (u > 1.0) { c = point(b.x, b.y); // closer to b  
        return dist(p, b); }  
  
    // c is inside AB, same as last slide  
    c = translate(a, scale(ab, u));  
    return dist(p, c);  
}
```

Angle between segments

Given three points, a , b and o , we can calculate the angle between \overline{oa} and \overline{ob} using the dot product.

Given that: $oa \cdot ob = |oa| \times |ob| \times \cos(\theta)$, we have $\theta = \arccos(\frac{oa \cdot ob}{|oa| \times |ob|})$

```
#import <cmath>

// angle in radians (0..2*PI)
double angle(point a, point o, point b) {
    vec oa = toVector(o, a), ob = toVector(o, b);
    return acos(dot(oa, ob) / sqrt(norm_sq(oa) * norm_sq(ob)));
}
```

Left, Right and Collinear Points

Given a line defined by points p and q , we are interested in knowing if point r is on the left/right side of the line, or if the three points are collinear.

Let \vec{pq} and \vec{pr} be two vectors, the **cross product** $\vec{pq} \times \vec{pr}$ is a vector that is perpendicular to both vectors. The magnitude of the cross product is positive / zero / negative if $p \rightarrow q \rightarrow r$ is left turn / collinear / right turn.

```
double cross(vec a, vec b) { return a.x * b.y - a.y * b.x; }

bool ccw(point p, point q, point r) {
    return cross(toVec(p, q), toVec(p, r)) > 0; }

collinear(point p, point q, point r) {
    return fabs(cross(toVec(p, q), toVec(p, r))) < EPS;
```

Part III: Circles and Triangles


Circles

- A circle is stored as its center point c , and its radius r .
- The circle contains all points (x, y) where $(x - a)^2 + (y - b)^2 \leq r^2$
- No square root, so less chance of floating point errors.

Test if Point p is inside Circle – Integer Version


```
int insideCircle(point_i p, point_i c, int r) {  
    int dx = p.x-c.x, dy = p.y-c.y;  
    int Euc = dx*dx + dy*dy, rSq = r*r;  
    return Euc < rSq ? 0 : Euc == rSq ? 1 : 2;  
    // 0 - inside, 1 - border, 2- outside  
}
```

Other circle properties



- **radius:** r , **diameter:** $2r$, **circumference:** $2 \times \pi \times r$
- You can obtain π from the problem, or with $\pi = 2 \times \arccos(0)$
- Given a central angle α :
 - **Arc:** $r \times \alpha$ (if in rad) or $r \times \frac{\alpha}{360} \times 2\pi$ (if degrees)
 - **Sector:** $\frac{\alpha r^2}{2}$ (if in rad) or $2\pi r^2 \times \frac{\alpha}{360}$ (if degrees)

Other circle properties – chord



- **chord:** Line segment with two ends in the circle's border.
- If you know p_1 , p_2 and c , you can find α from the "angle" function;
- If you know α and r , you can find the size of the chord by: $|p_1 p_2| = 2 \times r \times \sin(\alpha/2)$
 - **Quiz:** If you know a line and a circle, how do you find p_1 and p_2 ?
- If you know p_1 , p_2 , and r (but not α or c), you can find the center of the circle using the code in the next page;

Circle Center from points and radius

You have two points p_1, p_2 that form a chord in a circle, and the radius of that circle. How do you find the center?

```
bool circle2PtsRad(point p1, point p2, double r, point &c) {
    double d2 = (p1.x - p2.x) * (p1.x - p2.x) +
                (p1.y - p2.y) * (p1.y - p2.y);
    double det = r * r / d2 - 0.25;

    if (det < 0.0) return false; // Can't make circle

    double h = sqrt(det);
    c.x = (p1.x + p2.x) * 0.5 + (p1.y - p2.y) * h;
    c.y = (p1.y + p2.y) * 0.5 + (p2.x - p1.x) * h;
    return true;
}
// to get the other center, reverse p1 and p2
```



Triangle Problem Example: Soya milk

- **Input:**

The dimensions of a Milk box, and its inclination: l, w, h, θ

- **Output:**

The amount of milk left in the box.




Triangle/Circle Problem Example: Bounding Box

- **Input:** Three points that are the vertices of a **regular polygon**, and number n of sides in the polygon;
- **Output:** Area of smallest **axis aligned** rectangle that bounds this polygon.

Triangle Basic Facts

- **Triangle Inequality:** If a, b, c are sides of a triangle, then $a + b > c; a + c > b; b + c > a$;
- **Perimeter, Semiperimeter:** $p = a + b + c, s = p/2$
- **Area:** $A = \frac{bh_b}{2}$
- **Area (Heron's formula):** $A = \sqrt{s(s-a)(s-b)(s-c)}$
- **Triangulation:** Any 2D polygon can be decomposed into triangles;

Incircle of a Triangle



- An **Inscribed Circle (incircle)** is the largest circle that fits inside a triangle;
- The radius of the incircle is: $r = A/s$
- The center of the circle can be found by the intersection of two **angle bisectors**.

Radius of the Incircle: $r = \text{area}/s$

```
double rInCircle(double ab, double bc, double ca) {  
    return area(ab, bc, ca) / (0.5 * perimeter(ab, bc, ca));  
}
```

```
double rInCircle(point a, point b, point c) {  
    return rInCircle(dist(a, b), dist(b, c), dist(c, a));  
}
```

Finding the center of the Incircle of a triangle


```
int inCircle(point p1, point p2, point p3, point &ctr, double &r) {
    r = rInCircle(p1, p2, p3);
    if (fabs(r) < EPS) return 0;           // Test colinear points !!!
    line l1, l2;      // we calculate the intersect of two angle bisectors

    double ratio; point p;
    ratio = dist(p1, p2) / dist(p1, p3);
    p = translate(p2, scale(toVec(p2, p3), ratio / (1 + ratio)));
    pointsToLine(p1, p, l1);                // bisector 1

    ratio = dist(p2, p1) / dist(p2, p3);
    p = translate(p1, scale(toVec(p1, p3), ratio / (1 + ratio)));
    pointsToLine(p2, p, l2);                // bisector 2

    areIntersect(l1, l2, ctr);              // find center (ctr)
    return 1;
}
```

Circumcircle of a Triangle



- The radius of the circumcircle in a triangle with sides a, b, c and area A is $R = \frac{abc}{4A}$;
- The radius R is also related to the **Law of Sines**:

$$\frac{a}{\sin \alpha} = \frac{b}{\sin \beta} = \frac{c}{\sin \gamma} = 2R$$

- To find the center of the circumcircle:
 - Use a similar algorithm as the center of the incircle (last slide);
 - Instead of angle bisectors, use **perpendicular bisectors**;

Part IV – Polygons and Convex Hull

Polygons – Definition and data structure

A polygon is a plane figure bounded by a finite sequence of line segments.

Polygon Representation

- In general, we store an array of points of the segments;
- We want to sort the points in CW or CCW order;
- Add the first point at the end of the array to avoid special cases;

```
// 6 points, entered in counter clockwise order;
vector<point> P;
P.push_back(point(1, 1)); // P0
P.push_back(point(3, 3)); // P1
P.push_back(point(9, 1)); // P2
P.push_back(point(12, 4)); // P3
P.push_back(point(9, 7)); // P4
P.push_back(point(1, 7)); // P5
P.push_back(P[0]); // important: loop back
```


Characteristics of a Polygon

Perimeter of a Polygon – add the distances of the segments

```
double perimeter(const vector<point> &P) {  
    double result = 0.0;  
    for (int i = 0; i < (int)P.size()-1; i++)  
        // remember: P[0] = P[P.size()-1]  
        result += dist(P[i], P[i+1]);  
    return result; }
```

Area of a Polygon – half of the determinant of the XY matrix of segments

```
double area(const vector<point> &P) {  
    double result = 0.0, x1, y1, x2, y2;  
    for (int i = 0; i < (int)P.size()-1; i++) {  
        x1 = P[i].x; x2 = P[i+1].x;  
        y1 = P[i].y; y2 = P[i+1].y;  
        result += (x1 * y2 - x2 * y1); }  
    return fabs(result) / 2.0; }
```

Testing if a Polygon is Convex

- A convex polygon has no "holes";
- For any 2 points p_1, p_2 inside the polygon, segment is inside polygon too.

Easier Convex Testing: Every angle turns the same way

```
bool isConvex(const vector<point> &P) {
    // Returns true if every 3 neighb vertices turn the same way;
    int sz = (int)P.size();
    if (sz <= 3) return false; // Not a polygon

    bool isLeft = ccw(P[0], P[1], P[2]); // described earlier

    for (int i = 1; i < sz-1; i++)
        if (ccw(P[i], P[i+1], P[(i+2) == sz ? 1 : i+2]) != isLeft)
            return false; // not same direction as isLeft.

    return true;
}
```

Polygon – Test point inside the polygon

We can use the same idea to test if a point is inside the polygon: The direction of the point in relation to every edge should be the same.

Winding Algorithm Code for point in polygon detection

```
bool inPolygon(point pt, const vector<point> &P) {  
    if ((int)P.size() == 0) return false;  
    double sum = 0;  
  
    for (int i = 0; i < (int)P.size()-1; i++) {  
        if (ccw(pt, P[i], P[i+1]))  
            sum += angle(P[i], pt, P[i+1]);           //left turn/ccw  
        else sum -= angle(P[i], pt, P[i+1]);           //right turn/cw  
    }  
  
    return fabs(fabs(sum) - 2*PI) < EPS;  
}
```

QUIZ: What happens if the point is at an edge segment?

Polygon – Cutting


To cut P along a line AB , we separate the points in P to the left and right of the line.

```
point lineIntersectSeg(point p, point q, point A, point B) {
    double a = B.y-A.y; double b = A.x - B.x; double c = B.x*A.y - A.x*B.y;
    double u = fabs(a*p.x + b*p.y + c); double v = fabs(a*q.x + b*q.y + c);
    return point((p.x*v + q.x*u)/(u+v), (p.y*v + q.y*u)/(u+v)); }

vector<point> cutPolygon(point a, point b, const vector<point> &Q){
    vector<point> P;
    for (int i = 0; i < (int)Q.size(); i++) {
        double left1 = cross(toVec(a, b), toVec(a, Q[i])), left2 = 0;
        if (i != (int)Q.size()-1)
            left2 = cross(toVec(a, b), toVec(a, Q[i+1]));
        if (left1 > -EPS)
            P.push_back(Q[i]); //Q[i] is on the left of ab
        if (left1*left2 < -EPS) //edge (Q[i], Q[i+1]) crosses line ab
            P.push_back(lineIntersectSeg(Q[i], Q[i+1], a, b)); }
    if (!P.empty() && !(P.back() == P.front()))
        P.push_back(P.front()); // make P's first point = P's last point
    return P; }
```

Polygon – Convex Hull

- A common problem: Given a set of points S , what is the **smallest convex polygon** that includes all points in S ?
- One way to find the Convex Hull: for each point $p \in S$, determine if the point is at the edge of the polygon (in the hull) or inside the polygon (not in the hull).
- We will introduce the $O(n \log n)$ algorithm "Graham's Scan"



Polygon – Graham's Scan

Helper Functions – sort two points based on their angle against the X axis

```
point pivot(0, 0);

bool angleCmp(point a, point b) {
    // special case: if collinear, choose closet to pivot;
    if (collinear(pivot, a, b)) // special case
        return dist(pivot, a) < dist(pivot, b);

    // calculate angle against the X axis:
    double d1x = a.x - pivot.x, d1y = a.y - pivot.y;
    double d2x = b.x - pivot.x, d2y = b.y - pivot.y;

    return (atan2(d1y, d1x) - atan2(d2y, d2x)) < 0;
}
```

Polygon – Graham's Scan

Convex Hull – Initializing the algorithm

```
vector<point> CH(vector<point> P) {  
    int i, j, n = (int)P.size();  
    // Special Case: Polygon with 3 points  
    if (n <= 3) {  
        if (!(P[0]==P[n-1])) P.push_back(P[0]);  
        return P; }  
  
    // Find Initial Point: Low Y then Right X  
    int P0 = 0;  
    for (i = 1; i < n; i++)  
        if (P[i].y < P[P0].y ||  
            (P[i].y == P[P0].y && P[i].x > P[P0].x))  
            P0 = i;  
    point temp = P[0]; P[0] = P[P0]; P[P0] = temp;
```

Polygon – Graham's Scan

Convex Hull – More initialization

```
// second, sort points by angle with pivot P0
pivot = P[0];
sort(++P.begin(), P.end(), angleCmp);

// S holds the Convex Hull
// We initialize it with first three points
vector<point> S;
S.push_back(P[n-1]);
S.push_back(P[0]);
S.push_back(P[1]);

// We start on the third point
i = 2;
```


Polygon – Graham's Scan

Convex Hull – Main Loop

Now that we selected a pivot and sorted the points, we test every three points (following the sort) if they are in the convex hull.

```
while (i < n) {  
    j = (int) S.size() - 1;  
    // If the next point is left of CH, keep it.  
    // Else, pop the last CH point and try again.  
  
    if (ccw(S[j-1], S[j], P[i]))  
        S.push_back(P[i++]);  
    else  
        S.pop_back();  
}  
return S;  
} // End Graham's Scan CH
```

Class Summary

In this class we saw several algorithms for calculating computational geometry constructs:


- Points and Lines and Intersections;
- Circles and Triangles, areas and intersections;
- Convex Hull testing and Convex Hull construction;

Harder geometry problems will require you to perform search on geometry constructs, graph search, etc. Having a library with the functions of this class ready will be useful!

This Week's Problems


- Sunny Mountains – Line and Points
- Waterfall – Line and Points
- **Discussed in Class**
- Elevator – Circles and Rectangles
- Colorful Flowers – Circles and Triangles
- Bounding Box – Circles, Triangles and Polygons
- **Discussed in Class**
- Soya Milk – Rectangle and Triangle
- **Discussed in Class**
- Trash Removal – Polygon Manipulation
- Board Wrapping – Convex Hull

Sunny Mountains




- Given segment points as the input, calculate the area illuminated by the sun.
- **Hint:** This problem is about calculating line/segment intersections.
- **Hint:** Because the line is always HORIZONTAL, you can write a function that is simpler than the one I introduced in this class.

Elevator




- **Input:** Size of the elevator and two Radius: R_1 , R_2 .
- **Output:** Do the two circles fit in the elevator? Y/N?
- **Hint:** The code is very simple, solve this program on paper first.

Colorful Flowers




- **Input:** Three sides of blue triangle
- **Output:** Area of Yellow Zone, Blue Zone and Red Zone
- **Hint:** Practice the code for incircle and circumcircle!

Trash Removal



- What is the smallest trash box that can fit the polygon (trash)
- **Input:** Vertices of the polygon
- **Output:** Size of the smallest trash that fits the polygon
- **Hint:** It might help to think of the convex version of the polygon

Board Wrapping



- Convex Hull problem;
- Don't forget to rotate the rectangles correctly during input!

About these Slides

These slides were made by Claus Aranha, 2021. You are welcome to copy, re-use and modify this material.

Individual images in some slides might have been made by other authors. Please see the following pages for details.

Image Credits I

[Page 10] Problem image from <https://onlinejudge.org>

[Page 12] Problem image from <https://onlinejudge.org>

[Page 18] Rotation Image from "Competitive Programming 3", Steven Halim

[Page 30] Circle Properties Images from Stephen Halim "Competitive Programming 3"

[Page 45] Convex Hull image by Steven Halim "Competitive Programming 3"