



# Building long-form content on the web: Columns?

There are layouts that are only possible with columns. Thinking about IEEE and ACM paper formats.

# Brownian dynamics simulation of analytical ultracentrifugation experiments

Brownian dynamics simulation of analytical ultracentrifugation experiments

Al Díez

Departamento de Química Física,  
Facultad de Química, Universidad de  
Murcia  
Murcia, Spain

A Ortega

Departamento de Química Física,  
Facultad de Química, Universidad de  
Murcia  
Murcia, Spain

J Garcia de la Tore

Departamento de Química Física,  
Facultad de Química, Universidad de  
Murcia  
Murcia, Spain  
jgt@um.es

## ABSTRACT

**Background:** We have devised a protocol for the Brownian dynamics simulation of an analytical ultracentrifugation experiment that allows for an accurate and efficient prediction of the time-dependent concentration profiles,  $c(r, t)$  in the ultracentrifuge cell.

**Results:** Simulations are carried out for four molecules covering a wide range of the ratio of sedimentation and diffusion coefficients. The evaluation is done by extracting the molecular parameters that were initially employed in the simulation by analyzing the profiles with an independent tool, the well-proved SEDFIT software.

**Conclusions:** Our Brownian dynamics simulation procedure may be considered as an alternative to other predictors based in numerical solutions of the Lamm equation, and its efficiency could make it useful in the most relevant, inverse problem, which is that of extracting the molecular parameters from experimentally determined concentration profiles.

*The content used in this document is only for preview purpose. The original open access article can be found at <http://doi.org/10.1186/2046-1682-4-6>*

## KEYWORDS

Algorithms, Sequence alignment, Orthologous Genes, Software

### ACM Reference format:

Al Díez, A Ortega, and J Garcia de la Tore. 2018. Brownian dynamics simulation of analytical ultracentrifugation experiments. In *Proceedings of ACM Conference*, , 7 pages.  
<https://doi.org/0000001.0000001>

Authors addresses: Al Díez, Departamento de Química Física, Facultad de Química, Universidad de Murcia, Murcia, 30071Spain; A Ortega, Departamento de Química Física, Facultad de Química, Universidad de Murcia, Murcia, 30071Spain; J Garcia de la Tore, Departamento de Química Física, Facultad de Química, Universidad de Murcia, Murcia, 30071Spain.

Permission to make digital or hard copies of all or part of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. Copyrights for components of this work owned by others than the author(s) must be honored. Abstracting with credit is permitted. To copy otherwise, or republish, to post on servers or to redistribute to lists, requires prior specific permission and/or a fee. Request permissions from [permissions@acm.org](mailto:permissions@acm.org).

ACM Conference, ,

© 2018 Copyright held by the owner/author(s). Publication rights licensed to Association for Computing Machinery.

ACM ISBN 978-x-xxxx-xxxx-x/YY/MM. . . \$15.00

<https://doi.org/0000001.0000001>

## 1 BACKGROUND

Since the invention of the analytical ultracentrifuge by Svedberg, the technique of analytical ultracentrifugation (AUC) has become a classical - and, thanks to [10, 11] advances in instrumentation and analysis software, it is still a most modern - technique for the characterization of macromolecules and nanoparticles in solution. In this paper, the reader may grasp the recent importance of this field in the context of the thematic issues of other journals cite.

In the AUC, particles move under influence of a centrifugal field, caused by rotation of the sample with angular velocity  $\omega$ , which produces a centrifugal force (corrected by buoyancy)  $F_c = m\omega^2 r(1 - \bar{v}\rho)$ , where  $r$  is the instantaneous distance from the rotation axis,  $m$  is the mass of the particle ( $m = M/N_A$ ),  $M$  is the molecular weight and  $N_A$  is Avogadro's number,  $\bar{v}$  is the partial specific volume of the solute particles and  $\rho$  is the solvent density (nearly equal to the solvent density, if the solution is dilute). The velocity that the solute particles may acquire due to the centrifugal force is proportional to the centrifugal acceleration,  $v = s\omega^2 r$ , where  $s$  is the sedimentation coefficient, and modulated also by the frictional coefficient  $f$  of the particle in the viscous solvent:

$$s = \frac{v}{\omega^2 r} = \frac{m(1 - \bar{v}\rho)}{f} = \frac{M(1 - \bar{v}\rho)}{N_A f}$$

If this were the only action on the solute particles, the concentration would be purely deterministic. If  $r(t)$  is the radial position of a particle at time  $t$ , one easily finds (considering that  $v = dr/dt$ ) that the position after some time,  $\Delta t$ , would be given by

$$\ln \frac{r(t + \Delta t)}{r(t)} = s\omega^2 \Delta t$$

or

$$r(t + \Delta t) = r(t) \exp(s\omega^2 \Delta t)$$

Even if the initial (loading) concentration in the AUC cell is constant from the meniscus to the bottom in the cell, which are placed at distances  $r_m$  and  $r_b$ , respectively, from the axis of centrifugation will provoke some transport of the solute particles, therefore a concentration gradient will be produced. This will, in turn, generate a counterflow of solute in the direction of decreasing concentration, i.e., contrary to the centrifugal force. Macroscopically, at a point  $r$  the counterflow would be described by the first law of Fick,  $J = -D\nabla c(r, t)$ , where  $D$  is the diffusion

Figure 1:  
Example of  
a two  
column  
paper for  
ACM  
publications

# IEEE Format

## A DEFENSE AGAINST WORM ATTACKS BASED ON CROSS HONEYFARM WITH HONEY POTS

Title (use style: *paper title*)

Subtitle as needed (*paper subtitle*)

<sup>#1</sup> Pitamber Adhikari

Research Scholar (CSE), N.I.E.T. Gr. Noida,  
G.B.Nagar, UP, India  
pitamberadhikari.12@gmail.com

<sup>#2</sup> C S. Yadav

Associate Professor CSE), N.I.E.T. Gr. Noida,  
G.B.Nagar, UP, India  
cs.yadav@niet.co.in

**Abstract**—This electronic document is a “live” template. The various components of your paper [title, text, heads, etc.] are already defined on the style sheet, as illustrated by the portions given in this document. **DO NOT USE SPECIAL CHARACTERS, SYMBOLS, OR MATH IN YOUR TITLE OR ABSTRACT.** (*Abstract*)

**Index Terms**—Component, formatting, style, styling, insert. (*key words*)

### I. INTRODUCTION (*HEADING 1*)

All manuscripts must be in English. These guidelines include complete descriptions of the fonts, spacing, and related information for producing your proceedings manuscripts. Please follow them and if you have any questions, direct them to the production editor in charge of your proceedings (see author-kit message for contact info).

This template provides authors with most of the formatting specifications needed for preparing electronic versions of their papers. All standard paper components have been specified for three reasons: (1) ease of use when formatting individual papers, (2) automatic compliance to electronic requirements that facilitate the concurrent or later production of electronic products, and (3) conformity of style throughout a conference proceedings. Margins, column widths, line spacing, and type styles are built-in; examples of the type styles are provided throughout this document and are identified in italic type, within parentheses, following the example. PLEASE DO NOT

RE-ADJUST THESE MARGINS. Some components, such as multi-leveled equations, graphics, and tables are not prescribed, although the various table text styles are provided. The formatter will need to create these components, incorporating the applicable criteria that follow.

### II. TYPE STYLE AND FONTS

Wherever Times is specified, Times Roman or Times New Roman may be used. If neither is available on your word processor, please use the font closest in appearance to Times. Avoid using bit-mapped fonts. True Type 1 or Open Type fonts are required. Please embed all fonts, in particular symbol fonts as well, for math, etc.

### III. EASE OF USE

The template is used to format your paper and style the text. All margins, column widths, line spaces, and text fonts are prescribed; please do not alter them. You may note certain peculiarities. For example, the head margin in this template measures proportionately more than is customary. These measurements and others are deliberate, using specifications that anticipate your paper as one part of the entire proceedings, and not as an independent document. Please do not revise any of the current designations.

### IV. PREPARE YOUR PAPER BEFORE STYLING

Before you begin to format your paper, first write and save the content as a separate text file. Keep your text and graphics

Figure 2:  
Example of  
a paper  
formatted  
for IEEE  
publication

The biggest difference is that the paper formats are paginated so it's relatively easier to shift from one column to another and from page to page. Because the web is one continuous format, reading columns becomes much harder since we have to scroll to get to the bottom of one column and then scroll to the top to start the next one.

If we have small blocks of text then it would be easy to use common column markup like this:

```
.columns-block {  
  columns: 2;  
  gap: 4em;  
}
```

the `columns` selector tells the browser how many columns to create. We can also specify a width like `300px` and the browser will try to fit as many columns of that width in the available space.

Controlling the height of the columns is more complex since we don't know how high the text will be and controlling overflow can also be troublesome since there's no way to make overflowing content flow into a different portion of the page.

Fragmentation would help solve the issue by providing ways for the text to flow from one block to another, just as if the layout was paginated but, as far as I know, there are no fragmentation layouts that work to handle flowing text into multiple areas of the same page in any modern browser. Right now the only fragmentation layout deals with breaks in pages and columns. While there are provisions for breaks in regions, there is no implementation of CSS regions in any modern browser.

Both [CSS Regions](#) and [CSS Exclusions](#) haven't been updated in over five years so there's good reason to think that the specifications are no longer in active development.