



# The `:any-link` selector

The `:any-link` styles all a elements with an href attribute.

This allows us to target all links in a document, regardless of location or parents.

This is particularly useful when playing with `text-decoration-*` attributes.

Safari uses the `-webkit-` prefix for these properties so we need to duplicate work to ensure that the links display the same across browsers.

```
:any-link {  
  border: 1px solid blue;  
  color: orange;  
}  
  
/* WebKit browsers */  
:-webkit-any-link {  
  border: 1px solid blue;  
  color: orange;  
}
```

We can also add link pseudo elements like `:hover` and `:visited` to the `:any-link` selector.

```
:any-link {  
  border: 1px solid blue;  
  color: orange;  
}  
  
/* WebKit browsers */  
:-webkit-any-link {  
  border: 1px solid blue;  
  color: orange;  
}
```

In this example, the default link removes the underline altogether. We then add `text-decoration` attributes with the `:hover` pseudo classes.

```
:any-link,  
:-webkit-any-link {  
  text-decoration-line: none;  
}  
  
:any-link:hover,  
:-webkit-any-link:hover {  
  text-decoration-thickness: 2px;  
  text-decoration-color: hotpink;  
  text-decoration-style: wavy;  
  text-decoration-line: underline;  
}
```

What we can do with links hasn't changed. How we do it has.