

Owner	User Story	Tasks	Points	Hour Estimates	Status	Phase Reference	#	Hrs Left 7/19	Hrs Left 7/19	Hrs Left 7/17	Hrs Left 7/20	Hrs Left 7/22	#	Hrs Left
Devin Walton	As a user, I want the base station to expose a single endpoint that returns the active session's roster and exercise targets so that the rack screen can fetch everything it needs in one call at startup.			8	16	Completed	(New -- mirrors Phase 9 minimally, built entirely on existing Phase 1-4 models; no TrainingGroup() look/CSV this sprint)	16	10	0	0	0		
		Define "active session" lookup logic (most recent Session with ended_at null)	1	2	Completed		2	0	0	0	0	0		
		Implement GET /api/sessions/active/ returning session_id label roster/session_exercises per the m	2	4	Completed		4	0	0	0	0	0		
		Compute per-athlete has_data flag from existing completed Sets	1	2	Completed		2	2	0	0	0	0		
		Source each athlete's velocity zone / target weight from their existing Program record	1	2	Completed		2	2	0	0	0	0		
		Test & Verify	1	2	Completed		2	2	0	0	0	0		
		Document	1	2	Completed		2	2	0	0	0	0		
		Check-in	1	2	Completed		2	2	0	0	0	0		
Braydon Callendar	As a user, I want to understand exactly the API endpoints I'll actually be calling this sprint before I start my own stories, so I build against what's real instead of what I assume is there.		3	4	Completed	(Spike -- trimmed to just the endpoints this person's own stories touch)	4	0	8	0	0	0		
		Read and manually exercise (curlPostman) just the endpoints this sprint's stories depend on, again	1	2	Completed		2	0	0	0	0	0		
		Document	1	1	Completed		1	0	0	0	0	0		
		Check-in	1	1	Completed		1	0	8	0	0	0		
Carl Coleman	As a user, I want to understand exactly the API endpoints I'll actually be calling this sprint before I start my own stories, so I build against what's real instead of what I assume is there.		3	4	Completed	(Spike -- trimmed to just the endpoints this person's own stories touch)	4	4	4	4	4	0		
		Read and manually exercise (curlPostman) just the endpoints this sprint's stories depend on, again	1	2	Completed		2	2	2	2	2	0		
		Document	1	1	Completed		1	1	1	1	1	0		
		Check-in	1	1	Completed		1	1	1	1	1	0		
Derrion Young	As a user, I want to understand exactly the API endpoints I'll actually be calling this sprint before I start my own stories, so I build against what's real instead of what I assume is there.		3	4	Completed	(Spike -- trimmed to just the endpoints this person's own stories touch)	8	0	0	0	0	0		
		Read and manually exercise (curlPostman) just the endpoints this sprint's stories depend on, again	1	2	Completed		4	0	0	0	0	0		
		Document	1	1	Completed		2	0	0	0	0	0		
		Check-in	1	1	Completed		1	0	0	0	0	0		
Devin Walton, Derrion Young	As a user, I want the rack screen to boot straight into a working PWA shell -- registered to a rack, subscribed to its node, and running on the PI's own display -- so a coach doesn't have to open a browser or type a URL on game day.		14	26	Completed	(Phase 10, trimmed: device-role picker becomes a config flag; kiosk auto-launch becomes a documented manual step instead of full boot automation)	26	16	7	0	0	0		
		Set the device role via a config flag instead of building the full 3-button picker UI	1	2	Completed		2	0	0	0	0	0		
		Scaffold the installable rack-screen PWA: manifest + service worker	2	4	Completed		4	0	0	0	0	0		
		Implement the IndexedDB rep buffer	2	4	Completed		4	2	0	0	0	0		
		Wire an mqtt.js client to the linked node's rep/pulse topics per the message contract	2	4	Completed		4	2	0	0	0	0		
		Build the rack registration + "awaiting assignment" polling flow	2	4	Completed		4	4	2	0	0	0		
		Fetch GET /api/sessions/active/ once at rack assignment and store roster/exercises in state	1	2	Completed		2	2	0	0	0	0		
		Document a manual kiosk-launch step for demo day (full boot automation deferred)	1	2	Completed		2	2	2	0	0	0		
		Test & Verify	1	2	Completed		2	2	1	0	0	0		
		Document	1	1	Completed		1	1	1	0	0	0		
		Check-in	1	1	Completed		1	1	1	0	0	0		
Devin Walton	As a user, I want to run a complete set at the rack -- picking an athlete and exercise, watching reps stream in live, and having the set save automatically when it ends -- so a real workout can be captured start to finish on actual hardware.		14	30	Not started	(Phase 11, trimmed: Phase 7 multi-axis deflection & missing max entry deferred, not scheduled this sprint)	30	19	12	0	0	0		
		Build the athlete/exercise picker sourced from the active-session fetch	2	4	Completed		4	3	3	0	0	0		
		Implement the full lifecycle state machine: idle --> countdown --> active --> summary --> rest	3	8	Completed		8	4	2	0	0	0		
		Render the live rep panel (rep count, avg/peak velocity, velocity_color chip) from streamed rep mes	2	4	Completed		4	3	2	0	0	0		
		Implement the batch POST to /api/sets/dj/complete/ at set end, matching the message contract b	2	4	Completed		4	1	0	0	0	0		
		Implement false-set undo	1	2	Completed		2	1	0	0	0	0		
		Implement the rest timer	1	2	Completed		2	1	0	0	0	0		
		Test & Verify	1	2	Completed		2	2	2	0	0	0		
		Document	1	2	Completed		2	2	2	0	0	0		
		Check-in	1	2	Completed		2	2	1	0	0	0		
Braydon Callendar, Derrion Young	As a user, I want a real sensor node that computes velocity on-device and publishes reps and heartbeats over MQTT so that an actual barbell rep shows up on the rack screen without a simulator.		12	22	Completed	(Phase 13, trimmed: hardcoded WiFi/MQTT creds; less exploration time on the velocity loop; noise-reduction hook folded into another task instead of its own line)	22	17	8	0	0	0		
		Connect the ESP32 to the PI's AP and MQTT broker, using hardcoded creds for now	1	2	Completed		2	0	0	0	0	0		
		Read the MPU-6050 accelerometer in a loop and integrate single-axis vertical velocity	3	6	Completed		6	3	0	0	0	0		
		Implement 0.75s stillness rep-boundary detection (leave a one-line noise-reduction-hook comment	2	4	Completed		4	4	2	0	0	0		



