Summary

Run summarize.bat to update this file.

Last Updated: 2026-05-30

Author: HuangZy

[TOC]

DataStructure

FHQ-Treap.cpp

```cpp
#define DEBUG 1
#define FUCK cout << "fuck" << endl;
#if DEBUG
    #include "all.hpp"
#else
    #include <bits/stdc++.h>
#endif

using namespace std;
using ll = long long;
using pii = pair<int,int>;
using pll = pair<ll,ll>;
using db = long double;
using pdd = pair<db, db>;
using i128 = __int128_t;

const ll N = 2000000;
const ll INF = 5e18;
const ll MOD = 1e9 + 7;

/*
关于 FHQ-Treap 的易错点
注意懒标记的作用顺序
注意 unite 之后需要重新指定 rt 的值
*/

/*
以下是文艺平衡树模版，功能是对区间进行若干次翻转，最终输出反转后结果
这是根据 siz 进行反转的示例
大概的思想是把 1-(l-1) 的部分切开，然后切 l - r 的，然后懒标记
*/
struct FHQ_Treap {
    int ch[N][2], val[N], siz[N], rnd[N];
    bool tag[N];
    int tot, rt;
```

```
    FHQ_Treap() {
        tot = 0;
        rt = 0;
        memset(ch, 0, sizeof ch);
        memset(siz, 0, sizeof siz);
        memset(tag, 0, sizeof tag);
        srand((unsigned)time(NULL));
    }

    int New(int v) {
        ++tot;
        val[tot] = v;
        siz[tot] = 1;
        rnd[tot] = rand();
        tag[tot] = false;
        ch[tot][0] = ch[tot][1] = 0;
        return tot;
    }

    void push_up(int u) {
        siz[u] = siz[ch[u][0]] + siz[ch[u][1]] + 1;
    }

    void push_down(int u) {
        if (!u || !tag[u]) return;
        tag[u] = false;
        swap(ch[u][0], ch[u][1]);
        if (ch[u][0]) tag[ch[u][0]] ^= 1;
        if (ch[u][1]) tag[ch[u][1]] ^= 1;
    }

    void split(int u, int k, int &x, int &y) {
        if (!u) { x = y = 0; return; }
        push_down(u);
        if (siz[ch[u][0]] < k) {
            x = u;
            split(ch[u][1], k - siz[ch[u][0]] - 1, ch[u][1], y);
        } else {
            y = u;
            split(ch[u][0], k, x, ch[u][0]);
        }
        push_up(u);
    }

    int unite(int x, int y) {
        if (!x || !y) return x + y;
        if (rnd[x] < rnd[y]) {
            push_down(x);
            ch[x][1] = unite(ch[x][1], y);
            push_up(x);
            return x;
        } else {
            push_down(y);
            ch[y][0] = unite(x, ch[y][0]);
```

```
            push_up(y);
            return y;
        }
    }

    void insert(int v) {
        int a, b;
        split(rt, v, a, b);
        rt = unite(unite(a, New(v)), b);
    }

    void reverse(int l, int r) {
        int a, b, c;
        split(rt, l - 1, a, b);
        split(b, r - l + 1, b, c);
        tag[b] ^= 1;
        rt = unite(a, unite(b, c));
    }

    void dfs(int u) {
        if (!u) return;
        if (tag[u]) push_down(u);
        dfs(ch[u][0]);
        printf("%d ", val[u]);
        dfs(ch[u][1]);
    }

    void print() { dfs(rt); }
} solver;

/*
这个是按照值域分解的版本，同时具有给指定值域的数加上一定值的功能
*/

struct FHQ_Treap {
    int ch[N][2], rnd[N], idx[N];
    int tot, rt;
    ll val[N], laz[N];

    FHQ_Treap() {
        tot = 0;
        rt = 0;
        memset(ch, 0, sizeof ch);
        memset(laz, 0, sizeof laz);
        srand((unsigned)time(NULL));
    }

    void init() {
        tot = rt = 0;
    }

    int New(int v, int id) {
        ++tot;
        val[tot] = v;
```

```
        rnd[tot] = rand();
        laz[tot] = 0;
        idx[tot] = id;
        ch[tot][0] = ch[tot][1] = 0;
        return tot;
    }

    void push_down(int u) {
        if (!u || !laz[u]) return;
        for (int i = 0;i<2;i++) {
            if (!ch[u][i]) continue;
            val[ch[u][i]] += laz[u];
            laz[ch[u][i]] += laz[u];
        }
        laz[u] = 0;
    }

    void split(int u, ll k, int &x, int &y) {
        if (!u) { x = y = 0; return; }
        push_down(u);
        if (val[u] <= k) {
            x = u;
            split(ch[u][1], k, ch[u][1], y);
        } else {
            y = u;
            split(ch[u][0], k, x, ch[u][0]);
        }
    }

    int unite(int x, int y) {
        if (!x || !y) return x + y;
        if (rnd[x] < rnd[y]) {
            push_down(x);
            ch[x][1] = unite(ch[x][1], y);
            return x;
        } else {
            push_down(y);
            ch[y][0] = unite(x, ch[y][0]);
            return y;
        }
    }

    void insert(int v, int id) {
        int a, b;
        split(rt, v, a, b);
        rt = unite(unite(a, New(v, id)), b);
    }

    void add(ll x) {
        int a, b;
        split(rt, x - 1, a, b);
        if (b) {
            val[b] += x;
            laz[b] += x;
```

```
        }
        rt = unite(a, b);
    }
} solver;"\n"
```

KD-Tree.cpp

```cpp
#define DEBUG 1
#define FUCK cout << "fuck" << endl;
#if DEBUG
    #include "all.hpp"
#else
    #include <bits/stdc++.h>
#endif

using namespace std;
using ll = long long;
using pii = pair<int,int>;
using pll = pair<ll,ll>;
using db = long double;
using pdd = pair<db, db>;
using i128 = __int128_t;

const ll N = 2000000;
const ll INF = 5e18;
const ll MOD = 1e9 + 7;

// kd-tree, 好人类智慧。。。
// kd-tree, 好好写。。。
// 我就不信 xcpc 有人敢出 kd-tree

/*
二进制分组优化的 2D-Tree
二进制优化分组是为了保持在线情形的复杂度
不需要在线维护就直接一颗树就行了
注意， nodes[0] 是哨兵节点不要用！！！
插入均摊 log^2
查询均摊 n^0.5
*/

struct KD_Tree {
    struct Node {
        int x[2];               // 坐标
        int minC[2], maxC[2];   // 子树边界矩形
        int val, sum;           // 点权值，子树总和
        int ch[2];              // 左右儿子

        void init(int _x, int _y, int _v) {
            x[0] = minC[0] = maxC[0] = _x;
            x[1] = minC[1] = maxC[1] = _y;
            val = sum = _v;
```

```
            ch[0] = ch[1] = 0;
        }
    } t[N];

    int nodeCnt = 0;
    int stk[N], tp;

    // 更新节点的统计信息
    void pushup(int p) {
        t[p].sum = t[p].val + t[t[p].ch[0]].sum + t[t[p].ch[1]].sum;
        for (int i = 0; i < 2; ++i) {
            t[p].minC[i] = t[p].maxC[i] = t[p].x[i];
            if (t[p].ch[0]) {
                t[p].minC[i] = min(t[p].minC[i], t[t[p].ch[0]].minC[i]);
                t[p].maxC[i] = max(t[p].maxC[i], t[t[p].ch[0]].maxC[i]);
            }
            if (t[p].ch[1]) {
                t[p].minC[i] = min(t[p].minC[i], t[t[p].ch[1]].minC[i]);
                t[p].maxC[i] = max(t[p].maxC[i], t[t[p].ch[1]].maxC[i]);
            }
        }
    }

    // 递归构建平衡 KD-Tree
    int build(int l, int r, int dim) {
        if (l > r) return 0;
        int mid = (l + r) >> 1;
        nth_element(stk + l, stk + mid, stk + r + 1, [&](int a, int b) {
            return t[a].x[dim] < t[b].x[dim];
        });
        int p = stk[mid];
        t[p].ch[0] = build(l, mid - 1, dim ^ 1);
        t[p].ch[1] = build(mid + 1, r, dim ^ 1);
        pushup(p);
        return p;
    }

    // 展平子树
    void flatten(int p) {
        if (!p) return;
        stk[++tp] = p;
        flatten(t[p].ch[0]);
        flatten(t[p].ch[1]);
    }

    // 核心查询逻辑
    int query(int p, int x1, int y1, int x2, int y2) {
        if (!p) return 0;
        // 1. 完全包含
        if (t[p].minC[0] >= x1 && t[p].maxC[0] <= x2 && t[p].minC[1] >= y1 &&
t[p].maxC[1] <= y2)
            return t[p].sum;
        // 2. 完全不相交
        if (t[p].minC[0] > x2 || t[p].maxC[0] < x1 || t[p].minC[1] > y2 ||
```

```
t[p].maxC[1] < y1)
            return 0;
        // 3. 部分重叠
        int res = 0;
        if (t[p].x[0] >= x1 && t[p].x[0] <= x2 && t[p].x[1] >= y1 && t[p].x[1] <=
y2)
            res += t[p].val;
        return res + query(t[p].ch[0], x1, y1, x2, y2) + query(t[p].ch[1], x1, y1,
x2, y2);
    }

    // 二进制分组管理器
    int roots[25], treeSize[25];
    void insert(int x, int y, int v) {
        int cur = ++nodeCnt;
        t[cur].init(x, y, v);

        tp = 0;
        stk[++tp] = cur;

        // 类似二进制加法：1 + 1 = 10 (进位合并)
        for (int i = 0; i < 20; ++i) {
            if (!roots[i]) {
                roots[i] = build(1, tp, 0);
                treeSize[i] = tp;
                return;
            }
            flatten(roots[i]);
            roots[i] = 0; // 清空当前层，准备合并到下一层
            treeSize[i] = 0;
        }
    }
} solver;

// 这种写法， 就很优美!!
const int M = 2;
struct KD_Tree {
    struct Node {
        ll x[M], mn[M], mx[M], ch[M], val, sum;

        void init(array<ll, M> y, ll _v) {
            for (int i = 0;i<M;i++) {
                x[i] = mn[i] = mx[i] = y[i];
            }
            val = sum = _v;
            ch[0] = ch[1] = 0;
        }
    } nodes[N];

    int nodeCnt = 0;
    int stk[N], tp;

    #define LS (nodes[rt].ch[0])
    #define RS (nodes[rt].ch[1])
```

```
// 更新节点的统计信息
void pushup(int rt) {
    nodes[rt].sum = nodes[rt].val + nodes[LS].sum + nodes[RS].sum;
    for (int i = 0; i < 2; ++i) {
        nodes[rt].mn[i] = nodes[rt].mx[i] = nodes[rt].x[i];
        if (LS) {
            nodes[rt].mn[i] = min(nodes[rt].mn[i], nodes[LS].mn[i]);
            nodes[rt].mx[i] = max(nodes[rt].mx[i], nodes[LS].mx[i]);
        }
        if (RS) {
            nodes[rt].mn[i] = min(nodes[rt].mn[i], nodes[RS].mn[i]);
            nodes[rt].mx[i] = max(nodes[rt].mx[i], nodes[RS].mx[i]);
        }
    }
}

// 递归构建平衡 KD-Tree
int build(int l, int r, int dim) {
    if (l > r) return 0;
    int mid = (l + r) >> 1;
    nth_element(stk + l, stk + mid, stk + r + 1, [&](int a, int b) {
        return nodes[a].x[dim] < nodes[b].x[dim];
    });
    int rt = stk[mid];
    nodes[rt].ch[0] = build(l, mid - 1, dim ^ 1);
    nodes[rt].ch[1] = build(mid + 1, r, dim ^ 1);
    pushup(rt);
    return rt;
}

// 展平子树
void flatten(int rt) {
    if (!rt) return;
    stk[++tp] = rt;
    flatten(nodes[rt].ch[0]);
    flatten(nodes[rt].ch[1]);
}

ll get_mn(int rt, array<ll, M> v) {
    ll res = 0;
    if (nodes[rt].mx[0] < v[0]) {
        res += v[0] - nodes[rt].mx[0];
    } else if (nodes[rt].mn[0] > v[0]) {
        res += nodes[rt].mn[0] - v[0];
    }
    if (nodes[rt].mx[1] < v[1]) {
        res += v[1] - nodes[rt].mx[1];
    } else if (nodes[rt].mn[1] > v[1]) {
        res += nodes[rt].mn[1] - v[1];
    }
    return res;
}
```

```
ll get_mx(int rt, array<ll, M> v) {
    ll res = 0;
    res += max(abs(nodes[rt].mx[0] - v[0]), abs(nodes[rt].mn[0] - v[0]));
    res += max(abs(nodes[rt].mx[1] - v[1]), abs(nodes[rt].mn[1] - v[1]));
    return res;
}

void queryMn(int rt, array<ll, M> v, ll &mn) {
    if (!rt) return;
    if (nodes[rt].x[0] == v[0] && nodes[rt].x[1] == v[1]) {

    } else {
        mn = min(mn, abs(v[0] - nodes[rt].x[0]) + abs(v[1] - nodes[rt].x[1]));
    }
    ll lhs = INF, rhs = INF;
    if (LS) lhs = get_mn(LS, v);
    if (RS) rhs = get_mn(RS, v);
    if (lhs > rhs) {
        if (rhs < mn) queryMn(RS, v, mn);
        if (lhs < mn) queryMn(LS, v, mn);
    } else {
        if (lhs < mn) queryMn(LS, v, mn);
        if (rhs < mn) queryMn(RS, v, mn);
    }
    return;
}

void queryMx(int rt, array<ll, M> v, ll &mx) {
    if (!rt) return;
    mx = max(mx, abs(v[0] - nodes[rt].x[0]) + abs(v[1] - nodes[rt].x[1]));
    ll lhs = -INF, rhs = -INF;
    if (LS) lhs = get_mx(LS, v);
    if (RS) rhs = get_mx(RS, v);
    if (lhs < rhs) {
        if (rhs > mx) queryMx(RS, v, mx);
        if (lhs > mx) queryMx(LS, v, mx);
    } else {
        if (lhs > mx) queryMx(LS, v, mx);
        if (rhs > mx) queryMx(RS, v, mx);
    }
}

// 核心查询逻辑
ll query(array<ll, M> v) {
    ll mn = INF, mx = -INF;
    queryMn(roots[0], v, mn);
    queryMx(roots[0], v, mx);
    return mx - mn;
}

// 二进制分组管理器
int roots[25], treeSize[25];
void insert(array<ll, M> y, ll v) {
    int cur = ++nodeCnt;
```

```
        nodes[cur].init(y, v);

        tp = 0;
        stk[++tp] = cur;

        // 类似二进制加法：1 + 1 = 10 (进位合并)
        for (int i = 0; i < 20; ++i) {
            if (!roots[i]) {
                roots[i] = build(1, tp, 0);
                treeSize[i] = tp;
                return;
            }
            flatten(roots[i]);
            roots[i] = 0; // 清空当前层，准备合并到下一层
            treeSize[i] = 0;
        }
    }
} solver;"\n"
```

Link-Cut-Tree.cpp

```
#define DEBUG 1
#define FUCK cout << "fuck" << endl;
#if DEBUG
    #include "all.hpp"
#else
    #include <bits/stdc++.h>
#endif

using namespace std;
using ll = long long;
using pii = pair<int,int>;
using pll = pair<ll,ll>;
using db = long double;
using pdd = pair<db, db>;
using i128 = __int128_t;

const ll N = 2000000;
const ll INF = 5e18;
const ll MOD = 51061;

/*
通俗 LCT 模版
*/
struct LCT {
    int n;
    int f[N], st[N];
    array<int, 2> c[N];
    char rev[N];

    void init(int n_) {
```

```
        n = n_;
        for (int i = 1;i<=n;i++) {
            f[i] = st[i] = c[i][0] = c[i][1] = 0;
            rev[i] = 0;
        }
    }

    bool nroot(int x) {
        int fa = f[x];
        return c[fa][0] == x || c[fa][1] == x;
    }

    void pushup(int x) {
        // 维护路径信息的核心操作
    }

    void pushr(int x) {
        swap(c[x][0], c[x][1]);
        rev[x] ^= 1;
    }

    void pushdown(int x) {
        if (rev[x]) {
            if (c[x][0]) {
                pushr(c[x][0]);
            }
            if (c[x][1]) {
                pushr(c[x][1]);
            }
            rev[x] = 0;
        }
    }

    void rotate(int x) {
        int y = f[x];
        int z = f[y];
        int k = (c[y][1] == x);
        int w = c[x][!k];

        if (nroot(y)) {
            if (c[z][1] == y) {
                c[z][1] = x;
            } else {
                c[z][0] = x;
            }
        }

        c[x][!k] = y;
        c[y][k] = w;

        if (w) {
            f[w] = y;
        }
```

```
    f[y] = x;
    f[x] = z;

    pushup(y);
}

void splay(int x) {
    int y = x;
    int top = 0;
    st[++top] = y;
    while (nroot(y)) {
        y = f[y];
        st[++top] = y;
    }
    while (top) {
        pushdown(st[top--]);
    }
    while (nroot(x)) {
        y = f[x];
        int z = f[y];
        bool zigzag = (c[y][0] == x) ^ (c[z][0] == y);
        if (nroot(y)) {
            if (zigzag) {
                rotate(x);
            } else {
                rotate(y);
            }
        }
        rotate(x);
    }
    pushup(x);
}

void access(int x) {
    int y = 0;
    while (x) {
        splay(x);
        c[x][1] = y;
        pushup(x);
        y = x;
        x = f[x];
    }
}

void makeroot(int x) {
    access(x);
    splay(x);
    pushr(x);
}

int findroot(int x) {
    access(x);
    splay(x);
    while (c[x][0]) {
```

```
            pushdown(x);
            x = c[x][0];
        }
        splay(x);
        return x;
    }

    void split(int x, int y) {
        makeroot(x);
        access(y);
        splay(y);
    }

    void link(int x, int y) {
        makeroot(x);
        if (findroot(y) != x) {
            f[x] = y;
        }
    }

    void cut(int x, int y) {
        makeroot(x);
        if (findroot(y) == x && f[y] == x && c[y][0] == 0) {
            f[y] = 0;
            c[x][1] = 0;
            pushup(x);
        }
    }

    void setval(int x, ll v) {
        splay(x);
        // sum[x] = val[x] = v;
        pushup(x);
    }

    int query(int x, int y) {
        split(x, y);
        // return sum[y];
    }
} solver;

/*
维护子树信息特供版

*/
struct LCT {
    int n;
    int f[N], st[N];
    array<int, 2> c[N];
    char rev[N];

    int s[N], si[N];

    bool nroot(int x) {
```

```
    int fa = f[x];
    return c[fa][0] == x || c[fa][1] == x;
}

void pushup(int x) {
    // 维护路径信息的核心操作
    // 下面是维护两种常见信息 示例
    s[x] = s[c[x][0]] + s[c[x][1]] + si[x] + 1;
    // s[x] = s[c[x][0]] + s[c[x][1]] + si[x] + v[x];
}

void pushr(int x) {
    swap(c[x][0], c[x][1]);
    rev[x] ^= 1;
}

void pushdown(int x) {
    if (rev[x]) {
        if (c[x][0]) {
            pushr(c[x][0]);
        }
        if (c[x][1]) {
            pushr(c[x][1]);
        }
        rev[x] = 0;
    }
}

void rotate(int x) {
    int y = f[x];
    int z = f[y];
    int k = (c[y][1] == x);
    int w = c[x][!k];

    if (nroot(y)) {
        if (c[z][1] == y) {
            c[z][1] = x;
        } else {
            c[z][0] = x;
        }
    }

    c[x][!k] = y;
    c[y][k] = w;

    if (w) {
        f[w] = y;
    }

    f[y] = x;
    f[x] = z;

    pushup(y);
}
```

```
void splay(int x) {
    int y = x;
    int top = 0;
    st[++top] = y;
    while (nroot(y)) {
        y = f[y];
        st[++top] = y;
    }
    while (top) {
        pushdown(st[top--]);
    }
    while (nroot(x)) {
        y = f[x];
        int z = f[y];
        bool zigzag = (c[y][0] == x) ^ (c[z][0] == y);
        if (nroot(y)) {
            if (zigzag) {
                rotate(x);
            } else {
                rotate(y);
            }
        }
        rotate(x);
    }
    pushup(x);
}

void access(int x) {
    for (int y = 0; x; y = x, x = f[x]) {
        splay(x);
        si[x] += s[c[x][1]];
        si[x] -= s[c[x][1] = y];
        pushup(x);
    }
}

void makeroot(int x) {
    access(x);
    splay(x);
    pushr(x);
}

int findroot(int x) {
    access(x);
    splay(x);
    while (c[x][0]) {
        pushdown(x);
        x = c[x][0];
    }
    splay(x);
    return x;
}
```

```
    void split(int x, int y) {
        makeroot(x);
        access(y);
        splay(y);
    }

    void link(int x, int y) {
        makeroot(x);
        if (findroot(y) != x) {
            makeroot(y);
            f[x] = y;
            si[y] += s[x];
            pushup(y);
        }
    }

    void cut(int x, int y) {
        makeroot(x);
        if (findroot(y) == x && f[y] == x && c[y][0] == 0) {
            f[y] = 0;
            c[x][1] = 0;
            pushup(x);
        }
    }
} solver;

/*
这个 LCT 实现区间加乘
*/
struct LCT {
    int n;
    int f[N], val[N], st[N];
    array<int, 2> c[N];
    char rev[N];
    ll sum[N], sz[N], a[N], lp[N], lm[N];

    void init(int n_) {
        n = n_;
        for (int i = 1;i<=n;i++) {
            lp[i] = 0;
            lm[i] = 1;
            sum[i] = sz[i] = a[i] = 0;
            f[i] = val[i] = st[i] = c[i][0] = c[i][1] = 0;
            rev[i] = 0;
        }
    }

    bool nroot(int x) {
        int fa = f[x];
        return c[fa][0] == x || c[fa][1] == x;
    }

    void pushup(int x) {
        // 维护路径信息的核心操作
```

```
        sum[x] = (sum[c[x][0]] + sum[c[x][1]] + a[x]) % MOD;
        sz[x] = (sz[c[x][0]] + sz[c[x][1]] + 1) % MOD;
    }

    void pushr(int x) {
        swap(c[x][0], c[x][1]);
        rev[x] ^= 1;
    }

    void pushm(int x, ll c) {
        sum[x] = sum[x] * c % MOD;
        a[x] = a[x] * c % MOD;
        lm[x] = lm[x] * c % MOD;
        lp[x] = lp[x] * c % MOD;
    }

    void pusha(int x, ll c) {
        sum[x] = (sum[x] + sz[x] * c % MOD) % MOD;
        a[x] = (a[x] + c) % MOD;
        lp[x] = (lp[x] + c) % MOD;
    }

    void pushdown(int x) {
        if (lm[x] != 1) {
            pushm(c[x][0], lm[x]);
            pushm(c[x][1], lm[x]);
            lm[x] = 1;
        }
        if (lp[x]) {
            pusha(c[x][0], lp[x]);
            pusha(c[x][1], lp[x]);
            lp[x] = 0;
        }
        if (rev[x]) {
            if (c[x][0]) {
                pushr(c[x][0]);
            }
            if (c[x][1]) {
                pushr(c[x][1]);
            }
            rev[x] = 0;
        }
    }

    void rotate(int x) {
        int y = f[x];
        int z = f[y];
        int k = (c[y][1] == x);
        int w = c[x][!k];

        if (nroot(y)) {
            if (c[z][1] == y) {
                c[z][1] = x;
            } else {
```

```
                c[z][0] = x;
            }
        }

        c[x][!k] = y;
        c[y][k] = w;

        if (w) {
            f[w] = y;
        }

        f[y] = x;
        f[x] = z;

        pushup(y);
    }

    void splay(int x) {
        int y = x;
        int top = 0;
        st[++top] = y;
        while (nroot(y)) {
            y = f[y];
            st[++top] = y;
        }
        while (top) {
            pushdown(st[top--]);
        }
        while (nroot(x)) {
            y = f[x];
            int z = f[y];
            bool zigzag = (c[y][0] == x) ^ (c[z][0] == y);
            if (nroot(y)) {
                if (zigzag) {
                    rotate(x);
                } else {
                    rotate(y);
                }
            }
            rotate(x);
        }
        pushup(x);
    }

    void access(int x) {
        int y = 0;
        while (x) {
            splay(x);
            c[x][1] = y;
            pushup(x);
            y = x;
            x = f[x];
        }
    }
```

```
void makeroot(int x) {
    access(x);
    splay(x);
    pushr(x);
}

int findroot(int x) {
    access(x);
    splay(x);
    while (c[x][0]) {
        pushdown(x);
        x = c[x][0];
    }
    splay(x);
    return x;
}

void split(int x, int y) {
    makeroot(x);
    access(y);
    splay(y);
}

void link(int x, int y) {
    makeroot(x);
    if (findroot(y) != x) {
        f[x] = y;
    }
}

void cut(int x, int y) {
    makeroot(x);
    if (findroot(y) == x && f[y] == x && c[y][0] == 0) {
        f[y] = 0;
        c[x][1] = 0;
        pushup(x);
    }
}

void pls(int x, int y, ll v) {
    split(x, y);
    pusha(y, v);
}

void mul(int x, int y, ll v) {
    split(x, y);
    pushm(y, v);
}

void setval(int x, ll v) {
    splay(x);
    sum[x] = val[x] = v;
    pushup(x);
```

```
    }

    int query(int x, int y) {
        split(x, y);
        return sum[y];
    }
} solver;"\n"
```

ST表.cpp

```
#include <bits/stdc++.h>
using namespace std;
#define DEBUG 1
#define FUCK if (DEBUG) cout << "fuck" << endl;
using ll = long long;
using pii = pair<int,int>;
using i128 = __int128_t;
using pll = pair<ll,ll>;
const ll N = 2000000;
const ll INF = 1e18;
const ll MOD = 1e9 + 7;

/*
使用前记得 init
*/
namespace ST {
    int lg[N];
    void init(int n) {
        lg[0] = 0, lg[1] = 0;
        for (int i = 2;i<=n;i++) {
            lg[i] = lg[i / 2] + 1;
        }
    }
    struct ST {
        struct Info {
            ll val;
            Info() {
                val = INF;
            }
            Info operator+(const Info& A) const {
                Info z;
                z.val = min(val, A.val);
                return z;
            }
        };
        vector<vector<Info>> f;
        void init(const vector<ll>& a) {
            int n = (int)a.size();
            if (n == 0) return;
            for (int i = 2; i <= n; ++i) lg[i] = lg[i >> 1] + 1;
            int K = lg[n];
```

```
            f.assign(K + 1, vector<Info>(n));
            for (int i = 0; i < n; ++i) f[0][i].val = a[i];
            for (int k = 1; k <= K; ++k)
                for (int i = 0; i + (1 << k) <= n; ++i)
                    f[k][i] = f[k - 1][i] + f[k - 1][i + (1 << (k - 1))];
        }
        Info query(int l, int r) {
            if (l > r) return Info();
            int len = r - l + 1;
            int k = lg[len];
            return f[k][l] + f[k][r - (1 << k) + 1];
        }
    };
}"\n"
```

伸展树.cpp

```
// It's a wonderful life.
#include <bits/stdc++.h>
using namespace std;
typedef long long ll;
#define DEBUG 1
const ll N = 2000000;
const ll MOD = 998244353;
const ll MAX = 1e18;

/*
可重集合
rank 得到的是比 val 小的 Node 的数量
*/
template<typename T, typename Compare = std::less<T>>
struct Splay{
    int rt,tot;
    struct Node{
        T val;
        int cnt,fa,ch[2],siz;
    }nodes[N];

    Compare cmp;
    bool lt(const T &a, const T &b) const { return cmp(a,b); }
    bool eq(const T &a, const T &b) const { return !cmp(a,b) && !cmp(b,a); }

    int newNode(const T &x){
        ++tot;
        nodes[tot].val = x;
        nodes[tot].cnt = nodes[tot].siz = 1;
        nodes[tot].fa = nodes[tot].ch[0] = nodes[tot].ch[1] = 0;
        return tot;
    }

    void init(){
```

```
        // 初始化 nodes[0]
        nodes[0].cnt = nodes[0].siz = nodes[0].fa = nodes[0].ch[0] =
nodes[0].ch[1] = 0;
        tot = 0;
        int a = newNode(T(-INT_MAX));
        int b = newNode(T(INT_MAX));
        rt = a;
        nodes[rt].ch[1] = b;
        nodes[b].fa = rt;
        update(rt);
    }

    void update(int x){
        nodes[x].siz = nodes[nodes[x].ch[0]].siz + nodes[nodes[x].ch[1]].siz +
nodes[x].cnt;
    }

    void rot_left(int x){
        int y = nodes[x].fa,z = nodes[y].fa;
        nodes[y].ch[1] = nodes[x].ch[0]; nodes[nodes[x].ch[0]].fa = y;
        nodes[x].ch[0] = y; nodes[y].fa = x;
        nodes[z].ch[nodes[z].ch[1] == y] = x; nodes[x].fa = z;
        update(y); update(x);
    }

    void rot_right(int x){
        int y = nodes[x].fa,z = nodes[y].fa;
        nodes[y].ch[0] = nodes[x].ch[1]; nodes[nodes[x].ch[1]].fa = y;
        nodes[x].ch[1] = y; nodes[y].fa = x;
        nodes[z].ch[nodes[z].ch[1] == y] = x; nodes[x].fa = z;
        update(y); update(x);
    }

    int getlr(int x){
        return nodes[nodes[x].fa].ch[1] == x;
    }

    void rotate(int x){
        if (getlr(x)) rot_left(x); else rot_right(x);
    }

    void splay(int x,int target){
        if (!target) rt = x;
        while (nodes[x].fa != target){
            int y = nodes[x].fa, z = nodes[y].fa;
            if (z != target){
                if (getlr(x) == getlr(y)) rotate(y);
                else rotate(x);
            }
            rotate(x);
        }
    }

    void find(const T &x){
```

```
        if (!rt) return;
        int p = rt;
        while (!eq(nodes[p].val, x) && nodes[p].ch[ lt(nodes[p].val, x) ? 1 : 0 ])
{
            p = nodes[p].ch[ lt(nodes[p].val, x) ? 1 : 0 ];
        }
        splay(p,0);
    }

    int pre(const T &x){
        find(x);
        if (lt(nodes[rt].val, x)) return rt;
        int p = nodes[rt].ch[0];
        while (nodes[p].ch[1]) p = nodes[p].ch[1];
        splay(p,0);
        return p;
    }

    int suc(const T &x){
        find(x);
        if (lt(x, nodes[rt].val)) return rt;
        int p = nodes[rt].ch[1];
        while (nodes[p].ch[0]) p = nodes[p].ch[0];
        splay(p,0);
        return p;
    }

    void insert(const T &x){
        int p = rt, fp = 0;
        while (p && !eq(nodes[p].val, x)){
            fp = p; p = nodes[p].ch[ lt(nodes[p].val, x) ? 1 : 0 ];
        }
        if (!p){
            p = newNode(x);
            nodes[fp].ch[ lt(nodes[fp].val, x) ? 1 : 0 ] = p;
            nodes[p].fa = fp;
        }else{
            nodes[p].cnt++;
        }
        splay(p,0);
    }

    void del(const T &x){
        int xPre = pre(x), xSuc = suc(x);
        splay(xPre,0); splay(xSuc,xPre);
        int d = nodes[xSuc].ch[0];
        if (--nodes[d].cnt){
            splay(d,0);
        }else{
            nodes[xSuc].ch[0] = 0;
            update(xSuc); update(xPre);
        }
    }
```

```
    int kth(long long x){
        int p = rt;
        while (1){
            int v = nodes[p].ch[0];
            if (nodes[v].siz + nodes[p].cnt < x){
                x -= nodes[v].siz + nodes[p].cnt;
                p = nodes[p].ch[1];
            }else{
                if (nodes[v].siz < x){
                    splay(p,0);
                    return p;
                }else p = v;
            }
        }
    }

    int getRank(const T &x){
        find(x);
        return nodes[nodes[rt].ch[0]].siz;
    }
};

struct Node {
    ll val;
    Node(ll VAL_ = 0) {val = VAL_;}
    bool operator<(const Node& A) const {
        return val < A.val;
    }
};
Splay<Node> solver;

void solve(){
    int n,m;cin >> n >> m;
    solver.init();
    for (int i = 1;i<n+1;i++){
        int x;cin >> x;solver.insert(x);
    }
    int last = 0,ans = 0;
    while (m--){
        int opt,x;cin >> opt >> x;
        x ^= last;
        if (opt == 1){
            solver.insert(x);
        }else if (opt == 2){
            solver.del(x);
        }else if (opt == 3){
            solver.insert(x);
            last = solver.getRank(x);
            solver.del(x);
        }else if (opt == 4){
            last = solver.nodes[solver.kth(x+1)].val.val;
        }else if (opt == 5){
            last = solver.nodes[solver.pre(x)].val.val;
        }else{
```

```
            last = solver.nodes[solver.suc(x)].val.val;
        }
        if (opt > 2){
            ans ^= last;
        }
    }

    cout << ans;
    return;
}

signed main(){
    freopen("input.txt","r",stdin);
    ios::sync_with_stdio(0),cin.tie(0),cout.tie(0);
    int _ = 1;
    // cin >> _;
    while (_--){
        solve();
    }
    return 0;
}"\n"
```

左偏树.cpp

```
#include <bits/stdc++.h>
using namespace std;
typedef long long ll;
const ll N = 2000000;
class LeftLeaningHeap{
public:
    #define ls(x) nodes[x].ls
    #define rs(x) nodes[x].rs
    struct Node{
        int fa,dist,ls,rs,val,laz;
        bool operator<(const Node& A) const{
            return val > A.val;
        }
    } nodes[N];

    LeftLeaningHeap(){
        nodes[0].dist = -1;
    }

    int find(int x){
        if (x == nodes[x].fa){
            return x;
        }
        return nodes[x].fa = find(nodes[x].fa);
    }

    void pushUp(int x){
```

```
        nodes[x].dist = nodes[ls(x)].dist + 1;
        nodes[ls(x)].fa = nodes[rs(x)].fa = x;
    }

    int merge(int x,int y) {
        if (!x || !y) return x | y;

        if (nodes[x] < nodes[y]) {
            swap(x,y);
        }

        nodes[x].rs = merge(nodes[x].rs,y);
        if (nodes[ls(x)].dist < nodes[rs(x)].dist){
            swap(ls(x),rs(x));
        }

        pushUp(x);
        return x;
    }

    void erase(int x){
        nodes[x].fa = nodes[ls(x)].fa = nodes[rs(x)].fa = merge(ls(x),rs(x));
        nodes[x].dist = nodes[x].ls = nodes[x].rs = 0;
    }
};"\n"
```

并查集.cpp

```
#include <bits/stdc++.h>
using namespace std;
typedef long long ll;
const ll N = 2000000;

struct Dsu{
    int fa[N];
    void init(int n){
        for (int i = 1;i<n+1;i++){
            fa[i] = i;
        }
    }
    int find(int x){
        if (x == fa[x]){
            return x;
        }
        return fa[x] = find(fa[x]);
    }
    void merge(int x,int y){
        x = find(x),y = find(y);
        if (x == y){
            return;
        }
```

```
        fa[x] = y;
        return;
    }
};

struct dsu {
    struct edge {
        int x, y, sx;
        bool ok;
    };

    static const int N = 2000005;

    int fa[N], sz[N], top;
    edge st[N];

    void init(int n) {
        top = 0;
        for (int i = 1; i <= n; i++) {
            fa[i] = i;
            sz[i] = 1;
        }
    }

    int find(int x) {
        while (x != fa[x]) x = fa[x];
        return x;
    }

    bool merge(int u, int v) {
        int x = find(u), y = find(v);

        if (x == y) {
            st[++top] = {x, y, sz[x], false};
            return false;
        }

        if (sz[x] < sz[y]) swap(x, y);

        st[++top] = {x, y, sz[x], true};

        fa[y] = x;
        sz[x] += sz[y];

        return true;
    }

    void back() {
        edge e = st[top--];

        if (!e.ok) return;

        fa[e.y] = e.y;
        sz[e.x] = e.sx;
```

```
    }
};"\n"
```

李超树.cpp

```
#include <bits/stdc++.h>
using namespace std;
using ll = long long;
const ll INF = 1e18;
/*
查最小值就把整棵树按照 x 轴翻转
先用 init 函数初始化
注意空间开到 4 倍!!!

使用方法是先 add 再 update
*/
struct LiChaoTree {
    typedef pair<double, int> pdi;

    const double eps = 1e-9;
    const double NINF = -1e18;
    int cmp(double x, double y) {
        if (x - y > eps) return 1;
        if (y - x > eps) return -1;
        return 0;
    }

    struct line {
        double k, b;
    } p[100005];

    int s[160005];
    int cnt;

    void init(int x) {
        cnt = 0;
        p[0].k = 0; p[0].b = NINF;
        fill(s, s + x * 4 + 10, 0);
    }


    double calc(int id, int d) { return p[id].b + p[id].k * d; }

    void add(int x0, int y0, int x1, int y1) {
        cnt++;
        if (x0 == x1)  // 特判直线斜率不存在的情况
            p[cnt].k = 0, p[cnt].b = max(y0, y1);
        else
            p[cnt].k = double(1) * (y1 - y0) / (x1 - x0), p[cnt].b = y0 - p[cnt].k
* x0;
    }
```

```
    void upd(int root, int cl, int cr, int u) {  // 对线段完全覆盖到的区间进行修改
        int &v = s[root], mid = (cl + cr) >> 1;
        int bmid = cmp(calc(u, mid), calc(v, mid));
        if (bmid == 1 || (!bmid && u < v)) swap(u, v);
        int bl = cmp(calc(u, cl), calc(v, cl)), br = cmp(calc(u, cr), calc(v,
cr));
        if (bl == 1 || (!bl && u < v)) upd(root << 1, cl, mid, u);
        if (br == 1 || (!br && u < v)) upd(root << 1 | 1, mid + 1, cr, u);
    }

    void update(int root, int cl, int cr, int l, int r,
                int u) {  // 定位插入线段完全覆盖到的区间
        if (l <= cl && cr <= r) {
            upd(root, cl, cr, u);
            return;
        }
        int mid = (cl + cr) >> 1;
        if (l <= mid) update(root << 1, cl, mid, l, r, u);
        if (mid < r) update(root << 1 | 1, mid + 1, cr, l, r, u);
    }

    pdi pmax(pdi x, pdi y) {  // pair max函数
        if (cmp(x.first, y.first) == -1)
            return y;
        else if (cmp(x.first, y.first) == 1)
            return x;
        else
            return x.second < y.second ? x : y;
    }

    pdi query(int root, int l, int r, int d) {  // 查询
        if (r < d || d < l) return {0, 0};
        int mid = (l + r) >> 1;
        double res = calc(s[root], d);
        if (l == r) return {res, s[root]};
        return pmax({res, s[root]}, pmax(query(root << 1, l, mid, d),
                            query(root << 1 | 1, mid + 1, r, d)));
    }
};

/*
当插入的线段 k 和 b 都为整数时,使用这个版本可以提高精度.

直接 addLine(k,b) 插入, query(x) 查询.
*/
struct LiChao {
    struct Line { ll m, b; };
    struct Node { Line ln; Node *l, *r;
        Node(Line v):ln(v),l(nullptr),r(nullptr){}
    };
    ll L, R;
    Node *root;
    LiChao(ll _L, ll _R):L(_L),R(_R),root(nullptr){}
```

```
    ll eval(const Line &ln, ll x) {
        return ln.m*x + ln.b;
    }

    void addLine(Line nw, Node *&nd, ll l, ll r) {
        if (!nd) { nd = new Node(nw); return; }
        ll m = (l + r) >> 1;
        bool lef = eval(nw, l) < eval(nd->ln, l);
        bool mid = eval(nw, m) < eval(nd->ln, m);
        if (mid) swap(nw, nd->ln);
        if (r - l == 0) return;
        if (lef != mid) addLine(nw, nd->l, l, m);
        else addLine(nw, nd->r, m+1, r);
    }

    void addLine(ll m, ll b) {
        addLine({m, b}, root, L, R);
    }

    ll query(ll x, Node *nd, ll l, ll r) {
        if (!nd) return INF;
        ll res = eval(nd->ln, x);
        if (l==r) return res;
        ll m = (l + r) >> 1;
        if (x <= m) return min(res, query(x, nd->l, l, m));
        else return min(res, query(x, nd->r, m+1, r));
    }

    ll query(ll x) {
        return query(x, root, L, R);
    }
};

/*
应对 db 的版本
init 函数中给出定义域即可
long double 比 double 慢得多, 慎用!!!
*/

using db = double;
const db INF_LD = numeric_limits<db>::infinity();

struct LiChao {
    struct Line { db m, b; };
    struct Node { Line ln; Node *l, *r; Node(Line v):ln(v),l(nullptr),r(nullptr){}
};
    db L, R;
    Node *root;
    int maxDepth;
    LiChao(db _L = 0, db _R = 0, int _maxDepth =
50):L(_L),R(_R),root(nullptr),maxDepth(_maxDepth){}
    inline db eval(const Line &ln, db x) const { return ln.m * x + ln.b; }
    void addLine(Line nw, Node *&nd, db l, db r, int depth) {
```

```
        if (!nd) { nd = new Node(nw); return; }
        db m = (l + r) / 2;
        bool lef = eval(nw, l) < eval(nd->ln, l);
        bool mid = eval(nw, m) < eval(nd->ln, m);
        if (mid) swap(nw, nd->ln);
        if (depth == 0) return;
        if (lef != mid) addLine(nw, nd->l, l, m, depth-1);
        else addLine(nw, nd->r, m, r, depth-1);
    }
    void addLine(db m, db b) { addLine({m,b}, root, L, R, maxDepth); }
    db query(db x, Node *nd, db l, db r, int depth) const {
        if (!nd) return INF_LD;
        db res = eval(nd->ln, x);
        if (depth == 0) return res;
        db mid = (l + r) / 2;
        if (x <= mid) return min(res, query(x, nd->l, l, mid, depth-1));
        else return min(res, query(x, nd->r, mid, r, depth-1));
    }
    db query(db x) const { return query(x, root, L, R, maxDepth); }
    void init(db _L, db _R, int _maxDepth = 50) {
        L = _L;
        R = _R;
        maxDepth = _maxDepth;
        root = nullptr;
    }
};"\n"
```

树上启发式合并.cpp

```
#include <bits/stdc++.h>
using namespace std;
#define DEBUG 1
using ll = long long;
using pii = pair<int,int>;
using i128 = __int128_t;
using pll = pair<ll,ll>;
const ll N = 2000000;
const ll INF = 5e18;
const ll MOD = 1e9 + 7;

struct DsuOnTree {
    vector<vector<int>> g;
    int n,cntDfn;
    vector<int> dfn,L,R,son,siz;
    // 先填充 g
    void init() {
        cntDfn = 0;
        dfn.resize(n + 1,0);
        L.resize(n + 1,0);
        R.resize(n + 1,0);
        son.resize(n + 1,0);
```

```
        siz.resize(n + 1,0);
        g.resize(n + 1);
        return;
    }

    void dfsPre (int u,int f) {
        dfn[u] = ++cntDfn;
        L[u] = dfn[u];
        siz[u] = 1;
        for (auto v : g[u]) {
            if (v == f) continue;
            dfsPre(v,u);
            siz[u] += siz[v];
            if (!son[u] || siz[son[u]] < siz[v]) {
                son[u] = v;
            }
        }
        R[u] = cntDfn;
        return;
    };

    void add(int x) {
        return;
    }

    void del(int x) {
        return;
    }

    void dfs(int u,int f,bool keep) {
        for (auto v : g[u]) {
            if (v == f || v == son[u]) {
                continue;
            }
            dfs(v,u,0);
        }

        if (son[u]) dfs(son[u],u,1);

        for (auto v : g[u]) {
            if (v == f || v == son[u]) {
                continue;
            }
            for (int i = L[v];i<=R[v];i++) {
                // add();
            }
        }
        // add();

        if (!keep) {
            for (int i = L[u];i<=R[u];i++) {
                // del();
            }
        }
```

```
        return;
    };

};"\n"
```

树套树.cpp

```
#define DEBUG 1
#define FUCK cout << "fuck" << endl;
#if DEBUG
    #include "all.hpp"
#else
    #include <bits/stdc++.h>
#endif

using namespace std;
using ll = long long;
using pii = pair<int,int>;
using pll = pair<ll,ll>;
using db = long double;
using pdd = pair<db, db>;
using i128 = __int128_t;

const ll N = 2000000;
const ll INF = 5e18;
const ll MOD = 1e9 + 7;
const ll M = 1e8 + 10;

/*
这是一个树状数组套线段树的代码
树套树的细节还是非常多的
得写的很细很细才可以
*/

int n;
namespace TWT {
    #define ls(rt) nodes[rt].ch[0]
    #define rs(rt) nodes[rt].ch[1]
    struct Node {
        int ch[2], sum;
        Node() {
            ch[0] = ch[1] = sum = 0;
        }
    } nodes[N * 4];

    int tp, rt[N];
    void init() {
        tp = 0;
        for (int i = 1;i<n+1;i++) {
            rt[i] = 0;
        }
```

```
    }

    int New() {
        nodes[++ tp] = Node();
        return tp;
    }

    void push_up(int rt) {
        nodes[rt].sum = 0;
        if (ls(rt)) {
            nodes[rt].sum += nodes[ls(rt)].sum;
        }
        if (rs(rt)) {
            nodes[rt].sum += nodes[rs(rt)].sum;
        }
        return;
    }

    void seg_update(int& rt, int l, int r, int q, int v) {
        if (!rt) rt = New();
        if (l == r) {
            nodes[rt].sum += v;
            return;
        }
        int mid = l + r >> 1;
        if (q <= mid) seg_update(ls(rt), l, mid, q, v);
        else seg_update(rs(rt), mid + 1, r, q, v);
        push_up(rt);
        return;
    }

    int seg_query(int rt, int l, int r, int ql, int qr) {
        if (!rt) return 0;
        if (qr < l || r < ql || ql > qr) return 0;
        if (ql <= l && r <= qr) return nodes[rt].sum;
        int mid = l + r >> 1;
        return seg_query(ls(rt), l, mid, ql, qr) + seg_query(rs(rt), mid + 1, r,
ql, qr);
    }

    int lowbit(int x) { return x & -x; }

    void update(int x, int v, int c) {
        while (x <= n) {
            seg_update(rt[x], 0, M, v, c);
            x += lowbit(x);
        }
        return;
    }

    int query(int x, int k) {
        if (x == 0) return 0;
        int ans = 0;
        while (x) {
```

```
            ans += seg_query(rt[x], 0, M, 0, k - 1);
            x -= lowbit(x);
        }
        return ans;
    }

    int query(int l, int r, int k) {
        return query(r, k) - query(l - 1, k);
    }

    int L[N], R[N], tpL, tpR;
    int findK(int l, int r, int k) {
        tpL = tpR = 0;
        while (r) {
            R[tpR ++] = rt[r];
            r -= lowbit(r);
        }
        l --;
        while (l) {
            L[tpL ++] = rt[l];
            l -= lowbit(l);
        }

        l = 0, r = M;
        while (l < r) {
            int mid = l + r >> 1;
            int tot = 0;
            for (int j = 0;j<tpL;j++) {
                tot -= nodes[ls(L[j])].sum;
            }
            for (int j = 0;j<tpR;j++) {
                tot += nodes[ls(R[j])].sum;
            }
            if (tot >= k) {
                for (int j = 0;j<tpL;j++) {
                    L[j] = ls(L[j]);
                }
                for (int j = 0;j<tpR;j++) {
                    R[j] = ls(R[j]);
                }
                r = mid;
            } else {
                k -= tot;
                for (int j = 0;j<tpL;j++) {
                    L[j] = rs(L[j]);
                }
                for (int j = 0;j<tpR;j++) {
                    R[j] = rs(R[j]);
                }
                l = mid + 1;
            }
        }
        return l;
    }
```

```
    int get4(int l, int r, int k) {
        k = query(l, r, k);
        if (k == 0) return -2147483647;
        return findK(l, r, k);
    }

    int get5(int l, int r, int k) {
        k = query(l, r, k + 1);
        if (k >= r - l + 1) return 2147483647;
        int ans = findK(l, r, k + 1);
        return ans;
    }
};
using namespace TWT;
"\n"
```

树状数组.cpp

```
#include <bits/stdc++.h>
using namespace std;
typedef long long ll;
const ll N = 2000000;

/*
一个易错点， 树状数组上二分的时候， 注意那个， 这个树状数组的下标是从 1 开始的
这很重要！！！ 离散化的时候要对齐了
*/
struct BIT {
    int n;
    struct Info {
        Info() {

        }
        Info operator+(const Info& A) const {

        }
        Info operator-(const Info& A) const {

        }
    };
    vector<Info> infos;
    void init(int N_) {
        n = N_ + 1;
        infos.assign(n + 1, Info());
    }
    int lowbit(int x) {return x & -x;}
    void update(int x, ll v) {
        x ++;
        while (x <= n) {
```

```
            x += lowbit(x);
        }
    }
    Info query(int x) {
        x ++;
        Info res;
        while (x) {
            res = res + infos[x];
            x -= lowbit(x);
        }
        return res;
    }
    Info query(int l, int r) {
        if (l > r) return Info();
        return query(r) - query(l - 1);
    }
};
"\n"
```

珂朵莉树.cpp

```
#include <bits/stdc++.h>
using namespace std;
#define DEBUG 1
using ll = long long;
using pii = pair<int,int>;
using pll = pair<ll,ll>;
const ll N = 2000000;
const ll INF = 5e18;
const ll MOD = 1e9 + 7;


// 注意下标别搞错了, 什么从 0 开始之类...
struct ChthollyTree {
    struct Node {
        int l, r;
        int v;
        Node(int L_ = 0, int R_ = 0, int V_ = 0) {l = L_, r = R_, v = V_;}
        bool operator<(const Node& A) const {return l < A.l;}
    };
    set<Node> nodes;

    // 注意初始化插入全 1 段.
    // 注意插入 n + 1
    ChthollyTree(int N_) {
        nodes.insert(Node(1, N_ + 1, 0));
    }

    set<Node>::iterator split(int x) {
        auto it = nodes.lower_bound(Node(x, 0));
        if (it != nodes.end() && it->l == x) return it;
```

```
        -- it;
        int l = it->l, r = it->r, v = it->v;
        nodes.erase(it);
        nodes.insert(Node(l, x - 1, v));
        return nodes.insert(Node(x, r, v)).first;
    }

    void assign(int l, int r, int v) {
        auto itr = split(r + 1), itl = split(l);
        nodes.erase(itl, itr);
        nodes.insert(Node(l, r, v));
        return;
    }
};

struct ChthollyTree {
    const int M = 1e8;
    struct Node {
        int l,r;
        bool operator<(const Node& A) const {
            if (l != A.l) return l < A.l;
            return r < A.r;
        }
        Node (int L_ = 0,int R_ = 0) {
            l = L_, r = R_;
        }
    };
    set<Node> nodes;

    void init() {
        nodes.insert(Node(1,M));
    }

    void insert(Node a) {
        Node b; b.l = a.l, b.r = M;
        auto it = nodes.upper_bound(b);

        vector<Node> val;

        if (it == nodes.end()) {
            it = prev(nodes.end());
            if (it->r > a.r) {
                if (it->l <= a.l - 1) {
                    val.push_back(Node(it->l,a.l-1));
                }
                if (it->r >= a.r + 1) {
                    val.push_back(Node(a.r+1,it->r));
                }
                it = nodes.erase(it);
            } else if (it->r >= a.l) {
                if (it->l <= a.l - 1) {
                    val.push_back(Node(it->l,a.l-1));
                }
                it = nodes.erase(it);
```

```
            } else {
                ++ it;
            }
        } else {
            if (it == nodes.begin()) {

            } else {
                -- it;
                if (it->r > a.r) {
                    if (it->l <= a.l - 1) {
                        val.push_back(Node(it->l,a.l-1));
                    }
                    if (it->r >= a.r + 1) {
                        val.push_back(Node(a.r+1,it->r));
                    }
                    it = nodes.erase(it);
                } else if (it->r >= a.l) {
                    if (it->l <= a.l - 1) {
                        val.push_back(Node(it->l,a.l-1));
                    }
                    it = nodes.erase(it);
                } else {
                    ++ it;
                }
            }
        }

        while (it != nodes.end() && it->l <= a.r) {
            if (it->r <= a.r) {
                it = nodes.erase(it);
            } else {
                if (it->r >= a.r + 1) {
                    val.push_back(Node(a.r+1,it->r));
                }
                it = nodes.erase(it);
            }
        }

        nodes.insert(a);
        for (auto v : val) {
            nodes.insert(v);
        }
        return;
    }
} ;
"\n"
```

笛卡尔树.cpp

```
#include <bits/stdc++.h>
using namespace std;
```

```
/*
先 init 初始化
传入 vector<T> 构建小根堆笛卡尔树
*/

template<typename T>
class CartesianTree {
public:
    struct Node {
        T val;
        int ch[2];
        Node() {
            val = ch[0] = ch[1] = 0;
        }
    };
    vector<Node> nodes;

    void init(int N_) {
        nodes.clear();
        nodes.resize(N_ + 1);
    }

    void buildMinHeap(vector<T>& a) {
        vector<int> stk;
        stk.push_back(0);
        nodes[0].val = -INF;
        for (int i = 1;i<a.size();i++) {
            int lst = -1;
            while (a[stk.back()] > a[i]) {
                lst = stk.back();
                stk.pop_back();
            }

            if (lst != -1) {
                nodes[i].ch[0] = lst;
            }
            nodes[i].val = a[i];
            nodes[stk.back()].ch[1] = i;
            stk.push_back(i);
        }
        return;
    }
};"\n"
```

线段树.cpp

```
#include <bits/stdc++.h>
using namespace std;
typedef long long ll;
const ll N = 2000000;
```

```
const ll INF = 1e18;

/*
切记 pd 清空旧标记
*/

#define LS (rt << 1)
#define RS (rt << 1 | 1)

struct SegTree{
    struct Node{
        Node() {

        }
    }nodes[N*4];

    Node merge(Node L,Node R){
        Node M;
        return M;
    }
    void build(int rt,int l,int r){
        if (l == r){
            return;
        }
        int mid = l + r >> 1;
        build(LS,l,mid),build(RS,mid+1,r);
        nodes[rt] = merge(nodes[LS],nodes[RS]);
    }
    void pd(int rt){

    }
    void update(int rt,int l,int r,int ql,int qr,int val){
        if (ql > qr || l > qr || ql > r) return;
        if (ql <= l && r <= qr){
            return;
        }
        int mid = l+r>>1;
        pd(rt);
        if (ql <= mid){
            update(LS,l,mid,ql,qr,val);
        }
        if (qr >= mid + 1){
            update(RS,mid+1,r,ql,qr,val);
        }
        nodes[rt] = merge(nodes[LS],nodes[RS]);
        return;
    }
    void modify(int rt,int l,int r,int q,int val){
        if (l > q || r < q) return;
        if (l == r) {
            return;
        }
        int mid = l+r>>1;
        pd(rt);
```

```
        if (q <= mid){
            modify(LS,l,mid,q,val);
        }
        if (q >= mid + 1){
            modify(RS,mid+1,r,q,val);
        }
        nodes[rt] = merge(nodes[LS],nodes[RS]);
        return;
    }
    Node query(int rt,int l,int r,int ql,int qr){
        if (ql > qr) {
            return Node();
        }
        if (ql <= l && r <= qr){
            return nodes[rt];
        }
        int mid = l+r>>1;
        pd(rt);
        if (ql > mid){
            return query(RS,mid+1,r,ql,qr);
        }else if (qr < mid + 1){
            return query(LS,l,mid,ql,qr);
        }else{
            return merge(query(LS,l,mid,ql,qr),query(RS,mid+1,r,ql,qr));
        }
    }
};

// 调用前先 init
#define LS nodes[rt].ls
#define RS nodes[rt].rs
struct DynamicSegTree {
    struct Node {
        int ls,rs;
        Node() {
            ls = rs = 0;
        }
    } nodes[N];
    int cntNode;
    void init() {
        cntNode = 1;
        nodes[0] = Node();
    }
    int newNode() {
        nodes[cntNode] = Node();
        return cntNode++;
    }
    Node merge(Node L,Node R) {
        Node M;
        // 补充合并方法
        return M;
    }
    void pushUp(int rt) {
        // 更新父节点
```

```
        return;
    }
    void pushDown(int rt) {
        // 下传标记
    }
    void update(int& rt,int l,int r,int ql,int qr,int val) {
        if (ql > qr || l > qr || r < ql) return;
        if (!rt) rt = newNode();
        if (ql <= l && r <= qr) {
            // 更新方法
            return;
        }
        int mid = l + r >> 1;
        update(nodes[rt].ls,l,mid,ql,qr,val);
        update(nodes[rt].rs,mid+1,r,ql,qr,val);
        pushUp(rt);
        return;
    }
    Node query(int& rt,int l,int r,int ql,int qr) {
        if (ql > qr || l > qr || r < ql || !rt) return Node();
        if (ql <= l && r <= qr) {
            return nodes[rt];
        }
        int mid = l + r >> 1;
        pushDown(rt);
        return merge(query(LS,l,mid,ql,qr),query(RS,mid+1,r,ql,qr));
    }
    int treeMerge(int& ls,int& rs,int l,int r) {
        if (!ls || !rs) return ls | rs;
        if (l == r) {
            // 叶节点合并方法

            return ls;
        }
        int mid = l + r >> 1;
        nodes[ls].ls = treeMerge(nodes[ls].ls,nodes[rs].ls,l,mid);
        nodes[ls].rs = treeMerge(nodes[ls].rs,nodes[rs].rs,mid+1,r);
        pushUp(ls);
        return ls;
    }
};


struct DynamicSegTree {
    #define LS info[rt].ls
    #define RS info[rt].rs
    struct Info {
        int ls, rs;
        Info() {
            ls = rs = 0;
        }
        Info operator+(const Info& A) const {

        }
```

```
} info[N];
int cntNode = 0;

void init() {
    cntNode = 0;
};

int newNode() {
    ++cntNode;
    info[cntNode] = Info();
    return cntNode;
};

void pushUp(int rt) {
    return;
}

void build(int& rt,int l,int r) {
    rt = newNode();
    if (l == r) {
        return;
    }
    int mid = l + r >> 1;
    build(LS,l,mid); build(RS,mid+1,r);
    pushUp(rt);
    return;
}

// 主席树版本
// void update(int& rt,int l,int r,int ql,int qr) {
//  if (ql > qr || qr < l || r < ql) return;
//  if (ql <= l && r <= qr) {
//      return;
//  }
//  int mid = l + r >> 1;
//  if (ql <= mid) {
//      ++cntNode;
//      info[cntNode] = info[LS];
//      LS = cntNode;
//      update(LS,l,mid,ql,qr);
//  }
//  if (qr >= mid + 1) {
//      ++cntNode;
//      info[cntNode] = info[RS];
//      RS = cntNode;
//      update(RS,mid+1,r,ql,qr);
//  }
//  pushUp(rt);
//  return;
// }

void update(int& rt,int l,int r,int ql,int qr) {
    if (ql > qr || qr < l || r < ql) return;
    if (!rt) rt = newNode();
```

```
        if (ql <= l && r <= qr) {
            return;
        }
        int mid = l + r >> 1;
        if (ql <= mid) {
            update(LS,l,mid,ql,qr);
        }
        if (qr >= mid + 1) {
            update(RS,mid+1,r,ql,qr);
        }
        pushUp(rt);
        return;
    }

    Info query(int rt,int l,int r,int ql,int qr) {
        if (!rt || ql > qr || r < ql || qr < l) return Info();
        if (ql <= l && r <= qr) {
            return info[rt];
        }
        int mid = l + r >> 1;
        if (qr <= mid) {
            return query(LS,l,mid,ql,qr);
        } else if (ql >= mid + 1) {
            return query(RS,mid+1,r,ql,qr);
        } else {
            return query(LS,l,mid,ql,qr) + query(RS,mid+1,r,ql,qr);
        }
    }
} solver;


/*
线段树合并以及线段树分裂的整合代码
细节还是比较多的，比如说，注意这个 split 之后的 pushUp
*/
namespace SegTree {
    struct Node {
        int ch[2];
        ll cnt, sum;
        Node() {
            ch[0] = ch[1] = cnt = sum = 0;
        }
    } nodes[N * 4];
    int tp;

    void init() { tp = 0; }

    int New() {
        ++ tp;
        nodes[tp] = Node();
        return tp;
    }

    #define ls(x) nodes[x].ch[0]
```

```
#define rs(x) nodes[x].ch[1]

void push_up(int rt) {
    nodes[rt].sum = nodes[rt].cnt = 0;
    if (ls(rt)) {
        nodes[rt].sum += nodes[ls(rt)].sum;
        nodes[rt].cnt += nodes[ls(rt)].cnt;
    }
    if (rs(rt)) {
        nodes[rt].sum += nodes[rs(rt)].sum;
        nodes[rt].cnt += nodes[rs(rt)].cnt;
    }
    return;
}

void update(int &rt, int l, int r, int q, ll c) {
    if (!rt) rt = New();
    if (l == r) {
        nodes[rt].sum += c;
        nodes[rt].cnt += c;
        return;
    }
    int mid = l + r >> 1;
    if (q <= mid) update(ls(rt), l, mid, q, c);
    else update(rs(rt), mid + 1, r, q, c);
    push_up(rt);
    return;
}

ll query(int rt, int l, int r, int ql, int qr) {
    if (!rt) return 0;
    if (qr < l || ql > r || ql > qr) return 0;
    if (ql <= l && r <= qr) return nodes[rt].sum;
    int mid = l + r >> 1;
    return query(ls(rt), l, mid, ql, qr) + query(rs(rt), mid + 1, r, ql, qr);
}

int findK(int rt, int l, int r, ll k) {
    if (!rt || nodes[rt].sum < k) return -1;
    if (l == r) return l;
    int mid = l + r >> 1;
    if (nodes[ls(rt)].sum >= k) {
        return findK(ls(rt), l, mid, k);
    } else {
        k -= nodes[ls(rt)].sum;
        return findK(rs(rt), mid + 1, r, k);
    }
}

int merge(int x, int y, int l, int r) {
    if (!x || !y) return x + y;
    if (l == r) {
        nodes[x].cnt += nodes[y].cnt;
        nodes[x].sum += nodes[y].sum;
```

```
            return x;
        }
        int mid = l + r >> 1;
        ls(x) = merge(ls(x), ls(y), l, mid);
        rs(x) = merge(rs(x), rs(y), mid + 1, r);
        push_up(x);
        return x;
    }

    void split(int x, int& y, int l, int r, ll k) {
        if (!k) return;
        if (!y) y = New();
        if (l == r) {
            // assert(nodes[x].sum >= k);
            nodes[x].cnt -= k;
            nodes[x].sum -= k;
            nodes[y].cnt += k;
            nodes[y].sum += k;
            return;
        }
        int mid = l + r >> 1;
        if (nodes[ls(x)].sum <= k) {
            k -= nodes[ls(x)].sum;
            nodes[y].ch[0] = ls(x);
            ls(x) = 0;
            split(rs(x), rs(y), mid + 1, r, k);
        } else {
            split(ls(x), ls(y), l, mid, k);
        }
        push_up(x); push_up(y);
        return;
    }
};
using namespace SegTree;"\n"
```

高精度.cpp

```
#include <bits/stdc++.h>
using namespace std;
#define DEBUG 1
using ll = long long;
using pii = pair<int, int>;
using i128 = __int128_t;
using pll = pair<ll, ll>;
const ll N = 2000000;
const ll INF = 5e18;
const ll MOD = 1e9 + 7;

struct BigInt {
    vector<int> a;
    BigInt(int x = 0) {
```

```
        if (x == 0) {
            a.push_back(0);
            return;
        }
        while (x) {
            a.push_back(x % 10);
            x /= 10;
        }
    }
    void update() {
        for (int i = 0;i<a.size();i++) {
            if (a[i] >= 10) {
                if (i + 1 < a.size()) {
                    a[i + 1] += a[i] / 10;
                    a[i] %= 10;
                } else {
                    a.push_back(a[i] / 10);
                    a[i] %= 10;
                }
            }
        }
        while (a.size() > 1 && a.back() == 0) {
            a.pop_back();
        }
        return;
    }
    BigInt operator*(const BigInt& A) const {
        BigInt B;
        B.a.resize(a.size() + A.a.size());
        for (int i = 0;i<a.size();i++) {
            for (int j = 0;j<A.a.size();j++) {
                B.a[i + j] += a[i] * A.a[j];
            }
        }
        B.update();
        return B;
    }
};

ostream &operator<<(ostream &o, const BigInt &a) {
    for (int i = a.a.size() - 1;i>=0;i--) {
        o << a.a[i];
    }
    return o;
}"\n"
```

三角形.cpp

```
#include <bits/stdc++.h>
using namespace std;
typedef long long ll;
```

```
const ll N = 2000000;

/*
使用说明:
手动输入Triangle中三个点的坐标
update函数更新外心左边和外接圆半径
可以应对三点共线的特殊情况
*/

struct Point {
    double x, y;
    int idx;
    Point(double X = 0, double Y = 0) {
        x = X;
        y = Y;
    }

    Point operator-(const Point& A) const {
        return Point(x - A.x, y - A.y);
    }

    Point operator+(const Point& A) const{
        return Point(x + A.x,y + A.y);
    }

    double operator^(const Point& A) const {
        return x * A.y - A.x * y;
    }

    double operator*(const Point& A) const {
        return x * A.x + y * A.y;
    }

    double len() {
        return sqrt(x * x + y * y);
    }

    double len2() {
        return x * x + y * y;
    }

    bool operator==(const Point& A) const {
        return (x == A.x) && (y == A.y);
    }
};

class Triangle{
public:
    Point nodes[3];
    Point circumCenter;
    double r;
    void update(){
        double a,b,c,d,e,f;
        a=nodes[1].x-nodes[0].x,b=nodes[1].y-nodes[0].y,c=nodes[2].x-nodes[1].x;
```

```
        d=nodes[2].y-nodes[1].y;e=nodes[1].x*nodes[1].x+nodes[1].y*nodes[1].y
        -nodes[0].x*nodes[0].x-nodes[0].y*nodes[0].y;
        f=nodes[2].x*nodes[2].x+nodes[2].y*nodes[2].y-nodes[1].x*nodes[1].x
        -nodes[1].y*nodes[1].y;
        if (a*d == c*b){
            r = 0;
            if ((nodes[0] - nodes[1]).len() > r){
                r = (nodes[0] - nodes[1]).len();
                circumCenter = nodes[0] + nodes[1];
                circumCenter.x /= 2,circumCenter.y /= 2;
            }
            if ((nodes[0] - nodes[2]).len() > r){
                r = (nodes[0] - nodes[2]).len();
                circumCenter = nodes[0] + nodes[2];
                circumCenter.x /= 2,circumCenter.y /= 2;
            }
            if ((nodes[2] - nodes[1]).len() > r){
                r = (nodes[2] - nodes[1]).len();
                circumCenter = nodes[2] + nodes[1];
                circumCenter.x /= 2,circumCenter.y /= 2;
            }
            return;
        }
        circumCenter.x=(f*b-e*d)/(c*b-a*d)/2;
        circumCenter.y=(a*f-e*c)/(a*d-b*c)/2;
        r=(nodes[0]-circumCenter).len();
        return;
    }
};"\n"
```

凸包.cpp

```
#include <bits/stdc++.h>
using namespace std;
typedef long long ll;

using db = double;
const db eps = 1e-9;

struct Point {
    double x, y;
    Point operator-(const Point& b) const { return {x - b.x, y - b.y}; }
    Point operator+(const Point& b) const { return {x + b.x, y + b.y}; }
    Point operator*(double k) const { return {x * k, y * k}; }
    double operator^(const Point& b) const { return x * b.y - y * b.x; }
    double operator&(const Point& b) const { return x * b.x + y * b.y; }
    double len2() const { return x * x + y * y; }
    double len() const { return sqrt(len2()); }
};

Point rotate90(Point &v) { return {-v.y, v.x}; }
```

```
vector<Point> getConvexHull(vector<Point>& p) {
    int n = p.size();
    sort(p.begin(), p.end(), [](Point a, Point b) {
        return a.x < b.x || (abs(a.x - b.x) < eps && a.y < b.y);
    });
    vector<Point> hull;
    for (int i = 0; i < n; ++i) {
        while (hull.size() > 1 && ((hull.back() - hull[hull.size() - 2]) ^ (p[i] -
hull.back())) <= eps)
            hull.pop_back();
        hull.push_back(p[i]);
    }
    int k = hull.size();
    for (int i = n - 2; i >= 0; --i) {
        while (hull.size() > k && ((hull.back() - hull[hull.size() - 2]) ^ (p[i] -
hull.back())) <= eps)
            hull.pop_back();
        hull.push_back(p[i]);
    }
    hull.pop_back();
    return hull;
}"\n"
```

半平面交.cpp

```
#define DEBUG 1
#define FUCK cout << "fuck" << endl;
#if DEBUG
    #include "all.hpp"
#else
    #include <bits/stdc++.h>
#endif

using namespace std;
using ll = long long;
using pii = pair<int,int>;
using pll = pair<ll,ll>;
using db = long double;
using pdd = pair<db, db>;
using i128 = __int128_t;

const ll N = 2000000;
const ll INF = 5e18;
const ll MOD = 1e9 + 7;
/*
观察 getS 函数， 发现最后 tail 和 head 之间的就是半平面交的凸包
复杂度是 nlogn
*/

const db eps = 1e-10;
```

```
struct Point {
    db x, y;
    Point operator-(const Point& b) const { return {x - b.x, y - b.y}; }
    Point operator+(const Point& b) const { return {x + b.x, y + b.y}; }
    Point operator*(db k) const { return {x * k, y * k}; }
    db operator^(const Point& b) const { return x * b.y - y * b.x; }
};

struct Line {
    Point p1, p2;
    db angle;
    Line() {}
    Line(Point a, Point b) : p1(a), p2(b) {
        angle = atan2(b.y - a.y, b.x - a.x);
    }
};

Point getIntersect(Line a, Line b) {
    Point v1 = a.p2 - a.p1;
    Point v2 = b.p2 - b.p1;
    Point u = a.p1 - b.p1;
    db t = (v2 ^ u) / (v1 ^ v2);
    return a.p1 + v1 * t;
}

bool isRight(Line l, Point p) {
    return ((l.p2 - l.p1) ^ (p - l.p1)) < -eps;
}

db getS(vector<Line>& lines) {
    sort(lines.begin(), lines.end(), [](Line a, Line b) {
        if (abs(a.angle - b.angle) > eps) return a.angle < b.angle;
        return ((a.p2 - a.p1) ^ (b.p2 - a.p1)) < -eps;
    });

    int n = lines.size();
    int m = 0;
    for (int i = 0; i < n; i++) {
        if (i > 0 && abs(lines[i].angle - lines[i - 1].angle) < eps) continue;
        lines[m++] = lines[i];
    }
    lines.erase(lines.begin() + m, lines.end());

    int head = 0, tail = 0;
    vector<Line> dq(lines.size() + 5);
    vector<Point> p(lines.size() + 5);

    dq[tail++] = lines[0];
    for (int i = 1; i < (int)lines.size(); i++) {
        while (tail - head > 1 && isRight(lines[i], p[tail - 1])) tail--;
        while (tail - head > 1 && isRight(lines[i], p[head + 1])) head++;

        dq[tail++] = lines[i];
```

```
        if (abs((dq[tail - 1].p2 - dq[tail - 1].p1) ^ (dq[tail - 2].p2 - dq[tail -
2].p1)) < eps) {
            tail--;
            if (!isRight(dq[tail], lines[i].p1)) dq[tail] = lines[i];
        }
        if (tail - head > 1) p[tail - 1] = getIntersect(dq[tail - 2], dq[tail -
1]);
    }

    while (tail - head > 1 && isRight(dq[head], p[tail - 1])) tail--;
    while (tail - head > 1 && isRight(dq[tail - 1], p[head + 1])) head++;

    if (tail - head < 3) return 0.0;

    p[head] = getIntersect(dq[tail - 1], dq[head]);

    db area = 0;
    for (int i = head; i < tail; i++) {
        area += (p[i] ^ p[i == tail - 1 ? head : i + 1]);
    }
    return abs(area) / 2.0;
}"\n"
```

圆的并.cpp

```
#define DEBUG 1
#define FUCK cout << "fuck" << endl;
#if DEBUG
    #include "all.hpp"
#else
    #include <bits/stdc++.h>
#endif

using namespace std;
using ll = long long;
using pii = pair<int,int>;
using pll = pair<ll,ll>;
using db = long double;
using pdd = pair<db, db>;
using i128 = __int128_t;

const ll N = 2000000;
const ll INF = 5e18;
const ll MOD = 1e9 + 7;

namespace CircleUnion {
    const db PI = acos(-1);
    const db eps = 2e-10, pi2 = PI * 2.0;
    struct Circle { db x, y, r; };

    enum relation { outside = 0, intersective = 1, contained = 2, containing = 3
```

```
};

    struct Vec { db x, y; Vec(db _x=0, db _y=0):x(_x),y(_y){} };

    inline db sq(db x){return x*x;}
    inline db f(const Vec &O, db r, db t){ return r * (r * t + O.x * sin(t) - O.y
* cos(t)); }

    relation circle_relation(const Vec &O1, db r1, const Vec &O2, db r2) {
        db d2 = sq(O1.x - O2.x) + sq(O1.y - O2.y);
        if ((r1 + r2) * (r1 + r2) <= d2 + eps) return outside;
        if ((r1 - r2) * (r1 - r2) >= d2 - eps) return (r1 <= r2 + eps) ? contained
: containing;
        return intersective;
    }

    void intersection(const Vec &O1, db r1, const Vec &O2, db r2, db &beg, db
&end) {
        Vec O12{O2.x - O1.x, O2.y - O1.y};
        db d2 = sq(O12.x) + sq(O12.y), d = sqrt(d2);
        db Cos = (((r1 + r2) * (r1 - r2) + d2) / (2.0 * d * r1));
        if (Cos > 1) Cos = 1; if (Cos < -1) Cos = -1;
        db sAng = acos(Cos), iAng = atan2(O12.y, O12.x);
        if (iAng < 0.0) iAng += pi2;
        beg = iAng - sAng; if (beg < 0.0) beg += pi2;
        end = iAng + sAng; if (end >= pi2) end -= pi2;
    }

    static db union_area_ = 0.0, union_perim_ = 0.0;

    void init(const vector<Circle> &circles) {
        int n = (int)circles.size();
        vector<Vec> O(n); vector<db> r(n);
        for (int i=0;i<n;++i){ O[i].x = circles[i].x; O[i].y = circles[i].y; r[i]
= circles[i].r; }
        union_area_ = union_perim_ = 0.0;
        for (int i = 0; i < n; ++i) {
            vector<pair<db,db>> segs; segs.reserve(n*2+2);
            bool skip = false;
            for (int j = 0; j < n; ++j) {
                relation rel = circle_relation(O[i], r[i], O[j], r[j]);
                if (rel == contained) {
                    if (fabs(r[i] - r[j]) > eps || i > j) { skip = true; break; }
                }
            }
            if (skip) continue;
            for (int j = 0; j < n; ++j) {
                relation rel = circle_relation(O[i], r[i], O[j], r[j]);
                if (rel == intersective) {
                    db a,b; intersection(O[i], r[i], O[j], r[j], a, b);
                    if (a <= b) segs.emplace_back(a,b);
                    else { segs.emplace_back(0.0, b); segs.emplace_back(a, pi2); }
                }
            }
```

```
            segs.emplace_back(pi2, pi2);
            sort(segs.begin(), segs.end(), [](const pair<db,db>&A,const
pair<db,db>&B){ if (A.first!=B.first) return A.first < B.first; return A.second <
B.second; });
            db la = 0.0;
            for (size_t k = 0; k < segs.size(); ++k) {
                db L = segs[k].first, R = segs[k].second;
                if (la < L) {
                    union_area_ += 0.5 * (f(O[i], r[i], L) - f(O[i], r[i], la));
                    union_perim_ += r[i] * (L - la);
                    la = R;
                } else if (la < R) {
                    la = R;
                }
            }
        }
    }

    double area(){ return union_area_; }
    double perimeter(){ return union_perim_; }
}
using namespace CircleUnion;"\n"
```

平面最近点对.cpp

```
#include <bits/stdc++.h>
using namespace std;
using db   = double;
using i128 = __int128;

template<typename T>
auto closest_pair_sq(vector<pair<T,T>>& a){
    using R = conditional_t<is_integral_v<T>, long long, db>;
    if(a.size()<2) return R(0);
    sort(a.begin(), a.end(), [](auto&p,auto&q){ return p.first<q.first; });
    vector<pair<T,T>> buf(a.size());

    function<R(int,int)> rec = [&](int l,int r)->R{
        if(r-l<=1) return numeric_limits<R>::max();
        int m=(l+r)/2; T midx=a[m].first;
        R d = min(rec(l,m), rec(m,r));

        merge(a.begin()+l, a.begin()+m, a.begin()+m, a.begin()+r,
              buf.begin(), [](auto&p,auto&q){ return p.second<q.second; });
        copy(buf.begin(), buf.begin()+(r-l), a.begin()+l);

        vector<pair<T,T>> v; v.reserve(r-l);

        if constexpr(is_integral_v<T>){
            i128 D = d;
            for(int i=l;i<r;++i){
```

```
                i128 dx = (i128)a[i].first - midx;
                if(dx*dx <= D) v.push_back(a[i]);
            }
            for(int i=0;i<(int)v.size();++i)
                for(int j=i+1;j<(int)v.size() &&
                    (i128)(v[j].second-v[i].second)*(v[j].second-v[i].second) <=
D; ++j){
                    i128 dx = (i128)(v[j].first - v[i].first);
                    i128 dy = (i128)(v[j].second - v[i].second);
                    i128 w = dx*dx + dy*dy;
                    if(w < D) D = w;
                }
            return (R)D;

        } else {
            db D = d;
            for(int i=l;i<r;++i){
                db dx = db(a[i].first) - db(midx);
                if(dx*dx <= D) v.push_back(a[i]);
            }
            for(int i=0;i<(int)v.size();++i)
                for(int j=i+1;j<(int)v.size() &&
                    db(v[j].second-v[i].second)*db(v[j].second-v[i].second) <= D;
++j){
                    db dx = db(v[j].first - v[i].first);
                    db dy = db(v[j].second - v[i].second);
                    db w = dx*dx + dy*dy;
                    if(w < D) D = w;
                }
            return (R)D;
        }
    };

    return rec(0, (int)a.size());
}
"\n"
```

旋转卡壳.cpp

```
#define DEBUG 1
#define FUCK cout << "fuck" << endl;
#if DEBUG
    #include "all.hpp"
#else
    #include <bits/stdc++.h>
#endif

using namespace std;
using ll = long long;
using pii = pair<int,int>;
using pll = pair<ll,ll>;
```

```
using db = long double;
using pdd = pair<db, db>;
using i128 = __int128_t;

const ll N = 2000000;
const ll INF = 5e18;
const ll MOD = 1e9 + 7;

namespace Rotating_Calipers {

struct Point {
    ll x, y;
    Point operator-(const Point& b) const { return {x - b.x, y - b.y}; }
    ll operator^(const Point& b) const { return x * b.y - y * b.x; }
};

ll distSq(Point a, Point b) {
    return (a.x - b.x) * (a.x - b.x) + (a.y - b.y) * (a.y - b.y);
}

ll cross_product(Point a, Point b, Point c) {
    return (b - a) ^ (c - a);
}

vector<Point> getConvexHull(vector<Point>& pts) {
    int n = pts.size();
    if (n <= 2) return pts;
    sort(pts.begin(), pts.end(), [](Point a, Point b) {
        return a.x < b.x || (a.x == b.x && a.y < b.y);
    });

    vector<Point> hull;
    for (int i = 0; i < n; ++i) {
        while (hull.size() >= 2 && cross_product(hull[hull.size() - 2],
hull.back(), pts[i]) <= 0) {
            hull.pop_back();
        }
        hull.push_back(pts[i]);
    }
    int lower_size = hull.size();
    for (int i = n - 2; i >= 0; --i) {
        while (hull.size() > lower_size && cross_product(hull[hull.size() - 2],
hull.back(), pts[i]) <= 0) {
            hull.pop_back();
        }
        hull.push_back(pts[i]);
    }
    hull.pop_back();
    return hull;
}

ll rotatingCalipers(const vector<Point>& hull) {
    int m = hull.size();
    if (m == 2) return distSq(hull[0], hull[1]);
```

```
    ll max_dist = 0;
    int j = 1;

    for (int i = 0; i < m; i++) {
        int next_i = (i + 1) % m;
        while (abs(cross_product(hull[i], hull[next_i], hull[(j + 1) % m])) >
               abs(cross_product(hull[i], hull[next_i], hull[j]))) {
            j = (j + 1) % m;
        }
        max_dist = max({max_dist, distSq(hull[i], hull[j]), distSq(hull[next_i],
hull[j])});
    }
    return max_dist;
}

};
using namespace Rotating_Calipers;
"\n"
```

Lca.cpp

```
#include <bits/stdc++.h>
using namespace std;

typedef long long ll;
const ll N = 2000000;

/*
O(1) LCA
先把 Graph 边练好,然后调用 Lca 类的 init 函数
然后就可以使用 lca(查祖先) 和 query(查距离) 了

注意边权不要爆 ll !
*/

struct Lca {
    vector<vector<int>> *g;
    vector<int> depth, first, euler;
    vector<ll> dist;
    vector<vector<int>> st;
    vector<int> lg;

    void init(vector<vector<int>>* graph, int root) {
        g = graph;
        euler.clear();
        depth.clear();
        dist.assign(g->size(), 0);
        first.assign(g->size(), -1);
        dfs(root, -1, 0, 0);
        build_st();
```

```
    }

    void dfs(int u, int p, int d, ll s) {
        first[u] = euler.size();
        euler.push_back(u);
        depth.push_back(d);
        dist[u] = s;
        for (int v : (*g)[u]) if (v != p) {
            dfs(v, u, d + 1, s + 1);
            euler.push_back(u);
            depth.push_back(d);
        }
    }

    void build_st() {
        int m = euler.size();
        lg.assign(m + 1, 0);
        for (int i = 2; i <= m; ++i) lg[i] = lg[i >> 1] + 1;
        int K = lg[m] + 1;
        st.assign(K, vector<int>(m));
        for (int i = 0; i < m; ++i) st[0][i] = i;
        for (int j = 1; (1 << j) <= m; ++j)
            for (int i = 0; i + (1 << j) <= m; ++i) {
                int a = st[j - 1][i], b = st[j - 1][i + (1 << (j - 1))];
                st[j][i] = depth[a] < depth[b] ? a : b;
            }
    }

    int lca(int u, int v) {
        int l = first[u], r = first[v];
        if (l > r) swap(l, r);
        int j = lg[r - l + 1];
        int a = st[j][l], b = st[j][r - (1 << j) + 1];
        return euler[ depth[a] < depth[b] ? a : b ];
    }

    int query(int u, int v) {
        int L = lca(u, v);
        return dist[u] + dist[v] - 2 * dist[L];
    }
};

// dep 跟 dist 不要搞混了谢谢喵
struct Lca {
    int M = 20;
    vector<vector<int>> fa;
    vector<int> dep;
    void init(vector<vector<int>>& g, int rt) {
        int n = g.size() - 1;
        fa.clear();
        fa.resize(n + 1, vector<int>(M, 0));
        dep.clear();
        dep.resize(n + 1, 0);
        dep[0] = 0;
```

```
        auto dfs = [&](auto&&self, int u, int f) -> void {
            for (auto v : g[u]) {
                if (v == f) continue;
                fa[v][0] = u;
                dep[v] = dep[u] + 1;
                self(self, v, u);
            }
        };
        dfs(dfs, rt, 0);
        for (int i = 1;i<M;i++) {
            for (int j = 1;j<n+1;j++) {
                fa[j][i] = fa[fa[j][i-1]][i-1];
            }
        }
        return;
    }

    int lca(int x, int y) {
        if (dep[x] < dep[y]) swap(x, y);
        for (int i = M-1;i>=0;i--) {
            if (dep[fa[x][i]] >= dep[y]) {
                x = fa[x][i];
            }
        }
        if (x == y) return x;
        for (int i=M-1;i>=0;i--) {
            if (fa[x][i] != fa[y][i]) {
                x = fa[x][i], y = fa[y][i];
            }
        }
        return fa[x][0];
    }

    int query(int x, int y) {
        int z = lca(x, y);
        return dep[x] + dep[y] - 2 * dep[z];
    }
} solver;"\n"
```

Prufer.cpp

```
#include <bits/stdc++.h>
using namespace std;
#define DEBUG 1
using ll = long long;
using pii = pair<int,int>;
using i128 = __int128_t;
using pll = pair<ll,ll>;
const ll N = 2000000;
const ll INF = 5e18;
const ll MOD = 1e9 + 7;
```

```cpp
/*
做模版题的时候发现这个 push_back 的常数真不是一般的大
数据量大的时候慎用这个 push_back 吧
*/
struct Prufer {
    // 注意 g 的下标从 1 开始
    // vector<int> getPrufer(vector<vector<int>>& g) {
    //  int n = g.size() - 1;
    //  vector<int> d(n + 1, 0);
    //  for (int i = 1;i<n+1;i++) {
    //      d[i] = g[i].size();
    //  }
    //  vector<int> fa(n + 1, 0);
    //  {
    //      vector<int> stk;
    //      stk.push_back(n);
    //      while (!stk.empty()) {
    //          int u = stk.back(); stk.pop_back();
    //          for (auto v : g[u]) {
    //              if (v == fa[u]) continue;
    //              fa[v] = u;
    //              stk.push_back(v);
    //          }
    //      }
    //  }
    //  vector<int> p;
    //  for (int i = 1;i<=n&&p.size()<n-2;i++) {
    //      if (d[i] == 1 && fa[i]) {
    //          p.push_back(fa[i]);
    //          d[fa[i]] --;
    //          d[i] --;
    //          int u = fa[i];
    //          while (d[u] == 1 && u<i+1 && fa[u] && p.size()<n-2) {
    //              p.push_back(fa[u]);
    //              d[fa[u]] --;
    //              d[u] --;
    //              u = fa[u];
    //          }
    //      }
    //  }
    //  return p;
    // }
    vector<int> getPrufer(vector<int>& fa) {
        int n = fa.size() - 1;
        vector<int> d(n + 1, 0);
        for (int i = 1;i<n+1;i++) {
            if (fa[i]) {
                d[i] ++; d[fa[i]] ++;
            }
        }
        vector<int> p;
        for (int i = 1;i<=n&&p.size()<n-2;i++) {
            if (d[i] == 1 && fa[i]) {
```

```
                p.push_back(fa[i]);
                d[fa[i]] --;
                d[i] --;
                int u = fa[i];
                while (d[u] == 1 && u<i+1 && fa[u] && p.size()<n-2) {
                    p.push_back(fa[u]);
                    d[fa[u]] --;
                    d[u] --;
                    u = fa[u];
                }
            }
        }
        return p;
    }

    // 注意 p 的下标是从 0 开始
    // 返回的 fa 数组是从 1 开始
    vector<int> getTree(vector<int>& p) {
        int n = p.size() + 2;
        vector<int> d(n + 1, 1);
        for (auto v : p) {
            d[v] ++;
        }
        vector<int> fa(n + 1, 0);
        for (int i = 1,j=0;i<=n&&j<p.size();i++) {
            if (d[i] == 1) {
                fa[i] = p[j];
                d[i] --; d[p[j]] --;
                int u = p[j]; j ++;
                while (d[u] == 1&&j<p.size()&&u<i+1) {
                    fa[u] = p[j];
                    d[u] --; d[p[j]] --;
                    u = p[j]; j ++;
                }
            }
        }
        for (int i = 1;i<n;i++) {
            if (d[i] == 1) {
                fa[i] = n;
                break;
            }
        }
        return fa;
    }
} solver;"\n"
```

Tarjan.cpp

```
#include <bits/stdc++.h>
using namespace std;
#define DEBUG 1
```

```cpp
using ll = long long;
using pii = pair<int,int>;
using i128 = __int128_t;
using pll = pair<ll,ll>;
const ll N = 2000000;
const ll INF = 5e18;
const ll MOD = 1e9 + 7;

// inde 数组存的是合并后的新点编号
// 记得补充 info 的合并函数 !!!
// 其实 info 的合并完全可以写在外部，内部只实现一个缩点
// 默认建立正向边的啊
struct Tarjan {
    struct Info {
        Info() {

        }
    };
    int tot, idx;
    vector<int> dfn, low, s, inde;
    vector<vector<int>> e;
    vector<bool> vis;
    vector<Info> infos;
    void tarjan(int u, vector<vector<int>>& g) {
        dfn[u] = low[u] = ++idx;
        s.push_back(u);
        vis[u] = 1;
        for (auto v : g[u]) {
            if (!dfn[v]) {
                tarjan(v, g);
                low[u] = min(low[u], low[v]);
            } else if (vis[v]) {
                low[u] = min(low[u], dfn[v]);
            }
        }
        if (low[u] == dfn[u]) {
            tot ++;
            infos.push_back(Info());
            while (1) {
                inde[s.back()] = tot;
                // info merge

                if (s.back() == u) {
                    vis[s.back()] = 0;
                    s.pop_back();
                    break;
                }
                vis[s.back()] = 0;
                s.pop_back();
            }
        }
        return;
    }
    void init(vector<vector<int>>& g) {
```

```
        int n = g.size() - 1;
        idx = tot = 0;
        vector<int>().swap(dfn);
        dfn.resize(n + 1, 0);
        vector<int>().swap(low);
        low.resize(n + 1, 0);
        vector<int>().swap(inde);
        inde.resize(n + 1, 0);
        vector<bool>().swap(vis);
        vis.resize(n + 1, 0);
        vector<Info>().swap(infos);
        infos.resize(1, Info());
        vector<vector<int>>().swap(e);
        e.resize(n + 1);

        for (int i = 1;i<=n;i++) {
            if (!dfn[i]) {
                tarjan(i, g);
            }
        }

        for (int i = 1;i<=n;i++) {
            for (auto v : g[i]) {
                if (inde[v] == inde[i]) continue;
                e[inde[i]].push_back(inde[v]);
            }
        }
        return;
    }
} solver;"\n"
```

图.cpp

```
#include <bits/stdc++.h>
using namespace std;

typedef long long ll;
const ll N = 2000000;

// 尤其注意初始化 Graph 类的时候边的数量要分配够,双向边开两倍!!!

template<typename T>
class Graph{
public:
    int n,m;
    struct Edge{
        int next,to;
        T w;
    };
    vector<Edge> edge;
    vector<int> head;
```

```
    int cnt;
    void add(int u,int v,T w){
        edge[++cnt].next = head[u];
        head[u] = cnt;
        edge[cnt].to = v;
        edge[cnt].w = w;
    }
    void init(int N,int M){
        n = N; m = M;
        head.clear();
        head.resize(n+1,0);
        edge.clear();
        edge.resize(M + 1);
        cnt = 0;
        return;
    }
};"\n"
```

斯坦纳树.cpp

```
#include <bits/stdc++.h>
using namespace std;

typedef long long ll;
const ll N = 2000000;

template<typename T>
class Graph{
public:
    int n,m;
    struct Edge{
        int next,to;
        T w;
    };
    vector<Edge> edge;
    vector<int> head;
    int cnt;
    void add(int u,int v,T w){
        edge[++cnt].next = head[u];
        head[u] = cnt;
        edge[cnt].to = v;
        edge[cnt].w = w;
    }
    void init(int N,int M){
        n = N; m = M;
        head.clear();
        head.resize(n+1,0);
        Edge.clear();
        Edge.resize(M + 1);
        cnt = 0;
        return;
```

```
    }
};

template<typename T>
class SteinerTree {
public:
    Graph<T>* g;
    int n, k;
    vector<int> spe;
    vector<vector<T>> dp;
    vector<T> dist;
    vector<bool> vis;

    void init(Graph<T>* _g, const vector<int>& _spe) {
        g = _g; n = _g->n; k = _spe.size(); spe = _spe;
        int U = 1 << k;
        dp.assign(n+1, vector<T>(U, numeric_limits<T>::max()/4));
        dist.assign(n+1, numeric_limits<T>::max()/4);
        vis.assign(n+1, false);
        for (int i = 0; i < k; i++)
            dp[spe[i]][1<<i] = 0;
    }

    T solve() {
        int U = (1<<k) - 1;
        for (int S = 1; S <= U; S++) {
            for (int A = (S-1)&S; A; A = (A-1)&S)
                for (int i = 1; i <= n; i++)
                    dp[i][S] = min(dp[i][S], dp[i][A] + dp[i][S^A]);

            priority_queue<pair<T,int>, vector<pair<T,int>>, greater<>> pq;
            for (int i = 1; i <= n; i++) {
                dist[i] = dp[i][S];
                vis[i] = false;
                pq.emplace(dist[i], i);
            }
            while (!pq.empty()) {
                auto [d,u] = pq.top(); pq.pop();
                if (vis[u]) continue;
                vis[u] = true;
                for (int e = g->head[u]; e; e = g->edge[e].next) {
                    int v = g->edge[e].to; T w = g->edge[e].w;
                    if (dist[v] > d + w) {
                        dist[v] = d + w;
                        pq.emplace(dist[v], v);
                    }
                }
            }
            for (int i = 1; i <= n; i++)
                dp[i][S] = dist[i];
        }

        T ans = numeric_limits<T>::max()/4;
        for (int i = 1; i <= n; i++)
```

```
            ans = min(ans, dp[i][U]);
        return ans;
    }
};"\n"
```

最短路.cpp

```cpp
#include <bits/stdc++.h>
using namespace std;
typedef long long ll;

const ll N = 2000000;
const ll MOD = 998244353;
const ll MAX = 1e18;

struct ShortestPath {
    int n;
    vector<vector<int>>& g;
    struct Node {
        ll val;
        int idx;
        bool operator<(const Node& A) const {

        };
    };
    priority_queue<Node> nodes;
    void init(vector<vector<int>>& G) {
        g = G;
        int n = g.size() + 1;
    }
    void cal() {
        while (!nodes.empty()) {
            Node u = nodes.top(); nodes.pop();
            for (auto v : g[u.idx]) {

            }
        }
    }
};

template<typename T>
class Graph{
public:
    int n,m;
    struct Edge{
        int next,to;
        T w;
    };
    vector<Edge> edge;
    vector<int> head;
    int cnt;
```

```
    void add(int u,int v,T w){
        edge[++cnt].next = head[u];
        head[u] = cnt;
        edge[cnt].to = v;
        edge[cnt].w = w;
    }
    void init(int N,int M){
        n = N; m = M;
        head.clear();
        head.resize(n+1,0);
        Edge.clear();
        Edge.resize(M + 1);
        cnt = 0;
        return;
    }
};

template<typename T>
class Dijkstra{
public:
    Graph<T>* g;
    struct Node{
        int dist,idx;
        bool operator<(const Node &a) const {
            return dist > a.dist;
        }
        Node(int d,int x) {dist = d,idx = x;}
    };

    ll dist[N];
    bool vis[N];

    void dijkstra(int pos){
        priority_queue<Node> pq;
        for (int i = 1;i<g->n+1;i++){
            dist[i] = MAX;
            vis[i] = 0;
        }
        dist[pos] = 0;
        pq.push(Node(0,pos));

        while (!pq.empty()){
            int u = pq.top().idx;
            pq.pop();
            if (vis[u]){
                continue;
            }
            vis[u] = 1;
            for (int i = g->head[u];i;i = g->edge[i].next){
                int v = g->edge[i].to;
                if (dist[v] > dist[u] + g->edge[i].w){
                    dist[v] = dist[u] + g->edge[i].w;
                    if (!vis[v]){
                        pq.push(Node(dist[v],v));
```

```
                    }
                }
            }
        }
        return;
    }
};

/*
check 用于检查负环同时构造新边权
solve 输入起点,然后 dist 数组存最短路
*/

template<typename T>
class Johnson {
public:
    using ll = long long;
    Graph<T>* g;
    vector<T> h;
    vector<ll> dist;
    vector<bool> vis;

    void init(Graph<T>* G_) {
        g = G_;
        h.assign(g->n + 1, 0);
        vis.assign(g->n + 1, false);
    }

    bool check() {
        int n = g->n;
        int m = g->m;
        g->edge[0] = typename Graph<T>::Edge(); // dummy
        for (int i = 1; i <= n; i++) {
            g->add(0, i, 0); // 从虚拟源点 0 连向每个点
        }

        queue<int> q;
        vector<int> cnt(n + 2), inq(n + 2, 0);
        h.assign(n + 2, numeric_limits<T>::max() / 2);
        h[0] = 0;
        q.push(0);
        inq[0] = 1;

        while (!q.empty()) {
            int u = q.front(); q.pop();
            inq[u] = 0;
            for (int i = g->head[u]; i; i = g->edge[i].next) {
                int v = g->edge[i].to;
                T w = g->edge[i].w;
                if (h[v] > h[u] + w) {
                    h[v] = h[u] + w;
                    if (!inq[v]) {
                        q.push(v);
                        inq[v] = 1;
```

```
                        if (++cnt[v] > n) return false;
                    }
                }
            }
        }

        // 重新权重变换
        for (int u = 1; u <= n; u++) {
            for (int i = g->head[u]; i; i = g->edge[i].next) {
                int v = g->edge[i].to;
                g->edge[i].w += h[u] - h[v];
            }
        }

        return true;
    }

    void solve(int s) {
        dist.assign(g->n + 1, numeric_limits<ll>::max());
        vis.assign(g->n + 1, false);
        priority_queue<pair<ll, int>, vector<pair<ll, int>>, greater<>> q;

        dist[s] = 0;
        q.emplace(0, s);
        while (!q.empty()) {
            auto [d, u] = q.top(); q.pop();
            if (vis[u]) continue;
            vis[u] = true;
            for (int i = g->head[u]; i; i = g->edge[i].next) {
                int v = g->edge[i].to;
                T w = g->edge[i].w;
                if (dist[v] > dist[u] + w) {
                    dist[v] = dist[u] + w;
                    q.emplace(dist[v], v);
                }
            }
        }

        for (int i = 1; i <= g->n; i++) {
            if (dist[i] < numeric_limits<ll>::max() / 2) {
                dist[i] = dist[i] - h[s] + h[i];
            }
        }
    }
};"\n"
```

树哈希.cpp

```
#include <bits/stdc++.h>
using namespace std;
#define DEBUG 1
```

```
#define endl '\n'
#define FUCK if (DEBUG) cout << "fuck" << endl;
using ll = long long;
using pii = pair<int,int>;
using i128 = __int128_t;
using pll = pair<ll,ll>;
const ll N = 2000000;
const ll INF = 1e18;
const ll MOD = 1e9 + 7;

/*
定义 val[u] = 1 + f(h(val[v]))
v is son of u
*/

ll h(ll x) {
    return x * x * x * 1237123 + 19260817;
}
ll f(ll x) {
    ll cur = h(x & ((1 << 31) - 1)) + h(x >> 31);
    return cur;
}"\n"
```

树链剖分.cpp

```
#include <bits/stdc++.h>
using namespace std;
typedef long long ll;
const ll N = 2000000;

#define LS (rt << 1)
#define RS (rt << 1 | 1)

class SegTree{
public:
    struct Node{
        Node() {

        }
    }nodes[N*4];

    Node merge(Node L,Node R){
        Node M;
        return M;
    }
    void build(int rt,int l,int r){
        if (l == r){
            return;
        }
        int mid = l + r >> 1;
        build(LS,l,mid),build(RS,mid+1,r);
```

```
        nodes[rt] = merge(nodes[LS],nodes[RS]);
    }
    void pd(int rt){

    }
    void update(int rt,int l,int r,int ql,int qr,int val){
        if (ql > qr || l > qr || ql > r) return;
        if (ql <= l && r <= qr){
            return;
        }
        int mid = l+r>>1;
        pd(rt);
        if (ql <= mid){
            update(LS,l,mid,ql,qr,val);
        }
        if (qr >= mid + 1){
            update(RS,mid+1,r,ql,qr,val);
        }
        nodes[rt] = merge(nodes[LS],nodes[RS]);
        return;
    }
    void modify(int rt,int l,int r,int q,int val){
        if (l > q || r < q) return;
        if (l == r) {
            return;
        }
        int mid = l+r>>1;
        pd(rt);
        if (q <= mid){
            modify(LS,l,mid,q,val);
        }
        if (q >= mid + 1){
            modify(RS,mid+1,r,q,val);
        }
        nodes[rt] = merge(nodes[LS],nodes[RS]);
        return;
    }
    Node query(int rt,int l,int r,int ql,int qr){
        if (ql > qr) {
            return Node();
        }
        if (ql <= l && r <= qr){
            return nodes[rt];
        }
        int mid = l+r>>1;
        pd(rt);
        if (ql > mid){
            return query(RS,mid+1,r,ql,qr);
        }else if (qr < mid + 1){
            return query(LS,l,mid,ql,qr);
        }else{
            return merge(query(LS,l,mid,ql,qr),query(RS,mid+1,r,ql,qr));
        }
    }
```

```
};

struct TreeChainSeg {
    vector<vector<int>> g;
    SegTree seg;
    vector<int> fa, top, siz, son, dep, dfn, id;
    int cnt, n, cnt2;

    void dfs1(int u) {
        siz[u] = 1;
        for (auto v : g[u]) {
            if (fa[u] == v) continue;
            dep[v] = dep[u] + 1;
            fa[v] = u;
            dfs1(v);
            siz[u] += siz[v];
            if (!son[u] || siz[son[u]] < siz[v]) {
                son[u] = v;
            }
        }
        return;
    }

    void dfs2(int u, int tp) {
        id[cnt] = u;
        dfn[u] = ++cnt;
        top[u] = tp;
        if (son[u]) {
            dfs2(son[u], tp);
        }
        for (auto v : g[u]) {
            if (v == fa[u] || v == son[u]) continue;
            dfs2(v, v);
        }
        return;
    }

    void init(vector<vector<int>>& G) {
        g = G;
        n = g.size();
        cnt = 0, cnt2 = n + 1;
        fa.clear(); fa.resize(n + 1, 0);
        top.clear(); top.resize(n + 1, 0);
        siz.clear(); siz.resize(n + 1, 0);
        son.clear(); son.resize(n + 1, 0);
        dep.clear(); dep.resize(n + 1, 0);
        dfn.clear(); dfn.resize(n + 1, 0);
        id.clear(); id.resize(n + 1, 0);

        dfs1(1), dfs2(1, 1);
        seg.build(1, 1, n);
        return;
    }
```

```
    int lca(int u, int v) {
        while (top[u] != top[v]) {
            if (dep[top[u]] > dep[top[v]]) {
                u = fa[top[u]];
            } else {
                v = fa[top[v]];
            }
        }
        if (dep[u] > dep[v]) {
            return v;
        }
        return u;
    }
};
"\n"
```

流.cpp

```
#include <bits/stdc++.h>
using namespace std;
#define DEBUG 1
#define FUCK if (DEBUG) cout << "fuck" << endl;
using ll = long long;
using pii = pair<int,int>;
using i128 = __int128_t;
using pll = pair<ll,ll>;
const ll N = 2000000;
const ll INF = 5e18;
const ll MOD = 1e9 + 7;

class Graph {
public:
    int n;
    struct Edge {
        int next, to, rev;
        ll w;
    } edge[2 * N];
    int head[N];
    int cnt;

    void init(int N_) {
        n = N_;
        for (int i = 0; i <= n; i++)
            head[i] = 0;
        cnt = 0;
    }

    void add_edge(int u, int v, ll w) {
        cnt++;
        edge[cnt].to = v;
        edge[cnt].w = w;
```

```
        edge[cnt].next = head[u];
        head[u] = cnt;
        int forward_index = cnt;
        cnt++;
        edge[cnt].to = u;
        edge[cnt].w = 0;
        edge[cnt].next = head[v];
        head[v] = cnt;
        int reverse_index = cnt;
        edge[forward_index].rev = reverse_index;
        edge[reverse_index].rev = forward_index;
    }
} g;

class Dinic {
private:
    Graph* G;
    int s, t;
    vector<ll> d;
    vector<int> cur;

    bool bfs() {
        fill(d.begin(), d.end(), -1);
        queue<int> q;
        d[s] = 0;
        q.push(s);
        while (!q.empty()) {
            int u = q.front(); q.pop();
            for (int i = G->head[u]; i; i = G->edge[i].next) {
                int v = G->edge[i].to;
                if (d[v] < 0 && G->edge[i].w > 0) {
                    d[v] = d[u] + 1;
                    q.push(v);
                }
            }
        }
        return d[t] >= 0;
    }

    ll dfs(int u, ll flow) {
        if (u == t) return flow;
        for (int &i = cur[u]; i; i = G->edge[i].next) {
            int v = G->edge[i].to;
            if (d[v] == d[u] + 1 && G->edge[i].w > 0) {
                ll pushed = dfs(v, min(flow, G->edge[i].w));
                if (pushed) {
                    G->edge[i].w -= pushed;
                    G->edge[G->edge[i].rev].w += pushed;
                    return pushed;
                }
            }
        }
        return 0;
    }
```

```
public:
    Dinic(Graph* graph, int source, int sink) : G(graph), s(source), t(sink) {
        d.resize(G->n + 1);
        cur.resize(G->n + 1);
    }

    ll max_flow() {
        ll flow = 0;
        while (bfs()) {
            for (int i = 0; i <= G->n; i++)
                cur[i] = G->head[i];
            while (ll pushed = dfs(s, INF))
                flow += pushed;
        }
        return flow;
    }
};

template<typename T>
class MinCostMaxFlow {
public:
    struct Edge {
        int next, to;
        T w, c;
    };

    int n,cnt;
    vector<Edge> edge;
    vector<T> dis,flow;
    vector<int> pre,last,head;
    vector<bool> vis;


    MinCostMaxFlow(int n, int edgeCapacity = 4000000) : n(n) {
        head.assign(n + 1, 0);
        edge.resize(edgeCapacity + 1);
        cnt = 1;
        dis.assign(n + 1, 0);
        pre.assign(n + 1, -1);
        last.assign(n + 1, 0);
        flow.assign(n + 1, 0);
        vis.assign(n + 1, false);
    }

    void init(int n) {
        this->n = n;
        fill(head.begin(), head.end(), 0);
        cnt = 1;
    }

    void addEdge(int u, int v, T w,T c) {
        edge[++cnt] = { head[u], v, w, c };
        head[u] = cnt;
```

```
        edge[++cnt] = { head[v], u, 0, -c };
        head[v] = cnt;
    }

    bool spfa(int s, int t) {
        const int INF = 0x3f3f3f3f;
        fill(dis.begin(), dis.end(), INF);
        fill(flow.begin(), flow.end(), INF);
        fill(vis.begin(), vis.end(), false);
        fill(pre.begin(), pre.end(), -1);

        queue<int> q;
        q.push(s);
        vis[s] = true;
        dis[s] = 0;
        flow[s] = INF;

        while (!q.empty()) {
            int u = q.front();
            q.pop();
            vis[u] = false;
            for (int i = head[u]; i; i = edge[i].next) {
                int v = edge[i].to;
                if (edge[i].w > 0 && dis[v] > dis[u] + edge[i].c) {
                    dis[v] = dis[u] + edge[i].c;
                    pre[v] = u;
                    last[v] = i;
                    flow[v] = min(flow[u], edge[i].w);
                    if (!vis[v]) {
                        q.push(v);
                        vis[v] = true;
                    }
                }
            }
        }
        return pre[t] != -1;
    }

    pair<T, T> run(int s, int t) {
        T maxFlow = 0, minCost = 0;
        while (spfa(s, t)) {
            int f = flow[t];
            maxFlow += f;
            minCost += f * dis[t];
            for (int u = t; u != s; u = pre[u]) {
                int i = last[u];
                edge[i].w -= f;
                edge[i ^ 1].w += f;
            }
        }
        return { maxFlow, minCost };
    }
};
```

```cpp
// 有源汇上下界最大流
// add(S, E, L, R) 插入边
// solve(S, E) 输出最大流, -1 表示无解!!!
namespace MCMF{
    const int MAXN = 100000 + 3;
    const int MAXM = 700000 + 3; // 增大上界，避免边数超界
    int H[MAXN], V[MAXM], N[MAXM];
    ll F[MAXM]; // 改为 ll
    int o = 1, n;
    void add0(int u, int v, ll f){
        V[++ o] = v; N[o] = H[u]; H[u] = o; F[o] = f;
        V[++ o] = u; N[o] = H[v]; H[v] = o; F[o] = 0;
        n = max(n, u);
        n = max(n, v);
    }
    ll D[MAXN];
    bool bfs(int s, int t){
        queue <int> Q;
        for(int i = 1;i <= n;++ i) D[i] = 0;
        Q.push(s); D[s] = 1;
        while(!Q.empty()){
            int u = Q.front(); Q.pop();
            for(int i = H[u]; i; i = N[i]){
                int v = V[i];
                ll cap = F[i];
                if(cap != 0 && !D[v]){
                    D[v] = D[u] + 1;
                    Q.push(v);
                }
            }
        }
        return D[t] != 0;
    }
    int C[MAXN];
    ll dfs(int s, int t, int u, ll maxf){
        if(u == t) return maxf;
        ll totf = 0;
        for(int &i = C[u]; i; i = N[i]){
            int v = V[i];
            ll cap = F[i];
            if(cap && D[v] == D[u] + 1){
                ll pushed = dfs(s, t, v, min(F[i], maxf));
                if(pushed == 0) continue;
                F[i] -= pushed;
                F[i ^ 1] += pushed;
                totf += pushed;
                maxf -= pushed;
                if(maxf == 0) return totf;
            }
        }
        return totf;
    }
    ll mcmf(int s, int t){
```

```
        ll ans = 0;
        while(bfs(s, t)){
            memcpy(C, H, sizeof(H));
            ans += dfs(s, t, s, (ll)1e18);
        }
        return ans;
    }
    ll G[MAXN];
    void add(int u, int v, ll l, ll r){
        G[v] += l;
        G[u] -= l;
        add0(u, v, r - l);
    }
    void clear(){
        for(int i = 1;i <= o;++ i){
            N[i] = 0; F[i] = 0; V[i] = 0;
        }
        for(int i = 1;i <= n;++ i){
            H[i] = 0; G[i] = 0; C[i] = 0;
        }
        o = 1; n = 0;
    }
    bool solve(){ // 无源汇可行性检查
        int s = ++ n;
        int t = ++ n;
        ll sum = 0;
        for(int i = 1;i <= n - 2;++ i){
            if(G[i] < 0) add0(i, t, -G[i]);
            else add0(s, i,  G[i]), sum += G[i];
        }
        auto res = mcmf(s, t);
        if(res != sum) return false;
        return true;
    }
    ll solve(int s0, int t0){ // 有源汇上下界最大流
        add0(t0, s0, (ll)1e18);
        int s = ++ n;
        int t = ++ n;
        ll sum = 0;
        for(int i = 1;i <= n - 2;++ i){
            if(G[i] < 0) add0(i, t, -G[i]);
            else add0(s, i,  G[i]), sum += G[i];
        }
        auto res = mcmf(s, t);
        if(res != sum) return -1;
        return mcmf(s0, t0);
    }
}"\n"
```

点分治.cpp

```cpp
#include <bits/stdc++.h>
using namespace std;
#define DEBUG 1
using ll = long long;
using pii = pair<int,int>;
using i128 = __int128_t;
using pll = pair<ll,ll>;
const ll N = 2000000;
const ll INF = 5e18;
const ll MOD = 1e9 + 7;

// 传入一颗树，返回对应的点分树，已删去指向父亲的边!! 入度为 0 的就是根
vector<vector<int>> CentroidTree(vector<vector<int>>&g) {
    int n = g.size() - 1;
    vector<vector<int>> e(n + 1);
    vector<bool> bad(n + 1, 0);
    vector<int> siz(n + 1, 0);
    auto getCenter = [&](int u, int tot) -> int {
        int mn = n + 1, res;
        auto dfs = [&](auto&&self, int u, int f) -> void {
            int val = 1;
            siz[u] = 1;
            for (auto v : g[u]) {
                if (v == f || bad[v]) continue;
                self(self, v, u);
                siz[u] += siz[v];
                val = max(val, siz[v]);
            }
            val = max(val, tot - siz[u]);
            if (val < mn) {
                mn = val;
                res = u;
            }
            return;
        };
        dfs(dfs, u, u);
        return res;
    };
    auto getSiz = [&](auto&&self, int u, int f) -> int {
        int res = 1;
        for (auto v : g[u]) {
            if (v == f || bad[v]) continue;
            res += self(self, v, u);
        }
        return res;
    };
    vector<int> roots;
    int rt = getCenter(1, n);
    roots.push_back(rt);
    while (!roots.empty()) {
        rt = roots.back(); roots.pop_back();
        bad[rt] = 1;
```

```
        for (auto v : g[rt]) {
            if (bad[v]) continue;
            v = getCenter(v, getSiz(getSiz, v, v));
            e[rt].push_back(v);
            roots.push_back(v);
        }
    }
    return e;
};
"\n"
```

矩阵树定理.cpp

```
#define DEBUG 0
#define FUCK cout << "fuck" << endl;
#if DEBUG
    #include "all.hpp"
#else
    #include <bits/stdc++.h>
#endif

using namespace std;
using ll = long long;
using pii = pair<int,int>;
using pll = pair<ll,ll>;
using db = long double;
using pdd = pair<db, db>;
using i128 = __int128_t;

const ll N = 2000000;
const ll INF = 5e18;
const ll MOD = 1e9 + 7;

/*
opt = 0, 无向图
opt = 1, 外向有向
opt = 2, 内向有向
g: u, v, w
删除 A 中根所在的行列再求行列式
高斯消元交换行要乘 -1
*/

#define MOD(x) (x = (x % MOD + MOD) % MOD)
ll qpow(ll base,ll k,ll mod) {
    if (base == 0) return 0;
    ll res = 1;
    base %= mod; base = (base + mod) % mod;
    k %= (mod - 1); k = (k + mod - 1) % (mod - 1);
    while (k) {
        if (k & 1) {
            res *= base; res %= mod;
```

```
        }
        k >>= 1;
        base *= base; base %= mod;
    }
    return res;
}
ll A[2000 + 10][2000 + 10], P[2000 + 10][2000 + 10];
ll cal(int n, int rt, vector<array<int, 3>>& g, int opt) {
    ll ans = 0;
    for (int i = 1;i<=n;i++) {
        for (int j = 1;j<=n;j++) {
            A[i][j] = P[i][j] = 0;
        }
    }
    if (opt == 0) {
        for (auto [u, v, w] : g) {
            A[u][u] += w; A[v][v] += w;
            MOD(A[u][u]); MOD(A[v][v]);
            A[u][v] -= w; A[v][u] -= w;
            MOD(A[u][v]); MOD(A[v][u]);
        }
    } else if (opt == 1) {
        for (auto [u, v, w] : g) {
            A[v][v] += w; MOD(A[v][v]);
            A[u][v] -= w; MOD(A[u][v]);
        }
    } else {
        for (auto [u, v, w] : g) {
            A[u][u] += w; MOD(A[u][u]);
            A[u][v] -= w; MOD(A[u][v]);
        }
    }
    for (int i = 1, I = 1;i<=n;i++) {
        if (i == rt) continue;
        for (int j = 1, J = 1;j<=n;j++) {
            if (j == rt) continue;
            P[I][J] = A[i][j];
            J ++;
        }
        I ++;
    }
    int cnt = 0;
    for (int i = 1;i<=n-1;i++) {
        if (P[i][i] == 0) {
            cnt ^= 1;
            for (int j = i + 1;j<=n-1;j++) {
                if (P[j][i] != 0) {
                    swap(P[i], P[j]);
                    break;
                }
            }
        }
        for (int j = i + 1;j<=n-1;j++) {
            ll z = P[j][i] * qpow(P[i][i], MOD - 2, MOD) % MOD;
```

```
            for (int k = i;k<=n-1;k++) {
                P[j][k] -= z * P[i][k] % MOD;
                P[j][k] = (P[j][k] + MOD) % MOD;
            }
        }
    }
    ans = 1;
    for (int i = 1;i<=n-1;i++) {
        ans = ans * P[i][i] % MOD;
    }
    if (cnt) {
        ans = (-ans + MOD) % MOD;
    }
    return ans;
}

"\n"
```

虚树.cpp

```
#define DEBUG 1
#define FUCK cout << "fuck" << endl;
#if DEBUG
    #include "all.hpp"
#else
    #include <bits/stdc++.h>
#endif

using namespace std;
using ll = long long;
using pii = pair<int,int>;
using pll = pair<ll,ll>;
using db = long double;
using pdd = pair<db, db>;

const ll N = 2000000;
const ll INF = 5e18;
const ll MOD = 1e9 + 7;

/*
虚树的建立需要依靠 lca，这里写的是 O(1) lca
有时，虚树需要额外插入根节点，才能保证 dp 的正确性
*/

class Lca {
public:
    vector<vector<int>>* g;
    vector<int> depth, first, euler;
    vector<ll> dist;
    vector<vector<int>> st;
    int lg[2 * N];
```

```
    void init(vector<vector<int>>* graph, int root) {
        g = graph;
        euler.clear();
        depth.clear();
        dist.clear();
        dist.resize(g->size());
        first.assign(g->size(), -1);
        dfs(root, 0, 0, 0);
        build_st();
    }

    void dfs(int u, int fa, int d, ll sum) {
        first[u] = euler.size();
        euler.push_back(u);
        depth.push_back(d);
        dist[u] = sum;
        for (auto v : (*g)[u]) {
            if (v == fa) continue;
            dfs(v, u, d + 1, sum + 1); // 默认边权是 1
            euler.push_back(u);
            depth.push_back(d);
        }
    }

    void build_st() {
        int m = euler.size();
        int k = __lg(m) + 1;
        st.assign(k, vector<int>(m));
        for (int i = 0; i < m; ++i) st[0][i] = i;
        for (int i = 2; i < m + 5; ++i) lg[i] = lg[i >> 1] + 1;
        for (int j = 1; (1 << j) <= m; ++j)
            for (int i = 0; i + (1 << j) <= m; ++i) {
                int l = st[j - 1][i], r = st[j - 1][i + (1 << (j - 1))];
                st[j][i] = (depth[l] < depth[r] ? l : r);
            }
    }

    int lca(int u, int v) {
        int l = first[u], r = first[v];
        if (l > r) swap(l, r);
        int j = lg[r - l + 1];
        int a = st[j][l], b = st[j][r - (1 << j) + 1];
        return euler[depth[a] < depth[b] ? a : b];
    }

    int query(int u,int v) {
        int LCA = lca(u,v);
        return dist[u] + dist[v] - 2 * dist[LCA];
    }
} solver;

void solve() {
    int n; cin >> n;
```

```
    vector<vector<int>> g(n + 1);
    for (int i = 1;i<n;i++) {
        int u, v; cin >> u >> v;
        g[u].push_back(v);
        g[v].push_back(u);
    }
    solver.init(&g, 1);
    vector<int> dfn(n + 1, 0);
    int cntDfn = 0;
    auto dfs0 = [&](auto&&self, int u, int f) -> void {
        dfn[u] = ++cntDfn;
        for (auto v : g[u]) {
            if (v == f) continue;
            self(self, v, u);
        }
    };
    dfs0(dfs0, 1, -1);

    vector<int> spe;
    // 插入特殊点
    sort(spe.begin(), spe.end(), [&](int x, int y){
        return dfn[x] < dfn[y];
    });
    int sz = spe.size();
    for (int i = 0;i+1<sz;i++) {
        spe.push_back(solver.lca(spe[i], spe[i + 1]));
    }
    sort(spe.begin(), spe.end(), [&](int x, int y){
        return dfn[x] < dfn[y];
    });
    spe.erase(unique(spe.begin(), spe.end()), spe.end());
    vector<vector<int>> e(n + 1); // 虚树
    for (int i = 0;i+1<spe.size();i++) {
        int lca = solver.lca(spe[i], spe[i + 1]);
        e[lca].push_back(spe[i + 1]);
    }
    return;
}

signed main() {
#if DEBUG
    freopen("input.txt", "r", stdin);
    auto start_time = chrono::steady_clock::now();
#else
    ios::sync_with_stdio(false);
#endif
    cin.tie(nullptr);

    int t = 1;
    cin >> t;

    while (t--) {
        solve();
    }
```

```
#if DEBUG
    auto end_time = chrono::steady_clock::now();
    auto diff = chrono::duration_cast<chrono::milliseconds>(end_time -
start_time);
    cerr << "Time: " << diff.count() << " ms" << endl;

#endif

    return 0;
}
"\n"
```

BGSG.cpp

```
#include <bits/stdc++.h>
using namespace std;
#define DEBUG 1
using ll = long long;
using pii = pair<int,int>;
using i128 = __int128_t;
using pll = pair<ll,ll>;
const ll N = 2000000;
const ll INF = 5e18;
const ll MOD = 1e9 + 7;

// 调用 cal(a, n, p) 输出 (a^x = n) % p
// 复杂度 sqrt(p) * log
struct ExBSGS {
    static ll modpow(ll a, ll e, ll mod){
        ll r = 1;
        a %= mod;
        while(e){
            if(e & 1) r = (i128)r * a % mod;
            a = (i128)a * a % mod;
            e >>= 1;
        }
        return r;
    }
    static ll exgcd(ll a, ll b, ll &x, ll &y){
        if(b == 0){ x = 1; y = 0; return a; }
        ll x1, y1;
        ll g = exgcd(b, a % b, x1, y1);
        x = y1;
        y = x1 - a / b * y1;
        return g;
    }
    static ll invmod(ll a, ll mod){
        ll x, y;
        ll g = exgcd(a, mod, x, y);
        if(g != 1) return -1;
```

```
        x %= mod;
        if(x < 0) x += mod;
        return x;
    }
    static ll bsgs(ll a, ll b, ll mod){
        a %= mod; b %= mod;
        if(mod == 1) return 0;
        ll m = (ll)ceil(sqrt((double)mod));
        unordered_map<ll, ll> mp;
        mp.reserve(m * 2);
        ll aj = 1;
        for(ll j = 0; j < m; ++j){
            if(mp.find(aj) == mp.end()) mp[aj] = j;
            aj = (i128)aj * a % mod;
        }
        ll factor = modpow(a, m, mod);
        ll invfactor = invmod(factor, mod);
        if(invfactor == -1) return -1;
        ll cur = b % mod;
        for(ll i = 0; i <= m; ++i){
            auto it = mp.find(cur);
            if(it != mp.end()){
                return i * m + it->second;
            }
            cur = (i128)cur * invfactor % mod;
        }
        return -1;
    }
    static ll cal(ll a, ll n, ll p){
        if(p == 1) return 0;
        a %= p; n %= p;
        if(n == 1) return 0;
        ll cnt = 0;
        ll t = 1;
        ll g;
        while((g = std::gcd(a, p)) > 1){
            if(n == t) return cnt;
            if(n % g != 0) return -1;
            p /= g;
            n /= g;
            t = (i128)t * (a / g) % p;
            ++cnt;
        }
        ll invt = invmod(t, p);
        if(invt == -1) return -1;
        ll rhs = (i128)n * invt % p;
        ll res = bsgs(a, rhs, p);
        if(res == -1) return -1;
        return res + cnt;
    }
};
"\n"
```

Complex3.cpp

```cpp
#define DEBUG 1
#define FUCK cout << "fuck" << endl;
#if DEBUG
    #include "all.hpp"
#else
    #include <bits/stdc++.h>
#endif

using namespace std;
using ll = long long;
using pii = pair<int,int>;
using pll = pair<ll,ll>;
using db = long double;
using pdd = pair<db, db>;
using i128 = __int128_t;

const ll N = 2000000;
const ll INF = 5e18;
const ll MOD = 998244353;

ll qpow(ll base,ll k,ll mod) {
    if (base == 0) return 0;
    ll res = 1;
    base %= mod; base = (base + mod) % mod;
    k %= (mod - 1); k = (k + mod - 1) % (mod - 1);
    while (k) {
        if (k & 1) {
            res *= base; res %= mod;
        }
        k >>= 1;
        base *= base; base %= mod;
    }
    return res;
}

#define MMOD(x) ((x % MOD + MOD) % MOD)
struct Complex3 {
    ll x, y;
    Complex3(ll X_ = 0, ll Y_ = 0) {
        x = X_, y = Y_;
    }
    Complex3 operator+(const Complex3& z) const {
        return {MMOD(x + z.x), MMOD(y + z.y)};
    }
    Complex3 operator-(const Complex3& z) const {
        return {MMOD(x - z.x), MMOD(y - z.y)};
    }
    Complex3 operator*(const Complex3& z) const {
        ll a = x, b = y, c = z.x, d = z.y;
        return {MMOD(a*c%MOD - b*d%MOD), MMOD(a*d%MOD + b*c%MOD - b*d%MOD)};
```

```
    }
    Complex3 inv() const {
        ll a = x, b = y;
        ll n = a*a - a*b + b*b;
        n = MMOD(n);
        n = qpow(n, MOD - 2, MOD);
        return {MMOD((a - b) * n), MMOD((-b) * n)};
    }
    Complex3 operator/(const Complex3& z) const {
        return (*this) * z.inv();
    }
    bool operator==(const Complex3& z) const {
        return x == z.x && y == z.y;
    }
    Complex3 operator*(const ll& z) const {
        return Complex3(MMOD(x * z), MMOD(y * z));
    }
};
using Z = Complex3;"\n"
```

Crt.cpp

```
/*
功能简短说明：
1. 输入：两个 `(r,m)` 分别表示 `x ≡ r (mod m)`；建议 `m>0` 且 `0≤r<m`。
2. 支持 **模不互质** 的情况（会处理公约数）。
3. 输出：若有解返回 `(r,M)`，表示所有解为 `x = r + k*M`（`k∈Z`），且 `0 ≤ r < M`；若无解返回 `(-1,-1)`。
4. 合并规则：如果方程组相容（即 `r2-r1` 能被 `g = gcd(m1,m2)` 整除），则合并得到模 `M = m1 * (m2 / g)`，并计算最小非负解 `r`。
5. 算法要点：用扩展欧几里得求 `g` 和系数 `x,y`，检查 `(r2-r1)%g==0`，计算位移 `t = (r2-r1)/g * x (mod m2/g)`，再算出 `r = (r1 + m1*t) mod M`。实现中用 `__int128` 防止乘法溢出。
   示例：`(2,3)` 与 `(3,5)` 合并得 `(8,15)`，因为解集是 `x ≡ 8 (mod 15)`。
*/
#include <bits/stdc++.h>
using namespace std;
using ll = long long;
using i128 = __int128;
using pii = pair<int,int>;
using pll = pair<ll,ll>;
ll exgcd(ll a,ll b,ll &x,ll &y){
    if(b==0){x=1;y=0;return a;}
    ll x1,y1; ll g=exgcd(b,a%b,x1,y1);
    x=y1; y=x1-(a/b)*y1; return g;
}
pll crt(pll A,pll B){
    ll r1=A.first,m1=A.second,r2=B.first,m2=B.second;
    if(m1<=0||m2<=0) return {-1,-1};
    r1%=m1; if(r1<0) r1+=m1;
    r2%=m2; if(r2<0) r2+=m2;
```

```
    ll x,y; ll g=exgcd(m1,m2,x,y);
    ll d=r2-r1; if(d%g!=0) return {-1,-1};
    i128 t=(i128)(d/g)*(i128)x;
    i128 mod2=m2/g; t%=mod2; if(t<0) t+=mod2;
    i128 M=(i128)m1*mod2;
    i128 res=((i128)r1 + (i128)m1 * t) % M; if(res<0) res+=M;
    return {(ll)res,(ll)M};
}
pll crt_many(const vector<pll>& v){
    if(v.empty()) return {0,1};
    pll cur = v[0];
    for(size_t i=1;i<v.size();++i){
        cur = crt(cur,v[i]);
        if(cur.first==-1) return cur;
    }
    return cur;
}
ll inv_mod(ll a, ll b){
    ll x, y;
    ll g = exgcd(a, b, x, y);
    if(g != 1) return -1;
    x %= b;
    if(x < 0) x += b;
    return x;
}
int main(){
    ios::sync_with_stdio(false);
    cin.tie(nullptr);
    int n; if(!(cin>>n)) return 0;
    vector<pll> v; v.reserve(n);
    for(int i=0;i<n;++i){ ll r,m; cin>>r>>m; v.emplace_back(r,m); }
    auto ans = crt_many(v);
    cout<<ans.first<<" "<<ans.second<<"\n";
    return 0;
}
"\n"
```

Int128.cpp

```
#include <bits/stdc++.h>
using namespace std;

typedef __int128 int128;

// 快速读入 __int128
int128 readInt128() {
    int128 n = 0;
    bool negative = false;
    char c = getchar();
    while (c < '0' || c > '9') {
        if (c == '-') negative = true;
```

```
        c = getchar();
    }
    while (c >= '0' && c <= '9') {
        n = n * 10 + (c - '0');
        c = getchar();
    }
    return negative ? -n : n;
}

// 快速输出 __int128
void printInt128(int128 n) {
    if (n < 0) {
        putchar('-');
        n = -n;
    }
    if (n == 0) {
        putchar('0');
        return;
    }
    char buffer[100];
    int bufferIndex = 0;
    while (n > 0) {
        buffer[bufferIndex++] = (n % 10) + '0';
        n /= 10;
    }
    while (bufferIndex > 0) {
        putchar(buffer[--bufferIndex]);
    }
}

using i128 = __int128_t;
// 判断 i128 右移 s 位会不会溢出
bool check (i128 x, int s) {
    if (x == 0) return true;
    unsigned __int128 ux = x < 0 ? -(unsigned __int128)x : (unsigned __int128)x;
    if (s >= 127) return ux == 0;
    unsigned __int128 pos_limit = ((((unsigned __int128)1) << 127) - 1) >> s;
    unsigned __int128 neg_limit = (((unsigned __int128)1) << 127) >> s;
    if (x < 0) return ux <= neg_limit;
    else return ux <= pos_limit;
};"\n"
```

Lucas.cpp

```
#include <bits/stdc++.h>
using namespace std;
#define DEBUG 1
using ll = long long;
using pii = pair<int,int>;
using i128 = __int128_t;
using pll = pair<ll,ll>;
```

```
const ll N = 2000000;
const ll INF = 5e18;
const ll MOD = 1e9 + 7;

ll qpow(ll base,ll k,ll mod) {
    ll res = 1;
    if (k < 0) {
        return qpow(qpow(base,-k,mod),mod-2,mod);
    }
    while (k) {
        if (k & 1) {
            res *= base; res %= mod;
        }
        k >>= 1;
        base *= base; base %= mod;
    }
    return res;
}

// cal 函数是用于调用的接口, C 函数是内部使用的!!!
struct Lucas {
    int p;
    vector<int> fact;
    vector<int> inv;
    void init(int P_) {
        p = P_;
        fact.resize(p);
        inv.resize(p);
        fact[0] = 1;
        for (int i = 1;i<p;i++) {
            fact[i] = 1ll * fact[i - 1] * i % p;
        }
        vector<ll> pre(p, 1), suf(p, 1);
        for (int i = 1;i<p;i++) {
            pre[i] = pre[i - 1] * fact[i] % p;
        }
        suf[p - 1] = p - 1;
        for (int i = p - 2;i>=1;i--) {
            suf[i] = suf[i + 1] * fact[i] % p;
        }
        ll base = qpow(pre.back(), p - 2, p);
        inv[0] = 1;
        for (int i = 1;i<p;i++) {
            if (i + 1 < p) {
                inv[i] = pre[i - 1] * suf[i + 1] % p;
            } else {
                inv[i] = pre[i - 1];
            }
            inv[i] = inv[i] * base % p;
        }
    }
    int C(int n, int m) {
        if (m > n) return 0;
        return 1ll * fact[n] * inv[n - m] % p * inv[m] % p;
```

```
    }
    int cal(int n, int m) {
        if (m > n) return 0;
        if (n < p && m < p) {
            return C(n, m);
        }
        return 1ll * cal(n / p, m / p) * C(n % p, m % p) % p;
    }
} solver;

// 这个 C 真的是接口了
struct ExLucas {
    ll mod = 1;
    vector<ll> p, e, pk, prod;
    void init(ll M) {
        mod = M;
        ll x = M;
        for (ll i = 2; i * i <= x; i++) if (x % i == 0) {
            ll cnt = 0, pw = 1;
            while (x % i == 0) { x /= i; cnt++; pw *= i; }
            p.push_back(i); e.push_back(cnt); pk.push_back(pw);
        }
        if (x > 1) { p.push_back(x); e.push_back(1); pk.push_back(x); }
        prod.resize(pk.size());
        for (size_t idx = 0; idx < pk.size(); ++idx) {
            ll P = p[idx], PK = pk[idx], pr = 1;
            for (ll i = 1; i <= PK; i++) if (i % P) pr = (i128)pr * i % PK;
            prod[idx] = pr;
        }
    }
    ll modpow(ll a, ll b, ll m) {
        ll r = 1 % m;
        a %= m;
        while (b) {
            if (b & 1) r = (i128)r * a % m;
            a = (i128)a * a % m;
            b >>= 1;
        }
        return r;
    }
    ll exgcd(ll a, ll b, ll &x, ll &y) {
        if (b == 0) { x = 1; y = 0; return a; }
        ll x1, y1; ll g = exgcd(b, a % b, x1, y1);
        x = y1; y = x1 - (a / b) * y1; return g;
    }
    ll invmod(ll a, ll m) { ll x, y; ll g = exgcd((a % m + m) % m, m, x, y);
return g == 1 ? (x % m + m) % m : -1; }
    ll vp(ll n, ll P) { ll cnt = 0; while (n) { n /= P; cnt += n; } return cnt; }
    ll fac_mod(ll n, ll idx) {
        ll P = p[idx], PK = pk[idx], PR = prod[idx];
        if (n == 0) return 1 % PK;
        ll res = modpow(PR, n / PK, PK);
        for (ll i = 1; i <= n % PK; i++) if (i % P) res = (i128)res * i % PK;
        return (i128)res * fac_mod(n / P, idx) % PK;
```

```
    }
    ll C_mod_pk(ll n, ll m, ll idx) {
        if (m < 0 || m > n) return 0;
        ll P = p[idx], PK = pk[idx], K = e[idx];
        ll cnt = vp(n, P) - vp(m, P) - vp(n - m, P);
        if (cnt >= K) return 0;
        ll a = fac_mod(n, idx);
        ll b = fac_mod(m, idx) * fac_mod(n - m, idx) % PK;
        ll ib = invmod(b, PK);
        ll res = (i128)a * ib % PK;
        res = (i128)res * modpow(P, cnt, PK) % PK;
        return res;
    }
    ll C(ll n, ll m) {
        if (m < 0 || m > n) return 0;
        int sz = pk.size();
        if (sz == 0) return 1 % mod;
        vector<ll> r(sz);
        for (int i = 0; i < sz; i++) r[i] = C_mod_pk(n, m, i);
        ll M = mod, x = 0;
        for (int i = 0; i < sz; i++) {
            ll mi = pk[i], ai = r[i];
            ll Mi = M / mi;
            ll ti = invmod(Mi % mi, mi);
            x = (x + (i128)ai * Mi % M * ti) % M;
        }
        return (x % M + M) % M;
    }
};"\n"
```

O(1)gcd.cpp

```
#define DEBUG 1
#define FUCK cout << "fuck" << endl;
#if DEBUG
    #include "all.hpp"
#else
    #include <bits/stdc++.h>
#endif

using namespace std;
using ll = long long;
using pii = pair<int,int>;
using pll = pair<ll,ll>;
using db = long double;
using pdd = pair<db, db>;
using i128 = __int128_t;

const ll N = 2000000;
const ll INF = 5e18;
const ll MOD = 1e9 + 7;
```

```
// 先调用 init 函数！！！
// 复杂度是线性的！！！

namespace quickGcd {
    const int M = 1000000;
    const int T = 1000;

    int pre[T + 1][T + 1];
    int fac[M + 1][3];
    int pri[M / 10], tot;
    bool not_p[M + 1];

    // 预处理函数：在线性筛的基础上进行因子分解和GCD表制作
    void init() {
        for (int i = 0; i <= T; ++i) {
            pre[i][0] = pre[0][i] = i;
            for (int j = 1; j <= i; ++j)
                pre[i][j] = pre[j][i] = pre[j][i % j];
        }

        fac[1][0] = fac[1][1] = fac[1][2] = 1;
        for (int i = 2; i <= M; ++i) {
            if (!not_p[i]) {
                pri[++tot] = i;
                fac[i][0] = fac[i][1] = 1;
                fac[i][2] = i;
            }
            for (int j = 1; j <= tot && i * pri[j] <= M; ++j) {
                int tmp = i * pri[j];
                not_p[tmp] = true;
                fac[tmp][0] = fac[i][0] * pri[j];
                fac[tmp][1] = fac[i][1];
                fac[tmp][2] = fac[i][2];

                // 保持 fac[0] <= fac[1] <= fac[2]
                if (fac[tmp][0] > fac[tmp][1]) std::swap(fac[tmp][0], fac[tmp]
[1]);
                if (fac[tmp][1] > fac[tmp][2]) std::swap(fac[tmp][1], fac[tmp]
[2]);
                if (fac[tmp][0] > fac[tmp][1]) std::swap(fac[tmp][0], fac[tmp]
[1]);

                if (i % pri[j] == 0) break;
            }
        }
    }

    // O(1) 查询接口
    inline int gcd(int a, int b) {
        int res = 1;
        for (int i = 0; i < 3; ++i) {
            int f = fac[a][i];
            int cur;
```

```
            if (f <= T) {
                cur = pre[f][b % f];
            } else {
                cur = (b % f == 0) ? f : 1;
            }
            b /= cur;
            res *= cur;
        }
        return res;
    }
};
"\n"
```

Simpson积分.cpp

```
#define DEBUG 1
#define FUCK cout << "fuck" << endl;
#if DEBUG
    #include "all.hpp"
#else
    #include <bits/stdc++.h>
#endif

using namespace std;
using ll = long long;
using pii = pair<int,int>;
using pll = pair<ll,ll>;
using db = long double;
using pdd = pair<db, db>;
using i128 = __int128_t;

const ll N = 2000000;
const ll INF = 5e18;
const ll MOD = 1e9 + 7;

// oi-wiki 上扒下来的模版, 异常强大
namespace Simpson {
    db f(db x) {

    }

    double simpson(double l, double r) {
        double mid = (l + r) / 2;
        return (r - l) * (f(l) + 4 * f(mid) + f(r)) / 6;  // 辛普森公式
    }

    double asr(double l, double r, double eps, double ans, int step) {
        double mid = (l + r) / 2;
        double fl = simpson(l, mid), fr = simpson(mid, r);
        if (abs(fl + fr - ans) <= 15 * eps && step < 0)
            return fl + fr + (fl + fr - ans) / 15;  // 足够相似的话就直接返回
```

```
        return asr(l, mid, eps / 2, fl, step - 1) +
            asr(mid, r, eps / 2, fr, step - 1);  // 否则分割成两段递归求解
        }

    double calc(double l, double r, double eps) {
        return asr(l, r, eps, simpson(l, r), 12);
    }

};
"\n"
```

Wheel筛.cpp

```
#include <bits/stdc++.h>
using namespace std;
#define DEBUG 1
using ll = long long;
using pii = pair<int,int>;
using i128 = __int128_t;
using pll = pair<ll,ll>;
const ll N = 2000000;
const ll INF = 5e18;
const ll MOD = 1e9 + 7;

/*
2025牛客多校期间从 wanna be free 处 cv 得到的板子
可以快速(1800ms)筛出 1e9 以内质数
调用时,需要指定 U 表示筛选的最大质数的大小,可以输入 1e9
然后 init ,之后从 1 开始, prime 数组会填充质数, 遍历到为 0 的位置就表示没有质数了
1e9 以内质数大概有 5e7 个!!
*/

namespace wheelSieve {
    using std::cin,std::cout;
    using std::max,std::memcpy;

    #define N 50847534
    #define block 510510
    #define block_size 15953
    #define M 7
    #define K 1959

    #define set(a, b) a[b >> 5] |= 1 << (b & 31)
    typedef unsigned int uint;
    typedef unsigned char uchar;

    uint prime[N + 7], pre_block[block_size + 7], cur_block[block_size + 7];
    uchar p[block + 7];
    int U;
    void init(){
        uint cnt = 0;
```

```
        p[0] = p[1] = true;
        set(pre_block, 0);
        set(pre_block, block);
        for ( uint i = 2; i <= block; ++i){
            if (!p[i]){
                prime[++cnt] = i;
                if (cnt <= M) set(pre_block, i);
            }
            for ( uint j = 1; j <= cnt && i * prime[j] <= block; ++j){
                uint t = i * prime[j];
                p[t] = true;
                if (j <= M) set(pre_block, t);
                if (i % prime[j] == 0) break;
            }
        }
        for ( uint i = 1, j = cnt; i < K; ++i){
            uint end = (i + 1) * block - 1, start = i * block;
            memcpy(cur_block, pre_block, sizeof(cur_block));
            for ( uint k = M + 1; prime[k] * prime[k] <= end; ++k){
                uint t1 = max((start - 1) / prime[k] + 1, prime[k]) * prime[k], t2
= prime[k] << 1;
                for ( uint l = (t1 & 1 ? t1 : t1 + prime[k]) - start; l < block; l
+= t2){
                    set(cur_block, l);
                }
            }
            for ( uint k = 0; k <= block_size; ++k){
                uint t1 = ~cur_block[k];
                while (t1){
                    uint t2 = __builtin_ctz(t1);
                    if ((k << 5) + t2 >= block) break;
                    prime[++j] = start + (k << 5) + t2;
                    if (j >= N||prime[j]>=U) return;
                    t1 -= t1 & ((~t1) + 1);
                }
            }
        }
    }
};"\n"
```

卡特兰数.cpp

```
/* 死亡回放
你的输入，真的写对了吗?? (2025 ICPC 沈阳 M)
*/
#define DEBUG 1
#define FUCK cout << "fuck" << endl;
#if DEBUG
    #include "all.hpp"
#else
    #include <bits/stdc++.h>
```

```
#endif

using namespace std;
using ll = long long;
using pii = pair<int,int>;
using pll = pair<ll,ll>;
using db = long double;
using pdd = pair<db, db>;
using i128 = __int128_t;

const ll N = 2000000;
const ll INF = 5e18;
const ll MOD = 1e9 + 7;

namespace ComNum {
    const int MAXN = 5e6;
    ll fac[MAXN], inv[MAXN];

    ll qpow(ll base,ll k,ll mod) {
        if (base == 0) return 0;
        ll res = 1;
        base %= mod; base = (base + mod) % mod;
        k %= (mod - 1); k = (k + mod - 1) % (mod - 1);
        while (k) {
            if (k & 1) {
                res *= base; res %= mod;
            }
            k >>= 1;
            base *= base; base %= mod;
        }
        return res;
    }

    void init() {
        fac[0] = 1;
        for (int i = 1;i<MAXN;i++) {
            fac[i] = fac[i - 1] * i % MOD;
        }
        vector<ll> pre(MAXN, 1), suf(MAXN, 1);
        for (int i = 0;i<MAXN;i++) {
            if (i - 1 >= 0) pre[i] = pre[i - 1];
            pre[i] = pre[i] * fac[i] % MOD;
        }
        for (int i = MAXN - 1;i>=0;i--) {
            if (i + 1 < MAXN) suf[i] = suf[i + 1];
            suf[i] = suf[i] * fac[i] % MOD;
        }
        ll base = qpow(pre.back(), MOD - 2, MOD);
        for (int i = 0;i<MAXN;i++) {
            ll fenzi = 1;
            if (i - 1 >= 0) fenzi = pre[i - 1] * fenzi % MOD;
            if (i + 1 < MAXN) fenzi = suf[i + 1] * fenzi % MOD;
            inv[i] = fenzi * base % MOD;
        }
```

```
        return;
    }

    ll C(ll n, ll m){
        if(m == 0) return 1;
        if(n >= 0){
            if(n < m) return 0;
            return fac[n] * inv[n - m] % MOD * inv[m] % MOD;
        }else{
            ll a = -n;
            ll nn = a + m - 1;
            ll res = fac[nn] * inv[nn - m] % MOD * inv[m] % MOD;
            if(m & 1) res = (MOD - res) % MOD;
            return res;
        }
    }
};

namespace Catalan {
    ll get(int n) {
        ll res = ComNum::C(2 * n, n);
        res = (res - ComNum::C(2 * n, n + 1) + MOD) % MOD;
        return res;
    }
};"\n"
```

哈希.cpp

```
#include <bits/stdc++.h>
using namespace std;
typedef long long ll;
const ll N = 2000000;


// 双模数 hash, 记得先 init
struct Hash {
    int x,y,MOD1 = 1000000007,MOD2 = 1000000009;
    Hash(){x = y = 0;}
    Hash(int _x,int _y) { x = _x; y = _y; }
    Hash operator + (const Hash &a) const {
        return Hash((x + a.x) % MOD1,(y + a.y) % MOD2);
    }
    Hash operator - (const Hash &a) const {
        return Hash((x - a.x + MOD1) % MOD1,(y - a.y + MOD2) % MOD2);
    }
    Hash operator * (const Hash &a) const {
        return Hash(1ll * x * a.x % MOD1,1ll * y * a.y % MOD2);
    }
    Hash operator * (const ll &a) const {
        return Hash(1ll * x * a % MOD1,1ll * y * a % MOD2);
    }
```

```
    bool operator == (const Hash &a) const {
        return (x == a.x && y == a.y);
    }
    bool operator<(const Hash& a) const {
        if (x != a.x) {
            return x < a.x;
        }
        return y < a.y;
    }
    bool operator>(const Hash& a) const {
        if (x != a.x) {
            return x > a.x;
        }
        return y > a.y;
    }
}base(131,13331),hs[N],bs[N];

void hash_init(int n){
    bs[0] = Hash(1,1);
    for(int i = 1;i <= n;i ++) {
        bs[i] = bs[i-1] * base;
    }
}"\n"
```

基元勾股数.cpp

```
#include <bits/stdc++.h>
using namespace std;
/*
用于寻找基元勾股数
*/
typedef long long ll;
class Pythagoras{
public:
    vector<tuple<int,int,int>> q;
    int maxN;
    Pythagoras(int MAXN){
        maxN = MAXN;
    }
    void init(){
        for (int i = 1;i<=maxN;i++){
            for (int j = i+1;2*i*j<=maxN && j*j+i*i<=maxN;j++){
                ll a = j * j - i * i;
                ll b = 2 * i * j;
                ll c = j * j + i * i;
                if (b > c){
                    swap(b,c);
                }
                if (a > b){
                    swap(a,b);
                }
```

```
                if (__gcd(a,b) == 1){
                    for (int k = 1;k*c<=maxN;k++){
                        q.emplace_back(a*k,b*k,c*k);
                    }
                }
            }
        }
        return;
    }
};"\n"
```

多项式(旧).cpp

```cpp
#include <bits/stdc++.h>
using namespace std;
#define DEBUG 1
using ll = long long;
using pii = pair<int,int>;
using i128 = __int128_t;
using pll = pair<ll,ll>;
const ll N = 2000000;
const ll INF = 5e18;
const ll MOD = 1e9 + 7;

namespace polystd {
#ifdef LOCAL
#define debug(...) fprintf(stderr, ##__VA_ARGS__)
#else
#define endl "\n"
#define debug(...) void(0)
#endif
typedef long long LL;

template <unsigned umod>
struct modint {
  static constexpr int mod = umod;
  unsigned v;
  modint() : v(0) {}
  template <class T, enable_if_t<is_integral<T>::value>* = nullptr>
  modint(T x) {
    x %= mod;
    if (x < 0) x += mod;
    v = x;
  }
  modint(const string& str) {
    v = 0;
    size_t i = 0;
    if (str.front() == '-') i += 1;
    while (i < str.size()) {
      assert(isdigit(str[i]));
      v = (v * 10ull % umod + str[i] - '0') % umod;
```

```
      i += 1;
    }
    if (str.front() == '-' && v) v = umod - v;
  }
  modint operator+() const { return *this; }
  modint operator-() const { return modint() - *this; }
  friend int raw(const modint& self) { return self.v; }
  friend istream& operator>>(istream& is, modint& self) {
    string str;
    is >> str;
    self = str;
    return is;
  }
  friend ostream& operator<<(ostream& os, const modint& self) {
    return os << raw(self);
  }
  modint& operator+=(const modint& rhs) {
    v += rhs.v;
    if (v >= umod) v -= umod;
    return *this;
  }
  modint& operator-=(const modint& rhs) {
    v -= rhs.v;
    if (v >= umod) v += umod;
    return *this;
  }
  modint& operator*=(const modint& rhs) {
    v = static_cast<unsigned>(1ull * v * rhs.v % umod);
    return *this;
  }
  modint& operator/=(const modint& rhs) {
    static constexpr size_t ilim = 1 << 20;
    static modint inv[ilim + 10];
    static int sz = 0;
    assert(rhs.v);
    if (rhs.v > ilim) return *this *= qpow(rhs, mod - 2);
    if (!sz) inv[1] = sz = 1;
    while (sz < (int)rhs.v) {
      for (int i = sz + 1; i <= sz << 1; i++) inv[i] = -mod / i * inv[mod % i];
      sz <<= 1;
    }
    return *this *= inv[rhs.v];
  }
  template <class T>
  friend modint qpow(modint a, T b) {
    modint r = 1;
    for (; b; b >>= 1, a *= a)
      if (b & 1) r *= a;
    return r;
  }
  friend modint operator+(modint lhs, const modint& rhs) { return lhs += rhs; }
  friend modint operator-(modint lhs, const modint& rhs) { return lhs -= rhs; }
  friend modint operator*(modint lhs, const modint& rhs) { return lhs *= rhs; }
  friend modint operator/(modint lhs, const modint& rhs) { return lhs /= rhs; }
```

```
  friend bool operator==(const modint& lhs, const modint& rhs) {
    return lhs.v == rhs.v;
  }
  friend bool operator!=(const modint& lhs, const modint& rhs) {
    return lhs.v != rhs.v;
  }
};

typedef modint<998244353> mint;
int glim(const int& x) { return 1 << (32 - __builtin_clz(x - 1)); }
int bitctz(const int& x) { return __builtin_ctz(x); }
struct poly : vector<mint> {
  poly() {}
  explicit poly(int n) : vector<mint>(n) {}
  poly(const vector<mint>& vec) : vector<mint>(vec) {}
  poly(initializer_list<mint> il) : vector<mint>(il) {}
  mint operator()(const mint& x) const;
  poly& cut(int lim);
  void ntt(int op);
};
void print(const poly& a) {
  for (size_t i = 0; i < a.size(); i++) debug("%d, ", raw(a[i]));
  debug("\n");
}
istream& operator>>(istream& is, poly& a) {
  for (auto& x : a) is >> x;
  return is;
}
ostream& operator<<(ostream& os, const poly& a) {
  bool flag = false;
  for (auto& x : a) {
    if (flag)
      os << " ";
    else
      flag = true;
    os << x;
  }
  return os;
}
mint poly::operator()(const mint& x) const {
  const auto& a = *this;
  mint res = 0;
  for (int i = (int)a.size() - 1; i >= 0; i--) {
    res = res * x + a[i];
  }
  return res;
}
poly& poly::cut(int lim) {
  resize(lim);
  return *this;
}
void poly::ntt(int op) {
  static bool wns_flag = false;
  static vector<mint> wns;
```

```
  if (!wns_flag) {
    wns_flag = true;
    for (int j = 1; j <= 23; j++) {
      wns.push_back(qpow(mint(3), raw(mint(-1)) >> j));
    }
  }
  vector<mint>& a = *this;
  int n = a.size();
  for (int i = 1, r = 0; i < n; i++) {
    r ^= n - (1 << (bitctz(n) - bitctz(i) - 1));
    if (i < r) std::swap(a[i], a[r]);
  }
  vector<mint> w(n);
  for (int k = 1, len = 2; len <= n; k <<= 1, len <<= 1) {
    mint wn = wns[bitctz(k)];
    for (int i = raw(w[0] = 1); i < k; i++) w[i] = w[i - 1] * wn;
    for (int i = 0; i < n; i += len) {
      for (int j = 0; j < k; j++) {
        mint x = a[i + j], y = a[i + j + k] * w[j];
        a[i + j] = x + y, a[i + j + k] = x - y;
      }
    }
  }
  if (op == -1) {
    mint iz = mint(1) / n;
    for (int i = 0; i < n; i++) a[i] *= iz;
    reverse(a.begin() + 1, a.end());
  }
}
poly concalc(int n, vector<poly> vec,
             const function<mint(vector<mint>)>& func) {
  int lim = glim(n);
  int m = vec.size();
  for (auto& f : vec) f.resize(lim), f.ntt(1);
  vector<mint> tmp(m);
  poly ret(lim);
  for (int i = 0; i < lim; i++) {
    for (int j = 0; j < m; j++) tmp[j] = vec[j][i];
    ret[i] = func(tmp);
  }
  ret.ntt(-1);
  return ret;
}
poly getInv(const poly& a, int lim) {
  poly b{1 / a[0]};
  for (int len = 2; len <= glim(lim); len <<= 1) {
    poly c = vector<mint>(a.begin(), a.begin() + min(len, (int)a.size()));
    b = concalc(len << 1, {b, c}, [](vector<mint> vec) {
          return vec[0] * (2 - vec[0] * vec[1]);
        }).cut(len);
  }
  return b.cut(lim);
}
poly operator+=(poly& a, const poly& b) {
```

```
  if (a.size() < b.size()) a.resize(b.size());
  for (size_t i = 0; i < b.size(); i++) a[i] += b[i];
  return a;
}
poly operator-=(poly& a, const poly& b) {
  if (a.size() < b.size()) a.resize(b.size());
  for (size_t i = 0; i < b.size(); i++) a[i] -= b[i];
  return a;
}
poly operator*=(poly& a, const mint& k) {
  if (k == 1) return a;
  for (size_t i = 0; i < a.size(); i++) a[i] *= k;
  return a;
}
poly operator/=(poly& a, const mint& k) { return a *= 1 / k; }
poly operator<<=(poly& a, const int& k) {
  // mnltiple by x^k
  a.insert(a.begin(), k, 0);
  return a;
}
poly operator>>=(poly& a, const int& k) {
  // divide by x^k
  a.erase(a.begin(), a.begin() + min(k, (int)a.size()));
  return a;
}
poly operator*(const poly& a, const poly& b) {
  if (a.empty() || b.empty()) return {};
  int rlen = a.size() + b.size() - 1;
  int len = glim(rlen);
  if (1ull * a.size() * b.size() <= 1ull * len * bitctz(len)) {
    poly ret(rlen);
    for (size_t i = 0; i < a.size(); i++)
      for (size_t j = 0; j < b.size(); j++) ret[i + j] += a[i] * b[j];
    return ret;
  } else {
    return concalc(len, {a, b},
                   [](vector<mint> vec) { return vec[0] * vec[1]; })
        .cut(rlen);
  }
}
poly operator/(poly a, poly b) {
  if (a.size() < b.size()) return {};
  int rlen = a.size() - b.size() + 1;
  reverse(a.begin(), a.end());
  reverse(b.begin(), b.end());
  a = (a * getInv(b, rlen)).cut(rlen);
  reverse(a.begin(), a.end());
  return a;
}
poly operator-(poly a, const poly& b) { return a -= b; }
poly operator%(const poly& a, const poly& b) {
  return (a - (a / b) * b).cut(b.size() - 1);
}
poly operator*=(poly& a, const poly& b) { return a = a * b; }
```

```
poly operator/=(poly& a, const poly& b) { return a = a / b; }
poly operator%=(poly& a, const poly& b) { return a = a % b; }
poly operator+(poly a, const poly& b) { return a += b; }
poly operator*(poly a, const mint& k) { return a *= k; }
poly operator*(const mint& k, poly a) { return a *= k; }
poly operator/(poly a, const mint& k) { return a /= k; }
poly operator<<(poly a, const int& k) { return a <<= k; }
poly operator>>(poly a, const int& k) { return a >>= k; }
poly getDev(poly a) {
  a >>= 1;
  for (size_t i = 1; i < a.size(); i++) a[i] *= i + 1;
  return a;
}
poly getInt(poly a) {
  a <<= 1;
  for (size_t i = 1; i < a.size(); i++) a[i] /= i;
  return a;
}
poly getLn(const poly& a, int lim) {
  assert(a[0] == 1);
  return getInt(getDev(a) * getInv(a, lim)).cut(lim);
}
poly getExp(const poly& a, int lim) {
  assert(a[0] == 0);
  poly b{1};
  for (int len = 2; len <= glim(lim); len <<= 1) {
    poly c = vector<mint>(a.begin(), a.begin() + min(len, (int)a.size()));
    b = concalc(len << 1, {b, getLn(b, len), c}, [](vector<mint> vec) {
          return vec[0] * (1 - vec[1] + vec[2]);
        }).cut(len);
  }
  return b.cut(lim);
}
poly qpow(const poly& a, string k, int lim) {
  size_t i = 0;
  while (i < a.size() && a[i] == 0) i += 1;
  if (i == a.size() || (i > 0 && k.size() >= 9) ||
      1ull * i * raw(mint(k)) >= 1ull * lim)
    return poly(lim);
  lim -= i * raw(mint(k));
  return getExp(getLn(a / a[i] >> i, lim) * k, lim) *
            qpow(a[i], raw(modint<mint::mod - 1>(k)))
         << i * raw(mint(k));
}
poly qpow(const poly& a, LL k, int lim) {
  size_t i = 0;
  while (i < a.size() && a[i] == 0) i += 1;
  if (i == a.size() || (i > 0 && k >= 1e9) ||
      1ull * i * k >= 1ull * lim)
    return poly(lim);
  lim -= i * k;
  return getExp(getLn(a / a[i] >> i, lim) * k, lim) *
            qpow(a[i], raw(modint<mint::mod - 1>(k)))
         << i * k;
```

```
}
mint sqrt(const mint& c) {
  static const auto check = [](mint c) {
    return qpow(c, (mint::mod - 1) >> 1) == 1;
  };
  if (raw(c) <= 1) return 1;
  if (!check(c)) throw "No solution!";
  static mt19937 rng{random_device{}()};
  mint a = rng();
  while (check(a * a - c)) a = rng();
  typedef pair<mint, mint> number;
  const auto mul = [=](number x, number y) {
    return make_pair(x.first * y.first + x.second * y.second * (a * a - c),
                     x.first * y.second + x.second * y.first);
  };
  const auto qpow = [=](number a, int b) {
    number r = {1, 0};
    for (; b; b >>= 1, a = mul(a, a))
      if (b & 1) r = mul(r, a);
    return r;
  };
  mint ret = qpow({a, 1}, (mint::mod + 1) >> 1).first;
  return min(raw(ret), raw(-ret));
}
poly getSqrt(const poly& a, int lim) {
  poly b{sqrt(a[0])};
  for (int len = 2; len <= glim(lim); len <<= 1) {
    poly c = vector<mint>(a.begin(), a.begin() + min(len, (int)a.size()));
    b = (c * getInv(b * 2, len) + b / 2).cut(len);
  }
  return b.cut(lim);
}
template <class T>
mint divide_at(poly f, poly g, T n) {
  for (; n; n >>= 1) {
    poly r = g;
    for (size_t i = 1; i < r.size(); i += 2) r[i] *= -1;
    f *= r;
    g *= r;
    int i;
    for (i = n & 1; i < (int)f.size(); i += 2) f[i >> 1] = f[i];
    f.resize(i >> 1);
    for (i = 0; i < (int)g.size(); i += 2) g[i >> 1] = g[i];
    g.resize(i >> 1);
  }
  return f.empty() ? 0 : f[0] / g[0];
}
template <class T>
mint linear_rec(poly a, poly f, T n) {
  // a[n] = sum_i f[i] * a[n - i]
  a.resize(f.size() - 1);
  f = poly{1} - f;
  poly g = a * f;
  g.resize(a.size());
```

```
  return divide_at(g, f, n);
}
poly BM(poly a) {
  poly ans, lst;
  int w = 0;
  mint delta = 0;
  for (size_t i = 0; i < a.size(); i++) {
    mint tmp = -a[i];
    for (size_t j = 0; j < ans.size(); j++) tmp += ans[j] * a[i - j - 1];
    if (tmp == 0) continue;
    if (ans.empty()) {
      w = i;
      delta = tmp;
      ans = vector<mint>(i + 1, 0);
    } else {
      auto now = ans;
      mint mul = -tmp / delta;
      if (ans.size() < lst.size() + i - w) ans.resize(lst.size() + i - w);
      ans[i - w - 1] -= mul;
      for (size_t j = 0; j < lst.size(); j++) ans[i - w + j] += lst[j] * mul;
      if (now.size() <= lst.size() + i - w) {
        w = i;
        lst = now;
        delta = tmp;
      }
    }
  }
  return ans << 1;
}
poly lagrange(const vector<pair<mint, mint>>& a) {
  poly ans(a.size()), product{1};
  for (size_t i = 0; i < a.size(); i++) {
    product *= poly{-a[i].first, 1};
  }
  auto divide2 = [&](poly a, mint b) {
    poly res(a.size() - 1);
    for (size_t i = (int)a.size() - 1; i >= 1; i--) {
      res[i - 1] = a[i];
      a[i - 1] -= a[i] * b;
    }
    return res;
  };
  for (size_t i = 0; i < a.size(); i++) {
    mint denos = 1;
    for (size_t j = 0; j < a.size(); j++) {
      if (i != j) denos *= a[i].first - a[j].first;
    }
    poly numes = divide2(product, -a[i].first);
    ans += a[i].second / denos * numes;
  }
  return ans;
}
}
```

```
using namespace polystd;
"\n"
```

多项式.cpp

```cpp
/* 死亡回放
你的输入，真的写对了吗?? (2025 ICPC 沈阳 M)
*/
#define DEBUG 1
#define FUCK cout << "fuck" << endl;

#if DEBUG
#include "all.hpp"
#else
#include <bits/stdc++.h>
#endif

using namespace std;
using ll = long long;
using pii = pair<int, int>;
using pll = pair<ll, ll>;
using db = long double;
using pdd = pair<db, db>;
using i128 = __int128_t;

const ll N = 2000000;
const ll INF = 5e18;
const ll MOD = 998244353;

/*
此模版来自 https://hourai.nanani-fan.club/poly-family/
感谢 哈尔滨工业大学-蓬莱人形 的分享
*/

namespace poly {

    ll qpow(ll base, ll k) {
        if (base == 0) return 0;
        ll res = 1;
        base %= MOD; base = (base + MOD) % MOD;
        k %= (MOD - 1); k = (k + MOD - 1) % (MOD - 1);
        while (k) {
            if (k & 1) {
                res = res * base % MOD;
            }
            base = base * base % MOD;
            k >>= 1;
        }
        return res;
    }
```

```
ll inv(ll x) {
    return qpow(x, MOD - 2);
}

mt19937 MT;

using Poly = vector<ll>;
#define lg(x) ((x) == 0 ? -1 : __lg(x))
#define Size(x) int(x.size())

namespace NTT_ns {
    const long long G = 3, invG = inv(G);
    vector<int> rev;

    void NTT(ll* F, int len, int sgn) {
        rev.resize(len);
        for (int i = 1; i < len; ++i) {
            rev[i] = (rev[i >> 1] >> 1) | ((i & 1) * (len >> 1));
            if (i < rev[i]) swap(F[i], F[rev[i]]);
        }

        for (int tmp = 1; tmp < len; tmp <<= 1) {
            ll w1 = qpow(sgn ? G : invG, (MOD - 1) / (tmp << 1));
            for (int i = 0; i < len; i += tmp << 1) {
                for (ll j = 0, w = 1; j < tmp; ++j, w = w * w1 % MOD) {
                    ll x = F[i + j];
                    ll y = F[i + j + tmp] * w % MOD;
                    F[i + j]         = (x + y) % MOD;
                    F[i + j + tmp]   = (x - y + MOD) % MOD;
                }
            }
        }

        if (sgn == 0) {
            ll inv_len = inv(len);
            for (int i = 0; i < len; ++i)
                F[i] = F[i] * inv_len % MOD;
        }
    }
}

using NTT_ns::NTT;

Poly operator*(Poly F, Poly G) {
    int siz = Size(F) + Size(G) - 1;
    int len = 1 << (lg(siz - 1) + 1);

    if (siz <= 300) {
        Poly H(siz);
        for (int i = Size(F) - 1; ~i; --i)
            for (int j = Size(G) - 1; ~j; --j)
                H[i + j] = (H[i + j] + F[i] * G[j]) % MOD;
        return H;
    }
```

```
    F.resize(len);
    G.resize(len);

    NTT(F.data(), len, 1);
    NTT(G.data(), len, 1);

    for (int i = 0; i < len; ++i)
        F[i] = F[i] * G[i] % MOD;

    NTT(F.data(), len, 0);
    F.resize(siz);
    return F;
}

Poly operator+(Poly F, Poly G) {
    int siz = max(Size(F), Size(G));
    F.resize(siz);
    G.resize(siz);
    for (int i = 0; i < siz; ++i)
        F[i] = (F[i] + G[i]) % MOD;
    return F;
}

Poly operator-(Poly F, Poly G) {
    int siz = max(Size(F), Size(G));
    F.resize(siz);
    G.resize(siz);
    for (int i = 0; i < siz; ++i)
        F[i] = (F[i] - G[i] + MOD) % MOD;
    return F;
}

Poly lsh(Poly F, int k) {
    F.resize(Size(F) + k);
    for (int i = Size(F) - 1; i >= k; --i)
        F[i] = F[i - k];
    for (int i = 0; i < k; ++i)
        F[i] = 0;
    return F;
}

Poly rsh(Poly F, int k) {
    int siz = Size(F) - k;
    for (int i = 0; i < siz; ++i)
        F[i] = F[i + k];
    F.resize(siz);
    return F;
}

Poly cut(Poly F, int len) {
    F.resize(len);
    return F;
}
```

```
    Poly der(Poly F) {
        int siz = Size(F) - 1;
        for (int i = 0; i < siz; ++i)
            F[i] = F[i + 1] * (i + 1) % MOD;
        F.pop_back();
        return F;
    }

    Poly inte(Poly F) {
        F.emplace_back(0);
        for (int i = Size(F) - 1; i; --i)
            F[i] = F[i - 1] * inv(i) % MOD;
        F[0] = 0;
        return F;
    }

    Poly inv(Poly F) {
        int siz = Size(F);
        Poly G{inv(F[0])};
        for (int i = 2; (i >> 1) < siz; i <<= 1) {
            G = G + G - G * G * cut(F, i);
            G.resize(i);
        }
        G.resize(siz);
        return G;
    }

    Poly ln(Poly F) {
        return cut(inte(cut(der(F) * inv(F), Size(F))), Size(F));
    }

    Poly exp(Poly F) {
        int siz = Size(F);
        Poly G{1};
        for (int i = 2; (i >> 1) < siz; i <<= 1) {
            G = G * (Poly{1} - ln(cut(G, i)) + cut(F, i));
            G.resize(i);
        }
        G.resize(siz);
        return G;
    }
};

using namespace poly;
"\n"
```

拉格朗日插值.cpp

```
#define DEBUG 1
#if DEBUG
```

```
    #include "all.hpp"
#else
    #include <bits/stdc++.h>
#endif

using namespace std;
using ll = long long;
using pii = pair<int,int>;
using pll = pair<ll,ll>;
using db = long double;
using pdd = pair<db, db>;

const ll N = 2000000;
const ll INF = 5e18;
const ll MOD = 1e9 + 7;

/*
记得先 init !!!

cal 函数传入一段连续的函数值(按照横坐标排序)
格式为 (x, f(x)), 然后传入待计算的横坐标

单次插值复杂度 O(n) .
*/

namespace LagInt {
    ll fac[N];

    // 模数为质数 !!!
    ll qpow(ll base,ll k,ll mod) {
        if (base == 0) return 0;
        ll res = 1;
        base %= mod; base = (base + mod) % mod;
        k %= (mod - 1); k = (k + mod - 1) % (mod - 1);
        while (k) {
            if (k & 1) {
                res *= base; res %= mod;
            }
            k >>= 1;
            base *= base; base %= mod;
        }
        return res;
    }

    void init(int n) {
        fac[0] = 1;
        for (int i = 1;i<=n;i++) {
            fac[i] = fac[i - 1] * i % MOD;
        }
        return;
    }

    ll cal(vector<pll>& f, ll x) {
        int n = f.size() - 1;
```

```
        vector<ll> pre(n + 1, 0), suf(n + 1, 0);
        vector<ll> inv(n + 1, 0);

        for (int i = 0;i<=n;i++) {
            inv[i] = fac[i] * fac[n - i] % MOD;
        }
        for (int i = 0;i<=n;i++) {
            if (i - 1 >= 0) {
                pre[i] = pre[i - 1] * inv[i] % MOD;
            } else {
                pre[i] = inv[i];
            }
        }
        for (int i = n;i>=0;i--) {
            if (i + 1 <= n) {
                suf[i] = suf[i + 1] * inv[i] % MOD;
            } else {
                suf[i] = inv[i];
            }
        }
        ll base = qpow(pre[n], MOD - 2, MOD);
        for (int i = 0;i<=n;i++) {
            inv[i] = base;
            if (i - 1 >= 0) {
                inv[i] = inv[i] * pre[i - 1] % MOD;
            }
            if (i + 1 <= n) {
                inv[i] = inv[i] * suf[i + 1] % MOD;
            }
        }

        for (int i = 0;i<=n;i++) {
            if (i - 1 >= 0) {
                pre[i] = pre[i - 1] * (x - f[i].first) % MOD;
                pre[i] = (pre[i] + MOD) % MOD;
            } else {
                pre[i] = (x - f[i].first) % MOD;
                pre[i] = (pre[i] + MOD) % MOD;
            }
        }

        for (int i = n;i>=0;i--) {
            if (i + 1 <= n) {
                suf[i] = suf[i + 1] * (x - f[i].first) % MOD;
                suf[i] = (suf[i] + MOD) % MOD;
            } else {
                suf[i] = (x - f[i].first) % MOD;
                suf[i] = (suf[i] + MOD) % MOD;
            }
        }

        ll ans = 0;
        for (int i = 0;i<=n;i++) {
            ll res = f[i].second;
```

```
            if (i - 1 >= 0) res = res * pre[i - 1] % MOD;
            if (i + 1 <= n) res = res * suf[i + 1] % MOD;
            res = res * inv[i] % MOD;
            if ((n - i) & 1) res = (-res + MOD) % MOD;
            ans = (ans + res) % MOD;
        }
        return ans;
    }
};"\n"
```

拓展gcd.cpp

```
#include <bits/stdc++.h>
using namespace std;
typedef long long ll;

/*
使用说明:
首先调用 init 函数初始化 ax + by = c 的参数,返回 0 表示无解.
cal 函数计算特解,通解为 X1 + k * dx , Y1 + k * dy
*/

template<typename T>
struct ExGcd{
    T a,b,dx,dy,c,gcd_ab;
    T X0,Y0,X1,Y1;
    bool init(T A,T B,T C = 0){
        a = A,b = B,c = C;
        gcd_ab = __gcd(a,b);
        if (c % gcd_ab != 0){
            return 0;
        }
        return 1;
    }
    void exgcd(T a,T b){
        if (b == 0){
            X0 = 1;
            Y0 = 0;
        }else{
            exgcd(b,a % b);
            X1 = X0,Y1 = Y0;
            X0 = Y1;
            Y0 = X1 - a / b * Y1;
        }
        return;
    }
    void cal(){
        exgcd(a,b);
        X1 = X0 * c / gcd_ab;
        Y1 = Y0 * c / gcd_ab;
        dx = b / gcd_ab;
```

```
        dy = -a / gcd_ab;
        return;
    }
};"\n"
```

数论分块.cpp

```
#include <bits/stdc++.h>
using namespace std;

using ll = long long;

class NumberTheoryBlock {
public:
    void down(ll x,vector<pair<ll,ll>>& block) {
        block.clear();
        ll l = 1,r = 0;
        while (l <= x) {
            r = x / (x / l);
            if (r > x) r = x;
            block.emplace_back(l,r);
            l = r + 1;
        }
        return;
    }

    void up(ll x,vector<pair<ll,ll>>& block) {
        block.clear();
        ll l = 1,r = 0;
        while (l <= x) {
            if (l == x) {
                block.emplace_back(l,l);
                break;
            }
            r = (x - 1) / ((x - 1) / l);
            block.emplace_back(l,r);
            l = r + 1;
        }
        return;
    }
};"\n"
```

沃尔什卷积.cpp

```
#include <vector>
#include <algorithm>

using namespace std;
```

```
template <typename T>
struct FWTSolver {
    enum Type { OR = 0, AND = 1, XOR = 2 };

    // 核心变换
    static void transform(vector<T>& a, Type type, bool inv) {
        int n = a.size();
        for (int h = 1; h < n; h <<= 1) {
            for (int j = 0; j < n; j += (h << 1)) {
                for (int k = 0; k < h; k++) {
                    T &x = a[j + k], &y = a[j + k + h];
                    if (type == OR) {
                        if (!inv) y += x; else y -= x;
                    } else if (type == AND) {
                        if (!inv) x += y; else x -= y;
                    } else { // XOR
                        T u = x, v = y;
                        x = u + v; y = u - v;
                        if (inv) {
                            // 注意：如果是整数或浮点数直接 /2
                            // 如果是 ModInt，此处应乘上 2 的逆元
                            x /= 2; y /= 2;
                        }
                    }
                }
            }
        }
    }

    // 卷积通用接口
    static vector<T> convolution(vector<T> a, vector<T> b, Type type) {
        int n = 1, sz = max(a.size(), b.size());
        while (n < sz) n <<= 1;
        a.resize(n, T(0)); b.resize(n, T(0));

        transform(a, type, false);
        transform(b, type, false);
        for (int i = 0; i < n; i++) a[i] *= b[i];
        transform(a, type, true);
        return a;
    }

    // 快捷调用
    static vector<T> convOR(vector<T> a, vector<T> b) { return convolution(a, b,
OR); }
    static vector<T> convAND(vector<T> a, vector<T> b) { return convolution(a, b,
AND); }
    static vector<T> convXOR(vector<T> a, vector<T> b) { return convolution(a, b,
XOR); }
};"\n"
```

矩阵.cpp

```cpp
#include <bits/stdc++.h>
using namespace std;
typedef long long ll;

template <typename T>
struct Mat
{
    int n, m;
    T **a;
    Mat(int _n = 0, int _m = 0) : n(_n), m(_m)
    {
        a = new T *[n];
        for (int i = 0; i < n; i++)
            a[i] = new T[m], memset(a[i], 0, sizeof(T) * m);
    }
    Mat(const Mat &B)
    {
        n = B.n, m = B.m;
        a = new T *[n];
        for (int i = 0; i < n; i++)
            a[i] = new T[m], memcpy(a[i], B.a[i], sizeof(T) * m);
    }
    ~Mat() { delete[] a; }
    Mat &operator=(const Mat &B)
    {
        delete[] a;
        n = B.n, m = B.m;
        a = new T *[n];
        for (int i = 0; i < n; i++)
            a[i] = new T[m], memcpy(a[i], B.a[i], sizeof(T) * m);
        return *this;
    }
    Mat operator+(const Mat &B) const
    {
        assert(n == B.n && m == B.m);
        Mat ret(n, m);
        for (int i = 0; i < n; i++)
            for (int j = 0; j < m; j++)
                ret.a[i][j] = (a[i][j] + B.a[i][j]) % mod;
        return ret;
    }
    Mat &operator+=(const Mat &B) { return *this = *this + B; }
    Mat operator*(const Mat &B) const
    {
        Mat ret(n, B.m);
        for (int i = 0; i < n; ++i)
            for (int j = 0; j < B.m; ret.a[i][j++] %= mod)
                for (int k = 0; k < m; ++k)
                    ret.a[i][j] += a[i][k] * B.a[k][j] % mod;
        return ret;
    }
    Mat &operator*=(const Mat &B) { return *this = *this * B; }
```

```
};
Mat<ll> qpow(Mat<ll> A, ll b)
{
    Mat<ll> ret(A);
    for (--b; b; b >>= 1, A *= A)
        if (b & 1)
            ret *= A;
    return ret;
}"\n"
```

类欧几里得算法.cpp

```cpp
#include <bits/stdc++.h>
using namespace std;
using i128 = __int128_t;
using ll = long long;

// floor((a * i + b) / m)
// i 从 0 到 n - 1
i128 floor_sum_i128(i128 n, i128 m, i128 a, i128 b){
    if(n<=0) return 0;
    i128 ans=0;
    if(a<0){ b += a*(n-1); a = -a; }
    if(b<0){ i128 k = (-b + m - 1) / m; b += k*m; ans -= k*n; }
    while(true){
        if(a>=m){ ans += (a/m) * (n*(n-1)/2); a %= m; }
        if(b>=m){ ans += (b/m) * n; b %= m; }
        i128 y = a*n + b;
        if(y < m) break;
        n = y / m;
        b = y % m;
        i128 tmp = m; m = a; a = tmp;
    }
    return ans;
}

i128 floor_sum_mod(i128 n, i128 m, i128 a, i128 b, i128 mod){
    if(n<=0) return 0;
    a%=m; b%=m;
    i128 ans=0;
    if(a<0){ b += a*(n-1); a = -a; }
    if(b<0){ i128 k = (-b + m - 1) / m; b += k*m; ans -= k*n; }
    while(true){
        if(a>=m){ ans += (a/m) * (n*(n-1)/2); a %= m; }
        if(b>=m){ ans += (b/m) * n; b %= m; }
        i128 y = a*n + b;
        if(y < m) break;
        n = y / m;
        b = y % m;
        i128 tmp = m; m = a; a = tmp;
    }
```

```
    ans %= mod;
    if(ans<0) ans += mod;
    return ans;
}"\n"
```

线性基.cpp

```
#include <bits/stdc++.h>
using ll = long long;
const ll N = 2000000;
const ll INF = 5e18;
const ll MOD = 1e9 + 7;
using namespace std;

struct LinearBasis {
    ll basis[63];
    bool flag0; // 是否可以表示 0

    void insert(ll x) {
        if (!x) return;
        for (int i = 60;i>=0;i--) {
            if ((1ll<<i)&x) {
                if (basis[i]) {
                    x ^= basis[i];
                } else {
                    basis[i] = x;
                    break;
                }
            }
        }
        if (x) flag0 = 1;
        return;
    }

    void preprocess() {
        for (int i = 60;i>=0;i--) {
            if (!basis[i]) continue;
            for (int j = i-1;j>=0;j--) {
                if (basis[j] && ((1ll<<j)&basis[i])) {
                    basis[i] ^= basis[j];
                }
            }
        }
        return;
    }

    void init() {
        flag0 = 0;
        memset(basis,0,sizeof basis);
        return;
    }
```

```
    ll get_mn() {
        for (int i = 0;i<=60;i++) {
            if (basis[i]) {
                return basis[i];
            }
        }
    }

    ll get_mx() {
        ll res = 0;
        for (int i = 60;i>=0;i--) {
            if (basis[i] && !((1ll<<i)&res)){
                res ^= basis[i];
            }
        }
        return res;
    }
} ;"\n"
```

组合数.cpp

```
#include <bits/stdc++.h>
typedef long long ll;
const ll MOD = 1000000007;
using namespace std;
// 1e7 的数组慎开啊
// 支持广义二项式定理
namespace ComNum {
    const int MAXN = 5e6;
    ll fac[MAXN], inv[MAXN];

    ll qpow(ll base,ll k,ll mod) {
        if (base == 0) return 0;
        ll res = 1;
        base %= mod; base = (base + mod) % mod;
        k %= (mod - 1); k = (k + mod - 1) % (mod - 1);
        while (k) {
            if (k & 1) {
                res *= base; res %= mod;
            }
            k >>= 1;
            base *= base; base %= mod;
        }
        return res;
    }

    void init() {
        fac[0] = 1;
        for (int i = 1;i<MAXN;i++) {
            fac[i] = fac[i - 1] * i % MOD;
```

```
        }
        vector<ll> pre(MAXN, 1), suf(MAXN, 1);
        for (int i = 0;i<MAXN;i++) {
            if (i - 1 >= 0) pre[i] = pre[i - 1];
            pre[i] = pre[i] * fac[i] % MOD;
        }
        for (int i = MAXN - 1;i>=0;i--) {
            if (i + 1 < MAXN) suf[i] = suf[i + 1];
            suf[i] = suf[i] * fac[i] % MOD;
        }
        ll base = qpow(pre.back(), MOD - 2, MOD);
        for (int i = 0;i<MAXN;i++) {
            ll fenzi = 1;
            if (i - 1 >= 0) fenzi = pre[i - 1] * fenzi % MOD;
            if (i + 1 < MAXN) fenzi = suf[i + 1] * fenzi % MOD;
            inv[i] = fenzi * base % MOD;
        }
        return;
    }

    ll C(ll n, ll m){
        if(m == 0) return 1;
        if(n >= 0){
            if(n < m) return 0;
            return fac[n] * inv[n - m] % MOD * inv[m] % MOD;
        }else{
            ll a = -n;
            ll nn = a + m - 1;
            ll res = fac[nn] * inv[nn - m] % MOD * inv[m] % MOD;
            if(m & 1) res = (MOD - res) % MOD;
            return res;
        }
    }
};"\n"
```

自动取模.cpp

```
#include <iostream>
using ll = long long;

template<int P>
struct MODint {
    int v, c;
    constexpr MODint() : v(0), c(0) {}
    constexpr MODint(ll x) : v(0), c(0) {
        if (x != 0) {
            while (x % P == 0) x /= P, c++;
            v = x % P;
            if (v < 0) v += P;
        }
    }
```

```
    constexpr MODint(int v, int c) : v(v), c(c) {}
    constexpr int val() const {
        return c > 0 ? 0 : v;
    }
    constexpr int inv(int a) const {
        int b = P - 2, res = 1;
        for (; b; b >>= 1, a = 1LL * a * a % P) {
            if (b & 1) res = 1LL * res * a % P;
        }
        return res;
    }
    constexpr MODint& operator*=(MODint rhs) {
        if (v == 0 || rhs.v == 0) return *this = MODint();
        v = 1LL * v * rhs.v % P;
        c += rhs.c;
        return *this;
    }
    constexpr MODint& operator/=(MODint rhs) {
        v = 1LL * v * inv(rhs.v) % P;
        c -= rhs.c;
        return *this;
    }
    friend constexpr MODint operator*(MODint lhs, MODint rhs) {
        MODint res = lhs;
        res *= rhs;
        return res;
    }
    friend constexpr MODint operator/(MODint lhs, MODint rhs) {
        MODint res = lhs;
        res /= rhs;
        return res;
    }
    friend std::istream& operator>>(std::istream& is, MODint& a) {
        ll x;
        is >> x;
        a = MODint(x);
        return is;
    }
    friend std::ostream& operator<<(std::ostream& os, const MODint& a) {
        return os << a.val();
    }
};"\n"
```

质数检验.cpp

```
#define DEBUG 1
#define FUCK cout << "fuck" << endl;
#if DEBUG
    #include "all.hpp"
#else
    #include <bits/stdc++.h>
```

```cpp
#endif

using namespace std;
using ll = long long;
using pii = pair<int,int>;
using pll = pair<ll,ll>;
using db = long double;
using pdd = pair<db, db>;
using i128 = __int128_t;

const ll N = 2000000;
const ll INF = 5e18;
const ll MOD = 1e9 + 7;

// max_prime_factor, 输入 n, 返回 n 的最大质因子
// 如果 n 是质数, 返回 -1

namespace primeCheck {
    std::mt19937_64
rng((unsigned)std::chrono::steady_clock::now().time_since_epoch().count());
    ll mulmod(ll a, ll b, ll mod){ return (unsigned __int128)a*b%mod; }
    ll powmod(ll a, ll d, ll mod){
        ll r=1;
        while(d){
            if(d&1) r=mulmod(r,a,mod);
            a=mulmod(a,a,mod);
            d>>=1;
        }
        return r;
    }
    bool isPrime(ll n){
        if(n<2) return false;
        for(ll p:{2,3,5,7,11,13,17,19,23,29,31,37}){ if(n%p==0) return n==p; }
        ll d=n-1, s=0;
        while((d&1)==0){ d>>=1; ++s; }
        ll bases[] = {2,325,9375,28178,450775,9780504,1795265022};
        for(ll a:bases){
            if(a%n==0) continue;
            ll x=powmod(a,d,n);
            if(x==1||x==n-1) continue;
            bool comp=true;
            for(ll r=1;r<s;++r){
                x=mulmod(x,x,n);
                if(x==n-1){ comp=false; break; }
            }
            if(comp) return false;
        }
        return true;
    }
    ll pollards_rho(ll n){
        if(n%2==0) return 2;
        if(n%3==0) return 3;
        std::uniform_int_distribution<ll> dist(2, n-2);
        while(true){
```

```
            ll c = dist(rng);
            auto f = [&](ll x){ return (mulmod(x,x,n) + c) % n; };
            ll x = dist(rng), y = x, d = 1;
            while(d==1){
                x = f(x);
                y = f(f(y));
                d = std::gcd(std::llabs(x-y), n);
            }
            if(d!=n) return d;
        }
    }
    void factor_rec(ll n, std::vector<ll>& out){
        if(n==1) return;
        if(isPrime(n)){ out.push_back(n); return; }
        ll d = pollards_rho(n);
        factor_rec(d, out);
        factor_rec(n/d, out);
    }
    ll max_prime_factor(ll n){
        if(n<=1) return -1;
        if(isPrime(n)) return -1;
        std::vector<ll> f;
        factor_rec(n,f);
        return *std::max_element(f.begin(), f.end());
    }
}
"\n"
```

质数筛.cpp

```
#include <bits/stdc++.h>
using namespace std;
typedef long long ll;
#define DEBUG 1
const ll N = 2000000;

ll qpow(ll base,ll k,ll mod) {
    if (base == 0) return 0;
    ll res = 1;
    base %= mod; base = (base + mod) % mod;
    k %= (mod - 1); k = (k + mod - 1) % (mod - 1);
    while (k) {
        if (k & 1) {
            res *= base; res %= mod;
        }
        k >>= 1;
        base *= base; base %= mod;
    }
    return res;
}
```

```cpp
ll phi(ll x) {
    ll ans = x;
    for (int i = 2;i<=sqrt(x);i++) {
        if (x % i) continue;
        ans = ans - ans / i;
        while (x % i == 0) x /= i;
    }
    if (x > 1) {
        ans = ans - ans / x;
    }
    return ans;
}

struct Primes{
    ll notPrime[N];
    ll phi[N],mu[N];
    vector<ll> primes;
    void sieve(int maxn){
        phi[1] = 1;
        mu[1] = 1;
        for (ll i = 2;i<maxn + 1;i++){
            if (!notPrime[i]){
                primes.push_back(i);
                phi[i] = i - 1;
                mu[i] = -1;
            }

            for (auto p : primes) {
                if (i * p > maxn) break;
                notPrime[i * p] = 1;
                if (i % p == 0) {
                    phi[i * p] = phi[i] * p;
                    mu[i * p] = 0;
                    break;
                }
                phi[i * p] = phi[i] * phi[p];
                mu[i * p] = -mu[i];
            }
        }
        return;
    }
};

// 找奇质数 x 的原根,一定是奇素数!!!
// 时间复杂度不详
ll getYuanGen(ll x) {
    Primes solver;
    solver.sieve(x);
    ll y = x - 1;
    vector<ll> q;
    for (int i = 0;i<solver.primes.size() && y > 1;i++) {
        if (y % solver.primes[i] == 0) {
            q.push_back(solver.primes[i]);
        }
```

```
        while (y % solver.primes[i] == 0) {
            y /= solver.primes[i];
        }
    }

    for (ll i = 1;i<x;i++) {
        bool ok = 1;
        for (auto v : q) {
            if (qpow(i,(x-1)/v,x) == 1) {
                ok = 0;
                break;
            } else {

            }
        }
        if (ok) return i;
    }

    return 0;
}"\n"
```

逆元.cpp

```
#define DEBUG 1
#define FUCK cout << "fuck" << endl;
#if DEBUG
    #include "all.hpp"
#else
    #include <bits/stdc++.h>
#endif

using namespace std;
using ll = long long;
using pii = pair<int,int>;
using pll = pair<ll,ll>;
using db = long double;
using pdd = pair<db, db>;
using i128 = __int128_t;

const ll N = 2000000;
const ll INF = 5e18;
const ll MOD = 1e9 + 7;

ll qpow(ll base,ll k,ll mod) {
    if (base == 0) return 0;
    ll res = 1;
    base %= mod; base = (base + mod) % mod;
    k %= (mod - 1); k = (k + mod - 1) % (mod - 1);
    while (k) {
        if (k & 1) {
            res *= base; res %= mod;
```

```
        }
        k >>= 1;
        base *= base; base %= mod;
    }
    return res;
}

namespace NiYuan {
    vector<ll> fac, invFac, inv;

    void init(int n) {
        fac.resize(n + 1, 1), invFac.resize(n + 1, 1), inv.resize(n + 1, 1);
        for (int i = 1;i<n+1;i++) {
            fac[i] = fac[i - 1] * i % MOD;
        }
        invFac[n] = qpow(fac[n], MOD - 2, MOD);
        for (int i = n - 1;i>=1;i--) {
            invFac[i] = invFac[i + 1] * (i + 1) % MOD;
        }
        for (int i = 2; i <= n; i++) {
            inv[i] = (MOD - MOD / i) * inv[MOD % i] % MOD;
        }
    }
};"\n"
```

逆序数.cpp

```
#include <bits/stdc++.h>
using namespace std;
using ll = long long;

class ArrayInversion {
    ll mergeSort(vector<ll>& a, vector<ll>& temp, int l, int r) {
        if (l >= r) return 0;
        int mid = (l + r) / 2;
        ll inv_count = mergeSort(a, temp, l, mid) + mergeSort(a, temp, mid + 1,
r);
        int i = l, j = mid + 1, k = l;
        while (i <= mid && j <= r) {
            if (a[i] > a[j]) {
                temp[k++] = a[j++];
                inv_count += mid - i + 1;
            } else {
                temp[k++] = a[i++];
            }
        }
        while (i <= mid) temp[k++] = a[i++];
        while (j <= r) temp[k++] = a[j++];
        for (int i = l; i <= r; ++i) a[i] = temp[i];
        return inv_count;
    }
```

```
public:
    ll solve(vector<ll> a) {
        int n = a.size();
        vector<ll> temp(n);
        return mergeSort(a, temp, 0, n - 1);
    }
};
"\n"
```

闵可夫斯基和.cpp

```
#define DEBUG 1
#define FUCK cout << "fuck" << endl;
#if DEBUG
    #include "all.hpp"
#else
    #include <bits/stdc++.h>
#endif

using namespace std;
using ll = long long;
using pii = pair<int,int>;
using pll = pair<ll,ll>;
using db = long double;
using pdd = pair<db, db>;
using i128 = __int128_t;

const ll N = 2000000;
const ll INF = 5e18;
const ll MOD = 1e9 + 7;

const db pi = acos(-1);
using T = ll;
struct P {
    T x, y;
    P() : x(0), y(0) {}
    P(T x, T y) : x(x), y(y) {}

    P operator+ (const P &o) { return P(x + o.x, y + o.y); }
    P operator- (const P &o) { return P(x - o.x, y - o.y); }
    P operator* (const T &o) { return P(x * o, y * o); }
    P operator/ (const T &o) { return P(x / o, y / o); }
    T operator* (const P &o) { return x * o.x + y * o.y; }
    T operator^ (const P &o) { return x * o.y - y * o.x; }

    bool operator== (const P &o) const {
        return x == o.x && y == o.y;
    }
    bool operator< (const P &o) const {
        return x < o.x || (x == o.x && y < o.y);
```

```
    }

    T norm2() {
        return x * x + y * y;
    }
    db norm() {
        return sqrt(norm2());
    }
    P unit() {
        return *this / norm();
    }
    db angle() {
        db t = atan2(y, x);
        return t < 0 ? t + 2 * pi : t;
    }
    P rot(const T &o) {
        return P(x * cos(o) - y * sin(o), x * sin(o) + y * cos(o));
    }
};

vector<P> convex_hull(vector<P> pts) {
    int n = pts.size();
    if (n <= 1) return pts;

    sort(pts.begin(), pts.end());

    vector<P> lower, upper;
    for (auto &p : pts) {
        while (lower.size() >= 2 && ((lower.back() - lower[lower.size()-2]) ^ (p -
lower.back())) <= 0)
            lower.pop_back();
        lower.push_back(p);
    }

    for (int i = n-1; i >= 0; i--) {
        P p = pts[i];
        while (upper.size() >= 2 && ((upper.back() - upper[upper.size()-2]) ^ (p -
upper.back())) <= 0)
            upper.pop_back();
        upper.push_back(p);
    }

    lower.pop_back();
    upper.pop_back();
    lower.insert(lower.end(), upper.begin(), upper.end());
    return lower;
}

vector<P> minkowski(vector<P> P1, vector<P> P2) {
    int n = P1.size(), m = P2.size();

    rotate(P1.begin(), min_element(P1.begin(), P1.end()), P1.end());
    rotate(P2.begin(), min_element(P2.begin(), P2.end()), P2.end());
```

```
    vector<P> V1(n), V2(m);
    for (int i = 0; i < n; i++) {
        V1[i] = P1[(i + 1) % n] - P1[i];
    }
    for (int i = 0; i < m; i++) {
        V2[i] = P2[(i + 1) % m] - P2[i];
    }

    vector<P> ans = {P1[0] + P2[0]};
    int t = 0, i = 0, j = 0;
    while (i < n && j < m) {
        int val = V1[i] ^ V2[j];
        if (val == 0) ans.emplace_back(ans.back() + V1[i++] + V2[j++]);
        else if (val > 0) ans.emplace_back(ans.back() + V1[i++]);
        else if (val < 0) ans.emplace_back(ans.back() + V2[j++]);
    }
    while (i < n) ans.emplace_back(ans.back() + V1[i++]);
    while (j < m) ans.emplace_back(ans.back() + V2[j++]);
    ans.pop_back();
    return ans;
}"\n"
```

随机数.cpp

```
#include <bits/stdc++.h>
using namespace std;
typedef long long ll;

struct RandomNumberGenerator{
    RandomNumberGenerator() : gen(std::random_device{}()){}
    ll generate(ll l,ll r){
        uniform_int_distribution<ll> dis(l, r);
        return dis(gen);
    }
    mt19937 gen;
} gen;"\n"
```