



Bisoños Usuarios de GNU/Linux de Mallorca y Alrededores | Bergantells Usuaris de GNU/Linux de Mallorca i Afegitons

## Nueva versión de Apache (1.3.17) y configuración Bulma (9526 lectures)

Per **Ricardo Galli Granada**, [gallir](http://mnm.uib.es/gallir/) (<http://mnm.uib.es/gallir/>)

Creado el 30/01/2001 00:00 modificado el 30/01/2001 00:00

*Ya ha salido la [última versión](#)<sup>(1)</sup> del Apache que soluciona algunos problemas y mejora el funcionamiento con el 2.2.x. Adjunto los cambios y el `config.status` del Apache de Bulma que hace que el `make install` instale los ficheros en los directorios correctos sobre una RedHat. [ACTUALIZADO] Agregado opciones del configure para compilar PHP tal como está en [bulma.net](http://bulma.net)*

### Cambios

Apache 1.3.17 Major changes

The bug fixes are:

- \* Correct handling of request byte ranges as specified by RFC 2616.
- \* Restore functionality broken by the `mod_rewrite` security fix: `rewrite` map lookup keys and default values are now expanded so that the lookup can depend on the requested URI etc.
- \* PHP now works under Unixware 7.
- \* Eliminate caching problems of `mod_autoindex` results.
- \* Win32 CGI execution on all Windows platforms is corrected.
- \* NetWare file and path fixes.

The main new features include:

- \* Add a new `LogFormat` directive, `%c`.
- \* `mod_status` now respects `?refresh=n` of 1 or greater.
- \* `mod_autoindex` fixes browser caching by sending `LastModified` and `ETag` headers if `IndexOptions TrackModified` is enabled.

Selected new features that relate to Windows platforms:

- \* Complete handling of `ScriptInterpreterSource` Registry execution.
- \* NT and 2000 services can be started with `-D FOO` style options.
- \* The close console window button/menu option on 95 and 98 works.

Selected new features relating to other platforms:

- \* Better discovery of `dbm_open()` under Linux.
- \* Linux 2.2.x and later do not need a serialised single listener.

### `config.status` del 1.3.17 de Bulma

```
#!/bin/sh
##
## config.status -- APACI auto-generated configuration restore script
##
## Use this shell script to re-run the APACI configure script for
## restoring your configuration. Additional parameters can be supplied.
##

OPTIM="-O2" \
./configure \
"--with-layout=Apache" \
"--enable-module=so" \
"--sbindir=/usr/sbin" \
"--sysconfdir=/etc/httpd/conf" \
"--libexecdir=/usr/lib/apache" \
"--prefix=/home/httpd" \
```



```
"--mandir=/usr/man" \  
"--includedir=/usr/include/apache" \  
"--logfiledir=/var/log/httpd" \  
"--enable-module=rewrite" \  
"--enable-shared=rewrite" \  
"--enable-module=log_agent" \  
"--enable-shared=log_agent" \  
"--enable-module=expires" \  
"--enable-shared=expires" \  
"--enable-module=log_referer" \  
"--enable-shared=log_referer" \  
"--enable-module=auth_db" \  
"--enable-shared=auth_db" \  
"--enable-module=auth_dbm" \  
"--enable-shared=auth_dbm" \  
"--enable-module=mime_magic" \  
"--enable-shared=mime_magic" \  
"--enable-shared=alias" \  
"$@"
```

## Configuración PHP

```
./configure --with-gd \  
            --with-mysql \  
            --with-apxs \  
            --with-pgsql \  
            --enable-track-vars
```

---

### Lista de enlaces de este artículo:

1. [http://httpd.apache.org/dist/apache\\_1.3.17.tar.gz](http://httpd.apache.org/dist/apache_1.3.17.tar.gz)

---

E-mail del autor: [gallir\\_ARROBA\\_uib.es](mailto:gallir_ARROBA_uib.es)

Podrás encontrar este artículo e información adicional en: <http://bulma.net/body.phtml?nIdNoticia=448>