

---

# KKT-INFORMED NEURAL NETWORK

A PARALLEL SOLVER FOT PARAMETRIC CONVEX OPTIMIZATION PROBLEM

---

A PREPRINT

Carmine Delle Femine

September 3, 2024

## ABSTRACT

This is the abstract

### 1 Introduction

### 2 Background

Consider a parametric convex optimization problem in the standard form:

$$\begin{aligned} \min_{x \in \mathcal{D} \subseteq \mathbb{R}^n} \quad & f(x, \theta) \\ \text{s.t.} \quad & g_i(x, \theta) \leq 0 \quad i = 1, \dots, m \\ & A(\theta)x - b(\theta) = 0 \end{aligned}$$

where  $x \in \mathcal{D} \subseteq \mathbb{R}^n$  is the optimization variable;  $\theta \in \mathcal{D}_\theta \subseteq \mathbb{R}^k$  are the parameters defining the problem;  $f : \mathcal{D}_f \subseteq \mathbb{R}^n \times \mathbb{R}^k \rightarrow \mathbb{R}$  is the convex cost function;  $g_i : \mathcal{D}_{g_i} \subseteq \mathbb{R}^n \times \mathbb{R}^k \rightarrow \mathbb{R}$  are the convex inequality constraints,  $A : \mathcal{D}_\theta \rightarrow \mathbb{R}^{p \times n}$  and  $b : \mathcal{D}_\theta \rightarrow \mathbb{R}^p$  defines the affine equality constraints and  $\mathcal{D} = \bigcap_{i=1}^m \mathcal{D}_{g_i} \cap \mathcal{D}_f$  is the domain of the optimization problem.

Assume differentiable cost and constraints functions and that  $g_i$  satisfies Slater's condition. Given a set of parameters  $\theta$ ,  $x^* \in \mathcal{D}$  is optimal if and only if there are  $\lambda^*$  and  $\nu^*$  that, with  $x^*$ , satisfy the Karush-Kuhn-Tucker conditions (KKT):

$$A(\theta)x^* - b(\theta) = 0 \tag{1}$$

$$g_i(x^*, \theta) \leq 0 \quad i = 1, \dots, m \tag{2}$$

$$\lambda_i^* \geq 0 \quad i = 1, \dots, m \tag{3}$$

$$\lambda_i^* g_i(x^*, \theta) = 0 \quad i = 1, \dots, m \text{ Compl} \tag{4}$$

$$\nabla_{x^*} f(x^*, \theta) + \sum_{i=1}^m \lambda_i^* \nabla_{x^*} g_i(x^*, \theta) + A^T \nu^* = 0 \text{ Stationairty} \tag{5}$$

### 3 Proposed method

### 4 Case study

#### 4.1 Problem description

#### 4.2 Experimental results

### 5 Conclusions