

R package **rrtable**

Keon-Woong Moon

2018-04-05 15:05:21

If you are a data scientist or researcher, you will certainly be interested in reproducible research. R package **rrtable** makes it possible to make reports with HTML, LaTeX, MS word or MS Powerpoint formats from a table of R codes.

Package Installation

You can install R package **rrtable** with the following command.

```
if(!require(devtools)){ install.packages("devtools") }
devtools::install_github("cardiomoon/rrtable")
```

Package Loading

You can load the **rrtable** package with the following R command.

```
require(rrtable)
```

Sample Data

Sample data `sampleData3` is included in **rrtable** package. You can see the `sampleData3` by following R command.

```
str(sampleData3)
```

```
'data.frame':  22 obs. of  5 variables:
 $ type  : chr  "title" "subtitle" "author" "" ...
 $ title : chr  "" "" "" "" ...
 $ text  : chr  "R package `rrtable`" "Reproducible Research with a Table of R codes" "Keon-Woong Moon"
 $ code  : chr  "" "" "" "" ...
 $ option: chr  "" "" "" "" ...
```

Or you can make a table of this data

% latex table generated in R 3.4.3 by xtable 1.8-2 package % Thu Apr 5 15:05:21 2018

| type | title | text | code | option |
|------|----------------------------|------|------|--------|
| 18 | df2flectable2(sampleData3) | | | |

% latex table generated in R 3.4.3 by xtable 1.8-2 package % Thu Apr 5 15:05:21 2018

mytable object

You can add **mytable** object with the following R code.

% latex table generated in R 3.4.3 by xtable 1.8-2 package % Thu Apr 5 15:05:21 2018


| | type | title | text |
|----|----------|----------------------|---|
| 11 | title | | R package 'rrtable' |
| 13 | subtitle | | Reproducible Research with a Table of R codes |
| 12 | author | | Keon-Woong Moon |
| 25 | | | If you are a data scientist or researcher, you will certainly be interested in reproduc |
| 14 | header2 | Package Installation | You can install R package 'rrtable' with the following command. |
| 15 | header2 | Package Loading | You can load the 'rrtable' package with the following R command. |
| 16 | header2 | Sample Data | Sample data sampleData3 is included in rrtable package. You can see the sampleDa |
| 17 | | | Or you can make a table of this data |
| 18 | | | |
| 19 | header3 | mytable object | You can add mytable object with the following R code. |
| 1 | mytable | | |
| 2 | header3 | Plot | You can insert a plot into your document. |
| 3 | plot | | |
| 20 | header3 | ggplot | You can insert a ggplot into a document |
| 4 | ggplot | | |
| 21 | header3 | R code | You can insert the result of R code. For example, you can insert the result of regres |
| 24 | Rcode | | |
| 22 | header3 | Two ggplots | You can insert two parallel ggplots with the following code. |
| 8 | 2ggplots | | |
| 23 | header3 | Two plots | You can insert two parallel plots with the following code. |
| 10 | 2plots | | |
| 26 | header2 | HTML Report | You can get report with HTML format(this file) by following R command. |

| | type | title | text | code | option |
|---|---------|-------|------|-----------------------|--------|
| 1 | mytable | | | mytable(Dx~,data=acs) | |

Plot

You can insert a plot into your document.

% latex table generated in R 3.4.3 by xtable 1.8-2 package % Thu Apr 5 15:05:21 2018



ggplot


You can insert a ggplot into a document

| | NSTEMI (N=153) | STEMI (N=304) | Unstable Angina (N=400) | p |
|------------------|-------------------|------------------|----------------------------|-------|
| age | 64.3 \pm 12.3 | 62.1 \pm 12.1 | 63.8 \pm 11.0 | 0.073 |
| sex | | | | 0.012 |
| Female | 50 (32.7%) | 84 (27.6%) | 153 (38.2%) | |
| Male | 103 (67.3%) | 220 (72.4%) | 247 (61.8%) | |
| cardiogenicShock | | | | 0.000 |
| No | 149 (97.4%) | 256 (84.2%) | 400 (100.0%) | |
| Yes | 4 (2.6%) | 48 (15.8%) | 0 (0.0%) | |
| entry | | | | 0.001 |
| Femoral | 58 (37.9%) | 133 (43.8%) | 121 (30.2%) | |
| Radial | 95 (62.1%) | 171 (56.2%) | 279 (69.8%) | |
| EF | 55.0 \pm 9.3 | 52.4 \pm 9.5 | 59.2 \pm 8.7 | 0.000 |
| height | 163.3 \pm 8.2 | 165.1 \pm 8.2 | 161.7 \pm 9.7 | 0.000 |
| weight | 64.3 \pm 10.2 | 65.7 \pm 11.6 | 64.5 \pm 11.6 | 0.361 |
| BMI | 24.1 \pm 3.2 | 24.0 \pm 3.3 | 24.6 \pm 3.4 | 0.064 |
| obesity | | | | 0.186 |
| No | 106 (69.3%) | 209 (68.8%) | 252 (63.0%) | |
| Yes | 47 (30.7%) | 95 (31.2%) | 148 (37.0%) | |
| TC | 193.7 \pm 53.6 | 183.2 \pm 43.4 | 183.5 \pm 48.3 | 0.057 |
| LDLC | 126.1 \pm 44.7 | 116.7 \pm 39.5 | 112.9 \pm 40.4 | 0.004 |
| HDLC | 38.9 \pm 11.9 | 38.5 \pm 11.0 | 37.8 \pm 10.9 | 0.501 |
| TG | 130.1 \pm 88.5 | 106.5 \pm 72.0 | 137.4 \pm 101.6 | 0.000 |
| DM | | | | 0.209 |
| No | 96 (62.7%) | 208 (68.4%) | 249 (62.2%) | |
| Yes | 57 (37.3%) | 96 (31.6%) | 151 (37.8%) | |
| HBP | | | | 0.002 |
| No | 62 (40.5%) | 150 (49.3%) | 144 (36.0%) | |
| Yes | 91 (59.5%) | 154 (50.7%) | 256 (64.0%) | |
| smoking | | | | 0.000 |
| Ex-smoker | 42 (27.5%) | 66 (21.7%) | 96 (24.0%) | |
| Never | 50 (32.7%) | 97 (31.9%) | 185 (46.2%) | |
| Smoker | 61 (39.9%) | 141 (46.4%) | 119 (29.8%) | |

| | type | title | text | code | option |
|---|------|-------|------|------------|--------|
| 3 | plot | | | plot(iris) | |

% latex table generated in R 3.4.3 by xtable 1.8-2 package % Thu Apr 5 15:05:22 2018

| | type | title | text | code | option |
|---|--------|-------|------|---|--------|
| 4 | ggplot | | | ggplot(iris,aes(x=Sepal.Length,y=Sepal.Width,color=Species))+geom_point() | |



R code

You can insert the result of R code. For example, you can insert the result of regression analysis.

% latex table generated in R 3.4.3 by xtable 1.8-2 package % Thu Apr 5 15:05:23 2018

| | type | title | text | code | option |
|----|-------|-------|------|--|--------|
| 24 | Rcode | | | fit=lm(mpg~wt*hp,data=mtcars);summary(fit) | |

```
fit=lm(mpg~wt*hp,data=mtcars);summary(fit)
```

Call:

```
lm(formula = mpg ~ wt * hp, data = mtcars)
```

Residuals:

```
      Min       1Q   Median       3Q      Max 
-3.0632 -1.6491 -0.7362  1.4211  4.5513 
```

Coefficients:

```
            Estimate Std. Error t value Pr(>|t|)    
(Intercept)  49.80842     3.60516   13.816 5.01e-14 ***
wt           -8.21662     1.26971   -6.471 5.20e-07 ***
hp           -0.12010     0.02470   -4.863 4.04e-05 ***
wt:hp         0.02785     0.00742    3.753 0.000811 ***
---
Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
```


Residual standard error: 2.153 on 28 degrees of freedom
 Multiple R-squared: 0.8848, Adjusted R-squared: 0.8724
 F-statistic: 71.66 on 3 and 28 DF, p-value: 2.981e-13

Two ggplots

You can insert two parallel ggplots with the following code.

% latex table generated in R 3.4.3 by xtable 1.8-2 package % Thu Apr 5 15:05:23 2018

| | type | title | text | code |
|---|----------|-------|------|--|
| 8 | 2ggplots | | | ggplot(iris,aes(Sepal.Length,Sepal.Width))+geom_point() ggplot(iris,aes(Sepal.Length,Sepal.V |




Two plots

You can insert two parallel plots with the following code.

% latex table generated in R 3.4.3 by xtable 1.8-2 package % Thu Apr 5 15:05:24 2018

| | type | title | text | code | option |
|----|--------|-------|------|------------------------------|--------|
| 10 | 2plots | | | hist(rnorm(1000)) plot(1:10) | |



HTML Report

You can get report with HTML format(this file) by following R command.

```
data2HTML(sampleData3)
```