

Based on your screenshot, your current root users are locked to **127.0.0.1** and **localhost**, meaning they will strictly reject any connection coming from outside your physical computer.

To allow other users to connect to your local database, you need to add a user that accepts connections from any IP address using the wildcard symbol (%).

Here is exactly how to do it step-by-step:

Step 1: Create a Remote User Account

Instead of modifying your local root user, it is highly recommended to **create a new dedicated user** for your project team:

1. Click on the **Add user account** button (located near the bottom-left of your privilege table, under the "New" section).
2. Fill out the fields exactly like this:
 - **User name:** Enter a unique name for your project team (e.g., project_team).
 - **Host name:** Select **"Any host"** from the dropdown menu. This will automatically place a % in the text box next to it.
 - **Password:** Enter a strong password and re-type it to confirm.
3. Scroll down to **Database for user account** and check the box that says *"Grant all privileges on wildcard (username_%)."* (Alternatively, you can assign specific database permissions in the next step).
4. Scroll to the very bottom-right of the page and click **Go**.

Step 2: Assign Permissions to your Database

Now, you need to give this new user explicit access to your careerconnect_db database:

1. Go back to the main **Privileges** tab at the top.
2. Click **Edit privileges** next to your newly created user account (the one with the % host name).
3. Click on the **Database** tab at the top of the privileges menu.
4. Select careerconnect_db from the dropdown or list and click **Go**.
5. Check the **Check all** box to grant the user all administrative, data, and structure rights for this specific database, then click **Go**.

Critical Next Step: Update your MySQL Configuration File (my.ini)

Even after updating phpMyAdmin, your computer's built-in database firewall will block external users unless you change one setting in your configuration file.

1. Open your XAMPP/WAMP control panel.
2. Click the **Config** button next to MySQL and select **my.ini** (or search for the file manually

on your computer).

3. Press Ctrl + F and search for the phrase **bind-address**.

4. If it says bind-address=127.0.0.1, change it to:

```
bind-address = 0.0.0.0
```

(Setting it to 0.0.0.0 tells MySQL to listen to connections from any network interface, not just your local computer).

5. **Save the file** and **Restart MySQL** from your control panel.

Once these steps are done, your database is configured to accept incoming traffic! To help you connect your teammates, let me know:

- Are your teammates trying to connect over the **same local Wi-Fi network**, or are they **remote (working from home)**?
- What **framework or programming language** (e.g., Node.js, PHP, Python) are you using to connect to the database?